Remote State Estimation over a Wearing Channel: Information Freshness vs. Channel Aging

Jiping Luo, George Stamatakis, Osvaldo Simeone, and Nikolaos Pappas

Abstract—We study the remote estimation of a linear Gaussian system over a *nonstationary* channel that *wears out over time and with every use*. The sensor can either transmit a fresh measurement in the current time slot, restore the channel quality at the cost of downtime, or remain silent. More frequent transmissions yield accurate estimates but incur significant wear on the channel. Renewing the channel too often improves channel conditions but results in poor estimation quality. What is the optimal timing to transmit measurements and restore the channel? We formulate the problem as a Markov decision process (MDP) and show the monotonicity properties of an optimal policy. A structured policy iteration algorithm is proposed to find the optimal policy.

Index Terms—Remote estimation, wearing channel, stability, monotone policy.

I. INTRODUCTION

A. Motivation and Contributions

Channel unreliability is a salient feature and a bottleneck in networked control systems (NCSs) [1]. Wireless channels are inherently less reliable than their wired counterparts [2]. Data loss, delay, and nonstationarity can significantly degrade system performance. A fundamental yet challenging problem is the remote state estimation of dynamic processes that is robust to the realities of wireless networks.

Remote estimation and control over *stationary* lossy channels – whose statistical properties remain constant over time – have been extensively studied in the literature [3]–[8]. Data loss is modeled stochastically by assigning failure probabilities to different channel states. A common model is the independent and identically distributed (*i.i.d.*) Bernoulli process [3]–[6], where each packet is dropped independently with a fixed probability. The Markovian channel, modeled by a timehomogeneous finite-state Markov process, captures temporal correlations in packet losses [7], [8].

Remote estimation over *nonstationary* channels remains largely unexplored. This note studies a particular class of nonstationary channels whose quality deteriorates due to natural aging and usage. One example of such channels is neural connections in the brain [9]. Neural efficiency declines with age, weakening synaptic strength and neural connections. Repeated use or neurological conditions can further impair synaptic structure and function. Another example arises in quantum channels, where the quality of entanglement and the coherence of qubit pairs degrade over time due to environmental noise and interactions [10]. Other examples can be found in [11]. Restoring or replenishing channel quality requires external interventions, such as charging or replacing a device or generating and sharing fresh entangled qubit pairs.

Our main contributions are as follows. We formulate an optimization problem to minimize the average estimation error over a wearing channel. The channel reliability is modeled as a decreasing function of age, which grows with time and usage. It is possible to renew the channel at the cost of downtime. This problem is a Markov decision process (MDP) with a countably infinite state space that features two *dependent* age processes: the *Age of Information (AoI)* and the *Age of Channel (AoC)*. We show the existence of an AoC-monotone optimal policy; that is, the optimal policy is weakly increasing in AoC for any fixed AoI. We exploit these findings and propose a structured policy iteration algorithm to find the optimal policy with reduced computation overhead.

B. Related Works

Information *freshness* is closely related to *accuracy* in the remote estimation of linear Gaussian systems. The error covariance is a nonlinear, monotonically increasing function of the AoI, defined as the time elapsed since the last successful packet reception [6]. It has been shown that to achieve an optimized tradeoff between accuracy and transmission costs, the optimal transmission policy is of a threshold type; specifically, the sensor transmits whenever the AoI exceeds a threshold that depends on channel reliability [3]–[8]. Since the AoI, and hence the error covariance, can grow unbounded due to channel unreliability, sufficient and necessary conditions for mean-square stability have been established for *i.i.d.* [3] and Markovian [7], [8] channel models.

This work can be considered as a contribution to the rich literature on AoI. The problem of minimizing AoI has been well studied in previous papers, including [12]–[14]. A recent survey can be found in [15]. Besides freshness, significance-aware age metrics have been introduced to capture the cost of consecutive errors in the estimation of Markov processes [16], [17]. The closest study to this work is [18], which addresses the minimization of AoI over a wearing channel. To the best of our knowledge, structural and existence results for scheduling over wearing channels have not been established yet.

II. SYSTEM MODEL AND PROBLEM FORMULATION

A. System Setup

We consider the remote estimation system shown in Fig. 1, which consists of the following components:

Jiping Luo, George Stamatakis, and Nikolaos Pappas are with the Department of Computer and Information Science, Linköping University, Linköping 58183, Sweden. (e-mail: {jiping.luo, geost33, nikolaos.pappas}@liu.se).

Osvaldo Simeone is with the Department of Engineering, King's College London, London WC2R 2LS, UK. (e-mail: osvaldo.simeone@kcl.ac.uk).



Fig. 1. The remote estimation system with a wearing channel.

1) Process: We consider a linear Gaussian process with

$$\mathbf{x}_{k+1} = \mathbf{A}\mathbf{x}_k + \mathbf{w}_k,\tag{1}$$

where $\mathbf{x}_k \in \mathbb{R}^l$ is the state of the process at time slot k, $\mathbf{A} \in \mathbb{R}^{l \times l}$ is the state transition matrix, and $\mathbf{w}_k \in \mathbb{R}^l$ is the process noise, which is *i.i.d.* in time, following a Gaussian distribution with zero mean and covariance matrix $\mathbf{Q} \succeq 0$.

2) Sensor: The process in (1) is measured by a sensor as

$$\mathbf{y}_k = \mathbf{C}\mathbf{x}_k + \mathbf{v}_k, \tag{2}$$

where $\mathbf{y}_k \in \mathbb{R}^m$ is the noisy measurement at time slot k, $\mathbf{C} \in \mathbb{R}^{m \times l}$ is the measurement matrix, and $\mathbf{v}_k \in \mathbb{R}^m$ is the measurement noise, assumed to be *i.i.d.* Gaussian with zero mean and covariance $\mathbf{R} \succ 0$. The noise processes, $\{\mathbf{w}_k\}_{k\geq 0}$ and $\{\mathbf{v}_k\}_{k>0}$, are assumed to be mutually independent.

After taking a measurement \mathbf{y}_k , the sensor runs a Kalman filter to precompute the minimum mean square error (MSE) estimate of \mathbf{x}_k using measurements up till time slot k. The output of the Kalman filter is the state estimate $\mathbf{x}_{k|k}^{s}$ with the estimation error covariance $\mathbf{P}_{k|k}^{s}$, where [4]

$$\mathbf{x}_{k|k}^{s} = \mathbf{x}_{k|k-1}^{s} + \mathbf{K}_{k}(\mathbf{y}_{k} - \mathbf{C}\mathbf{x}_{k|k-1}^{s}), \quad (3)$$

$$\mathbf{P}_{k|k}^{s} = (\mathbf{I} - \mathbf{K}_{k}\mathbf{C})\mathbf{P}_{k|k-1}^{s}.$$
(4)

Here, $\mathbf{x}_{k|k-1}^{s}$, $\mathbf{P}_{k|k-1}^{s}$, and \mathbf{K}_{k} are the *a priori* state estimate, the *a priori* estimation error covariance, and the optimal filter gain at time slot *k*, respectively, which given by

$$\mathbf{x}_{k|k-1}^{\mathrm{s}} = \mathbf{A}\mathbf{x}_{k-1|k-1}^{\mathrm{s}},\tag{5}$$

$$\mathbf{P}_{k|k-1}^{s} = \mathbf{A}\mathbf{P}_{k-1|k-1}^{s}\mathbf{A}^{\mathrm{T}} + \mathbf{Q}, \tag{6}$$

$$\mathbf{K}_{k} = \mathbf{P}_{k|k-1}^{s} \mathbf{C}^{\mathsf{T}} (\mathbf{C} \mathbf{P}_{k|k-1}^{s} \mathbf{C}^{\mathsf{T}} + \mathbf{R})^{-1}.$$
 (7)

Under the mild assumptions that the pair (\mathbf{A}, \mathbf{C}) is observable and $(\mathbf{A}, \sqrt{\mathbf{Q}})$ is controllable, the error covariance $\mathbf{P}_{k|k}^{s}$ converges exponentially fast to the steady-state value $\mathbf{\bar{P}}$ as k goes to infinity [19, Chapter 4.4]. In the rest of the paper, we assume that the local Kalman filter operates in the steady state, i.e., $\mathbf{P}_{k|k}^{s} = \mathbf{\bar{P}}$ for all k. For notational simplicity, we shall use $\hat{\mathbf{x}}_{k}^{s}$ to denote the sensor's estimation $\mathbf{x}_{k|k}^{s}$.

3) Wearing channel: The sensor transmits local estimates to the receiver through a channel that wears out over time and with every use. Let u_k denote the sensor's decision at time slot k. This is selected from a finite set $\mathcal{U} = \{0, 1, 2\}$, where:

- $u_k = 0$ denotes the *idle* action. The channel is not used in slot k, and its reliability degrades due to natural aging.
- $u_k = 1$ denotes the *transmit* action. Each transmission incurs a certain amount of wear on the channel, leading to an additional reduction in its reliability.
- $u_k = 2$ denotes the *renewal* action. Maintenance or replacement can be performed to restore the channel's quality; however, this action takes time to complete.

We consider that data transmission takes at most one slot, while channel renewal occupies $\delta_{\rm R} > 1$ consecutive time slots. Given that many system transitions may occur between slot k and slot $k + \delta_{\rm R}$, we introduce another timeline, the decision epoch t = 0, 1, ..., for subsequent analysis. The Age of Channel (AoC) at decision epoch t is defined as

$$\tau_{t+1} \coloneqq \begin{cases} \tau_t + 1, & \text{if } u_t = 0, \\ \tau_t + \tau_{\mathrm{D}}, & \text{if } u_t = 1, \\ 1, & \text{if } u_t = 2, \end{cases}$$
(8)

where $\tau_D > 1$ represents the amount of wear incurred with each transmission. The AoC summarizes the aging effect through the history of all sensor actions. Fig. 2a shows the evolution of the AoC in different timelines.

Let $h_t = 1$ denote a good channel condition at epoch t, and $h_t = 0$ otherwise. The channel reliability is time-varying and deteriorates with the AoC. In particular, the probability of a successful transmission is

$$\Pr[h_t = 1 | u_t = 1] = \theta(\tau_t), \tag{9}$$

where $\theta : \mathbb{N}^+ \mapsto [\theta_{\min}, \theta_{\max}]$ is a monotonic decreasing¹ and bounded function of the AoC, while θ_{\min} and $\theta_{\max} \in [0, 1]$ represent the worst and best channel conditions, respectively. The probability of an unsuccessful transmission is

$$\Pr[h_t = 0 | u_t = 1] = 1 - \theta(\tau_t) = \bar{\theta}(\tau_t).$$
(10)

4) Receiver: The receiver is tasked with reconstructing source realizations using the received sensor measurements. It can either update its estimate using the newly received estimate, or predict the state if no packet is received. Letting $\eta_k = \mathbb{1}\{u_k = 1, h_k = 1\}$ denote a successful data reception event in slot k, the remote estimate at slot k + 1 is

$$\hat{\mathbf{x}}_{k+1} = \eta_k \mathbf{A} \hat{\mathbf{x}}_k^{\mathrm{s}} + (1 - \eta_k) \mathbf{A} \hat{\mathbf{x}}_k.$$
(11)

Provided that the Kalman filter is in its steady state, the error covariance at the receiver is given by

$$\mathbf{P}_{k+1} = \begin{cases} \mathbf{A}\bar{\mathbf{P}}\mathbf{A}^{\mathrm{T}} + \mathbf{Q}, & \text{if } \eta_k = 1, \\ \mathbf{A}\mathbf{P}_k\mathbf{A}^{\mathrm{T}} + \mathbf{Q}, & \text{otherwise.} \end{cases}$$
(12)

Define the *Age of Information (AoI)* at the receiver as the time elapsed since the last reception of a packet, i.e.,

$$\delta_k = k - \max\{\tau \le k : \eta_\tau = 1\}. \tag{13}$$

As depicted in Fig. 2b, the age increases linearly with time and resets to 1 only when a new update is received. Recall that the renewal action takes δ_R slots to complete. The AoI at each decision epoch evolves as

$$\delta_{t+1} = \begin{cases} 1, & \text{if } \eta_t = 1, \\ \delta_t + \delta_{\mathsf{R}}, & \text{if } u_t = 2, \\ \delta_t + 1, & \text{otherwise.} \end{cases}$$
(14)

Then, the error covariance (12) in terms of AoI is given by

$$\mathbf{P}_t = \mathbf{A}^{\delta_t} \bar{\mathbf{P}} (\mathbf{A}^{\mathrm{T}})^{\delta_t} + \sum_{r=0}^{\delta_t - 1} \mathbf{A}^r \mathbf{Q} (\mathbf{A}^{\mathrm{T}})^r.$$
(15)

¹Throughout this paper, the terms "decreasing" (or "increasing") are used in the weak sense, meaning "non-increasing" (or "non-decreasing").



Fig. 2. An illustration of different timelines and the evolution of the age processes, where 'I', 'T', and 'R' stand for idle, transmit, and renewal actions, respectively. The sensor triggers a transmission at the 2th slot and renews the channel at the 3th slot. The sensor must remain silent during the renewal period. Consequently, both the AoC and AoI continue to increase. Since data transmission takes one slot, the AoI resets to 1 at slot 3.

Lemma 1 ([5]). The estimation MSE at the receiver, i.e.,

$$\operatorname{Tr}\left(\mathbf{P}_{t}\right) \eqqcolon f(\delta_{t}),\tag{16}$$

is monotonically increasing in the AoI.

Remark 1. Lemma 1 implies that sensor measurements are more valuable when they are fresh. This draws a connection between distortion and information aging [16], [17]. While this paper primarily focuses on remote estimation, the results extend naturally to the broader AoI literature.

The receiver sends an acknowledgment (ACK) to the sensor upon the successful reception of an update packet. We assume instant and error-free feedback from the receiver. So the sensor knows exactly the error covariance at the receiver. Let $s_t =$ (τ_t, δ_t) denote the system state at decision epoch t, where $s_t \in S$ and the state space is $S = \mathbb{N}^+ \times \mathbb{N}^+$. We define the cost of taking an action u_t in state s_t as the lump sum received prior to decision epoch t + 1. Given that the cost is accrued during the renewal period, we may write

$$c(s_t, u_t) = \begin{cases} f(\delta_t), & \text{if } u_t = 0, 1, \\ \sum_{r=0}^{\delta_R - 1} f(\delta_t + r), & \text{if } u_t = 2. \end{cases}$$
(17)

It is noteworthy that, contrary to most existing research that incorporates transmission costs using an additive constant term (i.e., $c(s_t, 1) = f(\delta_t) + E$, where E is the cost associated with each transmission [5], [6]), the cost function here implicitly penalizes data transmission by aging the channel.

B. Problem Formulation

We aim to optimize estimation quality, while accounting for channel aging. The information available at the sensor up until the epoch t is

$$i_t = (\tau_{0:t}, \delta_{0:t}, u_{0:t-1}). \tag{18}$$

Using this information, the sensor selects an action u_t using a *decision rule* π_t , i.e.,

$$u_t = \pi_t(i_t) = \pi_t(\tau_{0:t}, \delta_{0:t}, u_{0:t-1}).$$
(19)

A policy $\pi \triangleq (\pi_0, \pi_1, ...)$ is a sequence of decision rules. We call a policy *Markovian* if, for every $t \ge 0$, it selects an action based only on the current system state, that is, $u_t = \pi_t(s_t)$ for

all t. A Markovian policy is considered *deterministic* if, for every $s_t \in S$, it selects an action with certainty. Otherwise, the policy is called *randomized*. We denote by Π and Π^{MD} the set of all admissible and Markovian deterministic policies.

The expected total estimation MSE of a policy $\pi \in \Pi$ over an infinite horizon is defined as

$$J^{\pi}(s_0) = \lim_{T \to \infty} \frac{1}{T} \sum_{t=0}^{T-1} \mathbb{E}^{\pi} [c(s_t, u_t) | s_0].$$
(20)

The goal is to find a policy π^* that minimizes the MSE, i.e.,

$$J^*(s_0) = \inf_{\pi \in \Pi} J^{\pi}(s_0).$$
(21)

Problem (21) is a Markov decision process (MDP) with an average-cost optimality criterion. The MDP can be characterized by the tuple (S, U, P, c), where $S = \mathbb{N}^+ \times \mathbb{N}^+$ and $U = \{0, 1, 2\}$ are the state space and action space, c(s, u) is the cost function defined in (17), and $P : S \times U \times S \mapsto [0, 1]$ is the system transition probability function. Based on the system setup described in Sec. II-A, this is obtained as

$$P_{s,s'}(u) \coloneqq \Pr[s_{t+1} = s' | s_t = (\tau, \delta), u_t = u]$$

$$= \begin{cases} 1, & \text{if } s' = (\tau + 1, \delta + 1), u = 0, \\ \theta(\tau), & \text{if } s' = (\tau + \tau_{\mathrm{D}}, 1), u = 1, \\ \bar{\theta}(\tau), & \text{if } s' = (\tau + \tau_{\mathrm{D}}, \delta + 1), u = 1, \\ 1, & \text{if } s' = (1, \delta + \delta_{\mathrm{R}}), u = 2, \\ 0, & \text{otherwise.} \end{cases}$$
(22)

Definition 1 (Mean-square stability). The remote estimation system is mean-square stable under a policy π if the MSE is finite, i.e., $J^{\pi}(s_0) < \infty$ for all initial state $s_0 \in S$.

Remark 2. Note that if the spectral radius of the state transition matrix **A** satisfies the inequality $\rho(\mathbf{A}) \geq 1$, the cost function c(s, u) may become unbounded and grow exponentially fast with the AoI [3]. Moreover, problem (21) confronts both computing and memory challenges, as the state space is (possibly) infinite. Therefore, a theoretical analysis of the existence and structure of an optimal policy is essential.

III. MAIN RESULTS

This section concerns establishing the existence and structure of optimal policies for problem (21). We also discuss the benefits and drawbacks of introducing channel renewal.



Fig. 3. State transitions induced by the transmit-always policy $\tilde{\pi}$.

A. Existence of an Optimal Policy

We first show that the possibility to choose the renewal action helps stabilize the system. Since for $\rho(\mathbf{A}) < 1$, the cost function c(s, u) is bounded and thus the system is always stable, in what follows, we discuss only the more challenging case where $\rho(\mathbf{A}) \geq 1$ (see Remark 2).

Let $\tilde{\pi} = (\tilde{\pi}_0, \tilde{\pi}_1, ...)$ be the transmit-always policy, i.e., $\tilde{\pi}_t(s_t) = 1$ for all $s_t \in S$ and $t \ge 0$. With this policy, starting from an arbitrary initial state $s_0 = (\tau_0, \delta_0)$, the system transitions to state $(\tau_0 + \tau_D, \delta_0 + 1)$ with probability $\bar{\theta}(\tau_0)$, or to state $(\tau_0 + \tau_D, 1)$ with probability $\theta(\tau_0)$. Examples of sample paths are illustrated in Fig. 3.

Remark 3. As seen in Fig. 3, the state transition probabilities depend on the history of all past actions through the channel age. This feature makes our problem significantly more challenging compared to existing studies that assume stationary *i.i.d.* or Markovian channel models [3]–[8].

The following lemma states that the system can be stabilized even without using the renewal action if it is stabilizable under the worst channel conditions. This result stems from prior findings that a sufficient condition for mean-square stability over an *i.i.d.* channel with constant reliability Θ is the inequality $\rho^2(\mathbf{A})(1 - \Theta) < 1$ [3].

Lemma 2. If $\rho^2(\mathbf{A})(1-\theta_{\min}) < 1$, the system can be stabilized even without using the renewal action.

We now discuss the merits of introducing channel renewal actions. Lemma 2 implies that mean-square stability is achieved if the system state is confined within the region

$$\underline{\mathcal{S}} \triangleq \{ s \in \mathcal{S} : \rho^2(\mathbf{A})(1 - \theta(\tau)) < 1 \} \neq \emptyset.$$
 (23)

Let $\overline{S} = S \setminus S$ denote the unstable region. Consider the policy

$$\pi'(s) = \begin{cases} 1, & \text{if } s \in \mathcal{S}, \\ 2, & \text{if } s \in \bar{\mathcal{S}}, \end{cases}$$
(24)

that initiates a transmission if the state is in the stable region S, and renews the channel whenever the state reaches the boundary of the unstable region \overline{S} . Therefore, each time the system hits the boundary, it resets with certainty to a state in the subset $\{(1, \delta) : \delta \ge 1\} \subset S$.

Lemma 3. If $\rho^2(\mathbf{A})(1-\theta_{max}) < 1$, the system can always be stabilized by leveraging renewal actions.

As a consequence of Lemma 3, we establish the existence of a deterministic optimal policy to problem (21) as follows. **Theorem 1.** If $\rho^2(\mathbf{A})(1-\theta_{max}) < 1$, there exists a constant λ^* and a bounded function V that satisfies the Bellman equation

$$\lambda^* + V(s) = \min_{u \in \mathcal{U}} \left[c(s, u) + \sum_{s' \in \mathcal{S}} P_{s, s'}(u) V(s') \right], \quad (25)$$

where λ^* is the minimal average cost, independent of the initial state s_0 , i.e., $J^*(s_0) = \lambda^*, \forall s_0 \in S$. Any deterministic policy $\pi^* \in \Pi^{MD}$ that realizes the minimum in (25) is optimal.

Theorem 1 says there is no loss of optimality in restricting our attention to Markovian and deterministic policies. Because histories need not be retained and nonrandomized policies suffice, this simplifies computation through reduced storage and fewer arithmetic operations. It also suggests that we can use the *relative value iteration* (RVI) [20] method to solve the Bellman equation (25).

For each iteration $n \ge 1$, the RVI updates the value function using the following recursion

$$Q^{n}(s,u) = c(s,u) + \sum_{s' \in \mathcal{S}} P_{s,s'}(u) V^{n-1}(s'), \qquad (26)$$

$$\tilde{V}^n(s) = \min_{u \in \mathcal{U}} \left[Q^n(s, u) \right],\tag{27}$$

$$V^n(s) = \tilde{V}^n(s) - \tilde{V}^n(s_{\text{ref}}), \qquad (28)$$

where $Q^n(s, u)$ is the Q-factor at iteration n, and $s_{\text{ref}} \in S$ is an arbitrary reference state. The sequences $\{\tilde{V}^n(s)\}$ and $\{V^n(s)\}$ converge as $n \to \infty$ [20]. Moreover, we have $\lambda^* = \tilde{V}(s_{\text{ref}})$ and $V(s) = \tilde{V}(s) - \tilde{V}(s_{\text{ref}})$ as a solution to (25).

However, RVI suffers from the curse of dimensionality [20]. In the sequel, we will establish some useful monotonicity properties of the optimal policy and propose a structured policy iteration method to reduce computation overhead.

B. Structure of an Optimal Policy

This section presents structural results on the optimal policy. As will become apparent, the introduction of channel renewal makes our problem challenging and disrupts some of the convenient properties that would hold in the absence of renewal.

We first show the monotonicity of the value function.

Proposition 1. The relative value function V satisfies the following properties:

i. for any
$$\tau \in \mathbb{N}^+$$
, $V(\tau, \delta)$ is increasing in δ .
ii. for any $\delta \in \mathbb{N}^+$, $V(\tau, \delta)$ is increasing in τ .

Proof. See Appendix B.

These properties align with the intuition that starting with fresh information, or with a good channel, yields a lower minimum cost than starting with outdated information, or with a poor channel. As channel quality deteriorates and information ages, it can become beneficial to take more *aggressive* actions, such as increasing transmission frequency or restoring channel quality. To formalize these properties, we introduce the following definitions.

Definition 2 (AoI-monotone). A policy π is AoI-monotone if, for any fixed τ , it satisfies the inequality $\pi(\tau, \delta') \geq \pi(\tau, \delta)$ for all $\delta' \geq \delta$. **Definition 3** (AoC-monotone). A policy π is AoC-monotone if, for any fixed δ , it satisfies the inequality $\pi(\tau', \delta) \ge \pi(\tau, \delta)$ for all $\tau' \ge \tau$.

Establishing structural results aligned with these definitions requires the submodularity property of the Q-factor.

Definition 4 (Submodularity). A function g(x, y) is submodular on $\mathcal{X} \times \mathcal{Y}$, if for all $x' \ge x$ and $y' \ge y$,

$$g(x', y') + g(x, y) \le g(x', y) + g(x, y').$$
⁽²⁹⁾

If the inequality is reversed, g(x, y) is called supermodular.

Lemma 4 ([20, Lemma 4.7.1]). If the Q-factor Q(s, u) is submodular in (τ, u) (or (δ, u)), the optimal policy $\pi^*(\tau, \delta) = \arg \min_{u \in \mathcal{U}} Q(s, u)$ is AoC-monotone (or AoI-monotone).

This lemma can be leveraged to conclude about the monotonicity properties of the optimal policy owing to the following result.

Theorem 2. Q(s, u) is submodular in (τ, \underline{u}) and (δ, \underline{u}) , where $\underline{u} \in \{0, 1\}$.

Proof. See Appendix C.

Combining Definition 4 and Theorem 2 gives the following.

Theorem 3. The optimal policy is AoC-monotone.

Proof. We need to show that, for all $u' \ge u$ and $\tau' \ge \tau$,

$$Q(\tau', u'; \delta) + Q(\tau, u; \delta) - Q(\tau', u; \delta) - Q(\tau, u'; \delta) \le 0.$$

Given that

$$Q(\tau, 2; \delta) = \sum_{i=0}^{\delta_{\rm R}-1} f(\delta + i) + V(1, \delta + \delta_{\rm R})$$
(30)

is independent of τ , we have, for each $u \in \{0, 1\}$,

$$Q(\tau', 2; \delta) + Q(\tau, u; \delta) - Q(\tau', u; \delta) - Q(\tau, 2; \delta)$$
$$= Q(\tau, u; \delta) - Q(\tau', u; \delta) \le 0.$$
(31)

Theorem 2 gives that

$$Q(\tau', 1; \delta) + Q(\tau, 0; \delta) - Q(\tau', 0; \delta) - Q(\tau, 1; \delta) \le 0.$$
(32)

So far, we have established that $Q(\tau, u; \delta)$ is submodular for the action pairs $\{0, 1\}, \{0, 2\}$ and $\{1, 2\}$. Since $Q(\tau, 2; \delta)$ is constant in τ , to establish the submodularity for all $u \in \mathcal{U}$, it remains to show that the threshold for renewal is no smaller than that for transmission (see Fig. 4). If not, the optimal action would be to restore when the AoC exceeds a threshold and remain idle otherwise. This cannot happen since renewal is unnecessary if no transmission takes place.

The property of AoC-monotonicity of an optimal policy is illustrated in Fig. 4. For each u, the Q-factor $Q(\tau, u; \delta)$ represents the cost of taking an action u in the current decision epoch and following the optimal policy onwards. By Theorem 3, the submodularity of the Q-factor $Q(\tau, u; \delta)$ implies that the lines are increasing with the AoC τ and that any two lines intersect at most once.



Fig. 4. The threshold structure of the optimal policy $\pi^*(\tau, \delta)$ with fixed δ .

Because of the possibility of taking renewal actions, the optimal policy is generally not AoI-monotone. To see this, let $u' = 2, u \in \{0, 1\}$, and $\delta' \ge \delta$. Then, we have

$$c(\delta', u'; \tau) + c(\delta, u; \tau) - c(\delta', u; \tau) - c(\delta, u'; \tau)$$
$$= \sum_{i=1}^{\delta_{\mathbb{R}}-1} \left(f(\delta'+i) - f(\delta+i) \right) \ge 0, \quad (33)$$

which implies the supermodularity of the cost function $c(\delta, u; \tau)$. Therefore, we cannot say anything specific about the Q-factor $Q(\delta, u; \tau)$, as it combines both submodular and supermodular components.

C. Structured Policy Iteration

We now exploit the structural results derived in Sec. III-B and propose a structured policy iteration algorithm to reduce the computation overhead. The algorithm proceeds as follows².

- 1) *Initialization:* Arbitrarily select initial policy π^0 , reference state s_{ref} , and set n = 0.
- 2) Policy Evaluation: Obtain λ^n and V^n by solving

$$\lambda^{n} + V^{n}(s) = c(s, \pi^{n}(s)) + \sum_{s'} P_{s,s'}(\pi^{n}(s))V^{n}(s')$$

for all s such that $V^n(s_{ref}) = 0$.

3) Policy Improvement: Choose π^{n+1} to satisfy

$$\pi^{n+1}(s) = \underset{u \in \mathcal{U}_s}{\operatorname{arg\,min}} \left[c(s,u) + \sum_{s'} P_{s,s'}(u) V^n(s') \right],$$

where U_s is the action set associated with state s, which decreases in size with increasing s. Specifically, for each fixed δ , if it is optimal to transmit in state (τ, δ) , then the optimal action for all the states (τ', δ) with $\tau' > \tau$ is either to transmit or to restore. Similarly, if it is optimal to renew the channel, the optimal action for all $(\tau', \delta), \tau' > \tau$ is to restore without further computation.

Stopping Criterion: If πⁿ⁺¹ = πⁿ, the algorithm terminates with λ* = λⁿ and π* = πⁿ; otherwise increase n = n + 1 and return to Step 2.

A low-complexity, yet suboptimal, policy is to restore the channel whenever the AoC exceeds a given threshold. Then, in Step 3, we only need to find the optimal thresholds for data transmission. If $\pi^*(\tau, \delta) = 1$, then we set $\pi^*(\tau', \delta') = 1$ for all $\delta' \ge \delta$ and $\tau' \ge \tau$. We can further restrict the policy space by noting that the transmission threshold is decreasing in τ .

²For numerical tractability, the algorithm operates in a finite policy space. The age processes are truncated with appropriately chosen large numbers.



Fig. 5. The structure of the optimal policy under different values of β when $\alpha = 0.1$, $\tau_D = 6$, $\delta_R = 15$. (a) $\beta = 0.9$, the system is always stable; (b) $\beta = 1.0$, the system becomes unstable with large AoC; and (c) $\beta = 1.1$, the system might be unstable even with moderate AoC.



Fig. 6. Counterexamples on the monotonicity of optimal policies when $\beta = 1.0, \alpha = 0.05$.

IV. NUMERICAL RESULTS

We examine a remote estimation system with parameters

$$\mathbf{A} = \begin{bmatrix} \beta & 0.5\\ 0 & 0.8 \end{bmatrix}, \mathbf{Q} = \begin{bmatrix} 1 & 0\\ 0 & 1 \end{bmatrix}, \mathbf{C} = \begin{bmatrix} 1, 1 \end{bmatrix}, \mathbf{R} = 1,$$

where $\beta > 0$ is a variable to be examined. The spectral radius is $\rho(\mathbf{A}) = \max\{\beta, 0.8\}$, so the process is unstable if $\beta \ge 1$. We consider an exponential wearing channel with $\theta(\tau) = (\theta_{\max} - \theta_{\min})e^{-\alpha\tau} + \theta_{\min}$ where $\alpha > 0$ is the decay rate. The channel reliability $\theta(\tau)$ declines from θ_{\max} to θ_{\min} as the AoC goes to infinity. We consider $\theta_{\max} = 0.99$ and $\theta_{\min} = 0$.

Fig. 5 shows the optimal policy results under different values of β . In this example, we assume that each transmission attempt increments $\tau_D = 6$ slots of wear on the channel, while a channel renewal requires $\delta_R = 15$ time slots to complete. The decay rate is set to $\alpha = 0.1$. It can be observed that the optimal policies are both AoI- and AoC-monotone. An interesting observation is that the data transmission and channel renewal thresholds decrease as β increases. This behavior arises because the error covariance grows rapidly for larger β . Thus, the sensor takes more aggressive actions to mitigate this growth.

Fig. 6a and Fig. 6b give counterexamples where the monotonicity in AoI does not hold. We set $\alpha = 0.05$ and $\beta = 1.0$. As shown in Fig.6a, when the channel quality is relatively poor, i.e., the AoC is large, even when the AoI is small, restoring the channel is worthwhile. This occurs because the downtime for channel renewal is short, while there is a high probability of an unsuccessful transmission. In contrast, Fig. 6b shows that when channel renewal takes a significantly longer time, i.e., δ_R is large, the optimal policy triggers renewal over a very narrow range of AoI. The optimal policy becomes AoI-monotone in Fig. 6c. We also observe that the optimal policy is monotone in AoI and AoC without renewal action. This suggests that a computationally efficient way is to restore the channel whenever the AoC exceeds a given threshold.

V. CONCLUSIONS

We have studied the optimal transmission scheduling for remote estimation over a wearing channel. The problem was formulated as an MDP with two dependent age processes. We established the optimality of an AoC-monotone policy and proposed a structured policy iteration algorithm to determine the optimal timing for data transmission and channel renewal. Numerical results were presented to validate our findings.

APPENDIX A Proof of Theorem 1

The proof relies on the vanishing discount approach [21]. The α -discounted version of Problem (21) is defined as

$$V_{\alpha}(s_0) = \inf_{\pi \in \Pi} V_{\alpha}^{\pi}(s_0), \qquad (34)$$

where $V_{\alpha}^{\pi}(s_0) \coloneqq \mathbb{E}^{\pi} \left[\sum_{t=0}^{\infty} \alpha^t c(s_t, u_t) | s_0 \right]$ is the total discounted cost of a policy $\pi \in \Pi$, and $\alpha \in (0, 1)$ is a discount factor. The α -discounted version of Bellman's equation is

$$V_{\alpha}(s) = \min_{u \in \mathcal{U}} \left[c(s, u) + \alpha \sum_{s'} P_{s, s'}(u) V_{\alpha}(s') \right].$$
(35)

Specifying a reference state $s_{ref} \in S$ and introducing the α -discounted relative value function

$$h_{\alpha}(s) = V_{\alpha}(s) - V_{\alpha}(s_{\text{ref}}), \qquad (36)$$

we obtain

$$(1-\alpha)V_{\alpha}(s_{\text{ref}}) + h_{\alpha}(s) = \min_{u \in \mathcal{U}} \left[c(s,u) + \alpha \sum_{s'} P_{s,s'}(u)h_{\alpha}(s') \right].$$
(37)

Taking a limit as $\alpha \uparrow 1$ and assuming the limit of all terms in the above equation exists, then we obtain Bellman's equation for the original average cost problem with

$$\lambda^* = \lim_{\alpha \uparrow 1} (1 - \alpha) V_\alpha(s_{\text{ref}}), \quad V(s) = \lim_{\alpha \uparrow 1} h_\alpha(s).$$
(38)

To show the convergence of the above limits, the following conditions need to be verified [21, Theorem 5.5.4]

- i. $V_{\alpha}(s) < \infty$ for every $s \in S$ and $\alpha \in (0, 1)$.
- ii. There exists a reference state s_{ref} , constants $M \ge 0$ and $\underline{\alpha} \in (0, 1)$, and a nonnegative function b(s) such that $-M \le h_{\alpha}(s) \le b(s)$ for all $s \in S$ and $\alpha \in [\alpha, 1)$.

iii.
$$b(s)$$
 satisfies $\sum_{s'} b(s) P_{s,s'}(u) < \infty$ for all s and u.

Specifically, the first condition guarantees a unique solution to (35). Conditions (ii)-(iii) ensure the convergences of the limits in (38). Since the cost achieved by the average-cost MDP is no smaller than that of its discounted counterpart [21, Lemma 5.3.1], these conditions follow from Lemma 3.

APPENDIX B PROOF OF PROPOSITION 1

We first prove part (i) by induction. We choose $V^0(\tau, \delta)$ to be increasing in δ , i.e.,

$$V^{0}(\tau,\delta) \le V^{0}(\tau,\delta'), \ \forall \delta \le \delta'.$$
(39)

Assume that $V^n(\tau, \delta)$ is increasing in δ for all $\tau \in \mathbb{N}^+$. Now we show that $V^{n+1}(\tau, \delta)$ is also increasing in δ . By (26)-(28), we have

$$V^{n+1}(s) = \min_{u} \left[Q^{n+1}(s, u) \right] - \min_{u} \left[Q^{n+1}(s_{\text{ref}}, u) \right].$$
(40)

Hence, it suffices to show that $Q^{n+1}(s, u)$ is increasing in δ for all u. We now establish this result as follows.

If u = 0, the system will transition into $(\tau + 1, \delta + 1)$ with certainty. Then

$$Q^{n+1}(\delta, 0; \tau) = f(\delta) + V^n(\tau + 1, \delta + 1), \qquad (41)$$

which by Lemma 1 and the induction hypothesis gives

$$Q^{n+1}(\delta,0;\tau) \le f(\delta') + V^n(\tau+1,\delta'+1) = Q^{n+1}(\delta',0;\tau).$$

If u = 1, the system can either transition to state $(\tau + \tau_D, 1)$ w.p. $\theta(\tau)$ or to state $(\tau + \tau_D, \delta + 1)$ w.p. $\bar{\theta}(\tau)$. Then,

$$Q^{n+1}(\delta, 1; \tau) = f(\delta) + \theta(\tau)V^n(\tau + \tau_{\rm D}, 1) + \bar{\theta}(\tau)V^n(\tau + \tau_{\rm D}, \delta + 1) \leq f(\delta') + \theta(\tau)V^n(\tau + \tau_{\rm D}, 1) + \bar{\theta}(\tau)V^n(\tau + \tau_{\rm D}, \delta' + 1) = Q^{n+1}(\delta', 1; \tau) \leq 0.$$
(42)

If u = 2, the system resets to $(1, \delta + \delta_R)$ with certainty, i.e.,

$$Q^{n+1}(\delta, 2; \tau) = \sum_{i=0}^{\delta_{\rm R}-1} f(\delta+i) + V^n(1, \delta+\delta_{\rm R})$$

$$\leq \sum_{i=0}^{\delta_{\rm R}-1} f(\delta'+i) + V^n(1, \delta'+\delta_{\rm R})$$

$$= Q^{n+1}(\delta', 2; \tau).$$
(43)

Hence, for each $u \in \mathcal{U}$, $Q^n(\delta, u; \tau)$ is increasing in δ .

We adopt a similar induction procedure to prove part (ii). Assume $V^n(\tau, \delta)$ is increasing in τ for all δ . We need to show that $Q^{n+1}(\tau, u; \delta)$ is increasing in τ for all u. Obviously, $Q^{n+1}(\tau, 0; \delta)$ and $Q^{n+1}(\tau, 2; \delta)$ are increasing in τ . The monotonicity for u = 1 follows by noting that, for all $\tau' \geq \tau$,

$$Q^{n+1}(\tau', 1; \delta) - Q^{n+1}(\tau, 1; \delta) = \theta(\tau')V^{n}(\tau' + \tau_{\rm D}, 1) - \theta(\tau)V^{n}(\tau + \tau_{\rm D}, 1) + \bar{\theta}(\tau')V^{n}(\tau' + \tau_{\rm D}, \delta + 1) - \bar{\theta}(\tau)V^{n}(\tau + \tau_{\rm D}, \delta + 1) = \theta(\tau') \underbrace{\left(\underbrace{V^{n}(\tau' + \tau_{\rm D}, 1) - V^{n}(\tau + \tau_{\rm D}, 1)}_{\geq 0} \right)}_{\geq 0} + \bar{\theta}(\tau') \underbrace{\left(\underbrace{V^{n}(\tau' + \tau_{\rm D}, \delta + 1) - V^{n}(\tau + \tau_{\rm D}, \delta + 1)}_{\geq 0} \right)}_{\geq 0} + \underbrace{\left(\underbrace{\theta(\tau') - \theta(\tau)}_{\leq 0} \right)} \underbrace{\left(\underbrace{V^{n}(\tau + \tau_{\rm D}, 1) - V^{n}(\tau + \tau_{\rm D}, \delta + 1)}_{\leq 0} \right)}_{\leq 0} \right)$$

APPENDIX C Proof of Theorem 2

We first show that $Q(\delta, \underline{u}; \tau)$ is submodular in (δ, \underline{u}) . By Definition 4, we need to verify that

$$Q(\delta', 1; \tau) + Q(\delta, 0; \tau) - Q(\delta', 0; \tau) - Q(\delta, 1; \tau) \le 0.$$
(44)

Substituting

$$Q(\delta, 1; \tau) = f(\delta) + \theta(\tau)V(\tau + \tau_{\rm D}, 1) + \bar{\theta}(\tau)V(\tau + \tau_{\rm D}, \delta + 1), \qquad (45)$$
$$Q(\delta, 0; \tau) = f(\delta) + V(\tau + 1, \delta + 1) \qquad (46)$$

$$\psi(\tau, \delta, \delta') = \bar{\theta}(\tau) \left(V(\tau + \tau_{\mathrm{D}}, \delta') - V(\tau + \tau_{\mathrm{D}}, \delta) \right) - \left(V(\tau + 1, \delta') - V(\tau + 1, \delta) \right) \le 0.$$
(47)

By Proposition 1, $V(\tau, \delta)$ is increasing in δ and τ . So it is not immediately clear whether the inequality in (47) holds in general. Moreover, since there is no closed-from expression of the value function, we will derive an upper bound of $\psi(\tau, \delta, \delta')$, denoted as $\Psi(\tau, \delta, \delta')$, and show that $\Psi(\tau, \delta, \delta') \leq 0$.

Let $\underline{u}_1^*, \underline{u}_2^* \in \{0, 1\}$ denote the optimal actions such that

$$V(\tau + \tau_{\rm D}, \delta) = Q(\delta, \underline{u}_1^*; \tau + \tau_{\rm D}), \tag{48}$$

$$V(\tau + 1, \delta') = Q(\delta', \underline{u}_2^*; \tau + 1).$$
(49)

Let $\underline{u}_0 = \underline{u}_1^*$ and $\underline{u}_3 = \underline{u}_2^*$. It gives that

$$V(\tau + \tau_{\mathrm{D}}, \delta') \le Q(\delta', \underline{u}_0; \tau + \tau_{\mathrm{D}}), \tag{50}$$

$$V(\tau+1,\delta) \le Q(\delta,\underline{u}_3;\tau+1),\tag{51}$$

and

$$\psi(\tau, \delta, \delta') \leq \bar{\theta}(\tau) \left(Q(\delta', \underline{u}_0; \tau + \tau_{\rm D}) - Q(\delta, \underline{u}_1^*; \tau + \tau_{\rm D}) \right) - \left(Q(\delta', \underline{u}_2^*; \tau + 1) - Q(\delta, \underline{u}_3; \tau + 1) \right)$$
(52)
$$\Psi(-\delta, \delta')$$
(52)

$$=\Psi(\tau,\delta,\delta').$$
(53)

The proof proceeds by induction. Assume that $V^n(\tau, \delta)$ satisfies (47) for all τ and $\delta' \geq \delta$. This is equivalent to assume that $Q^{n+1}(\delta, \underline{u}; \tau)$ is submodular at iteration n+1. We then show that the inequality in (47) holds for $V^{n+1}(\tau, \delta)$ by proving that $\Psi^{n+1}(\tau, \delta, \delta') \leq 0$ for all τ and $\delta' \geq \delta$.

The proof is divided into four cases: (1) $\underline{u}_1^* = \underline{u}_2^* = 0$; (2) $\underline{u}_1^* = 1$, $\underline{u}_2^* = 0$; (3) $\underline{u}_1^* = 0$, $\underline{u}_2^* = 1$; and (4) $\underline{u}_1^* = 1$, $\underline{u}_2^* = 1$. Due to space limits, we only present the proof for the first two cases. The remaining cases follow similarly.

Case 1): $\underline{u}_1^* = \underline{u}_2^* = 0$. Then we have

$$Q^{n+1}(\delta', \underline{u}_0; \tau + \tau_{\rm D}) - Q^{n+1}(\delta, \underline{u}_1^*; \tau + \tau_{\rm D}) = f(\delta') - f(\delta) + V^n(\tau + \tau_{\rm D} + 1, \delta' + 1) - V^n(\tau + \tau_{\rm D} + 1, \delta + 1),$$
(54)
$$Q^{n+1}(\delta', \underline{u}_2^*; \tau + 1) - Q^{n+1}(\delta, \underline{u}_3; \tau + 1) = f(\delta') - f(\delta) + V^n(\tau + 2, \delta' + 1) - V^n(\tau + 2, \delta + 1).$$
(55)

Substituting (54)-(55) into (53) and letting $\tau_0 = \tau + 1$ yields

$$\Psi^{n+1}(\tau, \delta, \delta') = -\theta(\tau) (f(\delta') - f(\delta)) + (\bar{\theta}(\tau) (V^n(\tau_0 + \tau_D, \delta' + 1) - V^n(\tau_0 + \tau_D, \delta + 1)) - (V^n(\tau_0 + 1, \delta' + 1) - V^n(\tau_0 + 1, \delta + 1))) \leq -\theta(\tau) (f(\delta') - f(\delta)) + (\bar{\theta}(\tau_0) (V^n(\tau_0 + \tau_D, \delta' + 1) - V^n(\tau_0 + \tau_D, \delta + 1)))$$

$$-\left(V^{n}(\tau_{0}+1,\delta'+1)-V^{n}(\tau_{0}+1,\delta+1)\right)\right)$$
(56)

$$= -\theta(\tau) \big(f(\delta') - f(\delta) \big) + \psi^n(\tau_0, \delta, \delta').$$
(57)

The inequality in (56) follows from the fact that $\theta(\tau)$ is increasing in τ . By the induction hypothesis, it follows that $\Psi^{n+1}(\tau, \delta, \delta') \leq 0$.

Case 2): $\underline{u}_{1}^{*} = 1, \underline{u}_{2}^{*} = 0$. We may write

$$\Psi^{n+1}(\tau,\delta,\delta') = -\theta(\tau) \big(f(\delta') - f(\delta) \big) + \bar{\theta}(\tau) \bar{\theta}(\tau+\tau_{\rm D}) \\ \times \big(V^n(\tau+2\tau_{\rm D},\delta'+1) - V^n(\tau+2\tau_{\rm D},\delta+1) \big) \\ - \big(V^n(\tau+2,\delta'+1) - V^n(\tau+2,\delta+1) \big).$$
(58)

Adding an auxiliary term on the right-hand side, we obtain

$$\Psi^{n+1}(\tau,\delta,\delta') = -\theta(\tau) \big(f(\delta') - f(\delta) \big) + \\ \Big(\bar{\theta}(\tau) \bar{\theta}(\tau+\tau_{\rm D}) \big(V^n(\tau+2\tau_{\rm D},\delta'+1) - V^n(\tau+2\tau_{\rm D},\delta+1) \big)$$

$$- \bar{\theta}(\tau) \left(V^{n}(\tau + \tau_{\rm D} + 1, \delta' + 1) - V^{n}(\tau + \tau_{\rm D} + 1, \delta + 1) \right) \right) \\ + \left(\bar{\theta}(\tau) \left(V^{n}(\tau + \tau_{\rm D} + 1, \delta' + 1) - V^{n}(\tau + \tau_{\rm D} + 1, \delta + 1) \right) \\ - \left(V^{n}(\tau + 2, \delta' + 1) - V^{n}(\tau + 2, \delta + 1) \right) \right).$$
(59)

Letting $\tau_1 = \tau + \tau_D$ and $\tau_2 = \tau + 1$ gives

$$\Psi^{n+1}(\tau,\delta,\delta') = -\theta(\tau) \big(f(\delta') - f(\delta) \big) + \\ \bar{\theta}(\tau) \psi^n(\tau_1,\delta,\delta') + \psi^n(\tau_2,\delta,\delta') \le 0.$$
(60)

Since $\Psi^{n+1}(\tau, \delta, \delta') \leq 0$ holds for all possible $\underline{u}_1^*, \underline{u}_2^* \in \{0, 1\}$, it follows that $Q(\delta, \underline{u}; \tau)$ is submodular in (δ, \underline{u}) . Using a similar induction, one can easily show that $Q(\tau, \underline{u}; \delta)$ is also submodular in (τ, \underline{u}) . This concludes our proof.

REFERENCES

- P. Park, S. Coleri Ergen, C. Fischione, C. Lu, and K. H. Johansson, "Wireless network design for control systems: A survey," *IEEE Commun. Surveys Tuts.*, vol. 20, no. 2, pp. 978–1013, 2018.
- [2] L. Schenato, B. Sinopoli, M. Franceschetti, K. Poolla, and S. S. Sastry, "Foundations of control and estimation over lossy networks," *Proc. IEEE*, vol. 95, no. 1, pp. 163–187, 2007.
- [3] L. Schenato, "Optimal estimation in networked control systems subject to random delay and packet drop," *IEEE Trans. Autom. Control*, vol. 53, no. 5, pp. 1311–1317, 2008.
- [4] L. Shi, P. Cheng, and J. Chen, "Sensor data scheduling for optimal state estimation with communication energy constraint," *Automatica*, vol. 47, no. 8, pp. 1693–1698, 2011.
- [5] A. S. Leong, S. Dey, and D. E. Quevedo, "Sensor scheduling in variance based event triggered estimation with packet drops," *IEEE Trans. Autom. Control*, vol. 62, no. 4, pp. 1880–1895, 2017.
- [6] S. Wu, X. Ren, Q.-S. Jia, K. H. Johansson, and L. Shi, "Learning optimal scheduling policy for remote state estimation under uncertain channel condition," *IEEE Trans. Control Netw. Syst.*, vol. 7, no. 2, pp. 579–591, 2020.
- [7] M. Huang and S. Dey, "Stability of kalman filtering with markovian packet losses," *Automatica*, vol. 43, no. 4, pp. 598–607, 2007.
- [8] W. Liu, D. E. Quevedo, Y. Li, K. H. Johansson, and B. Vucetic, "Remote state estimation with smart sensors over markov fading channels," *IEEE Trans. Autom. Control*, vol. 67, no. 6, pp. 2743–2757, 2022.
- [9] W. C. Abraham and M. F. Bear, "Metaplasticity: the plasticity of synaptic plasticity," *Trends in neurosciences*, vol. 19, no. 4, pp. 126–130, 1996.
- [10] M. Schlosshauer, "Quantum decoherence," *Physics Reports*, vol. 831, pp. 1–57, 2019.
- [11] T.-Y. Wu, L. R. Varshney, and V. Y. F. Tan, "On the throughput of channels that wear out," *IEEE Trans. Commun.*, vol. 67, no. 8, pp. 5311– 5320, 2019.
- [12] S. Kaul, R. Yates, and M. Gruteser, "Real-time status: How often should one update?" in *Proc. IEEE Int. Conf. Comput. Commun.*, 2012, pp. 2731–2735.
- [13] A. M. Bedewy, Y. Sun, S. Kompella, and N. B. Shroff, "Optimal sampling and scheduling for timely status updates in multi-source networks," *IEEE Trans. Inf. Theory*, vol. 67, no. 6, pp. 4019–4034, 2021.
- [14] V. Tripathi and E. Modiano, "A whittle index approach to minimizing functions of age of information," *IEEE/ACM Trans. Netw.*, pp. 1–15, 2024.
- [15] R. D. Yates, Y. Sun, D. R. Brown, S. K. Kaul, E. Modiano, and S. Ulukus, "Age of information: An introduction and survey," *IEEE J. Sel. Areas Commun.*, vol. 39, no. 5, pp. 1183–1210, 2021.
- [16] J. Luo and N. Pappas, "Exploiting data significance in remote estimation of discrete-state markov sources," arXiv:2406.18270, 2024.
- [17] —, "On the cost of consecutive estimation error: Significance-aware non-linear aging," arXiv:2410.03637, 2024.
- [18] G. J. Stamatakis, O. Simeone, and N. Pappas, "Optimizing information freshness over a channel that wears out," in *Proc. Asilomar Conf. Signals, Syst. Comput.*, 2023, pp. 85–89.
- [19] B. D. O. Anderson and J. B. Moore, *Optimal Filtering*. Prentice Hall, 1979.
- [20] M. L. Puterman, Markov decision processes: discrete stochastic dynamic programming. John Wiley & Sons, 1994.
- [21] O. Hernández-Lerma and J. B. Lasserre, *Discrete-time Markov control processes: basic optimality criteria*. Springer Science & Business Media, 1996, vol. 30.