How to Select Datapoints for Efficient Human Evaluation of NLG Models?

Vilém Zouhar Peng Cui Mrinmaya Sachan

Department of Computer Science, ETH Zürich

{vzouhar, pcui, msachan}@ethz.ch

Abstract

Human evaluation is the gold-standard for evaluating text generation models. It is also expensive, and to fit budgetary constraints, a random subset of the test data is often chosen in practice. The randomly selected data may not accurately represent test performance, making this approach economically inefficient for model comparison. Thus, in this work, we develop a suite of selectors to get the most informative datapoints for human evaluation while taking the evaluation costs into account. We show that selectors based on variance in automated metric scores, diversity in model outputs, or Item Response Theory outperform random selection. We further develop an approach to distill these selectors to the scenario where the model outputs are not yet available. In particular, we introduce source-based estimators, which predict item usefulness for human evaluation just based on the source texts. We demonstrate the efficacy of our selectors in two common NLG tasks, machine translation and summarization, and show that up to only \sim 50% of the test data is needed to produce the same evaluation result as the entire data. Our implementations are published in the subset2evaluate package.

1 Introduction

Robust model evaluation drives natural language generation (NLG) research. Despite improvements in automated evaluation metrics, human evaluation remains the gold standard in NLG (Zhou et al., 2022; Freitag et al., 2023). Distinguishing between high-quality models requires increasingly more expert human annotations to determine which model performs better. For example, the WMT shared tasks (Conference on Machine Translation, Kocmi et al., 2024a), annually evaluate dozens of state-ofthe-art machine translation models.

The dominant approach in human evaluation under budgetary constraints is to *randomly* select eval-



Figure 1: Output-based variant of our informative subset selection approach. Given model outputs and automated metrics, we select items to be human-evaluated on which the final model ranking can be computed.

uation items in the test data (Ruan et al., 2024). The random selection is clearly sub-optimal because it can lead to selecting overlapping items while omitting items that significantly impact the evaluation outcome, such as model ranking.

Thus, in this paper, we develop approaches to select a subset of test items to reduce humanevaluation cost without sacrificing evaluation accuracy. In particular, we are interested in selecting a subset of test items that would lead to a human ranking of multiple NLG models similar to that on the entire testset. We frame this as a subset selection problem (dubbed output-based selection, Figure 1) where we are given a set of items \mathcal{X} and model outputs \mathcal{M} , and would like to select a subset $\mathcal{Y} \subseteq \mathcal{X}$ such that the ranking of models with human evaluation on \mathcal{Y} is the same as on \mathcal{X} . While automated metrics can be noisy and may not always align with human judgments, they still help

⁰We release the subset2evaluate package, trained models, and reproducible paper code.

identify test items that are informative for evaluation. We build multiple data selectors that leverage these metrics, such as prioritizing challenging items, items leading to diverse model outputs, or using Item Response Theory.

Yet, in some evaluation scenarios, such as when organizing a large shared task, we may not yet know which models will be evaluated by our test set, or obtaining all model outputs on the whole \mathcal{X} may be computationally infeasible due to the size of \mathcal{X} . In this setting, dubbed source-based selection (Figure 2), the standard methods for output-based selection can not be used. However, by distilling the output-based selection methods, we build predictors that only use the item input to predict the expected item difficulty or likelihood that it leads to diverse model outputs.

We demonstrate the efficacy of our data selection approach with case studies on two typical natural language generation tasks: machine translation and summarization. Our key contributions include:

- framing the task of informative subset selection for evaluation in two variants,
- multiple evaluation subset selection methods, including cost- and document-aware selection,
- selector distillation for source-based selection,
- package subset2evaluate for budget-efficient test set construction for model evaluation.

This paper is structured as follows. We formalize the problem in Section 2, describe the output-based and source-based selectors in Sections 3 and 4. We show our results on efficient machine translation evaluation in Section 5 and the results on evaluating summarization models in Section 6. Notably, we find that in the WMT annual evaluation for machine translation models, our methods yield the same number of clusters in model ranking as random sampling but with only 32% of human annotations. At this scale, this is a non-trivial cost benefit.

2 Problem Statement

We are given a set of items \mathcal{X} and a set of models \mathcal{M} that we wish to rank based on \mathcal{X} . Here, each item $x \in \mathcal{X}$ is an input text and m(x) is the output of model m in the NLG task. For example, in machine translation, each x is the input in the source language and m(x) is the corresponding translation. Since $|\mathcal{X}|$ is very large (exceeding the human budget B), we seek a subset $\mathcal{Y} \subseteq \mathcal{X}$ such that the ranking of models on \mathcal{Y} can be as close to that on

 \mathcal{X} as possible. An illustration of the problem is also shown in Figure 1.

Human evaluation set selection. In order to obtain a subset $\mathcal{Y} \subseteq \mathcal{X}$ to be human-evaluated, we quantify the cost of human evaluations on \mathcal{Y} with $Cost(\mathcal{Y})$ and the usefulness of the subset for evaluation with $Utility(\mathcal{Y})$. In the ideal case, the utility of the set \mathcal{Y} indicates how close the human ranking of models on items $y \in \mathcal{Y}$ is to the human ranking of models on whole \mathcal{X} . We frame this as a subset selection problem as follows:

$$\underset{\mathcal{Y}\subseteq\mathcal{X}}{\operatorname{arg\,max}} \operatorname{Utility}(\mathcal{Y}) \quad \text{s.t.} \quad \operatorname{Cost}(\mathcal{Y}) \leq B \quad (1)$$

In our work, we make two simplifications. First, we note that the cost of evaluating a set of items is the sum of costs for evaluating individual items, i.e., $Cost(\mathcal{Y}) = \sum_{y \in \mathcal{Y}} Cost(y)$. This assumption is generally true if the human evaluation of items y is carried out one by one. Second, we assume that the utility of the set \mathcal{Y} is the sum of utilities of items $y \in \mathcal{Y}$. Note that this is generally not true as similar datapoints may not offer an extra marginal utility for model ranking. However, in our experiments, we find that this assumption leads to good empirical results. Moreover, our preliminary experiments on modeling diversity of datapoints did not lead to better performance. See Appendix Figure 7 for details.

With the two assumptions, we rewrite Equation (1) using 0/1 indicator variables z_x , which becomes a 0-1 knapsack problem.

maximize
$$\sum_{x \in \mathcal{X}} z_x \cdot \text{Utility}(x)$$

subject to
$$\sum_{x \in \mathcal{X}} z_x \cdot \text{Cost}(x) \le B$$

and $\forall x \in \mathcal{X} : z_x \in \{0, 1\}$ (2)

This problem is generally NP-complete (Karp et al., 1975). However, for constant Cost(.) and positive item utilities, we can find an optimal solution by taking the items with the highest utilities until the budget *B* is reached. For non-constant Cost(.), we find an approximate solution using integer linear programming (Huangfu and Hall, 2018).

Next, we present multiple ways to approximate the utility of an item Utility(x).

2.1 Subset selection evaluation

Once we select a subset of data for human evaluation, how do we know if it is good? We evaluate the quality of the selected subset with two measures: (1) Spearman rank correlation, and (2) Cluster count. The rank correlation reveals how closely the model ranking as per the selected subset matches with the ordering when evaluated on all data. Note that this requires the presence of human evaluations on the entire testdata. Our second metric, cluster count, popularly used by WMT (Kocmi et al., 2023), does not require human evaluations on the entire test data. The cluster count directly evaluates the discriminability of the model ranking by putting the models in various equivalence classes (clusters). Higher number of equivalence classes indicates higher discriminability of models. To compute cluster count, we start with the best performing model. If the second best model is statistically indistinguishable with Wilcoxon onesided test with p < 0.05, we add it to the same cluster, else we create a new cluster. Then, we compare the third best model with the lowest ranked model in the previous cluster and so on. See Appendix Algorithm 1 for details.

2.2 Source- vs. Output-based selection

In many practical scenarios, for example in the WMT shared tasks, the size of \mathcal{X} may be so large that it is prohibitively expensive to obtain model outputs on the whole dataset for all the models. Furthermore, we may not yet know all the participating models \mathcal{M} , e.g., when preparing blind test sets for a shared task. For such scenarios, we introduce source-based data selection. In contrast to output-based data selection, which models item utilities with the knowledge of model outputs m(x), source-based data selection models Utility(x) based solely on the input x.

3 Output-based Selectors

We begin by outlining various utility functions for output-based subset selection. We will describe methods for source-based selection later as these rely on the methods for output-based selection. Finally, we will compare data selection approaches using the defined utilities with a random subset selection baseline which randomly chooses a subset of data with the cost B for human evaluation.

3.1 Metrics moment

We first introduce two utility functions for selecting informative items based on the distribution moments induced by automated metric scores. Metrics provide us with a coarse estimate of item difficulty and the shape of the distribution can be used to select high-impact items for human evaluation.

Our first heuristic for defining utility is based on average metric scores. As average metric scores correlate negatively with the difficulty of the item for NLG models, our heuristic selects items with highest difficulty, i.e., lowest average metric score:

$$METRICAVG(x, \mathcal{M}) =$$

$$-\sum_{m \in \mathcal{M}} \frac{\operatorname{metric}(x, m(x))}{|\mathcal{M}|}$$
(3)

To optimize the selected evaluation subset quality, our second heuristic looks for items that impact the final ranking the most. Items where all models produce very high quality or very low quality outputs add lower value for final model ranking. Thus, to prioritize high-impact items that highlight differences between models, our second metric measures variance in metrics across models:

$$\operatorname{METRICVAR}(x, \mathcal{M}) = (4)$$

$$\sum_{m \in \mathcal{M}} \frac{(\operatorname{metric}(x, m(x)) - \operatorname{METRICAVG}(x, \mathcal{M}))^2}{|\mathcal{M}|}$$

3.2 Metric consistency

Another approach to utilize the shape of the distribution of metric scores over various models is to consider items where the automated metrics show model ranking consistent with the whole set \mathcal{X} :

$$METRICCONS(x) = (5)$$

RankCorr $\begin{pmatrix} \langle metric(x,m(x)) | m \in \mathcal{M} \rangle, \\ \langle \sum_{x' \in \mathcal{X}} metric(x',m(x')) | m \in \mathcal{M} \rangle \end{pmatrix}$

As these items mimic the ranking of models according to the automated metrics, they should be selected in the test set.

3.3 Output diversity

While metrics variance prioritizes items that lead to outputs of different qualities, our fourth metric goes a step further and prioritizes items that lead to diverse *outputs* as evaluating identical outputs from different models is not useful:

DIVERSITY
$$(x, \mathcal{M}) =$$
 (6)
$$-\frac{\sum_{m_1, m_2 \in \mathcal{M}} \sin(m_1(x), m_2(x))}{|\mathcal{M}|^2}$$

Output diversity can be captured by average text similarity among the outputs, for example with unigram overlap, or embedding similarity. We take the negative value of the average to prioritize items with lower similarity across outputs.

3.4 Item response theory

Previous works on informative test construction often use Item Response Theory (IRT, Santor and Ramsay, 1998), which provides a principled approach to the problem. Inspired from educational sciences, IRT provides a way to create a budgetefficient test for evaluating and comparing various students. Given a set of students' responses to a set of test items, IRT models the probability that a student m with a given ability level θ_m will answer a question x correctly as the standard logistic function:

$$p(r_{m,x}=1) = \frac{c_x}{1 + \exp[-a_x(\theta_m - b_x)]},$$
 (7)

Here, the student response (r) is typically a binary label (correct or incorrect), a_x denotes the **discriminability** of the item, b_x denotes the **difficulty** of the item x, and c_x denotes the probability that a random guess may lead to the correct answer. The item parameters define the shape of the standard logistic function – for items with high discriminability a_x , even very close students can be distinguished because a small change in θ_m changes the prediction.

We draw on this analogy and fit an IRT model to predict the metric scores metric(x, m(x)) for various models m on items x. However, in NLG, metric scores are usually not binary but continuous. While some previous approaches circumvent this by binarizing the continuous variable (Polo et al., 2024), this leads to a loss of information, and we can redefine the objective to directly predict the continuous score $r_{m,x} := metric(x, m(x))$ as in other works in psychometry (Noel and Dauvier, 2007):

$$r_{m,x} = \frac{c_x}{1 + \exp[-a_x(\theta_m - b_x)]},$$
 (8)

See an illustration of IRT predictions and parameters b_x and a_x in Appendix Figure 8. Following standard practice, we optimize the IRT model with stochastic variational inference (Wu et al., 2020; Rodriguez et al., 2021; Lalor and Rodriguez, 2023).

We repurpose this method from evaluating students to evaluating models and use both the item Evaluation items \mathcal{X} (sources)



Figure 2: Source-based variant of informative subset selection (in contrast with output-based in Figure 1). Given just the item inputs, we select items to be given to models and their outputs to be human-evaluated.

discriminability a_x , and difficulty b_x for utility:¹

$$DIFFDISC(x) = a_x \times b_x \tag{9}$$

4 Source-Based Selectors

Next, we discuss approaches for source-based data selection where the model outputs and metric scores are not available. We provide two ways to adapt our output-based methods to the case where we select datapoints given only source texts: (a) estimating item utility just based on x via **model distillation**, and (b) creating an **artificial crowd** of models imitating \mathcal{M} .

4.1 Item utility distillation

The calculation of item utilities in output-based selection requires access to the models \mathcal{M} . To mitigate this, we develop a model distillation approach to fit a model Utility^{src}(x) that predicts Utility(x, \mathcal{M}) in the absence of \mathcal{M} , just based on the item input x. We use the architecture of a learned NLG metric (Rei et al., 2020) to predict the utilities. The input text x is encoded with a pre-trained language model and a regression head is trained with MSE loss predicting output-based utilities. As a result, we obtain new source-based item utility estimators: METRICAVG^{STC}, METRICVAR^{STC}, METRICONS^{STC}, METRICDIVERSITY^{STC}, and DIFFDISC^{STC}. For IRT, Benedetto et al. (2020);

¹We use a product instead of addition because a_x and b_x may have different scales.

Byrd and Srivastava (2022) build functions that directly predict the item discriminability a_x and difficulty b_x for unseen items. In contrast, our predictor predicts directly the product $a_x \times b_x$ used for the item utility.

An advantage of source-based item utilities over output-based ones is that we can train the model to predict the utilities based on human scores as opposed to metric scores, if these exist in the training data. In the context of machine translation, similar models are used for estimating properties of translation and sources Rei et al. (2020); Don-Yehiya et al. (2022); Zouhar et al. (2023); Perrella et al. (2024). See implementation details in Appendix Table 6. Note that this method only works on novel items that are similar to those in the training data.

4.2 Artificial crowd

If \mathcal{M} is large, prohibiting the computation of all the model outputs, but a subset of models in \mathcal{M}' are available, one can use the subset of models or some other models \mathcal{M}' , to obtain some outputs. Then these outputs from the models \mathcal{M}' can be used to approximate the output-based utilities.

$$\begin{array}{l} \text{UTILITY}(x) \approx \text{UTILITY}(x) \\ \text{with } \mathcal{M} \\ \text{with } \mathcal{M}' \end{array} \tag{10}$$

In our implementation, we take a subset of the original \mathcal{M} , simulating the case where we are willing to compute model outputs for at least a portion of the models. The approach of designing an artificial crowd was previously used by Lalor et al. (2019) to train IRT on sentiment classification and natural language inference tasks.

5 Case Study 1: Machine Translation

As our first case study for budget-efficient human evaluation, we consider machine translation, particularly the setting in the general WMT shared task (Kocmi et al., 2024a). For WMT and similar venues, both source-based and output-based variations come into play sequentially: (1) all source data is collected, (2) an initial subset is created based on just sources, (3) the initial subset is distributed to participants & outputs are collected, (4) automated metrics are computed, (5) the final subset is created based on sources and outputs, (6) the final subset is human-evaluated, (7) the model ranking is produced.

We first describe the experimental setup by which we evaluate our data selection methods. We

then present the results for the simpler of the two scenarios: output-based selection, considering both segment-level translation and document-level translation (Section 5.1). Then, we explore the case considering annotation cost of individual items and its impact on subset selection (Section 5.2). We conclude with the results for the source-based data selection task (Section 5.3). In our results, we focus on selecting data subsets of sizes ranging from 5% to 50% of the original testset.

In order to satisfy the positivity constraints of item utility functions (Section 2), we shift all the utilities to be positive by a constant. In our initial experiments, we assume a constant human evaluation cost for each item.

Data setup. For our experiments, we use the human annotation data from publicly available past WMT campaigns. We include only language pairs and WMT years with at least 500 human annotations per model. As a result, we end with 33 campaigns with 31k source items and 395k translations. Out of these, we use the 9 language pairs from WMT 2023 which contain MetricX-23 (Cs+Uk, De+En, Ja+En, Zh+En, En+Cs, En+De, En+Ja, En+Zh, He+En), unless specified otherwise.

5.1 Output-based selection for WMT

The results for output-based selection (i.e., when models and metric scores are known) are shown in Figure 3. We evaluated the efficacy of our proposed methods using rank correlation and cluster count (Section 2.1). We compare these methods with random selection, which has been reported to be a strong baseline in previous works (Rodriguez et al., 2021; Park et al., 2022; Polo et al., 2024).²

We find that approaches based on metrics moments surpass the random baseline with a slight margin when measured by rank correlation, and by a large margin (>1 extra cluster) when measured by cluster count. The IRT model performs slightly better than the metrics moment approaches, and metric consistency performs best. The results across individual WMT years and languages are shown in the Appendix Table 10.

Balancing domains. Items in the WMT data come from multiple distinct domains, such as news, social, or chat. The substantial increase in cluster

²Central limit theorem shows that the mean of observed independent random variables (item scores) converges to the true mean (model score average) at least as fast as $x^{-1/2}$ converges to 0.



Figure 3: Main **output-based results for machine translation** (WMT23). Rank correlation (left) and cluster count (right) for random and our output-based subset selection methods: Metrics moments (MetricAvg, MetricVar), Consistency (MetricCons) and Item Response Theory (DiffDisc) based on MetricX-23, and output diversity (Diversity). Numbers in the legend show average Rank correlation/Cluster count across all data proportions.

count might appear to result from selecting from a single domain. Consequently, the test set might capture fewer aspects of model performance, resulting in more statistical clusters. To test this, we enforce all domains having the same number of selected items. The results in Appendix Table 7 show that even with this balancing, our methods perform much better than random selection for both ranking correlation and clustering.

Selecting document-level items. Recently, MT evaluation has shifted to document-level translation evaluations (Kocmi et al., 2024a, inter alia) where entire document translations are now evaluated. We extend our methods to this setting by defining the utility of a document as the average of various sentence-level utilities defined in this paper. We now consider entire documents to be items where the cost and utility of the document are the sum of costs of evaluating sentence-level translations in the document and average of sentence-level utilities, respectively. The results in Appendix Table 4 mimic the main results for item-level selection: Metric consistency and variance perform the best while metric average the poorest. Overall, they all perform better than random.

5.2 Accounting for human annotation cost in subset selection

Human evaluation costs are usually determined by the total human evaluation time. Furthermore, different annotation items take different times to annotate due to their lengths. For example, the machine translation evaluation campaign of Kocmi et al. (2024c) contains very short 3-word items that take less than 10 seconds to annotate but also multisentence items that take more than 3 minutes to annotate each.

As the human evaluation time is not known during the subset selection stage, we use source length as a rough measure for human evaluation time. Kocmi et al. (2024c) provide a human evaluation of machine translation dataset with evaluation times. We use this data to approximate human evaluation time as a linear function of source length. $\hat{t}(x) = 0.15 \cdot |x| + 33.7$. This approximation is weakly correlated with the real human evaluation time (ρ =0.24). Furthermore, items with the highest difficulty correlate positively (ρ =0.33) with human evaluation time; a more difficult item usually has a higher annotation cost compared to a random item. Selecting the most difficult items to human evaluate may thus be suboptimal.

Taking costs into account, we approximate the solution to Equation (2) with integer linear programming. The results in Table 1 show that costaware subset selection can lead to very high rank correlation or cluster count even with a limited budget. The important prerequisite for cost-aware subset selection is an estimate on the human evaluation time.

5.3 Source-based selection for WMT

We now describe the source-based selection case where we do not yet know model outputs for \mathcal{X} . The first approach is to distill the item utilities with a source-based predictor.



Figure 4: Main **source-based results for machine translation** (WMT23). We compare rank correlation (left) and cluster count (right) for random subset selection (same as Figure 3), and source-based subset selection methods: estimators of Metrics moments (MetricAvg^{src}, MetricVar^{src}), Consistency (MetricCons^{src}), output diversity, and Item Response Theory-based parameters (DiffDisc^{src}). Numbers in legend similarly show averages across all points.

Method	Correlation	Clusters
Random	96.3% _{+4.0%}	3.06+0.82
MetricAvg	96.7% _{+3.8%}	3.08-0.08
MetricVar	97.0%+3.2%	3.33+0.11
MetricCons	96.6% _{+2.4%}	3.19-0.05
Diversity	96.6%+2.6%	3.33+0.34
Diff.×Disc.	96.8%+3.0%	3.23+0.37

Table 1: Results for methods with cost-aware subset selection with integer linear programming (Equation 2). The sizes of the resulting subsets can differ but have the same cost. Numbers in subscripts indicate improvements against cost-unaware selection in Figure 3. Results are averaged across languages and subset sizes.

We train all item utility estimator models only up to WMT22 to avoid contamination of the evaluation on WMT23. Figure 4 shows the source-based selection results, which can be applied to unseen items without model outputs, unlike output-based selection. Although the source-based estimation of metric moments performs worse than in outputbased selection (Figure 3), it still outperforms random selection. Diversity^{src}, which predicts output diversity, and Diff.^{diff.}×Disc.^{src}, which predict the latent IRT parameters, perform the best and on par with their output-based selection versions.

For the artificial crowd approach, we assume that we know the model output on \mathcal{X} for at least some models. On the other hand, this does not require past evaluation data. Appendix Table 5 shows that the previous distillation methods for source-based selection perform on par with the artificial crowd approach. The choice whether to use an artificial crowd or item utility predictors for

the source-based subset selection case then depends on availability of at least some model outputs or past evaluation data on which an estimator can be trained.

5.4 Subset selection cuts costs substantially

At first glance, the improvements over random selection in both scenarios appear minor. Although previous work on active learning and subset selection agrees that random sampling is a strong baseline (Wei et al., 2015; Rodriguez et al., 2021; Park et al., 2022; Polo et al., 2024), the improvements shown do matter, when applied at a larger scale. To show this, we ask: *What budget would we need to arrive at the same evaluation result as random sampling with budget B?* The answer can be obtained with the following formula:

$$\hat{C} = \min \left\{ C | \operatorname{Eval}(\mathcal{Y}_{\leq C}^{\dagger}) \ge \operatorname{Eval}(\mathcal{Y}_{\leq B}^{R}) \right\} \quad (11)$$

where Eval is either rank correlation or cluster count, $\mathcal{Y}_{\leq C}^{\dagger}$ is a subset within budget C that is comparable to a random subset $\mathcal{Y}_{\leq B}^{R}$ of budget B.

In Table 2, we quantify the cost-efficiency of our subset selection approach by reporting the proportion of number of datapoints in our subset that achieves the same evaluation result as random sampling, \hat{C}/B . We find that even our simplest variance-based utility approach achieves the same or better rank correlation and cluster count with only 32.0% of the data as random sampling on the machine translation evaluation task. This means, that to achieve the same human evaluation quality, we need to now pay for evaluation of only half the

Method	Needed to match Correlation	Needed to match Clusters
Random	100.0%	100.0%
MetricAvg	97.8%	61.0%
MetricVar	86.8%	32.0%
MetricCons	87.4%	42.7%
Diversity	71.7%	56.4%
Diff.×Disc.	62.0%	44.7%
MetricAvg ^{src}	112.9%	67.5%
Metric Var ^{src}	124.8%	71.5%
MetricCons ^{src}	95.7%	76.1%
Diversity ^{src}	73.6%	60.4%
Diff. ^{src} ×Disc. ^{src}	91.1%	53.1%

Table 2: Proportion of data needed to reach the same evaluation result for WMT23 (rank correlation or cluster count) as random subset selection. Averaged across budgets from Figures 3 and 4.

test data. At the scale of industrial evaluation of NLP models, which gets bigger each year, these economical implications are substantial.

5.5 Importance of a good automated metric

In our main results for machine translation (Figure 3), we used MetricX-23, which is one of the best automated machine translation metrics (Freitag et al., 2023). *What happens with a weaker metric?* In Figure 5, we show the relationship between evaluation subset selection performance and quality of the metric, as measured by item-level correlations with human evaluations. We show results across the 25 metrics available in the WMT metrics shared task (Freitag et al., 2021, 2022, 2023).

MetricX-23 is a pretrained supervised metric, requiring human evaluation data for training. BERTscore (Zhang et al., 2020) is also a pretrained metric, based on a language model, but is not finetuned on human data. Lastly, BLEU (Papineni et al., 2002) and ChrF (Popović, 2015) are stringmatching metrics that do not need any pretraining or data. While the string-matching metrics do not provide enough signal for robust evaluation subset selection, pretrained (but not supervised) metrics are sufficient, because they correlate well enough with evaluations. However, combining multiple automated metrics into a single item utility provides no improvements, as shown in Appendix Table 8.

6 Case Study 2: Summarization

We now show the applicability of our methods to another natural language generation task, summarization. The summarization task is more openended than machine translation, making the evalua-



Figure 5: Proportion of data needed to reach the same evaluation result for WMT23 (rank correlation or cluster count) with respect to the automated metric used for informing the selection. The automated metric correlation quality (x-axis) is measured as Pearson correlation against human scores. Each value is a separate dataset and metric, averaged in bins 0.1, 0.2, 0.3, 0.4, 0.5. Even though random and diversity methods are invariant to the metrics, they are affected by the particular datasets characteristics (e.g. quality of human annotations), which differ across bins.

Method	Needed to match Correlation	Needed to match Clusters
Random	100.0%	100.0%
MetricAvg	75.4%	87.1%
MetricVar	61.5%	76.6%
MetricCons	59.9%	81.9%
Diversity	64.2%	62.5%
DiffDisc	117.7%	78.0%

Table 3: Proportion of data needed to reach the sameevaluation result on SummEval as random subset selection.Averaged across budgets from Figure 6.

tion even more difficult. In this section, we explore budget-efficient subset selection for both human evaluation and cheaper, yet still not free, large language model-based evaluation.

Setup. We use SummEval (Fabbri et al., 2021) which contains 17 human-evaluated models on 100 items. The human evaluation of each model output, in contrast to machine translation, is not a single scalar meaning overall quality. Instead, humans evaluate the output in four dimensions: *relevance*, *coherence*, *consistency*, and *fluency*. We use the subset selected for evaluation on each quality dimension independently, and then aggregate the final results. We choose G-Eval (Liu et al., 2023), an LLM-based evaluator, as it has a high correlation between metric predictions and human scores.



Figure 6: Main **output-based results for SummEval** averaged across relevance, coherence, consistency, fluency, and their sum. Rank correlation (left) and cluster count (right) for random subset selection and our output-based subset selection methods: metrics moments (MetricAvg, MetricVar), consistency (MetricCons) and Item Response Theory (DiffDisc) based on G-Eval, and output diversity. Numbers in legend show averages across all points.

Results. The results of output-based data selection for summarization are shown in Figure 6. We do not include source-based selection because that requires training data, which are not available for a dataset this small. In most cases, the methods outperform the random selection. Similarly to machine translation, the metric average is not consistently very good. Metric variance, consistency, and diversity are again much stronger. The results in Appendix Table 3 show that we only need $\sim 70\%$ of the budget to obtain the same evaluation result as random selection when using metric consistency selection. We show the results across the individual evaluation dimensions (Relevance, Coherence, Consistency, Fluency) in Appendix Table 11.

Even when using the LLM-based metric for final evaluation, it can become expensive at larger scale. Budget-efficient subset selection can also make even this type of evaluation more economical. The results in Appendix Table 9 show that we can again select only $\sim 70\%$ of the test set to be LLM evaluated to reach the same evaluation result as random selection.

7 Related Work

In this section we provide context for natural language generation evaluation and an overview of previous works on budget-efficient evaluation.

NLG evaluation. Machine translation is one of the most important NLG tasks, and the progress of MT is tracked annually in various WMT evaluations (Kocmi et al., 2024a; Nakazawa and Goto, 2024; Ahmad et al., 2024). As the output of NLG models is a string in natural language, its quality cannot be easily assessed by comparing to a

ground truth. For this reason, robust NLG evaluation eventually relies on human annotators. However, human evaluation process is not straightforward either, ranging from assigning a single score (Graham et al., 2015; Kocmi et al., 2022) to marking error spans (Lommel et al., 2014; Kocmi et al., 2024c). Typically, the output of this process is a single number per input+output, which is used to determine the final model ranking.

At scale, such as during model development, human evaluation is too costly. For this reason, automated metrics have been developed, starting from text-matching approaches (Papineni et al., 2002; Popović, 2015), progressing to learned metrics (Rei et al., 2020; Juraska et al., 2024). Although learned metrics correlate more strongly with humans (Freitag et al., 2022), they also have unexpected problems (Zouhar et al., 2024b,a; Falcão et al., 2024). Like human annotations, automated metrics also produce a single number for each input+output, evaluating the quality of the NLG model's output.

Budget-efficient evaluation. Previous works attempt to find the most informative or diverse evaluation items, primarily by comparison to a groundtruth answer. In contrast, our goal is to reduce the number of *human* evaluations, while still arriving at the same result, such as model ranking.

To select the most informative items for evaluation, Rodriguez et al. (2021) and Polo et al. (2024) use Item Response Theory (IRT, Santor and Ramsay, 1998), a framework for the creation of test sets for students in classrooms. However, these methods require ground-truth answers to which the model output is compared with a binary outcome. For natural language generation tasks, there is no single ground-truth answer, and the model output evaluation is a continuous score.

Ni et al. (2024) supersample items in an evaluation subset to mimic the distribution throughout the test set. The subset is constructed based on most difficult items, which again requires a comparison to a ground truth and a previous evaluation of some models on the whole test set. For the evaluation of classification models, Vivek et al. (2024) find anchor points that describe the outcome of the evaluation on the whole test set. Feng et al. (2024) choose items that have the least similar model output to be evaluated via pairwise comparisons, which is not applicable to direct model output evaluation.

Many previous works require that at least a few models have already been evaluated on the entire set of items from which we select a subset (Rodriguez et al., 2021; Feng et al., 2024; Ruan et al., 2024). This makes the methods not applicable for source-based selection, where either the evaluation set is too large to be processed or where the to-beevaluated models are not known in advance.

Subset selection via batched active learning (Park et al., 2022; Ruan et al., 2024; Li et al., 2024) is an iterative selection process. In practice, human evaluations are usually run all at once or outsourced to third party with annotators working asynchronously. Therefore, active learning is possible only when the annotation process is tightly controlled. In contrast, our item utilities can be simply used to sort the items from most to least informative and annotators can then stop ad-hoc when the budget is reached.

Zouhar et al. (2024c) already human-evaluate only a subset of the whole test set by skipping items where an automated metrics reports no errors. However, this subset selection is ad-hoc and without any control of the subset size.

To our knowledge, no prior work has studied subset selection for evaluation where the item evaluation cost is taken into account. See Appendix Table 12 for high-level comparison to prior work.

8 Conclusion and Key Takeaways

We formalize the task of test set subset selection with the goal of selecting a subset of the test set for efficient human evaluation. We explore two common variants of this task: source-based selection (no model outputs available), and output-based selection (outputs and automated metrics available). We present several methods based on metric variance, consistency, and diversity; and show that they outperform the dominantly used random selection approach for machine translation (Section 5) and summarization evaluations (Section 6). On the other hand, the simple heuristic of using difficulty estimate by prioritizing items with lowest automated metric scores does not lead to large improvements and can be counterproductive as it prioritizes costly-to-annotate items. All our methods are implemented in the subset2evaluate library with pre-trained item utility estimators ready to use for subset selection in machine translation.

Takeaways. Based on the analysis in this paper, we offer the following advice to NLG researchers to select a subset of data for human evaluators.

- If model outputs and reliable metrics are available, use metric variance or metric consistency.
- If model outputs are available but a reliable metric is not available, use output diversity.
- If model outputs are not available but historical data are available, use the diversity^{src} estimation.
- If only some model outputs are available, use artificial crowd with metric variance.

Limitations. A key limitation of our approach is the potential bias of automated metrics and artificial crowd selection. Automated metrics may already have been used to inform evaluation procedures, although they are misaligned with the final human judgments (Kocmi et al., 2024b,a). Data selection for human evaluation would make it harder to catch these biases. To illustrate this issue, consider a model that underperforms on specific types of item that is not detected by the automated metric. As these items are estimated to not be faulty, they are not selected for human evaluation. This issue primarily arises when using expected metric averages for item selection, although similar challenges could occur with variance- or discrimination-based methods. Section 5.5 shows that the performance of our methods directly corresponds to the alignment between automated metrics and human judgments. Thus, our methods would continue to benefit from future improvements in automated metrics.

Ethical considerations. We reuse existing data from WMT and SummEval and do not employ our own annotators. In the context of automatization and job security, our work aims not to substitute human work but to make sure that the effort is not wasted on annotating less informative items, ultimately making the work more meaningful.

References

- Ibrahim Said Ahmad, Antonios Anastasopoulos, Ondřej Bojar, Claudia Borg, Marine Carpuat, Roldano Cattoni, Mauro Cettolo, William Chen, Qianqian Dong, Marcello Federico, Barry Haddow, Dávid Javorský, Mateusz Krubiński, Tsz Kin Lam, Xutai Ma, Prashant Mathur, Evgeny Matusov, Chandresh Maurya, John McCrae, Kenton Murray, Satoshi Nakamura, Matteo Negri, Jan Niehues, Xing Niu, Atul Kr. Ojha, John Ortega, Sara Papi, Peter Polák, Adam Pospíšil, Pavel Pecina, Elizabeth Salesky, Nivedita Sethiya, Balaram Sarkar, Jiatong Shi, Claytone Sikasote, Matthias Sperber, Sebastian Stüker, Katsuhito Sudoh, Brian Thompson, Alex Waibel, Shinji Watanabe, Patrick Wilken, Petr Zemánek, and Rodolfo Zevallos. 2024. Findings of the IWSLT 2024 evaluation campaign. In Proceedings of the 21st International Conference on Spoken Language Translation (IWSLT 2024), 1-11, Bangkok, Thailand (in-person and online). Association for Computational Linguistics.
- Luca Benedetto, Andrea Cappelli, Roberto Turrin, and Paolo Cremonesi. 2020. R2DE: a NLP approach to estimating IRT parameters of newly generated questions. In *Proceedings of the tenth international conference on learning analytics & knowledge*, 412–421.
- Matthew Byrd and Shashank Srivastava. 2022. Predicting difficulty and discrimination of natural language questions. In Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers), 119–130. Association for Computational Linguistics.
- Alexis Conneau, Kartikay Khandelwal, Naman Goyal, Vishrav Chaudhary, Guillaume Wenzek, Francisco Guzmán, Edouard Grave, Myle Ott, Luke Zettlemoyer, and Veselin Stoyanov. 2020. Unsupervised cross-lingual representation learning at scale. In Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, 8440–8451. Association for Computational Linguistics.
- Shachar Don-Yehiya, Leshem Choshen, and Omri Abend. 2022. PreQuEL: Quality estimation of machine translation outputs in advance. In *Proceedings* of the 2022 Conference on Empirical Methods in Natural Language Processing, 11170–11183. Association for Computational Linguistics.
- Alexander R. Fabbri, Wojciech Kryściński, Bryan Mc-Cann, Caiming Xiong, Richard Socher, and Dragomir Radev. 2021. SummEval: Re-evaluating summarization evaluation. *Transactions of the Association for Computational Linguistics*, 9:391–409.
- Júlia Falcão, Claudia Borg, Nora Aranberri, and Kurt Abela. 2024. COMET for low-resource machine translation evaluation: A case study of English-Maltese and Spanish-Basque. In *Proceedings of the* 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024), 3553–3565, Torino, Italia. ELRA and ICCL.

- Kehua Feng, Keyan Ding, Kede Ma, Zhihua Wang, Qiang Zhang, and Huajun Chen. 2024. Sampleefficient human evaluation of large language models via maximum discrepancy competition.
- Markus Freitag, Nitika Mathur, Chi-kiu Lo, Eleftherios Avramidis, Ricardo Rei, Brian Thompson, Tom Kocmi, Frederic Blain, Daniel Deutsch, Craig Stewart, Chrysoula Zerva, Sheila Castilho, Alon Lavie, and George Foster. 2023. Results of WMT23 metrics shared task: Metrics might be guilty but references are not innocent. In *Proceedings of the Eighth Conference on Machine Translation*, 578–628. Association for Computational Linguistics.
- Markus Freitag, Ricardo Rei, Nitika Mathur, Chi-kiu Lo, Craig Stewart, Eleftherios Avramidis, Tom Kocmi, George Foster, Alon Lavie, and André F. T. Martins. 2022. Results of WMT22 metrics shared task: Stop using BLEU – neural metrics are better and more robust. In *Proceedings of the Seventh Conference on Machine Translation (WMT)*, 46–68. Association for Computational Linguistics.
- Markus Freitag, Ricardo Rei, Nitika Mathur, Chi-kiu Lo, Craig Stewart, George Foster, Alon Lavie, and Ondřej Bojar. 2021. Results of the WMT21 metrics shared task: Evaluating metrics with expert-based human evaluations on TED and news domain. In *Proceedings of the Sixth Conference on Machine Translation*, 733–774. Association for Computational Linguistics.
- Yang Gao, Wei Zhao, and Steffen Eger. 2020. SUPERT: Towards new frontiers in unsupervised evaluation metrics for multi-document summarization. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, 1347–1354. Association for Computational Linguistics.
- Yvette Graham, Timothy Baldwin, and Nitika Mathur. 2015. Accurate evaluation of segment-level machine translation metrics. In Proceedings of the 2015 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, 1183–1191. Association for Computational Linguistics.
- Nuno M. Guerreiro, Ricardo Rei, Daan van Stigt, Luisa Coheur, Pierre Colombo, and André F. T. Martins. 2023. xcomet: Transparent machine translation evaluation through fine-grained error detection.
- Q Huangfu and JAJ Hall. 2018. Parallelizing the dual revised simplex method. *Mathematical Programming Computation*, 10(1):119–142.
- Juraj Juraska, Daniel Deutsch, Mara Finkelstein, and Markus Freitag. 2024. Metricx-24: The google submission to the wmt 2024 metrics shared task.
- Richard M Karp, Raymond E Miller, and James W Thatcher. 1975. Reducibility among combinatorial problems. *Journal of Symbolic Logic*, 40(4).

- Tom Kocmi, Eleftherios Avramidis, Rachel Bawden, Ondřej Bojar, Anton Dvorkovich, Christian Federmann, Mark Fishel, Markus Freitag, Thamme Gowda, Roman Grundkiewicz, Barry Haddow, Marzena Karpinska, Philipp Koehn, Benjamin Marie, Christof Monz, Kenton Murray, Masaaki Nagata, Martin Popel, Maja Popović, Mariya Shmatova, Steinthór Steingrímsson, and Vilém Zouhar. 2024a. Findings of the WMT24 general machine translation shared task: The LLM era is here but MT is not solved yet. In Proceedings of the Ninth Conference on Machine Translation, 1–46, Miami, Florida, USA. Association for Computational Linguistics.
- Tom Kocmi, Eleftherios Avramidis, Rachel Bawden, Ondrej Bojar, Anton Dvorkovich, Christian Federmann, Mark Fishel, Markus Freitag, Thamme Gowda, Roman Grundkiewicz, Barry Haddow, Marzena Karpinska, Philipp Koehn, Benjamin Marie, Kenton Murray, Masaaki Nagata, Martin Popel, Maja Popovic, Mariya Shmatova, Steinþór Steingrímsson, and Vilém Zouhar. 2024b. Preliminary WMT24 ranking of general mt systems and Ilms.
- Tom Kocmi, Eleftherios Avramidis, Rachel Bawden, Ondřej Bojar, Anton Dvorkovich, Christian Federmann, Mark Fishel, Markus Freitag, Thamme Gowda, Roman Grundkiewicz, Barry Haddow, Philipp Koehn, Benjamin Marie, Christof Monz, Makoto Morishita, Kenton Murray, Makoto Nagata, Toshiaki Nakazawa, Martin Popel, Maja Popović, and Mariya Shmatova. 2023. Findings of the 2023 conference on machine translation (WMT23): LLMs are here but not quite there yet. In *Proceedings of the Eighth Conference on Machine Translation*, 1–42. Association for Computational Linguistics.
- Tom Kocmi, Rachel Bawden, Ondřej Bojar, Anton Dvorkovich, Christian Federmann, Mark Fishel, Thamme Gowda, Yvette Graham, Roman Grundkiewicz, Barry Haddow, Rebecca Knowles, Philipp Koehn, Christof Monz, Makoto Morishita, Masaaki Nagata, Toshiaki Nakazawa, Michal Novák, Martin Popel, and Maja Popović. 2022. Findings of the 2022 conference on machine translation (WMT22). In Proceedings of the Seventh Conference on Machine Translation (WMT), 1–45. Association for Computational Linguistics.
- Tom Kocmi, Vilém Zouhar, Eleftherios Avramidis, Roman Grundkiewicz, Marzena Karpinska, Maja Popović, Mrinmaya Sachan, and Mariya Shmatova. 2024c. Error span annotation: A balanced approach for human evaluation of machine translation. In *Proceedings of the Ninth Conference on Machine Translation*, 1440–1453. Association for Computational Linguistics.
- John Patrick Lalor and Pedro Rodriguez. 2023. py-irt: A scalable item response theory library for python. *INFORMS Journal on Computing*, 35(1):5-13.
- John Patrick Lalor, Hao Wu, and Hong Yu. 2019. Learning latent parameters without human response patterns: Item response theory with artificial crowds. In

Proceedings of the Conference on Empirical Methods in Natural Language Processing. Conference on Empirical Methods in Natural Language Processing, volume 2019, 4240. NIH Public Access.

- Yang Li, Jie Ma, Miguel Ballesteros, Yassine Benajiba, and Graham Horwood. 2024. Active evaluation acquisition for efficient llm benchmarking.
- Yang Liu, Dan Iter, Yichong Xu, Shuohang Wang, Ruochen Xu, and Chenguang Zhu. 2023. G-eval: NLG evaluation using gpt-4 with better human alignment. In Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, 2511–2522. Association for Computational Linguistics.
- Arle Lommel, Hans Uszkoreit, and Aljoscha Burchardt. 2014. Multidimensional quality metrics (MQM): A framework for declaring and describing translation quality metrics. *Tradumàtica*, 12:0455–463.
- Toshiaki Nakazawa and Isao Goto, editors. 2024. Proceedings of the Eleventh Workshop on Asian Translation (WAT 2024). Association for Computational Linguistics.
- Jinjie Ni, Fuzhao Xue, Xiang Yue, Yuntian Deng, Mahir Shah, Kabir Jain, Graham Neubig, and Yang You. 2024. MixEval: Deriving wisdom of the crowd from llm benchmark mixtures.
- Yvonnick Noel and Bruno Dauvier. 2007. A beta item response model for continuous bounded responses. *Applied Psychological Measurement*, 31(1):47–73.
- Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the* 40th Annual Meeting of the Association for Computational Linguistics, 311–318. Association for Computational Linguistics.
- Dongmin Park, Dimitris Papailiopoulos, and Kangwook Lee. 2022. Active learning is a strong baseline for data subset selection. In *Has it Trained Yet? NeurIPS* 2022 Workshop.
- Stefano Perrella, Lorenzo Proietti, Alessandro Scirè, Edoardo Barba, and Roberto Navigli. 2024. Guardians of the machine translation metaevaluation: Sentinel metrics fall in! In Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), 16216–16244. Association for Computational Linguistics.
- Felipe Maia Polo, Lucas Weber, Leshem Choshen, Yuekai Sun, Gongjun Xu, and Mikhail Yurochkin. 2024. tinyBenchmarks: evaluating LLMs with fewer examples.
- Maja Popović. 2015. chrF: character n-gram F-score for automatic MT evaluation. In Proceedings of the Tenth Workshop on Statistical Machine Translation, 392–395. Association for Computational Linguistics.

- Ricardo Rei, Craig Stewart, Ana C Farinha, and Alon Lavie. 2020. COMET: A neural framework for MT evaluation. In *Proceedings of the 2020 Conference* on Empirical Methods in Natural Language Processing (EMNLP), 2685–2702. Association for Computational Linguistics.
- Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence embeddings using Siamese BERTnetworks. In Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), 3982– 3992. Association for Computational Linguistics.
- Pedro Rodriguez, Joe Barrow, Alexander Miserlis Hoyle, John P. Lalor, Robin Jia, and Jordan Boyd-Graber. 2021. Evaluation examples are not equally informative: How should that change NLP leaderboards? In Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers), 4486–4503. Association for Computational Linguistics.
- Jie Ruan, Xiao Pu, Mingqi Gao, Xiaojun Wan, and Yuesheng Zhu. 2024. Better than random: Reliable NLG human evaluation with constrained active sampling.
- Darcy A Santor and James O Ramsay. 1998. Progress in the technology of measurement: Applications of item response models. *Psychological assessment*, 10(4):345.
- Rajan Vivek, Kawin Ethayarajh, Diyi Yang, and Douwe Kiela. 2024. Anchor points: Benchmarking models with much fewer examples. In Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 1: Long Papers), 1576–1601. Association for Computational Linguistics.
- Kai Wei, Rishabh Iyer, and Jeff Bilmes. 2015. Submodularity in data subset selection and active learning. In Proceedings of the 32nd International Conference on Machine Learning, volume 37 of Proceedings of Machine Learning Research, 1954–1963, Lille, France. PMLR.
- Mike Wu, Richard L. Davis, Benjamin W. Domingue, Chris Piech, and Noah Goodman. 2020. Variational item response theory: Fast, accurate, and expressive.
- Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q. Weinberger, and Yoav Artzi. 2020. BERTScore: Evaluating text generation with BERT.
- Kaitlyn Zhou, Su Lin Blodgett, Adam Trischler, Hal Daumé III, Kaheer Suleman, and Alexandra Olteanu. 2022. Deconstructing NLG evaluation: Evaluation practices, assumptions, and their implications. In *Proceedings of the 2022 Conference of the North*

American Chapter of the Association for Computational Linguistics: Human Language Technologies, 314–324. Association for Computational Linguistics.

- Vilém Zouhar, Pinzhen Chen, Tsz Kin Lam, Nikita Moghe, and Barry Haddow. 2024a. Pitfalls and outlooks in using COMET. In Proceedings of the Ninth Conference on Machine Translation, 1272–1288. Association for Computational Linguistics.
- Vilém Zouhar, Shehzaad Dhuliawala, Wangchunshu Zhou, Nico Daheim, Tom Kocmi, Yuchen Eleanor Jiang, and Mrinmaya Sachan. 2023. Poor man's quality estimation: Predicting reference-based MT metrics without the reference. In *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*, 1311–1325. Association for Computational Linguistics.
- Vilém Zouhar, Shuoyang Ding, Anna Currey, Tatyana Badeka, Jenyuan Wang, and Brian Thompson. 2024b. Fine-tuned machine translation metrics struggle in unseen domains. In Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers), 488–500. Association for Computational Linguistics.
- Vilém Zouhar, Tom Kocmi, and Mrinmaya Sachan. 2024c. AI-assisted human evaluation of machine translation.

Inputs: Models \mathcal{M} **Output**: Number of clusters |C|Add a system to the same cluster if it is not statistically distinguishable from the previous cluster.

1: $\mathcal{M} \leftarrow \text{Sort}(\mathcal{M}, \lambda m : -\text{Avg}(m))$
2: $C \leftarrow \langle \langle S_0 \rangle \rangle$
3: for $m \in \mathcal{M}_{>1}$
4: if WILCOXON $(C_{-1,-1}, m) < 0.05$
5: $C.APPEND(\langle m \rangle)$
6: else
7: C_{-1} .APPEND (m)
8: return $ C $

Algorithm 1: Computation of number of clusters given an evaluated set of items.

Method	Correlation	Clusters
Random	83.6%	2.67
MetricAvg	86.6%	3.04
MetricVar	88.8%	3.10
MetricCons	89.6%	3.23
Diversity	87.6%	2.86
DiffDisc	86.7%	3.20

Table 4: Document-level subset selection. The item utilities are averaged to create document-level utilities out of which a subset is chosen. Results are averaged across languages and subset sizes.

Method	Correlation Cluste			
Random	91.5%	2.44		
Metric Var ^{src}	91.7%	2.75		
MetricAvg ^{src}	90.1%	2.86		
MetricCons ^{src}	91.5%	2.90		
Diversity ^{src}	92.3%	2.96		
DiffDisc ^{src}	91.8%	3.17		
MetricVar	92.8%	2.91		
MetricAvg	92.4%	3.22		
MetricCons	91.5%	2.67		
Diversity	91.1%	2.73		
DiffDisc	90.9%	2.63		

Table 5: Output-based selection methods applied to source-based selection using artificial crowd of size of 4 models, randomly sampled from \mathcal{M} . The results differ from source-based selection (Figure 4) because the selection is evaluated on $\mathcal{M} \setminus \mathcal{M}'$. Averaged across languages and subset sizes.

Encoder	XLM-RoBERTa (Conneau et al., 2020)
Head	$768 \times 2048 \times 1024 \times 1$
Optimizer	Adam (lr= 1.5×10^{-5}) weight decay (0.95)
Epochs	4 (encoder frozen for first 0.3)
Batch size	16
Training data	50k (before WMT 2023)

Table 6: Implementation details of our item utility distillation models used for machine translation subset selection (WMT). The models are based on the COMET (Rei et al., 2020) quality estimation for machine translation framework and dubbed COMET^{src}. The item utilities are computed with respect to human scores and not automated metrics, since they are available.

Method	Correlation	Clusters
Random	91.8%	2.47
MetricAvg	92.9%	3.01
MetricVar	93.4%	3.06
MetricCons	94.6%	2.99
Diversity	94.4%	2.61
DiffDisc	91.7%	2.86

Table 7: Subset selection with balanced domains. Item utilities are sorted within domains \mathcal{D} and top- $^B/|\mathcal{D}|$ is taken from each domain for particular budget *B*. Results are averaged across languages and subset sizes.



Figure 7: Results for selection with clustering. After running k-means with number of cluster equal to the budget in embedding space provided by multilingual MiniLM (Reimers and Gurevych, 2019), the items closest to the center are chosen for \mathcal{Y} . The cluster count is lower because we intentionally choose diverse items.

Method	Correlation	Clusters
MetricVar (M)	93.8%	3.22
MetricVar (X)	94.3%	3.17
MetricVar (M+X)	94.3%	3.32
MetricCons (M)	94.2%	3.24
MetricCons (X)	92.2%	3.01
MetricCons (M+X)	93.1%	3.10
MetricVar (M+X) +MetricCons (M+X)	94.1%	3.38

Table 8: Subset selection with joint utilities on WMT23. The item utility is a product of individual 0-1-normalized utilities based either on MetricX-23 (M) or XCOMET-XL (X, Guerreiro et al., 2023). Results are averaged across languages and subset sizes.



Figure 8: Illustration on how item response theory parameters affect predictions of model success. The parameters are difficulty b_s (shift on x-axis), discriminability a_s (slope), and feasibility c_s (upper bound).

Method	Needed to match Correlation	Needed to match Clusters
Random	100.0%	100.0%
MetricAvg	68.6%	116.4%
MetricVar	91.6%	103.9%
MetricCons	61.4%	84.8%
Diversity	81.5%	104.8%
DiffDisc	63.1%	97.9%

Table 9: Proportion of data needed to reach the same evaluation result on SummEval (rank correlation or cluster count **based on GPT4 evaluation**) as random subset selection. Averaged across budgets from Figure 6. Selectors use Supert (Gao et al., 2020), an unsupervised automated metric for multi-document summarization.

Data	aset	#Models	#Items	Random	MetricAvg	MetricVar	MetricCons	Diversity	DiffDisc
	Cs→Uk	11	1955	94.3%/2.33	91.3%/ 4.00	93.2%/3.50	94.5% /2.60	94.5% /2.90	93.8%/2.00
	En→Cs En→Es	15 13	572 635	91.0%/2.61 89.0%/3.19	89.0%/2.90 93.8%/4.80	90.1%/2.70 90.5%/3.70	92.5%/ 3.10 93.2%/4.00	86.9%/2.20 84.2%/3.90	94.0% /3.00 86.4%/3.20
IT24	En→Hi En→Is	10 10	635 635	86.1%/2.83 97.4%/4.59	89.2%/ 3.50 97.1%/4.80	89.3%/3.10 96.8%/4.60	91.2%/3.50 97.8%/4.80	77.6%/3.30 99.3%/4.90	90.7%/3.30 95.9%/4.60
WN	En→Ja	12	635	74.0%/2.82	66.1%/ 4.20	79.8% /3.30	67.9%/2.90	50.1%/3.00	51.4%/2.80
	En→Ru En→Uk	13	635 635	90.2%/2.36 86.6%/2.60	86.9%/3.10 88.2%/2.90	86.8%/ 3.30 86.7%/2.70	89.9%/2.60 81.3%/2.60	92.9% /2.10 83.3%/2.30	86.9%/2.70 84.7%/2.60
	En→Zh Ja→Zh	12 14	635 560	86.1%/2.48 93.1%/4.45	75.5%/ 3.20 96.4%/5.40	85.0%/2.30 96.1%/5.10	89.8% /2.10 94.7%/4.20	73.5%/3.00 96.3%/4.50	78.3%/2.00 91.1%/3.70
	Cs→Uk	13	1009	91.3%/1.39	89.8%/2.40	90.9%/2.40	97.2%/2.60	94.8%/1.70	93.5%/2.20
~	De→En En→Cs	13 15	509 1098	91.4%/1.78 85 3%/1 54	92.9%/ 3.20 83.4%/2.30	92.4%/2.60 91.5%/1.90	94.6%/2.50 90.9%/1.70	97.1% /3.10 91.2%/1.70	91.1%/2.60 87.8%/2.50
MT2	En→De En→Ja	12 16	549 1098	93.1%/2.25 95.3%/2.61	91.4%/2.60 96.5%/3.20	96.6% /2.80 97.6% /3.70	85.2%/ 3.30 96.0%/3.60	88.9%/2.80 96.1%/2.50	94.5%/2.50
M	En→Zh	15	1098	93.4%/3.54	95.7%/4.60	96.2%/3.60	94.1%/ 5.50 98.2%/3.70	96.6% /3.70	95.9%/4.20
	Ja>En	17	1120	95.1%/2.18	96.9%/2.30	98.1%/3.60	93.6%/2.40	97.3%/2.90	93.5%/2.70
	Zh→En Cs→Uk	15 10	884 819	91.7%/2.30 89.9%/2.50	94.2%/ 3.90 82.8%/2.70	96.4% /3.20 84.1%/3.00	88.2%/3.50 93.8%/3.80	91.4%/3.20 87.0%/2.90	92.1%/2.70 90.1%/3.40
	En→De	15	1315	94.8%/3.42	96.3%/5.10	96.9%/5.30	93.2%/5.00	96.1%/4.30	93.2%/4.10
22	En→Hr En→Ja	13	1107	93.1%/2.88 77.4%/2.05	96.8%/ 4.50 71.6%/2.20	99.2%/4.50 85.2%/ 2.90	89.8% /2.30	87.8%/2.90 75.7%/2.40	94.7%/3.00 83.1%/2.40
LWI	En→Ru En→Uk	15 8	1315 1209	96.7%/4.20 93.8%/1.99	97.1% /6.50 91.7%/2.80	96.3%/5.60 96.7% /3.20	97.1%/6.70 96.2%/2.50	95.9%/4.70 87.1%/2.90	95.5%/5.00 95.2%/ 3.50
5	En→Zh Bu >En	13	1181	75.3%/1.31	71.7%/2.20	89.8% /2.00	76.5%/1.40	67.0%/1.20	86.9%/1.30
	Sah+Ru	10 1 2	1023	100% /2.00	100% /2.00	100% /2.00	100% /2.00	100% /2.00	100% /2.00
	Zh→En En→De	15 13	1875 529	91.3%/3.35 76.1%/1.13	95.5%/4.40 85.9%/1.00	97.7% /4.70 86.5%/ 1.30	95.1%/ 5.10 87.7%/1.30	97.4%/ 5.10 72.0%/1.00	89.4%/4.30 83.2%/1.10
IT21	En→Ru Zh - En	14	512	87.9%/2.91	97.1% /3.20	94.6%/2.90	90.2%/3.20	93.9%/ 3.50	93.9%/2.90
MM	En→Cs	14	529 988	98.3%/5.27	86.2%/2.00 95.5%/6.20	98.9%/ 6.50	70.9%/2.00 99.0%/ 6.50	98.3%/6.20	99.3% /5.40
	En→De En→Is	16 11	527 838	89.6%/1.34 96.5%/5.15	93.7%/ 2.00 89.0%/3.70	93.6%/1.30 98.6% /5.00	96.3% /1.40 95.5%/5.40	92.2%/1.40 95.9%/4.60	93.6%/1.70 96.5%/ 5.50
	En→Ja	15	878	96.3%/2.90	87.9%/3.20	96.2%/ 4.30	97.6% /3.50	83.7%/3.50	96.2%/3.30
	Zh→En	13	650	65.8%/1.07	97.1%/3.10 89.7%/1.00	93.0%/2.90 87.1%/ 1.20	82.8%/1.00	92.3%/2.40 92.0%/1.10	76.7%/ 1.20

Table 10: Individual subset selection results for machine translation evaluation (WMT) measured as "rank correlation/cluster count" averaged over data proportions from 5% to 50%. Bold numbers indicate best in evaluation category (correlation or clusters) within the row. For each dataset for MetricAvg, MetricVar, MetricCons, and DiffDisc, best automated metric is chosen.

Dimension	#Mode	ls #Iten	ns Random	MetricAvg	MetricVar	MetricCons	Diversity	DiffDisc
Relevance	16	100	97.0%/1.87	97.5%/2.20	98.1% /2.00	97.4%/ 2.60	96.3%/2.50	94.5%/2.58
Coherence	16	100	96.9%/3.14	97.8%/3.30	96.5%/ 4.10	96.8%/3.40	97.0%/ 4.10	97.2%/3.22
Consistency	16	100	91.9%/3.14	95.2%/3.20	94.5%/2.90	94.4%/2.60	93.7%/3.00	93.7%/2.60
Fluency	16	100	91.2%/2.32	97.0%/2.00	94.7%/ 3.00	96.4%/2.50	92.9%/2.30	97.1%/2.14
Sum	16	100	97.6%/3.64	97.9%/3.90	98.1% /3.90	97.7%/ 4.40	98.0%/4.00	95.5%/3.54

Table 11: Subset selection results for summarization evaluation (SummEval) across different dimensions, measured as "rank correlation/cluster count" averaged over data proportions from 25% to 75%. Bold numbers indicate best in evaluation category (correlation or clusters) within the row. MetricAvg, MetricVar, MetricCons, and DiffDisc use G-Eval as the automated metric.

Work	Human-evaluation	Scores	Output-based	Source-based	Cost-aware
subset2evaluate (ours)	🛷 yes	🛷 continuous	🛷 yes	🛷 yes	🛷 yes
Rodriguez et al. (2021)	🗙 ground-truth	🗙 binary	🖌 yes	🗙 no	🗙 no
Ni et al. (2024) MixEval	🗙 ground-truth	🗙 binary	💥 no	🛷 yes	🗙 no
Polo et al. (2024) tinyBenchmarks	🗙 ground-truth	🧪 continuous*	🖌 yes	🧪 partly	🗙 no
Vivek et al. (2024) Anchor Points	🗙 ground-truth	🗙 binary	🖌 yes	🛷 yes	🗙 no
Feng et al. (2024)	🛷 yes	🗙 pairwise	🖌 yes	🗙 no	🗙 no
Ruan et al. (2024)	🖌 yes	< continuous	🧪 yes, iterative	🗙 no	🗙 no

Table 12: Comparison to prior work on budget-efficient evaluation subset selection. Ground truth: needs comparison to ground truth, scores: binary or continuous outcomes, or pairwise comparisons, output/source-based: methods for the two subset selection variants, cost-aware: can take evaluation cost into account.