Data Overvaluation Attack and Truthful Data Valuation

¹Shuyuan Zheng^{*}, ²Sudong Cai, ^{1,4}Chuan Xiao, ³Yang Cao, ²Jianbin Qin, ⁵Masatoshi Yoshikawa, ¹Makoto Onizuka

¹Osaka University, ²Beijing Institute of Technology, ³Institute of Science Tokyo, ⁴Nagoya University, ⁵Osaka Seikei University

Abstract

In collaborative machine learning, data valuation, i.e., evaluating the contribution of each client' data to the machine learning model, has become a critical task for incentivizing and selecting positive data contributions. However, existing studies often assume that clients engage in data valuation truthfully, overlooking the practical motivation for clients to exaggerate their contributions. To unlock this threat, this paper introduces the first data overvaluation attack, enabling strategic clients to have their data significantly overvalued. Furthermore, we propose a truthful data valuation metric, named *Truth-Shapley*. Truth-Shapley is the unique metric that guarantees some promising axioms for data valuation while ensuring that clients' optimal strategy is to perform truthful data valuation. Our experiments demonstrate the vulnerability of existing data valuation metrics to the data overvaluation attack and validate the robustness and effectiveness of Truth-Shapley.

1 Introduction

As data regulations become increasingly stringent, it is becoming more challenging for enterprises to collect sufficient high-quality data for machine learning (ML). To address this issue, collaborative ML (CML), such as federated learning (McMahan et al., 2017), has emerged as a promising solution that enables enterprises to train accurate ML models without directly sharing data. Given that enterprises' datasets are often highly heterogeneous, a critical task in CML is data valuation, that is, how to reasonably evaluate the contribution of different heterogeneous datasets to model performance improvement. Based on the datasets' data values, i.e., the outcome of data valuation, enterprises can select higher-quality data to further enhance model performance and fairly allocate rewards among themselves, such as the revenue made by deploying the model.

In the literature, marginal contribution-based valuation metrics, represented by the leave-one-out (LOO) (Cook, 1977) and the Shapley value (SV) (Shapley, 1953), have been widely adopted for data valuation in CML. These metrics evaluate data value by measuring the impact of including or excluding a dataset on model performance. For example, the SV requires iterating over all possible combinations of the datasets and computing the model utility improvement contributed by each dataset to each combination, leading to significant computational costs for repeated model retraining. Consequently, extensive research efforts (e.g., (Ghorbani & Zou, 2019; Jia et al., 2019b,a; Kwon et al., 2021)) have been devoted to improving the computational efficiency of data valuation to enhance its practicality. However, existing studies overlook a critical trust vulnerability: During model retraining, clients may misreport their datasets to untruthfully overvalue them, thereby maximizing their gains in data selection and reward allocation.¹ This gap motivates us to conduct the first exploration of data overvaluation and truthful data valuation.

In this paper, we propose a novel attack method targeting data valuation: the data overvaluation attack. This attack enables strategic clients to misreport their datasets to significantly inflate their data value, thereby gaining an unfair advantage in subsequent data selection and reward allocation tasks. Notably, the attack works against all linear data valuation metrics, which cover most of the state-of-the-arts (SOTAs) including the LOO and the SV. Our experimental results demonstrate that the data overvaluation attack can increase an attacker's SV by up to **210%** and even boost their LOO value by **four orders of magnitude**.

Next, we explore how to ensure *truthful data valuation*. We theoretically characterize the subclass of *linear* data valuation metrics that can resist the data overvaluation attack. This characterization is fundamental since most of mainstream data valuation metrics are linear, inlcuding the LOO, the SV, Beta Shapley (Kwon & Zou, 2022), and Banzhaf value Wang & Jia (2023). From this subclass, we identify a novel valuation metric, named *Truth-Shapley*. Similar to the SV, Truth-Shapley uniquely satisfies a set of promising axioms for valuation, thereby ensuring effective data selection and

^{*}Correspondence to: zheng@ist.osaka-u.ac.jp

¹Since clients in CML do not share raw data, detecting data misreporting behavior during model retraining is challenging.

fair reward allocation. Therefore, regardless of whether a data overvaluation attack occurs, Truth-Shapley serves as an excellent choice for robust and effective data valuation.

We summarize our contributions as follows.

- First, we propose the data overvaluation attack. This attack reveals the unexplored vulnerability of existing data valuation metrics to strategic data manipulation and thus opens up a new research direction toward truthful data valuation for CML.
- Second, we theoretically analyze and characterize the necessary and sufficient conditions for linear data valuation metrics to ensure truthful data valuation. This characterization facilitates a rigorous assessment of their robustness against data overvaluation.
- Third, we propose Truth-Shapley, which is the unique data valuation metric that can prevent the data overvaluation attack while satisfying some key axioms for valuation.
- Finally, we conduct extensive experiments in three representative CML scenarios: horizontal FL, vertical FL, and hybrid FL. Our results demonstrate the vulnerability of existing data valuation metrics to the data overvaluation attack and validate the robustness and effectiveness of Truth-Shapley in data selection and reward allocation.

2 Preliminaries

2.1 Data Valuation Problem

We consider a CML scenario where N clients (i.e., data owners) $\mathbb{N} = \{1, \ldots, N\}$ collaboratively train an ML model under the coordination of a server (e.g., a model buyer or a broker in the data market). Each client $i \in \mathbb{N}$ possesses a dataset D_i that includes M_i data blocks. A data block $D_{i,j} \in D_i$ could be a subset of the samples in D_i , a subset of the features in D_i , or even a subset of the features from a subset of the samples in D_i . We write $\mathcal{C} \subseteq \mathbb{N}$ to denote a subset of clients and $D_{\mathcal{C}}$ to denote the set of data blocks possessed by clients \mathcal{C} , i.e., $D_{\mathcal{C}} = \bigcup_{i \in \mathcal{C}} D_i = \{D_{i,j} \mid i \in \mathcal{C}, j \in [M_i]\}$. Given all clients' data blocks, the server utilizes a CML algorithm \mathcal{A} to train an ML model $\mathcal{A}(D_{\mathbb{N}})$ on the grand dataset $D_{\mathbb{N}}$.

After model training, the server performs data valuation to evaluate each data block $D_{i,j}$'s block-level data value $\phi_{i,j}(D_{\mathbb{N}}, v)$, which reflects the contribution of $D_{i,j}$ to improving the utility $v(D_{\mathbb{N}})$ of the global model $\mathcal{A}(D_{\mathbb{N}})$. We write $\phi_{i,j}(D_{\mathbb{N}}, v)$ as $\phi_{i,j}$ for simplicity when there is no ambiguity. Then, each client *i*'s client-level data value $\phi_i(D_{\mathbb{N}}, v)$ or simply ϕ_i is the sum of their data blocks' data values, i.e., $\phi_i = \sum_{j \in [M_i]} \phi_{i,j}$. Consequently, the data valuation problem is to design a data valuation metric ϕ , defined as follows, to determine data values for all data blocks involved in the CML.

Definition 2.1 (Data Valuation). A utility metric $v : 2^{D_{\mathbb{N}}} \to \mathbb{R}$ maps a subset of data blocks $S \subseteq D_{\mathbb{N}}$ to the utility v(S) of the model $\mathcal{A}(S)$ with $v(\emptyset) = 0$. A data valuation metric $\phi : D_{\mathbb{N}} \times \mathcal{G}(D_{\mathbb{N}})$ allocates data values $\{\phi_{i,j}(D_{\mathbb{N}}, v) \mid i \in \mathbb{N}, j \in [M_i]\}$, where $\mathcal{G}(D_{\mathbb{N}}) = \{v \mid v : 2^{D_{\mathbb{N}}} \to \mathbb{R}\}$.

Data valuation facilitates the following two downstream tasks, which ensure fairness and incentivize clients to participate in CML:

- Data selection: The server selects data blocks $D_{i,j}$ with high(er) block-level data values $\phi_{i,j}$ to enhance the performance of CML next time (Cohen et al., 2005; Nagalapatti & Narayanam, 2021), which is critical when there exist clients who contribute trivial data or outliers.
- Reward allocation: The server allocates rewards $R_i(\phi_1, \ldots, \phi_N)$ to each client *i* based on their client-level data values ϕ_i . The rewards may be revenue obtained from commercializing the global model (i.e., monetary rewards (Nguyen et al., 2022)) or customized models with differing utility (i.e., model rewards (Sim et al., 2020)). Each client *i*'s reward $R_i(\phi_1, \ldots, \phi_N)$ increases with their own data value ϕ_i and decreases with the sum of the other clients' data values $\phi_{-i} = \sum_{i' \in \mathbb{N} \setminus \{i\}} \phi_{i'}$. Therefore, we assume that each client *i* is selfish and rational, aiming to maximize ϕ_i while minimizing ϕ_{-i} .

2.2 Shapley Value for Data Valuation

As a classic metric for contribution evaluation in cooperative game theory, the Shapley value (SV) has been widely adopted for data valuation in CML. It calculates the average contribution of each participant to a coalition. In our scenario, as each data block can be regarded as a participant, the SV determines the data value $\phi_{i,j}^{SV}$ of each data block $D_{i,j}$ as follows.

$$\phi_{i,j}^{SV}(D_{\mathbb{N}},v) \coloneqq \sum_{\mathcal{S} \subseteq D_{\mathbb{N}} \setminus \{D_{i,j}\}} w^{SV}(\mathcal{S}) \big(v(\mathcal{S}^+) - v(\mathcal{S}) \big) \tag{1}$$

where $w^{SV}(\mathcal{S}) \coloneqq \frac{|\mathcal{S}|!(|D_{\mathbb{N}}|-|\mathcal{S}|-1)!}{|D_{\mathbb{N}}|!}$ and $\mathcal{S}^+ = \mathcal{S} \cup \{D_{i,j}\}$. Specifically, the SV enumerates all possible subsets \mathcal{S} of $D_{\mathbb{N}}$ excluding the data block $D_{i,j}$. The term $(v(\mathcal{S}^+) - v(\mathcal{S}))$ quantifies the utility improvement achieved by adding $D_{i,j}$ to subset \mathcal{S} , and computing $v(\mathcal{S})$ and $v(\mathcal{S}^+)$ requires model retraining. $w^{SV}(\mathcal{S})$ is a coefficient that weights the importance of \mathcal{S} . The data value $\phi_{i,j}^{SV}$ thus is the weighted aggregation of all utility improvements attributed to $D_{i,j}$.

The SV is considered an ideal solution to data valuation because it has been proven be to the unique valuation metric that satisfies the following axioms (Shapley, 1953).

- Linearity (LIN): The server can linearly combine the data values evaluated on any two utility metrics v_1 and v_2 , i.e., $\phi_{i,j}(D_{\mathbb{N}}, v_1 + v_2) = \phi_{i,j}(D_{\mathbb{N}}, v_1) + \phi_{i,j}(D_{\mathbb{N}}, v_2).$
- Efficiency (EFF): The sum of all data blocks' data values equals the utility improved by the grand dataset $D_{\mathbb{N}}$, i.e., $\sum_{i \in \mathbb{N}} \sum_{j \in [M_i]} \phi_{i,j}(D_{\mathbb{N}}, v) = v(D_{\mathbb{N}}).$
- Dummy actions (DUM): If a data block $D_{i,j}$ does not have any synergy with the other blocks, its data value $\phi_{i,j}^{SV}$ equals the utility $v(D_{i,j})$ of the model trained only on itself. That is, if for all $S \subseteq D_{\mathbb{N}} \setminus \{D_{i,j}\}$, we have $v(S \cup D_{i,j}) v(S) = v(D_{i,j})$, then $\phi_{i,j}(D_{\mathbb{N}}, v) = v(D_{i,j})$.
- Symmetry (SYM): If two data blocks have the same effect on the model utility, they should obtain the same blocklevel data values. In other words, for two data blocks $D_{i_1,j_1}, D_{i_2,j_2} \in D_{\mathbb{N}}$, if for any subset of data blocks $S \subseteq D_{\mathbb{N}} \setminus \{D_{i_1,j_1}, D_{i_2,j_2}\}$, we have $v(S \cup D_{i_1,j_1}) = v(S \cup D_{i_2,j_2})$, then we have $\phi_{i_1,j_1}(D_{\mathbb{N}}, v) = \phi_{i_2,j_2}(D_{\mathbb{N}}, v)$.

Theorem 2.2 (Uniqueness of SV (Shapley, 1953)). The $SV \phi^{SV}$ is the unique data valuation metric that satisfies DUM, SYM, LIN, and EFF.

3 Data Overvaluation Attack

In this section, we first provide the *data overvaluation* attack against the SV and then generalize it for other metrics.

3.1 Data Overvaluation against the SV

Although the SV fairly allocates data values to honest clients, strategic clients can manipulate their SVs by misreporting data subsets for model retraining. As shown in Equation (1), the SV $\phi_{i,j}^{SV}$ enumerates all subsets S of the grand dataset $D_{\mathbb{N}}$; for each subset $S \subset D_{\mathbb{N}}$, a model $\mathcal{A}(S)$ is retrained, and its utility v(S) is evaluated for calculating $\phi_{i,j}^{SV}$. Let D_i^S denote the set of data blocks in S that belong to client i, D_{-i}^S denote the others data blocks in S, i.e., $D_{-i}^S = S/D_i^S$, and $\mathbb{N}(S)$ denote the set of clients who have at least one data block in S. Then, for each subset $S \subset D_{\mathbb{N}}$ with $i \in \mathbb{N}(S)$, since v(S) can also be expressed as $v(D_i^S \cup D_{-i}^S)$, client i can vary v(S) by misreporting D_i^S , thereby manipulating their block-level SVs $\phi_{i,j}^{SV}$.

Similarly, client *i* can also manipulate their client-level SV ϕ_i^{SV} by altering the model utility $v(\mathcal{S})$. Specifically, the client-level SV $\phi_i^{SV} = \sum_{j \in [M_i]} \phi_{i,j}^{SV}$ can be written in the following form:

$$\begin{split} \phi_i^{SV}(D_{\mathbb{N}}, v) &= \sum_{\mathcal{S} \subseteq D_{\mathbb{N}}} \beta_i^{SV}(\mathcal{S}) \cdot v(\mathcal{S}), \text{ where} \\ \beta_i^{SV}(\mathcal{S}) \\ &\coloneqq \begin{cases} (|D_i^{\mathcal{S}}||D_{\mathbb{N}}| - |D_i||\mathcal{S}|) \cdot \frac{(|\mathcal{S}| - 1)!(|D_{\mathbb{N}}| - |\mathcal{S}| - 1)!}{|D_{\mathbb{N}}|!}, & \mathcal{S} \subset D_{\mathbb{N}}, \mathcal{S} \neq \emptyset, \\ |D_i|/|D_{\mathbb{N}}|, & \mathcal{S} = D_{\mathbb{N}}, \\ -|D_i|/|D_{\mathbb{N}}|, & \mathcal{S} = \emptyset. \end{cases} \end{split}$$

Because $\frac{\partial \phi_i^{SV}}{\partial (v(\mathcal{S}))} = \beta_i^{SV}(\mathcal{S})$, when $\beta_i^{SV}(\mathcal{S}) > 0$, increasing $v(\mathcal{S})$ can enhance ϕ_i^{SV} ; when $\beta_i^{SV}(\mathcal{S}) < 0$, decreasing $v(\mathcal{S})$ improves ϕ_i^{SV} ; when $\beta_i^{SV}(\mathcal{S}) = 0$, changing $v(\mathcal{S})$ reduces ϕ_i^{SV} has no effect on ϕ_i^{SV} .

Algorithm. Based on the above analysis, we propose Algorithm 1 to implement data overvaluation against the SV, considering a strategic client *i* as an attacker. Let $\hat{D}_i^{\mathcal{S}}$ denote the version of $D_i^{\mathcal{S}}$ reported by client *i* and $\hat{D}_{-i}^{\mathcal{S}}$ denote the version of $D_{-i}^{\mathcal{S}}$ reported by the other clients for evaluating the model utility $v(\mathcal{S})$. That means, instead of truthfully using dataset $D_i^{\mathcal{S}}$, client *i* may untruthfully employ dataset $\hat{D}_i^{\mathcal{S}} \neq D_i^{\mathcal{S}}$ to increase the model utility from $v(\mathcal{S})$ to $v(\hat{\mathcal{S}})$, where $\hat{\mathcal{S}} = \hat{D}_i^{\mathcal{S}} \cup \hat{D}_{-i}^{\mathcal{S}}$. In Algorithm 1, to compute the SV, we iterate over every subset $\mathcal{S} \subset D_{\mathbb{N}}$ and evaluate its corresponding model utility (Lines 3–18). Note that the grand model's utility $v(D_{\mathbb{N}})$ is given as the algorithm's input, as the grand model $\mathcal{A}(D_{\mathbb{N}})$ has already been trained before data valuation. When a subset \mathcal{S} includes client *i*'s data blocks, if $\beta_i^{\mathcal{S}V}(\mathcal{S})$ is nonzero, client *i* has the incentive to manipulate $v(\mathcal{S})$; thus, in this case, client *i* positively/negatively augments their

Algorithm 1 Data Overvaluation against the SV

1: **Input:** dataset $D_{\mathbb{N}}$, grand model's utility $v(D_{\mathbb{N}})$

- 2: Attacker: client i3: for each subset $\mathcal{S} \subset D_{\mathbb{N}}$ do if $i \in \mathbb{N}(\mathcal{S})$ then 4:if $\beta_i^{SV}(\mathcal{S}) > 0$ then 5:
- Client *i*: Positively augment D_i^S to obtain a reported dataset \widehat{D}_i^S . 6:
- else if $\beta_i^{SV}(\mathcal{S}) < 0$ then 7:
- Client *i*: Negatively augment $D_i^{\mathcal{S}}$ to generate a reported dataset $\widehat{D}_i^{\mathcal{S}}$. 8:
- 9: else Client *i*: Honestly use $\widehat{D}_i^{\mathcal{S}} = D_i^{\mathcal{S}}$. 10:
- end if 11:
- end if 12:
- Clients $\mathbb{N}(\mathcal{S})$: Use dataset $\widehat{\mathcal{S}} = \bigcup_{i' \in \mathbb{N}(\mathcal{S})} \widehat{D}_{i'}^{\mathcal{S}}$ to train a model $\mathcal{A}(\widehat{\mathcal{S}})$. 13:
- Server: Evaluate the model's utility $v(\widehat{S})$. 14:
- 15: end for
- 16: Server: Calculate $\widehat{\phi}_{i,j}^{SV}(D_{\mathbb{N}}, v), \forall i, \forall j$ and return them.

dataset $D_i^{\mathcal{S}}$ to derive a new dataset $\widehat{D}_i^{\mathcal{S}}$ (Lines 6 and 8), resulting in an enhanced/reduced utility $v(\widehat{\mathcal{S}})$ (Lines 13–14). After evaluating all the model utilities, the server calculates client *i*'s *empirical* block-level SVs as:

$$\begin{aligned} \widehat{\phi}_{i,j}^{SV}(D_{\mathbb{N}}, v) &\coloneqq \sum_{\mathcal{S} \subset D_{\mathbb{N}} \setminus \{D_{i,j}\}} w^{SV}(\mathcal{S}) \big(v(\widehat{\mathcal{S}}^+) - v(\widehat{\mathcal{S}}) \big) \\ &+ w^{SV}(D_{\mathbb{N}}^-) \big(v(D_{\mathbb{N}}) - v(\widehat{D}_{\mathbb{N}}^-) \big) \end{aligned}$$

where \widehat{S}^+ is the reported version of S^+ , $D_{\mathbb{N}}^- = D_{\mathbb{N}} \setminus \{D_{i,j}\}$, and $\widehat{D}_{\mathbb{N}}^-$ is the reported version of $D_{\mathbb{N}}^-$. Consequently, client *i* obtains their empirical client-level SV as:

$$\widehat{\phi}_i^{SV}(D_{\mathbb{N}}, v) = \beta_i^{SV}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}}} \beta_i^{SV}(\mathcal{S}) \cdot v(\widehat{\mathcal{S}}).$$

 $\text{If } \forall \mathcal{S} \subset D_{\mathbb{N}} \text{ with } \beta_{i}^{SV}(\mathcal{S}) > 0, \text{ we have } v(\widehat{D}_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}}) \geq v(D_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}}), \text{ and } \forall \mathcal{S} \subset D_{\mathbb{N}} \text{ with } \beta_{i}^{SV}(\mathcal{S}) < 0, \text{ we have } v(\widehat{D}_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}}) \leq 0 \leq 0 \leq 0$ $v(D_i^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}})$, then $\widehat{\phi}_i^{SV}(D_{\mathbb{N}}, v)$ is guaranteed to be no less than the empirical SV $\widehat{\phi}_i^{SV}(D_{\mathbb{N}}, v \mid \forall \mathcal{S} \subset D_{\mathbb{N}}, \widehat{D}_i^{\mathcal{S}} = D_i^{\mathcal{S}})$ where client *i* truthfully reports their data contributions $\widehat{D}_i^{\mathcal{S}} = D_i^{\mathcal{S}}$, i.e.,

$$\widehat{\phi}_{i}^{SV}(D_{\mathbb{N}}, v \mid \forall \mathcal{S} \subset D_{\mathbb{N}}, \widehat{D}_{i}^{\mathcal{S}} = D_{i}^{\mathcal{S}}) = \beta_{i}^{SV}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}}} \beta_{i}^{SV}(\mathcal{S}) \cdot v(D_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}}).$$

This implies that client i may increase its (empirical) client-level SV $\hat{\phi}_i^{SV}$ through a data overvaluation attack. Moreover, since the SV satisfies the EFF axiom, the total SV $\hat{\phi}_{-i}^{SV}$ of the other clients will decrease accordingly.

3.2Generalization

In addition to the SV, we further generalize the data overvaluation attack to manipulate all linear data valuation metrics. **Lemma 3.1.** If a data valuation metric ϕ satisfies LIN, then for each client *i*, there exists $\beta_i : 2^{D_{\mathbb{N}}} \to \mathbb{R}$ such that

$$\phi_i(D_{\mathbb{N}}, v) \equiv \sum_{\mathcal{S} \subseteq D_{\mathbb{N}}} \beta_i(\mathcal{S}) \cdot v(\mathcal{S}).$$

Specifically, Lemma 3.1 indicates that any linear data value ϕ_i can be expressed as a weighted sum of model utilities $\{v(\mathcal{S})\}_{\mathcal{S}\subseteq D_{\mathbb{N}}}$. Consequently, similar to the case of the SV, for each subset $\mathcal{S} \subset D_{\mathbb{N}}$, and for each client $i \in \mathbb{N}(\mathcal{S})$, when $\beta_i(\mathcal{S})$ is positive (negative), they can increase (decrease) $v(\mathcal{S})$ to enhance their linear data value ϕ_i . However, unlike the SV, some data valuation metrics such as Beta Shapley and Banzhaf value do not satisfy EFF, meaning that an increase in ϕ_i does not necessarily lead to a decrease in ϕ_{-i} . As a result, client i may not always receive a higher reward. Therefore, when $\beta_i(\mathcal{S})$ is positive (negative), we should also ensure that $\beta_{-i}(\mathcal{S}) = \sum_{i' \in \mathbb{N}(\mathcal{S}) \setminus \{i\}} \beta_{i'}(\mathcal{S})$ is non-positive to prevent ϕ_{-i} from increasing.

Hence, we generalize the data overvaluation attack in Definition 3.2. As demonstrated in Lemma 3.3, by (successfully) implementing the attack, a strategic client *i* can derive an inflated empirical data value $\hat{\phi}_i(D_{\mathbb{N}}, v) \geq \hat{\phi}_i(D_{\mathbb{N}}, v \mid \forall S \subset D_{\mathbb{N}}, \hat{D}_i^S = D_i^S)$, where

$$\begin{split} \widehat{\phi}_i(D_{\mathbb{N}}, v) &= \beta_i(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}}} \beta_i(\mathcal{S}) \cdot v(\widehat{\mathcal{S}}), \\ \widehat{\phi}_i(D_{\mathbb{N}}, v \mid \forall \mathcal{S} \subset D_{\mathbb{N}}, \widehat{D}_i^{\mathcal{S}} = D_i^{\mathcal{S}}) \\ &= \beta_i(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}}} \beta_i(\mathcal{S}) \cdot v(D_i^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}}), \end{split}$$

and have the sum of the other clients' data values decreased, i.e., $\phi_{-i}(D_{\mathbb{N}}, v) \leq \phi_{-i}(D_{\mathbb{N}}, v \mid \forall S \subset D_{\mathbb{N}}, \widehat{D}_{i}^{S} = D_{i}^{S})$.

Definition 3.2 (Data Overvaluation Attack). Consider a linear data valuation metric ϕ . A data overvaluation attack against data value $\phi_i(D_{\mathbb{N}}, v)$ is to report data subsets $\{\widehat{D}_i^{\mathcal{S}} \mid \forall \mathcal{S} \subset D_{\mathbb{N}}, i \in \mathbb{N}(\mathcal{S})\}$ where $\exists \widehat{D}_i^{\mathcal{S}} \neq D_i^{\mathcal{S}}$ to achieve the following goal: $\forall \mathcal{S} \subset D_{\mathbb{N}}, i \in \mathbb{N}(\mathcal{S})$, if $\beta_i(\mathcal{S}) > 0$ and $\beta_{-i}(\mathcal{S}) \leq 0$, we have $v(\widehat{D}_i^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}}) > v(D_i^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}});$ if $\beta_i(\mathcal{S}) < 0$ and $\beta_{-i}(\mathcal{S}) \geq 0$, we have $v(\widehat{D}_i^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}}) > v(D_i^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}});$ if $\beta_i(\mathcal{S}) < 0$ and $\beta_{-i}(\mathcal{S}) \geq 0$, we have $v(\widehat{D}_i^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}}) > v(D_i^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}});$ otherwise, $v(\widehat{D}_i^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}}) = v(D_i^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}}).$

Lemma 3.3. If the goal is achieved, a data overvaluation attack against a linear data value $\phi_i(D_{\mathbb{N}}, v)$ ensures that $\widehat{\phi}_i(D_{\mathbb{N}}, v) \geq \widehat{\phi}_i(D_{\mathbb{N}}, v \mid \forall S \subset D_{\mathbb{N}}, \widehat{D}_i^S = D_i^S)$ while $\widehat{\phi}_{-i}(D_{\mathbb{N}}, v) \leq \widehat{\phi}_{-i}(D_{\mathbb{N}}, v \mid \forall S \subset D_{\mathbb{N}}, \widehat{D}_i^S = D_i^S)$.

4 Truthful Data Valuation for CML

In this section, we first characterize the subclass of data valuation metrics that can prevent the data overvaluation attack and then select a special metric from this class, named *Truth-Shapley* (Truthful Shapley value).

4.1 Characterization of Truthful Data Valuation

From Definition 3.2, we know that the issue of data overvaluation arises from strategic clients untruthfully reporting their data subset \hat{D}_i^S , which is highly analogous to the problem of untruthful bidding in auctions. Specifically, for each client *i*, if we regard their reported data \hat{D}_i^S , $\forall S \subset D_{\mathbb{N}}$ as their bid and the empirical data value $\hat{\phi}_i$ as their payoff, the problem of preventing data overvaluation can be viewed as ensuring a truthful auction.

Definition 4.1 (Bayesian Incentive Compatibility for Truthful Data Valuation). A data valuation metric ϕ is Bayesian incentive compatible (BIC) if for any game $(D_{\mathbb{N}}, v)$, for any client *i*, and for any reported data subsets $\{\widehat{D}_{i}^{S} \mid S \subset D_{\mathbb{N}}, i \in \mathbb{N}(S)\}$, we have

$$\mathbb{E}_{\widehat{D}_{-i}^{\mathcal{S}} \sim \sigma_i(\cdot|\mathcal{S}), \forall \mathcal{S} \subset D_{\mathbb{N}}}[\widehat{\phi}_i(D_{\mathbb{N}}, v)] \leq$$
(2)

$$\mathbb{E}_{\widehat{D}^{\mathcal{S}}_{i} \sim \sigma_{i}(\cdot|\mathcal{S}), \forall \mathcal{S} \subset D_{\mathbb{N}}} [\widehat{\phi}_{i}(D_{\mathbb{N}}, v \,|\, \forall \mathcal{S} \subset D_{\mathbb{N}}, \widehat{D}_{i}^{\mathcal{S}} = D_{i}^{\mathcal{S}})], \tag{3}$$

$$\mathbb{E}_{\widehat{D}_{-i}^{S} \sim \sigma_{i}(\cdot|S), \forall S \subset D_{\mathbb{N}}}[\widehat{\phi}_{-i}(D_{\mathbb{N}}, v)] \geq$$

$$(4)$$

$$\mathbb{E}_{\widehat{D}^{\mathcal{S}}_{i}\sim\sigma_{i}(\cdot|\mathcal{S}),\forall\mathcal{S}\subset D_{\mathbb{N}}}[\widehat{\phi}_{-i}(D_{\mathbb{N}},v\,|\,\forall\mathcal{S}\subset D_{\mathbb{N}},\widehat{D}_{i}^{\mathcal{S}}=D_{i}^{\mathcal{S}})],\tag{5}$$

where $\sigma_i(\cdot | S)$ denotes the distribution of \widehat{D}_{-i}^{S} estimated by client *i* in their belief.

Accordingly, we draw on the concept of *Bayesian incentive compatibility* (BIC) from auction theory d'Aspremont & Gérard-Varet (1982), defined in Definition 4.1, to ensure truthful data valuation. Intuitively, BIC ensures that for each client *i*, truthfully reporting their data $\hat{D}_i^{\mathcal{S}} = D_i^{\mathcal{S}}$ is the optimal strategy that not only maximizes their expected data value in Formula (2) but also minimizes the sum of the other clients' data values in Formula (4). Note that the expected data values in Formulas (2)-(5) are based on client *i*'s prior beliefs $\{\sigma_i(\cdot | \mathcal{S})\}_{\mathcal{S} \subset D_N}$ about the other clients' reported data. This implies that truthful reporting is subjectively optimal based on their beliefs, rather than objectively optimal. For simplicity, we will omit the conditional subscript of the expectation operator \mathbb{E} where there is no ambiguity.

Assumption 4.2 (Subjectively Optimal Data). For any data subset $S \subset D_{\mathbb{N}}$ with $D_i^S = D_i$, and for any \widehat{D}_i^S , we have

$$\mathbb{E}_{\widehat{D}_{-i}^{\mathcal{S}} \sim \sigma_{i}(\cdot|\mathcal{S}), \forall \mathcal{S} \subset D_{\mathbb{N}}}[v(D_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}})] \\ \geq \mathbb{E}_{\widehat{D}_{-i}^{\mathcal{S}} \sim \sigma_{i}(\cdot|\mathcal{S}), \forall \mathcal{S} \subset D_{\mathbb{N}}}[v(\widehat{D}_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}})]$$

Next, we characterize the subclass of linear data valuation metrics that ensure BIC, based on Assumption 4.2. Intuitively, Assumption 4.2 means that according to client *i*'s belief, D_i is the dataset known to them that can best optimize the model's utility. This is also why client *i* has used D_i to train the grand model $\mathcal{A}(D_{\mathbb{N}})$ in the CML. Then, according to Lemma 3.1, for any linear data valuation metric ϕ , Formulas (2)-(4) can be expressed in the following form:

$$\begin{split} & \mathbb{E}[\widehat{\phi}_{i}(D_{\mathbb{N}}, v)] = \beta_{i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}}} \beta_{i}(\mathcal{S}) \cdot \mathbb{E}[v(\widehat{D}_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}})], \\ & \mathbb{E}[\widehat{\phi}_{-i}(D_{\mathbb{N}}, v)] = \beta_{-i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}}} \beta_{-i}(\mathcal{S}) \cdot \mathbb{E}[v(\widehat{D}_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}})]. \end{split}$$

Therefore, for any data subset $S \subset D_{\mathbb{N}}$, if $D_i^S \neq D_i$, we should ensure that $\beta_i(S) = \beta_{-i}(S) = 0$ such that varying \widehat{D}_i^S has no impact on client *i*'s (the other clients') expected data value $\mathbb{E}[\widehat{\phi}_i(D_{\mathbb{N}}, v)]$ ($\mathbb{E}[\widehat{\phi}_{-i}(D_{\mathbb{N}}, v)]$), thereby ensuring no incentive to report $\widehat{D}_i^S \neq D_i^S$. If $D_i^S = D_i$, we can set $\beta_i(S) \geq 0$ and $\beta_{-i}(S) \leq 0$ to incentivize client *i* to optimize the utility $\mathbb{E}[v(\widehat{D}_i \cup \widehat{D}_{-i}^S)]$; because of Assumption 4.2, reporting their subjectively optimal data $\widehat{D}_i = D_i$ is their best strategy. Consequently, we derive the following characterization of linear and BIC data valuation metrics.

Theorem 4.3 (Characterization 1). Consider a linear data valuation metric $\phi_i(D_{\mathbb{N}}, v) \coloneqq \sum_{\mathcal{S} \subseteq D_{\mathbb{N}}} \beta_i(\mathcal{S}) \cdot v(\mathcal{S})$ where $\beta_i : 2^{D_{\mathbb{N}}} \to \mathbb{R}$. Under Assumption 4.2, ϕ satisfies BIC iff β_i satisfies that: $\forall \mathcal{S} \subset D_{\mathbb{N}}$, if $D_i^{\mathcal{S}} = D_i$, $\beta_i(\mathcal{S}) \ge 0$ and $\beta_{-i}(\mathcal{S}) \le 0$; otherwise, $\beta_i(\mathcal{S}) = \beta_{-i}(\mathcal{S}) = 0$.

4.2 Truth-Shapley

Next, we attempt to select a strong member from the subclass of linear and BIC data valuation metrics. Our idea is to satisfy the four axioms enjoyed by the SV as much as possible, even though, according to Theorem 2.2, full compliance is impossible. The first axiom we prioritize is EFF, as it ensures that the model utility $v(D_{\mathbb{N}})$ is fully attributed to all data blocks. Consequently, we propose Theorem 4.4, which characterizes linear, efficient, and BIC valuation metrics.

Theorem 4.4 (Characterization 2). Consider a linear, efficient data valuation metric $\phi_i(D_{\mathbb{N}}, v) \coloneqq \sum_{\mathcal{S} \subseteq D_{\mathbb{N}}} \beta_i(\mathcal{S}) \cdot v(\mathcal{S})$ where $\beta_i : 2^{D_{\mathbb{N}}} \to \mathbb{R}$. Under Assumption 4.2, ϕ satisfies BIC iff: $\phi_i(D_{\mathbb{N}}, v) \equiv \sum_{\mathcal{C} \subseteq \mathbb{N}} \beta_i(D_{\mathcal{C}}) \cdot v(D_{\mathcal{C}})$ where $\beta_i(D_{\mathcal{C}}) \ge 0$ for all $\mathcal{C} \subset \mathbb{N}$ with $i \in \mathcal{C}$.

Based on Theorem 4.4, we know that under a data valuation metric satisfying LIN, EFF, and BIC, each client's client-level data value ϕ_i should be determined only by the utilities $v(D_C)$ of all combinations D_C of client's full datasets D_1, \ldots, D_N . Accordingly, we propose Truth-Shapley (simply TSV) ϕ^{TSV} , which uses an SV-style approach to (1) compute the client-level data value ϕ_i^{TSV} based on the clients' full datasets and then (2) divide ϕ_i^{TSV} among individual data blocks to derive $\phi_{i,1}^{TSV}, \ldots, \phi_{i,M_i}^{TSV}$.

Specifically, let $\mathbb{D}_{\mathcal{C}} = \{D_i\}_{\forall i \in \mathcal{C}}$ for all $\mathcal{C} \subseteq \mathbb{N}$ and $\mathbb{D}_{-i} = \mathbb{D}_{\mathbb{N}} \setminus \{D_i\}$. Note that $\mathbb{D}_{\mathcal{C}}$ is mathematically distinct from $D_{\mathcal{C}}$, but it holds the same physical meaning and thus corresponds to the same utility $v(\mathbb{D}_{\mathcal{C}}) = v(D_{\mathcal{C}})$. Then, we apply the approach of the SV to calculate the client-level TSV:

$$\phi_i^{TSV}(D_{\mathbb{N}}, v) \coloneqq \phi_i^{SV}(\mathbb{D}_{\mathbb{N}}, v)$$
$$= \sum_{\mathcal{C} \subseteq \mathbb{N} \setminus \{i\}} w^{SV}(\mathcal{C} \mid \mathbb{N}) \big(v(\mathbb{D}_{\mathcal{C}} \cup \{D_i\}) - v(\mathbb{D}_{\mathcal{C}}) \big),$$

where $w^{SV}(\mathcal{C} \mid \mathbb{N}) \coloneqq \frac{|\mathcal{C}|!(|\mathbb{N}| - |\mathcal{C}| - 1)!}{|\mathbb{N}|!}$. Next, we employ the SV again to calculate the block-level TSV:

$$\phi_{i,j}^{TSV}(D_{\mathbb{N}},v) \coloneqq \phi_{j}^{SV}(D_{i},v^{\phi_{i}^{TSV}})$$

=
$$\sum_{\mathcal{S}\subseteq D_{i}\setminus\{D_{i,j}\}} w^{SV}(\mathcal{S}|D_{i}) (v^{\phi_{i}^{TSV}}(\mathcal{S}\cup\{D_{i,j}\}) - v^{\phi_{i}^{TSV}}(\mathcal{S})),$$

where $w^{SV}(\mathcal{S} \mid D_i) \coloneqq \frac{|\mathcal{S}|!(|D_i|-|\mathcal{S}|-1)!}{|D_i|!}$ and $v^{\phi_i^{TSV}}(\mathcal{S}) \coloneqq \phi_i^{TSV}(\mathbb{D}_{-i} \cup \{D_i^{\mathcal{S}}\}, v)$. Intuitively, the utility $v^{\phi_i^{TSV}}(\mathcal{S})$ represents the client-level TSV ϕ_i^{TSV} when client *i* contributes dataset $D_i^{\mathcal{S}}$. Consequently, the block-level TSV $\phi_{i,j}^{TSV}$ measures the expected marginal contribution of the data block $D_{i,j}$ to improving the client-level TSV ϕ_i^{TSV} . Due to the use of the SV-style approach for defining both ϕ_i^{TSV} and $\phi_{i,j}^{TSV}$, we ensure that Truth-Shapley is linear, efficient, and perfectly complies with the characterization in Theorem 4.4. Therefore, we conclude that it satisfies BIC.

Theorem 4.5. Truth-Shapley ϕ^{TSV} satisfies BIC.

From Theorem 2.2, we know that Truth-Shapley cannot simultaneously satisfy DUM, SYM, LIN, and EFF. However, we find that apart from LIN and EFF, Truth-Shapley satisfies the following axioms:

Table 1: Performance of data valuation metrics on the reward allocation task. The suffix (o/v) denotes that the valuation metric has undergone a data overvaluation attack. The percentage in parentheses represents the relative increase/decrease in comparison to ϕ_i .

Valuation	HFL	$({\rm FedAVG})$	VFL	$({ m Split}{ m NN})$		HyFL (FedMD)			
Metric	$egin{array}{llllllllllllllllllllllllllllllllllll$	$egin{array}{l} ext{decr. (rate)} \ ext{in } \widehat{\phi}_{-i} \end{array}$	val. err.	incr. (rate) in $\widehat{\phi}_i$	$egin{array}{l} ext{decr. (rate)} \ ext{in } \widehat{\phi}_{-i} \end{array}$	val. err.	incr. (rate) in $\widehat{\phi}_i$	$egin{array}{l} ext{decr. (rate)} \ ext{in } \widehat{\phi}_{-i} \end{array}$	val. err.
SV(o/v)	0.42~(139%)	0.42~(69.7%)	5.65	0.08~(106%)	0.08~(53.2%)	3.69	0.16~(210%)	0.16~(106%)	56.87
LOO(o/v)	1.99~(53265%)	0.0~(0.0%)	3.01	0.37~(5539%)	0.0~(0.0%)	2.91	0.70~(9738%)	0.0~(0.0%)	3.18
BV(o/v)	0.16(348%)	0.11(119%)	4.13	$0.04 \ (80.8\%)$	0.03~(33.1%)	3.71	0.08~(262%)	0.10~(165%)	62.46
BSV(o/v)	0.003~(15.8%)	0.002(5.0%)	3.92	$0.0 \ (0.0\%)$	0.0~(0.0%)	0.0	$0.0 \ (0.0\%)$	$0.0 \ (0.0\%)$	0.0
TSV(o/v)	0.0(0.0%)	0.0 (0.0%)	0.0	0.0(0.0%)	0.0(0.0%)	0.0	0.0(0.0%)	0.0(0.0%)	0.0

Table 2: Performance of data valuation metrics on the data selection task where data blocks with top-K data values are selected. The suffix (o/v) denotes that the valuation metric has undergone a data overvaluation attack. If the model accuracy decreases after the attack, we highlight it in bold.

Valuation		HFL (F	edAVG	1	VFL (SplitNN)				HyFL (FedMD)			
Metric	model accuracy (%) when the number of selected blocks = $\begin{pmatrix} 2 & 4 & 6 & 8 \\ 2 & 4 & 6 & 8 \\ \end{pmatrix}$											
	4	4	0	0	4	4	0	0	4	4	0	0
SV SV (o/v)	89.89 83.51	91.06 88.54	93.09 91.87	93.40 92.61	$\begin{array}{c} 66.35 \\ 67.02 \end{array}$	70.64 70.27	72.25 71.84	$71.90 \\ 72.01$	71.04 68.11	73.43 69.97	$71.68 \\ 72.27$	72.08 72.18
LOO LOO (o/v)	83.98 83.85	91.20 89.17	93.32 91.78	93.72 92.63	66.39 60.37	69.72 67.93	70.75 70.00	71.50 71.07	70.56 67.41	72.89 69.75	72.90 73.00	72.71 73.15
BV BV (o/v)	87.58 85.02	93.33 89.82	94.14 92.89	93.97 93.19	$66.40 \\ 67.03$	70.74 70.35	72.25 72.04	72.23 72.12	71.05 68.24	73.16 70.46	73.61 72.61	72.55 72.5 4
BSV BSV (o/v)	90.85 90.58	$88.55 \\ 91.95$	91.29 90.83	92.46 91.70		$70.62 \\ 70.62$	72.25 72.25	$71.63 \\ 71.63$	$71.06 \\ 71.06$	$73.26 \\ 73.26$	$71.68 \\ 71.68$	72.08 72.08
$\frac{TSV}{TSV \ (o/v)}$	90.58 90.58	$91.15 \\ 91.15$	92.13 92.13	92.51 92.51		70.42 70.42	72.21 72.21	72.17 72.17	71.07 71.07	73.55 73.55	71.79 71.79	72.08 72.08

• Client-level dummy actions (DUM-C): If for all $\mathcal{C} \subseteq \mathbb{N} \setminus \{i\}$, we have $v(D_{\mathcal{C}} \cup D_i) - v(D_{\mathcal{C}}) = v(D_i)$, then $\phi_i(D_{\mathbb{N}}, v) = v(D_i)$.

- Inner Block-level dummy actions (DUM-IB): If for all $S \subseteq D_i \setminus \{D_{i,j}\}$, we have $v(S \cup \{D_{i,j}\}) v(S) = v(\{D_{i,j}\})$, then $\phi_{i,j}(D_{\mathbb{N}}, v) = v(\{D_{i,j}\})$.
- Client-level symmetry (SYM-C): For any two clients i_1, i_2 , if for any subset of the other clients $\mathcal{C} \subseteq \mathbb{N} \setminus \{i_1, i_2\}$, we have $v(D_{\mathcal{C}} \cup D_{i_1}) = v(D_{\mathcal{C}} \cup D_{i_2})$, then we have $\phi_{i_1}(D_{\mathbb{N}}, v) = \phi_{i_2}(D_{\mathbb{N}}, v)$.
- Inner Block-level symmetry (SYM-IB): For any client *i*, if for any two data blocks D_{i,j_1}, D_{i,j_2} , and for any subset of their other blocks $S \subseteq D_i \setminus \{D_{i,j_1}, D_{i,j_2}\}$, we have $v(S \cup \{D_{i,j_1}\}) = v(S \cup \{D_{i,j_2}\})$, then we have $\phi_{i,j_1}(D_{\mathbb{N}}, v) = \phi_{i,j_2}(D_{\mathbb{N}}, v)$.

DUM-C and SYM-C are variants of DUM and SYM tailored for client-level data valuation, ensuring a fair allocation of client-level data values among all clients. Similarly, DUM-IB and SYM-IB are variants of DUM and SYM specific for block-level data valuation, ensuring a fair distribution of block-level data values among a single client's data blocks. More importantly, Truth-Shapley uniquely satisfies EFF, LIN, DUM-C, DUM-IB, SYM-C, and SYM-IB, highlighting its distinctiveness among all BIC data valuation metrics.

Theorem 4.6. Truth-Shapley is the unique data valuation metric that satisfies EFF, LIN, DUM-C, DUM-IB, SYM-C, and SYM-IB.

5 Experiments

Research questions. We conduct experiments to answer the following questions: Is the generalized data overvaluation attack effective against various data valuation metrics? When the attack occurs, how do the metrics perform in reward allocation and data selection?

Table 3: Performance of data valuation metrics on the data selection task where data blocks with sufficient contribution rate are selected. The suffix (o/v) denotes that the valuation metric has undergone a data overvaluation attack. If the model accuracy decreases after the attack, we highlight it in bold.

Valuation Metric		HFL (F	edAVG)		VFL (SplitNN)				HyFL (FedMD)			
	2%	moc 4%	lel accur 6%	racy (%) 8%	when s 2%	electing 4%	blocks 6%	with co 8%	ntributio 2%	on rate 4%	>=6%	8%
SV SV (o/v)	$91.37 \\ 91.80$	$91.76 \\ 91.88$	93.01 91.04	93.23 88.73	71.82 71.44	71.95 71.51	72.22 71.49	72.26 70.99	72.01 72.05	72.10 71.97	72.12 70.69	71.88 70.3 5
LOO LOO (o/v)	91.73 89.09	91.97 88.85	92.73 88.90	92.87 88.49	$69.88 \\ 70.17$	70.45 69.88	70.32 69.52	70.29 69.16	72.90 70.99	72.96 69.46	73.00 69.20	73.03 69.11
BV BV (o/v)	94.23 92.70	94.21 92.67	94.29 92.53	94.03 92.14	71.82 71.97	72.24 71.76	72.26 71.77	72.06 71.16	$73.18 \\ 73.30$	73.41 73.05	73.19 72.96	72.97 72.77
BSV BSV (o/v)	$91.37 \\ 91.37$	$91.36 \\ 91.38$	91.80 91.77	92.06 91.04	71.30 71.30	71.77 71.77	$71.94 \\ 71.94$	72.21 72.21	$71.92 \\ 71.92$	72.01 72.01	72.03 72.03	$71.68 \\ 71.68$
TSV TSV (o/v)	91.39 91.39	$91.76 \\ 91.76$	92.48 92.48	92.04 92.04	71.98 71.98	72.14 72.14	72.17 72.17	$71.85 \\ 71.85$	$71.99 \\ 71.99$	72.10 72.10	72.07 72.07	72.08 72.08

Baselines. We include four SOTA linear data valuation metrics as baselines: the SV, the LOO, Beta Shapley (BSV) (Kwon & Zou, 2022), and Banzhaf value (BV) (Wang & Jia, 2023). All of these metrics satisfy LIN, making the data overvaluation attack applicable to them. For Beta Shapley, parameters for the beta distribution need to be specified; we select the Beta(4, 1) distribution, which demonstrates good performance in the original paper.

Datasets, CML algorithms & models. We use the Apartments for Rent (apa, 2019), Bank Marketing (Moro et al., 2014), and CDC Healthcare (CDC, 2015) datasets for horizontal federated learning (HFL, using the FedAVG algorithm (McMahan et al., 2017)), vertical federated learning (VFL, using the SplitNN algorithm (Gupta & Raskar, 2018)), and hybrid federated learning (HyFL, using the FedMD algorithm (Li & Wang, 2019)), respectively. HFL allows clients to have data with different sample spaces, VFL allows different feature spaces, and HyFL permits both to differ. Each dataset is partitioned into 11 to 12 data blocks based on its content and assigned to three clients for CML. Then, the clients run one round of the CML algorithm to train $\mathcal{A}(D_{\mathbb{N}})$ and then evaluate each data subset for data valuation. More details can be found in Appendix A.

Implementation of data overvaluation. We conduct 90 experimental runs, where in each run, we randomly select a client *i* to perform the generalized data overvaluation attack. In HFL, for all $S \subset D_{\mathbb{N}}$, $i \in \mathbb{N}(S)$, when $\beta_i(S) > 0$ while $\beta_{-i}(S) \leq 0$, client *i* reports $\widehat{D}_i^S = D_i$ to increase v(S); when $\beta_i(S) < 0$ while $\beta_{-i}(S) \geq 0$, client *i* performs data poisoning over D_i^S to decrease v(S). In VFL and HyFL, since it is difficult to increase v(S) by augmenting D_i^S , client *i* only poisons D_i^S when $\beta_i(S) < 0$ and $\beta_{-i}(S) \geq 0$.

5.1 Reward Allocation

Table 1 presents the performance of various data valuation metrics in the reward allocation task. Since the reward of client *i* depends on both client *i*'s empirical data value $\hat{\phi}_i$ and the sum of the other clients' data values $\hat{\phi}_{-i}$, we measure the impact of the data overvaluation attack on reward allocation by assessing the *increase in* $\hat{\phi}_i$ and the *decrease in* $\hat{\phi}_{-i}$ caused by the attack. Additionally, we compute the *valuation error*, defined as the normalized mean squared error between the vectors $[\hat{\phi}_1, \ldots, \hat{\phi}_N]$ and $[\phi_1, \ldots, \phi_N]$, to measure the robustness of different data valuation metrics against data overvaluation.

In HFL, Truth-Shapley is completely resistant to the data overvaluation attack, whereas other data valuation metrics are significantly affected. For SV, BV, and BSV, data overvaluation not only increases the attacker's data value $\hat{\phi}_i$ but also substantially reduces the total data value $\hat{\phi}_{-i}$ of other clients. Notably, since SV satisfies the EFF axiom, the increase in $\hat{\phi}_i$ is exactly equal to the decrease in $\hat{\phi}_{-i}$. However, in both the VFL and HyFL scenarios, the effect of data overvaluation is relatively weaker. This is because, in these CML settings, the feature heterogeneity of data blocks limits the opportunities for data overvaluation. Specifically, when $\beta_i(S) > 0$ and $\beta_{-i}(S) \leq 0$, it is difficult to augment \hat{D}_i^S using other data blocks to enhance v(S); instead, data overvaluation is only achieved through data poisoning when $\beta_i(S) < 0$ and $\beta_{-i}(S) \geq 0$. In particular, data overvaluation fails entirely against BSV because there is no subset S satisfying $\beta_i(S) < 0$ and $\beta_{-i}(S) \geq 0$.

Overall, data overvaluation can significantly impact reward allocation outcomes, and only Truth-Shapley can fully prevent such an attack. Although BSV also performs well in VFL and HyFL settings, its performance in HFL reveals a potential vulnerability: it may still be possible to bypass BSV's defense by implementing data augmentation when $\beta_i(S) > 0$ and $\beta_{-i}(S) \leq 0$.

5.2 Data Selection

For data selection, we evaluate data valuation metrics based on two selection criteria. In Table 2, we perform CML using the top K data blocks ranked by their data values. In Table 3, we calculate the contribution rate of each data block, defined as the ratio of its block-level data value to the sum of all data blocks' data values. Only data blocks with a contribution rate no less than a predefined threshold are selected for CML.

As shown in Tables 2 and 3, in HFL, data overvaluation attacks against Truth-Shaply cannot affect the model accuracy at all, as it can fully resist such attacks. In contrast, under other data valuation metrics, since data overvaluation significantly alters both the absolute values of block-level data values and their relative rankings, the model accuracy declines significantly in most cases. Additionally, in VFL and HyFL, the situation is generally similar, except in the case of BSV, where data overvaluation does not succeed as shown in Table 1.

In summary, under data valuation metrics that do not satisfy BIC, the data overvaluation attack can significantly impact data selection outcomes. This not only harms model accuracy but also leads to unfair opportunities for participating in CML, indirectly affecting clients' potential rewards. Notably, even in the absence of the attack, Truth-Shapley remains as effective as other metrics in selecting data blocks.

6 Discussion

Poisoning attacker. Assumption 4.2 is the core assumption of this paper, which implicitly assumes that the attacker's dataset D_i is not a poisoning dataset. This assumption is based on the premise that client *i* aims to maximize their reward and thus will not poison the grand model $\mathcal{A}(D_{\mathbb{N}})$, as doing so would reduce the reward derived from monetizing/utilizing $\mathcal{A}(D_{\mathbb{N}})$. However, in certain scenarios, client *i* may pursue dual objectives: both attacking the grand model and conducting data overvaluation. Addressing this dual-objective scenario requires further exploration.

Computational efficiency. Similar to computing the SV, computing Truth-Shapley is time-consuming, as it requires $O(2^{N+\max_i M_i})$ times of model retraining. Since Truth-Shapley utilizes the SV-style approach to define both its client-level data value and block-level data value, existing techniques for accelerating SV computation can be applied to computing these two levels of data value. Also, designing more efficient acceleration methods specifically for Truth-Shapley is a promising direction for future research.

Extension of data overvaluation attack. The data overvaluation attack proposed in Definition 3.2 allows client i to manipulate the utility v(S) of a data subset $S \subset D_{\mathbb{N}}$ by misreporting client i's data blocks \widehat{D}_i^S . Similarly, client i can achieve the same objective by violating the training algorithm \mathcal{A} . For example, client i can decrease v(S) by performing a gradient ascent attack during model training. Truth-Shapley remains resistant to this extension of data overvaluation attack with a slight modification to Assumption 4.2: we assume that, in client i's belief, following algorithm \mathcal{A} maximizes the expected utility for any $S \subset D_{\mathbb{N}}$.

7 Related Work

Most of existing studies designed data valuation methods for CML based on two data valuation metrics: LOO (Cook, 1977) and the SV (Shapley, 1953). Since computing these metrics usually requires evaluating the model utilities for a large number of data subsets, substantial research efforts have been devoted to improving the efficiency of the computation. Their approaches include downsampling data subsets Ghorbani & Zou (2019); Jia et al. (2019b); Luo et al. (2024, 2022); Lin et al. (2022); Jia et al. (2019a); Kwon et al. (2021), designing training-free utility functions (Wang et al., 2024a; Pruthi et al., 2020; Koh & Liang, 2017), and approximating retrained models (Wu et al., 2022; Just et al., 2023; Nohyun et al., 2022).

Another line of research focuses on enhancing the robustness and reliability of data valuation. Xu et al. (2021) designed a new utility function that is more robust to clients' data replication behavior. Lin et al. (2024) provided a validation-free utility function for clients without a joinly-agreed validation dataset. Some studies (Schoch et al., 2022; Xu et al., 2024; Xia et al., 2024) have designed utility functions that capture a model's predictive capability at a finer granularity than prediction accuracy. Tian et al. (2024) and Xia et al. (2023) proposed methods to accelerate recomputing data values in machine unlearning scenarios. Zheng et al. (2023) and Wang et al. (2024b) proposed methods to ensure privacy and security in data valuation. Wang et al. (2023) introduced the Banzhaf value as a data valuation metric, which is robust to the randomness of model retraining. Kwon et al. (2022) extended the SV to Beta Shapley, improving the detection of noisy data points. Our work reveals a new vulnerability in data valuation, i.e., data overvaluation, and proposes Truth-Shapley to enhance robustness/reliability against data overvaluation.

8 Conclusion

This paper introduces the first data overvaluation attack in CML scenarios. We characterized the subclass of linear and BIC data valuation metrics that can resist this attack and selected Truth-Shapley from the subclass as a promising solution to truthful data valuation. Through both theoretical analysis and empirical experiments, we demonstrated the vulnerability of existing linear data valuation metrics to data overvaluation and the robustness and effectiveness of Truth-Shapley. In addition to the research opportunities discussed in Section 6, there remains substantial room for further exploration in data overvaluation and truthful data valuation. Potential directions include developing new data overvaluation strategies, designing tailored algorithms for implementing data overvaluation in specific CML scenarios, and constructing defense mechanisms compatible with those vulnerable data valuation metrics.

Impact Statement

For the industry, this paper identifies a new attack method that poses a trust crisis for data valuation in CML. For the academia, this paper opens up a new research direction: truthful data valuation for CML.

References

Apartment for Rent Classified. UCI Machine Learning Repository, 2019. DOI: https://doi.org/10.24432/C5X623.

- CDC. Diabetes Health Indicators Dataset, 2015. https://www.kaggle.com/datasets/alexteboul/diabetes-health-indicators-dataset.
- Cohen, S. B., Dror, G., and Ruppin, E. Feature selection based on the shapley value. In *Proceedings of IJCAI*, pp. 1–6, 2005.
- Cook, R. D. Detection of influential observation in linear regression. *Technometrics*, 19(1):15–18, 1977.
- d'Aspremont, C. and Gérard-Varet, L.-A. Bayesian incentive compatible beliefs. *Journal of Mathematical Economics*, 10 (1):83–103, 1982.
- Ghorbani, A. and Zou, J. Data shapley: Equitable valuation of data for machine learning. In *International conference on machine learning*, pp. 2242–2251. PMLR, 2019.
- Gupta, O. and Raskar, R. Distributed learning of deep neural network over multiple agents. *Journal of Network and Computer Applications*, 116:1–8, 2018.
- Jia, R., Dao, D., Wang, B., Hubis, F. A., Gurel, N. M., Li, B., Zhang, C., Spanos, C., and Song, D. Efficient task-specific data valuation for nearest neighbor algorithms. *Proceedings of the VLDB Endowment*, 12(11):1610–1623, 2019a.
- Jia, R., Dao, D., Wang, B., Hubis, F. A., Hynes, N., Gürel, N. M., Li, B., Zhang, C., Song, D., and Spanos, C. J. Towards efficient data valuation based on the shapley value. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pp. 1167–1176. PMLR, 2019b.
- Just, H. A., Kang, F., Wang, T., Zeng, Y., Ko, M., Jin, M., and Jia, R. LAVA: Data valuation without pre-specified learning algorithms. In *The Eleventh International Conference on Learning Representations*, 2023.
- Koh, P. W. and Liang, P. Understanding black-box predictions via influence functions. In International conference on machine learning, pp. 1885–1894. PMLR, 2017.
- Kwon, Y. and Zou, J. Beta shapley: a unified and noise-reduced data valuation framework for machine learning. In International Conference on Artificial Intelligence and Statistics, pp. 8780–8802. PMLR, 2022.
- Kwon, Y., Rivas, M. A., and Zou, J. Efficient computation and analysis of distributional shapley values. In International Conference on Artificial Intelligence and Statistics, pp. 793–801. PMLR, 2021.
- Li, D. and Wang, J. Fedmd: Heterogenous federated learning via model distillation. arXiv preprint arXiv:1910.03581, 2019.
- Lin, J., Zhang, A., Lécuyer, M., Li, J., Panda, A., and Sen, S. Measuring the effect of training data on deep learning predictions via randomized experiments. In *International Conference on Machine Learning*, pp. 13468–13504. PMLR, 2022.

- Lin, X., Xu, X., Wu, Z., Ng, S.-K., and Low, B. K. H. Distributionally robust data valuation. In Proceedings of the 41st International Conference on Machine Learning, 2024.
- Luo, X., Pei, J., Cong, Z., and Xu, C. On shapley value in data assemblage under independent utility. Proceedings of the VLDB Endowment, 15(11):2761–2773, 2022.
- Luo, X., Pei, J., Xu, C., Zhang, W., and Xu, J. Fast shapley value computation in data assemblage tasks as cooperative simple games. *Proceedings of the ACM on Management of Data*, 2(1):1–28, 2024.
- McMahan, B., Moore, E., Ramage, D., Hampson, S., and y Arcas, B. A. Communication-efficient learning of deep networks from decentralized data. In Artificial intelligence and statistics, pp. 1273–1282, 2017.
- Moro, S., Cortez, P., and Rita, P. Bank Marketing. UCI Machine Learning Repository, 2014. DOI: https://doi.org/10.24432/C5K306.
- Nagalapatti, L. and Narayanam, R. Game of gradients: Mitigating irrelevant clients in federated learning. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 35, pp. 9046–9054, 2021.
- Nguyen, Q. P., Low, B. K. H., and Jaillet, P. Trade-off between payoff and model rewards in shapley-fair collaborative machine learning. *Advances in Neural Information Processing Systems*, 35:30542–30553, 2022.
- Nohyun, K., Choi, H., and Chung, H. W. Data valuation without training of a model. In *The Eleventh International Conference on Learning Representations*, 2022.
- Pruthi, G., Liu, F., Kale, S., and Sundararajan, M. Estimating training data influence by tracing gradient descent. Advances in Neural Information Processing Systems, 33:19920–19930, 2020.
- Schoch, S., Xu, H., and Ji, Y. Cs-shapley: class-wise shapley values for data valuation in classification. Advances in Neural Information Processing Systems, 35:34574–34585, 2022.
- Shapley, L. S. A value for n-person games. Contribution to the Theory of Games, 2, 1953.
- Sim, R. H. L., Zhang, Y., Chan, M. C., and Low, B. K. H. Collaborative machine learning with incentive-aware model rewards. In *International conference on machine learning*, pp. 8927–8936. PMLR, 2020.
- Tian, X., Sim, R. H. L., Fan, J., and Low, B. K. H. Derdava: Deletion-robust data valuation for machine learning. In Proceedings of the AAAI Conference on Artificial Intelligence, volume 38, pp. 15373–15381, 2024.
- Wang, J., Lin, X., Qiao, R., Foo, C.-S., and Low, B. K. H. Helpful or harmful data? fine-tuning-free shapley attribution for explaining language model predictions. In *Proceedings of the 41st International Conference on Machine Learning*, 2024a.
- Wang, J. T. and Jia, R. Data banzhaf: A robust data valuation framework for machine learning. In International Conference on Artificial Intelligence and Statistics, pp. 6388–6421. PMLR, 2023.
- Wang, J. T., Zhu, Y., Wang, Y.-X., Jia, R., and Mittal, P. A privacy-friendly approach to data valuation. Advances in Neural Information Processing Systems, 36, 2024b.
- Wu, Z., Shu, Y., and Low, B. K. H. Davinz: Data valuation using deep neural networks at initialization. In International Conference on Machine Learning, pp. 24150–24176. PMLR, 2022.
- Xia, H., Liu, J., Lou, J., Qin, Z., Ren, K., Cao, Y., and Xiong, L. Equitable data valuation meets the right to be forgotten in model markets. *Proceedings of the VLDB Endowment*, 16(11):3349–3362, 2023.
- Xia, H., Li, X., Pang, J., Liu, J., Ren, K., and Xiong, L. P-shapley: Shapley values on probabilistic classifiers. Proceedings of the VLDB Endowment, 17(7):1737–1750, 2024.
- Xu, X., Wu, Z., Foo, C. S., and Low, B. K. H. Validation free and replication robust volume-based data valuation. Advances in Neural Information Processing Systems, 34:10837–10848, 2021.
- Xu, X., Lam, T., Foo, C. S., and Low, B. K. H. Model shapley: equitable model valuation with black-box access. Advances in Neural Information Processing Systems, 36, 2024.
- Zheng, S., Cao, Y., and Yoshikawa, M. Secure shapley value for cross-silo federated learning. Proceedings of the VLDB Endowment, 16(7):1657–1670, 2023.

			Table 4: Settings	of three	CML scenarios.				
CML CML		Dataset	Client 1		Client 2		Client 3		
\mathbf{type}	algorithm	Dataset	data blocks data s		data blocks	data size	data blocks	data size	
HFL	FedAVG	Apartments for Rent	 (1) Northeast, (2) Mid-Atlantic, (3) Southeast, (4) East Central 	4215	 (1) Great Lakes, (2) Midwest Palins, (3) Central Plains, (4) Southern Plains 	1722	 Mountain States, Northwest, Pacific Coast, Southwest 	2063	
VFL	SplitNN	Bank Marketing	 (1) age, (2) job, (3) marital, (4) education 	8000	(1) default,(2) balance,(3) housing,(4) loan	8000	 (1) contact, (2) day_of_week, month (3) campaign, pdays, previous (4) poutcome 	8000	
HyFL	FedMD	CDC	 (1) Sex, Age, Education, Income, AnyHealthcare, NoDocbcCost, (2) Smoker, HvyAlcoholConsump, (3) PhysActivity, DiffWalk, (4) Fruits, Veggies 	2666	 Sex, Age, Education, Income, AnyHealthcare, NoDocbcCost, highBP, highChol, CholCheck, Stroke, HeartDiseaseorAttack 	2666	 (1) Sex, Age, Education, Income, AnyHealthcare, NoDocbcCost, (2) GenHlth, MentHlth, PhysHlth (3) BMI 	2666	

A Experimental Setup

As shown in Table 4, we perform data valuation in the following three CML scenarios.

- Horizontal federated learning (HFL): In HFL, clients possess data blocks with the same feature space but different sample spaces. In this scenario, we use the *Apartments for Rent* dataset (apa, 2019), which contains rental data from various states. We assume three regional rental companies as clients and divide the dataset into 12 data blocks based on the geographic regions of the apartments in the US, assigning these blocks to the clients. These clients utilize the FedAVG algorithm (McMahan et al., 2017) to perform HFL, collaboratively training a multilayer perceptron (MLP) to predict rental prices.
- Vertical federated learning (VFL): In VFL, clients possess different features of the same samples. We use the *Bank Marketing* dataset (Moro et al., 2014) and partition its features into 12 data blocks based on their content, assigning them to three finance-related companies as clients. These clients then perform VFL using the split learning algorithm Gupta & Raskar (2018) to train a SplitNN-based binary classification model for target customer detection.
- Hybrid federated learning (HyFL): HyFL allows clients to have data with both different sample spaces and feature spaces. We consider three medical institutions as clients, each with a non-overlapping patient group and distinct diagnostic tests. They own 11 data blocks from the *CDC* medical dataset (CDC, 2015), where each data block contains patient data related to a specific diagnostic test at a particular institution. These institutions use the FedMD algorithm (Li & Wang, 2019) to collaboratively train an MLP-based ensemble model for diabetes prediction.

B Proofs

Proof of Lemma 3.1. For every data subset $\mathcal{S} \subseteq D_{\mathbb{N}}$, we define the basis game $\delta_{\mathcal{S}}(T) = by$

$$\delta_{\mathcal{S}}(T) = \begin{cases} 1, & T = S, \\ 0, & T \neq S. \end{cases}$$

The set $\{\delta_{\mathcal{S}} \mid \mathcal{S} \subseteq D_{\mathbb{N}}\}\$ is a natural basis for $\mathcal{G}(D_{\mathbb{N}})$. Then, consider a linear data valuation metric $\phi(D_{\mathbb{N}}, v)$. For any two utility functions v_1 and v_2 and scalars $w_1, w_2 \in \mathbb{R}$, we have:

$$\phi_i(D_{\mathbb{N}}, w_1v_1 + w_2v_2) = w_1\phi_i(D_{\mathbb{N}}, v_1) + w_2\phi_i(D_{\mathbb{N}}, v_2).$$

Therefore, $\phi_i(D_{\mathbb{N}}, \cdot) : \mathcal{G}(D_{\mathbb{N}}) \to \mathbb{R}$ is a linear functional on the vector space $\mathcal{G}(D_{\mathbb{N}})$. Then, because any utility function $v \in \mathcal{G}(D_{\mathbb{N}})$ can be written as $v = \sum_{\mathcal{S} \subseteq D_{\mathbb{N}}} v(\mathcal{S}) \cdot \delta_{\mathcal{S}}$, we have:

$$\phi_i(D_{\mathbb{N}}, v) = \phi_i(D_{\mathbb{N}}, \sum_{\mathcal{S} \subseteq D_{\mathbb{N}}} v(\mathcal{S}) \cdot \delta_{\mathcal{S}}) = \sum_{\mathcal{S} \subseteq D_{\mathbb{N}}} v(\mathcal{S}) \cdot \phi_i(D_{\mathbb{N}}, \delta_{\mathcal{S}}).$$

By defining $\beta_i(\mathcal{S}) \coloneqq \phi_i(D_{\mathbb{N}}, \delta_{\mathcal{S}})$, we conclude that Lemma 3.1 is true.

Proof of Lemma 3.3. According to Definition 3.2, under a data overvaluation attack, we have

$$\begin{split} \widehat{\phi}_{i}(D_{\mathbb{N}},v) &= \beta_{i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{S \subset D_{\mathbb{N}}} \beta_{i}(S) \cdot v(\widehat{S}) \\ &= \beta_{i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{S \subset D_{\mathbb{N}}, \beta_{i}(S) > 0, \beta_{-i}(S) \leq 0} \beta_{i}(S) \cdot v(\widehat{S}) + \sum_{S \subset D_{\mathbb{N}}, \beta_{i}(S) > 0, \beta_{-i}(S) > 0} \beta_{i}(S) \cdot v(\widehat{S}) \\ &+ \sum_{S \subset D_{\mathbb{N}}, \beta_{i}(S) > 0, \beta_{-i}(S) > 0} \beta_{i}(S) \cdot v(\widehat{S}) + \sum_{S \subset D_{\mathbb{N}}, \beta_{i}(S) \leq 0, \beta_{-i}(S) \leq 0} \beta_{i}(S) \cdot v(\widehat{S}) \\ &\geq \beta_{i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{S \subset D_{\mathbb{N}}, \beta_{i}(S) > 0, \beta_{-i}(S) \leq 0} \beta_{i}(S) \cdot v(D_{i}^{S} \cup \widehat{D}_{-i}^{S}) + \sum_{S \subset D_{\mathbb{N}}, \beta_{i}(S) > 0, \beta_{-i}(S) > 0} \beta_{i}(S) \cdot v(D_{i}^{S} \cup \widehat{D}_{-i}^{S}) \\ &+ \sum_{S \subset D_{\mathbb{N}}, \beta_{i}(S) > 0, \beta_{-i}(S) > 0} \beta_{i}(S) \cdot v(D_{i}^{S} \cup \widehat{D}_{-i}^{S}) + \sum_{S \subset D_{\mathbb{N}}, \beta_{i}(S) \leq 0, \beta_{-i}(S) \leq 0} \beta_{i}(S) \cdot v(D_{i}^{S} \cup \widehat{D}_{-i}^{S}) \\ &= \beta_{i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{S \subset D_{\mathbb{N}}} \beta_{i}(S) \cdot v(D_{i}^{S} \cup \widehat{D}_{-i}^{S}) = \widehat{\phi}_{i}(D_{\mathbb{N}}, v \mid \forall S \subset D_{\mathbb{N}}, \widehat{D}_{i}^{S} = D_{i}^{S}). \end{split}$$

Similarly, under a data overvaluation attack, we have

$$\begin{split} \widehat{\phi}_{-i}(D_{\mathbb{N}},v) &= \beta_{-i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}}} \beta_{-i}(\mathcal{S}) \cdot v(\widehat{\mathcal{S}}) \\ &= \beta_{-i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}},\beta_{i}(\mathcal{S}) > 0,\beta_{-i}(\mathcal{S}) \leq 0} \beta_{-i}(\mathcal{S}) \cdot v(\widehat{\mathcal{S}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}},\beta_{i}(\mathcal{S}) \leq 0,\beta_{-i}(\mathcal{S}) > 0} \beta_{-i}(\mathcal{S}) \cdot v(\widehat{\mathcal{S}}) \\ &+ \sum_{\mathcal{S} \subset D_{\mathbb{N}},\beta_{i}(\mathcal{S}) > 0,\beta_{-i}(\mathcal{S}) > 0} \beta_{-i}(\mathcal{S}) \cdot v(\widehat{\mathcal{S}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}},\beta_{i}(\mathcal{S}) \leq 0,\beta_{-i}(\mathcal{S}) \leq 0} \beta_{-i}(\mathcal{S}) \cdot v(\widehat{\mathcal{S}}) \\ &\leq \beta_{-i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}},\beta_{i}(\mathcal{S}) > 0,\beta_{-i}(\mathcal{S}) \leq 0} \beta_{-i}(\mathcal{S}) \cdot v(D_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}},\beta_{i}(\mathcal{S}) \geq 0,\beta_{-i}(\mathcal{S}) > 0} \beta_{-i}(\mathcal{S}) \cdot v(D_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}}) \\ &+ \sum_{\mathcal{S} \subset D_{\mathbb{N}},\beta_{i}(\mathcal{S}) > 0,\beta_{-i}(\mathcal{S}) > 0} \beta_{-i}(\mathcal{S}) \cdot v(D_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}},\beta_{i}(\mathcal{S}) \leq 0,\beta_{-i}(\mathcal{S}) \leq 0} \beta_{-i}(\mathcal{S}) \cdot v(D_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}}) \\ &= \beta_{-i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}}} \beta_{-i}(\mathcal{S}) \cdot v(D_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}}) = \widehat{\phi}_{-i}(D_{\mathbb{N}}, v \mid \forall \mathcal{S} \subset D_{\mathbb{N}}, \widehat{D}_{i}^{\mathcal{S}} = D_{i}^{\mathcal{S}}). \end{split}$$

Proof of Theorem 4.3. \Rightarrow : Under Assumption 4.2, for any game $(D_{\mathbb{N}}, v)$, for any client *i*, and for any reported data subsets $\{\widehat{D}_{i}^{\mathcal{S}} \mid \mathcal{S} \subset D_{\mathbb{N}}, i \in \mathbb{N}(\mathcal{S})\}$, we have

$$\begin{split} \mathbb{E}[\widehat{\phi}_{i}(D_{\mathbb{N}},v)] &= \beta_{i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}}} \beta_{i}(\mathcal{S}) \cdot \mathbb{E}[v(\widehat{D}_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}})] \\ &= \beta_{i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}}, D_{i}^{\mathcal{S}} = D_{i}} \beta_{i}(\mathcal{S}) \cdot \mathbb{E}[v(\widehat{D}_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}})] + \sum_{\mathcal{S} \subset D_{\mathbb{N}}, D_{i}^{\mathcal{S}} \neq D_{i}} \beta_{i}(\mathcal{S}) \cdot \mathbb{E}[v(\widehat{D}_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}})] \\ &= \beta_{i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}}, D_{i}^{\mathcal{S}} = D_{i}} \beta_{i}(\mathcal{S}) \cdot \mathbb{E}[v(D_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}})] \\ &\leq \beta_{i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}}, D_{i}^{\mathcal{S}} = D_{i}} \beta_{i}(\mathcal{S}) \cdot \mathbb{E}[v(D_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}})] \\ &= \beta_{i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{S} \subset D_{\mathbb{N}}, D_{i}^{\mathcal{S}} = D_{i}} \beta_{i}(\mathcal{S}) \cdot \mathbb{E}[v(D_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}})] + \sum_{\mathcal{S} \subset D_{\mathbb{N}}, D_{i}^{\mathcal{S}} \neq D_{i}} \beta_{i}(\mathcal{S}) \cdot \mathbb{E}[v(D_{i}^{\mathcal{S}} \cup \widehat{D}_{-i}^{\mathcal{S}})] \\ &= \mathbb{E}[\widehat{\phi}_{i}(D_{\mathbb{N}}, v \mid \forall \mathcal{S} \subset D_{\mathbb{N}}, \widehat{D}_{i}^{\mathcal{S}} = D_{i}^{\mathcal{S}})]. \end{split}$$

Similarly, under Assumption 4.2, for any game $(D_{\mathbb{N}}, v)$, for any client *i*, and for any reported data subsets $\{\widehat{D}_i^{\mathcal{S}} \mid \mathcal{S} \subset D_{\mathbb{N}}, i \in \mathbb{N}(\mathcal{S})\}$, we have

$$\begin{split} \mathbb{E}[\widehat{\phi}_{-i}(D_{\mathbb{N}},v)] &= \beta_{-i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{S \subseteq D_{\mathbb{N}}} \beta_{-i}(S) \cdot \mathbb{E}[v(\widehat{D}_{i}^{S} \cup \widehat{D}_{-i}^{S})] \\ &= \beta_{-i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{S \subseteq D_{\mathbb{N}}, D_{i}^{S} = D_{i}} \beta_{-i}(S) \cdot \mathbb{E}[v(\widehat{D}_{i}^{S} \cup \widehat{D}_{-i}^{S})] + \sum_{S \subseteq D_{\mathbb{N}}, D_{i}^{S} \neq D_{i}} \beta_{-i}(S) \cdot \mathbb{E}[v(\widehat{D}_{i}^{S} \cup \widehat{D}_{-i}^{S})] \\ &= \beta_{-i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{S \subseteq D_{\mathbb{N}}, D_{i}^{S} = D_{i}} \beta_{-i}(S) \cdot \mathbb{E}[v(D_{i}^{S} \cup \widehat{D}_{-i}^{S})] \\ &\geq \beta_{-i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{S \subseteq D_{\mathbb{N}}, D_{i}^{S} = D_{i}} \beta_{-i}(S) \cdot \mathbb{E}[v(D_{i}^{S} \cup \widehat{D}_{-i}^{S})] \\ &= \beta_{-i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{S \subseteq D_{\mathbb{N}}, D_{i}^{S} = D_{i}} \beta_{-i}(S) \cdot \mathbb{E}[v(D_{i}^{S} \cup \widehat{D}_{-i}^{S})] + \sum_{S \subseteq D_{\mathbb{N}}, D_{i}^{S} \neq D_{i}} \beta_{-i}(S) \cdot \mathbb{E}[v(D_{i}^{S} \cup \widehat{D}_{-i}^{S})] \\ &= \mathbb{E}[\widehat{\phi}_{-i}(D_{\mathbb{N}}, v \mid \forall S \subseteq D_{\mathbb{N}}, \widehat{D}_{i}^{S} = D_{i}^{S})]. \end{split}$$

 $\Leftarrow: \text{ If } \exists \mathcal{S} \subset D_{\mathbb{N}} \text{ such that if } D_{i}^{\mathcal{S}} = D_{i}, \text{ we have } \beta_{i}(\mathcal{S}) < 0, \text{ or such that if } D_{i}^{\mathcal{S}} \neq D_{i}, \text{ we have } \beta_{i}(\mathcal{S}) \neq 0, \text{ we can always construct a utility function } v \text{ such that } \mathbb{E}[\widehat{\phi}_{i}(D_{\mathbb{N}}, v)] > \mathbb{E}[\widehat{\phi}_{i}(D_{\mathbb{N}}, v \mid \forall \mathcal{S} \subset D_{\mathbb{N}}, \widehat{D}_{i}^{\mathcal{S}} = D_{i}^{\mathcal{S}})]. \text{ Also, if } \exists \mathcal{S} \subset D_{\mathbb{N}} \text{ such that if } D_{i}^{\mathcal{S}} = D_{i}, \text{ we have } \beta_{-i}(\mathcal{S}) > 0, \text{ or such that if } D_{i}^{\mathcal{S}} \neq D_{i}, \text{ we have } \beta_{-i}(\mathcal{S}) \neq 0, \text{ we can always construct a utility function } v \text{ such that } \mathbb{E}[\widehat{\phi}_{-i}(D_{\mathbb{N}}, v \mid \forall \mathcal{S} \subset D_{\mathbb{N}}, \widehat{D}_{i}^{\mathcal{S}} = D_{i}^{\mathcal{S}})].$

Proof of Theorem 4.4. \Rightarrow : Under Assumption 4.2, for any game $(D_{\mathbb{N}}, v)$, for any client *i*, and for any reported data subsets $\{\widehat{D}_{i}^{\mathcal{S}} \mid \mathcal{S} \subset D_{\mathbb{N}}, i \in \mathbb{N}(\mathcal{S})\}$, we have

$$\mathbb{E}[\widehat{\phi}_{i}(D_{\mathbb{N}}, v)] = \beta_{i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{C} \subset \mathbb{N}} \beta_{i}(D_{\mathcal{C}}) \cdot \mathbb{E}[v(\widehat{D}_{\mathcal{C}})]$$

$$= \beta_{i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{C} \subset \mathbb{N}, i \in \mathcal{C}} \beta_{i}(D_{\mathcal{C}}) \cdot \mathbb{E}[v(\widehat{D}_{\mathcal{C}})] + \sum_{\mathcal{C} \subset \mathbb{N}, i \notin \mathcal{C}} \beta_{i}(D_{\mathcal{C}}) \cdot \mathbb{E}[v(\widehat{D}_{\mathcal{C}})]$$

$$\leq \beta_{i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{C} \subset \mathbb{N}, i \in \mathcal{C}} \beta_{i}(D_{\mathcal{C}}) \cdot \mathbb{E}[v(D_{i} \cup (\cup_{i' \in \mathcal{C} \setminus \{i\}} \widehat{D}_{i'}))] + \sum_{\mathcal{C} \subset \mathbb{N}, i \notin \mathcal{C}} \beta_{i}(D_{\mathcal{C}}) \cdot \mathbb{E}[v(\widehat{D}_{\mathcal{C}})]$$

$$= \mathbb{E}[\widehat{\phi}_{i}(D_{\mathbb{N}}, v \mid \forall \mathcal{S} \subset D_{\mathbb{N}}, \widehat{D}_{i}^{\mathcal{S}} = D_{i}^{\mathcal{S}})]$$

Because ϕ is efficient, we have $\beta_{-i}(D_{\mathcal{C}}) = -\beta_i(D_{\mathcal{C}})$ for all $\mathcal{C} \subset \mathbb{N}$. Therefore, under Assumption 4.2, for any game $(D_{\mathbb{N}}, v)$, for any client *i*, and for any reported data subsets $\{\widehat{D}_i^{\mathcal{S}} \mid \mathcal{S} \subset D_{\mathbb{N}}, i \in \mathbb{N}(\mathcal{S})\}$, we have

$$\begin{split} \mathbb{E}[\widehat{\phi}_{-i}(D_{\mathbb{N}},v)] &= \beta_{-i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{C} \subset \mathbb{N}} \beta_{-i}(D_{\mathcal{C}}) \cdot \mathbb{E}[v(\widehat{D}_{\mathcal{C}})] \\ &= -\beta_{i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) - \sum_{\mathcal{C} \subset \mathbb{N}, i \in \mathcal{C}} \beta_{i}(D_{\mathcal{C}}) \cdot \mathbb{E}[v(\widehat{D}_{\mathcal{C}})] - \sum_{\mathcal{C} \subset \mathbb{N}, i \notin \mathcal{C}} \beta_{i}(D_{\mathcal{C}}) \cdot \mathbb{E}[v(\widehat{D}_{\mathcal{C}})] \\ &\geq -\beta_{i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) - \sum_{\mathcal{C} \subset \mathbb{N}, i \in \mathcal{C}} \beta_{i}(D_{\mathcal{C}}) \cdot \mathbb{E}[v(D_{i} \cup (\cup_{i' \in \mathcal{C} \setminus \{i\}} \widehat{D}_{i'}))] - \sum_{\mathcal{C} \subset \mathbb{N}, i \notin \mathcal{C}} \beta_{i}(D_{\mathcal{C}}) \cdot \mathbb{E}[v(\widehat{D}_{\mathcal{C}})] \\ &= \beta_{-i}(D_{\mathbb{N}}) \cdot v(D_{\mathbb{N}}) + \sum_{\mathcal{C} \subset \mathbb{N}, i \in \mathcal{C}} \beta_{-i}(D_{\mathcal{C}}) \cdot \mathbb{E}[v(D_{i} \cup (\cup_{i' \in \mathcal{C} \setminus \{i\}} \widehat{D}_{i'}))] + \sum_{\mathcal{C} \subset \mathbb{N}, i \notin \mathcal{C}} \beta_{-i}(D_{\mathcal{C}}) \cdot \mathbb{E}[v(\widehat{D}_{\mathcal{C}})] \\ &= \mathbb{E}[\widehat{\phi}_{-i}(D_{\mathbb{N}}, v \mid \forall \mathcal{S} \subset D_{\mathbb{N}}, \widehat{D}_{i}^{\mathcal{S}} = D_{i}^{\mathcal{S}})] \end{split}$$

 \Leftarrow : According to Theorem 4.3, if a data valuation metric ϕ is linear and BIC, we have

$$\phi_i(D_{\mathbb{N}}, v) = \sum_{\mathcal{S} \subseteq D_{\mathbb{N}}} \beta_i(\mathcal{S}) \cdot v(\mathcal{S}) = \sum_{\mathcal{S} \subseteq D_{\mathbb{N}}, D_i^{\mathcal{S}} = D_i} \beta_i(\mathcal{S}) \cdot v(\mathcal{S})$$

Then, because ϕ is efficient, we have

$$\begin{split} \phi_i(D_{\mathbb{N}}, v) &= \sum_{\mathcal{S} \subseteq D_{\mathbb{N}}, D_i^{\mathcal{S}} = D_i} \beta_i(\mathcal{S}) \cdot v(\mathcal{S}) = \sum_{\mathcal{C} \subseteq \mathbb{N}} \beta_i(D_{\mathcal{C}}) \cdot v(D_{\mathcal{C}}) + \sum_{\mathcal{S} \subseteq D_{\mathbb{N}}, D_i^{\mathcal{S}} = D_i, \exists i' \in \mathbb{N}(\mathcal{S}) \setminus \{i\}, D_{i'}^{\mathcal{S}} \neq D_{i'}} \beta_i(\mathcal{S}) \cdot v(\mathcal{S}) \\ &= \sum_{\mathcal{C} \subseteq \mathbb{N}} \beta_i(D_{\mathcal{C}}) \cdot v(D_{\mathcal{C}}) - \sum_{\mathcal{S} \subseteq D_{\mathbb{N}}, D_i^{\mathcal{S}} = D_i, \exists i' \in \mathbb{N}(\mathcal{S}) \setminus \{i\}, D_{i'}^{\mathcal{S}} \neq D_{i'}} \beta_{-i}(\mathcal{S}) \cdot v(\mathcal{S}) = \sum_{\mathcal{C} \subseteq \mathbb{N}} \beta_i(D_{\mathcal{C}}) \cdot v(D_{\mathcal{C}}), \end{split}$$

where $\beta_i(D_{\mathcal{C}})$ must be non-negative for all $\forall \mathcal{C} \subset \mathbb{N}$ with $i \in \mathcal{C}$ to ensure BIC.

Proof of Theorem 4.5. The client-level TSV can be written as:

$$\phi_i^{TSV}(D_{\mathbb{N}}, v) = \sum_{\mathcal{C} \subseteq \mathbb{N} \setminus \{i\}} w^{SV}(\mathcal{C} \mid \mathbb{N}) \left(v(\mathbb{D}_{\mathcal{C}} \cup \{D_i\}) - v(\mathbb{D}_{\mathcal{C}}) \right) = \sum_{\mathcal{C} \subseteq \mathbb{N}} \beta_i^{TSV}(D_{\mathcal{C}}) \cdot v(D_{\mathcal{C}}),$$

where $\beta_i^{TSV}(D_{\mathcal{C}}) = \begin{cases} w^{SV}(\mathcal{C} \mid \mathbb{N}), & i \notin \mathcal{C}, \\ -w^{SV}(\mathcal{C} \mid \mathbb{N}), & i \in \mathcal{C}. \end{cases}$ Because $\beta_i^{TSV}(D_{\mathcal{C}}) \ge 0$ for all $\mathcal{C} \subset \mathbb{N}$ with $i \in \mathcal{C}$, according to Theorem 4.4, ϕ^{TSV} satisfies BIC.

Proof of Theorem 4.6. Because $\phi_i^{TSV}(D_{\mathbb{N}}, v) = \phi_i^{SV}(\mathbb{D}_{\mathbb{N}}, v)$, according to Theorem 2.2, ϕ_i^{TSV} uniquely satisfies LIN, DUM-C, SYM-C and EFF-C, where EFF-C means $\sum_{i \in \mathbb{N}} \phi_i(D_{\mathbb{N}}, v) = v(D_{\mathbb{N}})$. Then, because $\phi_{i,j}^{TSV}(D_{\mathbb{N}}, v) = \phi_j^{SV}(D_i, v^{\phi_i^{TSV}})$, according to Theorem 2.2, $\phi_{i,j}^{TSV}$ uniquely satisfies LIN, DUM-IB, SYM-IB and EFF-IB, where EFF-IB means $\forall i \in \mathbb{N}, \sum_{j \in [M_i]} \phi_{i,j}(D_{\mathbb{N}}, v) = \phi_i(D_{\mathbb{N}}, v)$. Therefore, ϕ^{TSV} uniquely satisfies EFF, LIN, DUM-C, DUM-IB, SYM-C, and SYM-IB.