A note on Ordered Ruzsa-Szemerédi graphs

Kevin Pratt*

February 5, 2025

Abstract

A recent breakthrough of Behnezhad and Ghafari [BG24] and subsequent work of Assadi, Khanna, and Kiss [AKK25] gave algorithms for the fully dynamic $(1-\varepsilon)$ -approximate maximum matching problem whose runtimes are determined by a purely combinatorial quantity: the maximum density of Ordered Ruzsa-Szemerédi (ORS) graphs. We say a graph G is an (r, t)-ORS graph if its edges can be partitioned into t matchings M_1, M_2, \ldots, M_t each of size r, such that for every i, M_i is an induced matching in the subgraph $M_i \cup M_{i+1} \cup \cdots \cup M_t$. This is a relaxation of the extensively-studied notion of a Ruzsa-Szemerédi (RS) graph, the difference being that in an RS graph each M_i must be an induced matching in G.

In this note, we show that these two notions are roughly equivalent. Specifically, let ORS(n) be the largest t such that there exists an n-vertex $ORS(\Omega(n), t)$ graph, and define RS(n) analogously. We show that if $ORS(n) \ge \Omega(n^c)$, then for any fixed $\delta > 0$, $RS(n) \ge \Omega(n^{c(1-\delta)})$. This resolves a question of [BG24].

1 Introduction

In the fully dynamic approximate matching problem, we are given an *n*-vertex graph G which is undergoing edge insertions and deletions, and we seek to maintain a $(1 - \varepsilon)$ -approximate maximum matching after each update. Despite much work, the update complexity of this problem remains poorly understood. It is known that for $\varepsilon = 1/2$ one needs only constant update time [Sol16], and for $\varepsilon > 1/3$ one can achieve $n^{1/2+o(1)}$ update time [BS16]. However, for any $\varepsilon \le 1/3$, it is only known that one can achieve $n^{1-o(1)}$ update time [Liu24].

In [BG24], the following notion was introduced in the context of this problem:

Definition 1.1. A graph G is an (r,t)-ordered Ruzsa-Szemerédi (ORS) graph if its edge set can be partitioned into t edge-disjoint matchings M_1, M_2, \ldots, M_t each of size r, such that the subgraph of G induced by M_i does not include any edges from M_j for any j > i.

We let ORS(n,r) denote the maximum t for which there exists an n-vertex (r,t)-ORS graph.

The relevance of this quantity is due to an algorithm of [BG24] with update time

$$\sqrt{n^{1+\varepsilon} \cdot \operatorname{ORS}(n, \Theta_{\varepsilon}(n))}.$$

Currently it is only known that for fixed $\varepsilon < 1/4$

$$n^{o(1)} < \text{ORS}(n, \varepsilon n) < n^{1-o(1)},$$

^{*}Department of Computer Science, Courant Institute of Mathematical Sciences, New York University.

with the upper bound due to [BG24] and the lower bound due to [FLN⁺02]. Importantly, note that if the lower bound is optimal, then [BG24] gives an $n^{1/2+O(\varepsilon)}$ -time algorithm, significantly improving on the current record for small ε . In follow-up work [AKK25], this was improved to $n^{o(1)} \cdot \text{ORS}(n, \Theta_{\varepsilon}(n))$ update time [AKK25], thereby giving an algorithm whose complexity entirely rests on ORS $(n, \Theta_{\varepsilon}(n))$.

A closely related but much older (see [RS78]) notion is that of a Ruzsa-Szemerédi graph:

Definition 1.2. A graph G is an (r,t) Ruzsa-Szemerédi (RS) graph if its edge set can be partitioned into t edge-disjoint matchings M_1, M_2, \ldots, M_t each of size r, such that the subgraph of G induced by M_i is a matching.

We let RS(n,r) denote the maximum t for which there exists an n-vertex (r,t)-RS graph.

As for ORS graphs, it is only known that $n^{o(1)} \leq \text{RS}(n, \varepsilon n) \leq n^{1-o(1)}$ for $\varepsilon < 1/4$ [FLN⁺02, Fox11]. Clearly we have that $RS(n,r) \leq ORS(n,r)$; could it be that ORS is significantly larger than RS? We show that the answer is no:

Theorem 1.3. If $ORS(n, \varepsilon n) \ge \Omega(n^c)$, then for any fixed $\delta > 0$, $RS(n, \Theta(\varepsilon^{1/\delta}n)) \ge \Omega(n^{c(1-\delta)})$.

Thus, understanding the maximum density of ORS graphs with linear-sized matchings is roughly equivalent to understanding the density of RS graphs with linear-sized matchings. While previously it was conceivable that $RS = n^{o(1)}$ while $ORS = n^{1-o(1)}$, our result shows that this not possible. In the context of the dynamic matching problem, this means that the result of [AKK25] can be stated instead as an algorithm with update time of

$$n^{o(1)} \cdot RS(n, \Theta_{\varepsilon}(n)).$$

Looking at this differently, if the update time of the algorithm of [AKK25] turns out to be polynomial, then not only are current constructions of ORS graphs far from optimal, but so are current constructions of RS graphs.

2 A lower bound on RS via ORS

Lemma 2.1. For all n, r, k, $\operatorname{RS}(n^k, r^k) \ge \operatorname{ORS}(n, r)^{k-1}/k$.

Proof. Let $G = M_1 \cup \cdots \cup M_t$ be an *n*-vertex ORS-(r,t) graph. For an edge $(u,v) \in E(G)$, we let f(u,v) denote the index of the matching to which (u,v) belongs.

For $s \in \mathbb{N}$, consider the graph H_s with $V(H_s) = V(G)^k$ and

$$E(H_s) = \{((u_1, u_2, \dots, u_k), (v_1, v_2, \dots, v_k)) \in V(H_s)^2 : \forall i \in [k] \ (u_i, v_i) \in E(G), \sum_{i=1}^k f(u_i, v_i) = s\}.$$

First, H_s is a graph on n^k vertices. For $a \in [t]^k$ with $\sum a_i = s$, let M_a be the set of edges $(U, V) = ((u_1, \ldots, u_k), (v_1, \ldots, v_k))$ in H_s for which $f(u_i, v_i) = a_i$. Then the sets M_a partition the edges of H_s , and $|M_a| = \prod_i |M_{a_i}| = r^k$.

We claim that the subgraph of H_s induced by each M_a is a matching. First note that M_a is a matching, since if any vertex $U \in M_a$ had two distinct neighbors $V, W \in M_a$, there would exist some *i* with $V_i \neq W_i$, and then (U_i, V_i) and (U_i, W_i) would be edges in *G* both belonging to M_{a_i} , a contradiction. To see why it is an *induced* matching, let (U, V) be an edge in the induced subgraph. We know that for all *i* it must be the case that $f(U_i, V_i) \leq a_i$, since otherwise the subgraph of *G* induced by M_{a_i} would violate the ORS property. Also, $\sum f(U_i, V_i) = s = \sum a_i$. Together these imply that $f(U_i, V_i) = a_i$ for all *i*, and hence $(U, V) \in M_a$.

The number of matchings in H_s equals the number of solutions to $a_1 + \cdots + a_k = s$ with $a_i \in [t]$. By the pigeonhole principle, for some choice of s this is at least $t^k/(kt) = t^{k-1}/k$.

Proof of Theorem 1.3. By Lemma 2.1 and the assumption,

$$\operatorname{RS}(n^k, (\varepsilon n)^k) \ge \operatorname{ORS}(n, \varepsilon n)^{k-1}/k \ge \Omega_k(n^{c(k-1)}).$$

For all $N = n^k$, this shows that $\operatorname{RS}(N, \varepsilon^k N) \ge \Omega_k(N^{c(k-1)/k})$. By choosing $k = \lceil 1/\delta \rceil$ the statement holds for all sufficiently large such N. For N that is not a kth power, we can apply the construction for $\lceil N^{1/k} \rceil^k$ and then delete an arbitrary subset of $\lceil N^{1/k} \rceil^k - N$ vertices, which will only shrink the size of a matching by $O_k(N^{(k-1)/k})$.

We remark that the idea of Lemma 2.1 is motivated by a trick used in the context of fast matrix multiplication which converts a relaxed notion of an induced matching in a hypergraph into a legitimate induced matching in its tensor powers; see for example [BCC⁺17, Lemma 3.4], [CFTZ22, Theorem 23].

3 Acknowledgments

I thank Sepehr Assadi for encouraging me to write this note, and for feedback on an earlier draft.

References

- [AKK25] Sepehr Assadi, Sanjeev Khanna, and Peter Kiss, Improved bounds for fully dynamic matching via ordered ruzsa-szemeredi graphs, Proceedings of the 2025 Annual ACM-SIAM Symposium on Discrete Algorithms (SODA), SIAM, 2025, pp. 2971–2990.
- [BCC⁺17] Jonah Blasiak, Thomas Church, Henry Cohn, Joshua A Grochow, Eric Naslund, William F Sawin, and Chris Umans, On cap sets and the group-theoretic approach to matrix multiplication, Discrete Analysis (2017).
- [BG24] Soheil Behnezhad and Alma Ghafari, *Fully dynamic matching and ordered ruzsa-szemerédi graphs*, 2024 IEEE 65th Annual Symposium on Foundations of Computer Science (FOCS), IEEE Computer Society, 2024, pp. 314–327.
- [BS16] Aaron Bernstein and Cliff Stein, Faster fully dynamic matchings with small approximation ratios, Proceedings of the twenty-seventh annual ACM-SIAM symposium on Discrete algorithms, SIAM, 2016, pp. 692–711.
- [CFTZ22] Matthias Christandl, Omar Fawzi, Hoang Ta, and Jeroen Zuiddam, Larger corner-free sets from combinatorial degenerations, ITCS 2022-13th Innovations in Theoretical Computer Science Conference, 2022, pp. 1–2410.
- [FLN⁺02] Eldar Fischer, Eric Lehman, Ilan Newman, Sofya Raskhodnikova, Ronitt Rubinfeld, and Alex Samorodnitsky, *Monotonicity testing over general poset domains*, Proceedings of the thiry-fourth annual ACM symposium on Theory of computing, 2002, pp. 474–483.

- [Fox11] Jacob Fox, A new proof of the graph removal lemma, Annals of Mathematics (2011), 561–579.
- [Liu24] Yang P. Liu, On Approximate Fully-Dynamic Matching and Online Matrix-Vector Multiplication, 2024 IEEE 65th Annual Symposium on Foundations of Computer Science (FOCS) (Los Alamitos, CA, USA), IEEE Computer Society, October 2024, pp. 228–243.
- [RS78] Imre Z Ruzsa and Endre Szemerédi, Triple systems with no six points carrying three triangles, Combinatorics (Keszthely, 1976), Coll. Math. Soc. J. Bolyai 18 (1978), no. 939-945, 2.
- [Sol16] Shay Solomon, Fully dynamic maximal matching in constant update time, 2016 IEEE 57th Annual Symposium on Foundations of Computer Science (FOCS), IEEE, 2016, pp. 325–334.