Unweighted Code Sparsifiers and Thin Subgraphs

Shayan Oveis Gharan¹ and Arvin Sahami²

¹University of Washington, shayan@cs.washington.edu ²University of British Columbia, arvin52@student.ubc.ca

February 4, 2025

Abstract

We show that for every k-dimensional linear code $\mathcal{C} \subseteq \mathbb{F}_2^n$ there exists a set $S \subseteq [n]$ of size at most $n/2 + O(\sqrt{nk})$ such that the projection of \mathcal{C} onto S has distance at least $\frac{1}{2} \operatorname{dist}(\mathcal{C})$. As a consequence we show that any connected graph G with m edges and n vertices has at least $2^{m-(n-1)}$ many 1/2-thin subgraphs.

1 Introduction

Given a code \mathcal{C} over \mathbb{F}_2^n , its distance is defined as

 $\operatorname{dist}(\mathcal{C}) \coloneqq \min_{c \in \mathcal{C}, c \neq 0} \operatorname{wt}(c),$

where $\operatorname{wt}(c) = \|c\|_0$ is the number of nonzero coordinates of c. We say \mathcal{C} is a *linear code* if for any $c, c' \in \mathcal{C}, c + c' \in \mathcal{C}$. We say \mathcal{C} is k-dimensional if it has 2^k codewords. For convenience, we identify the set $S \subseteq [n]$ with its indicator vector $S \in \mathbb{F}_2^n$ (thus $2^{[n]}$ is identified with \mathbb{F}_2^n).

The projection of \mathcal{C} onto $S \subseteq [n]$ is the code $\mathcal{C}_S = \{c_S : c \in \mathcal{C}\}$ obtained by taking the S coordinates of every codeword in \mathcal{C} . Recently, Khanna-Putterman-Sudan [KPS24] initiated the study of code sparsification where they proved that any linear code \mathcal{C} of dimension k over \mathbb{F}_2^n has a "weighted" code sparsifier which projects \mathcal{C} onto at most $\widetilde{O}(k/\epsilon^2)$ -coordinates and such that the weighted hamming weight of every code word is preserved (up to a $1 \pm \epsilon$ multiplicative error).

In our main theorem, we show that every linear code $\mathcal{C} \subseteq \mathbb{F}_2^n$ has unweighted sparsifier \mathcal{C}_S such that $|S| \approx n/2$ and $\operatorname{dist}(\mathcal{C}_S) \geq \frac{1}{2}\operatorname{dist}(\mathcal{C})$. In other words, (assuming $k \ll n$), we can increase the rate of the code by a factor of 2 while preserving almost the same distance-rate). Our main theorem is the following.

Theorem 1.1. For any linear code $C \subseteq \mathbb{F}_2^n$, there is a set $S \subseteq [n]$ of size $\leq n(\frac{1}{2} + \sqrt{\frac{k}{2.88n}})$ such that for any $c \in C$, wt $(c_S) \geq \text{wt}(c)/2$. In particular we have $\text{dist}(C_S) \geq \text{dist}(C)/2$.

We remark that the proof of the theorem is not algorithmic. We also briefly explain applications of this theorem to thin subgraphs.

Given an unweighted (undirected) graph G = (V, E) with *n* vertices and *m* edges, we say a set $T \subseteq E$ is a α -thin w.r.t. *G* if for any nonempty set $S \subsetneq V$,

$$|T(S,\overline{S})| \le \alpha |E(S,\overline{S})|,$$

i.e., T has at most α -fraction of the edges of every cut. Recall that a graph G is t-edgeconnected if every cut in G has at least t edges. The following thin tree conjecture is proposed by Goddyn two decades ago [God04] and has been a subject of intense study since then [Asa+10; OS11; HO14; AO15; MP19; Mou; Alg23; KO23].

Conjecture 1.2 (Thin Tree Conjecture). For any $\alpha < 1$, there exists $t \ge 1$ such that any *t*-edge-connected graph G has a spanning tree T that is α -thin.

We remark that there has been several "spectral" constructions of thin subsets but it remained an open problem whether one can construct thin subsets combinatorially without appealing to eigenvalue arguments (this is specially motivated to address the thin tree conjecture, since *t*-edge-connected graphs do not necessarily have spectrally thin trees, see [AO15]).

Corollary 1.3. For any connected graph G with n vertices and m edges, there exists a $\frac{1}{2}$ -thin set $T \subseteq E$ with $|T| \ge m(\frac{1}{2} - \sqrt{\frac{n-1}{2.88m}})$.

Proof. The main observation is that if we identify every cut (S, \overline{S}) with the indicator vector of the set of edges of that cut, we obtain a linear code (over \mathbb{F}_2^m) of dimension n-1. Having said that to prove the statement it is enough to use the set $T \subseteq E$ promised in Theorem 1.1 which satisfies $|T| \ge m(\frac{1}{2} + \sqrt{\frac{n-1}{2.88m}})$; then \overline{T} is a $\frac{1}{2}$ -thin subgraph of G and has size $|\overline{T}| \le m(\frac{1}{2} - \sqrt{\frac{n-1}{2.88m}})$.

The following stronger statement also follows from our proof.

Theorem 1.4. Any graph G with m edges and n vertices has at least $2^{m-(n-1)}$ many 1/2-thin subgraphs.

The bound is tight, as a spanning tree only has a single 1/2-thin subgraph, the empty-set.

We remark that although the existence of 1/2-thin subgraphs follows by spectral arguments such as [BSS14], we are not aware of any exponential lower-bound on the number of spectrally thin subgraphs.

2 Main Proof

Definition 2.1 (codeword flip). Given a code word $c \in C$, the flip corresponding to c is the map $\mathbb{F}_2^n \to \mathbb{F}_2^n$ sending $S \in \mathbb{F}_2^n$ to S + c.

When \mathcal{C} is linear, this defines an equivalence relation on subsets of [n]. We say $S \sim S'$ if S can be obtained from S' by a codeword flip, i.e., $S + S' \in \mathcal{C}$. The transitivity of this relation follows from the linearity of \mathcal{C} .

Note that the collection of equivalence classes is the quotient space $\mathbb{F}_2^n/\mathcal{C}$ (this is a vector space over \mathbb{F}_2). Since dim $\mathbb{F}_2^n/\mathcal{C} = n-k$ there are precisely $|\mathbb{F}_2^n/\mathcal{C}| = 2^{n-k}$ equivalence classes.

$$\operatorname{wt}(c_{S^*}) \ge \operatorname{wt}(c)/2.$$

Proof. We prove this by contradiction. Suppose that there exists a codeword $c \in \mathcal{C}$ such that

$$\operatorname{wt}(c_{S^*}) < \operatorname{wt}(c)/2.$$

Let $S = c + S^*$. By definition $S \in H$. But the above equation implies $|S| > |S^*|$ which is a contradiction.

For an equivalence class H, let $S_H \subseteq [n]$ be a set of the largest size in H. Lemma 2.2 implies that the collection $\{S_H : H \in \mathbb{F}_2^n/\mathcal{C}\}$ contains 2^{n-k} distinct subsets $S \subseteq [n]$ s.t. $\operatorname{dist}(\mathcal{C}_S) \geq \frac{1}{2} \operatorname{dist}(\mathcal{C})$.

Now, it follows by the pigeon-hole principle that there must be a set $S \approx n/2$ such that C_S has distance at least half of the distance of C.

Proof of Theorem 1.1. Let

$$H^* = \operatorname*{argmin}_{H \in \mathbb{F}_2^n/\mathcal{C}} |S_H|$$

be the equivalence class whose largest set is the smallest. The set S_{H^*} is the smallest among 2^{n-k} distinct sets. Hence by the following lemma, we must have $|S_{H^*}| \leq n/2 + \sqrt{nk/2.88}$. This finishes the proof.

Lemma 2.3. For every n the number of subsets of size $\geq n/2 + \sqrt{nk/2.88}$ is less than 2^{n-k} .

Proof. Let X_1, \ldots, X_n be independent Bernoulli random variable. Then, by Hoeffding's bound

 $\mathbb{P}[X_1 + \dots + X_n \ge n/2 + \sqrt{\epsilon n}] \le \exp(-2\epsilon).$

Equivalently, the number of subsets of [n] of size $\geq n/2 + \sqrt{\epsilon n}$ is at most $2^n \cdot \exp(-2\epsilon)$. Letting $\exp(-2\epsilon) = 2^{-k}$ we get $\epsilon = \frac{\ln 2}{2}k$.

References

- [Alg23] Mahtab Alghasi. "Combinatorially Thin Trees and Spectrally Thin Trees in Structured Graphs". MA thesis. University of Waterloo, 2023 (cit. on p. 2).
- [AO15] Nima Anari and Shayan Oveis Gharan. "Effective-Resistance-Reducing Flows, Spectrally Thin Trees, and Asymmetric TSP". In: *FOCS*. Ed. by Venkatesan Guruswami. IEEE Computer Society, 2015, pp. 20–39 (cit. on p. 2).
- [Asa+10] Arash Asadpour, Michel X. Goemans, Aleksander Madry, et al. "An $O(\log n / \log \log n)$ approximation Algorithm for the Asymmetric Traveling Salesman Problem". In: SODA. 2010, pp. 379–389 (cit. on p. 2).
- [BSS14] Joshua Batson, Daniel A. Spielman, and Nikhil Srivastava. "Twice-Ramanujan Sparsifiers". In: *SIAM Review* 56.2 (2014), pp. 315–334 (cit. on p. 2).
- [God04] Luis A. Goddyn. "Some Open Problems I Like". available at http://www.math.sfu.ca/goddyn/Problems/problems.html. 2004 (cit. on p. 2).
- [HO14] Nicholas J. A. Harvey and Neil Olver. "Pipage Rounding, Pessimistic Estimators and Matrix Concentration". In: SODA. 2014, pp. 926–945 (cit. on p. 2).

[KO23]	Nathan Klein and Neil Olver. "Thin Trees for Laminar Families". In: <i>FOCS</i> . IEEE, 2023, pp. 50–59 (cit. on p. 2).
[KPS24]	Sanjeev Khanna, Aaron (Louie) Putterman, and Madhu Sudan. "Code Sparsification and its Applications". In: <i>SODA</i> . 2024, pp. 5145–5168 (cit. on p. 1).
[Mou]	"Thin trees in 8-edge-connected planar graphs". In: Information Processing Let- ters 143 (2019), pp. 51–55 (cit. on p. 2).

- [MP19] Martin Merker and Luke Postle. "Bounded diameter arboricity". In: Journal of Graph Theory 90.4 (2019), pp. 629–641 (cit. on p. 2).
- [OS11] Shayan Oveis Gharan and Amin Saberi. "The Asymmetric Traveling Salesman Problem on Graphs with Bounded Genus". In: *SODA*. 2011, pp. 967–975 (cit. on p. 2).