The Role of Integrity Monitoring in Connected and Automated Vehicles: Current State-of-Practice and Future Directions

Saswat Priyadarshi Nayak[®], Student Member, IEEE, and Matthew Barth[®], Fellow, IEEE

Abstract—Connected and Automated Vehicle (CAV) research has gained traction in the last decade due to significant advancements in perception, navigation, communication, and control functions. Accurate and reliable position information is needed to meet the requirements of CAV applications, especially when safety is concerned. With the advent of various perception sensors (e.g. camera, LiDAR, etc.), the vehicular positioning system has improved both in accuracy and robustness. Vehicle-to-Vehicle (V2V) and Vehicle-to-Infrastructure (V2I) based cooperative positioning can improve the accuracy of the position estimates, but the integrity risks involved in multi-sensor fusion in a cooperative environment have not yet been fully explored. This paper reviews existing research in the field of positioning Integrity Monitoring (IM) and identifies various research gaps. Particular attention has been placed on identifying research that highlights cooperative IM methods. This analysis helps pave the way for the development of new IM frameworks for cooperative positioning solutions in the future.

Index Terms—Vehicle positioning, Integrity monitoring, Fault detection, Connected and Automated Vehicles

I. INTRODUCTION

Connected and Automated Vehicle (CAV) research is crucial to ensure safety, smooth traffic operation, and minimize energy consumption and carbon emissions. With the advent of sophisticated sensor platforms, computation hardware, and communication capability, it is now possible to deploy intelligent CAV applications through cooperation between various road agents. CAV applications can be broadly classified into three major use categories: safety, mobility, and environmental. Mobility and environmental applications such as eco-routing. eco-approach and departure (EAD) typically require coarse positioning accuracy (5-10 m) and/or lane level positioning accuracy (< 1 m), while safety-critical applications such as collision avoidance, autonomous intersection management, etc., generally require a where-in lane level accuracy (< 0.2m). Nigel et al. provided a qualitative analysis on various CAV applications and their positioning requirements in [1]. The positioning accuracy required for various CAV applications can be achieved through onboard positioning sensors, such as the Global Navigation Satellite System (GNSS) receivers and Inertial Measurement Units (IMU), as well as perception sensors like cameras and LiDAR. Additionally, external sensor

data, including information from roadside cameras and Li-DAR, can be shared via wireless communication technologies such as cellular and/or Dedicated Short Range Communication (DSRC).

1

Further, in a mixed traffic environment, vehicles can be classified as Human-driven Vehicles (HDV), Automated Vehicles (AV), Connected Vehicles (CV), or Connected and Automated Vehicles (CAV). Various levels of autonomy (SAE Level 0-5) [2] and connectivity (fully or partially connected) also exist for CAVs. Mixed traffic also consists of vulnerable road users (VRUs) who are often not given much attention in CAV research. They are assumed to be non-connected and are tracked by vehicular and infrastructure sensors. This is not entirely true as many VRUs typically possess smart devices such as smartphones and smartwatches which have built-in GNSS/IMU capabilities with cellular connectivity. These features can facilitate VRU cooperation with the rest of the traffic improving their safety. Although mixed traffic encompasses a huge variety of road agents, only vehicles are considered in this review.

Various types of sensors are used to estimate the state of a vehicle and perceive the environment around it. Providing accurate vehicle state information while maintaining a lower risk of misinformation is instrumental in smooth navigation and control operations. Several integrity monitoring (IM) techniques have been used to monitor key parameters such as accuracy, availability, continuity, and integrity risk for positioning systems. The historical development of IM methods revolves around the Receiver Autonomous Integrity Monitoring (RAIM) method [3] development in the 1980s as a way to evaluate the trustworthiness of GPS signals used in aviation and marine navigation. Recently, more attention has been received in cooperative driving automation (CDA) research, as the existence of mixed traffic, varied sensing, and compute capabilities makes it challenging to implement and evaluate the integrity for real-time safety-critical CAV applications.

The type, quantity, placement, and measurement uncertainty of sensors play an important role in determining the navigation performance of a vehicle. Onboard positioning systems utilizing GNSS-IMU modules have proven to be a good source for providing absolute position information. In deep urban canyons, additional perception sensors such as a camera or LiDAR can augment these GNSS-based positioning systems, when signals are lost. Perception sensors are expensive, but they play an important role for autonomous driving functions

Saswat Priyadarshi Nayak (Corresponding author) is with the Department of Electrical and Computer Engineering, University of California, Riverside, Riverside, USA (email: snaya004@ucr.edu).

Matthew Barth is with the Department of Electrical and Computer Engineering, University of California, Riverside, Riverside, USA (email: barth@ece.ucr.edu).

in vehicles. Legacy vehicles or HDVs may not possess the necessary sensors for autonomous functionalities, but they can still reap the benefits of a connected ecosystem by sharing information with surrounding vehicles and infrastructure via vehicle-to-vehicle (V2V) and vehicle-to-infrastructure (V2I) communications. Today, many vehicle owners use smartphones for plug-in navigation applications such as Android Auto and Apple Carplay [4], [5]. With cellular connectivity, HDVs are loosely connected to the cellular ecosystem and can thus share information over the network, making them a partially-connected vehicle (P-CV). The use of smartphone-based plug-in technology has primarily been explored for long-term planning, such as route planning. However, its potential for reactive or short-term planning, particularly in safety-critical scenarios, remains largely untapped.

AVs and CAVs have access to a large amount of sensor data, but processing them in real time can be challenging. AVs have access to the onboard sensor data through reliable local wired connections. This allows an AV to run algorithms on a centralized on-board computation unit. However, in a cooperative or collaborative environment, the sensor information from multiple vehicles/infrastructure nodes can be processed either in a centralized or decentralized manner. This depends on the computational capabilities of the individual nodes (vehicle, infrastructure), communication capacity, and the end requirements of the vehicle.

In a mixed-traffic scenario, there exist various types of positioning solutions, vehicles, sensor modalities, and applications. It is unlikely that two vehicles having the same set of sensors and computation hardware will produce similar navigation performance. Hence, it is important to study and analyze the integrity of positioning systems under various conditions.

The different sections of this paper are organized as follows. Section II discusses various uncertainties considered in past CAV research, i.e. model uncertainty, position uncertainty, etc. Integrity monitoring methods for vehicles via standalone and cooperative operations are presented in Section III. Section IV discusses key automotive safety standards in practice. Section VI explores existing research gaps and highlights potential opportunities for future work. The paper concludes with a comprehensive conclusion, synthesizing the key findings and implications of the research in Section VII.

II. BACKGROUND: CONSIDERATION OF POSITIONING UNCERTAINTIES IN CAV APPLICATIONS

Uncertainty originates from imperfect knowledge about the state or condition of a vehicle. Various navigation and control algorithms rely on mathematical models to define the vehicle's motion and interaction with their surroundings. These models are often an approximation of the real vehicle operations leading to model uncertainties [6], [7]. In existing work, the vehicles are often assumed to be homogeneous across the same vehicle class, i.e. HDVs, AVs, CAVs. However, vehicles are different when it comes to car-following models or powertrain control strategies. Hence, the uncertainties of the model and the heterogeneity in mixed traffic should be taken into account when developing intelligent applications.

Accurate state information, especially the vehicle's position, is critical in deciding whether an application could be deployed or not. Uncertainty in positioning information can sabotage driving functionalities and cause major safety concerns.

The position uncertainty of a vehicle can be attributed to the sensor suite available on the vehicle, along with any additional external sensor information that may aid the invehicle sensors. A fully connected and automated vehicle may turn itself into a degraded-CAV, AV only, CV only, and HDV while experiencing loss of communication and / or control. Hence, a sensitivity analysis is required to evaluate the positioning needs of a CAV application and to determine whether the necessary position accuracy can be achieved with just vehicular sensors or a combination of vehicular sensors with external sensor information [8]. If where-in-lane-level position accuracy is ensured for vehicles, CAV applications such as Intersection Movement Assist (IMA) and Autonomous Intersection Management (AIM) can be implemented. If not, the application parameters may be dynamically adjusted so that the vehicle can perform less critical applications such as IMA or eco-approach and departure with basic longitudinal speed control.

One of the promising CAV applications is some form of platooning [9]. Platooning involves three fundamental maneuvers: merging, formation maintenance, and splitting. Merging and splitting involve coordinated actions between vehicles for safe lane changes, while formation maintenance involves longitudinal control along with an appropriate car-following model [6]. A good deal of research has been done in this area, focusing mainly on protocol design and trajectory planning, as depicted in fig1. Li et al. [10] conducted experiments on platoon control with vehicles connected via V2X communication. A nonlinear consensus-based longitudinal control was implemented considering communication probability in the car-following model. Luo et al. presented a cooperative control strategy to manage vehicle platoon in [11] under measurement uncertainties. Real-world vehicle trajectories were taken from NGSIM dataset to simulate the experiments. Li et al. [6] explored uncertainties in relative velocity and headway in analyzing carfollowing stability. Lu et al. [12] proposed a stochastic model for mixed traffic modeling and considered CAV degradation under communication constraints. Furthermore, the efficiency and stability of the mixed traffic were evaluated under different CAV penetration rates. A distributed Model Predictive Control (MPC) technique was explored in [7] for platoon control with model mismatch error and mixed disturbances.

In addition to platooning experiments, other CAV applications, such as cooperative ramp merging and autonomous intersection management (AIM) have been studied in this context. Nigel et al. [8] studied the merging of vehicles in a mixed-traffic scenario under position uncertainty. The impact of position uncertainty was studied in [13] where a hierarchical MPC was developed to control the traffic and the vehicle at an intersection. Vitale et al. [14], [15] proposed a mathematical framework for AIM problem considering uncertainty in location and provided an optimization technique to generate optimal vehicle acceleration profiles. Aoki and Rajkumar presented a data sharing framework [16] for intersection



Fig. 1. Fundamental operations of vehicle platooning.

management utilizing a cooperative perception-based HD map.



Fig. 2. Research Gaps in CAV applications.

Existing literature on the implementation and deployment of CAV applications focuses mostly on the planning aspect of the application. There is a lack of real-world experiments, as most of them are either conducted in simulation or controlled environments (see fig2). Multiple sensor modalities and their errors need to be quantified to properly evaluate their impact on the application's performance. Heterogeneity in carfollowing models and parameters needs to be considered, as existing research often assumes homogeneous vehicle types in a mixed traffic environment. Uncertainties in communication, measurements, and related processes must be studied to assess the integrity of vehicle navigation and to prepare CAVs for the road. Hence, this paper focuses on revisiting existing work on positioning integrity monitoring methods and identifying key gaps that will help improve modern navigation systems.

III. POSITIONING INTEGRITY MONITORING

Integrity refers to "trust" in the performance of a system [17]. In the context of Intelligent Transportation Systems (ITS), integrity has been evaluated using various strategies including Fault Detection and Isolation (FDI) [18], parity space [19], Kalman filter residuals, cross-consistency checks [20], context-aware monitoring [21], among others. A fault can occur at multiple levels, such as sensor level,

signal transmission level, data processing level, system integration level, and application level [22]–[24]. These multilevel faults are summarized in TABLE I. Most of the FDI-based research has either been conducted for faults at the sensor (hardware) level or the application (software) level. Raouf et al. presented a sensor-based prognostic health management for vehicle ADAS [22]. This paper shall only focus on the system integration and application-level faults associated with vehicle positioning.

 TABLE I

 FAULT LEVELS IN INTEGRITY MONITORING

Level	Fault
Sensor	 Aging and faulty physical components Thermal, electromagnetic, harsh weather conditions Bias, scale factor errors, calibration errors
Signal Transmission	 Electromagnetic interference, crosstalk, etc. Packet loss, transmission delay Time synchronization error
Data Processing	 Faults in data filtering or fusion algorithms Software bugs, misinterpretation of data Incorrect system configurations
System Integration	 Multipath error, reference signal errors Data fusion issues, sensor alignment and coordinate transformation errors Power overloading, memory constraints, cybersecurity, etc.
Application	 Operational constraints, logic flaws, unoptimized application features Misinterpretation of sensor data Error handling issues, resource bottlenecks

The integrity monitoring (IM) framework consists of a set of requirements for the navigation system that must be met to ensure safe operation. These requirements are subject to the positioning system used by the vehicle and the application it intends to perform. These requirements are referred to as Required Navigation Performance (RNP). The performance of the vehicle positioning and navigation system is quantified using four properties defined by the RNP framework - Accuracy, Availability, Continuity, and Integrity. These properties are quantified by four parameters [25], [26]:

- **Protection level (PL):** An upper bound on the position error (PE) with a specified confidence level. Protection levels can be defined for the longitudinal and lateral direction of a vehicle.
- Alert limit (AL): The maximum allowable error before an alert is triggered. AL is set by safety requirements and system specifications.
- **Time-to-alert (TTA):** The maximum allowable time from the occurrence of a fault to the time when an alert is issued.
- **Integrity risk (IR):** The likelihood of true position error exceeding the alert limit without raising an alert.



Fig. 3. Stanford-ESA integrity diagram to monitor positioning integrity [26].

The Stanford-ESA (Error Separation Algorithm) integrity diagram [26] is a graphical tool used to illustrate and assess the integrity of GNSS-based navigation systems, particularly in aviation. Although this plot was developed for GNSS positioning systems, it can be adapted and used for other navigation solutions. The PL estimated from standard deviations in position estimates and multipliers derived from desired confidence levels is plotted against the true position error over time across different scenarios. Different operating zones in the Stanford plot are discussed in detail in [25] and [27]. Integrity risk is determined by the percentage of (PL, PE) pair in the Hazardously Misleading Information (HMI) region without raising an alert, thus compromising safety of the vehicle.

A. In-vehicle (Standalone) Integrity Monitoring

FDI-based integrity monitoring (IM) methods such as Receiver Autonomous Integrity Monitoring (RAIM) and its variants have been extensively used in the Global Navigation Satellite System (GNSS)-based systems to ensure the accuracy and reliability of position data provided by the receiver [3]. In the literature, different integration schemes and IM methods have been explored to fuse information from GNSS receivers, the inertial measurement unit (IMU), and vehicle odometry [27].

Automated vehicle research and their applications have surged in the last decade with the advent of advanced perception sensors and improved onboard computational capabilities. Reference [25] surveys integrity for autonomous driving and presents two approaches: (1) FDI, and (2) boundederror assumption to evaluate localization safety in autonomous vehicles. Apart from the widely used FDI methods, other IM methods have been developed for various driving scenarios and ITS applications. Integrity methods for sensor data fusion algorithms were developed in [28] to estimate the vehicle's dynamic state during automated driving. In this work, Kalman Integrated Protection Level (KIPL) performed the best while estimating protection level (PL) compared to the kSigma and Advanced-RAIM (ARAIM) method [29]. Cross-consistency metric between multi-modal data sources is proposed in [30] instead of classical FDI schemes to evaluate localization integrity in automated vehicles.

Visual information for navigation has been a wellresearched topic since the last decade. Direct, indirect, and deep learning-based approaches have been used for relative pose estimation. In most research, robustness has been a key criterion for evaluating visual-navigation methods. Although state-of-the-art approaches may excel in information availability and continuity, they often fail to meet the minimum integrity requirements. Integrity frameworks define additional parameters such as accuracy and risk, for difficult navigation scenarios where reliable estimates are more crucial than outputting the best available solution under high risk.

References [31] and [32] propose integrity monitoring for camera-based lane marking detection and removal of faulty measurements by monitoring the residuals of the estimated position. Visual information has also been used to aid existing GNSS measurements and help identify and eliminate Non-Line-of-Sight (NLOS) errors in deep urban canyons [33]. Zhu and Taylor [34] studied the effect of correlated measurements on integrity in visual navigation. Zhu et al. proposed a technique to quantify the feature association error in [35]. The research so far has focused on a specific type of error associated with visual navigation. The errors are often not modeled correctly and there is a lack of integrity monitoring methods for camera-only solutions. In [36], a preliminary integrity monitoring framework is presented for a feature-based relative pose estimation problem in visual navigation. Additionally, the authors point out the challenges and developments in integrity analysis for visual navigation.

B. Cooperative Integrity Monitoring

IM methods have been extensively studied and developed for in-vehicle sensor systems primarily consisting of GNSS receivers often integrated with IMUs, vehicle odometry, and perception sensors such as radar, camera, and LiDAR. The localization performance and safety of a vehicle have mainly been studied from the vehicle's perspective focusing on enabling automated driving functions through onboard sensors and computing platform. AVs constitute a small percentage of traffic on the road today. There is a surge in V2V/V2I/V2P/V2X research focusing on information sharing between road agents for improved positioning, navigation, and control. Given the number of sensor sources and the amount of data shared between road agents, it is imperative to develop integrity monitoring frameworks for cooperative scenarios. Despite the growing interest in this area, there is a noticeable gap in the current literature that addresses the "cooperative-IM" framework. For CAV applications, only a few studies have thoroughly examined different ways to evaluate integrity risks in wireless information exchange, indicating a need for further research to propose new RNP parameters [27].

In addition to the standard parameters used in the traditional IM framework, i.e. accuracy, availability, continuity, integrity, two other parameters - timeliness & interoperability, have been proposed in the literature to evaluate the performance of cooperative-ITS (C-ITS) applications [37]. In [38], a runtime IM framework for real-time relative positioning was introduced focusing on sharing raw GPS observation data through Dedicated Short Range Communications (DSRC). The author of previous work also explored a real-time relative position prediction strategy [39] in a V2V environment using several position prediction techniques to compensate for the loss of the V2V DSRC link. In this work, only road-level accuracy (<5 m error) could be guaranteed. A hybrid integrity monitoring method is proposed in [40] that overcomes the limitations of conventional RAIM technique under limited GNSS satellite coverage. It generates virtual satellite measurements using DSRC range rate measurements from neighboring vehicles and road map data. Recently, signals of opportunity (SOPs) such as AM/FM radio, cellular signals, etc., have aided the IMU in the absence of GNSS signals. Cellular signals in particular are of great interest due to their availability in urban canyons. A SOP-based RAIM framework was developed in [41] which fuses cellular pseduorange measurements with IMU measurements. The proposed method showed a reduction of position Root Mean Square Error (RMSE) by 66%.

In existing studies, the IM framework majorly focuses on improving GNSS-based positioning systems either through an onboard IMU, vehicle odometry, or use of external information like SOPs, DSRC ranging, pseudorange differences relayed through wireless communication. IM methods have been developed for perception sensors such as cameras, Li-DARs, radars, etc., but as a part of the onboard or in-vehicle perception system. The sharing of perception data in raw or processed format via V2V/V2I means has proven to enhance the detection of surrounding vehicles and improve localization performance [42]–[44]. However, research on cooperative integrity monitoring for sharing perception data through wireless communication has been limited. Xiong et al. experimented with a cooperative integrity monitoring (CIM) method with FDE based on the innovation residual of the Kalman filter [45]. The CIM method was better at fault detection in GNSS and ultra-wide band (UWB) measurements compared to the traditional RAIM method & CERIM method [46]. Various research experiments on integrity monitoring for automotive sensor fusion algorithms have been presented in [47]. In this work, the authors have proposed integrity concepts based on interval set theory. A dynamic sensor network is created consisting of three vehicles equipped with stereo cameras, laser scanners, GNSS receivers, and IMUs. Issues such as inconsistency in GNSS measurements, random and bounded uncertainties are addressed in this paper.

The development of cooperative integrity monitoring methods is still in its early stages. The question remains whether the empirically determined Required Navigation Performance (RNP) values hold consistent across different driving conditions, positioning hardware, and communication topologies. Inconsistencies in RNP parameters in CAV applications would lead to multiple solutions from various automotive OEMs resulting in loss of standardization. In [48], the authors have defined the minimum operational performance standards that can be adjusted to meet the needs of a specific safety application based on the positioning capabilities of a vehicle. The ESA-funded P-CAR project [49] focuses on identifying and validating connected and automated driving (CAD) functions to meet safety integrity needs. It aims at creating realistic Hardware-in-Loop (HiL) simulations and appropriate fault injection strategies to evaluate events with integrity risks that might be rare and difficult to test in real-world conditions. Based on the initial stakeholder surveys, truck platooning is being favored to test the efficacy of V2V communication, whereas, applications such as highway pilot, urban automated shuttle, and valet parking are key contenders in the navigation segment. Various cooperative integrity monitoring strategies and key findings are summarized in TABLE II.

IV. AUTOMOTIVE SAFETY STANDARDS AND PROTOCOLS

Vehicles depend on several automotive safety standards that are essential for precise navigation, effective collision avoidance, and ensuring the overall safety and reliability of the system. These safety standards are defined and maintained by various organizations around the world such as the Society of Automotive Engineers (SAE), the International Organization for Standardization (ISO), the National Highway Traffic Safety Administration (NHTSA), the European New Car Assessment Programme (EURO NCAP), the European Telecommunications Standards Institute (ETSI), United Nations (UN), and others. Vehicle safety is considered across various vehicle subsystems and application areas, including passive safety, active safety, EV safety, cybersecurity and data safety, V2X communication safety, perception and ADAS safety, functional safety, occupant & VRU safety. Considering the scope of this paper, only the standards concerned with the following vehicle safety categories are discussed:

- Active safety: Driver assistance and vehicle control systems
- Cybersecurity and data safety: cyber threats detection and protection
- V2X communication safety: Safe and secure V2X communication
- Perception and ADAS safety: Accuracy and reliability of sensor systems
- Occupant and VRU safety: Protection of occupants and vulnerable road users (VRUs)

Paper	Authors	Year	Mode	Data Source	Techniques	
[17]	Hassan et al.	2021	Standalone	GNSS, IMU, Odometry, LiDAR	RAIM, KF-based	
[25]	Worner et al.	2016	Standalone	N.A	FDI, BE approach	
[27]	Jing et al.	2022	Standalone & Cooperative	GNSS/IMU, Map, Wire- less	RAIM, KF-based	
[22]	Raouf et al.	2022	Standalone	GNSS, Camera, LiDAR, Radar	RAIM, KF-based	
[20], [30]	Balakrishnan et al.	2020	Standalone	GPS, Camera, LiDAR, Map	RAIM, KF-based	
[28], [29]	Gottschalg et al.	2021	Standalone	GNSS, IMU, Odometry	kSigma, KIPL, ARAIM	
[38]	Ansari et al.	2015	Cooperative	GNSS/RTK, IMU, DSRC	PRMF, RAIM, KF- based fault detection	
[39]	Ansari	2020	Cooperative	GNSS, DSRC	KF, EKF, PF, MR, MFNN	
[40]	Liu et al.	2020	Cooperative	GNSS, DSRC, Road map	Hybrid-RAIM, Virtual satellite measurements	
[41]	Maaref et al.	2022	Cooperative	GNSS, IMU, Cellular- LTE	SOP-based RAIM	
[45]	Xiong et al.	2021	Cooperative	GNSS, UWB	CIM, Kalman residual	
[47]	Schon et al.	2018	Cooperative	GNSS, IMU, stereo cam- era, laser scanner	Interval set theory	

TABLE II Standalone and Cooperative Integrity Monitoring Techniques

Two of the most important standards in this area are ISO 26262 [50] and ISO 21448 [51]. ISO 26262 defines a risk classification system known as the Automotive Safety Integrity Level (ASIL) for the functional safety of vehicles. ASIL is determined based on hazard analysis and risk assessment of a vehicle operating scenario. Factors such as severity, exposure, and controllability of the vehicle contribute to the ASIL estimation. ISO 26262 standard ensures that automotive systems are designed and built to prevent and handle failures within the functional safety framework of a vehicle. Functional safety for GNSS positioning systems were studied in [52], [53] for autonomous land vehicles. Existing functional safety frameworks do not provide concrete information and guidance or evaluating Artifical Intelligence (AI) based systems, which are often deployed in autonomous vehicles. Diemert et al. [54] proposed an AI based Safety Integirty Level (AI-SIL) framework which determines the complexity of an AI system and combines it with the existing 'Level of Rigor' approaches. The advancements in safety standards for machine learningbased road vehicle functions are reviewed in [55].

However, with the emergence of newer sensor technologies, advanced driver functionalities are hugely dependent on cameras, LiDARs, radars, and other sensors, to understand its surrounding environment. A vehicle can encounter sensor faults, and malfunctions due to adverse weather conditions or dynamic environment factors beyond the operational design domain of the safety framework. Sensor data are accessed to monitor the overall system health and the environment through a method called SOTIF (Safety of the Intended Functionality) governed by the ISO 21488 standard. ISO 21448 addresses safety concerns that arise from the intended functionality of the system, particularly in scenarios where the system is functioning as designed but still may pose safety risks. It is especially relevant for systems that rely on complex sensors, algorithms, and machine learning, like those used in automated driving. Challenges in Validating SOTIF are presented in [56], with particular attention to addressing false positives and false negatives for different levels of autonomy. With increasing levels of autonomy (level-3 and higher), scenario-based validation becomes important. However, it is not entirely possible to test all the scenarios with possible triggering conditions. Jimenez et al. presented a perception performance insufficiency approach [57] to validate SOTIF in different scenarios. Huang et al. [58] proposed a systematic identification framework for triggering events consisting of system limitations and human errors.

In addition to ISO 21448 and ISO 26262 standards, there exists other ISO and UN regulatory standards focusing on active safety and ADAS systems. UN R79 and UN R152 respectively, oversee the steering control and automatic emergency brake systems (AEBS) requirements [59] to enable functionalities such as lane-keeping assist and crash avoidance. In the realm of automated vehicles, ISO 23150 [60] provides the logical interface for data communication between sensors and the data fusion unit for automated driving functions. ISO 16505 [61] provides the minimum requirements for safety and performance of camera monitoring systems (CMS) in road vehicles. It offers enhanced visual information on the vehicle's surroundings, assisting the driver by improving visibility. Another important automotive standard that focuses on cybersecurity is ISO/SAE 21434 [62] which defines common cybersecurity practices and provides a common language for risk communication and management.

ITS-G5 C-V2X IEEE 802.11p Technology 3GPP (Cellular-based) Direct Direct Mode (PC5) and Modes communication only Network Mode (Uu) 1-2 ms in PC5; higher in Latency 1-2 msUu mode 300-500 meters (PC5); Range 300-500 meters broader in Uu Uses existing cellular Requires RSUs Infrastructure infrastructure Widely deployed in Newer, gaining support in Maturity Europe North America and China Future-Limited scalability Highly scalable with 5G readiness Regional Europe North America, China Adoption

TABLE III Comparison between ITS-G5 and C-V2X

Apart from the onboard positioning and perception sensors, the vehicles can communicate information with surrounding vehicles and infrastructure through V2V, V2I, and V2X communication. Standards such as ISO 20077, ISO 20078, and ISO 21217 are essential in the context of connected and cooperative vehicles [63], focusing on data exchange, security, and system architecture aspects. There are mainly two V2X technologies - namely ITS-G5 and Cellular-V2X (C-V2X) [64], [65]. ITS-G5 is a short, direct communication protocol based on the IEEE 802.11p standard. It used the 5.9 GHz frequency, for low-latency, real-time communication. However, the C-V2X technology is a cellular-based technology developed by the 3rd Generation Partnership Project (3GPP). It operates in two modes: (a) Direct Mode (PC5), for direct communication between vehicles and infrastructures using the 5.9 GHz band without relying on cellular networks, and (b) Network Mode (Uu), which uses cellular networks (4G-LTE and preferably 5G) to provide long-range communication enabling sharing of traffic data via cloud sharing. A comparison between ITS-G5 and C-V2X technology is presented in TABLE III.

The ETSI ITS-G5 standards developed by the European Telecommunications Standards Institute (ETSI) are designed to enable reliable, real-time V2X communication, especially for critical cooperative safety applications like collision warning, emergency braking, and road hazard notifications. ETSI ITS-G5 has been widely adopted across Europe, primarily in EU-funded projects like SCOOP@F and C-Roads, where countries collaborate on cross-border interoperability and safety [66], [67]. The implementation of ETSI ITS-G5 by various automakers and research groups is provided in the TABLE IV. A few key ETSI ITS-G5 standards are as follows:

• ETSI EN 302 637-2: Cooperative Awareness Messages (CAM) [68]

The standard defines the periodic Cooperative Awareness Messages (CAM) that the vehicles broadcast to provide essential information such as position, speed, heading, etc. CAM Messages enhance situational awareness critical for collision avoidance, lane-keeping, and cooperative adaptive cruise control (CACC), where precise vehicle positions are required for safe and coordinated maneuvers. It is quite similar to the Basic Safety Messages (BSM) defined under SAE standards.

• ETSI EN 302 637-3: Decentralized Environmental Notification Messages (DENM) [69]

DENM messages improve real-time response to unpredictable events, allowing vehicles to adjust speed, change lanes, or even stop in advance of encountering hazards. This standard is vital for emergency electronic braking and real-time traffic updates, allowing vehicles to communicate situational hazards that can prevent collisions and protect vulnerable road users.

• ETSI EN 302 665: ITS Communications Architecture [70]

This standard specifies the architecture for ITS communications in a way that enables interoperability between different ITS stations, including vehicles, RSUs, and central management systems. In high-density traffic environments, this interoperability enables coordinated safety maneuvers and effective traffic management, essential for applications like lane merging and intersection management.

• ETSI EN 302 571: Radio Spectrum Requirements for ITS [71]

This standard regulates the use of the 5.9 GHz frequency band specifically for ITS applications, minimizing interference and ensuring secure communication for V2X applications. By dedicating the 5.9 GHz band to ITS, this standard helps prevent interference from non-ITS devices, preserving the reliability and integrity of critical safety messages.

• ETSI TR 102 863: Local Dynamic Map (LDM) standardization [72]

This technical report provides standardization of LDM based on the requirements of various ITS applications. It acts as a central repository storing both static elements such as road traffic road signs and dynamic elements like moving vehicles. The LDM acquires data from various entities such as vehicles, on-board units, roadside units, ITS stations, etc., which is essential to deploy cooperative ITS applications.

Unlike ETSI ITS-G5, standards SAE J2735 and SAE J2945 designed by the Society of Automotive Engineers (SAE) primarily focuses on the C-V2X, though it is also applicable to ITS-G5. J2735 defines message sets, data frame and data elements used in V2X communication. The standardization of messages and its structure facilitates interoperability between V2X communication devices. Few of the key J2735 messages include Basic Safety Message (BSM), Singal Phase and Timing (SPaT), Map message (MAP), Traveler Information Message (TIM) and many more. A list of experiments demonstrating the use of the SAE J2735 messages is mentioned in TABLE V. J2945 defines performance requirements and guidelines for V2X safety

Project	Stakeholders	Key Applications	ETSI ITS-G5 Messages	Deployment Stage	Year
Scoop@F [66]	French ministry of trans- portation, Renault, PSA, METS, etc.	Intersection safety, Road work alert, onboard sig- nalling	CAM, DENM	Field trials	2014-2018
5G-ROUTES [73]	AIRBUS, ERICSSON, LMT, TELIA, CERTH, etc.	Cooperative collision avoidance, Vehicle platooning, state sharing	CAM, CPM, DENM, MAPEM, SPATEM	Cross-border tests	2021- ongoing
DRIVE C2X [74]	DAIMLER, CRF, BMW, RENAULT, etc.	Emergency vehicle warn- ing, In-vehicle signage, obstacle warning	CAM, DENM	Cross-border tests	2011-2014
5GAA [75]	3GPP, ETSI, OmniAir, 5G-IA/5GPPP, etc.	CACC, Automated valet parking, Platooning	DENM, IVIM, SPATEM, MAPEM, SREM, SSEM, CAM, CPM	Field trials, Commercial deployments	2016- ongoing
Car2X [76]	Volkswagen, BMW, VEC- TOR, etc.	Intersection movement as- sist, Road work alert, Pla- tooning	CAM, DENM	Field trials, Pi- lot tests, Com- mercial deploye- ments	2013- ongoing
C-Roads platform [67]	EU member states, Renault, PSA, Garmin, VOLVO, Swarco, etc.	Road work alert, In-vehicle signage, Automated vehicle guidance, Collective perception	CAM, DENM, SPATEM, MAPEM, IVIM, SREM	Cross-border interoperability tests	2016- ongoing
CONCORDA [77]	ERTICO, BOSCH, RE- NAULT, PSA, etc.	High-density truck pla- tooning	CAM, DENM	Cross-border interoperability tests	2017-2021
NordicWay [78] - NordicWay 1 - NordicWay 2 - NordicWay 3	EU, VOLVO, SAFEROAD, SKANSKA, BM SYSTEM, etc.	Emergency vehicle warn- ing, Road work alert, Traf- fic management	CAM, DENM, SPATEM, MAPEM	Cross-border deployment pilot, Interoperability tests	(2015-2023) - 2015-2017 - 2017-2020 - 2019-2023
5G-Mobix [79]	Nokia, Valeo, Siemens, Ericsson, CTAG, etc.	Cooperative collision avoidance, Cloud-enabled platooning, Automated shuttle remote driving	CAM, DENM, CPM	Pre-deployment trials, Cross- border tests	2018-2022
C-MobILE [80]	PTV group, Swarco, Tom- Tom, CTAG, Applus IDI- ADA	Urban parking management, Dynamic eco-driving, CACC, Road work alerts	CAM, DENM, SPATEM, MAPEM, IVIM	Pilot tests, Urban & regional de- ployments	2017-2021

 TABLE IV

 Summary of C-ITS Projects and Deployments In Europe

applications, focusing on ensuring interoperability, safety, and reliability in vehicle-to-everything (V2X) communication. Some of the important J2945 standards are summarized as follows:

• SAE J2945/1: On-Board System Requirements for V2V Safety Communications [81]

Defines the minimum performance requirements for *Basic Safety Messages (BSM)* that vehicles broadcast in Vehicle-to-Vehicle (V2V) safety applications. BSMs contain essential vehicle data, such as position, speed, heading, brake status, and size. These messages enable applications like forward collision warning, emergency braking, and lane change warnings. The standard specifies the message frequency (typically 10 Hz) and message structure to ensure timely and accurate data exchange, critical for collision avoidance.

• SAE J2945/2: DSRC Performance Requirements for V2V Safety Awareness [82]

Establishes the performance requirements for Vehicle-to-

Vehicle (V2V) safety awareness applications, particularly using Dedicated Short-Range Communications (DSRC). The standard focuses on V2V applications that involve infrastructure components such as roadside units (RSUs) and traffic signals. The use cases covered in this document include (a) Emergency Vehicle Alert (EVA), (b) Roadside Alert (RA), (c) Safety Awareness - Object (SAW - O), and (d) Safety Awareness - Adverse road conditions (A).

• SAE J2945/4: Road Safety Applications [83]

The standard specifies message set requirements for different roadside safety applications which include: (a) Curve Speed Warning (CSW), (b) Reduced Speed Zone Warning (RSZW), (c) Lane Closure Warning (LCW), (d) Dynamic Traveler Information (DTI), and (e) Incident Information (INC). The document also presents the Road Safety Message (RCM) and the application of I2V communication for roadside safety. The message set and structure definition help achieve interoperability between I2V communication devices.

• SAE J2945/7: High-Precision Positioning for V2X Systems [84]

J2945/7 addresses new use cases that can benefit from increased precision and integrity in positioning systems. High-Precision Positioning Systems (HPPS) equipped V2X devices would allow to assess the quality of data being shared among road agents, especially vehicle state information such as position, and speed, which can be integrated with on-board positioning system to enable automated driving. Applications such as Emergency Brake Light (EEBL), Pedestrian cooperative detection, Cooperative automation platooning can be enhanced through the use of HPPS.

• SAE J2945/9: Vulnerable Road User (VRU) Safety [85]

Defines requirements for communicating Personal Safety Message (PSM) between vehicles and *Vulnerable Road Users (VRUs)*, such as pedestrians, bicyclists, and public safety personnel. This standard enables Vehicle-to-Pedestrian (V2P) applications where VRUs equipped with communication devices can broadcast their position and movement status to nearby vehicles equipped with Dedicated Short Range Communication (DSRC) devices. The document emphasizes the use of DRSC for broadcasting the PSM, although different wireless means may be used. J2945/9 sets criteria for alerting drivers about VRUs in potential collision paths, especially in urban environments with mixed traffic.

Today, many vehicles are already equipped with Advanced Driver-Assistance System (ADAS) and are able to perform level 1-2 autonomy tasks such as Forward Collision Warning (FCW), Lane Keeping Assistance (LKA), Automatic Emergency Braking (AEB) and many other functions (refer to SAE J3016 [86]). On the other hand, Level 3-5 vehicles (e.g. Waymo) equipped with Automated Driving Systems (ADS) are able to perform Dynamic Driving Tasks (DDT) and Object and Event Detection and Response (OEDR) with extended Operational Design Domain (ODD)(refer to SAE J3216 [87]).

As per the SAE J3216, Cooperative Driving Automation (CDA), cooperation between two or more road agents through Machine-to-Machine (M2M) communication can further enhance driver safety and improve traffic flow. It can enhance the performance of DDTs while the driving autonomous features are engaged in a vehicle. The Federal Highway Administration (FHWA) launched the open-source software - CARMA [88] in 2013 to demonstrate CDA and test the V2X capabilities and algorithms. Other notable open-source CDA frameworks include OpenCDA [89] and CoDrivingLLM [90]. OpenCDA focuses on developing a unified open-source CDA framework, while CoDrivingLLM leverages Large Language Models (LLMs) for decision-making in critical traffic scenarios.

SAE J3216 presents the taxonomy and definitions related to CDA, whereas other SAE standards focus on Concept of Operations (CONOPS), use cases, message flows, and performance requirements for specific CDA applications. Some of these standards are mentioned below:

• SAE J3186: Application protocol and requirements for

maneuver sharing and coordinating service (refer to [91]);

- SAE J3224: V2X sensor-sharing for cooperative and automated driving (refer to [92]);
- **SAE J3282:** CDA Feature Cooperative permissive left turn across opposing traffic with infrastructure guidance (refer to [93]);
- **SAE J3256:** CDA Feature Infrastructure-based prescriptive cooperative merge (refer to [94]); and
- SAE J3251: CDA Feature Perception status sharing for occluded pedestrian collision avoidance (refer to [95]).

V. REAL-WORLD COOPERATIVE DRIVING AUTOMATION EXPERIMENTS AND PUBLIC-DATASETS

The development and testing of integrity solutions for Cooperative Driving Automation (CDA) systems heavily rely on high-quality public datasets, as they provide foundational sensor data, environmental context, and multi-agent interactions for experimentation and benchmarking. Datasets [104] like KITTI, Waymo, and nuScenes have set industry standards by providing robust datasets for single-agent autonomous driving. These datasets include comprehensive sensor logs from onboard GNSS, IMUs, cameras, LiDARs, and radars, but focus predominantly on scenarios without active vehicle-to-vehicle (V2V) or vehicle-to-infrastructure (V2I) communications. As such, they primarily support perception tasks in isolated, single-agent settings and are less suitable for cooperative tasks central to CDA, such as shared situational awareness or collaborative decision-making.

Recognizing the limitations of single-agent datasets, new V2X datasets have been introduced in the last three years to capture multi-agent cooperative interactions. These datasets feature sensor logs from both onboard and infrastructure sensors, offering data in vehicle-to-vehicle and vehicle-to-infrastructure (V2V and V2I) settings. These data logs enable research on perception and decision-making for multi-agent interactions, enhancing autonomous systems with cooperative awareness and more accurate situational assessments.

The V2X datasets (see TABLE VI) serve various purposes such as 3D detection, tracking, trajectory prediction, and communication performance evaluation. V2X-Sim [105] data were collected from vehicles and infrastructure sensors in a SUMO and CARLA-built co-simulation environment. V2V4Real [106] focuses on data collected from two test vehicles in urban and highway conditions involving only V2V scenarios. However, data sets such as DAIR-V2X [107], TUMTraf-V2X [108], and V2X-Real [109] provide data that contain both V2V and V2I scenarios. V2X-Seq [110], a subset of DAIR-V2X provides sequential trajectory data at intersections for trajectory forecasting. The aforementioned datasets are collected mostly at intersections or in urban conditions. The H-V2X dataset consisting of the V2I scenario collected in China spans more than 100 km of highway roads with cameras and radars mounted on overhead masts.

These V2X datasets mostly focus on cooperative perception and sensor fusion problems and offer a benchmark for 3D detection, tracking, and trajectory prediction analyses. However, the dataset is collected locally at source i.e. vehicle,

 TABLE V

 Summary of C-ITS Projects and Deployments In USA

Project	Stakeholders	Key Applications	SAE J2735 Messages	Deployment Stage	Year
Safety Pilot Model De- ployment (SPMD) [96]	UMich, USDOT, ITS JPO, NGTSA, FHWA, etc.	Forward collision avoid- ance, intersection move- ment assist, left turn as- sist, blind spot warning	BSM, SPaT, TIM	Pilot Demonstrations, Interoperability Testing, Data collection	2010-2014
ITS-America national C-V2X deployment plan [97], [98]	USDOT, FHWA, FCC, NTIA, Automotive OEMs, State and local transportation agencies, etc.	FCC, Intersection movement assist, left-turn assist, eco- local driving, traffic signal pri- ority, etc.		Planning & De- ployment	2024- ongoing
Crash Avoidance Metrics Partnership (CAMP) [99]	Ford, GM, FHWA, etc.	Traffic optimization, red light violation warning, queue advisory	BSM, SPaT, MAP	Field Testing, Interoperability Testing	1999- ongoing
SAFE SWARM [100]	Honda, Ohio DOT, Veri- zon, etc.	Vehicle-to-vehicle obsta- cle detection, lane speed monitoring, braking event communication	BSM, SPaT	Field Testing	2017- ongoing
Heavy truck CACC project [101]	FHWA & Auburn univer- sity, Peloton technology, Meritor, Inc., etc.	Truck platooning, CACC	BSM	Field Testing	2013-2019
USDOT Connected Vehi- cle Pilots [102] - New york city pilot - Tampa (THEA) pilot - Wyoming DOT pilot	nected Vehi- 2]USDOT, ITS JPO, NY- CDOT, WYDOT, THEA, etc.Intersection assist, forward collision avoidance, red light violation warning, probe enabled traffic monitoringBS		BSM, SPaT, MAP, TIM, PSM	3SM, SPaT, MAP, TIM, Pilot Deployment, Interoperability Testing	
Ann Arbor Connected Vehicle Test Environment (AACVTE) [103]	UMTRI, USDOT, Savari, Denso, Cohda Wireless, etc.	{Same as SPMD project}	Same as SPMD project} BSM, SPaT, MAP, TIM, Large-scale Operational Deployment		2015-2018

infrastructure, and doesn't involve active V2X communication among the agents. The communication constraints such as bandwidth, latency, packet drops, etc., are imposed in postprocessing analysis. Recently released datasets such as Berlin-V2X, V2AIX, and TiHAN-V2X, involve active communication among the agents and have collected data for evaluating real-time communication performance. Berlin-V2X [111] and TIHAN-V2X [112] primarily provide information on cellular and sidelink communication in V2X scenarios that can help evaluate Quality of Service (QoS) Prediction and ML algorithms focusing on optimizing the communication channel. V2AIX dataset [113], released in 2024, consists of both cooperative perception data (V2V & V2I) and ETSI ITS-G5 V2X messages such as CAM, DENM, MAPEM, and SPATEM. Such datasets are crucial for analyzing the effects of CAV penetration rate on various applications under real-world communication constraints.

Despite recent advances, CDA research faces challenges due to the scarcity of datasets incorporating adversarial conditions, such as spoofed GNSS signals or real-time V2X messaging data under unreliable communication networks. Such scenarios are critical for testing system robustness against location spoofing, signal jamming, and data latency—factors that can severely impact automated vehicle safety and decisionmaking in the real world. Future datasets could improve by including edge cases, various weather and lighting conditions, and data with sporadic GNSS availability. Expanding upon these aspects will enable more resilient CDA systems, capable of handling a wider variety of environments and potential adversarial events.

VI. RESEARCH GAPS AND FUTURE DIRECTIONS

In this study, we reviewed the existing work on integrity monitoring for connected and automated vehicles. This section describes the implications of our findings and discusses potential limitations and possibilities for future research.

- Classical GNSS-based IMs: The majority of the research to date has been focused on IM methods for GNSS-based systems. This is primarily due to the ubiquitous nature of GNSS positioning systems and well-defined RNPs for GNSS-based navigation. Recently, researchers have started exploring integrity solutions for alternate GNSS-based positioning systems involving Signals of Opportunity, and communication techniques such as UWB and 5G-sidelink.
- IM for onboard perception systems: RNPs for navigation systems involving various other onboard sensors, such as camera, LiDAR, and radar are being developed for intelligent CAV applications. However, the research can be quickly brought to pace by leveraging Hardware-in-the-Loop (HiL) setups to test different sensor modalities, driving, and environment conditions that would be otherwise difficult to test in real-world conditions. Corner cases and external conditions such

Dataset	Year	Source	Test Infrastructure	Sensors / Information	Traffic Environment	V2X Comm. Protocol	Use Cases
V2X-Sim [105]	2022	In-Simulation: SUMO-CARLA	Multiple test vehicles / infrastructure	<i>OB</i> : G, I, L, C <i>RS</i> : L, C	Intersection	N.A	3D object detection, tracking, segmentation
DAIR- V2X [107]	2022	Beijing, China	Multiple test vehicles, 28 smart-intersection	<i>OB</i> : G, I, L, C <i>RS</i> : L, C	Intersection	N.A	3D object detection
V2X-Seq [110]	2023	Beijing, China	Multiple test vehicles, 28 smart-intersection	<i>OB</i> : G, I, L, C <i>RS</i> : L, C	Intersection	N.A	3D tracking, Trajectory forecasting
V2V4Real [106]	2023	Columbus, USA	2 test vehicles	<i>OB</i> : G, I, L, C	Highway, Urban	N.A	3D object detection, tracking, transfer learning
Berlin- V2X [111]	2023	Berlin, Germany	4 test vehicles	Cellular, Sidelink, GPS	Highway, Urban	LTE, SDR	multi-RAT QoS predic- tion, transfer learning
TUMTraf- V2X [108]	2024	Munich, Germany	1 test vehicle, 1 smart-intersection	<i>OB</i> : G, I, L, C <i>RS</i> : L, C	Intersection	N.A	3D object detection, tracking
V2X-Real [109]	2024	L.A, USA	2 test vehicles, 2 smart-intersection	<i>OB</i> : G, I, L, C <i>RS</i> : G, L, C	Intersection, Urban corridor	N.A	3D object detection
OpenAD [109]	2024	L.A, USA	2 test vehicles, 2 smart-intersection	<i>OB</i> : G, I, L, C <i>RS</i> : G, L, C	Intersection, Urban corridor	N.A	3D object detection
H-V2X [114]	2024	China	Smart-infrastructure spanning 100 Km	<i>RS</i> : C, R	Highway	N.A	BEV detection & track- ing, trajectory forecast- ing
V2AIX [113]	2024	Germany	V2X-enabled sensor- rich test vehicles & infrastructure	<i>OB</i> : G, I, L, C, V2X <i>RS</i> : L, C, V2X	Highway, Urban, Rural	ETSI ITS-G5	Vehicle Localization, V2X message standardization, CAV penetration analysis
TiHAN- V2X [112]	2024	Hyderabad, India	2 test vehicles, 1 smart-intersection	<i>OB</i> : G, V2X <i>RS</i> : V2X	Highway, Urban, Rural	5G-sidelink	Communication performance analysis - latency, path loss, throughput, SNR, etc.

TABLE VI SUMMARY OF V2X DATASETS

Legend:

G= GNSS, I= IMU, C= Camera, L= LiDAR, R= Radar, V2X= V2X communication module, OB: Onboard, RS: Roadside

as weather, and communication constraints could be imposed in a simulation environment to evaluate and validate IM methods.

- IM for V2X-based perception systems: There is a lack of IM methods to evaluate integrity risks in CAV applications that involve the sharing of perception data between vehicles. There is a wide variety of publicly available V2X datasets (see TABLE VI), but they are mostly used for cooperative perception tasks. Thus far, only a small amount of attention has been paid to evaluating integrity measures using these datasets. This could help quantify RNP parameters and provide new insights for developing new IM techniques for CAV applications in various traffic conditions.
- Sensitivity analyses: Furthermore, the performance of a CAV application on a vehicle depends on the type of vehicle, sensor modality, communication performance, and traffic environment. Hence, thorough sensitivity analyses are required to establish the RNPs for CAV applications in mixed-traffic situations. This could be

achieved by building virtual traffic environments in simulation platforms e.g. CARLA, with various road agents and sensor modalities to evaluate critical traffic conditions.

- Integrity for AI systems: In the last decade, Artificial Intelligence (AI) algorithms e.g. Machine Learning (ML) have become ubiquitous in the field of ITS. The emergence of deep neural networks and improvements in computational capabilities have made it possible to run real-time perception, planning, and control tasks. In addition, with the advent of generative AI and Large Language Models (LLMs), there is a buzz in the research community on the possible use of these models to handle complex perception tasks. However, few researchers have looked into the error quantification and reliability of such models. This could be a challenging yet interesting research topic in the future, especially for end-to-end deep neural net-based methods.
- Adherence to automotive standards: Researchers and automotive OEMs should form a consensus on defining

the RNPs that adhere to the existing automotive safety standards. This will help to encourage the early adoption of the developed FDI and IM methods in manufactured vehicles.

VII. CONCLUSIONS

This paper reviews existing Integrity Monitoring (IM) methods used in vehicle navigation and advocates the need for the development of new IM techniques in the field of Connected and Automated Vehicle (CAV) research. The consideration of positioning uncertainties in past CAV-related experiments is discussed followed by the definition of minimum Required Navigation Performance (RNP) criteria used in IM. It is found that most of the existing IM research focuses on onboard GNSS-based positioning systems. Although there exists a plethora of cooperative IM methods, the external sensor information such as Signals of Opportunity, DSRC, etc., are only used to eliminate the errors (multipath, NLOS) in GNSS signals. The integrity evaluation for cooperative positioning solutions involving V2V and V2I-based perception sensors are almost non-existent, even if various perception data-based V2X datasets are available in abundance. This might be due to the primary use cases of the aforementioned V2X datasets being 3D detection, tracking, and trajectory forecasting. Automotive safety standards and protocols are reviewed to gain insight into the standardization of V2X messages. These standards can be adopted by research communities for the development of new CA-centric IM frameworks. In future work, sensitivity analyses will be performed in simulation environments to identify safety-critical traffic maneuvers in various CAV applications and define a benchmark RNP chart that can be referred to by future researchers.

ACKNOWLEDGMENTS

This work was funded, partially or entirely, by a grant from the US Department of Transportation's University Transportation Centers Program through the Center for Assured & Resilient Navigation in Advanced Transportation Systems (CARNATIONS). The contents of this paper reflect only the views of the authors, who are responsible for the facts and the accuracy of the data presented.



Saswat Priyadarshi Nayak received the B. Tech degree in Electrical Engineering from the National Institute of Technology Rourkela, India in 2018. He served as a Project Associate at the Department of Aerospace Engineering, Indian Institute of Technology Kanpur, India 2018-19. He is currently pursuing a Ph.D. degree at the Center of Environmental Research and Technology (CE-CERT), University of California Riverside, USA. He is one of the recipients of the 2024 ITS California (ITS CA) and California Transportation Foundation (CTF) Schol-

arship. His main research interests include vehicle positioning and localization in mixed traffic scenarios, multi-sensor fusion, and connected vehicle applications.



Matthew J. Barth (Fellow, IEEE) received the M.S. and Ph.D degree in electrical and computer engineering from the University of California at Santa Barbara, in 1985 and 1990, respectively. He is currently the Hays Families Professor in the College of Engineering, University of California at Riverside, USA. He also served as the Director of the Center for Environmental Research and Technology. His current research interests include ITS and the environment, transportation/emissions modeling, vehicle activity analysis, advanced navigation techniques,

electric vehicle technology, and advanced sensing and control. Dr. Barth has been active in the IEEE Intelligent Transportation System Society for many years, serving as a Senior Editor for both the Transactions of ITS and the Transactions on Intelligent Vehicles. He served as the IEEE ITSS President for 2014 and 2015 and is currently the IEEE ITSS Vice President of Education.

REFERENCES

- N. Williams and M. Barth, "A qualitative analysis of vehicle positioning requirements for connected vehicle applications," *IEEE Intelligent Transportation Systems Magazine*, vol. 13, no. 1, pp. 225–242, 2021.
- [2] E. Yurtsever, J. Lambert, A. Carballo, and K. Takeda, "A Survey of Autonomous Driving: Common Practices and Emerging Technologies," *IEEE Access*, vol. 8, pp. 58443–58469, 2020.
- [3] P. Zabalegui, G. De Miguel, A. Pérez, J. Mendizabal, J. Goya, and I. Adin, "A review of the evolution of the integrity methods applied in gnss," *IEEE Access*, vol. 8, pp. 45813–45824, 2020.
- [4] W. Yan, Q. Zhang, Y. Zhang, A. Wang, and C. Zhao, "The Validation and Performance Assessment of the Android Smartphone Based GNSS/INS Coupled Navigation System," in *Lecture Notes in Electrical Engineering*, 2021, vol. 772 LNEE, pp. 310–319. [Online]. Available: https://link.springer.com/10.1007/978-981-16-3138-2_30
- [5] W. Yan, L. Bastos, A. Magalhães, Y. Zhang, and A. Wang, "Assessing Android Smartphone Based GNSS Positioning Accuracy," *Lecture Notes in Electrical Engineering*, vol. 652 LNEE, no. 18, pp. 144–153, 2020.
- [6] S. Li, B. Zhou, and M. Xu, "Analysis and improvement of car-following stability for connected automated vehicles with multiple information uncertainties," *Applied Mathematical Modelling*, vol. 123, pp. 790– 809, 11 2023.
- [7] X. Hu, L. Xie, L. Xie, S. Lu, W. Xu, and H. Su, "Distributed Model Predictive Control for Vehicle Platoon With Mixed Disturbances and Model Uncertainties," *IEEE Transactions on Intelligent Transportation Systems*, vol. 23, no. 10, pp. 17354–17365, 10 2022.
- [8] N. Williams, G. Wu, and M. Barth, "Position Uncertainty-Tolerant Cooperative Merging Application for Mixed Multilane Traffic," *IEEE Transactions on Intelligent Vehicles*, vol. 7, no. 1, pp. 143–153, 3 2022.
- [9] Q. Li, Z. Chen, and X. Li, "A Review of Connected and Automated Vehicle Platoon Merging and Splitting Operations," *IEEE Transactions* on *Intelligent Transportation Systems*, vol. 23, no. 12, pp. 22790– 22 806, 12 2022.
- [10] Y. Li, W. Chen, S. Peeta, and Y. Wang, "Platoon Control of Connected Multi-Vehicle Systems under V2X Communications: Design and Experiments," *IEEE Transactions on Intelligent Transportation Systems*, vol. 21, no. 5, pp. 1891–1902, 5 2020.
- [11] W. Luo, X. Li, J. Hu, and W. Hu, "Modeling and Optimization of Connected and Automated Vehicle Platooning Cooperative Control with Measurement Errors," *Sensors 2023, Vol. 23, Page 9006*, vol. 23, no. 21, p. 9006, 11 2023. [Online]. Available: https://www.mdpi.com/1424-8220/23/21/9006/ htmhttps://www.mdpi.com/1424-8220/23/21/9006
- [12] L. Lu, F. Zheng, and X. Liu, "Uncertainty, Efficiency, and Stability of Mixed Traffic Flow: Stochastic Model-Based Analyses," *Transportation Research Record*, 1 2024. [Online]. Available: https://journals.sagepub.com/doi/full/10.1177/03611981231215338
- [13] S. Chamideh, W. Tärneberg, and M. Kihl, "Impact of Positioning Uncertainty on Autonomous Intersection Management System," in 2023 IEEE 26th International Conference on Intelligent Transportation Systems (ITSC). IEEE, 9 2023, pp. 1912–1919. [Online]. Available: https://ieeexplore.ieee.org/document/10421986/
- [14] C. Vitale, P. Kolios, and G. Ellinas, "Autonomous Intersection Crossing With Vehicle Location Uncertainty," *IEEE Transactions on Intelligent Transportation Systems*, vol. 23, no. 10, pp. 17546–17561, 10 2022. [Online]. Available: https://ieeexplore.ieee.org/document/9721150/

- [15] —, "Optimizing vehicle re-ordering events in coordinated autonomous intersection crossings under cavs' location uncertainty," *IEEE Transactions on Intelligent Vehicles*, vol. 8, no. 5, pp. 3473– 3488, 2023.
- [16] S. Aoki and R. Rajkumar, "Safe Intersection Management With Cooperative Perception for Mixed Traffic of Human-Driven and Autonomous Vehicles," *IEEE Open Journal of Vehicular Technology*, vol. 3, pp. 251– 265, 2022.
- [17] T. Hassan, A. El-Mowafy, and K. Wang, "A review of system integration and current integrity monitoring methods for positioning in intelligent transport systems," *IET Intelligent Transport Systems*, vol. 15, no. 1, pp. 43–60, 1 2021. [Online]. Available: https: //onlinelibrary.wiley.com/doi/10.1049/itr2.12003
- [18] R. Sun, J. Wang, Q. Cheng, Y. Mao, and W. Y. Ochieng, "A new imu-aided multiple gnss fault detection and exclusion algorithm for integrated navigation in urban environments," *GPS Solut.*, vol. 25, no. 4, oct 2021. [Online]. Available: https: //doi.org/10.1007/s10291-021-01181-4
- [19] M. A. STURZA, "Navigation system integrity monitoring using redundant measurements," *NAVIGATION*, vol. 35, no. 4, pp. 483–501, 1988. [Online]. Available: https://onlinelibrary.wiley.com/doi/abs/10. 1002/j.2161-4296.1988.tb00975.x
- [20] A. Balakrishnan, S. A. Rodriguez F., and R. Reynaud, "An Integrity Assessment Framework for Multi-modal Vehicle Localization," in 2019 IEEE Intelligent Transportation Systems Conference (ITSC). IEEE, 10 2019, pp. 2976–2983. [Online]. Available: https://ieeexplore. ieee.org/document/8916874/
- [21] T. Binjammaz, A. H. Al-Bayatti, and A. Al-Hargan, "Context-aware gps integrity monitoring for intelligent transport systems," *Journal* of *Traffic and Transportation Engineering (English Edition)*, vol. 3, no. 1, pp. 1–15, 2016. [Online]. Available: https://www.sciencedirect. com/science/article/pii/S209575641530564X
- [22] I. Raouf, A. Khan, S. Khalid, M. Sohail, M. M. Azad, and H. S. Kim, "Sensor-Based Prognostic Health Management of Advanced Driver Assistance System for Autonomous Vehicles: A Recent Survey," *Mathematics 2022, Vol. 10, Page 3233*, vol. 10, no. 18, p. 3233, 9 2022. [Online]. Available: https://www.mdpi.com/2227-7390/10/18/ 3233/htmhttps://www.mdpi.com/2227-7390/10/18/3233
- [23] J. R. V. Solaas, E. Mariconti, and N. Tuptuk, "Systematic literature review: Anomaly detection in connected and autonomous vehicles," *IEEE Transactions on Intelligent Transportation Systems*, pp. 1–16, 2024.
- [24] F. A. Costa De Oliveira, F. S. Torres, and A. Garcia-Ortiz, "Recent Advances in Sensor Integrity Monitoring Methods - A Review," *IEEE Sensors Journal*, vol. 22, no. 11, pp. 10256–10279, 6 2022.
- [25] M. Worner, F. Schuster, F. Dolitzscher, C. G. Keller, M. Haueis, and K. Dietmayer, "Integrity for autonomous driving: A survey," *Proceedings of the IEEE/ION Position, Location and Navigation Symposium, PLANS 2016*, pp. 666–671, 5 2016.
- [26] M. Tossaint, J. Samson, F. Toran, J. Ventura-Traveset, M. Hernandez-Pajares, J. M. Juan, J. Sanz, and P. Ramos-Bosch, "The stanford -ESA integrity diagram: A new tool for the user domain SBAS integrity assessment," *Navigation, Journal of the Institute of Navigation*, vol. 54, no. 2, pp. 153–162, 2007.
- [27] H. Jing, Y. Gao, S. Shahbeigi, and M. Dianati, "Integrity Monitoring of GNSS/INS Based Positioning Systems for Autonomous Vehicles: State-of-the-Art and Open Challenges," *IEEE Transactions on Intelligent Transportation Systems*, 2022.
- [28] G. Gottschalg and S. Leinen, "Comparison and evaluation of integrity algorithms for vehicle dynamic state estimation in different scenarios for an application in automated driving," *Sensors*, vol. 21, no. 4, pp. 1–22, 2021.
- [29] G. Gottschalg, M. Becker, and S. Leinen, "Integrity concept for sensor fusion algorithms used in a prototype vehicle for automated driving," 2020 European Navigation Conference, ENC 2020, 11 2020.
- [30] A. Balakrishnan, S. R. Florez, and R. Reynaud, "Integrity Monitoring of Multimodal Perception System for Vehicle Localization," *Sensors* 2020, Vol. 20, Page 4654, vol. 20, no. 16, p. 4654, 8 2020. [Online]. Available: https://www.mdpi.com/1424-8220/20/16/ 4654/htmhttps://www.mdpi.com/1424-8220/20/16/4654
- [31] C. Mario and J. H. Rife, "Integrity monitoring of vision-based automotive lane detection methods," 2010. [Online]. Available: https://api.semanticscholar.org/CorpusID:113952716
- [32] J. Al Hage, P. Xu, and P. Bonnifait, "High integrity localization with multi-lane camera measurements," *IEEE Intelligent Vehicles Sympo*sium, Proceedings, vol. 2019-June, pp. 1232–1238, 6 2019.

- [33] X. Bai, W. Wen, and L. T. Hsu, "Using sky-pointing fish-eye camera and LiDAR to aid GNSS single-point positioning in urban canyons," pp. 908–914, 2020.
- [34] Z. Zhu and C. Taylor, "Conservative Uncertainty Estimation in Map-Based Vision-Aided Navigation," *IEEE Transactions on Aerospace and Electronic Systems*, vol. 53, no. 2, pp. 941–949, 4 2017.
- [35] C. Zhu, "Cooperative vision for swarm navigation," Ph.D. dissertation, Technische Universität München, 2019. [Online]. Available: https: //elib.dlr.de/133488/
- [36] C. Zhu, M. Meurer, and C. Günther, "Integrity of Visual Navigation—Developments, Challenges, and Prospects," *NAVIGATION: Journal of the Institute of Navigation*, vol. 69, no. 2, p. 69, 6 2022. [Online]. Available: https://navi.ion.org/content/69/2/navi.518https: //navi.ion.org/content/69/2/navi.518.abstract
- [37] D. Green, J. Gaffney, P. Bennett, Y. Feng, M. Higgins, and J. Millner, "Vehicle positioning for C-ITS in Australia (background document)," pp. 1–79, 4 2013. [Online]. Available: https://austroads. com.au/publications/connected-and-automated-vehicles/ap-r431-13
- [38] K. Ansari, Y. Feng, and M. Tang, "A Runtime Integrity Monitoring Framework for Real-Time Relative Positioning Systems Based on GPS and DSRC," *IEEE Transactions on Intelligent Transportation Systems*, vol. 16, no. 2, pp. 980–992, 4 2015.
- [39] K. Ansari, "Cooperative position prediction: Beyond vehicle-to-vehicle relative positioning," *IEEE Transactions on Intelligent Transportation Systems*, vol. 21, no. 3, pp. 1121–1130, 3 2020.
- [40] J. Liu, C. Rizos, and B. g. Cai, "A hybrid integrity monitoring method using vehicular wireless communication in difficult environments for GNSS," *Vehicular Communications*, vol. 23, p. 100229, 6 2020.
- [41] M. Maaref and Z. M. Kassas, "Autonomous Integrity Monitoring for Vehicular Navigation With Cellular Signals of Opportunity and an IMU," *IEEE Transactions on Intelligent Transportation Systems*, vol. 23, no. 6, pp. 5586–5601, 6 2022.
- [42] Z. Bai, S. Member, S. P. Nayak, X. Zhao, G. Wu, S. Member, M. J. Barth, X. Qi, Y. Liu, E. Akin Sisbot, and K. Oguchi, "Cyber Mobility Mirror: A Deep Learning-based Real-World Object Perception Platform Using Roadside LiDAR," SSRN Electronic Journal, 2 2022. [Online]. Available: https://arxiv.org/abs/2202.13505v2
- [43] S. P. Nayak, G. Wu, M. Barth, Y. Liu, E. A. Sisbot, and K. Oguchi, "Evaluation of Infrastructure-Assisted Cooperative Tracking of Vehicles Using Various Motion Models," 2023 IEEE/ION Position, Location and Navigation Symposium, PLANS 2023, pp. 243–253, 2023.
- [44] —, "Infrastructure-Assisted Cooperative State Estimation of Ego-Vehicle via Augmentation of Asynchronous Kinematic Measurements," in *Proceedings of the International Technical Meeting of The Institute of Navigation, ITM*, vol. 2024-January. Institute of Navigation, 2 2024, pp. 1103–1116. [Online]. Available: https: //www.ion.org/publications/abstract.cfm?articleID=19537
- [45] J. Xiong, J. W. Cheong, Z. Xiong, A. G. Dempster, S. Tian, and R. Wang, "Integrity for Multi-Sensor Cooperative Positioning," *IEEE Transactions on Intelligent Transportation Systems*, vol. 22, no. 2, pp. 792–807, 2 2021.
- [46] J. H. Rife, "Collaboration-enhanced receiver integrity monitoring (cerim)," 2011 14th International IEEE Conference on Intelligent Transportation Systems (ITSC), pp. 13–18, 2011. [Online]. Available: https://api.semanticscholar.org/CorpusID:7488196
- [47] S. Schön, C. Brenner, H. Alkhatib, M. Coenen, H. Dbouk, N. Garcia-Fernandez, C. Fischer, C. Heipke, K. Lohmann, I. Neumann, U. Nguyen, J. A. Paffenholz, T. Peters, F. Rottensteiner, J. Schachtschneider, M. Sester, L. Sun, S. Vogel, R. Voges, and B. Wagner, "Integrity and Collaboration in Dynamic Sensor Networks," *Sensors 2018, Vol. 18, Page 2400,* vol. 18, no. 7, p. 2400, 7 2018. [Online]. Available: https://www.mdpi.com/1424-8220/18/7/ 2400/htmhttps://www.mdpi.com/1424-8220/18/7/2400
- [48] Y. Feng, C. Wang, and C. Karl, "Determination of Required Positioning Integrity Parameters for Design of Vehicle Safety Applications," pp. 129–141, 2 2018. [Online]. Available: http: //www.ion.org/publications/abstract.cfm?jp=p&articleID=15556
- [49] F. Valentini, E. Cinque, V. Sulli, F. Rispoli, M. Pratesi, F. Santucci, and A. Neri, "On the Validation of Multi-sensor High Integrity Positioning solutions for the Connected Car: The P-CAR Infrastructure," in Proceedings of the International Technical Meeting of The Institute of Navigation, ITM, vol. 2022-January. Institute of Navigation, 2 2022, pp. 1358–1370. [Online]. Available: https: //www.ion.org/publications/abstract.cfm?articleID=18224
- [50] M. A. Gosavi, B. B. Rhoades, and J. M. Conrad, "Application of Functional Safety in Autonomous Vehicles Using ISO 26262 Standard:

- [51] M. Götze, M. Witt, N. Willer, and F. Raisch, "Safety in Use and Automated Driving in Consideration of the New ISO 21448," *ATZ worldwide 2023 125:4*, vol. 125, no. 4, pp. 38–43, 3 2023. [Online]. Available: https://link.springer.com/article/10.1007/ s38311-022-1456-9
- [52] F. Pisoni, G. Avellone, D. D. Grazia, A. Silverio, J. Durand, J. Garcia, E. D. Tijero, and E. Falletti, "GNSS Functional Safety for the Autonomous Vehicle," *Proceedings of the 32nd International Technical Meeting of the Satellite Division of the Institute of Navigation*, *ION GNSS+ 2019*, pp. 1696–1706, 9 2019. [Online]. Available: http://www.ion.org/publications/abstract.cfm?jp=p&articleID=16999
- [53] E. Infante, R. Gaum, and L. Norman, "Demonstration of a Functionally Safe GNSS/INS Positioning Software Library for Autonomous Land Vehicles," pp. 295–315, 9 2024. [Online]. Available: http://www.ion.org/publications/abstract.cfm?jp=p&articleID=19742
- [54] S. Diemert, L. Millet, J. Groves, and J. Joyce, "Safety Integrity Levels for Artificial Intelligence," *Lecture Notes in Computer Science* (*including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics*), vol. 14182 LNCS, pp. 397–409, 2023. [Online]. Available: https://link.springer.com/chapter/10.1007/ 978-3-031-40953-0_34
- [55] S. Burton, "Navigating the Evolving Landscape of Safety Standards for Machine Learning-based Road Vehicle Functions," SAE Research Report EPR2024017, 8 2024. [Online]. Available: https://www.sae. org/content/epr2024017
- [56] S. Krishnan, P. K. Venkatesh, S. Krishnan, and P. K. Venkatesh, "Validation Challenges of Safety of the Intended Functionalities (SOTIF) Risks/Hazards," *SAE Technical Papers*, 10 2022. [Online]. Available: https://doi.org/10.4271/2022-28-0005
- [57] V. J. E. Jiménez, G. Macher, D. Watzenig, and E. Brenner, "Safety of the Intended Functionality Validation for Automated Driving Systems by Using Perception Performance Insufficiencies Injection," *Vehicles* 2024, Vol. 6, Pages 1164-1184, vol. 6, no. 3, pp. 1164–1184, 7 2024. [Online]. Available: https://www.mdpi.com/2624-8921/6/3/55/ htmhttps://www.mdpi.com/2624-8921/6/3/55
- [58] A. Huang, X. Xing, T. Zhou, and J. Chen, "A Safety Analysis and Verification Framework for Autonomous Vehicles Based on the Identification of Triggering Events," in *SAE Technical Papers*, no. 2021. SAE International, 1 2021. [Online]. Available: https: //doi.org/10.4271/2021-01-5010
- [59] "Automotive Regulatory Guide 2023 ACEA European Automobile Manufacturers' Association." [Online]. Available: https: //www.acea.auto/publication/automotive-regulatory-guide-2023/
- [60] J. Y. Han, J. H. Park, H. J. Kim, and S. Lee, "Design of Sensor Data Processing Software for the ISO 23150 Standard: Application to Autonomous Vehicle Software," *Electronics 2023*, *Vol. 12, Page 4505*, vol. 12, no. 21, p. 4505, 11 2023. [Online]. Available: https://www.mdpi.com/2079-9292/12/21/4505/ htmhttps://www.mdpi.com/2079-9292/12/21/4505
- [61] "ISO 16505:2019 Road vehicles Ergonomic and performance aspects of Camera Monitor Systems — Requirements and test procedures." [Online]. Available: https://www.iso.org/standard/72000. html
- [62] Y. Li, W. Liu, Q. Liu, X. Zheng, K. Sun, and C. Huang, "Complying with ISO 26262 and ISO/SAE 21434: A Safety and Security Co-Analysis Method for Intelligent Connected Vehicle," *Sensors 2024, Vol. 24, Page 1848*, vol. 24, no. 6, p. 1848, 3 2024. [Online]. Available: https://www.mdpi.com/1424-8220/24/6/ 1848/htmhttps://www.mdpi.com/1424-8220/24/6/1848
- [63] J. M. L. Domínguez and T. J. Mateo Sanguino, "Review on V2X, I2X, and P2X Communications and Their Applications: A Comprehensive Analysis over Time," *Sensors 2019, Vol.* 19, Page 2756, vol. 19, no. 12, p. 2756, 6 2019. [Online]. Available: https://www.mdpi.com/1424-8220/19/12/2756/ htmhttps://www.mdpi.com/1424-8220/19/12/2756
- [64] A. Turley, K. Moerman, A. Filippi, and V. Martinez, "C-ITS: Three observations on LTE-V2X and ETSI-ITS G5," 2018. [Online]. Available: https://api.semanticscholar.org/CorpusID:54546491
- [65] M. Karoui, A. Freitas, and G. Chalhoub, "Performance comparison between LTE-V2X and ITS-G5 under realistic urban scenarios," *IEEE Vehicular Technology Conference*, vol. 2020-May, 5 2020.
- [66] "SCOOP Project : connected road and vehicle." [Online]. Available: https://www.scoop.developpement-durable.gouv.fr/en/
- [67] "Documents: C-Roads." [Online]. Available: https://www.c-roads.eu/ platform/documents.html

- [68] "EN 302 637-2 V1.3.1 Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Part 2: Specification of Cooperative Awareness Basic Service," Tech. Rep., 2014.
- [69] "EN 302 637-3 V1.3.1 Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Part 3: Specifications of Decentralized Environmental Notification Basic Service," Tech. Rep., 2019.
- [70] "EN 302 665 V1.1.1 Intelligent Transport Systems (ITS); Communications Architecture," Tech. Rep., 2010. [Online]. Available: http://portal.etsi.org/chaircor/ETSI_support.asp
- [71] "EN 302 571 V2.1.1 Intelligent Transport Systems (ITS); Radiocommunications equipment operating in the 5 855 MHz to 5 925 MHz frequency band; Harmonised Standard covering the essential requirements of article 3.2 of Directive 2014/53/EU," Tech. Rep., 2017. [Online]. Available: https://portal.etsi.org/TB/ ETSIDeliverableStatus.aspx
- [72] "TR 102 863 V1.1.1 Intelligent Transport Systems (ITS); Vehicular Communications; Basic Set of Applications; Local Dynamic Map (LDM); Rationale for and guidance on standardization," Tech. Rep., 2011.
- [73] J. Rodriguez, G. Gomez, J. Baranda, A. Lindenbergs, and M. Manni, "5G Architecture for Cross-border Mobility Services: The 5G-Routes Project Approach," in *15th ITS European Congress*, Lisbon, Portugal, 5 2023, pp. 22–24.
- [74] M. Schulze, T. Mäkinen, T. Kessel, S. Metzner, and H. Stoyanov, "DRIVE C2X Deliverable D11.6 Version 1.0 2 (Final Report)," European Union's Seventh Framework Programme, Tech. Rep., 2014.
- [75] "V2N2X Communications: Architecture, Solution Blueprint, and Use Case Examples." [Online]. Available: https://5gaa.org/content/uploads/
- [76] H.-W. Schaal and T. Löffler, "Car2x-From Research to Product Development: How Automotive OEMs and Suppliers are Successfully Completing Production Car2x Projects," VECTOR, Tech. Rep., 2012.
- [77] E. Catana, "CONCORDA approach: Connected Corridor for Driving Automation." Hamburg, Germany: 27th ITS World Congress, 2021, pp. 11–15. [Online]. Available: https://www. researchgate.net/publication/359258448_CONCORDA_approach_ Connected_Corridor_for_Driving_Automation_Proceedings_at_27th_ ITS_World_Congress_Hamburg_Germany_11-15_October_2021
- [78] S. Innamaa, "NordicWay 3 Final report: Evaluation Report," VTT Technical Research Centre of Finland Ltd, Tech. Rep., 2024. [Online]. Available: https://www.nordicway.net/
- [79] K. Trichias, "5GMOBIX D2.2: 5G architecture and technologies for CCAM specifications," Tech. Rep., 2019. [Online]. Available: https://www.5g-mobix.com/assets/files/5G-MOBIX-D2. 2-5G-architecture-and-technologies-for-CCAM-specifications-V1.0. pdf
- [80] R. Ferrandez, Y. Dajsuren, P. Karkhanis, M. Fünfrocken, and M. Pillado, "Modelling the C-ITS architectures: C-MobILE case study," in 25th ITS World Congress 2018, Copenhagen, Denmark, 11 2018.
- [81] V2X Core Technical Committee, On-Board System Requirements for V2V Safety Communications, apr 2020. [Online]. Available: https://doi.org/10.4271/J2945/1_202004
- [82] V2X Vehicular Applications Technical Committee, Dedicated Short Range Communications (DSRC) Performance Requirements for V2V Safety Awareness, oct 2018. [Online]. Available: https: //doi.org/10.4271/J2945/2_201810
- [83] Infrastructure Applications Technical Committee, Road Safety Applications, may 2023. [Online]. Available: https://doi.org/10. 4271/J2945/4_202305
- [84] V2X Core Technical Committee, *High-Precision Positioning for V2X Systems*, aug 2023. [Online]. Available: https://doi.org/10.4271/J2945/7_202308
- [85] V2X Vehicular Applications Technical Committee, Vulnerable Road User Safety Message Minimum Performance Requirements, mar 2017. [Online]. Available: https://doi.org/10.4271/J2945/9_201703
- [86] On-Road Automated Driving (ORAD) Committee, Taxonomy and Definitions for Terms Related to Driving Automation Systems for On-Road Motor Vehicles, apr 2021. [Online]. Available: https://doi.org/10.4271/J3016_202104
- [87] Cooperative Driving Automation(CDA) Committee, Taxonomy and Definitions for Terms Related to Cooperative Driving Automation for On-Road Motor Vehicles, jul 2021. [Online]. Available: https: //doi.org/10.4271/J3216_202107
- [88] Y. Lou, D. Hale, M. McConnel, A. Ghiasi, M. Jannat, and S. Racha, "FHWA Cooperative Automation Research: CARMA Proof of-Concept TSMO Use Case Testing: CARMA Cooperative Perception

Low-Level Concept of Operations — FHWA," 11 2022. [Online]. Available: https://doi.org/10.21949/1521946

- [89] R. Xu, Y. Guo, X. Han, X. Xia, H. Xiang, and J. Ma, "OpenCDA: An Open Cooperative Driving Automation Framework Integrated with Co-Simulation," *IEEE Conference on Intelligent Transportation Systems*, *Proceedings*, *ITSC*, vol. 2021-September, pp. 1155–1162, 9 2021.
- [90] S. Fang, J. Liu, M. Ding, Y. Cui, C. Lv, S. Member, P. Hang, and J. Sun, "Towards Interactive and Learnable Cooperative Driving Automation: a Large Language Model-Driven Decision-Making Framework," 9 2024. [Online]. Available: https://arxiv.org/abs/2409.12812v2
- [91] V2X Vehicular Applications Technical Committee, Application Protocol and Requirements for Maneuver Sharing and Coordinating Service, mar 2023. [Online]. Available: https://doi.org/10.4271/J3186_ 202303
- [92] Advanced Applications Technical Committee, V2X Sensor-Sharing for Cooperative and Automated Driving, aug 2022. [Online]. Available: https://doi.org/10.4271/J3224_202208
- [93] Cooperative Driving Automation(CDA) Committee, Cooperative Infrastructure CDA Feature: Cooperative Permissive Left Turn Across Opposing Traffic with Infrastructure Guidance, jun 2024. [Online]. Available: https://doi.org/10.4271/J3282_202406
- [94] —, Cooperative Driving Automation (CDA) Feature Infrastructure-Based Prescriptive Cooperative Merge, mar 2024. [Online]. Available: https://doi.org/10.4271/J3256_202403
- [95] —, Cooperative Driving Automation (CDA) Feature: Perception Status Sharing for Occluded Pedestrian Collision Avoidance, aug 2023. [Online]. Available: https://doi.org/10.4271/J3251_202308
- [96] K. Gay and V. Kniss, "Safety Pilot Model Deployment: Lessons Learned and Recommendations for Future Connected Vehicle Activities," Tech. Rep., 9 2015. [Online]. Available: https://rosap.ntl. bts.gov/view/dot/4361
- [97] ITS America, "ITS America National V2X Deployment Plan: An Infrastructure & Automaker Collaboration," Connected Vehicles, ITS America, Tech. Rep., 4 2023. [Online]. Available: https://itsa.org/ advocacy-material/its-america-national-v2x-deployment-plan/
- [98] US-DOT ITS Joint Program Office, "Saving Lives with Connectivity: A Plan to Accelerate V2X Deployment Non-Binding Contents," Tech. Rep., 8 2024. [Online]. Available: https://www.its.dot.gov/research_ areas/emerging_tech/pdf/Accelerate_V2X_Deployment_final.pdf
- [99] "Publications Farmington Hills, Novi, Southfield CAMP LLC." [Online]. Available: https://www.campllc.org/publications/
- [100] "Honda Global SAFE SWARM." [Online]. Available: https: //global.honda/en/innovation/CES/2020/safe_swarm.html
- [101] S. E. Shladover, L. Yang, H. Ramezani, J. Spring, C. Nowakowski, D. Nelson, D. Thompson, A. Kailas, and B. McAuliffe, "Cooperative Adaptive Cruise Control (CACC) For Partially Automated Truck Platooning," Tech. Rep., 2018. [Online]. Available: https://rosap.ntl. bts.gov/view/dot/43776
- [102] "USDOT ITS Research Connected Vehicle Pilot Deployment Program." [Online]. Available: https://www.its.dot.gov/pilots/overview. htm
- [103] X. Wang, S. Shen, D. Bezzina, J. R. Sayer, H. X. Liu, and Y. Feng, "Data Infrastructure for Connected Vehicle Applications," *Transportation Research Record*, vol. 2674, no. 5, pp. 85–96, 5 2020.
- [104] M. Liu, E. Yurtsever, J. Fossaert, X. Zhou, W. Zimmer, Y. Cui, B. L. Zagar, and A. C. Knoll, "A Survey on Autonomous Driving Datasets: Statistics, Annotation Quality, and a Future Outlook," *IEEE Transactions on Intelligent Vehicles*, 2024.
- [105] Y. Li, D. Ma, Z. An, Z. Wang, Y. Zhong, S. Chen, and C. Feng, "V2X-Sim: Multi-Agent Collaborative Perception Dataset and Benchmark for Autonomous Driving," *IEEE Robotics and Automation Letters*, vol. 7, no. 4, pp. 10914–10921, 10 2022.
- [106] R. Xu, X. Xia, J. Li, H. Li, S. Zhang, Z. Tu, Z. Meng, H. Xiang, X. Dong, R. Song, H. Yu, B. Zhou, and J. Ma, "V2V4Real: A Real-world Large-scale Dataset for Vehicle-to-Vehicle Cooperative Perception," *Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition*, vol. 2023-June, pp. 13712– 13722, 3 2023. [Online]. Available: https://arxiv.org/abs/2303.07601v2
- [107] H. Yu, Y. Luo, M. Shu, Y. Huo, Z. Yang, Y. Shi, Z. Guo, H. Li, X. Hu, J. Yuan, and Z. Nie, "DAIR-V2X: A Large-Scale Dataset for Vehicle-Infrastructure Cooperative 3D Object Detection," *Proceedings* of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition, vol. 2022-June, pp. 21 329–21 338, 4 2022. [Online]. Available: https://arxiv.org/abs/2204.05575v1
- [108] W. Zimmer, G. A. Wardana, S. Sritharan, X. Zhou, R. Song, and A. C. Knoll, "TUMTraf V2X Cooperative Perception Dataset," 2024 IEEE/CVF Conference on Computer Vision and Pattern

Recognition (CVPR), pp. 22668–22677, 62024. [Online]. Available: https://ieeexplore.ieee.org/document/10658179/

- [109] H. Xiang, Z. Zheng, X. Xia, R. Xu, L. Gao, Z. Zhou, X. Han, X. Ji, M. Li, Z. Meng, L. Jin, M. Lei, Z. Ma, Z. He, H. Ma, Y. Yuan, Y. Zhao, and J. Ma, "V2X-Real: a Largs-Scale Dataset for Vehicle-to-Everything Cooperative Perception," 3 2024. [Online]. Available: https://arxiv.org/abs/2403.16034v1
- [110] H. Yu, W. Yang, H. Ruan, Z. Yang, Y. Tang, X. Gao, X. Hao, Y. Shi, Y. Pan, N. Sun, J. Song, J. Yuan, P. Luo, and Z. Nie, "V2X-Seq: A Large-Scale Sequential Dataset for Vehicle-Infrastructure Cooperative Perception and Forecasting," pp. 5486–5495, 5 2023. [Online]. Available: https://arxiv.org/abs/2305.05938v1
- [111] R. Hernangómez, P. Geuer, A. Palaios, D. Schäufele, C. Watermann, K. Taleb-Bouhemadi, M. Parvini, A. Krause, S. Partani, C. Vielhaus, M. Kasparick, D. F. Külzer, F. Burmeister, F. H. P. Fitzek, H. D. Schotten, G. Fettweis, and S. Stańczak, "Berlin V2X: A Machine Learning Dataset from Multiple Vehicles and Radio Access Technologies," in 2023 IEEE 97th Vehicular Technology Conference (VTC2023-Spring), vol. 2023-June. IEEE, 6 2023, pp. 1–5. [Online]. Available: https://ieeexplore.ieee.org/document/10200750/
- [112] A. ., P. Pydimarri, P. Rajalakshmi, S. V. Srikanth, and M. Prasad, "Tihan-v2x: A comprehensive dataset for dynamic c-v2x communication within the indian context," 2024. [Online]. Available: https://dx.doi.org/10.21227/f2kd-9g03
- [113] G. Kueppers, J.-P. Busch, L. Reiher, and L. Eckstein, "V2AIX: A Multi-Modal Real-World Dataset of ETSI ITS V2X Messages in Public Road Traffic," 3 2024. [Online]. Available: https: //arxiv.org/abs/2403.10221v2
- [114] C. Liu, M. Zhu, and C. Ma, "H-V2X: A Large Scale Highway Dataset for BEV Perception," in *Lecture Notes in Computer Science* (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics). Springer, Cham, 2025, vol. 15059 LNCS, pp. 139–157. [Online]. Available: https://link.springer.com/10. 1007/978-3-031-73232-4_8