Transformers versus the EM Algorithm in Multi-class Clustering

Yihan He¹ Hong-Yu Chen² Yuan Cao³ Jianqing Fan¹ Han Liu²

Abstract

LLMs demonstrate significant inference capacities in complicated machine learning tasks, using the Transformer model as its backbone. Motivated by the limited understanding of such models on the unsupervised learning problems, we study the learning guarantees of Transformers in performing multi-class clustering of the Gaussian Mixture Models. We develop a theory drawing strong connections between the Softmax Attention layers and the workflow of the EM algorithm on clustering the mixture of Gaussians. Our theory provides approximation bounds for the Expectation and Maximization steps by proving the universal approximation abilities of multivariate mappings by Softmax functions. In addition to the approximation guarantees, we also show that with a sufficient number of pre-training samples and an initialization, Transformers can achieve the minimax optimal rate for the problem considered. Our extensive simulations empirically verified our theory by revealing the strong learning capacities of Transformers even beyond the assumptions in the theory, shedding light on the powerful inference capacities of LLMs.

1. Introduction

Large Language Models (LLMs) have demonstrated significant success in learning and performing inference on real world high dimensional datasets. Most modern LLMs use the Transformer model (Vaswani, 2017) as their backbone.

Many existing works have considered the theoretical guarantees of the in-context-learning setup of Transformers (Bai et al., 2024; Akyürek et al., 2022). However, in practice, LLMs require a significant amount of pretraining data to achieve their empirical advantage. And, little is known about the unsupervised learning guarantees of Transformers, especially after a sufficient number of problem instances are observed by the Transformer model in the pre-training phase. Motivated by the strong empirical performance of Transformers, we provide theoretical analysis of the Transformers on a standard unsupervised learning problem of clustering a mixture of Gaussians in the multi-class setup. Our results suggest that Transformers, like human brains, can benefit from experienced problem instances and learn the way to solve the problem (algorithms). Then, when fed with a new problem instance, Transformers can solve it through the learned algorithms naturally.

The problem of clustering a mixture of multivariate Gaussian is one of the most standard unsupervised learning problems (Bishop & Nasrabadi, 2006) that can be solved by the EM algorithm or Lloyd's algorithm (Lloyd, 1982). The EM algorithm contains both the *Expectation* and the *Maximization* sub-procedures where the *Expectation Step* creates a function for **the expectation** of the log-likelihood evaluated using the current estimate for the parameters and the *Maximization Step* computes parameters maximizing the expected log-likelihood given by the *Expectation Step*. We draw connections between the Softmax Attention in Transformers and the EM algorithms through the following:

- 1. *The Expectation Step* involves a normalized sum in **the expectation** whose weight vector is naturally given by the output of the softmax function as $\left[\frac{\exp(z_1)}{\sum_{i=1}^{D} \exp(z_i)}, \dots, \frac{\exp(z_D)}{\sum_{i=1}^{D} \exp(z_i)}\right].$
- 2. *The Maximization Step* involves finding the index with the maximum value in a vector (the Hardmax Function). This is naturally approximated by the Softmax function as its name suggests.

Given the strong connections of the two steps to the Softmax function, we build an approximation theory for Lloyd's algorithm in a constructive manner. We also note that existing works only build approximation bound for multihead ReLU neural networks (Bach, 2017) while the Softmax approximation of multivariate to multivariate mapping remains a myth. We resolve this obstacle by proving an approximation bound for multi-head Transformers on a class of $\mathbb{R}^{d_1} \to \mathbb{R}^{d_2}$ mappings that might be of independent interests.

Contributions. We summarize our major contributions as follows:

¹Princeton University, Princeton, NJ, USA ²Northwestern University, Evanston, IL, USA ³The University of Hong Kong, Hong Kong. Correspondence to: Yihan He <yihan.he@princeton.edu>.

- We rigorously show that a pre-trained Transformer can perform multi-class clustering by drawing its connection to Lloyd's algorithm, which is used as a proof machine. We provide constructive proof and error bound for the approximation;
- 2. We further consider the setup where the Transformer model is trained with independent instances from a class of clustering problems whose labels are used as supervision. We show that Transformers are able to generalize the mapping on new clustering problem instances. We provide upper bounds on the generalization error for the empirical risk minimizer in the pretraining task. Moreover, we show that given a sufficient number of training instances and proper initialization, pre-trained Transformers reach the fundamental limit of the problem;
- 3. We systematically evaluate the performance of Transformers through extensive simulations. These empirical results demonstrate that Transformers perform well in the multi-class clustering task even when the assumptions leading to the theoretical results no longer hold.

1.1. Related Works

Transformers are algorithm approximators. Recently, the capacity of Transformers to automatically performing certain algorithms has drawn great attention from researchers. In particular, a rich line of recent works studied the expressive power of Transformers to perform in-context learning (ICL) (Akyürek et al., 2022; Bai et al., 2024; Abernethy et al., 2024; Li et al., 2023a; Jeon et al., 2024). Specifically, Akyürek et al. (2022); Bai et al. (2024); Abernethy et al. (2024) studied how Transformers perform gradient descent based training to perform ordinary or sparse linear regression on the context. Chen et al. (2024b) further showed how Transformers utilize the multi-head structure to perform in-context sparse linear regression. Li et al. (2023a) studied the generalization and stability of transformers in ICL tasks. Jeon et al. (2024) studies the informationtheoretical lower bound of in-context learning. Another closely related line of works studied how Transformers can be pretrained by gradient descent to perform certain tasks. Specifically, Zhang et al. (2023); Huang et al. (2023); Chen et al. (2024a) studied the pretraining optimization dynamics of Transformers to learn in-context linear prediction rules. Li et al. (2024b) showed that one-layer Transformers can be trained to perform one-nearest neighbor classification in context. Ahn et al. (2024); Giannou et al. (2024) studied the training of Transformers in learning various optimization methods. Li et al. (2023b) studied how Transformers can be trained to learn topic models. Jelassi et al. (2022) proved that Vision Transformers can learn a class of image-like data

whose patches follow certain spatial structures. Zhang & Cao (2025) studied how Transformers can learn to perform variable selection in "group-sparse" linear regression.

Other theoretical studies on Transformers. Various efforts have been made to gain a theoretical understanding of Transformers. Yun et al. (2019) analyzed the universal approximation properties of Transformers for sequence-tosequence functions. Li et al. (2023b) studied the mean-filed limit of large-scale Transformers and proved global convergence in regression tasks. Pérez et al. (2021) showed that Transformers with hard-attention are Turing complete exclusively based on their capacity to compute and access internal dense representations of the data. Bhattamishra et al. (2020) further provided an alternate and simpler proof to show that vanilla Transformers are Turing-complete, and then proved that Transformers with only positional masking and without any positional encoding are also Turing-complete. Liu et al. (2022) showed that a low-depth Transformer can represent the computations of any finite-state automaton by hierarchically reparameterizing its recurrent dynamics. Yao et al. (2021) demonstrated that Transformers can efficiently process bounded hierarchical languages, offering better space complexity compared to recurrent neural networks.

Notations In this work we follow the following notation conventions. The vector-valued variable is given by boldfaced characters. We denote $[n] := \{1, \ldots, n\}$ and $[i : j] := \{i, i + 1, \ldots, j\}$ for i < j. The universal constants are given by C and are ad hoc. For a vector \boldsymbol{v} we denote $\|\boldsymbol{v}\|_2$ as its L_2 norm. For a matrix $\boldsymbol{A} \in \mathbb{R}^{m \times n}$ we denote its operator norm as $\|\boldsymbol{A}\|_2 := \sup_{\boldsymbol{v} \in \mathbb{S}^{n-1}} \|\boldsymbol{A}\boldsymbol{v}\|_2$. Given two sequences a_n and b_n , we denote $a_n \leq b_n$ or $a_n = O(b_n)$ if $\limsup_{n \to \infty} |\frac{a_n}{b_n}| < \infty$ and $a_n = o(b_n)$ if $\limsup_{n \to \infty} |\frac{a_n}{b_n}| < \infty$ and $a_n = o(b_n)$ if $\limsup_{n \to \infty} |\frac{a_n}{b_n}| < \infty$ and $a_n = o(b_n)$ if $\limsup_{n \to \infty} |\frac{a_n}{b_n}| < \infty$ and $a_n = o(b_n)$ if $\limsup_{n \to \infty} |\frac{a_n}{b_n}| < \infty$ and $a_n = o(b_n)$ if $\limsup_{n \to \infty} |\frac{a_n}{b_n}| < \infty$ and $a_n = o(b_n)$ if w and are ad hoc. We use $\mathcal{B}(\|\cdot\|, r)$ to denote a ball with radius r under the norm $\|\cdot\|$.

Organizations The rest of the paper is organized as follows: Section 2 reviews standard contexts and describes the learning problem; Section 3 provides rigorous theoretical results and sketches of proof; Section 4 provides extensive experimental details and results; Section 5 discusses the limitations and potential future works. The detailed proofs and additional figures in experiments are delayed to the appendix. The supplementary materials include the code for the experiments.

2. Connecting Transformers with EM

This section discusses the connections between the EM algorithm and the Transformer architecture. Our discussion is split into 2 separate subsections: In 2.1, we review the

mathematical definitions of the Softmax-based Transformer model; In 2.2, we review the EM algorithm and connect it with the multiphase Transformer design. In section 2.3, we discuss the pretraining procedure of the Transformers.

2.1. The Transformer Architecture

We consider the Softmax Attention Layer, which is defined as follows:

Definition 2.1 (Softmax Attention). The Softmax Attention layer is defined as a self-attention layer with M heads denoted as $Attn_{\theta_1}(\cdot)$ with parameters $\theta_1 = \{(V_m, Q_m, K_m)\}_{m \in [M]} \subset \mathbb{R}^{D \times D}$. On input sequence $H \in \mathbb{R}^{D \times N}$,

$$Attn_{\boldsymbol{\theta}_{1}}(\boldsymbol{H}) = \boldsymbol{H} \\ + \sum_{m=1}^{M} (\boldsymbol{V}_{m}\boldsymbol{H}) \text{SoftMax}\Big((\boldsymbol{Q}_{m}\boldsymbol{H})^{\top} (\boldsymbol{K}_{m}\boldsymbol{H}) \Big)$$

where SoftMax is the activation function defined by

SoftMax(
$$\boldsymbol{x}$$
) = $\begin{bmatrix} \exp(x_1) & \cdots & \exp(x_d) \\ \sum_{i=1}^d \exp(x_i) & \cdots & \sum_{i=1}^d \exp(x_d) \end{bmatrix}^\top$,

for all $x \in \mathbb{R}^d$.

In addition to the Softmax Attention layer, we also consider an un-normalized Attention layer, given by

Definition 2.2 (Un-normalized Attention). The unnormalized Attention layer is defined as a self-attention layer with M heads and denoted as $nAttn_{\theta_1}(\cdot)$ with parameters $\theta_1 = \{(V_m, Q_m, K_m)\}_{m \in [M]} \subset \mathbb{R}^{D \times D}$. On input sequence $H \in \mathbb{R}^{D \times N}$,

$$nAttn_{\boldsymbol{\theta}_1}(\boldsymbol{H}) = \boldsymbol{H} + \sum_{m=1}^{M} (\boldsymbol{V}_m \boldsymbol{H}) (\boldsymbol{Q}_m \boldsymbol{H})^{\top} (\boldsymbol{K}_m \boldsymbol{H}).$$

Remark 1. The un-normalized Attention layer is the Attention layer without the non-linear activation function. This layer is studied mainly for technical reasons. We also provide results not using the un-normalized Attention layer, despite having weaker rates.

The following defines the classical Fully-Connected (FC) layers with residual connections.

Definition 2.3 (FC Layer). A FC layer with hidden dimension D' is denoted as $FC_{\theta}(\cdot)$ with parameter $\theta_2 \in (W_1, W_2) \in \mathbb{R}^{D' \times D} \times \mathbb{R}^{D \times D'}$. On any input sequence $H \in \mathbb{R}^{D \times N}$, we define

$$FC_{\boldsymbol{\theta}_2}(\boldsymbol{H}) := \boldsymbol{H} + \boldsymbol{W}_2 \sigma(\boldsymbol{W}_1 \boldsymbol{H}).$$

Then, we use the above definitions on the FC and the Attn/nAttn layers to define the Transformer model and the Transformer+ model.

Definition 2.4 (Transformer). We define the Transformer $TF_{\theta}(\cdot)$ as a composition of the self-attention layers with the FC layers. Consider the output dimension to be \tilde{D} , a *L*-layered Transformer is defined by

$$TF_{\boldsymbol{\theta}}(\boldsymbol{H}) :=$$

$$\tilde{\boldsymbol{W}}_{0} \times FC_{\boldsymbol{\theta}_{2}^{L}}(Attn_{\boldsymbol{\theta}_{1}^{L}}(\cdots FC_{\boldsymbol{\theta}_{2}^{1}}(Attn_{\boldsymbol{\theta}_{1}^{1}}(\boldsymbol{H}))) \times \tilde{\boldsymbol{W}}_{1},$$

 $W_0 \times FC_{\theta_2}(Attn_{\theta_1}(\dots FC_{\theta_2}(Attn)))$ where $\tilde{W}_0 \in \mathbb{R}^{d_1 \times D}$ and $\tilde{W}_1 \in \mathbb{R}^{N \times d_2}$.

The two additional matrices \tilde{W}_0 and \tilde{W}_1 serve for the dimension adjustment purpose such that the output of $TF_{\theta}(H)$ or $TF_{\theta}^+(H)$ will be of dimension $\mathbb{R}^{d_1 \times d_2}$.

Then, we introduce a class of models called the Transformer+, which includes the un-normalized Attention layer. **Definition 2.5** (Transformer+). Under the same notations as definition 2.4. We define the Transformer+ model $TF_{\theta}^{+}(\cdot)$ as

$$TF_{\boldsymbol{\theta}}^{+}(\boldsymbol{H}) := \tilde{\boldsymbol{W}}_{0} \times FC_{\boldsymbol{\theta}_{2}^{L}}(A_{\boldsymbol{\theta}_{1}^{L}}(\cdots FC_{\boldsymbol{\theta}_{2}^{1}}(A_{\boldsymbol{\theta}_{1}^{1}}(\boldsymbol{H}))) \times \tilde{\boldsymbol{W}}_{1},$$

where $A \in \{Attn, nAttn\}$ is either the Attn layer defined in definition 2.1 or the nAttn layer defined in definition 2.2.

We use θ to denote all the parameters in the Transformer and the super-index ℓ to denote the parameter matrix corresponding to the ℓ -th layer. Under such definition, the parameter θ is given by

$$\boldsymbol{\theta} = \{\{(\{\boldsymbol{Q}_m^{(\ell)}, \boldsymbol{K}_m^{(\ell)}, \boldsymbol{V}_m^{(\ell)}\}_{m \in [M]}, \boldsymbol{W}_1^{(\ell)}, \boldsymbol{W}_2^{(\ell)})\}_{\ell \in [L]}, \tilde{\boldsymbol{W}}_0, \tilde{\boldsymbol{W}}_1\}$$

Following the notations in (Bai et al., 2024), we define the operator norm of the parameter θ as follows.

$$\begin{split} \|\boldsymbol{\theta}\| &:= \max_{\ell \in [L]} \Big\{ \max_{m \in [M^{(\ell)}]} \Big\{ \|\boldsymbol{Q}_m^{(\ell)}\|_2, \|\boldsymbol{K}_m^{(\ell)}\|_2 \Big\} \\ &+ \|\tilde{\boldsymbol{W}}_0\|_2 + \|\tilde{\boldsymbol{W}}_1\|_2 + \sum_{m=1}^{M^{(\ell)}} \|\boldsymbol{V}_m^{(\ell)}\|_2 + \|\boldsymbol{W}_1^{(\ell)}\|_2 + \|\boldsymbol{W}_2^{(\ell)}\|_2 \Big\}, \end{split}$$

where $M^{(\ell)}$ is the number of heads of the ℓ -th attention layer. It is also shown in (Bai et al., 2024) that such a norm relates to the Lipschitz constant of Transformers, which controls the model complexity and leads to the generalization bound. Hence, in this work, we consider the following space of the model

$$\Theta(B_{\boldsymbol{\theta}}, B_M, B_L) = \left\{ (\boldsymbol{\theta}, \{M^{(\ell)}\}_{\ell \in [L]}, L) : \|\|\boldsymbol{\theta}\|\| \le B_{\boldsymbol{\theta}}, \\ \sup_{\ell \in [L]} M^{(\ell)} \le B_M, L \le B_L \right\}.$$

And for the subspace of θ given M and L as hyperparamaters, we denote by $\Theta_{B_M,B_L}(B_{\theta})$.

2.2. The Learning Problem and EM

In this section, we first provide notations for the sub-Gaussian mixture models and the clustering problem. Then, we provide the literature on the EM Algorithm and Lloyd's algorithm.

2.2.1. CLUSTERING MIXTURE OF GAUSSIANS

We take samples $\{X_i\}_{i \in [N]}$ from a sub-Gaussian mixture model with in total of k centers $\{\mu_i\}_{i \in [k]}$. In particular, we let

$$oldsymbol{X} := ig[oldsymbol{X}_1 \dots oldsymbol{X}_Nig], \quad oldsymbol{X}_i := oldsymbol{\mu}_{z_i} + oldsymbol{\omega}_i ext{ for all } i \in [N],$$

where $z_i :\in [k]$ corresponds to the membership of *i*-th index. We assume the following condition to hold for ω_i .

Assumption 2.6. $\{\omega_i\}_{i \in [N]}$ are i.i.d. zero mean random variables from sub-Gaussian distribution that satisfies $\mathbb{E}[\exp(\boldsymbol{a}^{\top}\boldsymbol{\omega})] \leq \exp\left(\frac{1}{2}\sigma^2 \|\boldsymbol{a}\|_2^2\right)$ for all $\boldsymbol{a} \in \mathbb{R}^d$.

We consider the mapping from z to a set of one-hot vectors

$$\boldsymbol{P}_{1}(z) := \begin{bmatrix} \boldsymbol{p}_{1,1} & \boldsymbol{p}_{1,2} & \dots & \boldsymbol{p}_{1,N} \end{bmatrix} \in \mathbb{R}^{k \times N}, \boldsymbol{p}_{1,i,j} := \mathbb{1}_{j=z_{i}}.$$
(1)

Define $S_k : [k] \to [k]$ as the set of permutations of [k]. We consider the following loss function for the Transformer output.

$$L(A_{\boldsymbol{\theta}}(\boldsymbol{H}), \boldsymbol{P}_{1}(\boldsymbol{z})) := \inf_{\pi \in \mathcal{S}_{k}} \frac{1}{N} \|\boldsymbol{P}_{1}(\pi(\boldsymbol{z}_{i})) - A_{\boldsymbol{\theta}}(\boldsymbol{H})\|_{1,1}$$

where $A \in \{TF, TF^+\}$.

The Parameter Space This work considers the following space of parameters of the generative model. Here, we denote F_{ω} as the distribution of the random variable ω .

$$\Theta_{GM} = \left\{ (\boldsymbol{\mu}, \boldsymbol{z}, F_{\boldsymbol{\omega}}), \boldsymbol{\mu} \in \mathbb{R}^{d \times k}, \Delta \leq \min_{i \neq j} \|\boldsymbol{\mu}_i - \boldsymbol{\mu}_j\|_2, \\ \boldsymbol{z} : [N] \to [k], |\{i \in [N], \boldsymbol{z}_i = u\}| \geq \alpha n, \forall u \in [k], \\ \omega_i \text{ is i.i.d. } \sigma \text{ sub-Gaussian random variable } \forall i \in [N] \right\}.$$

We further consider the solution space $\Theta_{\boldsymbol{A}} = \{\boldsymbol{A} : \sum_{j=1}^{N} \boldsymbol{A}_{ij} = 1, \forall i \in [k], \boldsymbol{A} \in [0, 1]^{k \times N} \}$. Then, the fundamental limit of the problem class Θ_{GM} is given by the following lemma.

Lemma 2.1 (Lower Bound (Yu et al., 2015)). For model class Θ_{GM} , given $\frac{\Delta}{\sigma \log(k/\alpha)} \to \infty$,

$$\inf_{\hat{\boldsymbol{A}}\in\Theta_{\boldsymbol{A}}}\sup_{(z,\theta,F_{\omega})}\mathbb{E}[L(\hat{\boldsymbol{A}},\boldsymbol{P}_{1})]\geq\exp\left(-(1+o(1))\frac{\Delta^{2}}{8\sigma^{2}}\right).$$

Remark 2. The above result implies that the difficulty of this problem is governed by the Signal-to-Noise ratio $\frac{\Delta}{\sigma}$. In particular, the above results imply that the minimax rate of this problem is largely dependent on the distance between the two closest centroids. We also note that the original result is instead on the 0-1 loss between \hat{z} and z. However, it is also not difficult to show the same results hold for the solution space Θ_A and our defined loss L.

2.2.2. THE EM (LLOYD'S) ALGORITHM

Lloyd's algorithm is a special case of EM algorithm on the Gaussian mixture model, which is formally stated by Algorithm 1. The Lloyd's algorithm iteratively updates: (1) The centroid of each cluster; (2) The membership of each sample. Since Lloyd's algorithm requires an initial input $\{\hat{\mu}_i^{(0)}\}$, Lu & Zhou (2016) has shown that given a proper initialization algorithm 2, Lloyd's algorithm provably achieves good performance. An example initialization algorithm is given by algorithm 2 where the spectral algorithm and k-means++ algorithm (Kumar et al., 2004) are first called to obtain approximate solutions.

Algorithm 1 Lloyd's Algorithm

Input: A sample matrix from Mixture of Gaussians $X \in \mathbb{R}^{d \times N}$, number of iterations τ , and initial centroids $\{\hat{\mu}_i^{(0)}\}_{i \in [k]}$.

Compute the Initial Clusters

$$\hat{z}_{i}^{(0)} = \underset{i \in [k]}{\operatorname{arg\,min}} \| X_{j} - \hat{\mu}_{i}^{(0)} \|_{2} \text{ for all } j \in [N].$$
 (2)

for $\ell = 1$ to τ do

(1) The Expectation Step: Update the centroid by

$$\hat{\mu}_{i}^{(\ell)} = rac{\sum_{j=1}^{N} \mathbb{1}_{\hat{z}_{j}^{(\ell-1)} = i} X_{j}}{\sum_{j=1}^{N} \mathbb{1}_{\hat{z}_{j}^{(\ell-1)} = i}}.$$

(2) The Maximization Step: Update the cluster assignment by

$$\hat{oldsymbol{z}}_j^{(\ell)} = \operatorname*{arg\,min}_{i\in[k]} \lVert oldsymbol{X}_j - \hat{oldsymbol{\mu}}_i^{(\ell)}
Vert_2 \quad ext{ for all } j\in[N].$$

end for

2.3. Pretraining with Supervised Learning

The clustering problem is unsupervised where no labels are given. Transformers are usually used in the supervised learning setup. To let Transformers learn the algorithms, we perform supervised pre-training.

In this setup, we are first given in a total of *n* pretraining instances $\{X^{(i)}\}_{i \in [n]}$ and $\{z^{(i)}\}_{i \in [n]}$. We also form the pretraining instances by feeding the Transformer with the initialization given by 2, encoded in $\{H^{(i)}\}_{i \in [n]}$. Then, we train the Transformer using the standard supervised learning on this set. Since the optimization of Transformers is nonconvex and difficult to analyze, we consider the empirical risk minimizer of the Transformer given by

$$\hat{\boldsymbol{\theta}} := \operatorname*{arg\,min}_{\boldsymbol{\theta} \in \Theta_{(B_M, B_L)}(B_{\boldsymbol{\theta}})} \sum_{i=1}^n L\left(A_{\boldsymbol{\theta}}(\boldsymbol{H}^{(i)}), \boldsymbol{P}_1(\boldsymbol{z}^{(i)})\right), \quad (3)$$

Algorithm 2 Initialization by Spectral Clustering

Input: Matrix $X \in \mathbb{R}^{d \times N}$.

Perform PCA on XX^{\top} and obtain its top-k eigenvectors $\{V_i\}_{i \in [k]}$.

Project the input matrix by $\tilde{X} = V^{\top} X$.

Solve the k-means program given by

$$ilde{oldsymbol{z}} := rgmin_{\hat{z}:[N] o [k]} \min_{\{oldsymbol{\mu}_i\}_{i \in [N]}} \sum_{i=1}^k \lVert oldsymbol{\mu}_{\hat{z}_i} - ilde{oldsymbol{X}}_i
Vert_2$$

by the *k*-means++ algorithm (Kumar et al., 2004). **Return:** Initial Cluster Assignment \tilde{z} .

where $A \in \{TF, TF^+\}$.

In our theoretical analysis, we construct the input of the Transformer as a *context-augmented matrix* given by the following

$$\boldsymbol{H} = \begin{bmatrix} \boldsymbol{X} \\ \boldsymbol{P} \end{bmatrix}, \boldsymbol{P} = \begin{bmatrix} \hat{\boldsymbol{\mu}}_{1}^{(0)} & \hat{\boldsymbol{\mu}}_{2}^{(0)} & \dots & \hat{\boldsymbol{\mu}}_{k}^{(0)} & \dots & \boldsymbol{0} \\ \boldsymbol{p}_{1,1}^{(0)} & \boldsymbol{p}_{1,2}^{(0)} & \dots & \boldsymbol{p}_{1,k}^{(0)} & \dots & \boldsymbol{p}_{1,N}^{(0)} \\ \boldsymbol{p}_{2,1} & \boldsymbol{p}_{2,2} & \dots & \boldsymbol{p}_{2,k} & \dots & \boldsymbol{p}_{2,N} \\ 1 & 1 & \dots & 1 & \dots & 1 \\ & & \boldsymbol{0} & & & \end{bmatrix},$$
(4)

where $\boldsymbol{H} \in \mathbb{R}^{D \times N}$ and $\boldsymbol{P}^{(D-d) \times N}$. We let the input dimension $D \leq Ckd$ for some universal constant C. The matrix \boldsymbol{P} contains contextual information. For the first row, $\{\hat{\boldsymbol{\mu}}_i^{(0)}\}_{i \in [k]} \subset \mathbb{R}^d$ are the initial centroid estimates given by the initialization algorithm 2. Then the next row $\{\boldsymbol{p}_{1,i}\}_{i \in [N]} \subset [0,1]^k$ is given by $\boldsymbol{P}_1(\hat{\boldsymbol{z}}^{(0)})$ as in (1) where $\hat{\boldsymbol{z}}^{(0)}$ corresponds to the initialized membership in (2). Then the row $\{\boldsymbol{p}_{2,i}\}_{i \in [N]} \subset \mathbb{R}^d$ satisfies

$$p_{2,i,j} = \mathbb{1}_{i=j}$$
 if $j \in [d]$.

And the last row is set to all 1 for the technical purpose of introducing constants into the Softmax function.

3. Theoretical Results

This section presents our theoretical results and a proof sketch of our results. This section is divided into three parts: section 3.1 provides the approximation bound to EM algorithms by Transformers; section 3.2 provides the generalization bound; section 3.3 provides a short proof sketch over the main theorem.

3.1. The Approximation Bound

We first present an approximation bound for Lloyd's algorithm by both the Transformer and the Transformer+.

Theorem 3.1. Assume that d = o(N), k < d. There exists a Transformer with number of layers $L = \tau(3 + 3k)$ and

norm $\|\|\boldsymbol{\theta}\|\| \lesssim C^d (\log N + M)$ with the number of heads M such that

$$\left\| TF_{\boldsymbol{\theta}}(\boldsymbol{H}) - \begin{bmatrix} \boldsymbol{p}_{1,1}^{(\tau)} & \boldsymbol{p}_{1,2}^{(\tau)} & \dots & \boldsymbol{p}_{1,N}^{(\tau)} \end{bmatrix} \right\|_{2} \\ \lesssim \tau C^{d} \left(\sqrt{k} \sup_{j \in [k], \ell \in [\tau]} \| \hat{\boldsymbol{\mu}}_{j}^{(\tau)} \|_{2} \sqrt{\frac{\log M}{M}} + N^{-1} \right)$$

where τ is the number of iterations in the Lloyd's algorithm, and $p_{1,i}^{(\tau)}$ the one-hot coding of the membership $\hat{z}_i^{(\tau)}$ there. Remark 3. The two terms in the bound come from the expectation and the maximization steps, respectively. The N^{-1} term comes from the expectation step, where we relate the weighted average with the weights given by the Softmax function. The second term related to multi-head attention comes from a few multi-head approximation layers for some general functions. To achieve this bound, we prove a new result on the universal approximation of the Softmax function, which brings in the approximation term discussed in section 3.3. We also note that the N^{-1} term can be further improved by introducing the non-activated Attention layer, given by the next theorem for Transformer+ architecture.

Theorem 3.2. Under the same condition as theorem 3.1, there exists a Transformer+with the number of layers $L = \tau(7+3k)$ and norm $|||\theta||| \leq C^d M \log N$ with the number of heads M such that

$$\begin{aligned} & \left\| TF_{\boldsymbol{\theta}}^{+}(\boldsymbol{H}) - \begin{bmatrix} \boldsymbol{p}_{1,1}^{(\tau)} & \boldsymbol{p}_{1,2}^{(\tau)} & \dots & \boldsymbol{p}_{1,N}^{(\tau)} \end{bmatrix} \right\|_{2} \lesssim \tau \Big(dN^{-100} \\ & + C^{d}\sqrt{k} \sup_{j \in [k], \ell \in [\tau]} \| \hat{\boldsymbol{\mu}}_{j}^{(\ell)} \|_{2} \sqrt{\frac{\log M}{M}} + C^{d} \sqrt{\frac{d^{2} \log M}{M}} \Big). \end{aligned}$$

Remark 4. The key difference between Theorems 3.1 and 3.2 comes from different designs of the Expectation Step. Through the introduction of the non-activated Attention layer, we manage to approximate a wider range of functions, including the polynomials on H with degree 3. We also believe that the non-activated Attention layer is unnecessary if a stronger *right-product* universal approximation result can be proved for the Softmax functions, which is discussed in section 3.3.

3.2. The Generalization Bounds

Given the approximation error provided by Theorems 3.1 and 3.2, we further provide the generalization error bound for the ERM defined by (3). We consider the problem instances $\{X^{(i)}, z^{(i)}\}_{i \in [n]}$ to be sampled i.i.d. from a distribution supported on Θ_{GM} . Then, we can show the following generalization bound for the Transformer network in the space of $\Theta(B_{\theta}, B_M, B_L)$.

Proposition 3.1 (Generalization Bounds). *With probability at least* $1 - \delta$,

$$L(A_{\hat{\theta}}(\boldsymbol{H}), \boldsymbol{P}_{1}(\boldsymbol{z})) \leq \inf_{\boldsymbol{\theta} \in \Theta_{B_{M}, B_{L}}(B_{\boldsymbol{\theta}})} \mathbb{E}[L(A_{\boldsymbol{\theta}}(\boldsymbol{H}), \boldsymbol{P}_{1}(\boldsymbol{z}))] + C\sqrt{\frac{D^{2}B_{L}B_{M}\log(NB_{\boldsymbol{\theta}}B_{M}D\sigma m_{0}) + \log(2/\delta)}{n}},$$

where $m_0 = \sup_{i \in [N], j \in [n]} \| \boldsymbol{\mu}_i^{(j)} \|_2$.

Remark 5. The above proposition implies that, given the sufficiently large number of samples n, the ERM solution generalizes to new samples as we can use the approximation results given by Theorem 3.1 and 3.2 to upper bound the first term on the R.H.S. of the inequality. The following results ultimately provide an ultimate bound for the error of the ERM estimator on the unseen instance.

Theorem 3.3 (The Matching Upper Bound). Let $r_k = \frac{\Delta}{\sigma} \sqrt{\frac{\alpha}{1+kd/N}}$, $k \log N = o(N\alpha^2)$, $M \asymp n^{1/2}$, $L \asymp k \log n$, $\sqrt{k} = o(r_k)$ as $n \to \infty$. Assume that we use Algorithm 2 as initialization and let $\tau > 4 \log n + 1$. Then, with probability at least $1 - \delta - 5n^{-1} - 2 \exp(-\Delta/\sigma)$, the ERM estimator given by the Transformer satisfies

$$\begin{split} L(TF_{\hat{\theta}}(\boldsymbol{H}), \boldsymbol{P}_{1}(\boldsymbol{z})) \lesssim \exp\left(-(1+o(1))\frac{\Delta^{2}}{8\sigma^{2}}\right) \\ + \sqrt{kn^{-1/4}}C^{d}\sqrt{Polylog(n) + \log(1/\delta)} + N^{-3/2}. \end{split}$$

And with the same parameter setup and initialization, with probability at least $1 - \delta - 5n^{-1} - 2\exp(-\Delta/\sigma)$, the ERM estimator given by the Transformer+ satisfies

$$L(TF_{\hat{\theta}}^{+}(\boldsymbol{H}), \boldsymbol{P}_{1}(\boldsymbol{z})) \lesssim \exp\left(-(1+o(1))\frac{\Delta^{2}}{8\sigma^{2}}\right) + d\sqrt{kn^{-1/4}}C^{d}\sqrt{Polylog(n) + \log(1/\delta)} + N^{-100.5}.$$

Remark 6. Our results in the above theorem imply that, given the number of samples $n \asymp \exp\left(\frac{\Delta^2}{2\sigma^2}\right)$, Transformers can reach the fundamental limits given by Lemma 2.1 and achieve the minimax optimal rate of the clustering problem with high probability. Moreover, the introduction of the non-activated Attention layer in Softmax+ significantly improves the upper bound in the exponent of N. In particular, the $N^{-100.5}$ can even be improved with arbitrarily large universal constants. We discuss in section 3.3 that solving a potential open problem on the universal approximation of the Transformer might lead to the removal of the non-activated Attention layer in the proof.

3.3. The Proof Ideas

This section discusses some new results we obtained on the midway of proving Theorems 3.1 and 3.2. We then present a proof sketch for the more complicated proof of Theorem 3.1.

3.3.1. AN APPROXIMATION BOUND FOR THE SOFTMAX FUNCTION

We provide a new approximation bound for the sum of Softmax functions to mappings from $\mathbb{R}^{d_1} \to \mathbb{R}^{d_2}$. We first introduce the class of (R, C_ℓ) smooth functions. The (R, C_{ℓ}) smooth function class contains a wide range of functions.

Definition 3.4 ((Bach, 2017)(Bai et al., 2024)). A function $g : \mathbb{R}^d \to \mathbb{R}$ is (R, C_ℓ) smooth if for $s = \lceil (k-1)/2 \rceil + 2$, g is a C^s function supported on $\lceil -R, R \rceil^k$ such that

$$\sup_{\boldsymbol{x}\in[-R,R]^k} \|\nabla^i g(\boldsymbol{x})\|_{\infty} \leq L_i,$$

for all $i \in \{0, 1, \ldots, s\}$, with $\max_{0 \le i \le s} L_i R^i \le C_{\ell}$.

Then, we are ready to present our results on the approximation error of Softmax functions.

Lemma 3.1 (Approximating *d* Dimensional (R, C_{ℓ}) Smooth Mappings by Softmax Neural Networks). Consider an element-wise (R, C_{ℓ}) smooth mapping f(x) = $(f_1(x), \ldots f_{d_1}(x))^{\top}$ where $x \in [-R, R]^d$. There exists a set of points $\{(A_i, a_i)\}_{i \in [M]}$ with $\sup_{i \in [M]} ||A||_2 \leq C$ such that the following holds

$$\sup_{\boldsymbol{x}\in\mathcal{B}(\|\cdot\|_{\infty,R})}\frac{1}{C_{\ell}}\left\|\boldsymbol{f}(\boldsymbol{x})-\sum_{i=1}^{Md}a_{i}Softmax\left(\boldsymbol{A}_{i}\begin{bmatrix}\boldsymbol{x}\\1\end{bmatrix}\right)\right\|_{\infty}$$
$$\leq C(f)^{d}\sqrt{\frac{dd_{1}}{M}\log\left(\frac{MR}{dd_{1}}\right)}.$$

Remark 7. The above bound demonstrates the universal approximation of Softmax functions to smooth mappings. Our proof idea utilizes a preliminary result on the sigmoid function and dissects the softmax function into multiple sigmoid functions. For each of the sigmoid functions, we use the probabilistic method to construct L_{∞} approximation bound.

In Lemma A.2, our proof applies to the left product of A. It is then of general interest to know whether there exists a universal approximation bound for the right product form SoftMax ($\begin{bmatrix} x & 1 \end{bmatrix} A$). Solving this fundamental problem helps us to achieve the rate of the Transformer+ using the Transformer model.

3.3.2. THE PROOF SKETCHES OF THEOREM 3.1

We here provide the proof sketch of the Theorem 3.1. The proof of Theorem 3.2 is more involved in the Expectation step and is delayed to the appendix. Our proof idea is to manually construct θ for the network and estimate the error caused by each layer constructed.

The Expectation Step. In the expectation step, we notice the following relationship holds

$$\begin{bmatrix} \boldsymbol{X}_1 & \dots & \boldsymbol{X}_N \end{bmatrix} \operatorname{SoftMax} \left(\begin{bmatrix} \boldsymbol{p}_{1,1}^{(0)} \\ \vdots \\ \boldsymbol{p}_{1,N}^{(0)} \end{bmatrix} \right) \approx \begin{bmatrix} \hat{\boldsymbol{\mu}}_1^{(1)} & \dots & \hat{\boldsymbol{\mu}}_k^{(1)} \end{bmatrix}.$$

However, we have $\begin{bmatrix} p_{1,1}^{(0)} & \dots & p_{1,N}^{(0)} \\ \mathbf{0} & \dots & \mathbf{0} \end{bmatrix}^{\top}$ and the **0** part needs to be cancelled. We then construct another head with **0** matrix in the SoftMax function to cancel out the **0** part in the first head. The two cancellations result in an approximation error of O(1/N).

The Maximization Step In the maximization step, our proof involves a total of 4 steps. Our initial matrix is given by

$igrap_X$	$oldsymbol{X}_2$		$oldsymbol{X}_k$	 X_N	
$\hat{\mu}_{1}^{(1)}$	$\hat{oldsymbol{\mu}}_2^{(1)}$		$\hat{oldsymbol{\mu}}_k^{(1)}$	 0	
$m{p}_{1,1}^{(0)}$	$oldsymbol{p}_{1,2}^{\overline{(0)}}$		$oldsymbol{p}_{1,k}^{(0)}$	 $oldsymbol{p}_{1,N}^{(0)}$.
$oldsymbol{p}_{2,1}$	$oldsymbol{p}_{2,2}$		$oldsymbol{p}_{2,k}$	 $p_{2,N}$	·
1	1		1	 1	
		0			

Then, in the **Step 1**, we copy in a total of k times the first row and move them to the **0** part using two FC layers, with one moving the negative part and one moving the positive part, providing

$$egin{bmatrix} ec{1} & ec{$$

Then, in the **Step 2**, we move $\{\hat{\mu}_i^{(1)}\}_{i \in [M]}$ to $\{x_{j,i}\}_{j \in [N]}$, yielding

$$\begin{bmatrix} \vdots & \vdots & \vdots & \vdots & \vdots \\ 1 & \dots & 1 & \dots & 1 \\ \boldsymbol{X}_{1,1} - \hat{\boldsymbol{\mu}}_1^{(1)} & \dots & \boldsymbol{X}_{k,1} - \hat{\boldsymbol{\mu}}_1^{(1)} & \dots & \boldsymbol{X}_{N,1} - \hat{\boldsymbol{\mu}}_1^{(1)} \\ & \vdots & & \\ \boldsymbol{X}_{1,k} - \hat{\boldsymbol{\mu}}_k^{(1)} & \dots & \boldsymbol{X}_{k,k} - \hat{\boldsymbol{\mu}}_k^{(1)} & \dots & \boldsymbol{X}_{N,k} - \hat{\boldsymbol{\mu}}_k^{(1)} \end{bmatrix}$$

This step utilizes the approximation bound given by Lemma A.2 to approximate the function of $f(x) = x_i$.

Then, in the **Step 3**, we apply the approximation bound again to construct Softmax networks that approximate the mapping from a vector to its norm, providing us with the following matrix.

$$\begin{bmatrix} \vdots & \vdots & \vdots & \vdots & \vdots \\ 1 & \dots & 1 & \dots & 1 \\ \|\boldsymbol{X}_{1,1} - \hat{\boldsymbol{\mu}}_{1}^{(1)}\|_{2} & \dots & \|\boldsymbol{X}_{k,1} - \hat{\boldsymbol{\mu}}_{1}^{(1)}\|_{2} & \dots & \|\boldsymbol{X}_{N,1} - \hat{\boldsymbol{\mu}}_{1}^{(1)}\|_{2} \\ & \vdots & & \\ \|\boldsymbol{X}_{1,k} - \hat{\boldsymbol{\mu}}_{k}^{(1)}\|_{2} & \dots & \|\boldsymbol{X}_{k,k} - \hat{\boldsymbol{\mu}}_{k}^{(1)}\|_{2} & \dots & \|\boldsymbol{X}_{N,k} - \hat{\boldsymbol{\mu}}_{k}^{(1)}\|_{2} \end{bmatrix}$$

Finally, in the **Step 4**, we obtain approximate vectors to $\{p_{1,i}^{(1)}\}_{i \in [N]}$ through applying the softmax function to the

submatrix

$$\begin{bmatrix} \|\boldsymbol{X}_{1,1} - \hat{\boldsymbol{\mu}}_1^{(1)}\|_2 & \dots & \|\boldsymbol{X}_{N,1} - \hat{\boldsymbol{\mu}}_1^{(1)}\|_2 \\ \vdots & \vdots & \vdots \\ \|\boldsymbol{X}_{1,k} - \hat{\boldsymbol{\mu}}_1^{(1)}\|_2 & \dots & \|\boldsymbol{X}_{N,k} - \hat{\boldsymbol{\mu}}_1^{(1)}\|_2 \end{bmatrix}$$

Using another approximation bound showing the difference between the Softmax and the Hardmax function we accomplish the Maximization step.

4. Simulations



Figure 1. 4-Class Clustering with Different Minimum Distance, Data Dimension, and Number of Training Data. We train a small Transformer (layer = 3, head = 2, embedding = 64) and iterate for 300 steps for each different setting. Each point in the figure is evaluated on 512 testing data. We report the 10 runs averaged result with a shaded region representing the standard deviation. Each training sample is generated according to isotropic Gaussian with covariances $\sigma^2 I$. (1) First Row: Minimum Distance. We set $\sigma^2 \sim \text{Uniform}[10, 40]$. (2) Second Row: Data Dimension. We set $\sigma^2 \sim \text{Uniform}[10, 20]$, minimum distance = 5. (3) Three Row: Number of Training Data. We set $\sigma^2 \sim \text{Uniform}[0.5, 5]$, minimum distance = 5.

In this section, we verify our theoretical results on the multiclass clustering problem and examine its interplay with five key factors: the minimum distance between centroids Δ , the data dimension d, the training sample size N, the total number of classes, and an imbalance ratio α . These results are presented in Figure 1 and Figure 2. Furthermore, we compare the impact of a number of layers in the Transformer with the number of iterations τ in Figure 3.

Experimental Setup We use a small Transformer with 3 layers, 2 heads, and 64-dimensional embedding size. All



Figure 2. 4-Class Clustering with Different Number of Class and Inbalance Ratio. We train a small Transformer (layer = 3, head = 2, embedding = 64) and train for 300 steps for each different setting. Each point in the figure is evaluated on 512 testing data. We report the 10 runs averaged result with a shaded region representing the standard deviation. Each training sample is generated according to isotropic Gaussian with covariances $\sigma^2 I$. (1) First Row: Number of Class. We set $\sigma^2 \sim$ Uniform[10, 20], minimum distance = 5. (2) Second Row: Inbalance Ratio. Two clusters each contain 50 data points, while the other two contain $50 \times \text{ratio}$ and $50 \times 1 - \text{ratio}$ respectively. We set $\sigma^2 \sim \text{Uniform}[10, 20]$, minimum distance = 5.



Figure 3. Comparision between Transformer and Lloyd's Algorithm. We compare the effect of the number of layers in Transformers with the number of iterations τ in Lloyd's algorithm under the same dataset configuration. We use a 6-class dataset, where each cluster contains 50 data points in a d = 10 dimensional space. Each training sample is generated according to isotropic Gaussian with covariances $\sigma^2 I$, where $\sigma^2 \sim \text{Uniform}[20, 30]$, and the minimum cluster separation is set to 1. (1) Left: Trans*former.* We train Transformers with fixed head = 2, embedding = 64, but vary the number of layers from 3 to 20. Each model is trained for 500 steps per layer. (2) Right: Lloyd's Algorithm. We use sklearn(Pedregosa et al., 2011) to run the Lloyd's algorithm, varying the maximum iteration count from 1 to 6. Early convergence is declared when the Frobenius norm of the difference between cluster centers in consecutive iterations falls below 10^{-4} . Each point in the figure represents an evaluation of 512 test samples. Results are averaged over 10 runs, with the shaded region indicating the standard deviation.

simulations are conducted on NVIDIA A100 80G GPUs. We run each experiment for 300 iterations, initialize the model with 10 different random seeds, and report the mean and standard deviation of the resulting metrics. The model is trained using the Adam optimizer with a learning rate of 0.0005 and an exponential decay factor of 0.995 for each step. After training, each configuration is evaluated on 512 synthetic and random test samples. Note that our empirical evaluation slightly differs from the theoretical part through removing the auxiliary matrix P given by (4) from the input.

Metrics. We compute cross entropy among every permutation of the label and choose the minimum as the loss function since clustering tasks are permutation invariant. We evaluate the clustering performance using two widely adopted permutation-invariant metrics: Adjusted Rand Index (ARI) and Normalized Mutual Information (NMI) (Ma et al., 2019; Huang et al., 2020; Monnier et al., 2020; Sun et al., 2024; Li et al., 2024a).

Preparation for the Synthetic Data. We generate our synthetic data as follows: For each input $X \in \mathbb{R}^{d \times N}$, we sample 50 data points from every cluster. Each sample is generated according to isotropic Gaussian with covariances $\sigma^2 I$. The variance σ differs from task to task; we specify more details in the caption of figures.

Results Our results suggest that the theoretical threshold given by the minimax rate matches with the trend given in the experiments. Moreover, we also showcase that the pre-trained Transformers can be a strong alternative to Lloyd's algorithm, verifying the strong inference capacities of Transformers on this problem.

5. Discussions

This section discusses the limitations on the theory part of this work and points to future working directions.

Limitations. Our limitations in the theoretical results can be summarized as follows: (1) From the theoretical perspective, our results guarantee the performance of ERM solutions whereas the true estimator is obtained through stochastic gradient descent method; (2) Our theoretical results utilize the context-augmented matrix P, which is verified removable from our empirical results.

Future Works. Beyond resolving the limitations in this work, other future working directions from this work include: (1) Taking into consideration of the layer norm in the Transformer architecture. (2) Resolving the universal approximation problem raised in section 3.3; (3) Removing the initialization procedure in the theory.

Impact Statement

This paper theoretically analyzes the capability of Transformers in performing EM algorithm. Due to the theoretical nature of this work, there is no negative sociatal impact.

References

- Abernethy, J., Agarwal, A., Marinov, T. V., and Warmuth, M. K. A mechanism for sample-efficient in-context learning for sparse retrieval tasks. In *International Conference* on Algorithmic Learning Theory, pp. 3–46. PMLR, 2024.
- Ahn, K., Cheng, X., Daneshmand, H., and Sra, S. Transformers learn to implement preconditioned gradient descent for in-context learning. *Advances in Neural Information Processing Systems*, 36, 2024.
- Akyürek, E., Schuurmans, D., Andreas, J., Ma, T., and Zhou, D. What learning algorithm is in-context learning? investigations with linear models. *arXiv preprint arXiv:2211.15661*, 2022.
- Bach, F. Breaking the curse of dimensionality with convex neural networks. *The Journal of Machine Learning Research*, 18(1):629–681, 2017.
- Bai, Y., Chen, F., Wang, H., Xiong, C., and Mei, S. Transformers as statisticians: Provable in-context learning with in-context algorithm selection. Advances in neural information processing systems, 36, 2024.
- Bhattamishra, S., Patel, A., and Goyal, N. On the computational power of transformers and its implications in sequence modeling. *arXiv preprint arXiv:2006.09286*, 2020.
- Bishop, C. M. and Nasrabadi, N. M. *Pattern recognition* and machine learning, volume 4. Springer, 2006.
- Chen, S., Sheen, H., Wang, T., and Yang, Z. Training dynamics of multi-head softmax attention for in-context learning: Emergence, convergence, and optimality. *arXiv* preprint arXiv:2402.19442, 2024a.
- Chen, X., Zhao, L., and Zou, D. How transformers utilize multi-head attention in in-context learning? a case study on sparse linear regression. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024b.
- Giannou, A., Yang, L., Wang, T., Papailiopoulos, D., and Lee, J. D. How well can transformers emulate in-context newton's method? *arXiv preprint arXiv:2403.03183*, 2024.
- He, Y., Cao, Y., Chen, H.-Y., Wu, D., Fan, J., and Liu, H. Learning spectral methods by transformers. arXiv preprint arXiv:2501.01312, 2025.
- Huang, Y., Cheng, Y., and Liang, Y. In-context convergence of transformers. arXiv preprint arXiv:2310.05249, 2023.

- Huang, Z., Hu, P., Zhou, J. T., Lv, J., and Peng, X. Partially view-aligned clustering. *Advances in Neural Information Processing Systems*, 33:2892–2902, 2020.
- Jelassi, S., Sander, M., and Li, Y. Vision transformers provably learn spatial structure. Advances in Neural Information Processing Systems, 35:37822–37836, 2022.
- Jeon, H. J., Lee, J. D., Lei, Q., and Roy, B. V. An information-theoretic analysis of in-context learning, 2024.
- Kumar, A., Sabharwal, Y., and Sen, S. A simple linear time (1+/spl epsiv/)-approximation algorithm for k-means clustering in any dimensions. In 45th Annual IEEE Symposium on Foundations of Computer Science, pp. 454–462. IEEE, 2004.
- Li, Y., Ildiz, M. E., Papailiopoulos, D., and Oymak, S. Transformers as algorithms: Generalization and stability in in-context learning. In *International Conference on Machine Learning*, pp. 19565–19594. PMLR, 2023a.
- Li, Y., Li, Y., and Risteski, A. How do transformers learn topic structure: Towards a mechanistic understanding. In *International Conference on Machine Learning*, pp. 19689–19729. PMLR, 2023b.
- Li, Y., Hu, P., Peng, D., Lv, J., Fan, J., and Peng, X. Image clustering with external guidance. In *Fortyfirst International Conference on Machine Learning*, 2024a. URL https://openreview.net/forum? id=JSYN891WnB.
- Li, Z., Cao, Y., Gao, C., He, Y., Liu, H., Klusowski, J. M., Fan, J., and Wang, M. One-layer transformer provably learns one-nearest neighbor in context. In *The Thirtyeighth Annual Conference on Neural Information Processing Systems*, 2024b.
- Liu, B., Ash, J. T., Goel, S., Krishnamurthy, A., and Zhang, C. Transformers learn shortcuts to automata. arXiv preprint arXiv:2210.10749, 2022.
- Lloyd, S. Least squares quantization in pcm. IEEE transactions on information theory, 28(2):129–137, 1982.
- Lu, Y. and Zhou, H. H. Statistical and computational guarantees of lloyd's algorithm and its variants. *arXiv preprint arXiv:1612.02099*, 2016.
- Ma, Q., Zheng, J., Li, S., and Cottrell, G. W. Learning representations for time series clustering. *Advances in neural information processing systems*, 32, 2019.
- Monnier, T., Groueix, T., and Aubry, M. Deep transformation-invariant clustering. *Advances in neural information processing systems*, 33:7945–7955, 2020.

- Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M., Prettenhofer, P., Weiss, R., Dubourg, V., et al. Scikit-learn: Machine learning in python. *the Journal of machine Learning research*, 12:2825–2830, 2011.
- Pérez, J., Barceló, P., and Marinkovic, J. Attention is turingcomplete. *Journal of Machine Learning Research*, 22 (75):1–35, 2021.
- Pisier, G. Remarques sur un résultat non publié de b. maurey. Séminaire d'Analyse fonctionnelle (dit" Maurey-Schwartz"), pp. 1–12, 1981.
- Sun, L., Huang, Z., Peng, H., Wang, Y., Liu, C., and Yu, P. S. Lsenet: Lorentz structural entropy neural network for deep graph clustering. *arXiv preprint arXiv:2405.11801*, 2024.
- Vaswani, A. Attention is all you need. *Advances in Neural Information Processing Systems*, 2017.
- Wu, Y. Information-theoretic methods for high-dimensional statistics. *Lecture notes, Yale University, New Haven, CT*, 2020.
- Yao, S., Peng, B., Papadimitriou, C., and Narasimhan, K. Self-attention networks can process bounded hierarchical languages. arXiv preprint arXiv:2105.11115, 2021.
- Yu, Y., Wang, T., and Samworth, R. J. A useful variant of the davis–kahan theorem for statisticians. *Biometrika*, 102(2):315–323, 2015.
- Yun, C., Bhojanapalli, S., Rawat, A. S., Reddi, S. J., and Kumar, S. Are transformers universal approximators of sequence-to-sequence functions? *arXiv preprint arXiv:1912.10077*, 2019.
- Zhang, C. and Cao, Y. Transformer learns optimal variable selection in group-sparse classification. In *International Conference on Learning Representations*, 2025.
- Zhang, R., Frei, S., and Bartlett, P. L. Trained transformers learn linear models in-context. *arXiv preprint arXiv:2306.09927*, 2023.

A. Theoretical Background

This section provides approximation results of the Softmax function in the form of $f(\boldsymbol{x}) := \sum_{i=1}^{M} a_i \text{Sigmoid} (\boldsymbol{x}^\top \boldsymbol{v}_i) + a_0$ where $\{a_i\}_{i \in [M]} \subset \mathbb{R}$ and $\{\boldsymbol{v}_i\} \subset \mathbb{R}^{d+1}$. We consider the class of (R, C_ℓ) -smooth functions (Bach, 2017; Bai et al., 2024) defined as follows.

Definition A.1 (Bai et al. (2024)). A function $g : \mathbb{R}^d \to \mathbb{R}$ is (R, C_ℓ) smooth if for $s = \lceil (k-1)/2 \rceil + 2$, g is a C^s function supported on $\lceil -R, R \rceil^k$ such that

$$\sup_{\boldsymbol{x}\in[-R,R]^k} \|\nabla^i g(\boldsymbol{x})\|_{\infty} \leq L_i,$$

for all $i \in \{0, 1, \ldots, s\}$, with $\max_{0 \le i \le s} L_i R^i \le C_{\ell}$.

We then consider the following class of functions

$$\mathcal{F}_d = \left\{ f: f(\boldsymbol{x}) = \int_{\mathcal{W}: \|\boldsymbol{v}\|=1} \operatorname{Sigmoid}\left([\boldsymbol{x}^\top, 1] \boldsymbol{v} \right) d\mu(\boldsymbol{v}) \right\}, \text{ with } TV(\mu) = \int_{\mathcal{W}: \|\boldsymbol{v}\|_2 = 1} d|\mu(\boldsymbol{v})| < C_\ell C(f)^d,$$

where C(f) is a constant that depends only on f. It is further noted that by Bach (2017), we can write that the class of (R, C_{ℓ}) smooth functions belongs to the above class. Then we prove the following approximation lemma for the sigmoid function, which provides explicit dependence on B and C.

Lemma A.1. Suppose f is (R, C_{ℓ}) smooth. Then there exists a set of points $(v_1, a_1), \ldots, (v_M, a_M) \in \mathcal{B}(\|\cdot\|_2, 1)$ that makes the following hold

$$\sup_{\boldsymbol{x}\in\mathcal{B}(\|\cdot\|_{\infty},R)} \left| \frac{1}{C_{\ell}} f(\boldsymbol{x}) - \frac{1}{M} \sum_{i=1}^{M} a_{i} Sigmoid\left([\boldsymbol{x}^{\top},1]^{\top} \boldsymbol{v}_{i} \right) \right| \leq C(f)^{d} \inf_{\epsilon>0} \left(2\epsilon + \sqrt{\frac{\log(\mathcal{N}(\mathcal{B}(\|\cdot\|_{\infty},R),\epsilon)/\delta)}{M}} \right) \\ \lesssim C(f)^{d} \sqrt{\frac{d}{M} \log\left(\frac{MR}{d}\right)},$$

where we also have $\sum_{i=1}^{M} |a_i| \leq C(f)^d$.

Proof. The proof goes by the probabilistic method, where we can first use Pisier (1981) to show that when we sample from the distribution given by $f(v) = \frac{|\mu(v)|}{\int_{\mathbb{S}^d} d\mu(v)} = \frac{|\mu(v)|}{TV(\mu)}$. Then, under this probability measure, we sample independently in a total of M samples (V_1, \ldots, V_M) to obtain that for any $x \in \mathcal{V}$, pointwise

$$\begin{split} \int_{\mathbb{R}^{d+1}} &\operatorname{Softmax}\left([\boldsymbol{x}^{\top},1]\boldsymbol{v}\right) d\mu(\boldsymbol{v}) - \frac{TV(\mu)}{M} \sum_{i=1}^{M} \operatorname{Softmax}\left([\boldsymbol{x}^{\top},1]\boldsymbol{V}_{i}\right) \\ &= TV(\mu) \bigg(\mathbb{E} \Big[\operatorname{sign}(\mu(\boldsymbol{v})) \operatorname{Softmax}\left([\boldsymbol{x}^{\top},1]\boldsymbol{V}\right) \Big] - \frac{1}{M} \sum_{i=1}^{M} \operatorname{sign}\left(\mu(\boldsymbol{v})\right) \operatorname{Softmax}\left([\boldsymbol{x}^{\top},1]\boldsymbol{V}_{i}\right) \bigg). \end{split}$$

And we have by Hoeffding's inequality,

$$\mathbb{P}\left(\left|\mathbb{E}\left[\operatorname{sign}(\mu(\boldsymbol{v}))\operatorname{Softmax}\left([\boldsymbol{x}^{\top},1]\boldsymbol{V}\right)\right] - \frac{1}{M}\sum_{i=1}^{M}\operatorname{sign}(\sigma_{f}(\boldsymbol{V}_{i}))\operatorname{Softmax}\left([\boldsymbol{x}^{\top},1]\boldsymbol{V}_{i}\right)\right| \geq \frac{t}{TV(\mu)}\right) \leq \exp\left(-\frac{CMt^{2}}{TV(\mu)^{2}}\right).$$

And, by the union bound, we can show that for points in the ϵ -cover of $\mathcal{B}(\|\cdot\|_{\infty}, R)$, the following holds

$$\begin{split} \mathbb{P}\bigg(\sup_{\boldsymbol{x}\in\mathcal{N}(\mathcal{B}(\|\cdot\|_{\infty},R),\epsilon)} \Big| \mathbb{E}\Big[\underbrace{\operatorname{sign}(\sigma_{f}(\boldsymbol{V}))\operatorname{Softmax}\left([\boldsymbol{x}^{\top},1]\boldsymbol{V}\right)}_{=:F(\boldsymbol{V},\boldsymbol{x})}\Big] - \frac{1}{M}\sum_{i=1}^{M}\operatorname{sign}(\sigma_{f}(\boldsymbol{V}_{i}))\operatorname{Softmax}\left([\boldsymbol{x}^{\top},1]\boldsymbol{V}_{i}\right)\Big| \geq \frac{t}{TV(\mu)}\bigg) \\ \leq |\mathcal{N}(\mathcal{B}(\|\cdot\|_{\infty},R),\epsilon)| \exp\left(-\frac{CMt^{2}}{TV(\mu)^{2}}\right). \end{split}$$

Alternatively, we can show the following holds with probability at least $1 - \delta$,

$$\sup_{\boldsymbol{x} \in \mathcal{N}(\mathcal{B}(\|\cdot\|_{\infty}, R), \epsilon)} \left| \mathbb{E} \left[\operatorname{sign}(\mu(\boldsymbol{v})) \operatorname{Softmax}\left([\boldsymbol{x}^{\top}, 1] \boldsymbol{V} \right) \right] - \frac{1}{M} \sum_{i=1}^{M} \operatorname{sign}(\sigma_{f}) \operatorname{Softmax}\left([\boldsymbol{x}^{\top}, 1] \boldsymbol{V}_{i} \right) \right| \\ \leq \sqrt{\frac{\log\left(\mathcal{N}(\mathcal{B}(\|\cdot\|_{\infty}, R), \epsilon) / \delta\right)}{M}}.$$

Then we consider generalizing these results to uniform convergence. For \boldsymbol{x} , we denote $\pi(\boldsymbol{x})$ as the closest point in the ϵ -cover of $\mathcal{B}(\|\cdot\|_{\infty}, R)$ denoted by $\mathcal{N}(\mathcal{B}(\|\cdot\|_{\infty}, R), \epsilon)$. For function F, we can show that for all $\boldsymbol{x} \in \mathcal{B}(\|\cdot\|_{\infty}, R)$,

$$\sup_{\boldsymbol{x}\in\mathcal{B}(\|\cdot\|_{\infty},R)} \left|\mathbb{E}[F(\boldsymbol{V},\boldsymbol{x})] - \mathbb{E}[F(\boldsymbol{V},\pi(\boldsymbol{x}))]\right| \leq \left|\boldsymbol{V}^{\top}(\boldsymbol{X}_{1}-\boldsymbol{X}_{2})\right| \leq \|\mathbb{E}[\boldsymbol{V}^{\top}]\|_{2} \|\boldsymbol{X}_{1}-\boldsymbol{X}_{2}\|_{2} \leq \epsilon$$

Then we consider the error given by

$$\sup_{\boldsymbol{x}\in\mathcal{B}(\|\cdot\|_{\infty},R)}\left|\frac{1}{M}\sum_{i=1}^{M}F(\boldsymbol{V}_{i},\boldsymbol{x})-\frac{1}{M}\sum_{i=1}^{M}F(\boldsymbol{V}_{i},\pi(\boldsymbol{x}))\right|\leq\frac{1}{M}\sum_{i=1}^{M}\epsilon\|\boldsymbol{V}_{i}\|_{2}\leq\epsilon.$$

Then the following holds with probability at least $1 - \delta$,

$$\begin{split} \sup_{\boldsymbol{x}\in\mathcal{B}(\|\cdot\|_{\infty},R)} \left| \mathbb{E}\left[F(\boldsymbol{V},\boldsymbol{x})\right] &- \frac{1}{M} \sum_{i=1}^{M} F(\boldsymbol{V}_{i},\boldsymbol{x}) \right| \\ \leq \sup_{\boldsymbol{x}\in\mathcal{B}(\|\cdot\|_{\infty},R)} \left| \mathbb{E}\left[F(\boldsymbol{V},\boldsymbol{x})\right] - \mathbb{E}\left[F(\boldsymbol{V},\pi(\boldsymbol{x}))\right] \right| + \sup_{\boldsymbol{x}\in\mathcal{B}(\|\cdot\|_{\infty},R)} \left| \frac{1}{M} \sum_{i=1}^{M} F(\boldsymbol{V}_{i},\boldsymbol{x}) - \frac{1}{M} \sum_{i=1}^{M} F(\boldsymbol{V}_{i},\pi(\boldsymbol{x})) \right| \\ &+ \sup_{\pi(\boldsymbol{x})\in\mathcal{N}(\mathcal{B}(\|\cdot\|_{\infty},R),\epsilon)} \left| \mathbb{E}\left[F(\boldsymbol{V},\pi(\boldsymbol{x}))\right] - \frac{1}{M} \sum_{i=1}^{M} F(\boldsymbol{V}_{i},\pi(\boldsymbol{x})) \right| \leq \epsilon + \epsilon + \sqrt{\frac{\log(\mathcal{N}(\mathcal{B}(\|\cdot\|_{\infty},R),\epsilon)/\delta)}{M}}. \end{split}$$

Given these results, we show that there exists a set of parameters $\{(V_i, a_i = TV(\mu) \operatorname{sign}_f(V_i))\}_{i \in [m]}$ where the following holds

$$\sup_{\boldsymbol{x}\in\mathcal{B}(\|\cdot\|_{\infty},R)} \left| \frac{1}{C_{\ell}} f(\boldsymbol{x}) - \frac{1}{M} \sum_{i=1}^{M} a_{i} \text{Softmax} \left([\boldsymbol{x}^{\top},1] \boldsymbol{V}_{i} \right) \right| \lesssim \inf_{\epsilon} \left\{ \epsilon + \sqrt{\frac{\log(\mathcal{N}(\mathcal{B}(\|\cdot\|_{\infty},R),\epsilon))}{M}} \right\} \\ \lesssim \inf_{\epsilon} \left\{ \epsilon + \sqrt{\frac{d\log\frac{R}{\epsilon}}{M}} \right\} \lesssim \sqrt{\frac{d}{M} \log\left(\frac{MR}{d}\right)},$$

where we already utilize the estimate given by Wu (2020) on the covering number of L_2 balls.

Lemma A.2 (Approximating *d* Dimensional (R, C_{ℓ}) smooth functions by Softmax Neural Networks). Consider an element-wise (R, C_{ℓ}) smooth mapping $\mathbf{f}(\mathbf{x}) = (f_1(\mathbf{x}), \dots, f_k(\mathbf{x}))^{\top}$ where $\mathbf{x} \in [-R, R]^d$. There exists a set of points $\{(\mathbf{A}_i, a_i)\}_{i \in [M]}$ with $\sup_{i \in [M]} \|\mathbf{A}\|_2 \leq C$ such that the following holds

$$\sup_{\boldsymbol{x}\in\mathcal{B}(\|\cdot\|_{\infty},R)}\frac{1}{C_{\ell}}\left\|\boldsymbol{f}(\boldsymbol{x})-\sum_{i=1}^{Md}a_{i}Softmax\left(\boldsymbol{A}_{i}\begin{bmatrix}\boldsymbol{x}\\1\end{bmatrix}\right)\right\|_{\infty}\leq C(f)^{d}\sqrt{\frac{d^{2}}{M}\log\left(\frac{MR}{d^{2}}\right)}.$$

Proof. Our proof goes by connecting the SoftMax activation with the Sigmoid functions. Note that by lemma A.1 we can show that for all $\ell \in [k]$, there exists a set $\{(v_i^{(\ell)}, a_i^{(\ell)})\}_{\ell \in [M']}$

$$\sup_{\boldsymbol{x}\in\mathcal{B}(\|\cdot\|_{\infty},R)}\frac{1}{C_{\ell}}\Big|f_{\ell}(\boldsymbol{x})-\sum_{i=1}^{M'}a_{i}^{(\ell)}\text{Sigmoid}\left(\boldsymbol{v}_{i}^{(\ell),\top}\begin{bmatrix}\boldsymbol{x}\\1\end{bmatrix}\right)\Big|\leq C(f)^{d}\sqrt{\frac{d}{M'}\log\left(\frac{M'R}{d}\right)}.$$

Consider the following matrices construction of $\{B_i^{(\ell)}\}_{i\in[d],\ell\in[M]}$ \subset $\mathbb{R}^{k\times d}$, given by $B_i^{(\ell)}$ $\begin{bmatrix} \mathbf{0}_{(\ell-1)\times(d-1)} & \mathbf{0} \\ \mathbf{v}_{i,[d-1]}^{(\ell),\top} & \log d + \mathbf{v}_{i,d}^{(\ell)} \end{bmatrix}$. Then we can show that $\sup_{\boldsymbol{x}\in\mathcal{B}(\|\cdot\|_{\infty})} \left\| \begin{bmatrix} \mathbf{0}_{(\ell-1)\times 1} \\ f_{\ell}(\boldsymbol{x}) \\ \mathbf{0} \end{bmatrix} - \sum_{i=1}^{M'} a_{i}^{(\ell)} \operatorname{Softmax}\left(\boldsymbol{B}_{i}^{(\ell)} \begin{bmatrix} \boldsymbol{x} \\ 1 \end{bmatrix}\right) \right\|_{\infty} \leq C(f)^{d} \sqrt{\frac{d}{M'} \log\left(\frac{M'R}{d}\right)},$

which completes the proof through noticing that M'd = M.

Lemma A.3 (Norm Approximation by Sigmoid Functions). *Consider the vector* $v \in \mathbb{R}^d$. *Assume that there exists a constant* $C \text{ with } \|\boldsymbol{v}\|_2 \leq C.$ For $M < \left(C\frac{\overline{R}}{\overline{R}}\right)^d \frac{1}{\epsilon^2} \log(1 + C/\epsilon)$ such that there exists $\{\boldsymbol{a}_m\}_{m \in [M]} \subset \mathbb{S}^d$ and $\{c_m\}_{m \in [M]} \subset \mathbb{R}$ where for all \boldsymbol{v} with $\overline{R} \geq \|\boldsymbol{v}\|_2 \geq R$, we have

$$\left|\sum_{m=1}^{M} c_m Sigmoid\left(\boldsymbol{a}_m^{\top} \begin{bmatrix} \boldsymbol{v} \\ 1 \end{bmatrix}\right) - \frac{1}{\|\boldsymbol{v}\|_2}\right| \leq \left(\frac{C\overline{R}}{\underline{R}}\right)^d \sqrt{\frac{d^2}{M} \log\left(\frac{MR}{d^2}\right)}.$$

Proof. Consider a set $\mathcal{C}^d(\overline{R}) := \mathcal{B}^d_{\infty}(\overline{R}) \setminus \mathcal{B}^d_2(\underline{R})$, we note that

$$\sup_{\boldsymbol{v}\in\mathcal{C}^{d}(\overline{R})}\partial_{v_{j_{1}},\ldots,v_{j_{i}}\in[d]}\left(\frac{1}{\|\boldsymbol{v}\|_{2}}\right)\leq\frac{C^{d}}{\|\boldsymbol{v}\|_{2}^{d}}\leq\frac{C^{d}}{\underline{R}^{d}}$$

Therefore, consider the definition A.1, we have $C_{\ell} = \left(\frac{\overline{R}}{\overline{R}}\right)^d C^d$. Then the result is concluded by lemma A.3.

B. Omitted Proofs

B.1. Proof of Theorem 3.1

The proof of the Maximization step follows directly from that of the proof of theorem 3.2. We only change the proof of the Expectation Step for the Transformer layers.

1. The Expectation Step.

For the expectation step, our network is designed by

$$\begin{split} \boldsymbol{V}_{1}^{(1)} &= \begin{bmatrix} \boldsymbol{0}_{(3d+k+1)\times(D-d)} & \boldsymbol{0} \\ I_{d} & \boldsymbol{0} \\ \boldsymbol{0} & \boldsymbol{0} \end{bmatrix}, \quad \boldsymbol{Q}_{1}^{(1)} = \begin{bmatrix} \boldsymbol{0}_{k\times 2d} & I_{k} & \boldsymbol{0} \\ \boldsymbol{0} & \boldsymbol{0} \end{bmatrix}, \quad \boldsymbol{K}_{1}^{(1)} = \begin{bmatrix} \boldsymbol{0}_{d\times(2d+k)} & I_{d} & \boldsymbol{0} \\ 0 & \boldsymbol{0} \end{bmatrix}, \\ \boldsymbol{V}_{2}^{(1)} &= \begin{bmatrix} \boldsymbol{0}_{(3d+k+1)\times(D-d)} & \boldsymbol{0} \\ I_{d} & \boldsymbol{0} \\ \boldsymbol{0} & \boldsymbol{0} \end{bmatrix}, \quad \boldsymbol{Q}_{2}^{(1)} = \boldsymbol{0}, \quad \boldsymbol{K}_{1}^{(1)} = \begin{bmatrix} \boldsymbol{0}_{d\times(2d+k)} & I_{d} & \boldsymbol{0} \\ 0 & \boldsymbol{0} \end{bmatrix}. \end{split}$$

Then we can show that

$$V_1^{(1)}H = \begin{bmatrix} \mathbf{0}_{d \times N} \\ X_1 & \cdots & X_N \\ \mathbf{0} \end{bmatrix}, \quad Q_1^{(1)}H_1 = \begin{bmatrix} (2\log N)\mathbf{p}_{1,1}^{(0)} & \cdots & (2\log N)\mathbf{p}_{1,N}^{(0)} \\ \mathbf{0} \end{bmatrix}, \quad K_1^{(1)}H_1 = \begin{bmatrix} I_d & \mathbf{0} \\ \mathbf{0} & \mathbf{0} \end{bmatrix}.$$

Hence we can show that

$$\operatorname{SoftMax}\left((\boldsymbol{Q}_1^{(1)} \boldsymbol{H}_1)^\top (\boldsymbol{K}_1^{(1)} \boldsymbol{H}_1) \right) = \operatorname{SoftMax}\left(\begin{bmatrix} C(\log N) \boldsymbol{p}_{1,1}^{(0),\top} & \boldsymbol{0} \\ \vdots & \vdots \\ C(\log N) \boldsymbol{p}_{1,N}^{(0),\top} & \boldsymbol{0} \end{bmatrix} \right).$$

. -

We further note that

$$\left|\frac{\exp(C\log N)}{\sum_{i=1}^{N}\mathbbm{1}_{\hat{z}_{i}^{(0)}=j}\exp(C\log N)+\mathbbm{1}_{\hat{z}_{i}^{(0)}\neq j}}-\frac{1}{\sum_{i=1}^{N}\mathbbm{1}_{\hat{z}_{i}^{(0)}=j}}\right|\leq N^{-C}.$$

Similarly we have

$$\left|\frac{1}{\sum_{i=1}^{N} \mathbb{1}_{\hat{z}_{i}^{(0)}=j} \exp(C \log N) + \mathbb{1}_{\hat{z}_{i}^{(0)}\neq j}}\right| \leq N^{-C}$$

We further note that

SoftMax
$$\left((\boldsymbol{Q}_1^{(1)} \boldsymbol{H}_1)^{\top} (\boldsymbol{K}_1^{(1)} \boldsymbol{H}_1) \right) = \begin{bmatrix} \frac{1}{N} & \cdots & \frac{1}{N} \\ \vdots & \ddots & \vdots \\ \frac{1}{N} & \cdots & \frac{1}{N} \end{bmatrix}.$$

Hence one can show that

$$\left\| \boldsymbol{H} \sum_{i=1}^{2} \operatorname{SoftMax} \left(\boldsymbol{H}^{\top} \boldsymbol{Q}_{i}^{(1),\top} \boldsymbol{K}_{i}^{(1)} \boldsymbol{H} \right) - \begin{bmatrix} \hat{\boldsymbol{\mu}}_{1}^{(1)} & \dots & \hat{\boldsymbol{\mu}}_{k}^{(1)} & \boldsymbol{0} \\ \boldsymbol{0} & & \end{bmatrix} \right\|_{2} \leq N^{-1}.$$

Therefore, applying V_1 we have

$$\left\| \sum_{i=1}^{2} \boldsymbol{V}_{i}^{(1)} \boldsymbol{H} \cdot \operatorname{SoftMax} \left(\boldsymbol{H}^{\top} \boldsymbol{Q}_{i}^{(1), \top} \boldsymbol{K}_{i}^{(1)} \boldsymbol{H} \right) - \left[\begin{matrix} \boldsymbol{X}_{1} & \boldsymbol{X}_{2} & \dots & \boldsymbol{x}_{k} & \dots & \boldsymbol{X}_{N} \\ \hat{\boldsymbol{\mu}}_{1}^{(0)} & \hat{\boldsymbol{\mu}}_{2}^{(0)} & \dots & \hat{\boldsymbol{\mu}}_{k}^{(0)} & \dots & \boldsymbol{0} \\ \boldsymbol{p}_{1,1}' & \boldsymbol{p}_{1,2}' & \dots & \boldsymbol{p}_{1,k}' & \dots & \boldsymbol{p}_{1,N}' \\ \boldsymbol{p}_{2,1} & \boldsymbol{p}_{2,2} & \dots & \boldsymbol{p}_{2,k} & \dots & \boldsymbol{p}_{2,N}' \\ 1 & 1 & \dots & 1 & \dots & 1 \\ \hat{\boldsymbol{\mu}}_{1}^{(1)} & \hat{\boldsymbol{\mu}}_{2}^{(1)} & \dots & \hat{\boldsymbol{\mu}}_{k}^{(1)} & \dots & \boldsymbol{0} \\ & \boldsymbol{0} & & \end{matrix} \right] \right\|_{2} \leq N^{-1}.$$

And the Expectation Step is concluded as we updates the centroids from $\{\mu_i^{(0)}\}_{i \in [k]}$ to $\{\mu_i^{(1)}\}_{i \in [k]}$. The next step is to update the assignment $p'_{1,i}$ to $p_{1,i}^{(1)}$ for $i \in [N]$.

B.2. Proof of Theorem 3.2

We first consider the input matrix to be

$$m{H}_1 \coloneqq egin{bmatrix} m{X}_1 & m{X}_2 & \dots & m{x}_n \ \hat{m{\mu}}_1^{(0)} & \hat{m{\mu}}_2^{(0)} & \dots & m{0} \ m{p}_{1,1} & m{p}_{1,2} & \dots & m{p}_{1,N} \ m{p}_{2,1} & m{p}_{2,2} & \dots & m{p}_{2,N} \ 1 & 1 & \dots & 1 \ m{p}_{3,1} & m{p}_{3,2} & \dots & m{p}_{3,N} \end{bmatrix} \in \mathbb{R}^{D imes N},$$

where $\hat{z}^{(0)} : [n] \to [k]$ is the assignment function, $\hat{\mu}_i \in \mathbb{R}^d$ is the initially estimated centroid for the *i*-th cluster. $p_{1,i} \in \mathbb{R}^k$ satisfies $p_{1,i,j} = \mathbb{1}_{\hat{z}^{(0)}(i)=j}$ for all $j \in [k]$. And for $p_{2,i}$ we have $p_{2,i,j} = \mathbb{1}_{j=i}$ for $i \leq d$ and $p_{2,i,j} = 0$ for $i \leq N$ and $j \leq d$. We let $p_{3,1} = p_{3,2} = \ldots = p_{3,N} = \mathbf{0} \in \mathbb{R}^k$. We note that algorithm 1 consists of two iterative steps: (1) The expectation step where we take the averages to get an initial estimate $\hat{\mu}_{\ell}^{(i)}$. (2) The maximization step where we assign each individual sample their labels. Our following discussions simulate the two steps separately as follows.

1. The Expectation Step.

To achieve the first step, we construct our transformer weights as follows:

$$\boldsymbol{V}_{1}^{(1)} = \begin{bmatrix} \tilde{\boldsymbol{V}}_{1,1}^{(1)} & \tilde{\boldsymbol{V}}_{1,2}^{(1)} & \tilde{\boldsymbol{V}}_{1,3}^{(1)} \end{bmatrix}, \quad \boldsymbol{Q}_{1}^{(1)} = \begin{bmatrix} \boldsymbol{0}_{1 \times (3d+k)} & 1 & \boldsymbol{0} \\ \boldsymbol{0} & \boldsymbol{0} & \boldsymbol{0} \end{bmatrix}, \quad \boldsymbol{K}_{1}^{(1)} = \begin{bmatrix} \boldsymbol{0}_{1 \times (3d+k)} & 1 & \boldsymbol{0} \\ \boldsymbol{0} & \boldsymbol{0} & \boldsymbol{0} \end{bmatrix},$$

where
$$\tilde{\boldsymbol{V}}_{1,1}^{(1)} \in \mathbb{R}^{2d \times D} = \boldsymbol{0}, \ \tilde{\boldsymbol{V}}_{1,2}^{(1)} = \begin{bmatrix} \boldsymbol{0}_{3d+k} \\ I_k \\ \boldsymbol{0} \end{bmatrix} \in \mathbb{R}^{k \times D}$$
. Then we can show that
$$\begin{pmatrix} \boldsymbol{K}_1^{(1)} \boldsymbol{H}_1 \end{pmatrix}^\top = \begin{pmatrix} \boldsymbol{Q}_1^{(1)} \boldsymbol{H} \end{pmatrix}^\top = \begin{bmatrix} 1 & \boldsymbol{0} \\ \vdots & \boldsymbol{0} \\ 1 & \boldsymbol{0} \end{bmatrix}.$$

Then we can show that

$$(\boldsymbol{Q}_1^{(1)}\boldsymbol{H})^{\top}(\boldsymbol{K}_1^{(1)}\boldsymbol{H}) = \begin{bmatrix} \boldsymbol{v}_1 & \dots & \boldsymbol{v}_1 \end{bmatrix}, \quad \boldsymbol{v}_{1,i} = 1 \quad \forall i \in [N].$$

And after the Softmax function we obtain that

SoftMax
$$\left((\boldsymbol{Q}_1^{(1)} \boldsymbol{H})^\top (\boldsymbol{K}_1^{(1)} \boldsymbol{H}) \right) = \begin{bmatrix} \frac{1}{D} \boldsymbol{v}_1 & \dots & \frac{1}{D} \boldsymbol{v}_1 \end{bmatrix}$$
.

Hence, we further obtain that

$$\begin{split} \boldsymbol{V}_{1}^{(1)}\boldsymbol{H} \times \operatorname{SoftMax}((\boldsymbol{Q}_{1}^{(1)}\boldsymbol{H})^{\top}(\boldsymbol{K}_{1}^{(1)}\boldsymbol{H})) &= \boldsymbol{V}_{1}\boldsymbol{H} \times \begin{bmatrix} \frac{1}{D}\boldsymbol{v}_{1} & \dots & \frac{1}{D}\boldsymbol{v}_{1} \end{bmatrix} = \boldsymbol{V}_{1} \times \begin{bmatrix} \boldsymbol{A}_{0} & \\ \frac{1}{D}\boldsymbol{v}_{k} & \dots & \frac{1}{D}\boldsymbol{v}_{k} \end{bmatrix} \\ &= \begin{bmatrix} \tilde{\boldsymbol{V}}_{1,1}^{(1)} & \tilde{\boldsymbol{V}}_{1,2}^{(1)} & \tilde{\boldsymbol{V}}_{1,3}^{(1)} \end{bmatrix} \begin{bmatrix} \frac{1}{D}\boldsymbol{v}_{k} & \frac{\boldsymbol{A}_{0}}{\boldsymbol{A}_{1}} & \frac{1}{D}\boldsymbol{v}_{k} \end{bmatrix} = \tilde{\boldsymbol{V}}_{1,2}^{(1)} \begin{bmatrix} \frac{1}{D}\boldsymbol{v}_{k} & \dots & \frac{1}{D}\boldsymbol{v}_{k} \end{bmatrix} \\ &= \begin{bmatrix} \boldsymbol{0}_{3d+k} \\ \boldsymbol{I}_{k} \\ \boldsymbol{0} \end{bmatrix} \begin{bmatrix} \frac{1}{D}\boldsymbol{v}_{k} & \dots & \frac{1}{D}\boldsymbol{v}_{k} \end{bmatrix} = \begin{bmatrix} \frac{1}{D}\boldsymbol{v}_{k} & \dots & \frac{1}{D}\boldsymbol{v}_{k} \end{bmatrix}, \end{split}$$

where $A_0 \in \mathbb{R}^{2d \times N}$ and $v_{k,\ell} = \sum_{i=1}^N \mathbb{1}_{\hat{z}_i^{(0)} = \ell}$. Then it is checked that

$$\boldsymbol{H}_{2} = \boldsymbol{H}_{1} + \boldsymbol{V}_{1}^{(1)} \boldsymbol{H}_{1} \times \text{SoftMax} \left((\boldsymbol{Q}_{1}^{(1)} \boldsymbol{H}_{1})^{\top} (\boldsymbol{K}_{1}^{(1)} \boldsymbol{H}_{1}) \right) = \begin{bmatrix} \boldsymbol{X}_{1} & \boldsymbol{X}_{2} & \dots & \boldsymbol{X}_{N} \\ \hat{\boldsymbol{\mu}}_{1}^{(0)} & \hat{\boldsymbol{\mu}}_{2}^{(0)} & \dots & \boldsymbol{0} \\ \boldsymbol{p}_{1,1}^{(0)} & \boldsymbol{p}_{1,2}^{(0)} & \dots & \boldsymbol{p}_{1,N}^{(0)} \\ \boldsymbol{p}_{2,1} & \boldsymbol{p}_{2,2} & \dots & \boldsymbol{p}_{2,N} \\ 1 & 1 & \dots & 1 \\ \frac{1}{D} \boldsymbol{v}_{k} & \frac{1}{D} \boldsymbol{v}_{k} & \dots & \frac{1}{D} \boldsymbol{v}_{k} \end{bmatrix}$$

Therefore, we construct the following multi-head layer to remove the off-diagonal elements in $\begin{bmatrix} \frac{1}{D} v_k & \frac{1}{D} v_k & \dots & \frac{1}{D} v_k \end{bmatrix}$, given by

$$\begin{split} \boldsymbol{V}_{2i}^{(2)} &= -\boldsymbol{V}_{2i+1}^{(2)} = \frac{N}{N-1} \begin{bmatrix} \mathbf{0}_{(3d+2k+i)\times D} \\ \mathbf{0}_{1\times(3d+2k+i)} & 1 & \mathbf{0} \\ \mathbf{0} \end{bmatrix}, \\ \boldsymbol{Q}_{2i}^{(2)} &= \begin{bmatrix} \mathbf{0}_{i-1} & \mathbf{0}_{1\times(2d+k)} & 1 & \mathbf{0} \\ \mathbf{0} \end{bmatrix}, \quad \boldsymbol{K}_{2i+1}^{(2)} = \mathbf{0}, \quad \text{for } i \in [k]. \end{split}$$

Given this formulation, we can show that the mapping f(x) = 1 is (1, 1) smooth

$$\begin{pmatrix} \boldsymbol{Q}_{2i}^{(2)} \boldsymbol{H} \end{pmatrix}^{\top} \begin{pmatrix} \boldsymbol{K}_{2i}^{(2)} \boldsymbol{H} \end{pmatrix} = \begin{bmatrix} \boldsymbol{0}_{(i-1)\times 1} & \boldsymbol{0}_{1\times(D-1)} \\ N & \boldsymbol{0}_{1\times(D-1)} \\ 0 & \mathbf{0} \end{bmatrix} \begin{bmatrix} \boldsymbol{0}_{1\times(i-1)} & N & \mathbf{0} \\ \mathbf{0} & \mathbf{0} & \mathbf{0} \end{bmatrix} = \begin{bmatrix} \boldsymbol{0}_{(i-1)\times N} \\ \boldsymbol{0}_{1\times(i-1)} & N^2 & \mathbf{0} \\ \mathbf{0} & \mathbf{0} \end{bmatrix} .$$

After the Softmax function, we have

$$\operatorname{SoftMax}\left((\boldsymbol{Q}_{2i}^{(2)}\boldsymbol{H})^{\top}(\boldsymbol{K}_{2i}^{(2)}\boldsymbol{H})\right) = \begin{bmatrix} \frac{1}{N} & \cdots & \frac{1}{\exp(N^2)+N-1} & \cdots & \frac{1}{N} \\ \vdots & \ddots & \vdots & \cdots & \vdots \\ \frac{1}{N} & \cdots & \frac{\exp(N^2)}{\exp(N^2)+N-1} & \cdots & \frac{1}{N} \\ \vdots & \ddots & \vdots & \ddots & \vdots \\ \frac{1}{N} & \cdots & \frac{1}{\exp(N^2)+N-1} & \cdots & \frac{1}{N} \end{bmatrix}$$

And similarly we can show that $(\boldsymbol{Q}_{2i+1}^{(2)}\boldsymbol{H})^{\top}(\boldsymbol{K}_{2i+1}^{(2)}\boldsymbol{H}) = \boldsymbol{0}$, which implies that

SoftMax
$$\left((\boldsymbol{Q}_{2i+1}^{(2)} \boldsymbol{H})^{\top} (\boldsymbol{K}_{2i+1}^{(2)} \boldsymbol{H}) \right) = \begin{bmatrix} \frac{1}{N} & \cdots & \frac{1}{N} \\ \vdots & \ddots & \vdots \\ \frac{1}{N} & \cdots & \frac{1}{N} \end{bmatrix}$$

We notice that after the softmax, only the *i*-th column remains nonzero, where the value for its *i*-th row is given by

$$\left|\frac{\exp(N^2) - 1}{\exp(N^2) + D - 1} - 1\right| \lesssim D\exp(-N^2).$$

Hence, the following holds

$$\begin{split} & \operatorname{SoftMax} \left((\boldsymbol{Q}_{2i}^{(2)} \boldsymbol{H})^{\top} (\boldsymbol{K}_{2i}^{(2)} \boldsymbol{H}) \right) - \operatorname{SoftMax} \left((\boldsymbol{Q}_{2i+1}^{(2)} \boldsymbol{H})^{\top} (\boldsymbol{K}_{2i+1}^{(2)} \boldsymbol{H}) \right) \\ & = \begin{bmatrix} \boldsymbol{0}_{(i-1) \times (i-1)} & \boldsymbol{0}_{(i-1) \times 1} & \boldsymbol{0}_{(i-1) \times (N-1)} \\ \boldsymbol{0}_{1 \times (i-1)} & \frac{N-1}{N} + O \left(D \exp \left(-N^2 \right) \right) & \boldsymbol{0} \\ \boldsymbol{0} & \boldsymbol{0} & \boldsymbol{0} \end{bmatrix} \\ & = \frac{N-1}{N} \begin{bmatrix} \boldsymbol{0}_{(3d+2k+i) \times D} \\ \boldsymbol{0}_{(i-1)} & \boldsymbol{v}_{k,i} + O (D \exp \left(-N^2 \right)) & \boldsymbol{0} \\ \boldsymbol{0} & \boldsymbol{0} \end{bmatrix}, \end{split}$$

which immediately implies that

$$\sum_{i=1}^{2k} \mathbf{V}_i^{(2)} \mathbf{H}_2 \text{SoftMax} \left((\mathbf{Q}_i^{(2)} \mathbf{H}_2)^\top (\mathbf{K}_i^{(2)} \mathbf{H}_2) \right) = \begin{bmatrix} \mathbf{0}_{(3d+2k) \times N} \\ \text{diag}(\mathbf{v}_k) + O(D \exp(-N^2)) & \mathbf{0} \\ \mathbf{0} \end{bmatrix}$$

Given the above design, we can show that

$$\begin{split} \boldsymbol{H}_{3,1} &= \boldsymbol{H}_2 + \sum_{i=1}^k \boldsymbol{V}_i^{(2)} \boldsymbol{H}_2 \text{SoftMax} \left((\boldsymbol{Q}_i^{(2)} \boldsymbol{H}_2)^\top (\boldsymbol{K}_i^{(2)} \boldsymbol{H}_2) \right) \\ &= \begin{bmatrix} \boldsymbol{X}_1 & \boldsymbol{X}_2 & \dots & \boldsymbol{X}_N \\ \hat{\boldsymbol{\mu}}_1^{(0)} & \hat{\boldsymbol{\mu}}_2^{(0)} & \dots & \boldsymbol{0} \\ \boldsymbol{p}_{1,1}^{(0)} & \boldsymbol{p}_{1,2}^{(0)} & \dots & \boldsymbol{p}_{1,N}^{(0)} \\ \boldsymbol{p}_{2,1} & \boldsymbol{p}_{2,2} & \dots & \boldsymbol{p}_{2,N} \\ 1 & 1 & \dots & 1 \\ \boldsymbol{v}_k & \boldsymbol{v}_k & \dots & \boldsymbol{v}_k \\ \text{diag}(\boldsymbol{v}_k) + O(D \exp(-N^2)) & \boldsymbol{0} \\ & \boldsymbol{0} \end{bmatrix}. \end{split}$$

Then, we construct the MLP layer to remove the v_k part, which is designed by

$$m{W}_1^{(2)} = I_D, \quad m{W}_2^{(2)} = egin{bmatrix} m{0}_{(3d+k) imes D} & & \ m{0}_{k imes (3d+k)} & -I_k & I_k & m{0} \ m{0} & -I_k & m{0} & m{0} \ m{0} & -I_k & m{0} & m{0} \ m{0} & m{0} & m{0} \end{bmatrix}.$$

Given this formulation, we can show that

$$\boldsymbol{H}_{3} := \boldsymbol{H}_{3,1} + \boldsymbol{W}_{1}^{(2)} \sigma \left(\boldsymbol{W}_{2}^{(2)} \boldsymbol{H}_{3,1} \right) = \begin{bmatrix} \boldsymbol{X}_{1} & \boldsymbol{X}_{2} & \dots & \boldsymbol{X}_{N} \\ \hat{\boldsymbol{\mu}}_{1}^{(0)} & \hat{\boldsymbol{\mu}}_{2}^{(0)} & \dots & \boldsymbol{0} \\ \boldsymbol{p}_{1,1}^{(0)} & \boldsymbol{p}_{1,2}^{(0)} & \dots & \boldsymbol{p}_{1,N}^{(0)} \\ \boldsymbol{p}_{2,1} & \boldsymbol{p}_{2,2} & \dots & \boldsymbol{p}_{2,N} \\ 1 & 1 & \dots & 1 \\ \boldsymbol{v}_{k} & \boldsymbol{v}_{k} & \dots & \boldsymbol{v}_{k} \\ \operatorname{diag}(\boldsymbol{v}_{k}) + O(D \exp(-N^{2})) & \boldsymbol{0} & \\ & \boldsymbol{0} & \end{bmatrix}.$$

The following layer converts the term $diag(v_k)$ to $diag(v'_k)$ where $v'_{k,i} = 1/v_{k,i}$. The design is given as follows for all $i \in [M]$,

$$\begin{split} \boldsymbol{V}_{i}^{(3)} &= \begin{bmatrix} \mathbf{0}_{(3d+3k+1)\times D} \\ \mathbf{0}_{k\times(2d+2k)} & \operatorname{diag}(c_{i})_{k\times k} & \mathbf{0} \\ \mathbf{0} \end{bmatrix}, \quad \boldsymbol{Q}_{i}^{(3)} = \begin{bmatrix} \mathbf{0}_{(3d+3k+1)\times D} \\ \mathbf{0}_{k\times(2d+2k)} & \boldsymbol{I}_{k} & \mathbf{0} \\ \mathbf{0} \end{bmatrix}, \\ \boldsymbol{K}_{i}^{(3)} &= \begin{bmatrix} \mathbf{0}_{(3d+3k+1)\times D} \\ \mathbf{0}_{k\times(3d+3k+1)} & \operatorname{diag}(a_{i})_{k\times k} & \mathbf{0} \\ \mathbf{0} \end{bmatrix} \begin{bmatrix} \mathbf{0}_{k\times(3d+2k+1)} & \boldsymbol{I}_{k} & \mathbf{0} \\ \mathbf{0} \end{bmatrix}, \end{split}$$

where we show in lemma A.1 that there exists set of values $\{(c_i, a_i)\}_{i \in [M]}$ such that the following holds for all $\underline{R} \leq x \leq \overline{R}$,

$$\left\|\sum_{i=1}^{M} c_i \operatorname{Sigmoid}(a_i x) - \frac{1}{x}\right\|_2 \le \left(\frac{C\overline{R}}{\underline{R}}\right) \sqrt{\frac{\log\left(M\overline{R}\right)}{M}}.$$

Using the above result, we immediately obtain that

$$\begin{split} \boldsymbol{H}_{4,1} &:= \boldsymbol{H}_3 + \sum_{i=1}^{M} \boldsymbol{V}_i^{(3)} \boldsymbol{H}_3 \text{SoftMax} \left((\boldsymbol{Q}_i^{(3)} \boldsymbol{H}_3)^\top (\boldsymbol{K}_i^{(3)} \boldsymbol{H}_3) \right) \\ &= \begin{bmatrix} \boldsymbol{X}_1 & \boldsymbol{X}_2 & \dots & \boldsymbol{X}_N \\ \hat{\boldsymbol{\mu}}_1^{(0)} & \hat{\boldsymbol{\mu}}_2^{(0)} & \dots & \boldsymbol{0} \\ \boldsymbol{p}_{1,1}^{(0)} & \boldsymbol{p}_{1,2}^{(0)} & \dots & \boldsymbol{p}_{1,N}^{(0)} \\ \boldsymbol{p}_{2,1} & \boldsymbol{p}_{2,2} & \dots & \boldsymbol{p}_{2,N} \\ 1 & 1 & \dots & 1 \\ \boldsymbol{v}_k & \boldsymbol{v}_k & \dots & \boldsymbol{v}_k \\ \text{diag}(\boldsymbol{v}_k) & \boldsymbol{0} \\ \text{diag}(\boldsymbol{v}_k) & \boldsymbol{0} \\ & \boldsymbol{0} \end{bmatrix} + C \sqrt{\frac{\log(MD)}{M}}, \end{split}$$

where $m{v}_{k,i}' = m{v}_{k,i}^{-1}$. Then we apply the MLP again with the following design

$$oldsymbol{W}_1^{(4)} = I_D, \quad oldsymbol{W}_2^{(4)} = egin{bmatrix} oldsymbol{0}_{k imes (3d+k)} & -I_k & I_k & oldsymbol{0}_k & oldsymbol{0}_{k imes (3d+k)} & -I_k & oldsymbol{0}_k & oldsymbol{0}_k$$

The above construction implies that

$$m{H}_4 = m{W}_2^{(3)} \sigma \left(m{W}_1^{(3)} m{H}_3
ight) = egin{bmatrix} m{X}_1 & m{X}_2 & \dots & m{X}_N \ \hat{m{\mu}}_1^{(0)} & \hat{m{\mu}}_2^{(0)} & \dots & m{0} \ m{p}_{1,1}^{(0)} & m{p}_{1,2}^{(0)} & \dots & m{p}_{1,N}^{(0)} \ m{p}_{2,1} & m{p}_{2,2} & \dots & m{p}_{2,N} \ 1 & 1 & \dots & 1 \ m{v}_k & m{v}_k & \dots & m{v}_k \ m{diag}(m{v}_k') & m{0} & m{u} \end{bmatrix}.$$

We construct the following layer to perform the normalization, given by

$$\begin{split} \boldsymbol{V}_{i}^{(4)} &= \begin{bmatrix} \boldsymbol{0}_{(3d+2k+1)\times D} \\ \boldsymbol{0}_{k\times(3d+k+1)} & I_{k} & \boldsymbol{0} \\ & \boldsymbol{0} \end{bmatrix}, \quad \boldsymbol{Q}_{i}^{(4)} &= \begin{bmatrix} \boldsymbol{0}_{(3d+2k+1)\times D} \\ \boldsymbol{0}_{k\times 3d} & I_{k} & \boldsymbol{0} \\ & \boldsymbol{0} \end{bmatrix}, \\ \boldsymbol{K}_{i}^{(4)} &= \begin{bmatrix} \boldsymbol{0}_{(3d+1)\times D} \\ \boldsymbol{0}_{d\times(3d+2k+1)} & \boldsymbol{A}_{i} & \boldsymbol{0} \\ & \boldsymbol{0} \end{bmatrix} \begin{bmatrix} \boldsymbol{0}_{k\times(3d+1)} & I_{k} & \boldsymbol{0} \\ & \boldsymbol{0} \end{bmatrix}. \end{split}$$

Then, using the approximation bound for the Softmax mapping in lemma A.3, we can show that there exists $\{(A_i, c_i)\}_{i \in [M]}$ such that

$$\sum_{i=1}^{M} c_i \text{SoftMax} \left((\boldsymbol{Q}_i^{(4)} \boldsymbol{H}_4)^\top (\boldsymbol{K}_i^{(4)} \boldsymbol{H}_4) \right) = \begin{bmatrix} \boldsymbol{0}_{(3d+2k+1) \times D} \\ \boldsymbol{p}_{1,1} & \dots & \boldsymbol{p}_{1,N} \end{bmatrix} + O\left(C^d \sqrt{\frac{d}{M} \log\left(\frac{M}{d^2}\right)} \right).$$

And we also have

$$\boldsymbol{V}_2^{(4)}\boldsymbol{H}_4 = \begin{bmatrix} \boldsymbol{0}_{(3d+3k+1)\times D} \\ \boldsymbol{0}_{k\times(3d+2k+1)} & \operatorname{diag}(\boldsymbol{v}_k') + C\sqrt{\frac{\log(MD)}{M}} & \boldsymbol{0} \end{bmatrix},$$

which implies that

$$\begin{split} \boldsymbol{H}_{4,1} &= \boldsymbol{H}_3 + \sum_{i=1}^{M} \boldsymbol{V}_i^{(4)} \boldsymbol{H}_3 \times \text{SoftMax} \left((\boldsymbol{Q}_i^{(4)} \boldsymbol{H}_3)^\top (\boldsymbol{K}_i^{(3)} \boldsymbol{H}_3) \right) \\ &= \begin{bmatrix} \boldsymbol{X}_1 & \boldsymbol{X}_2 & \dots & \boldsymbol{X}_N \\ \hat{\boldsymbol{\mu}}_1^{(0)} & \hat{\boldsymbol{\mu}}_2^{(0)} & \dots & \boldsymbol{0} \\ \boldsymbol{p}_{1,1}^{(0)} & \boldsymbol{p}_{1,2}^{(0)} & \dots & \boldsymbol{p}_{1,N}^{(0)} \\ \boldsymbol{p}_{2,1} & \boldsymbol{p}_{2,2} & \dots & \boldsymbol{p}_{2,N} \\ 1 & 1 & \dots & 1 \\ \text{diag}(\boldsymbol{v}_k') & \boldsymbol{0} \\ \boldsymbol{p}_{1,1}' & \boldsymbol{p}_{1,2}' & \dots & \boldsymbol{p}_{1,N}' \end{bmatrix} + O\left(C^d \sqrt{\frac{d}{M} \log\left(\frac{M}{d^2}\right)}\right), \end{split}$$

where $p'_{1,i} = \text{diag}(v'_k)p_{1,i}$ for all $i \in [N]$. We therefore construct an MLP layer to replace the p_1 part using the following design

$$m{W}_1^{(4)} = I_D, \qquad m{W}_2^{(4)} = egin{bmatrix} m{0}_{k imes 2d} & -I_k & m{0}_{d imes d} & I_k & m{0} \ m{0} & m{0} & m{0} & m{0} & m{0} \ m{0}_{k imes 2d} & -I_k & m{0} & m{0} & m{0} \ m{0}_{k imes 2d} & -I_k & m{0} & m{0} & m{0} \ m{0}_{(d+1) imes D} & m{0} \end{bmatrix},$$

which immediately leads to

$$\boldsymbol{H}_{4} = \boldsymbol{W}_{1}^{(4)} \sigma \left(\boldsymbol{W}_{2}^{(4)} \boldsymbol{H}_{3} \right) + \boldsymbol{H}_{3} = \begin{bmatrix} \boldsymbol{X}_{1} & \boldsymbol{X}_{2} & \dots & \boldsymbol{x}_{k} & \dots & \boldsymbol{X}_{N} \\ \hat{\boldsymbol{\mu}}_{1}^{(0)} & \hat{\boldsymbol{\mu}}_{2}^{(0)} & \dots & \hat{\boldsymbol{\mu}}_{k}^{(0)} & \dots & \boldsymbol{0} \\ \boldsymbol{p}_{1,1}' & \boldsymbol{p}_{1,2}' & \dots & \boldsymbol{p}_{1,k}' & \dots & \boldsymbol{p}_{1,N}' \\ \boldsymbol{p}_{2,1} & \boldsymbol{p}_{2,2} & \dots & \boldsymbol{p}_{2,k} & \dots & \boldsymbol{p}_{2,N}' \\ 1 & 1 & \dots & 1 & \dots & 1 \end{bmatrix} + O\left(C^{d}\sqrt{\frac{d}{M}\log\left(\frac{M}{d^{2}}\right)}\right)$$

Then the next layer is designed as follows

_

$$\begin{split} \boldsymbol{V}_{1}^{(5)} &= \begin{bmatrix} \boldsymbol{0}_{d \times (D-d)} & \boldsymbol{0} \\ I_{d} & \boldsymbol{0} \\ \boldsymbol{0} & \boldsymbol{0} \end{bmatrix}, \quad \boldsymbol{Q}_{1}^{(5)} = \begin{bmatrix} \boldsymbol{0}_{k \times 2d} & I_{k} & \boldsymbol{0} \\ \boldsymbol{0} & \boldsymbol{0} \end{bmatrix}, \quad \boldsymbol{K}_{1}^{(5)} = \begin{bmatrix} \boldsymbol{0}_{d \times (2d+k)} & I_{d} & \boldsymbol{0} \\ 0_{d \times d} & \boldsymbol{0} & \boldsymbol{0} \\ \boldsymbol{0}_{d \times d} & -I_{d} & \boldsymbol{0} \\ \boldsymbol{0} & \boldsymbol{0} \end{bmatrix}, \quad \boldsymbol{Q}_{2}^{(5)} = \boldsymbol{K}_{2}^{(5)} = \begin{bmatrix} \boldsymbol{0}_{d \times d} & \boldsymbol{0} & \boldsymbol{0} \\ \boldsymbol{0}_{d \times d} & -I_{d} & \boldsymbol{0} \\ \boldsymbol{0} & \boldsymbol{0} \end{bmatrix}. \end{split}$$

And we can show that under this construction,

$$\boldsymbol{V}_{1}^{(5)}\boldsymbol{H}_{4}(\boldsymbol{Q}_{1}^{(5)}\boldsymbol{H}_{4})^{\top} = \begin{bmatrix} \boldsymbol{0}_{d} \\ \hat{\boldsymbol{\mu}}_{1}^{(1)} & \dots & \hat{\boldsymbol{\mu}}_{k}^{(1)} & \boldsymbol{0} \end{bmatrix} + O\left(C^{d}\sqrt{\frac{d}{M}\log\left(\frac{M}{d^{2}}\right)}\right), \quad \boldsymbol{K}^{(5)}\boldsymbol{H}_{4} = \begin{bmatrix} I_{d} & \boldsymbol{0} \\ \boldsymbol{0} & \boldsymbol{0} \end{bmatrix},$$
$$\boldsymbol{V}_{2}^{(5)}\boldsymbol{H}_{4}(\boldsymbol{Q}_{2}^{(5)}\boldsymbol{H}_{4})^{\top}(\boldsymbol{K}_{2}^{(5)}\boldsymbol{H}_{4}) = \begin{bmatrix} -\hat{\boldsymbol{\mu}}_{1}^{(0)} & \dots & \hat{\boldsymbol{\mu}}_{k}^{(0)} & \boldsymbol{0} \end{bmatrix}.$$

And, we can show that

$$oldsymbol{H}_{5,1} = oldsymbol{H}_4 + oldsymbol{V}^{(5)}oldsymbol{H}_4)^ op (oldsymbol{K}^{(5)}oldsymbol{H}_4) = egin{bmatrix} oldsymbol{X}_1 & oldsymbol{X}_2 & \dots & oldsymbol{x}_k & \dots & oldsymbol{X}_N \ oldsymbol{\mu}_1^{(1)} & oldsymbol{\mu}_2^{(1)} & \dots & oldsymbol{\mu}_k^{(1)} & \dots & oldsymbol{0} \ oldsymbol{p}_{1,1}' & oldsymbol{p}_{1,2}' & \dots & oldsymbol{p}_{1,k}' & \dots & oldsymbol{p}_{1,N}' \ oldsymbol{p}_{2,1} & oldsymbol{p}_{2,2} & \dots & oldsymbol{p}_{2,k}' & \dots & oldsymbol{p}_{2,N}' \ oldsymbol{1} & \dots & oldsymbol{1} & \dots & oldsymbol{1} \ oldsymbol{0} & oldsymbol{u} & \dots & oldsymbol{1} \ oldsymbol{0} & oldsymbol{u}_1 & oldsymbol{1} & oldsymbol{1} & \dots & oldsymbol{p}_{1,N}' \ oldsymbol{p}_{2,1} & oldsymbol{p}_{2,2} & \dots & oldsymbol{p}_{2,k} & \dots & oldsymbol{p}_{2,N}' \ oldsymbol{1} & oldsymbol{1} & \dots & oldsymbol{1} \ oldsymbol{0} & oldsymbol{0} & oldsymbol{1} \ oldsymbol{1} & oldsymbol{1} & \dots & oldsymbol{1} \ oldsymbol{1} & oldsymbol{1} & oldsymbol{1} & oldsymbol{1} & oldsymbol{1} \ oldsymbol{1} & oldsymbol{1} & oldsymbol{1} & oldsymbol{1} \ oldsymbol{1} & oldsymbol{1} & oldsymbol{1} \ oldsymbol{1} & oldsymbol{1} & oldsymbol{1} \ oldsymbol{1} & oldsymbol{1} \ oldsymbol{1} & oldsymbol{1} \ oldsymbol{1} & oldsymbol{1} \ oldsymbol{1}$$

And the Expectation Step is concluded as we update the centroids from $\{\mu_i^{(0)}\}_{i \in [k]}$ to $\{\mu_i^{(1)}\}_{i \in [k]}$. The next step is to update the assignment $p'_{1,i}$ to $p_{1,i}^{(1)}$ for $i \in [N]$.

2. The Maximization Step.

The maximization step involves two sub-networks: Step 1: Copy the x below the 1s, yielding

$igrap_X$	$oldsymbol{X}_2$		$oldsymbol{x}_k$		X_N (
$\hat{\mu}_1^{(1)}$	$\hat{oldsymbol{\mu}}_2^{(1)}$		$\hat{oldsymbol{\mu}}_k^{(1)}$		0	
$p_{1,1}'$	$p_{1,2}^\prime$		$\boldsymbol{p}_{1,k}'$		$p_{1,N}^\prime$	
$p_{2,1}$	$oldsymbol{p}_{2,2}$		$oldsymbol{p}_{2,k}$	• • •	$oldsymbol{p}_{2,N}$	
1	1		1		1	;
$ x_{1,1} $	$oldsymbol{x}_{2,1}$		$oldsymbol{x}_{k,1}$		$x_{N,1}$	
		÷				
$ x_{1,k} $	$oldsymbol{x}_{2,k}$		$oldsymbol{x}_{k,k}$		$oldsymbol{x}_{N,k}$	
		0				

Step 2: Move $\{\hat{\mu}_i^{(1)}\}_{i\in[M]}$ to $\{x_{j,i}\}_{j\in[N]}$, yielding

$$egin{bmatrix} m{X}_1 & m{X}_2 & \ldots & m{x}_k & \ldots & m{X}_N \ \hat{m{\mu}}_1^{(1)} & \hat{m{\mu}}_2^{(1)} & \ldots & \hat{m{\mu}}_k^{(1)} & \ldots & m{0} \ m{p}_{1,1}' & m{p}_{1,2}' & \ldots & m{p}_{1,k}' & \ldots & m{p}_{1,N}' \ m{p}_{2,1} & m{p}_{2,2} & \ldots & m{p}_{2,k} & \ldots & m{p}_{2,N} \ 1 & 1 & \ldots & 1 & \ldots & 1 \ m{x}_{1,1} - \hat{m{\mu}}_1^{(1)} & m{x}_{2,1} - \hat{m{\mu}}_1^{(1)} & \ldots & m{x}_{k,1} - \hat{m{\mu}}_1^{(1)} & \ldots & m{x}_{N,1} - \hat{m{\mu}}_1^{(1)} \ & \vdots & & & & \\ m{x}_{1,k} - \hat{m{\mu}}_k^{(1)} & m{x}_{2,k} - \hat{m{\mu}}_k^{(1)} & \ldots & m{x}_{k,k} - \hat{m{\mu}}_k^{(1)} & \ldots & m{x}_{N,k} - \hat{m{\mu}}_k^{(1)} \ & & & & & \\ m{0} & & & & & & \end{bmatrix},$$

Step 3: One-by-one, compute the norm and obtain the following matrix

Step 4: And finally, we apply the Softmax and recover approximates to $\{\tilde{p}_{1,i}^{(2)}\}_{i\in[N]}$. Then we move it back to the original places belonging to $\{p'_{1,i}\}_{i\in[k]}$. Then we give the following construction for each step:

Step 1.

In step 1, we construct the following parameters

$$m{W}_1^{(5)} = egin{bmatrix} m{0}_{(3d+k+1) imes N} & \ I_d & m{0} \ m{0} & \ \end{bmatrix}, \quad m{W}_2^{(5)} = I_D.$$

And the Attention layer of the 6-th layer makes an identity mapping. Then we consider

$$m{W}_1^{(6)} = egin{bmatrix} m{0}_{(3d+k+1) imes N} & \ I_d & m{0} \ m{0} & \ \end{bmatrix}, \quad m{W}_2^{(5)} = -I_D$$

Similarly we define $\left\{ \boldsymbol{W}_{1}^{(i)}, \boldsymbol{W}_{2}^{(i)} \right\}_{i \in [7:6+2(k-1)]}$, and the task is achieved. Hence we show that

$$m{H}_{4+2k} = egin{bmatrix} m{X}_1 & m{X}_2 & \ldots & m{x}_k & \ldots & m{X}_N \ \hat{m{\mu}}_1^{(1)} & \hat{m{\mu}}_2^{(1)} & \hat{m{\mu}}_k^{(1)} & \ldots & m{\mu}_k^{(1)} & \ldots & m{0} \ m{p}_{1,1}' & m{p}_{1,2}' & \ldots & m{p}_{1,k}' & \ldots & m{p}_{1,N}' \ m{p}_{2,1} & m{p}_{2,2} & \ldots & m{p}_{2,k} & \ldots & m{p}_{2,N}' \ 1 & 1 & \cdots & 1 & \ddots & 1 \ m{x}_{1,1} & m{x}_{2,1} & \ldots & m{x}_{k,1} & \ldots & m{x}_{N,1}' \ & \vdots & & & \ m{x}_{1,k} & m{x}_{2,k} & \ldots & m{x}_{k,k} & \ldots & m{x}_{N,k} \ \end{bmatrix}.$$

Step 2.

To achieve step 2, we note that the following holds

where

$$\tilde{\boldsymbol{V}}^{(j)} = \begin{bmatrix} \boldsymbol{0}_{(3d+k+j)\times D} \\ 0_{d\times 1} & I_d & \boldsymbol{0} \\ & \boldsymbol{0} & \end{bmatrix}, \quad \tilde{\boldsymbol{G}} = \begin{bmatrix} 1 & \dots & 1 \\ & \boldsymbol{0} & \end{bmatrix}.$$

Hence, using lemma A.2 to show that there exists a set of parameter $\{V_i^{(5+2k)}, Q_i^{(5+2k)}, K_i^{(5+2k)}\}_{i \in [M]}$ given as follows for $i \in [M]$,

$$\boldsymbol{V}_{i}^{(5+2k)} = c_{i}\tilde{\boldsymbol{V}}, \quad \boldsymbol{Q}_{i}^{(5+2k)} = \begin{bmatrix} \boldsymbol{0}_{(2d+k)\times d} & I_{d} & \boldsymbol{0} \\ & \boldsymbol{0} \end{bmatrix}, \quad \boldsymbol{K}_{i}^{(5k+2)} = \begin{bmatrix} \boldsymbol{A}_{i} & \boldsymbol{0} \\ \boldsymbol{0} & \boldsymbol{0} \end{bmatrix} \times \begin{bmatrix} \boldsymbol{0}_{1\times(3d+k+1)} & 1 & \boldsymbol{0} \\ & \boldsymbol{0} \end{bmatrix}$$

And one can show that

$$\left\| \Delta \boldsymbol{H}_{1} - \sum_{i=1}^{M} \boldsymbol{V}_{i} \boldsymbol{H}^{(4+2k)} \text{SoftMax} \left(\boldsymbol{H}_{i}^{(2k+4),\top} \boldsymbol{Q}_{i}^{\top} \boldsymbol{K}_{i}^{(2k+4)} \boldsymbol{H}_{i}^{(4+2k)} \right) \right\|_{2} \leq \| \hat{\boldsymbol{\mu}}_{1}^{(1)} \|_{2} \sqrt{\frac{d}{M} \log(M)}.$$

Hence, we design accordingly the next (k-1)M heads $\left\{ V_i^{(2k+4)}, Q_i^{(2k+4)}, K_i^{(2k+4)} \right\}_{j \in [2:k]}$ similarly. We also let all the FC layer preserve their identity maps. The above construction implies that

$$\left\|\sum_{i=1}^{k} \Delta \boldsymbol{H}_{i} - \sum_{i=1}^{kM} \boldsymbol{V}_{i} \boldsymbol{H}^{(4+2k)} \operatorname{SoftMax}\left(\boldsymbol{H}_{i}^{(2k+4),\top} \boldsymbol{Q}_{i}^{\top} \boldsymbol{K}_{i}^{(2k+4)} \boldsymbol{H}_{i}\right)\right\|_{2} \leq \sqrt{k} \sup_{j \in [k]} \left\|\hat{\boldsymbol{\mu}}_{j}^{(1)}\right\|_{2} \sqrt{\frac{d \log(M)}{M}} + \frac{1}{2} \operatorname{SoftMax}\left(\boldsymbol{H}_{i}^{(2k+4),\top} \boldsymbol{Q}_{i}^{\top} \boldsymbol{K}_{i}^{(2k+4)} \boldsymbol{H}_{i}\right)\right\|_{2} \leq \sqrt{k} \sup_{j \in [k]} \left\|\hat{\boldsymbol{\mu}}_{j}^{(1)}\right\|_{2} \sqrt{\frac{d \log(M)}{M}} + \frac{1}{2} \operatorname{SoftMax}\left(\boldsymbol{H}_{i}^{(2k+4),\top} \boldsymbol{Q}_{i}^{\top} \boldsymbol{K}_{i}^{(2k+4)} \boldsymbol{H}_{i}\right)\right\|_{2} \leq \sqrt{k} \sup_{j \in [k]} \left\|\hat{\boldsymbol{\mu}}_{j}^{(1)}\right\|_{2} \sqrt{\frac{d \log(M)}{M}} + \frac{1}{2} \operatorname{SoftMax}\left(\boldsymbol{H}_{i}^{(2k+4),\top} \boldsymbol{Q}_{i}^{\top} \boldsymbol{K}_{i}^{(2k+4)} \boldsymbol{H}_{i}\right)\right\|_{2} \leq \sqrt{k} \operatorname{SoftMax}\left(\boldsymbol{H}_{i}^{(2k+4),\top} \boldsymbol{Q}_{i}^{\top} \boldsymbol{K}_{i}^{(2k+4)} \boldsymbol{H}_{i}\right)\right\|_{2} \leq \sqrt{k} \operatorname{SoftMax}\left(\boldsymbol{H}_{i}^{(2k+4),\top} \boldsymbol{Q}_{i}^{\top} \boldsymbol{K}_{i}^{(2k+4)} \boldsymbol{H}_{i}\right)$$

which alternatively implies that

$$egin{aligned} egin{aligned} egin{aligne} egin{aligned} egin{aligned} egin{aligned} egin$$

Step 3.

To achieve step 3, we first divide the heads into k-blocks where the j-th block achieves the task of approximating the norm function $\|\boldsymbol{x}_{1,j} - \hat{\boldsymbol{\mu}}_{j}^{(1)}\|_{2}$ taking $\boldsymbol{x}_{1,j} - \hat{\boldsymbol{\mu}}_{j}^{(1)}$ as input. We design the parameters for the first block as follows, as an example

$$\begin{split} \boldsymbol{V}_{i}^{(5+3k)} &= \begin{bmatrix} \boldsymbol{0}_{(k+3)d+k+1} & \mathbf{0}_{i}I_{d} & \mathbf{0} \\ \boldsymbol{0}_{d\times((k+3)d+k+1)} & c_{i}I_{d} & \mathbf{0} \end{bmatrix}, \quad \boldsymbol{Q}_{i}^{(5+3k)} = \begin{bmatrix} \boldsymbol{0}_{(2d+k)\times N} & \mathbf{0} \\ \mathbf{0}_{2d+k} & I_{d} & \mathbf{0} \\ \mathbf{0}_{0} & \mathbf{0} \end{bmatrix}, \\ \boldsymbol{K}_{i}^{(5+3k)} &= \begin{bmatrix} \boldsymbol{0}_{(3d+k+1)\times D} & \mathbf{0} \\ \mathbf{0}_{d\times(3d+k+1)} & \boldsymbol{A}_{i} & \mathbf{0} \\ \mathbf{0} & \mathbf{0} \end{bmatrix} \cdot \begin{bmatrix} \boldsymbol{0}_{(3d+k+1)\times D} & \mathbf{0} \\ \mathbf{0}_{d\times(3d+k+1)} & I_{d} & \mathbf{0} \\ \mathbf{0} & \mathbf{0} \end{bmatrix}. \end{split}$$

 $\{c_i, A_i\}_{i \in [M]}$ satisfies $\sup_{i \in [M]} ||A||_2 \leq C$, whose existence is guaranteed by lemma A.2. Moreover, it is not hard to show that one can utilize 2 FC layers to remove the vector part and the $\{p'_{1,i}\}_{i \in [N]}$ Under this design, our final output satisfies

$$\left\| \boldsymbol{H}_{6+3k} - \begin{bmatrix} \boldsymbol{X}_1 & \boldsymbol{X}_2 & \dots & \boldsymbol{x}_k & \dots & \boldsymbol{X}_N \\ \hat{\boldsymbol{\mu}}_1^{(1)} & \hat{\boldsymbol{\mu}}_2^{(1)} & \dots & \hat{\boldsymbol{\mu}}_k^{(1)} & \dots & \boldsymbol{0} \\ & \boldsymbol{0}_{k \times N} & & & \\ \boldsymbol{p}_{2,1} & \boldsymbol{p}_{2,2} & \dots & \boldsymbol{p}_{2,k} & \dots & \boldsymbol{p}_{2,N} \\ 1 & 1 & \dots & 1 & \dots & 1 \\ \|\boldsymbol{x}_{1,1} - \hat{\boldsymbol{\mu}}_1^{(1)}\|_2 & \|\boldsymbol{x}_{2,1} - \hat{\boldsymbol{\mu}}_1^{(1)}\|_2 & \dots & \|\boldsymbol{x}_{k,1} - \hat{\boldsymbol{\mu}}_1^{(1)}\|_2 & \dots & \|\boldsymbol{x}_{N,1} - \hat{\boldsymbol{\mu}}_1^{(1)}\|_2 \\ & \vdots & & & \\ \|\boldsymbol{x}_{1,k} - \hat{\boldsymbol{\mu}}_k^{(1)}\|_2 & \|\boldsymbol{x}_{2,k} - \hat{\boldsymbol{\mu}}_k^{(1)}\|_2 & \dots & \|\boldsymbol{x}_{k,k} - \hat{\boldsymbol{\mu}}_k^{(1)}\|_2 & \dots & \|\boldsymbol{x}_{N,k} - \hat{\boldsymbol{\mu}}_k^{(1)}\|_2 \\ & \boldsymbol{0} & \\ \lesssim \sqrt{k} \sup_{j \in [k]} \left\| \hat{\boldsymbol{\mu}}_j^{(1)} \right\|_2 \sqrt{\frac{\log(M)}{M}}. \end{aligned} \right\|$$

Step 4.

In step 4, we utilize the property of the Softmax function to approximate the hard max and replace the $p'_{1,1}$ with our new estimate $p_{1,k}^{(1)}$. We construct our layer weights by

$$\mathbf{V}^{(7+3k)} = \begin{bmatrix} \mathbf{0}_{(2d) \times N} \\ \mathbf{0}_{k \times (2d+k)} & I_k & \mathbf{0} \\ \mathbf{0} & \mathbf{0} \end{bmatrix}, \quad \mathbf{Q}^{(7+3k)} = \begin{bmatrix} \mathbf{0}_{(2d+k)} & \mathbf{0}_{(2d+k) \times k} & I_k & \mathbf{0} \\ \mathbf{0} & \mathbf{0} \end{bmatrix}, \\
 \mathbf{K}^{(7+3k)} = C \log N \begin{bmatrix} \mathbf{0}_{(3d+k+1) \times N} \\ \mathbf{0}_{k \times (2d)} & I_k & \mathbf{0} \\ \mathbf{0} & \mathbf{0} \end{bmatrix}.$$

Note that the result given by B.1 implies that

$$\left\| \operatorname{SoftMax} \left(\begin{bmatrix} \| \boldsymbol{x}_{1,1} - \hat{\boldsymbol{\mu}}_{1}^{(1)} \|_{2} & \dots & \| \boldsymbol{x}_{N,1} - \hat{\boldsymbol{\mu}}_{1}^{(1)} \|_{2} \\ & \ddots & \\ \| \boldsymbol{x}_{1,k} - \hat{\boldsymbol{\mu}}_{k}^{(1)} \|_{2} & \dots & \| \boldsymbol{x}_{N,k} - \hat{\boldsymbol{\mu}}_{k}^{(1)} \|_{2} \end{bmatrix} \right) - \begin{bmatrix} \boldsymbol{p}_{1,1}^{(1)} & \boldsymbol{p}_{1,2}^{(1)} & \dots & \boldsymbol{p}_{1,N}^{(1)} \end{bmatrix} \right\|_{2} \lesssim N \exp(-C \log N) = dN^{-C}.$$

Under this construction and let the FC layer retain the identity of the first 3d + k + 1 columns and remove the rest, our approximation results in lemma B.1 implies that

$$\left\| \boldsymbol{H}_{7+3k} - \begin{bmatrix} \boldsymbol{X}_1 & \boldsymbol{X}_2 & \dots & \boldsymbol{x}_k & \dots & \boldsymbol{X}_N \\ \hat{\boldsymbol{\mu}}_1^{(1)} & \hat{\boldsymbol{\mu}}_2^{(1)} & \dots & \hat{\boldsymbol{\mu}}_k^{(1)} & \dots & \boldsymbol{0} \\ \boldsymbol{p}_{1,1}^{(1)} & \boldsymbol{p}_{1,2}^{(1)} & \dots & \boldsymbol{p}_{1,k}^{(1)} & \dots & \boldsymbol{p}_{1,N}^{(1)} \\ \boldsymbol{p}_{2,1} & \boldsymbol{p}_{2,2} & \dots & \boldsymbol{p}_{2,k} & \dots & \boldsymbol{p}_{2,N} \\ 1 & 1 & \dots & 1 & \dots & 1 \\ & & \boldsymbol{0} & & & \end{bmatrix} \right\|_2 \lesssim dN^{-C} + \sqrt{k} \sup \| \hat{\boldsymbol{\mu}}_j^{(1)} \|_2 \sqrt{\frac{\log M}{M}} + C^d \sqrt{\frac{d^2 \log M}{M}}.$$

Hence, we construct in total of τ sets of subnetwork, and use the final layer to extract the set of output $\{p_{1,i}^{(\tau)}\}_{i \in [N]}$. By subadditivity of the L_2 norm we finalize our results by

$$\left| \text{Transformer+}(\boldsymbol{H}) - \begin{bmatrix} \boldsymbol{p}_{1,1}^{(1)} & \boldsymbol{p}_{1,2}^{(1)} & \dots & \boldsymbol{p}_{1,N}^{(1)} \end{bmatrix} \right\|_2 \lesssim \tau \left(dN^{-C} + \sqrt{k} \sup \| \hat{\boldsymbol{\mu}}_j^{(1)} \|_2 \sqrt{\frac{\log M}{M}} + C^d \sqrt{\frac{d^2 \log M}{M}} \right)$$

Lemma B.1 (Approximating the Hardmax Function by the Softmax Function). Consider a vector $\boldsymbol{x} \in \mathbb{R}^d$. Let $x^* = \max_{i \in [d]}$. Define $x^* = \max_{i \in [d]} x_i$, $\mathcal{N}_2 = \{i : x_i = x^*\}$, $\Delta = x^* - \max_{i \in \mathcal{N}_2} x_i$. Define the Hardmax function as $Hardmax(\boldsymbol{x}) = \begin{bmatrix} \frac{\mathbb{1}_{x_1 = \max_{i \in [d]} \{x_i\}}}{\sum_{i=1}^d \mathbb{1}_{x_i = \max_{i \in [d]} \{x_i\}}} & \cdots & \frac{\mathbb{1}_{x_d = \max_{i \in [d]} \{x_i\}}}{\sum_{i=1}^d \mathbb{1}_{x_i = \max_{i \in [d]} \{x_i\}}} \end{bmatrix}$, we subsequently show that $\left| SoftMax(\beta \boldsymbol{v}) - Hardmax(\boldsymbol{v}) \right| \leq \left((d - |\mathcal{N}_2|) + \frac{(d - |\mathcal{N}_2|)^2}{|\mathcal{N}_2|^3} \right)^{\frac{1}{2}} \exp(-\beta \Delta).$

Proof. We can show that the difference is given by

$$\begin{aligned} \operatorname{SoftMax}(\beta v) - \operatorname{Hardmax}(v) \Big\|_{2} &= \left(\sum_{i=1}^{d} \left(\frac{\mathbbm{1}_{x_{i} = \max_{i \in [d]} \{x_{i}\}}{\sum_{i=1}^{d} \mathbbm{1}_{x_{i} = \max_{i \in [d]} \{x_{i}\}}} - \frac{\exp(\beta x_{i})}{\sum_{i=1}^{d} \exp(\beta x_{i})}\right)^{2}\right)^{\frac{1}{2}} \\ &= \left(\sum_{i=1}^{d} \left(\frac{\mathbbm{1}_{x_{i} = \max_{i \in [d]} \{x_{i}\}}{\sum_{i=1}^{d} \mathbbm{1}_{x_{i} = \max_{i \in [d]} \{x_{i}\}}} - \frac{\exp(\beta(x_{i} - x^{*}))}{\sum_{i=1}^{d} \exp(\beta(x_{i} - x^{*}))}\right)\right)^{\frac{1}{2}} \\ &\leq \left(\sum_{i=1}^{d} \mathbbm{1}_{x_{i} \neq x^{*}} \exp\left(2\beta(x_{i} - x^{*})\right) + \mathbbm{1}_{x_{i} = x^{*}}\left(\frac{\exp\left(\beta(x_{i} - x^{*})\right)}{\sum_{i=1}^{d} \exp\left(\beta(x_{i} - x^{*})\right)} - \frac{1}{|\{i : x_{i} = x^{*}\}|}\right)^{2}\right)^{\frac{1}{2}} \\ &\leq \left(|\mathcal{N}_{1}|\exp(-2\beta\Delta) + |\mathcal{N}_{2}|\left(\frac{1}{|\mathcal{N}_{2}| + |\mathcal{N}_{1}|\exp(-\beta\Delta)} - \frac{1}{|\mathcal{N}_{2}|}\right)^{2}\right)^{\frac{1}{2}} \\ &\leq \left((d - |\mathcal{N}_{2}|)\exp(-2\beta\Delta) + \frac{(d - |\mathcal{N}_{2}|)^{2}\exp(-2\beta\Delta)}{|\mathcal{N}_{2}|(|\mathcal{N}_{2}| + (d - |\mathcal{N}_{2}|)\exp(-\beta\Delta))^{2}}\right)^{\frac{1}{2}} \\ &= \left((d - |\mathcal{N}_{2}|) + \frac{(d - |\mathcal{N}_{2}|)^{2}}{|\mathcal{N}_{2}|(|\mathcal{N}_{2}| + (d - |\mathcal{N}_{2}|)\exp(-\beta\Delta))^{2}}\right)^{\frac{1}{2}} \exp\left(-\beta\Delta\right) \\ &\leq \left((d - |\mathcal{N}_{2}|) + \frac{(d - |\mathcal{N}_{2}|)^{2}}{|\mathcal{N}_{2}|^{3}}\right)^{\frac{1}{2}}\exp(-\beta\Delta). \end{aligned}$$

B.3. Proof of Proposition 3.1

Before we start the proof, we first consider the event of $\mathcal{E} = \left\{ \left\| \mathbf{X}_{i}^{(j)} - \boldsymbol{\mu}_{\mathbf{z}_{i}}^{(j)} \right\|_{2} \leq \sigma \sqrt{d \log(nN/\delta)}, \forall i \in [N], j \in [n] \right\}$, it is not hard to check that by sub-Gaussian tail bound, $\mathbb{P}(E) \geq 1 - \delta$. Then, it is not hard to check that under E, $\|\mathbf{H}\|_{2} \leq \sigma \sqrt{d \log(nN/\delta)} \times N$. Then we obtain generalization bound under the event \mathcal{E} using the proof machine created by Bai et al. (2024) J.2 He et al. (2025) Proposition 1, where we note that the multi-layered Transformer satisfies the following conditions

- 1. The metric entropy of the operator norm ball satisfies $\log (\delta, \mathcal{B}_{\parallel,\parallel}, \parallel \mid \parallel) \leq CB_L B_M D^2 \log(1 + (B_{\theta} + B_X + k)/\delta).$
- 2. $L(TF_{\theta}(H), P_1(z)) \leq 2$ and is 2 sub-Gaussian.
- 3. The Lipschitz condition of the Transformer satisfies for $\theta_1, \theta_2 \in \Theta_{B_M, B_L}(B_{\theta})$,

$$L(TF_{\boldsymbol{\theta}_1}(\boldsymbol{H}), \boldsymbol{P}_1(\boldsymbol{z})) - L(TF_{\boldsymbol{\theta}_2}(\boldsymbol{H}), \boldsymbol{P}_1(\boldsymbol{z})) \leq CLB_{\boldsymbol{\theta}}^{4L}B_X^{3L} \| \boldsymbol{\theta}_1 - \boldsymbol{\theta}_2 \|.$$

where the last condition is obtained through noticing that the Softmax function is Lipschitz with constant C. And for bounded input H the Lipschitz constant of the non-activated Attention layer is proportional to B^3_{θ} . Then, using proposition A.4 in Bai et al. (2024), one can show by union bound that with probability at least $1 - \delta$,

$$L\left(A_{\hat{\boldsymbol{\theta}}}(\boldsymbol{H}), \boldsymbol{P}_{1}(\boldsymbol{z})\right) \leq \inf_{\boldsymbol{\theta}\in\Theta_{B_{M},B_{L}}(B_{\boldsymbol{\theta}})} \mathbb{E}[L\left(A_{\hat{\boldsymbol{\theta}}}(\boldsymbol{H}), \boldsymbol{P}_{1}(\boldsymbol{z})\right) |\mathcal{E}] + C\sqrt{\frac{D^{2}B_{L}B_{M}\log(NB_{\boldsymbol{\theta}}B_{M}D\sigma \cdot \sup_{i\in[N],j\in[n]}\|\boldsymbol{\mu}_{i}^{(j)}\|_{2}) + \log(2/\delta)}{n}}$$

where $A \in \{TF, TF^+\}$.

B.4. Proof of Theorem 3.3

We prove the above theorem through upper bounding the term $\inf_{\theta \in \Theta_{B_M, B_L(B_{\theta})}} \mathbb{E}[L(A_{\hat{\theta}}(H), P_1(z)) | \mathcal{A} \cap \mathcal{E}]$ where \mathcal{A} appears to be the event in Corollary 3 in Lu & Zhou (2016). Note that $\mathbb{P}(\mathcal{A}) \geq 1 - 5n^{-1} - 2\exp(-\Delta/\sigma)$. Since the proof

for the Transformer and the Transformer+ shares similar idea, we only prove the case with the Transformer model where $\tilde{\theta}$ is the construction. Denote the estimate given by Lloyd's algorithm as $\hat{P}(z) := \begin{bmatrix} p_{1,1}^{(\tau)} & \dots & p_{1,N}^{(\tau)} \end{bmatrix}$ Then we can see that

$$\inf_{\boldsymbol{\theta}\in\Theta_{B_{M},B_{L}}(B_{\boldsymbol{\theta}})} \mathbb{E}[L(TF_{\hat{\boldsymbol{\theta}}}(\boldsymbol{H}),\boldsymbol{P}_{1}(\boldsymbol{z}))|\mathcal{A}\cap\mathcal{E}] \leq \mathbb{E}\left[L(TF_{\tilde{\boldsymbol{\theta}}}(\boldsymbol{H}),\boldsymbol{P}_{1}(\boldsymbol{z}))|\mathcal{A}\cap\mathcal{E}\right]$$
$$\leq \mathbb{E}\left[L(\hat{\boldsymbol{P}}_{1}(\boldsymbol{z}),\boldsymbol{P}_{1}(\boldsymbol{z}))|\mathcal{A}\cap\mathcal{E}\right] + \frac{1}{N}\|\hat{\boldsymbol{P}}_{1} - TF_{\tilde{\boldsymbol{\theta}}}(\boldsymbol{H})\|_{1}.$$

Note that the first term can be controlled by Yu et al. (2015) Corollary 3.1 as follows

$$\begin{split} \mathbb{E}\left[L(\hat{\boldsymbol{P}}_{1}(\boldsymbol{z}),\boldsymbol{P}_{1}(\boldsymbol{z}))\Big|\mathcal{E}\right] &\leq 2\mathbb{E}\left[L(\hat{\boldsymbol{P}}_{1}(\boldsymbol{z}),\boldsymbol{P}_{1}(\boldsymbol{z}))|\mathcal{A}\cap\mathcal{E}\right]\mathbb{P}(\mathcal{A}) + 2\mathbb{P}(\mathcal{A}) \\ &\leq \exp\left(-(1+o(1))\frac{\Delta^{2}}{8\sigma^{2}}\right) + \frac{10}{n} + 2\exp\left(-\frac{\Delta}{\sigma}\right) \end{split}$$

For the second term, we note that

$$\frac{1}{N} \left\| \hat{\boldsymbol{P}}_{1}(\boldsymbol{z}) - TF_{\tilde{\boldsymbol{\theta}}}(\boldsymbol{H}) \right\|_{1} \leq \frac{1}{\sqrt{N}} \left\| \hat{\boldsymbol{P}}_{1}(\boldsymbol{z}) - TF_{\tilde{\boldsymbol{\theta}}}(\boldsymbol{H}) \right\|_{2}.$$

Then we can show that, with probability at least $1 - \delta - 5n^{-1} - 2\exp(-\Delta/\sigma)$, given $\tau \ge 4\log n + 1$, $B_L = k\tau + C\tau$, $B_M \ge M$, D = Cdk,

$$\begin{split} L\left(TF_{\hat{\boldsymbol{\theta}}}(\boldsymbol{H}), \boldsymbol{P}_{1}(\boldsymbol{z})\right) &\lesssim \exp\left(-(1+o(1))\frac{\Delta^{2}}{8\sigma^{2}}\right) \\ &+ \sqrt{\frac{D^{2}B_{L}B_{M}\log(NB_{\boldsymbol{\theta}}B_{M}D\sigma \cdot \sup_{i\in[N], j\in[n]}\|\boldsymbol{\mu}_{i}^{(j)}\|_{2}) + \log(2/\delta)}{n}} \\ &+ \tau\sqrt{N}C^{d}\left(\sqrt{k}\sup_{j\in[k], \ell\in[\tau]}\|\boldsymbol{\hat{\mu}}_{j}^{(1)}\|_{2}\sqrt{\frac{\log M}{M}} + N^{-1}\right). \end{split}$$

We further let $M = n^{\frac{1}{4}}$, $L \asymp k \log n$ and obtain that with probability at least $1 - \delta - 5n^{-1} - 2\exp(-\Delta/\sigma)$.

$$L(TF_{\hat{\boldsymbol{\theta}}}(\boldsymbol{H}), \boldsymbol{P}_{1}(\boldsymbol{z})) \lesssim \exp\left(-(1+o(1))\frac{\Delta^{2}}{8\sigma^{2}}\right) + \sqrt{kn^{-1/4}}C^{d}\sqrt{Polylog(n) + \log(2/\delta)} + N^{-3/2}$$

And similarly we have with probability at least $1 - \delta - 5n^{-1} - 2\exp(-\Delta/\sigma)$

$$L(TF_{\hat{\theta}}^{+}(\boldsymbol{H}), \boldsymbol{P}_{1}(\boldsymbol{z})) \lesssim \exp\left(-(1+o(1))\frac{\Delta^{2}}{8\sigma^{2}}\right) + d\sqrt{k}n^{-1/4}C^{d}\sqrt{Polylog(n) + \log(2/\delta)} + N^{-100.5}.$$

C. Additional Experiments



Figure 4. Comparison of Concatenated Attention and Averaged Attention on Synthetic Dataset. *Top: Performance Comparision on Minimum Distance Task. Bottom: Performance Comparision on Number of Data Task.* We observe similar trend of performance between concatenated multihead attention a averaged multihead attention across three tasks, two evaluation metrics, and the converged loss. All the experiment settings are the same as the experiments in Section 4.



Figure 5. Comparison of Concatenated Attention and Averaged Attention on Synthetic Dataset. *Top: Performance Comparision on Number of Classes Task. Bottom: Performance Comparision on Inbalance Ratio Task.* Again, we observe a similar performance trend between concatenated multihead attention and averaged multihead attention across both tasks. All experimental settings remain the same as those in Section 4.