Economics of Sourcing Human Data

Sebastin Santy¹ Prasanta Bhattacharya² Manoel Horta Ribeiro³ Kelsey Allen⁴ Sewoong Oh¹

¹University of Washington ²Institute of High Performance Computing (IHPC), A*STAR ³Princeton University ⁴University of British Columbia

Abstract

Progress in AI has relied on human-generated data, from annotator marketplaces to the wider Internet. However, the widespread use of large language models now threatens the quality and integrity of human-generated data on these very platforms. We argue that this issue goes beyond the immediate challenge of filtering AIgenerated content—it reveals deeper flaws in how data collection systems are designed. Existing systems often prioritize speed, scale, and efficiency at the cost of intrinsic human motivation, leading to declining engagement and data quality. We propose that rethinking data collection systems to align with contributors' intrinsic motivations—rather than relying solely on external incentives—can help sustain high-quality data sourcing at scale while maintaining contributor trust and long-term participation.

1. Human Data in Crisis

Artificial Intelligence relies heavily on human-generated data to develop ever more capable models and systems that can emulate human-like intelligent behavior. The currently used sources of human data include: (1) human annotations, from data collection platforms (e.g., Amazon MTurk) and (2) raw data, from the Internet (e.g., Wikipedia, social media platforms). Our understanding of how to effectively use these two data sources has been a driving force behind the two most prominent eras of artificial intelligence: the **Deep Learning era** which began with AlexNet [Krizhevsky et al. 2012] in 2012 and facilitated by ImageNet [Deng et al. 2009] collected at scale through MTurk, and the **Pre-trained Language Models era** ushered in by BERT [Devlin et al. 2018] in 2018 and enabled by the availability of large-scale Internet data.

However, the emergence of the third **Generative Large Language Chat models era**, marked by ChatGPT in 2022 [OpenAI 2023], has made human-like language generation ubiquitous and accessible to the general public, disrupting the very mechanisms of data sourcing that have historically enabled AI development. The indiscriminate usage of large language models (LLMs) impacts the previous two key sources of human-produced data: participants in existing data collection systems are turning to LLMs to expedite their tasks [Veselovsky et al. 2023b,a], and the Internet is being flooded with LLM-generated content [Brooks et al. 2024]. This makes it increasingly challenging to obtain and discern authentic human-generated data, raising concerns about a looming shortage of human data needed for continued AI progress. To compensate, machine learning has further leaned into synthetic data—either to mimic human annotations [Dubois et al. 2024] or emulate human behavior [Argyle et al. 2023; Park et al. 2023, 2022]— albeit not yet at the highest quality [Geng et al. 2024] and facing other challenges, such as model collapse [Shumailov et al. 2024; Taori and Hashimoto 2023], keeping the ember of human-generated data still alive [Ashok and May 2024].

We argue that these flaws have always existed in data collection platforms but have been recently amplified by LLMs to the point where their very existence is being called into question [Pieces 2025]. Specifically, at the heart of this problem lies the issue of human incentives and motivations for contributing data—one that cannot be solved by simply increasing external rewards like pay but requires careful attention to intrinsic motivations that drive people to engage willingly and actively on platforms, which in turn leads to better-quality data. Designing new data collection systems necessitates a critical examination of the flaws in existing ones.

In this paper, we analyze the current data requirements in machine learning and how existing data collection systems attempt to meet them. We open up the black box of data collection—complex sociotechnical systems shaped by human behaviors, idiosyncrasies, and technical constraints—drawing from popular theories and experiments in psychology, sociology, and economics. In doing so, we examine the quantity-quality tradeoff and argue that, while this tradeoff may not be entirely eliminable, the overall quality and quantity of data can still be improved by identifying and removing factors that undermine intrinsic human motivations. Given that data collection systems operate within broader economic and social structures, we also complement academic research with real-world discourse and case studies of different data collection strategies. Finally, we explore novel paradigms, including games, that offer promising directions for the future of human data sourcing.

2. Characterizing Human Data Needs

Progress in machine learning depends on the availability of data at a sufficient scale to inductively learn patterns from it [Hoffmann et al. 2022; Kaplan et al. 2020]. This need for data has grown exponentially as learning algorithms have evolved from statistical to deep learning and pre-trained language models. The *quantity* of data has uncontestedly been the key consideration for the field [Sutton 2019], with any data source that adds several orders of magnitude to the size of existing datasets, such as data from the Internet, being considered indispensable. A general trend in machine learning regarding data sourcing, especially after the advent of pre-training with BERT [Devlin et al. 2018], has been to leverage sources of large data wherever they can be found, such as BookCorpus [Zhu et al.

[†]Institute of High Performance Computing (IHPC), Agency for Science, Technology and Research (A*STAR), 1 Fusionopolis Way, #16-16 Connexis, Singapore 138632, Republic of Singapore.

Corresponding author: ssanty@cs.washington.edu.

2015], Wikipedia [Raffel et al. 2020], Reddit [Gokaslan and Cohen 2019], and CommonCrawl [Common Crawl 2021].

Recently, however, as datasets have grown larger, the importance of *quality* has become more apparent [Lee et al. 2021; Nguyen et al. 2022; Zhou et al. 2024]. While learning algorithms have improved in extracting signal from noise, they still have limits when faced with excessive noise or irrelevant data [e.g., DataComp-LM discards 99% of data and Text-Image DataComp filters out 70%; Gadre et al. 2024; Li et al. 2024]. Data quality has long been assumed to matter, but its significance has become clearer than ever as models trained on external proprietary datasets consistently outperform others on benchmarks and in real-world applications [Brown et al. 2020]. This outperformance—often attributed to access to "highquality" proprietary datasets, such as paywalled content or licensed secondary sources [Bommasani et al. 2021]—has pushed the data quality discourse to the forefront and is now a high priority in machine learning.

Human Data Sourcing Desiderata

(1) High Quality

Collecting high-quality data with a strong signal-tonoise ratio for training ML models.

(2) High Quantity

Collecting data large enough to satisfy the exponentially increasing complexity of tasks.

While both high quality and high quantity are critical for data sourcing, they often come at the expense of each other—improving one typically leads to a decline in the other. However, this trade-off is not an inherent property of data itself but rather a consequence of system design choices. One way to conceptualize this trade-off is as resembling a Pareto frontier, as illustrated in Figure 1.

This trade-off explains why data collection systems struggle to balance quality and quantity. Platforms prioritizing quality, like freelance job platforms (e.g., UpWork), tend to be slower with lower output, while high-throughput systems, like rapid crowdwork platforms (e.g., MTurk), scale efficiently but often sacrifice consistency and quality [Douglas et al. 2023]. While this quantity-quality tradeoff may never be fully eliminated for any designed data collection system, it is not a fixed constraint—rather than eliminating the trade-off, the key is to expand the frontier by addressing structural inefficiencies in incentive design, annotation methods, and human oversight.

The dynamics of the quantity-quality trade-off are shaped by multiple interacting and, often, latent factors. Untangling these factors requires opening up current data collection systems and examining their trade-offs through the lens of human behavior, organizational processes, and technical constraints. At a system level, quality depends on balancing intrinsic motivation with external incentives,




Figure 1: Illustration of the quantity-quality trade-off in data collection systems. Platforms like MTurk, Prolific, and Up-Work optimize for either scale or quality but struggle to achieve both simultaneously. In contrast, data from sources not explicitly designed for data collection—such as Wikipedia and Reddit—operate outside this trade-off, hinting at potential alternative paradigms.

while quantity is largely driven by process efficiency, often through task fragmentation and parallelization. However, excessive fragmentation can erode intrinsic motivation, leading to long-term declines in quality. This self-reinforcing cycle lies at the heart of the quantity-quality trade-off in data collection system design.

3. Position vs. Current Stance

Position: Sustaining human-generated data for ML requires shifting focus toward intrinsic human motivations.

Majoritarian Stance: Data quality is a major consideration in machine learning, and many researchers and companies are actively exploring how to best collect high-quality human-produced data. Researchers recognize that incentives influence the level of effort contributed, and as a result, they often rely exclusively on financial incentives to encourage greater effort in data production. While incentives are important, we contend that solely relying on financial rewards—counter to intuition—risks backfiring by reducing the quality of the data collected. Instead, ML researchers should prioritize enhancing the intrinsic motivation of human participants, using external incentives sparingly as supportive nudges rather than primary drivers.

4. Understanding Data Quality

While quantity is easily measurable and increasingly attainable through new data-sourcing methods, quality has become ever more elusive. As data availability has surged, the question of what constitutes "high-quality" data is increasingly debated in machine learning. The challenge then is to understand the existing notions of data quality and explore ways to make it more certain, before dissecting data collection systems.

Prior Definitions. Defining "data quality" has long been a challenge in machine learning, as it lacks a universal, quantifiable standard. While it is widely acknowledged that human-generated data varies in quality (e.g., curated datasets from specific websites being more reliable than scraped content), there is no single, absolute definition for what makes data "high-quality". Attempts to define quality span both subjective and objective perspectives. Subjectively, quality is often linked to trustworthiness—Wikipedia, for instance, is generally regarded as more reliable than personal blogs [Albalak et al. 2024; Soldaini et al. 2024]. Objectively, quality has been measured using statistical metrics (e.g., readability) or modeled metrics, such as GPT-3 Quality Filters [Gururangan et al. 2022] and Data-Comp's curated datasets [Li et al. 2024], which define quality in the context of their downstream use.

Naturalness as the Basis of Data Quality. Without clarity on data's intended use, defining quality becomes challenging. We contend that one of the most intuitive ways to conceptualize quality—without presupposing a specific application—is by anchoring it in *naturalness*: how people behave in routine activities, online or offline, in an authentic manner. Unlike other definitions that rely on the perceived reliability of the source or application-specific criteria, naturalness provides an observable and generalizable signal for what constitutes high-quality data. This pattern is evident in organic data sources, where humans naturally generate valuable data through meaningful tasks, such as editing Wikipedia, participating in Reddit discussions, or sharing artwork and photos on platforms like Flickr. In these settings, data is generated naturally, often without direct external incentives, making it more representative of authentic human behavior.

Is There a Case for Naturalness in AI Training? Naturalness has already been central to pretraining, where large-scale internet data—capturing naturally occurring human behavior—has been crucial to the success of LLMs. But its importance extends beyond achieving generalization. Even in supervised fine-tuning, where data is tailored for task-specific applications, naturalness matters, as collected data should ideally reflect real task engagement rather than behavior shaped by artificial constraints or incentives.

Interestingly, this divide between pretraining and fine-tuning mirrors a broader debate in AI. Artificial Intelligence (AI)—as envisioned by John McCarthy [McCarthy 1987]—aims to achieve human-like general intelligence and, therefore, benefits from diverse, free-flowing human interactions, much like those found in pretraining data. In contrast, Intelligence Augmentation (IA)—as suggested by Douglas Engelbart [Engelbart 1962]—prioritizes enhancing human intelligence through specialized tools, requiring goal-oriented human interactions towards performing a task, similar to fine-tuning data. In both cases, naturalness remains key but plays distinct roles: capturing free-flowing or goal-oriented human interactions, free from artificial constraints or incentives.

To that end, the use of LLMs in data collection is not inherently bad—what matters is *how* they are used. The real risk to naturalness

comes from indiscriminate, careless reliance on AI as a shortcut, rather than as a tool for balancing meaningful engagement and productivity. Instead of aggressively policing AI use, the focus should be on designing environments where contributors engage with tasks in ways that make shortcuts feel unnecessary—just as one wouldn't feel compelled to take shortcuts in a personally meaningful hobby. For example, a survey respondent outsourcing an entire essay writing task to AI without any personal input demonstrates an unwillingness to engage meaningfully with the task—this is the kind of AI use that undermines data quality.

5. Human Factors in Quality– Motivation & Incentives


Data collection platforms used in machine learning, such as MTurk, Prolific, UpWork, and ScaleAI, are designed in ways that include compensation structures, that directly influence both effort and data quality. While rapid crowdsourcing platforms (e.g., MTurk) favor low-effort and low-pay tasks that can scale easily, the quality of task output remains unreliable. In contrast, freelance job platforms tend to favor high-effort and higher-pay gigs which require more deliberate and engaged participation, often leading to higher quality outputs.

This difference aligns with a straightforward intuition—higher pay leads to greater effort and better-quality contributions [e.g., Ho et al. 2015; Laux et al. 2024; Mason and Watts 2009; Shah and Zhou 2016]. This assumption drives much of the current incentive-based data collection paradigm, where the goal is to use external compensation as a lever to elicit higher-quality data, when required. However, while external rewards can drive greater effort, evidence suggests that they are not always the primary determinant of high-quality engagement.

For instance, some of the highest-quality human contributions come from platforms where users are not financially compensated at all, such as Wikipedia, Reddit, and open-source communities. Here, participants contribute not because of pay, but because they find the activity meaningful, socially rewarding, or aligned with personal interests [Forte and Bruckman 2005; Lampe et al. 2010]. These platforms challenge the idea that quality data generation must always rely on financial incentives, illustrating that intrinsic motivations can sustain long-term engagement without depending on financial rewards as the primary driver.

While many assume that external incentives and intrinsic motivation are correlated, research shows that their relationship is far more complex.

Overjustification Effect [Lepper et al. 1973] explains how external rewards can diminish intrinsic motivation and affect task performance. In a classic experiment, preschool children who already enjoyed drawing were divided into three groups: (1) those who were promised and received a reward, (2) those who received an unexpected reward, and (3) those who received no reward. This experiment revealed two notable outcomes: first, children in the expected-reward group spent significantly less time drawing voluntarily after the reward was removed, compared to the other groups.



Internally Motivated

Second, the drawings from the no-reward and unexpected-reward groups were rated as slightly higher in quality than those from the expected-reward group. This suggests that when an activity initially driven by intrinsic motivation is externally incentivized, the removal of rewards can lead to a decline in voluntary participation, and rewards may also subtly shift focus from quality to mere completion of the task.

So why do external incentives sometimes backfire? Two key psychological theories help explain why the Overjustification Effect-how extrinsic rewards can sometimes diminish intrinsic motivation-occurs:

- Self-Perception Theory (SPT) [Bem 1972] suggests that individuals infer their own attitudes and motivations by observing their past behaviors. When external rewards are introduced, people may start attributing their participation to the incentive rather than to their original or intrinsic interest. Over time, this shift in self-perception can make them less likely to continue the behavior once the reward is removed.
- Self-Determination Theory (SDT) [Deci 1971] offers a broader framework by focusing on autonomy, competence, and relatedness as key psychological needs for intrinsic motivation. When a task is externally controlled through incentives, individuals may feel a loss of autonomy, making the activity feel like an obligation rather than a choice. This helps explain why highly controlled environments often struggle to sustain long-term engagement.

Together, SPT and SDT highlight why financial incentives alone are not a sustainable solution for maintaining high-quality, long-term engagement.

If intrinsic motivation is key to sustaining high-quality, longterm contributions, then what role do external incentives play? While excessive reliance on extrinsic rewards can be detrimental, carefully designed incentives can help initiate engagement in behaviors that might otherwise remain dormant. For example, small, well-calibrated incentives can serve as interventions, bringing attention to valuable behaviors without overwhelming intrinsic motivation [Deci 1971]. Even in systems designed to favor intrinsically motivated behavior-such as laissez-faire environments [Hayek and Caldwell 2014], where individuals are free to act and bear the consequences of their choices-subtle incentive mechanisms can still be useful to align individual and collective goals, as with nudging [Leonard 2008]. Overpresence of incentives has generally led to unintended consequences-either they are optimized to the point of losing effectiveness [Goodhart's Law; Goodhart

and Goodhart 1984], or, worse, they introduce undesirable behaviors counterproductive to desired goals [Perverse Incentives; Kerr 1975][Cobra Effect; Siebert 2001].

So, how do these social theories play out in real-world data sources? Returning to the two sources of data-data collection systems like MTurk vs. naturally occurring data sources (communitybased platforms) like Wikipedia-the discussed social theories provide valuable insights into their differing approaches to engagement. Data collection systems, being intentionally designed, are structured around external incentives, with financial rewards and intrinsic motivation naturally coexisting at first. However, over time, a crowding-out effect takes hold: as intrinsic motivation erodes, platforms and data collectors continually increase external incentives and tighten control to sustain participation and quality, creating a vicious cycle where contributors optimize for efficiency rather than genuine engagement. This often leads to over-reliance on shortcuts, such as automating survey responses with AI tools, at the expense of quality.

In contrast, community-based platforms, like Wikipedia or Reddit, primarily rely on intrinsic motivation, with minimal external incentives such as contributor badges, reputation systems, and recognition. These platforms sustain engagement over the long term by creating a sense of social belonging, often intertwined with competence and autonomy, demonstrating that high-quality contributions can be sustained without heavy reliance on financial incentives.


This contrast underscores a crucial insight: designing sustainable data collection systems is not just about offering better incentives-it requires structuring environments that actively sustain and enhance intrinsic motivation.

6. Human Factors in Quantity-**Efficiency through Fragmentation**

Data collection systems differ not only in how they compensate contributors but also in how they structure tasks for scalability. At one end, rapid crowdwork platforms fragment tasks into micro-tasks (e.g., HITs on MTurk) that take seconds to complete, optimizing for speed and mass throughput [Malsburg 2024]. Platforms like Prolific handle slightly larger but still modular tasks, spanning minutes to hours [Prolific 2024]. On the other end, freelance job platforms (e.g., UpWork) structure work as full projects, lasting days or weeks and offering greater autonomy and depth of engagement [at Home Smart 2024; Upwork 2024a,b].

Fragmentation into repeatable units that can be completed in a consistent and orderly manner allows tasks to be parallelized across multiple workers, replacing the traditionally serial process of creation. Many innovations and processes begin as creative, effortful tasks-akin to System 2 processes, requiring deliberate, conscious effort [Kahneman and Tversky 2013]. However, to scale, they are often refined into a System 1 process, where execution becomes fast, automated, and intuitive. This transformation-breaking down complex, uncertain tasks into simpler, repeatable steps-underpins mass production systems.

Crucially, this shift from System 2 to System 1 is not just a natural evolution but is actively accelerated by task fragmentation. When work is divided into modular, repetitive tasks, the process of routinization happens more quickly. A useful analogy here is **Fordism** [Hounshell 1984], which introduced the assembly line, a mechanized, repetitive setup where products are built step by step. This structured fragmentation enables processes to be repeated at scale, maximizing efficiency and throughput.



However, as tasks become increasingly repetitive and fragmented, they sacrifice the creativity and problem-solving scope that contribute to meaningful engagement. Over time, workers become disconnected from the broader purpose of their efforts [Theory of Alienation; Marx 2016], shifting their motivation from seeking fulfillment to merely achieving survival goals – a regression in the hierarchy of needs [Maslow 1943]. For employers/collectors, this shift manifests as a decline in quality, as contributors disengage from the task itself. Unlike physical labor, which has built-in quality checks (e.g., material standards, product inspections), knowledge-based tasks lack robust safeguards. In data annotation, for example, there is often no immediate way to verify whether a task was completed thoughtfully or rushed [Klie et al. 2024a,b]. As a result, quality can quietly degrade, with errors compounding over time—often going unnoticed until the system has deteriorated beyond repair.

So, how does task fragmentation impact real-world data sourcing? Micro-tasking on platforms like MTurk was once hailed as a transformative shift in computer science, enabling large-scale user studies [Bernstein et al. 2011; Bohannon 2011; Kittur et al. 2013] and efficient data collection for machine learning [Deng et al. 2009]. However, over time, research has raised concerns about the reliance on "piece rate" or pay-per-task systems, favoring "quota" systems instead [Ikeda and Bernstein 2016; Mason and Watts 2009], which alludes to a reduction in task quality when micro-tasking is pushed too far.

Micro-tasking doesn't just impact data quality—it also affects the workers behind it. Beyond quality concerns, it has drawn criticism for its effect on worker well-being. Works such as Ghost Work [Gray and Suri 2019] and Anatomy of AI [Crawford and Joler 2018] have illustrated the often invisible and exploitative nature of these atomized tasks. The non-physical nature of knowledge labor further exacerbates this issue, making its value difficult to quantify [Martin et al. 2016]. This issue is taken to the extreme when microtasks are outsourced to developing countries with favorable exchange

rates [Dicken 2007] to cut costs—and thus, incentives—even further [Cheng 2023; Perrigo 2023], often trapping workers in exploitative, sweatshop-like conditions [Hao 2022; Williams et al. 2022].

Then, what happens when tasks become so repetitive and unfulfilling that workers disengage from them entirely? As discussed earlier, over time, many human-driven processes shift from System 2 (deliberate & effortful) to System 1 (intuitive & fast). As tasks become more structured and predictable, they become prime targets for automation. In physical labor, this transition has been gradual—machines take over repetitive, routine tasks, while humans focus on creative and uncertain work [Brynjolfsson and McAfee 2014].

A similar shift is occurring in knowledge-based work, where highquality LLMs give workers the opportunity to offload mundane tasks—such as grammar corrections, spell-checking, and phrasing refinements—to AI. When used judiciously, this assistance promotes meaningful engagement and enhances productivity without compromising data quality. However, the problem arises when workers become over-reliant on LLMs, using them indiscriminately to complete entire tasks without oversight [Veselovsky et al. 2023b,a]. Since knowledge-based tasks often lack clear-cut quality standards, it becomes harder to detect when quality has deteriorated, making it easier for such opportunistic behavior to go unchecked.

As a result, the transition to automation in data sourcing has been rather chaotic. While repetitive physical labor was gradually offloaded to machines in structured ways, knowledge work faces conflicting views—some advocate for fully replacing human contributors [e.g., Dubois et al. 2024], while others for eliminating LLM usage entirely [e.g., Thorp 2023]. However, fully relying on synthetic data risks model feedback loops and collapse [Shumailov et al. 2024; Taori and Hashimoto 2023], while a complete ban slows human productivity and sacrifices efficiency [Kreitmeir and Raschky 2023; Liao et al. 2024]. The most effective approach lies somewhere in between—where AI serves as a tool that productively and progressively supports human effort rather than a crutch for task completion [e.g., Ashok and May 2024; Qian et al. 2024].

In this landscape, intrinsic motivation becomes even more crucial. Workers must make thoughtful decisions about how to incorporate LLMs in ways that enhance rather than replace meaningful engagement. Designing a sustainable data collection system, therefore, is not just about limiting LLM use for workers or maximizing automation with synthetic data—it's about creating an environment where contributors remain actively engaged with the task, rather than optimizing for speed at the cost of quality.


7. Elevating the Quality-Quantity Trade-off: Rethinking Control

Data collection systems have long operated under the assumption that control at the task level—through explicit instructions, incentive structures, and quality enforcement mechanisms—is necessary to ensure both high-quality and high-quantity data. However, as we have discussed, these very mechanisms often introduce unintended side effects. External incentives, while effective in driving participation, tend to crowd out intrinsic motivations over time, leading to disengagement and lower-quality contributions. Similarly, excessive task fragmentation, though useful for efficiency and scalability, can erode a sense of purpose and hence leads contributors to disengage from the task itself—resulting in an over-reliance on shortcuts, manifesting in careless task completion and non-judicious use of LLMs.

In contrast, data that we obtain from systems not intentionally designed for data collection—such as Wikipedia, Reddit, and opensource projects—demonstrate an alternative paradigm. These platforms do not enforce control at the task level but instead create environments where intrinsically motivated contributors engage meaningfully. Crucially, this lack of task-level control removes two major pitfalls seen in structured data collection systems: it prevents (a) the crowding-out effect, where external incentives replace intrinsic motivation over time, and (b) excessive fragmentation, ensuring that contributors remain connected to their purpose of participation. Taking inspiration, ceding control at task level could be the key to pushing the pareto-frontier forward.

Ceding Control at the Task Level. Rather than controlling individual (micro) tasks, data collection systems can benefit from structuring conditions that naturally guide contributor engagement. Moving from direct task management to a broader, environmentdriven approach discourages individuals from attributing their participation to external rewards, helping preserve intrinsic motivation [Bem 1972].

However, this shift presents a new challenge: relinquishing finegrained control over tasks means that collectors must instead focus on shaping engagement at a more systemic level. Coarse-grained control—where engagement is influenced through platform design, incentives, and structural conditions—takes longer to align with desired outcomes and demands greater up-front effort. But once in place, it can lead to more sustainable data collection, enabling both higher-quality and higher-quantity contributions, as seen in rare but influential examples.



Deployed Robots are a prime example of achieving this delicate balance. For example, robotic vacuum cleaners (e.g., Roomba) provide utility to users, by cleaning their homes, while simultaneously collecting spatial and navigation data that improves future performance [Astor 2017]. Users engage with the system for its primary function, yet their interactions naturally generate high-quality data

that feeds back into the AI's development [Brynjolfsson and McAfee 2014]. This data collection approach also scales effectively, as data is gathered continuously and passively as a result of users' routine behaviors, without requiring any additional effort towards data contribution. This model extends to more complex, high-stakes deployments, such as electric vehicles equipped with driver-assist and self-driving features. As an example, consider how Tesla uses real-world driving data from its fleet to refine its self-driving AI algorithms, which ultimately benefit car owners by improving the technology [Karpathy 2021; Tesla 2021] and can drive future innovation for the company (e.g., driverless Robotaxi). Similarly, Waymo operates self-driving taxis in real-world environments and has gathered large-scale data that has proven valuable for advancing computer vision research [Sun et al. 2020].

However, replicating such large-scale, product-driven data collection systems is exceptionally difficult. They demand massive hardware infrastructure, well-articulated and trusted benefits for both users and companies, and real-world applications with extensive safeguards and privacy protections. For entities whose primary goal is simply to collect human-generated data, establishing such ecosystems solely for this purpose is neither feasible nor sustainable.

More importantly, these symbiotic relationships rely on a delicate balance of implicit or explicit social contracts, mutual trust, and fair distribution of costs and benefits, as explained by theories of social interaction and exchange—such as Social Exchange Theory [Homans 1958] and Social Contract Theory [Rousseau 1762]. When the benefits clearly extend beyond the primary parties—for example, when collected data is repurposed to serve third parties—this balance can be disrupted. If users feel that their contributions are being exploited without fair reciprocity, trust erodes, and they may come to see the system as exploitative or unjust.

These feelings of mistrust and exploitation are already prevalent in AI, particularly in creative and knowledge-sharing communities. Artists have protested against their work being scraped to train AI models without consent or compensation [Jiang et al. 2023]¹, with many calling for stronger protections against AI-generated art [Guardian 2025]. Similarly, Stack Overflow users, frustrated by their contributions being used for external profits, have intention-ally altered or deleted their posts to hinder AI training—leading to bans, boycott, and subsequent decline in engagement on the platform [Hardware 2024; Technica 2024]. These examples highlight the fragility of trust in data collection and the potential consequences when contributors feel that their data is being repurposed beyond its original intent.

8. Games as a New Pareto-Frontier?

Games are uniquely positioned at the intersection of structured environments and intrinsic motivation. Designed worlds crafted by game developers set the rules and constraints, yet within them, players engage voluntarily, driven by curiosity, competition, and creativity [Koster 2005]. Unlike traditional work, where tasks are

¹https://www.aitrainingstatement.org/

often externally imposed, games offer a space where challenge and engagement emerge naturally, sustaining long-term participation without the need for direct financial incentives.

For most players—aside from professional esports competitors—games are played purely for enjoyment. At the same time, they require diverse forms of reasoning, strategy, and problem-solving, making them a rich ground for capturing complex human behaviors and decision making [as already evidenced by their role in evaluating intelligence; Berner et al. 2019; FAIR; Silver et al. 2016; Vinyals et al. 2019]. In this way, games hint at a new frontier—one where many structured environments and organic engagements seamlessly coexist. This intersection offers a compelling model for AI training, where intrinsically motivated interactions can yield structured, high-quality data without the pitfalls of external incentive-driven systems.

Games as a Tool for Data Collection. Games have long been explored as a tool for large-scale human annotation and AI training, most notably through von Ahn's Games with a Purpose (GWAP) [Von Ahn 2006]. One of the earliest and most influential examples was the ESP Game [Von Ahn and Dabbish 2005], introduced in 2004, which engaged thousands of players in a collaborative tagging game, generating millions of image annotations. While players simply enjoyed the game, their interactions helped bootstrap Google Image Search [Guardian 2006], which previously relied only on filenames, as large-scale labeled datasets like ImageNet were not available until 2009 [Deng et al. 2009].

Von Ahn argued that the billions of hours spent on games—such as the 9 billion hours on Solitaire in 2003 alone, enough to build the Empire State Building in 6.8 hours or the Panama Canal in a day—could be repurposed for more meaningful tasks, inspiring the broader Games with a Purpose framework [Law and Von Ahn 2011]. Other notable games in this series included Peek-a-boom [Von Ahn et al. 2006b], which collected image segmentation data, and Verbosity [Von Ahn et al. 2006a], designed to gather commonsense factual knowledge.

Games in Mainstream ML. While recent efforts towards this in machine learning have not reached the scale of GWAP, they have made notable progress. Examples include Google's Quick-Draw [Ha and Eck 2017] and AllenAI's Iconary [Clark et al. 2021], which focus on collecting freehand drawing data, and AI21's HumanOrNot [Jannai et al. 2023], which gathers conversational data through a gamified Turing Test [Dugan et al. 2023].

However, developing entirely new games for data collection presents significant challenges. Machine learning researchers often lack expertise in designing engaging gameplay, making it difficult to ensure both high-quality data and sustained participation. To navigate this, some approaches have focused on repurposing existing games rather than building from scratch. For example, Family Feud has been adapted to generate QA pairs [Boratko et al. 2020], and Minecraft has been used as a platform for collecting conversational dialogues [Narayan-Chen et al. 2019].

On a smaller scale, some efforts have explored gamification, introducing game-like mechanics into traditionally non-game tasks to enhance engagement, without requiring a full game environment. For instance, CommonsenseQA 2.0 incorporates elements such as scoring, competition, and progression to make data contribution more engaging, improving both user participation and data quality [Talmor et al. 2022].

Design Considerations. Designing data collection games requires solving multiple challenges at once—the most critical challenge is optimizing data utility while preserving intrinsic player motivation. This involves balancing two often competing objectives:

- Ensuring that collected data meets the needs of AI/ML tasks requiring structure, reliability, and task relevance.
- Designing a player experience that remains engaging over time -avoiding disengagement due to artificial constraints or coercive incentives.

Achieving this balance is a multi-objective optimization problem that requires close collaboration between ML researchers and game developers. This design space spans multiple approaches, including creating entirely new games optimized for data collection, leveraging existing games to re-purpose organic player interactions, or introducing game-like elements into existing data collection tasks to enhance engagement. Each of these approaches comes with trade-offs in control, scalability, and long-term sustainability.

While prior efforts have successfully optimized for quality and quantity, sustaining trust has proven far more elusive, leading to short-lived or unsustainable solutions. Historical implementations offer valuable lessons—GWAP demonstrated the potential for highquality, high-quantity crowdsourced data but did not endure over time. In contrast, ReCAPTCHA [Von Ahn et al. 2008] conceptualized in 2008, used for annotating books and self-driving data [Anton 2018; O'Malley 2018], remains widely used today but has blurred the line between voluntary participation and coercion, with users reporting frustration and annoyance [Searles et al. 2023a,b], alluding to lack of trust. These examples illustrate the challenge of designing systems that optimize for all three aspects: high-quality, high-quantity, and high-trust data collection.

This challenge becomes even more evident when considering longterm sustainability. While data collection games have proven effective in gathering large-scale, high-quality data, few have endured over time. To our knowledge, no sustained data collection effort through games exists in machine learning. However, other research fields provide examples of systems that have successfully maintained engagement and trust over extended periods. Scientific discovery platforms such as Zooniverse for citizen science in astronomy [Cardamone et al. 2009; Lintott et al. 2008], Lab in the Wild for HCI and psychology user studies [Reinecke and Gajos 2015], FoldIt for protein folding [Cooper et al. 2010; Khatib et al. 2011], and even Eve Online for epidemiology research [Kafai and Burke 2016] demonstrate how engagement, motivation, and trust can be sustained without relying on short-lived external incentives. Psychology and cognitive science studies [Allen et al. 2024] further reinforce that game-like participation can be structured in ways that maintain engagement over time.

While games and other naturalistic environments show significant potential towards achieving higher quality and quantity at the same time, they come with their own unique benefits and challenges previously not encountered with data collection systems:

Benefits include the collection of previously inaccessible data, such as natural dialogue interactions. Human conversations are often behind privacy walls, and attempting to collect dialogue through traditional data collection platforms is impractical, because unlike simple annotation tasks, dialogues need to be organic with real-time back-and-forth exchanges. In such cases, LLM-generated synthetic data has been a relief, with datasets like SODA [Kim et al. 2022] playing a pivotal role in advancing dialogue systems. However, games offer an ideal setting where natural dialogues happen organically in non-real-world contexts, often under pseudonyms, making privacy concerns less of an issue. For instance, Minecraft has been leveraged to collect goal-driven player dialogues [Narayan-Chen et al. 2019], demonstrating how game environments facilitate authentic, context-rich communication.

Benefits also arise from the nature of games, including their ability to **collect data for open-ended tasks**, which has traditionally been challenging [Karpinska et al. 2021], especially over the long term. Moreover, games provide a unique advantage by enabling multi-modal data collection—capturing vision, language, and speech for the same actions—thus supporting advancements in embodied AI research. This has already been demonstrated in virtual environments like Habitat [Puig et al. 2023] and AI2-THOR [Kolve et al. 2017], albeit without game-like objectives or direct human involvement to learn from yet.

Challenges include difficulty in designing meaningful intrinsic rewards, as motivations and preferences naturally vary across individuals and cultures. Unlike money, which serves as a universal incentive, intrinsic rewards must align with diverse motivational drivers—curiosity, competition, or self-improvement—to sustain engagement [Jun et al. 2017]. This also impacts demographic representation, as cultural and personal factors shape motivation [Deci and Ryan 1985]. Certain groups may be overrepresented while others disengage based on how well rewards align with their preferences [Triandis 1995]. To ensure fairness, intrinsically motivated data collection must be designed to encourage diverse participation rather than benefiting only specific user segments.

While games are often seen as leisure activities or "unproductive," repurposing them for data collection contributes to value creation, in which case, it is important to recognize and fairly compensate contributors. The challenge is that, unlike traditional annotation tasks, AI data attribution is ambiguous, making it difficult to measure and **distribute compensation effectively**. One way to address this is by ensuring that contributors have a stake in the value their data generates, potentially through decentralized compensation models [Oh et al. 2025]. However, in general, compensation must be carefully structured to avoid distorting intrinsic motivation. If participants anticipate compensation upfront, their engagement risks becoming extrinsically driven, leading to lower-quality contributions. A potential solution is delayed, post-hoc recognition, where participants are acknowledged after the fact, ensuring they remain intrinsically engaged while still benefiting from their contributions.

Beyond incentive design, another fundamental challenge is ensuring that game-derived data remains both ethical and useful. Not all games inherently separate real-world contexts, which may necessitate distinguishing user-identifiable behavior from game-playing behavior for privacy reasons [Nair et al. 2022]. More broadly, extracting useful and generalizable data from inherently noisy and unstructured game records can be a significant challenge, similar to the difficulties faced in filtering large-scale Internet data [Fang et al. 2023].

9. Reviving Human Data Sourcing: A New Path Forward

In the search for sustainable ways to collect human-generated data for AI, we examined existing data collection systems through the lens of the quantity-quality trade-off which arises as a consequence of system-level design choices that make achieving both difficult. While such trade-offs are inherent to designed systems, they can be mitigated by carefully addressing the factors that shape them.

To unpack the latent factors involved, we examined two core drivers of this trade-off: quality, influenced by motivation and incentives, and quantity, shaped by fragmentation and efficiency. We examined how over-reliance on external incentives and excessive task fragmentation erode intrinsic motivation, ultimately leading to long-term declines in data quality. To counteract this, we propose shifting from controlling individual tasks to designing structured and trustworthy environments that sustain engagement while still allowing data collectors to shape the kind of data they gather.

We explore games as a promising new frontier for data collection. By naturally balancing structure with voluntary participation, they offer a scalable, high-quality, and sustainable alternative to conventional data collection systems—one that is increasingly important as traditional approaches face growing limitations.

References

- Alon Albalak, Yanai Elazar, Sang Michael Xie, Shayne Longpre, Nathan Lambert, Xinyi Wang, Niklas Muennighoff, Bairu Hou, Liangming Pan, Haewon Jeong, et al. 2024. A survey on data selection for language models. <u>arXiv preprint arXiv:2402.16827</u> (2024).
- Kelsey Allen, Franziska Brändle, Matthew Botvinick, Judith E Fan, Samuel J Gershman, Alison Gopnik, Thomas L Griffiths, Joshua K Hartshorne, Tobias U Hauser, Mark K Ho, et al. 2024. Using games to understand the mind. <u>Nature Human Behaviour</u> (2024), 1–9.
- Anton. 2018. reCAPTCHA: The Brilliant Business Model that Only One Man Could Create. https://d3.harvard.edu/platform-digit/submission/recaptcha-the-brilliantbusiness-model-that-only-one-man-could-create/ Digital Innovation and Transformation, Posted on March 26, 2018.
- Lisa P Argyle, Ethan C Busby, Nancy Fulda, Joshua R Gubler, Christopher Rytting, and David Wingate. 2023. Out of one, many: Using language models to simulate human samples. <u>Political Analysis</u> 31, 3 (2023), 337–351.
- Dhananjay Ashok and Jonathan May. 2024. A Little Human Data Goes A Long Way. arXiv preprint arXiv:2410.13098 (2024).
- Maggie Astor. 2017. Your Roomba may be mapping your home, collecting data that could be shared. <u>The New York Times</u> 25 (2017), 186.
- Work at Home Smart. 2024. Lionbridge vs Appen: Task Completion Times and Processes. (2024). https://workathomesmart.com/lionbridge-vs-appen/ Accessed: 2025-01-19.

Economics of Sourcing Human Data

- Daryl J Bem. 1972. Self-perception theory. In <u>Advances in experimental social</u> psychology. Vol. 6. Elsevier, 1–62.
- Christopher Berner, Greg Brockman, Brooke Chan, Vicki Cheung, Przemysław Dębiak, Christy Dennison, David Farhi, Quirin Fischer, Shariq Hashme, Chris Hesse, et al. 2019. Dota 2 with large scale deep reinforcement learning. <u>arXiv preprint</u> arXiv:1912.06680 (2019).
- Michael S Bernstein, Joel Brandt, Robert C Miller, and David R Karger. 2011. Crowds in two seconds: Enabling realtime crowd-powered interfaces. In <u>Proceedings of the</u> 24th annual ACM symposium on User interface software and technology. 33–42. John Bohannon. 2011. Social science for pennies.
- Rishi Bommasani, Drew A Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sidney von Arx, Michael S Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, et al. 2021. On the Opportunities and Risks of Foundation Models. <u>arXiv preprint</u> arXiv:2108.07258 (2021).
- Michael Boratko, Xiang Lorraine Li, Rajarshi Das, Tim O'Gorman, Dan Le, and Andrew McCallum. 2020. ProtoQA: A question answering dataset for prototypical commonsense reasoning. arXiv preprint arXiv:2005.00771 (2020).
- Creston Brooks, Samuel Eggert, and Denis Peskoff. 2024. The Rise of AI-Generated Content in Wikipedia. arXiv preprint arXiv:2410.08044 (2024).
- Tom B Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language Models are Few-Shot Learners. <u>Advances in Neural Information</u> Processing Systems 33 (2020), 1877–1901.
- Erik Brynjolfsson and Andrew McAfee. 2014. The second machine age: Work, progress, and prosperity in a time of brilliant technologies. WW Norton & Company.
- Carolin Cardamone, Kevin Schawinski, Marc Sarzi, Steven P Bamford, Nicola Bennert, C Megan Urry, Chris Lintott, William C Keel, John Parejko, Robert C Nichol, et al. 2009. Galaxy Zoo Green Peas: discovery of a class of compact extremely starforming galaxies. <u>Monthly Notices of the Royal Astronomical Society</u> 399, 3 (2009), 1191–1205.
- Michelle Cheng. 2023. Microsoft, Google, and OpenAI are getting questioned about their AI "data labelers". https://qz.com/tech-companies-ai-data-labelers-congress-1850834407
- Christopher Clark, Jordi Salvador, Dustin Schwenk, Derrick Bonafilia, Mark Yatskar, Eric Kolve, Alvaro Herrasti, Jonghyun Choi, Sachin Mehta, Sam Skjonsberg, et al. 2021. Iconary: a pictionary-based game for testing multimodal communication with drawings and text. <u>arXiv preprint arXiv:2112.00800</u> (2021).
- Common Crawl. 2021. Common Crawl Dataset. https://commoncrawl.org/
- Seth Cooper, Firas Khatib, Adrien Treuille, Janos Barbero, Jeehyung Lee, Michael Beenen, Andrew Leaver-Fay, David Baker, Zoran Popović, et al. 2010. Predicting protein structures with a multiplayer online game. <u>Nature</u> 466, 7307 (2010), 756– 760.
- Kate Crawford and Vladan Joler. 2018. Anatomy of an AI System. <u>Anatomy of an AI</u> <u>System</u> (2018).
- Edward L Deci. 1971. Effects of externally mediated rewards on intrinsic motivation. Journal of personality and Social Psychology 18, 1 (1971), 105.
- Edward L. Deci and Richard M. Ryan. 1985. <u>Intrinsic Motivation and</u> <u>Self-Determination in Human Behavior</u>. Springer Science & Business Media.
- Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. 2009. Imagenet: A large-scale hierarchical image database. In 2009 IEEE conference on computer vision and pattern recognition. Ieee, 248–255.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2018. Bert: Pretraining of deep bidirectional transformers for language understanding. <u>arXiv</u> preprint arXiv:1810.04805 (2018).
- Peter Dicken. 2007. <u>Global shift: Mapping the changing contours of the world</u> economy. SAGE Publications Ltd.
- Benjamin D Douglas, Patrick J Ewell, and Markus Brauer. 2023. Data quality in online human-subjects research: Comparisons between MTurk, Prolific, CloudResearch, Qualtrics, and SONA. <u>Plos one</u> 18, 3 (2023), e0279720.
- Yann Dubois, Chen Xuechen Li, Rohan Taori, Tianyi Zhang, Ishaan Gulrajani, Jimmy Ba, Carlos Guestrin, Percy S Liang, and Tatsunori B Hashimoto. 2024. Alpacafarm: A simulation framework for methods that learn from human feedback. <u>Advances</u> in Neural Information Processing Systems 36 (2024).
- Liam Dugan, Daphne Ippolito, Arun Kirubarajan, Sherry Shi, and Chris Callison-Burch. 2023. Real or fake text?: Investigating human ability to detect boundaries between human-written and machine-generated text. In <u>Proceedings of the AAAI</u> Conference on Artificial Intelligence, Vol. 37. 12763–12771.
- Douglas Engelbart. 1962. Augmenting human intellect: A conceptual framework. Summary report. Stanford Research Institute, on Contract AF 49, 638 (1962), 1024.
- Meta Fundamental AI Research Diplomacy Team (FAIR)[†], Anton Bakhtin, Noam Brown, Emily Dinan, Gabriele Farina, Colin Flaherty, Daniel Fried, Andrew Goff, Jonathan Gray, Hengyuan Hu, et al. 2022. Human-level play in the game of Diplomacy by combining language models with strategic reasoning. <u>Science</u> 378, 6624 (2022), 1067–1074.
- Alex Fang, Albin Madappally Jose, Amit Jain, Ludwig Schmidt, Alexander Toshev, and Vaishaal Shankar. 2023. Data filtering networks. <u>arXiv preprint arXiv:2309.17425</u> (2023).

- Andrea Forte and Amy Bruckman. 2005. Why do people write for Wikipedia? Incentives to contribute to open-content publishing. In <u>Proceedings of the 2005 GROUP</u> <u>Conference</u>. ACM.
- Samir Yitzhak Gadre, Gabriel Ilharco, Alex Fang, Jonathan Hayase, Georgios Smyrnis, Thao Nguyen, Ryan Marten, Mitchell Wortsman, Dhruba Ghosh, Jieyu Zhang, et al. 2024. Datacomp: In search of the next generation of multimodal datasets. <u>Advances</u> in Neural Information Processing Systems 36 (2024).
- Scott Geng, Cheng-Yu Hsieh, Vivek Ramanujan, Matthew Wallingford, Chun-Liang Li, Pang Wei Koh, and Ranjay Krishna. 2024. The Unmet Promise of Synthetic Training Images: Using Retrieved Real Images Performs Better. <u>arXiv preprint</u> arXiv:2406.05184 (2024).
- Aaron Gokaslan and Vanya Cohen. 2019. OpenWebText Corpus. http://Skylion007. github.io/OpenWebTextCorpus.
- Charles AE Goodhart and CAE Goodhart. 1984. <u>Problems of monetary management:</u> the UK experience. Springer.
- Mary L Gray and Siddharth Suri. 2019. <u>Ghost work: How to stop Silicon Valley from</u> building a new global underclass. Eamon Dolan Books.
- The Guardian. 2006. Google uses ESP Game to improve image search. <u>The Guardian</u> (3 September 2006). <u>https://www.theguardian.com/technology/blog/2006/sep/03/</u> googleusesesp
- The Guardian. 2025. 'Mass theft': Thousands of artists call for AI art auction to be cancelled. <u>The Guardian</u> (10 February 2025). https: //www.theguardian.com/technology/2025/feb/10/mass-theft-thousands-ofartists-call-for-ai-art-auction-to-be-cancelled
- Suchin Gururangan, Dallas Card, Sarah K Dreier, Emily K Gade, Leroy Z Wang, Zeyu Wang, Luke Zettlemoyer, and Noah A Smith. 2022. Whose language counts as high quality? measuring language ideologies in text data selection. <u>arXiv preprint</u> arXiv:2201.10474 (2022).
- David Ha and Douglas Eck. 2017. A neural representation of sketch drawings. <u>arXiv</u> preprint arXiv:1704.03477 (2017).
- Review
 (2022).
 How the Al Industry Profits from Catastrophe.
 MIT Technology

 Review
 (2022).
 https://www.technologyreview.com/2022/04/20/1050392/aiindustry-appen-scale-data-labels/
 Accessed: 2025-02-10.
- Tom's Hardware. 2024. Stack Overflow bans users en masse for rebelling against OpenAI partnership. https://www.tomshardware.com/tech-industry/artificialintelligence/stack-overflow-bans-users-en-masse-for-rebelling-against-openaipartnership-users-banned-for-deleting-answers-to-prevent-them-being-usedto-train-chatgpt. Accessed: 2025-01-03.
- Friedrich August Hayek and Bruce Caldwell. 2014. <u>The road to serfdom: Text and</u> <u>documents: The definitive edition</u>. Routledge.
- Chien-Ju Ho, Aleksandrs Slivkins, Siddharth Suri, and Jennifer Wortman Vaughan. 2015. Incentivizing high quality crowdwork. In <u>Proceedings of the 24th International</u> <u>Conference on World Wide Web</u>. 419–429.
- Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, et al. 2022. Training compute-optimal large language models. <u>arXiv</u> preprint arXiv:2203.15556 (2022).
- George C. Homans. 1958. <u>Social Behavior as Exchange</u>. Vol. 63. University of Chicago Press. 597–606 pages. <u>https://doi.org/10.1086/222355</u>
- D Hounshell. 1984. From the American system to mass production, 1800-1932: The development of manufacturing technology in the United States. Baltimore, Md.: Johns Hopkins University Press.
- Kazushi Ikeda and Michael S Bernstein. 2016. Pay it backward: Per-task payments on crowdsourcing platforms reduce productivity. In <u>Proceedings of the 2016 CHI</u> Conference on Human Factors in Computing Systems. 4111–4121.
- Daniel Jannai, Amos Meron, Barak Lenz, Yoav Levine, and Yoav Shoham. 2023. Human or Not? A gamified approach to the Turing test. <u>arXiv preprint arXiv:2305.20010</u> (2023).
- Harry H Jiang, Lauren Brown, Jessica Cheng, Mehtab Khan, Abhishek Gupta, Deja Workman, Alex Hanna, Johnathan Flowers, and Timnit Gebru. 2023. AI Art and its Impact on Artists. In <u>Proceedings of the 2023 AAAI/ACM Conference on AI,</u> <u>Ethics, and Society</u>. 363–374.
- Eunice Jun, Gary Hsieh, and Katharina Reinecke. 2017. Types of motivation affect study selection, attention, and dropouts in online experiments. <u>Proceedings of the</u> <u>ACM on Human-Computer Interaction</u> 1, CSCW (2017), 1–15.
- Yasmin B Kafai and Quinn Burke. 2016. <u>Connected gaming</u>: What making video games can teach us about learning and literacy. Mit Press.
- Daniel Kahneman and Amos Tversky. 2013. Prospect theory: An analysis of decision under risk. In <u>Handbook of the fundamentals of financial decision making</u>: Part I. World Scientific, 99–127.
- Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. 2020. Scaling laws for neural language models. <u>arXiv preprint arXiv:2001.08361</u> (2020).
- Andrej Karpathy. 2021. Tesla AI Day: Full Self-Driving and Neural Network Training. Tesla AI Day Presentation. https://www.youtube.com/watch?v=j0z4FweCy4M
- Marzena Karpinska, Nader Akoury, and Mohit Iyyer. 2021. The perils of using Mechanical Turk to evaluate open-ended text generation. <u>arXiv preprint arXiv:2109.06835</u> (2021).

- Steven Kerr. 1975. On the folly of rewarding A, while hoping for B. <u>Academy of Management Journal</u> 18, 4 (1975), 769–783. https://doi.org/10.2307/255378
- Firas Khatib, Frank DiMaio, Foldit Contenders Group, Foldit Void Crushers Group, Seth Cooper, Maciej Kazmierczyk, Mirosław Gilski, Szymon Krzywda, Helena Zabranska, Iva Pichova, et al. 2011. Crystal structure of a monomeric retroviral protease solved by protein folding game players. <u>Nature structural & molecular biology</u> 18, 10 (2011), 1175–1177.
- Hyunwoo Kim, Jack Hessel, Liwei Jiang, Peter West, Ximing Lu, Youngjae Yu, Pei Zhou, Ronan Le Bras, Malihe Alikhani, Gunhee Kim, et al. 2022. Soda: Million-scale dialogue distillation with social commonsense contextualization. <u>arXiv preprint</u> arXiv:2212.10465 (2022).
- Aniket Kittur, Jeffrey V Nickerson, Michael Bernstein, Elizabeth Gerber, Aaron Shaw, John Zimmerman, Matt Lease, and John Horton. 2013. The future of crowd work. In Proceedings of the 2013 conference on Computer supported cooperative work. 1301–1318.
- Jan-Christoph Klie, Richard Eckart de Castilho, and Iryna Gurevych. 2024a. Analyzing Dataset Annotation Quality Management in the Wild. <u>Computational Linguistics</u> (2024), 1–48.
- Jan-Christoph Klie, Juan Haladjian, Marc Kirchner, and Rahul Nair. 2024b. On Efficient and Statistical Quality Estimation for Data Annotation. <u>arXiv preprint</u> arXiv:2405.11919 (2024).
- Eric Kolve, Roozbeh Mottaghi, Winson Han, Eli VanderBilt, Luca Weihs, Alvaro Herrasti, Matt Deitke, Kiana Ehsani, Daniel Gordon, Yuke Zhu, et al. 2017. Ai2-thor: An interactive 3d environment for visual ai. arXiv preprint arXiv:1712.05474 (2017).
- Ralph Koster. 2005. <u>A Theory of Fun for Game Design</u>. Paraglyph Press, Scottsdale, AZ.
- David H Kreitmeir and Paul A Raschky. 2023. The Unintended Consequences of Censoring Digital Technology–Evidence from Italy's ChatGPT Ban. <u>arXiv preprint</u> arXiv:2304.09339 (2023).
- Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. 2012. Imagenet classification with deep convolutional neural networks. <u>Advances in neural information</u> processing systems 25 (2012).
- Cliff Lampe, Rick Wash, Alcides Velasquez, and Elif Ozkaya. 2010. Motivations to participate in online communities. In <u>CHI</u> '10 Extended Abstracts on Human Factors in Computing Systems. ACM. https://doi.org/10.1145/1753846.1753863
- Johann Laux, Fabian Stephany, and Alice Liefgreen. 2024. Improving Task Instructions for Data Annotators: How Clear Rules and Higher Pay Increase Performance in Data Annotation in the AI Economy. <u>arXiv preprint arXiv:2312.14565v2</u> (2024). https://arxiv.org/abs/2312.14565v2
- Edith Law and Luis Von Ahn. 2011. Human computation. (2011).
- Katherine Lee, Daphne Ippolito, Andrew Nystrom, Chiyuan Zhang, Douglas Eck, Chris Callison-Burch, and Nicholas Carlini. 2021. Deduplicating training data makes language models better. arXiv preprint arXiv:2107.06499 (2021).
- Thomas C Leonard. 2008. Richard H. Thaler, Cass R. Sunstein, Nudge: Improving decisions about health, wealth, and happiness: Yale University Press, New Haven, CT, 2008, 293 pp.
- Mark R Lepper, David Greene, and Richard E Nisbett. 1973. Undermining children's intrinsic interest with extrinsic reward: A test of the" overjustification" hypothesis. Journal of Personality and social Psychology 28, 1 (1973), 129.
- Jeffrey Li, Alex Fang, Georgios Smyrnis, Maor Ivgi, Matt Jordan, Samir Gadre, Hritik Bansal, Etash Guha, Sedrick Keh, Kushal Arora, et al. 2024. Datacomp-lm: In search of the next generation of training sets for language models. <u>arXiv preprint</u> arXiv:2406.11794 (2024).
- Zhehui Liao, Maria Antoniak, Inyoung Cheong, Evie Yu-Yen Cheng, Ai-Heng Lee, Kyle Lo, Joseph Chee Chang, and Amy X Zhang. 2024. LLMs as Research Tools: A Large Scale Survey of Researchers' Usage and Perceptions. <u>arXiv preprint</u> arXiv:2411.05025 (2024).
- Chris J Lintott, Kevin Schawinski, Anže Slosar, Kate Land, Steven Bamford, Daniel Thomas, M Jordan Raddick, Robert C Nichol, Alex Szalay, Dan Andreescu, et al. 2008. Galaxy Zoo: morphologies derived from visual inspection of galaxies from the Sloan Digital Sky Survey. <u>Monthly Notices of the Royal Astronomical Society</u> 389, 3 (2008), 1179–1189.
- T. Malsburg. 2024. Mechanical Turk Task Completion Times and Compensation. (2024). https://tmalsburg.github.io/mturk-compensation.html Accessed: 2025-01-19.
- David Martin, Jacki O'Neill, Neha Gupta, and Benjamin V Hanrahan. 2016. Turking in a global labour market. <u>Computer Supported Cooperative Work (CSCW)</u> 25 (2016), 39–77.
- Karl Marx. 2016. Economic and philosophic manuscripts of 1844. In <u>Social Theory</u> <u>Re-Wired</u>. Routledge, 152–158.
- Abraham Harold Maslow. 1943. A theory of human motivation. <u>Psychological review</u> 50, 4 (1943), 370.
- Winter Mason and Duncan J Watts. 2009. Financial incentives and the "performance of crowds". In <u>Proceedings of the ACM SIGKDD workshop on human computation</u>. 77–85.
- John McCarthy. 1987. Generality in artificial intelligence. <u>Commun. ACM</u> 30, 12 (1987), 1030–1035.
- Vivek Nair, Gonzalo Munilla Garrido, and Dawn Song. 2022. Exploring the unprecedented privacy risks of the metaverse. arXiv preprint arXiv:2207.13176 (2022).

- Anjali Narayan-Chen, Prashant Jayannavar, and Julia Hockenmaier. 2019. Collaborative dialogue in Minecraft. In <u>Proceedings of the 57th Annual Meeting of the</u> <u>Association for Computational Linguistics</u>. 5405–5415.
- Thao Nguyen, Gabriel Ilharco, Mitchell Wortsman, Sewoong Oh, and Ludwig Schmidt. 2022. Quality not quantity: On the interaction between dataset design and robustness of clip. <u>Advances in Neural Information Processing Systems</u> 35 (2022), 21455–21469.
- Sewoong Oh, Himanshu Tyagi, and Pramod Viswanath. 2025. Training AI to be loyal. (2025). https://sentient.xyz/Sentient_Loyal_ALpdf.
- OpenAI. 2023. ChatGPT: OpenAI Language Model. https://chat.openai.com. Accessed: January 26, 2025.
- James O'Malley. 2018. Captcha if you can: how you've been training ai for years without realising it. <u>Tech Radar. URL https://bit.ly/37H1esA</u> (2018).
- Joon Sung Park, Joseph O'Brien, Carrie Jun Cai, Meredith Ringel Morris, Percy Liang, and Michael S Bernstein. 2023. Generative agents: Interactive simulacra of human behavior. In <u>Proceedings of the 36th Annual ACM Symposium on User Interface</u> Software and Technology. 1–22.
- Joon Sung Park, Lindsay Popowski, Carrie Cai, Meredith Ringel Morris, Percy Liang, and Michael S Bernstein. 2022. Social simulacra: Creating populated prototypes for social computing systems. In <u>Proceedings of the 35th Annual ACM Symposium on</u> User Interface Software and Technology. 1–18.
- Billy Perrigo. 2023. Exclusive: OpenAI used Kenyan workers on less than \$2 per hour to make ChatGPT less toxic. <u>Time Magazine</u> 18 (2023), 2023.
- Pieces. 2025. Data Scarcity: When Will AI Hit a Wall? (2025). https://pieces.app/blog/ data-scarcity-when-will-ai-hit-a-wall Accessed: 2025-01-19.
- Prolific. 2024. Prolific vs MTurk: Average Task Completion Times. (2024). https: //www.prolific.com/prolific-vs-mturk Accessed: 2025-01-19.
- Xavier Puig, Eric Undersander, Andrew Szot, Mikael Dallaire Cote, Tsung-Yen Yang, Ruslan Partsey, Ruta Desai, Alexander William Clegg, Michal Hlavac, So Yeon Min, et al. 2023. Habitat 3.0: A co-habitat for humans, avatars and robots. <u>arXiv preprint</u> arXiv:2310.13724 (2023).
- Crystal Qian, Michael Xieyang Liu, Emily Reif, Grady Simon, Nada Hussein, Nathan Clement, James Wexler, Carrie J Cai, Michael Terry, and Minsuk Kahng. 2024. The Evolution of LLM Adoption in Industry Data Curation Practices. <u>arXiv preprint</u> arXiv:2412.16089 (2024).
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J Liu. 2020. Exploring the limits of transfer learning with a unified text-to-text transformer. <u>Journal of machine learning</u> research 21, 140 (2020), 1–67.
- Katharina Reinecke and Krzysztof Z Gajos. 2015. LabintheWild: Conducting largescale online experiments with uncompensated samples. In <u>Proceedings of the 18th</u> <u>ACM conference on computer supported cooperative work & social computing.</u> <u>1364–1378.</u>
- Jean-Jacques Rousseau. 1762. <u>The Social Contract, or Principles of Political Right</u>. Original Publication in French. Translated in various editions. See: https://plato. stanford.edu/entries/rousseau/.
- Andrew Searles, Yoshimichi Nakatsuka, Ercan Ozturk, Andrew Paverd, Gene Tsudik, and Ai Enkoji. 2023a. An Empirical Study & Evaluation of Modern {CAPTCHAs}. In <u>32nd usenix security symposium (usenix security 23)</u>. 3081–3097.
- Andrew Searles, Renascence Tarafder Prapty, and Gene Tsudik. 2023b. Dazed & Confused: A Large-Scale Real-World User Study of reCAPTCHAv2. <u>arXiv preprint</u> arXiv:2311.10911 (2023).
- Nihar B Shah and Dengyong Zhou. 2016. Double or nothing: Multiplicative incentive mechanisms for crowdsourcing. <u>Journal of Machine Learning Research</u> 17, 165 (2016), 1–52.
- Ilia Shumailov, Zakhar Shumaylov, Yiren Zhao, Nicolas Papernot, Ross Anderson, and Yarin Gal. 2024. AI models collapse when trained on recursively generated data. <u>Nature</u> 631, 8022 (2024), 755–759.
- Horst Siebert. 2001. <u>Der Kobra-Effekt: Wie man Irrwege der Wirtschaftspolitik</u> vermeidet, Deutsche Verlags-Anstalt, Stuttgart, Germany.
- David Silver, Aja Huang, Chris J Maddison, Arthur Guez, Laurent Sifre, George Van Den Driessche, Julian Schrittwieser, Ioannis Antonoglou, Veda Panneershelvam, Marc Lanctot, et al. 2016. Mastering the game of Go with deep neural networks and tree search. <u>nature</u> 529, 7587 (2016), 484–489.
- Luca Soldaini, Rodney Kinney, Akshita Bhagia, Dustin Schwenk, David Atkinson, Russell Authur, Ben Bogin, Khyathi Chandu, Jennifer Dumas, Yanai Elazar, et al. 2024. Dolma: An open corpus of three trillion tokens for language model pretraining research. arXiv preprint arXiv:2402.00159 (2024).
- Pei Sun, Henrik Kretzschmar, Xerxes Dotiwalla, Aurelien Chouard, Vijaysai Patnaik, Paul Tsui, James Guo, Yin Zhou, Yuning Chai, Benjamin Caine, et al. 2020. Scalability in perception for autonomous driving: Waymo open dataset. In <u>Proceedings of the</u> IEEE/CVF conference on computer vision and pattern recognition. 2446–2454.
- Richard Sutton. 2019. The bitter lesson. Incomplete Ideas (blog) 13, 1 (2019), 38.
- Alon Talmor, Ori Yoran, Ronan Le Bras, Chandra Bhagavatula, Yoav Goldberg, Yejin Choi, and Jonathan Berant. 2022. Commonsenseqa 2.0: Exposing the limits of ai through gamification. arXiv preprint arXiv:2201.05320 (2022).
- Rohan Taori and Tatsunori Hashimoto. 2023. Data feedback loops: Model-driven amplification of dataset biases. In International Conference on Machine Learning.

Economics of Sourcing Human Data

PMLR, 33883-33920.

- Ars Technica. 2024. Stack Overflow users sabotage their posts after OpenAI deal. https://arstechnica.com/information-technology/2024/05/stack-overflowusers-sabotage-their-posts-after-openai-deal/. Accessed: 2025-01-03.
- Inc. Tesla. 2021. Tesla's Approach to Autonomous Driving: Autopilot AI and Full Self-Driving. Online. https://www.tesla.com/autopilotAI
- Holden Thorp. 2023. ChatGPT is fun, but not an author. <u>Science</u> 379, 6630 (2023), 313. https://doi.org/10.1126/science.adg7879
- Harry C. Triandis. 1995. Individualism & Collectivism. Westview Press.
- Upwork. 2024a. How Long Does it Take to Start and Complete a Project on Upwork? (2024). https://www.upwork.com/resources/how-long-project-on-upwork Accessed: 2025-01-19.
- Upwork. 2024b. Upwork vs Fiverr: Comparing Freelance Platforms and Completion Times. (2024). https://www.upwork.com/resources/upwork-vs-fiverr Accessed: 2025-01-19.
- Veniamin Veselovsky, Manoel Horta Ribeiro, Philip Cozzolino, Andrew Gordon, David Rothschild, and Robert West. 2023b. Prevalence and prevention of large language model use in crowd work. arXiv preprint arXiv:2310.15683 (2023).
- Veniamin Veselovsky, Manoel Horta Ribeiro, and Robert West. 2023a. Artificial artificial artificial intelligence: Crowd workers widely use large language models for text production tasks. <u>arXiv preprint arXiv:2306.07899</u> (2023).
- Oriol Vinyals, Igor Babuschkin, Wojciech M Czarnecki, Michaël Mathieu, Andrew Dudzik, Junyoung Chung, David H Choi, Richard Powell, Timo Ewalds, Petko

Georgiev, et al. 2019. Grandmaster level in StarCraft II using multi-agent reinforcement learning. <u>nature</u> 575, 7782 (2019), 350–354.

Luis Von Ahn. 2006. Games with a purpose. Computer 39, 6 (2006), 92-94.

- Luis Von Ahn and Laura Dabbish. 2005. ESP: Labeling Images with a Computer Game.. In <u>AAAI spring symposium</u>: Knowledge collection from volunteer contributors, Vol. 2. 1.
- Luis Von Ahn, Mihir Kedia, and Manuel Blum. 2006a. Verbosity: a game for collecting common-sense facts. In <u>Proceedings of the SIGCHI conference on Human Factors</u> in computing systems. 75–78.
- Luis Von Ahn, Ruoran Liu, and Manuel Blum. 2006b. Peekaboom: a game for locating objects in images. In Proceedings of the SIGCHI conference on Human Factors in computing systems. 55–64.
- Luis Von Ahn, Benjamin Maurer, Colin McMillen, David Abraham, and Manuel Blum. 2008. recaptcha: Human-based character recognition via web security measures. <u>Science</u> 321, 5895 (2008), 1465–1468.
- Adrienne Williams, Milagros Miceli, and Timnit Gebru. 2022. The exploited labor behind artificial intelligence. Noema Magazine 22 (2022).
- Chunting Zhou, Pengfei Liu, Puxin Xu, Srinivasan Iyer, Jiao Sun, Yuning Mao, Xuezhe Ma, Avia Efrat, Ping Yu, Lili Yu, et al. 2024. Lima: Less is more for alignment. Advances in Neural Information Processing Systems 36 (2024).
- Yukun Zhu, Ryan Kiros, Richard Zemel, Ruslan Salakhutdinov, Raquel Urtasun, Antonio Torralba, and Sanja Fidler. 2015. Aligning books and movies: Towards story-like visual explanations by watching movies and reading books. In <u>Proceedings of the</u> <u>IEEE international conference on computer vision</u>. 19–27.