# Constructions of Covering Sequences and Arrays

Yeow Meng Chee\*, Tuvi Etzion\*<sup>†</sup>, Hoang Ta\*, and Van Khu Vu\*

\*Department of Industrial Systems Engineering and Management, National University of Singapore, Singapore †Department of Computer Science, Technion — Israel Institute of Technology, Haifa, 3200003 Israel

#### Abstract

An (n, R)-covering sequence is a cyclic sequence whose consecutive *n*-tuples form a code of length *n* and covering radius *R*. Using several construction methods improvements of the upper bounds on the length of such sequences for  $n \le 20$  and  $1 \le R \le 3$ , are obtained. The definition is generalized in two directions. An (n, m, R)-covering sequence code is a set of cyclic sequences of length *m* whose consecutive *n*-tuples form a code of length *n* and covering radius *R*. The definition is also generalized to arrays in which the  $m \times n$  sub-matrices form a covering code with covering radius *R*. We prove that asymptotically there are covering sequences that attain the sphere-covering bound up to a constant factor.

#### I. INTRODUCTION

An (n, R)-covering code C is a set of words of length n over a given alphabet  $\Sigma_q$ , of size q, such that each word of length n over  $\Sigma_q$  is within distance R from at least one codeword in C. In other words, for each  $x \in \Sigma_q^n$ , there exists  $c \in C$  such that  $d(x, c) \leq R$ , where d(y, z),  $y, z \in \Sigma_q^n$ , denotes the Hamming distance between y and z.

Chung and Cooper [10] generalized the notion of an (n, R)-covering code of length n and radius R to a cyclic sequence whose consecutive n-tuples form a covering code of length n and radius R. They called such a structure a de Bruijn covering code since n-tuples of a cyclic sequence are considered and this sequence forms a cycle in the de Bruijn graph. However, any cyclic sequence can be viewed as a cycle in the de Bruijn graph, and the sequence itself has a very loose connection to the de Bruijn graph, although some of the constructions in the paper use ingredients and concepts from the de Bruijn graph. Therefore, we prefer to call such a sequence a *covering sequence*. This is a dual definition of what is known as a robust sequence, i.e., a sequence whose consecutive n-tuples form an error-correcting code of length n and minimum distance d. Such sequences as well as arrays have been considered for example in [1], [7], [8], [26], [32], [35], [44], [47] and they have variety of applications.

All the discussion from Section III will be restricted to the binary alphabet and hence alphabet size will rarely be mentioned. However, many of the ideas that will be presented can be generalized quite easily to any alphabet size. An (n, R)-covering sequence (an (n, R)-CS for short) is a cyclic sequence whose consecutive *n*-tuples form an (n, R)-covering code. This structure was first defined and analyzed in [10]. To find the shortest (n, R)-CS, denoted by  $\mathcal{L}(n, R)$ , we define two more related structures of cyclic sequence codes. A cyclic covering sequence code contains sequences in which the consecutive *n*-tuples of all the sequences form an (n, R)-covering code. Such codes will be discussed in our exposition.

In recent years many one-dimensional coding problems have been considered in the two-dimensional framework due to modern applications. This is quite natural and has become fashionable from both theoretical and practical points of view. Such generalizations were considered for various structures such as error-correcting codes [2], [38], burst-correcting codes [3], [5], [22], [23], constrained codes [39], [43], de Bruijn sequences [14], [17], [34], [37], M-sequences where the two dimensional sequences are pseudo-random arrays [16], [33]. Other structures designed for applications are robust self-location arrays with window property [7] and structured-light patterns [36]. Therefore, it is very tempting to generalize the concept of covering sequences into a two-dimensional framework and this is one of the targets of the current work. An  $(m \times n, R)$ -covering array (an  $(m \times n, R)$ -CA for short) is a doubly-periodic  $M \times N$  array (cyclic horizontally and vertically like a torus) over an alphabet of size q such that the set of all

its  $m \times n$  windows form a covering code with radius R. While in the one-dimensional case we are interested in the (n, R)-CS of the shortest length, in the two-dimensional case we are interested in the  $(m \times n, R)$ -CA with the smallest area, but the ratio between M and N can be important too.

Our goals in this paper are to present construction methods for covering sequences, covering sequence codes, and covering arrays. Some of the constructions yield sequences and codes that are almost optimal.

The rest of the paper is organized as follows. In Section II, some basic results and important known results on covering codes and covering sequences are presented. Section III is devoted to cyclic covering sequence codes and the constructions of covering sequences from cyclic covering sequence codes. In Section IV a cyclic covering sequence code based on self-dual sequences is presented. Based on this code a relatively short  $(2^k, 1)$ -CS whose length is with factor of 1.25 from the sphere-covering bound is obtained. An interleaving construction to obtain an (n, R)-CS from an  $(n_1, R_1)$ -CS and an  $(n_2, R_2)$ -CS, where  $n = n_1 + n_2$  and  $R = R_1 + R_2$  is presented in Section V. When  $n_1 = n_2$  and  $R_1 = R_2$ a better interleaving construction is presented. A construction based on primitive polynomials, with a certain structure, is presented in Section VI. Section VII is the only one devoted to covering arrays and introduces two methods to generate such arrays: one is by folding a covering sequence and the other is by making all possible shifts of a related covering sequence. These methods are used to obtain upper bounds on the size of such arrays and to construct them. Finally, conclusion and further problems for future research are presented in Section VIII.

#### **II. PRELIMINARIES**

The area of covering codes is very well established in information theory as a dual for error-correcting codes. An excellent book that covers all aspects of such codes is [11]. Bounds on the sizes of such codes were extensively studied, where the upper bounds are either by constructions or using probabilistic methods to prove the existence of some codes asymptotically. Lower bounds are usually obtained by analytic methods, but they are usually not much better than the sphere-covering bound which is the most basic bound.

A ball of radius R around a word x of length n is the set of words whose distance is at most R from  $\boldsymbol{x}$ . The size of such ball denoted by  $V_q(n, R)$  is

$$V_q(n,R) = \sum_{i=0}^R \binom{n}{i} (q-1)^i \; .$$

Since the balls of radius R around the codewords of an (n, R)-covering code C contain the whole space, it follows that a lower bound on the size of C is

$$|\mathcal{C}| \ge \frac{q^n}{V_q(n,R)}.$$

This bound is the *sphere-covering bound*. There exists a covering code that approaches this bound up to a factor roughly  $eR \log R$  [31]. The proof method for this bound is probabilistic. A similar bound for an (n, R)-CS over a prime power alphabet was presented in [10]. This bound was generalized to any alphabet by Vu [46]. The bound states that for fixed R there exists an (n, R)-CS, over  $\Sigma_q$ , whose length is at most  $\mathcal{O}\left(\frac{q^n}{V_q(n,R)}\log n\right)$ . This result of Vu [46] was generalized in our conference paper [9] where we proved the following

**Theorem 1.** Let m, n be nonnegative integers. For any  $M \ge m$ , there exists an  $M \times N$   $(m \times n, R)$ -CA such that  $M \cdot N = \mathcal{O}\left(\frac{q^{mn}}{V_q(mn,R)} \cdot (\log m + \log n)\right)$ , for fixed q and R.

The proof of Theorem 1 was presented in [9] using a probabilistic method and will not be proved here since using the one-dimensional asymptotic bound and a folding technique which will be presented in Section VII a similar result can be obtained.

For small R, there are some (n, R)-covering codes that attain the sphere-covering bound with equality, such as the Hamming codes of length  $n = 2^k - 1$  and radius one. Other codes are very close to the upper bound, such as the ones for R = 2 which are perfect asymptotically [42, Construction 4.24] or other similar codes [18], [20]. Similarly, such sparse covering codes were also considered for R = 3 [18], [20]. The main goal of the research on (n, R)-CSs is to get as close as possible to the upper bounds obtained for covering codes.

One of our constructions will use a span n de Bruijn sequence over  $\Sigma_q$ . This is a cyclic sequence of length  $q^n$ , where each n-tuple over  $\Sigma_q$  is contained in exactly one window of consecutive digits in the sequence. Such sequences exist for all  $q \ge 2$  and  $n \ge 1$ .

Finally, one very trivial bound which was mentioned in [10] will be used in one of the best known bounds (see Table I).

**Theorem 2.** For any  $n, R \ge 1$  we have that  $\mathcal{L}(n, R) \le \mathcal{L}(n+1, R)$ .

#### III. CONSTRUCTION FROM A CYCLIC COVERING CODE

Cyclic covering codes are perhaps the most important ingredients in constructions of (n, R)-CSs, especially when n and R are relatively small. They were considered in various papers, e.g. [12], [13], [27], [30]. There are two definitions for covering sequence codes. An (n, m, R)-CS code (an (n, m, R)-CSC for short) C is a set of cyclic codewords of length m such that each word of length n is within distance R from at least one n-tuple of C, i.e., the consecutive n-tuples of all the codewords form an (n, R)-covering code. An (n, R)-CS code (an (n, R)-CSC for short) C is a set of cyclic words of possibly different lengths such that each word of length n is within distance R from at least one window of length n in one of the sequences, i.e., the consecutive n-tuples of all the codewords form an (n, R)-covering code. The only distinction between the two types of codes is that in the first one of an (n, m, R)-CSC, all codewords have the same length m and in the second one of an (n, R)-CSC codewords can be of different lengths. The (n, R)-CS is a cyclic sequence and hence it is a cyclic covering sequence code with one codeword. The natural criteria to compare different (n, m, R)-CSCs is the total length of all the sequences in each code. Another criteria for comparison between CSCs which is important in our exposition is the length of the (n, R)-CS that can be constructed by combining the codewords of each CSC. The sequences of the code are combined by first concatenating the first n-1 bits of each sequence after its last bit. This converts a cyclic sequence to an acyclic sequence, where both sequences have the same *n*-tuples. After the sequences become acyclic, we order the sequences in a cyclic list, where two consecutive sequences in the list overlap such that the suffix of the first sequence aligns with the prefix of the next sequence. The target is to have the total overlaps (sum of the lengths of all the overlaps) as large as possible. For this purpose, when we concatenate the suffix of length n-1 after the last bit of the codeword, we should try to do it for every cyclic shift of the codeword and ultimately use the shifts that yield the largest total overlaps. Merging all the sequences together is done following the order of the list, where each overlap is taken naturally only once. Finally, there might be sequences in the code with periodicity. The periodicity should be eliminated either within the code or in the final (n, R)-CS. This is demonstrated in the following example.

**Example 3.** The following eight codewords form a (9, 10, 1)-CSC C:

[1000010000], [0001001101], [1001111001], [1111010111], [1010101010], [0101011000], [0110111001], [0111010000].

We extend each cyclic sequence by eight bits to obtain all the 9-tuples of the cyclic sequences in acyclic sequences, We furthermore find the largest overlap between the suffix of any acyclic sequence and the prefix of the next acyclic sequence in a created list (including the last sequence in the list and

the first sequence in the list). The obtained eight acyclic sequences of length 18 are as follows, where the overlap is written after the sequence:

the sequence	over lap
100001000010000100	6
000100110100010011	5
100111100110011110	5
111101011111110101	5
101010101010101010	5
010101100001010110	4
011011100101101110	5
011101000001110100	3

The total number of bits in the eight sequences is 144 and the total number of overlaps is 38. This yield a (9, 1)-CS of length 144 - 38 = 106 as follows:

## 

However, the codeword [1000010000] of C is periodic and contains only five 9-tuples as the cyclic sequence [10000]. Moreover, the codeword [1010101010] of C is also periodic and it contains only two 9-tuples as the cyclic sequence [10]. Hence, they are redundant in the code and in the final (9,1)-CS. Therefore, we can eliminate the redundancy in the covering sequence and obtain the following (9,1)-CS of length 106 - 13 = 93:

## 

Introducing the codewords [10000] instead of [1000010000] and [10] instead of [1010101010] in the code C yields a (9,1)-CSC with 6 codewords of length 10, one codeword of length 5, and one codeword of length 2.

This sequence of length 93 can be extended to a (9, 1)-CS of length 102 with 8 consecutive *ones* which will be required later:

Many of the shortest (n, R)-CSs for small n and R were found by computer search. For this purpose we use the well-known problem of the *Shortest Cyclic Superstring (SCS)*. This problem is designed to find the shortest cyclic superstring, i.e. to find a short sequence as possible which contains all the sequences of a given set S as subsequences. The acyclic version of the SCS problem, which find the shortest superstring, has been extensively studied in the literature. This problem has numerous applications in data compression [41] and computational biology [25]. However, the problem is known to be NP-complete [24] and even APX-complete [4], indicating that polynomial-time approximation schemes with arbitrary constant approximations are not to be expected. Many greedy and approximation algorithms have been developed to tackle this problem, and they have demonstrated numerical efficiency [28], [29], [40]. Furthermore, we note that any solution for the acyclic SCS problem can also be considered a feasible solution for the cyclic SCS problem. In our variant to the problem we built a complete directed graph which represent all the sequences of the code C and their possible overlaps with all the other sequences that follow them. For this purpose we use the well-known approximation algorithm for the set cover problem [45, Chapter 2].

While comparing codes with codewords of different lengths is not trivial, it is much easier to compare codes in which all codewords have the same length. Given two (n, m, R)-CSCs, it is obvious that the code with a smaller number of codewords will be considered better. Given two codes,  $C_1$  an  $(n, m_1, R)$ -CSC and  $C_2$  an  $(n, m_2, R)$ -CSC where the total length of the codewords is smaller in  $C_1$  and  $m_1 \ge m_2$ , then  $C_1$  is considered superior to  $C_2$ . However, if the total length of the codewords in  $C_1$  is smaller and  $m_1 < m_2$ , then the two codes are incomparable. Nevertheless, there should be some tradeoff between the two parameters. We demonstrate these concepts for a length  $n = 2^k - 1$  in this section and for a length  $n = 2^k$  in Section IV.

For a length  $n = 2^k - 1$  we consider the Hamming code C. The Hamming code C of length  $2^k - 1$  can be represented as a cyclic covering code that contains  $2^{2^k-k-1}$  codewords. If c is a codeword in C then all the cyclic shifts of c are also codewords in C. Each codeword of C has d distinct cyclic shifts, where d is a divisor of n. For example, the all-zero word is a codeword and it has one distinct cyclic shift. From the set of d distinct cyclic shifts only one is considered in the code.

**Example 4.** For n = 15, we consider the cyclic Hamming code of length 15. It has 134 codewords of length 15, 6 codewords of length 5, 2 codewords of length 3, and 2 codewords of length 1. Together, these 144 codewords contain 2048 words of length 15 which form the Hamming code of length 15. They are merged to form a (15, 1)-CS of length 3600 (see Appendix A-C) compared to a lower bound 2048 obtained by the sphere-covering bound.

In general, the Hamming code C contains  $2^{2^k-k-1}$  codewords. There are at most

$$\sum_{l \mid n, d < n} 2^{d} \le 2^{\lfloor \frac{n}{2} \rfloor + 1} < 2^{2^{k-1}}$$

cyclic words that contain less than *n* distinct cyclic shifts (see [15, p. 105, Lemma 3.20]). Thus, the  $(2^k - 1, 2^k - 1, 1)$ -CSC code contains much less than  $\frac{2^{2^k - k - 1}}{2^k - 1} + 2^{2^{k-1}}$  codewords and hence asymptotically it is an optimal CSC.

We can make a more precise computation when  $n = 2^k - 1$  is a prime. In this case only two codewords, the all-zero codeword and the all-one codeword have less than n distinct shifts. Therefore, the number of codewords in the  $(2^k - 1, 2^k - 1, 1)$ -CSC is  $\frac{2^{2^k - k - 1} - 2}{2^k - 1} + 2$ . To obtain a  $(2^k - 1, 1)$ -CS we have to add to each sequence at most  $2^k - 2$  bits to convert it to acyclic sequence which contains all its words of length  $2^k - 1$ . The  $(2^k - 1, 1)$ -CS that is generated has length shorter than  $2^{2^k - k}$ , i.e., within factor of at most 2 from optimality.

#### **IV. CONSTRUCTION FROM SELF-DUAL SEQUENCES**

In this section, we continue with the construction of cyclic codes as presented in Section III by using a specific family of sequences called self-dual sequences. A self-dual sequence is a cyclic sequence Swhose complement  $\overline{S}$  is the same sequence as S after another shift. The construction will be described to fit n which is a power of two, but it can be generalized to other values of n. For a given word of length nwe are interested in self-dual sequences of length 2n. Such sequences are of the form  $[X \ \overline{X}]$ , where Xis a sequence of length n and  $[X \ \overline{X}]$  has no periodicity since its length is a power of 2. The construction for self-dual sequences starts with a (n, 2n, 1)-CSC C in which for each n-tuple U of a codeword in Cthere exists exactly one other n-tuple V of a codeword in C such that d(U, V) = 1. For this purpose, the code C will be designed in such a way that if  $[X\overline{X}]$  is a codeword in C, then there exists exactly one codeword  $[Y, \overline{Y}]$  in C such that d(X, Y) = 1. This immediately implies the following observation [6].

**Lemma 5.** The *n*-tuples in the codeword of C form an (n, 1)-covering code C for which each codeword  $c \in C$  there exists exactly one other codeword  $c' \in C$  such that d(c, c') = 1.

Now, we are in a position to present a construction for an (n, 1)-CS based on self-dual sequences of length 2n. The computation of the sizes of the codes and the correctness of the details can be found in [6].

**Construction 1.** Let  $C_n$  be an (n, 2n, 1)-CSC code,  $n = 2^k$ , with  $2^{2^k-2k-1}$  sequences, all of them are self-dual. Moreover, if  $c \in C$  then there exists a shift  $[X \ \overline{X}]$  of c for which C has exactly one other codeword  $[X' \ \overline{X}']$ , where X' differs from X only in the last coordinate.

Let  $\mathcal{E}_n$  be the set of all  $2^{n-2}$  even-weight words in  $\mathbb{F}_2^n$  that start with a zero. Let  $\mathcal{C}_{2n}$  be the code with self-dual sequences of length 4n defined by

$$\mathcal{C}_{2n} \triangleq \{ [U \ U + X \ \bar{U} \ \bar{U} + X] : U \in \mathcal{E}_n, \ [X \ \bar{X}] \in \mathcal{C}_n] \}, \tag{1}$$

where the basis is

 $C_8 = [0001101111100100], [0001101011100101]$ 

In a very similar way to the proof of the same construction presented in [6] we have the following result.

**Theorem 6.** The code  $C_{2n}$ ,  $n = 2^k$ , of Construction 1 is an (2n, 4n, 1)-CSC with  $2^{2^{k+1}-2k-3}$  codewords which are self-dual sequences of length  $2^{k+1}$ . If a codeword is in  $C_{2n}$  then it has the form  $[X \ \bar{X}]$  and  $[X' \ \bar{X}']$  is another codeword in  $C_{2n}$ .

**Remark 7.** Construction 1 is very similar to the constructions presented in [19], [21]. The construction based on self-dual sequences was found by one of the authors and was motivated by the introduction of nearly-perfect covering codes [6]. It was first introduced for the earlier conference version of this paper [9].

From the two codewords of  $C_8$ , we can form the optimal (8, 1)-CS of length 32

 $\begin{bmatrix} 0001101111100100 & 0001101011100101 \end{bmatrix} .$ 

Construction 1 is applied on  $C_8$  to obtain a (16, 32, 1)-CSC with 128 codewords of length 32. These 128 codewords are partitioned into 64 pairs of the form

$$[X \ \bar{X}]$$
 and  $[X' \ \bar{X}']$ .

Each pair is combined into one sequence of length 64 that contains all the 16-tuples of the original two codewords of length 32. Hence, this code is an optimal (16, 64, 1)-CSC of length 64 with 64 codewords. Trivially, each sequence can be extended with its first 15 bits to an acyclic sequence of length 64 + 15 = 79. In other words, these 64 sequences can be concatenated to form a (16, 1)-CS of length  $64 \cdot (64 + 15) = 5056$ . However, we can merge these sequences with overlaps between the suffixes and the prefixes of the sequences and obtain a (16, 1)-CS of length 4462 (see Appendix A-D), where the known lower bound, for a (16, 1)-covering code, is 4096. The same idea can be applied recursively on the 64 pairs of sequences of length 32 to obtain an upper bound on the shortest length of a  $(2^k, 1)$ -CS.

For  $n = 2^k$ , k > 2, we obtain a  $(2^k, 2^{k+2}, 1)$ -CSC of length  $2^{k+2}$  with  $2^{2^k-2k-2}$  codewords. This code is optimal as the total length of the codewords is the same as the number of codewords in an optimal  $(2^k, 1)$ -covering code. Without considering any overlap we can merge these  $2^{2^k-2k-2}$  sequences, whose length is  $2^{k+2} + 2^k - 1$  (the n-1 prefix is concatenated after the last bit of each sequence) as an acyclic sequence, to obtain a  $(2^k, 1)$ -CS of length  $2^{2^k-2k-2}(2^{k+2}+2^k-1)$ . We can also compute some overlaps between the prefixes and the suffixes of these sequences; however, we omit this computation due to its complexity. The number of codewords in an optimal  $(2^k, 1)$ -covering code is  $K = 2^{2^k-k}$ , so this sequence has a length of less than 1.25K, i.e., within factor of at most 1.25 from optimality.

#### V. INTERLEAVING OF COVERING SEQUENCES:

Interleaving is probably the most simple method to construct (n, R)-CSs with a large length and a large covering radius from two or more covering sequences of smaller length and a smaller covering radius. When two covering sequences participate in the construction, one is an  $(n_1, R_1)$ -CS of length  $k_1$  and th other is an  $(n_2, R_2)$ -covering sequence of length  $k_2$ , where  $n_2 \le n_1 \le n_2 + 1$  and  $gcd(k_1, k_2) = 1$ . From these two covering sequences we generate an  $(n_1 + n_2, R_1 + R_2)$ -CS of length  $2k_1k_2$ .

**Construction 2.** Let  $\mathcal{A} = [a_0, a_1, \dots, a_{k_1-1}]$  be an  $(n_1, R_1)$ -CS and  $\mathcal{B} = [b_0, b_1, \dots, b_{k_2-1}]$  be an  $(n_2, R_2)$ -CS and assume further that  $n_1 = n_2$  or  $n_1 = n_2 + 1$  and  $gcd(k_1, k_2) = 1$ . The interleaving of  $\mathcal{A}$  and  $\mathcal{B}$ , is the sequence  $\mathcal{S} = [s_0, s_1, \dots, s_{2k_1k_2-1}]$  of length  $2k_1k_2$  defined by  $s_0 = a_0, s_1 = b_0, s_2 = a_1, s_3 = b_1$ , and in general  $s_{2i} = a_i$ , where *i* is taken modulo  $k_1$  and  $s_{2i+1} = b_i$ , where *i* is taken modulo  $k_2$ , for  $0 \le i \le k_1k_2 - 1$ .

**Theorem 8.** If  $n_1 = n_2$  or  $n_1 = n_2 + 1$ , then the sequence S defined in Construction 2 is an  $(n_1 + n_2, R_1 + R_2)$ -CS of length  $2k_1k_2$ .

*Proof.* First note that since  $gcd(k_1, k_2) = 1$ , it follows that for each i and j,  $0 \le i \le k_1 - 1$ ,  $0 \le j \le k_2 - 1$  the string  $a_i b_j a_{i+1} b_{j+1} \cdots a_{i+n_1} b_{j+n_1} a_{i+n_1+1}$ , where indices of  $\mathcal{A}$  are taken modulo  $k_1$  and indices of  $\mathcal{B}$  are taken modulo  $k_2$ , is a subsequence in  $\mathcal{S}$ . This also implies that the length of the sequence is  $2k_1k_2$ . We distinguish between the two cases of  $n_1 = n_2$  and  $n_1 = n_2 + 1$ .

**Case 1:** If  $n_1 = n_2 = n$ , then consider a word  $(\alpha_1, \beta_1, \alpha_2, \beta_2, \ldots, \alpha_n, \beta_n)$ . Since  $\mathcal{A}$  is an  $(n, R_1)$ -CS and  $\mathcal{B}$  is an  $(n, R_2)$ -CS, it follows that there exists a subsequence  $a_i a_{i+1} \cdots a_{i+n-1}$  of  $\mathcal{A}$  whose distance from  $\alpha_1, \alpha_2, \ldots, \alpha_n$  is at most  $R_1$  and there exists a subsequence  $b_j b_{j+1} \cdots b_{j+n-1}$  of  $\mathcal{B}$  whose distance from  $\beta_1, \beta_2, \ldots, \beta_n$  is at most  $R_2$ . Therefore, the subsequence of  $\mathcal{S}$ ,  $a_i b_j a_{i+1} b_{j+1} \cdots a_{i+n-1} b_{j+n-1}$  is within distance at most  $R_1 + R_2$  from  $(\alpha_1, \beta_1, \alpha_2, \beta_2, \ldots, \alpha_n, \beta_n)$ .

**Case 2:** If  $n_1 = n_2 + 1$ , then consider a word  $(\alpha_1, \beta_1, \alpha_2, \beta_2, \ldots, \alpha_{n_2-1}, \beta_{n_2-1}, \alpha_{n_2}, \beta_{n_2}, \alpha_{n_1})$ . Since we have that  $\mathcal{A}$  is an  $(n_1, R_1)$ -CS and  $\mathcal{B}$  is an  $(n_2, R_2)$ -CS, it follows that there exists a subsequence  $a_i a_{i+1} \cdots a_{i+n_1-1}$  of  $\mathcal{A}$  whose distance from  $\alpha_1, \alpha_2, \ldots, \alpha_{n_1}$  is at most  $R_1$  and there exists a subsequence  $b_j b_{j+1} \cdots b_{j+n_2-1}$  of  $\mathcal{B}$  whose distance from  $\beta_1, \beta_2, \ldots, \beta_{n_2}$  is at most  $R_2$ . Therefore, the subsequence of  $\mathcal{S}$ ,  $a_i b_j a_{i+1} b_{j+1} \cdots a_{i+n_2-1} b_{j+n_2-1} a_{i+n_1-1}$  is within distance at most  $R_1 + R_2$  from the word  $(\alpha_1, \beta_1, \alpha_2, \beta_2, \ldots, \alpha_{n_2}, \beta_{n_2}, \alpha_{n_1})$ .

**Example 9.** The following (n, R)-CSs were obtained by using Construction 2 on two shorter covering sequences which are either trivial or presented in Appendix A-A or in Appendix A-B.

Consider the (9,0)-CS of length 512 and a (9,1)-CS length 93. Interleaving these two sequences using Construction 2 yields a (18,1)-CS of length  $2 \cdot 512 \cdot 93 = 95232$ .

Consider the (10, 0)-CS of length 1024 and a (10, 1)-CS length 175. Interleaving these two sequences using Construction 2 yields a (20, 1)-CS of length  $2 \cdot 1024 \cdot 175 = 358400$ .

Consider an (8, 1)-CS of length 32 and a (9, 1)-CS length 93. Interleaving these two sequences using Construction 2 yields a (17, 2)-CS of length  $2 \cdot 32 \cdot 93 = 5952$ .

Consider an (8,1)-CS of length 37 and an (8,2)-CS length 14. Interleaving these two sequences using Construction 2 yields a (16,3)-CS of length  $2 \cdot 37 \cdot 14 = 1036$ .

Consider an (8, 1)-CS of length 37 and a (9, 2)-CS length 20. Interleaving these two sequences using Construction 2 yields a (17, 3)-CS of length  $2 \cdot 37 \cdot 20 = 1480$ .

Consider a (9,1)-CS of length 93 and a (9,2)-CS length 20. Interleaving these two sequences using Construction 2 yields a (18,3)-CS of length  $2 \cdot 93 \cdot 20 = 3720$ .

Consider a (9,1)-CS of length 93 and a (10,2)-CS length 38. Interleaving these two sequences using Construction 2 yields a (19,3)-CS of length  $2 \cdot 93 \cdot 38 = 7068$ .

Consider a (10, 1)-CS of length 175 and a (10, 2)-CS length 38. Interleaving these two sequences using Construction 2 yields a (20, 3)-CS of length  $2 \cdot 175 \cdot 38 = 13300$ .

Construction 2 can be generalized to three or more sequences. When t sequences are interleaved the requirement is that each sequence is an  $(n_i, R_i)$ -CS of length  $k_i$ ,  $1 \le i \le t$ , where  $gcd(k_i, k_j) = 1$ ,  $1 \le i < j \le k$ , and  $n \le n_i \le n + 1$  for some positive integer n. From these t sequences we generate an  $(\sum_{i=1}^t n_i, \sum_{i=1}^t R_i)$ -CS sequence of length  $\ell = t \prod_{i=1}^t k_i$ ,  $[s_0s_1 \cdots s_{\ell-1}]$ , where  $s_r$ ,  $r \equiv j \pmod{t}$ ,  $1 \le j \le t$ , is a bit from the j-th sequence. Unfortunately, the factor t in the length of the sequence makes this construction quite weak for t > 2 and also for t = 2 (see Construction 2) it is not too effective, but some of our best (n, R)-CSs for  $n \le 20$  and  $1 \le R \le 3$  are obtained by this construction. Fortunately, we can get rid of the factor 2 when t = 2 and  $n_1 = n_2$  at the expense of some extra small redundancy as follows.

**Construction 3.** Let  $\mathcal{A} = [a_0, a_1, \dots, a_{k-1}]$  be an (n, R)-CS in which  $a_i = 0$  for  $0 \le i \le n-2$ , i.e.,  $\mathcal{A}$  has a subsequence with n-1 consecutive zeros (the same can be applied for the *ones*). If k is even then form the following sequence  $\mathcal{S}$  presented in k/2 parts. The first part is

$$a_0 a_0 a_1 a_1 \cdots a_{k-1} a_{k-1} a_0 0$$

The second part is

$$a_1 a_0 a_2 a_1 \cdots a_{k-1} a_{k-2} a_0 a_{k-1} a_1 0$$
.

The *i*-th part,  $1 \le i \le k/2$ , is

 $a_{i-1}a_0a_ia_1a_{i+1}a_2 \cdots a_{i-2}a_{k-1}a_{i-1}0$ .

These k/2 parts, each one of length 2k+2, are concatenated together, in their order, to the final sequence S.

If k is odd, then form the same parts, where the last one is for  $i = \frac{k+1}{2}$ .

**Theorem 10.** The sequence S defined in Construction 3 is an (2n, 2R)-CS of length k(k+1) if k is even and  $(k+1)^2$  if k is odd.

*Proof.* The proof is essentially as the one of Theorem 8. The main difference is that the two sequences  $\mathcal{A}$  and  $\mathcal{B}$  in Construction 2 is replaced with only one sequence in Theorem 8. The sequence  $\mathcal{B}$  is replaced by  $\mathcal{A}$  to which a *zero* is concatenated at the end. All the associated shifts between the different positions of the sequence are guaranteed by the different parts. The 0 at the end of each part makes sure that we will move to another shift of  $\mathcal{A}$ . It does not destroy any *n*-tuples since it can be considered as adding another *zero* to the run of n - 1 *zeros* in one of the interleaved sequences which does not damage any of the covered words of length n.

**Example 11.** The following (n, 2)-CSs were obtained by using Construction 3.

Consider a (8,1)-CS of length 40 with a subsequence of 7 consecutive zeros apply Construction 3 to obtain a (16,2)-CS of length  $40 \cdot 41 = 1640$ .

Consider a (9,1)-CS of length 102 with a subsequence of 8 consecutive *ones* apply Construction 3 to obtain an (18,2)-CS of length  $102 \cdot 103 = 10506$ .

Consider a (10, 1)-CS of length 177 with a subsequence of 9 consecutive zeros apply Construction 3 to obtain a (20, 2)-CS of length  $178 \cdot 178 = 31684$ .

#### VI. A CONSTRUCTION FROM PRIMITIVE POLYNOMIALS

A construction based on a specific type of primitive polynomials usually does not generate a very short sequence. However, one of our specific bounds (see Table I) comes from such a sequence.

Let  $c(x) = \sum_{i=0}^{n} c_i x^i$ , where  $c_n = c_0 = 1$  be an irreducible polynomial. Define the following sequence

$$a_k = \sum_{i=1}^n c_i a_{k-i} \tag{2}$$

with the initial nonzero *n*-tuple  $(a_{-n}, a_{-n+1}, \ldots, a_{-1})$ . If c(x) is a primitive polynomial, then the sequence  $\mathcal{A} = [a_0, a_1, a_2, \ldots]$  is called an M-sequence and its period is period  $2^n - 1$ . In this sequence each nonzero *n*-tuple appears exactly once as a window of length *n*. Consider now another recursion for a sequence defined by

$$b_k = \sum_{i=1}^n c_i b_{k-i} + 1$$
(3)

with the initial nonzero *n*-tuple  $(b_{-n}, b_{-n+1}, \ldots, b_{-1})$ .

**Lemma 12.** The sum  $\sum_{i=1}^{n} c_i$  is an even integer.

*Proof.* This follows from the fact that after *n* consecutive *ones* we should have a *zero* in such a sequence. Another argument is that if  $\sum_{i=1}^{n} c_i$  is an odd integer, then  $\sum_{i=0}^{n} c_i = 0$ , 1 is a root of c(x) and hence c(x) is not a primitive polynomial.

**Lemma 13.** The sequence  $\mathcal{B} = (b_0, b_1, b_2, ...)$  is the binary complement of the sequence  $\mathcal{A}$ .

*Proof.* Let  $\mathbf{a} \triangleq (a_j, a_{j+1}, \dots, a_{j+n-1})$  be an *n*-tuple in the sequence  $\mathcal{A}$ . By Equation (2) we have that

$$a_{j+n} = \sum_{i=1}^{n} c_i a_{j+n-i}$$

Let  $\mathbf{b} \triangleq (b_j, b_{j+1}, \dots, b_{j+n-1})$  be an *n*-tuple in the sequence  $\mathcal{B}$ , where  $b_i = a_i + 1$ , for  $j \le i \le j + n - 1$ , i.e.,  $\mathbf{b} = \bar{\mathbf{a}}$ . Therefore, we have that

$$b_{j+n} = \sum_{i=1}^{n} c_i b_{j+n-i} + 1 = \sum_{i=1}^{n} c_i (a_{j+n-i} + 1) + 1 = \sum_{i=1}^{n} c_i a_{j+n-i} + \sum_{i=1}^{n} c_i + 1$$
$$= \sum_{i=1}^{n} c_i a_{j+n-i} + 1 = a_{j+n} + 1$$

This implies that the sequence  $\mathcal{B}$  is the binary complement of the sequence  $\mathcal{A}$ .

**Corollary 14.** The recursion of Equation (2) generates the sequence A and the all-zero sequence. The recursion of Equation (3) generates the sequence  $B = \overline{A}$  and the all-one sequence.

**Lemma 15.** Let  $c(x) = \sum_{i=0}^{n} c_i x^i$  be a primitive polynomial for which  $c_i = 0$  for  $1 \le i \le 2R + 1$  and consider the sequences  $\mathcal{A}$ ,  $\mathcal{B}$ , the all-zeros sequence and the all-ones sequence. The code that contains these four sequences is an (n + 2R + 1, R)-CSC.

*Proof.* Let X be any given n-tuple. Since the first 2R + 1  $c_i$ s (except for  $c_0$ ) are zeros, it follows that the last 2R + 1 elements of X are not influencing the result of the next bit for both recursions and hence the addition of the 1 in the sequence  $\mathcal{B}$  implies that the next 2R + 1 bits after X in  $\mathcal{A}$  and  $\mathcal{B}$  will be complementing. This implies that  $Xz_1z_2 \cdots z_{2R+1}$  is in the ball of radius R either by an (n+2R+1)-tuple of  $\mathcal{A}$  that starts with X or by an (n+2R+1)-tuple of  $\mathcal{B}$  that starts with X.

The number of sequences of the code defined in Lemma 15 is four and they can be efficiently concatenated to one (n + 2R + 1, R)-CS.

**Theorem 16.** The four sequences of the (n + 2R + 1, R)-CSC can be combined to a (n + 2R + 1, R)-CS of length  $2^{n+1} + 2n + 8R + 2$ .

*Proof.* The span n M-sequence A has length  $2^n - 1$  and the same length has the sequence B. The sequence A has a subsequence of n-1 consecutive zeros and hence it can be combines with the all-zero sequence to an acyclic sequence of length  $2^n + n + 4R + 1$ . The same can be done for the sequence B and

the all-one sequence and the two sequences can be combined with no overlaps to an (n + 2R + 1, R)-CS of length  $2^{n+1} + 2n + 8R + 2$ .

The sequences generated in Theorem 16 can be combined with some overlap to reduce its length, but this will make only a very small improvement in the length of the covering sequence. It should be noted the required primitive polynomials exist for relative small n and larger one.

Finally, in Table I the current best lower and upper bounds on  $\mathcal{L}(n, R)$  are presented, where the lower bounds are either by computer search for very small n or the known lower bound on the smallest size of an (n, R)-covering code.

n	R = 1	R=2	R = 3
9	62-93 <sup>a</sup>	20 <sup>b</sup>	12 <sup>b</sup>
10	107-175 <sup>a</sup>	38 <sup>b</sup>	16 <sup>b</sup>
11	180-283 <sup>a</sup>	38-111 <sup>a</sup>	20 <sup>b</sup>
12	342-597 <sup>a</sup>	62-161 <sup>a</sup>	34-40 <sup>b</sup>
13	598-1172 <sup>a</sup>	97-292 <sup>a</sup>	34-93 <sup>a</sup>
14	1172-2271 <sup>a</sup>	159-525 <sup>a</sup>	44-239 <sup>c</sup>
15	2048-3600 <sup>e</sup>	310-907 <sup>a</sup>	70-406 <sup>a</sup>
16	4096-4462 <sup>f</sup>	512-1640 <sup>c</sup>	115-1036 <sup>d</sup>
17	7419-17719 <sup>a</sup>	859-5952 <sup>d</sup>	187-1480 <sup>d</sup>
18	14564-95232 <sup>d</sup>	1702-10506 <sup>c</sup>	316-3720 <sup>d</sup>
19	26309-176170 <sup>g</sup>	2898-31684 <sup>h</sup>	513-7068 <sup>d</sup>
20	52618-358400 <sup>d</sup>	5330-31684 <sup>c</sup>	892-13300 <sup>d</sup>

Table I: Bounds for the length of the shortest (n, R)-CS for  $9 \le n \le 20$  and R = 1, 2, 3. a - computer search, b - Chung and Cooper [10], c - Construction 3, d - Construction 2, e - from the Hamming code, f - from self-dual sequences, g - from primitive polynomial, h - Theorem 2.

#### VII. FOLDING OF A COVERING SEQUENCE INTO A COVERING ARRAY

After we have looked at covering sequences and covering sequence codes we continue with a generalization of the one-dimensional framework into two-dimensional arrays. The ultimate goal is to construct an  $M \times N$  array  $\mathcal{A}$  in which for each  $m \times n$  matrix  $\mathcal{B}$  there exists an  $m \times n$  submatrix  $\mathcal{X}$  of  $\mathcal{A}$  such that  $d(\mathcal{B}, \mathcal{X}) \leq R$ . Two techniques will be presented in this section. The first one is a folding technique and the second one involves different related shifts of a one-dimensional covering sequence.

For the first technique, folding, we will use the following simple lemma that was already observed in [10].

**Lemma 17.** If there exists an (n, R)-CS of length k, then there exists an (n, R)-CS sequence of length  $k + n - 1 + \epsilon$  for any  $\epsilon \ge 0$ .

*Proof.* If the (n, R)-CS starts at a certain position, then we can append to it the first n-1 bits and any  $\epsilon$  bits after that to keep it an (n, R)-CS.

**Construction 4.** Start with an (mn, R)-CS  $S = s_0, s_1, \ldots, s_{k-1}$  of length k, where w.l.o.g. (without loss of generality) k is divisible by n (see Lemma 17, where  $0 \le \epsilon < n-1$ ). The sequence S is folded row by row into an  $M \times n$  array A, where  $M = \frac{k}{n}$ . The array is extended into an  $M \times (2n-1)$  array A' by adding to each row of the  $M \times n$  array A the next n-1 symbols from S associated with the given row. In other words, the *j*-th row of the array A', where  $0 \le j \le \frac{k}{n} - 1$ , is defined by

$$s_{jn+1}, s_{jn+2}, \dots, s_{jn+n}, s_{jn+n+1}, \dots, s_{jn+2n-1},$$
(4)

where the indices are taken modulo k.

Before proving that  $\mathcal{A}'$  generated in Construction 4 is an  $(m \times n, R)$ -CA we will prove one property of the array  $\mathcal{A}'$ .

**Lemma 18.** The array  $\mathcal{A}'$  generated in Construction 4 contains the  $m \times n$  subarray

where  $0 \le i \le n - 1$ ,  $0 \le j \le \frac{k}{n} - 1$ , and indices are taken modulo k.

*Proof.* This is an immediate consequence of Equation (4) which defines the *j*-th row of the array  $\mathcal{A}'$ .

**Corollary 19.** Each  $m \times n$  matrix obtained by folding row by row mn consecutive bits of S is contained as an  $m \times n$  subarray of A'.

**Theorem 20.** The array  $\mathcal{A}'$  generated in Construction 4 is an  $(m \times n, R)$ -CA.

*Proof.* Given an  $m \times n$  matrix  $\mathcal{B}$  we have to show that there exists an  $m \times n$  subarray  $\mathcal{X}$  of  $\mathcal{A}'$  such that  $d(\mathcal{B}, \mathcal{X}) \leq \mathcal{R}$ . Let  $X_1, X_2, \ldots, X_m$  be the *m* consecutive rows of  $\mathcal{B}$  and let  $\mathcal{T} = X_1 X_2 \cdots X_m$  the sequence of length mn obtained by concatenating them. The sequence  $\mathcal{T}$  has length nm and hence there exists a subsequence  $\mathcal{Y}$  in  $\mathcal{S}$  such that  $d(\mathcal{T}, \mathcal{Y}) \leq R$ . By corollary 19 the  $m \times n$  matrix  $\mathcal{Y}'$  obtained by folding  $\mathcal{Y}$  into an  $m \times n$  matrix is contained in  $\mathcal{A}'$ . Since  $d(\mathcal{T}, \mathcal{Y}) \leq R$  it follows that  $d(\mathcal{B}, \mathcal{Y}') \leq R$  which completes the proof.

Construction 4 implies the following consequence.

**Theorem 21.** If there exists an (mn, R)-CS of length k, where n divides k, then there exists a  $(m \times n, R)$ -CA of size  $M \times N$ , where  $M = \frac{k}{n}$  and N = 2n - 1.

If there exists an (mn, R)-CS of length k, where n does not divide k, then there exists an  $(m \times n, R)$ -CA of size  $M \times N$ , where N = 2n - 1 and  $\frac{k}{n} \le M \le \left\lceil \frac{k}{n} \right\rceil + m$ .

The main disadvantage of Construction 4 is that the width of the array N = 2n - 1 is not large enough compared to the width of the window n. Next, we will be interested in starting with an (mn, R)-CS sequence  $S = [s_0, s_1, s_2, \ldots, s_{k-1}]$  and construct an  $M \times N$   $(m \times n, R)$ -CA for which M will be considerably larger than m and N considerably larger than n and the ratio  $\frac{MN}{k}$  should be as small as possible (i.e., with as little redundancy as possible). There are a few ways to construct such an array using the same principles as in Construction 4. The sequence is partitioned into r subsequences which form an (mn, R)-CSC. The r sequences should be of the same length  $\kappa$  which is divisible by n. From each sequence we create an  $M \times (2n-1)$  array and we concatenate these r arrays into one  $M \times (2nr-r)$  array which is a  $(m \times n, R)$ -CA. The specific details are omitted as they are the same as in Construction 4.

The folding construction is very simple and asymptotically, it yields optimal  $(m \times n, R)$ -CA if the (mn, R)-CS is asymptotically optimal. As we mentioned, Theorem 1 can be obtained by using the folding construction, along with the covering sequence whose existence was proved by Vu [46]. The length of this (mn, R)-CS is close up to a factor of  $\log mn$  from the sphere-covering bound.

It is natural to think that an (mn, R)-CS of length  $k_1$ , will have a smaller length than the area of an  $(m \times n, R)$ -CA with dimension  $M \times N$ , i.e.,  $k_1 \leq M \cdot N$ . This is indeed the case when folding is applied,  $M \cdot N$  is about twice as large as  $k_1$ . However, we provide one more construction for covering arrays from covering sequences, whose outcome is quite surprising as it produces smaller arrays (in area) than the length of the ones obtained by folding the related sequence. Moreover, sometimes it yields an array whose area is smaller than the associated best known covering sequence. This second technique is done by considering different shifts of an one-dimensional (n, R)-CS. It will be presented in two constructions, where the first one is very simple.

**Construction 5.** Let S be an (n, R)-CS of length k.

If k is even, then form an  $(k+1) \times k$  array whose *i*-th row,  $0 \le i \le k-1$  is  $\mathbf{E}^j S$ , where  $j = \sum_{\ell=0}^{i} \ell$ ,  $\mathbf{E}^j S$  is a cyclic shift of S by j positions to the left, i.e.,

$$\mathbf{E}^{j}[s_{0}, s_{1}, \dots, s_{k-1}] = [s_{j}, s_{j+1}, \dots, s_{k-1}, s_{0}, \dots, s_{j-1}],$$

and the k-th row is the same as the (k-1)th row.

If k is odd, then form an  $k \times k$  array whose *i*-th row, where  $0 \le i \le k-1$  is  $\mathbf{E}^{j}S$ ,  $j = \sum_{\ell=0}^{i} \ell$ .

**Theorem 22.** If n is even, then the  $(k + 1) \times k$  array obtained in Construction 5 is an  $(2 \times n, 2R)$ -CA. If n is odd, then the  $k \times k$  array obtained in Construction 5 is an  $(2 \times n, 2R)$ -CA.

*Proof.* Let  $\mathcal{A}$  a  $k \times k$  array obtained in Construction 5 and let  $\mathcal{B}$  a  $2 \times n$  matrix that consists of two sequences (rows) of length n, the first one X and the second one Y. Each row of  $\mathcal{A}$  is the sequence  $\mathcal{S}$  at some shift, where the sequence  $\mathcal{S}$  of the *i*-th row,  $1 \leq i \leq k$ , is shifted by *i* positions to the left compared to the sequence in the (i - 1)-th row. The 0-th row is taken without shifting.

Assume first that k is even. Since S is an (n, R)-CS, it follows that there exists a subsequence U of length n in S such the  $d(X, U) \leq R$  and a subsequence V of length n in S such that  $d(Y, V) \leq R$ . Since S is an (n, R)-CS and all possible shifts are taken between consecutive rows, it follows that in two consecutive rows of A we have the subsequence U and V one on top of the other, i.e., a  $2 \times n$  matrix W such that  $d(W, B) \leq 2R$ . Thus, the  $(k + 1) \times k$  array obtained in Construction 5 is an  $(2 \times n, 2R)$ -CA.

When k is odd the proof is similar, but we have to notice that since  $\sum_{i=1}^{k} i \equiv 0 \pmod{k}$ , it follows that the 0-th row is without any shift compared to the last row and hence one less row is required.  $\Box$ 

**Example 23.** Consider the (6, 1)-CS of length 12 presented in Appendix A-A. By applying the defined shifts of Construction 5 on this sequence which is the first row in the array we obtain a  $13 \times 12$  ( $2 \times 6$ , 2)-CA whose area is 156. The best associated (12, 2)-CS that we find is based on computer search has length 161 (see Appendix A-B). The generated  $13 \times 12$  ( $2 \times 6, 2$ )-CA whose area is 156 which smaller than the related (12, 2)-CS of length 161 that was found by computer search. It is the following array:

0	0	0	1	0	0	1	1	1	0	1	1
0	0	1	0	0	1	1	1	0	1	1	0
1	0	0	1	1	1	0	1	1	0	0	0
1	1	1	0	1	1	0	0	0	1	0	0
1	1	0	0	0	1	0	0	1	1	1	0
1	0	0	1	1	1	0	1	1	0	0	0
0	1	1	0	0	0	1	0	0	1	1	1
0	0	1	1	1	0	1	1	0	0	0	1
0	0	0	1	0	0	1	1	1	0	1	1
0	1	1	0	0	0	1	0	0	1	1	1
1	1	0	1	1	0	0	0	1	0	0	1
1	1	1	0	1	1	0	0	0	1	0	0
1	1	1	0	1	1	0	0	0	1	0	0

**Example 24.** Consider the (7, 1)-CS of length 22 presented in Appendix A-A. By applying the defined shifts of construction 5 on this sequence which is the first row in the array, we obtain a  $23 \times 22$  ( $2 \times 7$ , 2)-CA whose area 506. The best related (14, 2)-CS that we found is based on computer search has length 525 (see Appendix A-B).

Finally, Construction 5 can be generalized as follows.

**Construction 6.** Let S be an (n, R)-CS of length k and let  $\mathcal{T} = [t_1, t_2, \ldots, t_{k^{m-1}}]$  be a span m-1 de Bruijn sequence over  $\Sigma_k$ . We form the following  $k^{m-1} \times k$  array  $\mathcal{A}$ , where the sequence S in the *i*-th

row of A,  $1 \le i \le k^{m-1}$  is shifted  $t_i$  positions related to the sequence S in the (i-1)-th row, where the 0-th row is considered to be with no shift.

### **Theorem 25.** The $k^{m-1} \times k$ array $\mathcal{A}$ of Construction 6 is an $(m \times n, mR)$ -CA.

*Proof.* The proof is very similar to the one of Theorem 22. First note that the sum of all the shifts is zero and hence the virtual 0-th row can be considered to be with no shifts. For any an  $m \times n$  matrix  $\mathcal{B}$  we have to find an  $m \times n$  window  $\mathcal{X}$  in  $\mathcal{A}$  such that  $d(\mathcal{B}, \mathcal{W}) \leq mR$ . Let  $B_1, B_2, \ldots, B_m$  be the m consecutive rows of  $\mathcal{B}$ . Each  $B_i$  has length n and hence there exists a subsequence  $X_i$  of length n in  $\mathcal{S}$  such that  $d(B_i, X_i) \leq R$ . Let  $(i_1, i_2, \ldots, i_{m-1})$  be the m - 1 consecutive shifts of  $\mathcal{S}$  such that these m copies of  $\mathcal{S}$  placed on each other contain  $\mathcal{B}$  as a window. Since  $(i_1, i_2, \ldots, i_{m-1})$  is an (m-1)-tuple over  $\mathbb{Z}_k$  and  $\mathcal{T}$  is a span m - 1 de Bruijn sequence over  $\Sigma_k$  which implies that  $(i_1, i_2, \ldots, i_{m-1})$  is contained in  $\mathcal{T}$ , it follows that the associated shifts of  $\mathcal{S}$  are contained in m consecutive rows of  $\mathcal{A}$ . These shifts contain an  $m \times n$  window  $\mathcal{X}$  whose consecutive rows are  $X_1, X_2, \ldots, X_m$ . Since  $d(X_i, B_i) \leq R$ , it follows that  $d(\mathcal{B}, \mathcal{X}) \leq mR$ .

Thus, the  $k^{m-1} \times k$  array  $\mathcal{A}$  of Construction 6 is an  $(m \times n, mR)$ -CA.

#### 

#### VIII. CONCLUSION AND FUTURE RESEARCH

Covering sequences and covering sequence codes which generalize the well-known covering codes, were considered. Some new construction methods for such covering sequences as well as covering sequence codes were presented. In particular, nearly optimal and asymptotically optimal sequences and codes were obtained using the Hamming codes and self-dual sequences. Finally, generalization of covering arrays was also discussed and related constructions were given.

This area is far from being fully explored and we conclude with the following problems for future research.

- 1) The current work and also all the previous papers that considered this topic, have concentrating on the upper bounds of (n, R)-CSs. The lower bounds mentioned in this paper are the ones used for (n, R)-covering codes. We would like to see improvements in these lower bounds and not just by one or two (something which is not difficult to do).
- 2) Many of the upper bounds used in Table I are quite weak as Construction 2 is used and we do not have for these parameters a stronger construction like Construction 3. We would like to see some new constructions that will make the table more balanced. Similarly, we want to see upper bounds on the sizes of covering sequence codes.
- 3) The  $(2^k 1, 1)$ -CS and the  $(2^k, 1)$ -CS introduced in Sections III and IV are the best covering sequences obtained for small radii. We would like to have a more precise computation on the length of these sequences. We would also like to see similar sequences for radius 2 and radius 3. The Preparata code used to obtain covering codes for radii 2 and 3 [18], [20] might be the ones to use for this purpose.
- 4) We would like to see more constructions as well as lower bounds on the size of covering arrays.
- 5) Finally, we would like to see a more comprehensive study on covering sequence codes as the current work is mainly on covering sequences.

#### APPENDIX A

A. Very small (n, R)-CSs used for other bounds

An (8,1)-CS sequence of length 32 - [00011011111001000001101011100101].

An (8, 1)-CS sequence of length 35 - [00010110110110000100011110110001].

An (8,1)-CS sequence of length 37 - [0001101111100100000110101110011100101].

An (8,1)-CS sequence of length 40 (with 7 consecutive zeros) -

[000110111110010000001000001101011100101].

An (8,2)-CS sequence of length 14 - [00111011010010].

An (9,2)-CS sequence of length 20 - [00010010001110110111].

#### B. Small (n, R)-CSs

The following thirteen codewords form a (10, 11, 1)-CSC:

 $\begin{bmatrix} 00001010000 \end{bmatrix}, \begin{bmatrix} 00101001011 \end{bmatrix}, \begin{bmatrix} 10100101111 \end{bmatrix}, \begin{bmatrix} 10110111001 \end{bmatrix}, \begin{bmatrix} 11011101111 \end{bmatrix}, \\ \begin{bmatrix} 11011101111 \end{bmatrix}, \begin{bmatrix} 01110111100 \end{bmatrix}, \begin{bmatrix} 11110010011 \end{bmatrix}, \begin{bmatrix} 11110010000 \end{bmatrix}, \begin{bmatrix} 11001000101 \end{bmatrix}, \\ \begin{bmatrix} 00100011000 \end{bmatrix}, \begin{bmatrix} 01000110101 \end{bmatrix}, \begin{bmatrix} 10001101001 \end{bmatrix}, \begin{bmatrix} 00011010000 \end{bmatrix}.$ 

Their extension by nine bits and their associated overlaps are as follows:

00001010000000010100	7	01110111100011101111	4	01000110101010001101	8
00101001011001010010	7	11110010011111100100	9	10001101001100011010	8
10100101111101001011	4	11110010000111100100	7	00011010000000110100	2
10110111001101101110	7	11001000101110010001	7		
11011101111110111011	7	00100011000001000110	8		

The total number of bits in the thirteen sequences is 260 and the total number of overlaps is 85. This yields a (10, 1)-CS of length 260 - 85 = 175:

The following thirteen codewords form a (10, 11, 1)-CSC:

 $[11010111111], [01011110000], [10111100101], [11100110011], [11001100001] \\ [00110001101], [10001101100], [1101101010], [01101010010], [10101000011], \\ [10000010010], [00000100000], [00001000101] .$ 

Their extension by nine bits and their associated overlaps are as follows:

110101111111101011111	7	00110001101001100011	6	10000010010100000100	8
01011110000010111100	8	10001101100100011011	5	0000010000000001000	8
10111100101101111001	6	11011010101110110101	7	00001000101000010001	1
11100110011111001100	8	011010010011010100	7		
11001100001110011000	7	10101000011101010000	5		

The total number of bits in the thirteen sequences is 260 and the total number of overlaps is 83. This yields a (10, 1)-CS of length 260 - 83 = 177 with a subsequence having 10 consecutive zeros:

The following twenty codewords form a (11, 11, 1)-CSC:

[00111011011], [01110110100], [1011010100], [10101100010], [10001001011], [10001001010], [0101010111], [01010011010], [01001101110], [1011111110], [1011111111], [1111111001], [11111000010], [11100001100], [00011011001], [01100000000], [000000100000], [00001000001], [00000111101], [00011110011].

Their extension by ten bits and their associated overlaps are as follows:

9	010100110100101001101	8	000110110010001101100	5
7	010011011100100110111	5	01100000000110000000	6
7	10111111101011111111	10	00000010000000001000	8
5	10111111111011111111	8	000010000010000100000	5
10	11111110011111111100	7	000001111010000011110	8
4	1111100001011111100001	8	000111100110001111001	3
8	111000011001110000110	6		
	9 7 7 5 10 4 8	9         01010011010011001101           7         010011011001011011           7         10111111100101111111           5         101111111100111111111           10         111111100111111111           4         11110000101111100001           8         1110000110011000110	9         0101001101001001101         8           7         01001101100100110111         5           7         101111111101011111111         10           5         1011111111011111111         8           10         1111111100111111111         7           4         111110000101111100001         8           8         11100001100110000110         6	9         0101001101001101         8         000110110010001101100           7         0100110110000110111         5         01100000000011000000           7         101111111001011111111         10         000000000000000000           5         1011111111100111111111         8         0000100000000000000000           10         111111100111111111         8         00001000001000010000           4         1111000010111100001         8         00011110011001111001           8         111000011001110000110         6         6

The total number of bits in the twenty sequences is 420 and the total number of overlaps is 137. This yields a (11, 1)-CS of length 420 - 137 = 283:

The following sequence is a (14, 1)-CS of length 2271:

15

11111000010000111110000100010010100001000100010010010010001000

The following sequences is a (13, 1)-CS of length 1172:

The following sequences is a (12, 1)-CS of length 597:

00110000011000010110000011000].

The following six codewords form a (11, 15, 2)-CSC:

[110011101001001], [111010111001011], [110101110000000], [010111001000000], [100101000111101], [001010001101100].

Their extension by ten bits and their associated overlaps are as follows:

1100111010010011100111010	6	1101011100000001101011100	8	1001010001111011001010001	9
1110101110010111110101110	9	0101110010000000101110010	5	0010100011011000010100011	2

The total number of bits in the six sequences is 150 and the total number of overlaps is 39. This yields a (11, 2)-CS of length 150 - 39 = 111:

The following nine codewords form a (12, 13, 2)-CSC:

[1000101000010], [010000000100], [1000000001101], [0000110101101], [1010110011110], [1001110110000], [1000111001001], [1100101111100], [1100101111111].

Their extension by eleven bits and their associated overlaps are as follows:

100010100001010001010000	6	000011010110100001101011	6	100011100100110001110010	6
01000000010001000000001	10	101011001111010101100111	6	110010111110011001011111	11
1000000011011000000011	6	100111011000010011101100	3	1100101111111110010111111	1

The total number of bits in the nine sequences is 216 and the total number of overlaps is 55. This yields a (12, 2)-CS of length 216 - 55 = 161:

The following sixteen codewords form a (13, 13, 2)-CSC:

[1111111001011], [1001010011010], [010100110110], [0011011000110], [0110001100101], [0011001011011], [0101101000001], [1011010000011], [0001001001111], [0100111010111], [101111110111], [1111011100000], [1110000010001], [1000001000000], [0000000111001], [0111000100001].

Their extension by twelve bits and their associated overlaps are as follows:

11111110010111111111100101	6	0101101000001010110100000	11	1110000010001111000001000	10
1001010011010100101001101	10	1011010000011101101000001	4	100000100000100000100000	5
0101001101101010100110110	8	0001001001111000100100111	7	0000000111001000000011100	6
0011011000110001101100011	8	0100111010111010011101011	4	0111000100001011100010000	0
0110001100101011000110010	8	10111111011110111111111011	7		
0011001011011001100101101	7	1111011100000111101110000	7		

The total number of bits in the sixteen sequences is 400 and the total number of overlaps is 108. This yields a (13, 2)-CS of length 400 - 108 = 292:

The following sequence is a (14, 2)-CS of length 525:

The following sequence is a (15, 2)-CS of length 907:

0101011].

The following five codewords form a (13, 13, 3)-CSC:

[0110111110111], [1111101100010], [0110001101000], [1101000001001], [0100000100000].

Their extension by twelve bits and their associated overlaps are as follows:

01101111101110110111111011	8	0110001101000011000110100	6	0100001000001000010000	1
11111011000101111110110001	7	1101000001001110100000100	10	0100001000001000010000	1

The total number of bits in the five sequences is 125 and the total number of overlaps is 32. This yields a (13,3)-CS of length 125 - 32 = 93:

The following ten codewords form a (14, 15, 3)-CSC:

 $[11001100000010], [0110101001111], [010011101011110], [110101111000100], \\ [000101100001001], [10110101111101], [11111110001101], [000111011001010], \\ [001001000010000], [010100001100010] .$ 

Their extension by thirteen bits and their associated overlaps are as follows:

1100110000000101100110000000	1	0001011000010010001011000010	2	001001000101000001001001010	5
0110101010011110110101010011	6	10110101111110110110101111111	6	0101001000101000010100001010	0
0100111010111100100111010111	8	1111111100011011111111100011	5	0101000011000101000011000	0
1101011110001001101011110001	4	0001110110010100001110110010	4		

The total number of bits in the ten sequences is 280 and the total number of overlaps is 41. This yields a (14, 3)-CS of length 280 - 41 = 239:

The following sequence is a (15, 3)-CS of length 406:

00001011101010100001011101010	1				
00010011001110100010011001110	1	00001110110010100001110110010	4	000100111111001000100111111100	$^{2}$
00001010001110100001010001110	7	00101110100110100101110100110	1	00000110011100100000110011100	<b>2</b>
00011100111111100011100111111	8	00000101100110100000101100110	1	0000000100111100000000100111	10
001111111110101001111111111010	1	00000011110110100000011110110	1	00001001110100100001001110100	<b>2</b>
00010011100101100010011100101	5	00000010010010100000010010010	8	0000000010101100000000010101	10
00101101101110100101101101110	1	10010010010010010010010010010010	7	00000101010100100000101010100	2
00000111100001100000111100001	6	00100101011001100100101011001	3	00001101001000100001101001000	3
10000100001000010000100001000	8	00100101110010100100101110010	1	00001011011000100001011011000	3
00001000100010100001000100010	9	00000001011010100000001011010	10	00000111111000100000111111000	3
00010001001001100010001001001	9	00010110100100100010110100100	5	00000001101000100000001101000	3
00100100111101100100100111101	8	00100111011110100100111011110	1	00000100110000100000100110000	4
00111101010110100111101010110	1	00011100100110100011100100110	8	00000010100000100000010100000	5
00011001111110100011001111110	1	00100110111010100100110111010	1	00000000000000	10
00011011010010100011011010010	4	00011010110110100011010110110	1	000000000110010000000001100	10
001010111111101001010111111110	1	00001100101100100001100101100	2	00000011000100100000011000100	6
00001101111010100001101111010	1	00010101101100100010101101100	2	00010001100010100010001100010	5
00001110011001100001110011001	7	00001010111100100001010111100	2	00010101000111100010101000111	6
001100110110100110011011010	1	00011111011100100011111011100	2	00011111101110100011111101110	1
00000110101110100000110101110	1	00011001001100100011001001100	2	00010100111010100010100111010	8

The total number of bits in the one hundred forty-four sequences is 4148 and the total number of overlaps is 548. This yields a (15, 1)-CS of length 4148 - 548 = 3600.

## D. (16,1)-CS from Self-Dual Sequences of Length 32

111001001101001100011011001011001001001	11
0100110100100101011011011011010010011010	11
110100100011011000101100100111010011001100100101	9
100011011010010101110010010110100001011010	9
01101001010000011001111010111100110000101	9
010100000010110010101111111001101000000	8
00010110100000101110100101111101000100	7
10000011110001010011110000111010100001111	5
0001011110000111110100001111000001001110000	10
111100001101100000000111001001111111000110110000	8
0110110010001001001001101110110110110001001001001001001110111011001000100	8
01000100001011111011101110100000100010	12
0010000101110000110011100001111001000101	13
1000010111000100011010100011101110010101	12
001011100010100011010001110101110110110	10
11000101000010011101111011110110001000	8
1001000010001010011011110111010010010001000101	7
1000101110111100011000100000110001011101111	8
1101111000100111001000011101100011011110001100010000	7
00100110011000001101100110011101100110	10
1100110000110100110011100101010011000111010	9
000011010111111111001010000000000011011	10
1010111111000000010100000011101110101111	10
11111000001100000000010111001111111101000110000	10

00000110001100011111100111001110000001100011001111	11
0110001100001001100111100111100011000	9
110000100110110000111101100100111100001001111	10
010011011011010010110010010010110110110	9
011011010010011011001001010100100100100	7
0100110000001101101100111111001001011110000	12
0110000001100110100111111001100100100000	9
00011001100110101100110011001010011100110011001100110011001100110010001100011001100110011000110001100110011000110000	6
0011010001110010110010111000110101110000	11
01000111001110111011100011000100010001	10
11100111010111100001100011100001111001110001111	9
1101011110101010000110000111010010101010	7
1010101011111011010101010000010010111010	10
01011111010100101010000010101101110111	8
10101001001110010101001011000110101010	10
001001110001001011011000111011110010011100010000	11
01110001001000001001111011011111011000010010000	11
000100100001010010101101111010110100100	9
10000101011000000111101110011111100001000110000	11
01010110000010101010101010101010101010	10
110000010100001000011110101111011110000101	5
0000101001011011111101011010010000011010	13
001010010110100011010101010101110010110000	8
1011010000100100100111111011011101100000	13
1101000010010110011011110110100110010000	5
0101101111001111101001000011000001011111	10
01111001111011010000010000100100111110111011010	9
01111011001010101000010011010101010101	13
111011001010101001001001101010010111111	10
1001010110001111010100111000110010101010	7
1000111101111010111000010000010100011111	9
11011111000101110010000011101000110111010	12
1111100010111110000001110100000110111000101	11
10001011111101110111010000001000100010	8
11111011011011011010000100100100100001111	10
011011011101001110010010001111000110110	9
01110100101010111100010110101110001110000	8
0101010110011111101010100000010101111001111	12
101011001111000001010011000011111010110011010	11
11001111000100000110000111001111001111000110000	0

The total number of bits in the sixty-four sequences is 5056 and the total number of overlaps is 594. This yields a (16, 1)-CS of length 5056 - 594 = 4462.

#### ACKNOWLEDGEMENT

Parts of the paper were presented in IEEE International Symposium on Information Theory and appeared in *Proceedings IEEE Symposium on Information Theory*, Athens, Greece 2024, pp. 1343–1348.

#### References

- [1] R. BERKOWITZ AND S. KOPPARTY, Robust positioning patterns, in Proc. 27th Annu. ACM-SIAM Disc. Algorithms (2016) 1937–1951.
- [2] M. BLAUM AND J. BRUCK, MDS array codes for correcting criss-cross errors, IEEE Trans. on Infor. Theory, 46 (2000) 1068–1077.
- [3] M. BLAUM, J. BRUCK, A. VARDY, Interleaving schemes for multidimensional cluster errors, *IEEE Trans. on Infor. Theory*, 44 (1998) 730–743.
- [4] A. BLUM, T. JIANG, M. LI, J. TROMP, AND M. YANNAKAKIS, Linear approximation of shortest superstrings, Journal Of The ACM (JACM). 41 (1994) 630–647.

- [5] M. BREITBACH, M. BOSSERT, V. ZYABLOV, V. SIDORENKO, Array codes correcting a two-dimensional cluster of errors, IEEE Trans. on Infor. Theory, 44 (1998) 2025–2031.
- [6] A. BORUCHOVSKY, T. ETZION, AND R. M. ROTH, On nearly perfect covering codes, https://arxiv.org/abs/2405.00258 (2024), IEEE Trans. Infor. Theory, to appear.
- [7] A. M. BRUCKSTEIN, T. ETZION, R. GIRYES, N. GORDON, R. J. HOLT, AND D. SHULDINER, Simple and robust binary self-location patterns, IEEE Trans. on Infor. Theory, 58 (2012) 4884–4889.
- [8] Y. M. CHEE, D. T. DAO, H. M. KIAH, S. LING, AND H. WEI, Robust positioning with low redundancy, SIAM J. Comput. 49 (2020) 284–317.
- [9] Y. M. CHEE, T. ETZION, H. TA, AND V. K. VU, On de Bruijn Covering Sequences and Arrays, in Proceedings IEEE Symposium on Information Theory, Athens, Greece 2024, pp. 1343–1348.
- [10] F. CHUNG AND J. N. COOPER, De bruijn cycles for covering codes, Random Structures & Algorithms, 25 (2004) 421-431.
- [11] G. COHEN, I. HONKALA, S. LITSYN, AND A. LOBSTEIN, Covering Codes, North-Holland, Amsterdam, 1997.
- [12] R. DOUGHERTY AND H. JANWA, Covering radius computations for binary cyclic codes, Mathematics of computation, 57 (1991) 415–434.
- [13] D. DOWNIE AND N. SLOANE, The covering radius of cyclic codes of length up to 31, IEEE Trans. on Infor. Theory, 31 (1985) 446-447.
- [14] T. ETZION, Constructions for perfect maps and pseudorandom arrays, IEEE Trans. on Infor. Theory, 34 (1988) 1308–1316.
- [15] T. ETZION, Sequences and the de Bruijn Graph: Properties, Constructions, and Applications, London, UK; San Diego, US, Cambridge, US: Elsevier, 2024.
- [16] T. ETZION, Pseudo-Random and de Bruijn Array Codes, IEEE Int. Symp. on Inf. Theory, pp. 1742–1747, Athens, Greece, July 2024.
- [17] T. ETZION, On de Bruijn array codes, Part I: nonlinear codes, IEEE Trans. on Infor. Theory, 71 (2025) 1434–1449.
- [18] T. ETZION AND G. GREENBERG, Constructions for perfect mixed Codes and other covering codes, *IEEE Trans. on Infor. Theory*, 39 (1993) 209–214.
- [19] T. ETZION AND A. LEMPEL, Construction of de bruijn sequences of minimal complexity, IEEE Trans. on Infor. Theory, 30 (1984) 705–709.
- [20] T. ETZION AND B. MOUNITS Quasi-perfect codes with small distance, IEEE Trans. on Infor. Theory 51 (2005) 3938–3946.
- [21] T. ETZION AND K. G. PATERSON, Near optimal single-track gray codes, IEEE Trans. on Infor. Theory, 42 (1996) 779–789.
- [22] T. ETZION AND A. VARDY, Two-dimensional interleaving schemes with repetitions: Constructions and bounds, *IEEE Trans. on Infor. Theory*, 48 (2002) 428–457.
- [23] T. ETZION AND E. YAAKOBI, Error-correction of multidimensional bursts, IEEE Trans. on Infor. Theory, 55 (2009) 961–976.
- [24] J. GALLANT, D. MAIER, D., AND J. ASTORER, On finding minimal length superstrings, Journal Of Computer And System Sciences, 20 (1980) 50–58.
- [25] T. GINGERAS, J. MILAZZO, D. SCIAKY, AND R. ROBERTS, Computer programs for the assembly of DNA sequences, Nucleic Acids Research, 7 (1979) 529–543.
- [26] V. HORAN AND B. STEVENS, Locating patterns in the de Bruijn torus, Disc. Math. 339 (2016) 1274–1282.
- [27] H. JANWA, Some new upper bounds on the covering radius of binary linear codes, IEEE Trans. on Infor. Theory, 35 (1989) 110–112.
- [28] T. JIANG AND M. LI, Approximating shortest superstrings with constraints, Theoretical Computer Science. 134 (1994) 473–491.
- [29] H. KAPLAN AND N. SHAFRIR, The greedy algorithm for shortest superstrings, Information Processing Letters. 93 (2005) 13–17.
- [30] S. KAVUT AND S. TUTDERE, The covering radii of a class of binary cyclic codes and some bch codes, Des., Codes and Crypt., 87 (2019) 317–325.
- [31] M. KRIVELEVICH, B. SUDAKOV, AND V. H. VU, Covering codes with improved density, IEEE Trans. on Infor. Theory, 49 (2003) 1812–1815.
- [32] P. V. KUMAR AND V. K. WEI, Minimum distance of logarithmic and fractional partial *m*-sequences, *IEEE Trans. on Infor. Theory*, 38 (1992) 1474–1482.
- [33] F. J. MACWILLIAMS AND N. J. A. SLOANE, Pseudo-random sequences and arrays, Proceedings of the IEEE, 64 (1976) 1715–1729.
- [34] C. J. MITCHELL, Aperiodic and semi-periodic perfect maps, *IEEE Trans. on Infor. Theory*, 41 (1995) 88–95.
- [35] C. J. MITCHELL AND P. R. WILD, Constructing orientable sequences, IEEE Trans. on Infor. Theory, 68 (2022) 4782–4789.
- [36] R. A. MORANO, C. OZTURK, R. CONN, S. DUBIN, S. ZIETZ, AND J. NISSANO, Structured light using pseudorandom codes, IEEE Transactions on Pattern Analysis and Machine Intelligence, 20 (1998) 322–327.
- [37] K. G. PATERSON, Perfect maps, IEEE Trans. on Infor. Theory, 40 (1994) 743-753.
- [38] R. M. ROTH, Maximum-rank array codes and their application to crisscross error correction, *IEEE Trans. on Infor. Theory*, 37 (1991) 328–336.
- [39] M. SCHWARTZ AND J. BRUCK, Constrained codes as networks of relations, IEEE Trans. on Infor. Theory, 54 (2008) 2179–2195.
- [40] G. STEPHEN, String searching algorithms, World Scientific, 1994.
- [41] J. STORER, Data compression: methods and theory, Computer Science Press, Inc., 1987.
- [42] R. STRUIK, Covering codes, Ph.D. thesis, Eindhoven University of Technology, Eindhoven, The Netherlands, 1994.
- [43] I. TAL, T. ETZION, AND R. ROTH, On row-by-row coding for 2d constraints, IEEE Trans. on Infor. Theory, 55 (2009) 3565–3576.
- [44] L. WANG, S. HU, AND O. SHAYEVITZ, Quickest sequence phase detection, IEEE Trans. Infor. Theory 63 (2017) 5834–5849.
- [45] V. VAZIRANI, Approximation algorithms. Springer, 2001.
- [46] V. VU, De bruijn covering codes with arbitrary alphabets, Advances in Applied Mathematics, 34 (2005) 65–70.
- [47] H. WEI, Nearly optimal robust positioning patterns, IEEE Trans. Infor. Theory 68 (2022) 193–203.