RECOVERY GUARANTEES FOR COMPRESSED SENSING PHOTOACOUSTIC TOMOGRAPHY

ALESSANDRO FELISI

ABSTRACT. Photoacoustic tomography is an emerging medical imaging technology whose primary aim is to map the high-contrast optical properties of biological tissues by leveraging high-resolution ultrasound measurements. Mathematically, this can be framed as an inverse source problem for the wave equation over a specific domain. In this work, for the first time, it is shown how, by assuming signal sparsity, it is possible to establish rigorous stable recovery guarantees when the data collection is given by spatial averages restricted to a limited portion of the boundary. Our framework encompasses many approaches that have been considered in the literature. The result is a consequence of a general framework for subsampled inverse problems developed in previous works and refined stability estimates for an inverse problem for the wave equation with surface measurements.

1. INTRODUCTION

Photoacoustic tomography (PAT) is an emerging medical imaging technology, recognized as one of the most sophisticated among hybrid imaging modalities [3, 36, 55, 54, 53]. PAT integrates two distinct forms of energy: electromagnetic (EM) waves, such as light, and acoustic waves, like ultrasound. The core objective of PAT is to map the optical properties of biological tissues, which is particularly valuable for applications such as tumor detection, vascular imaging, and even monitoring oxygen saturation levels in tissues.

The underlying mechanism of PAT is based on the thermoacoustic effect. When tissue is exposed to a brief pulse of EM radiation, it undergoes rapid heating and subsequent thermal expansion. This expansion creates a pressure wave that propagates through the tissue and can be detected by wide-band ultrasonic transducers placed outside the body. Cancerous tissues, absorbing a higher level of EM radiation, generate stronger pressure waves than healthy tissues. By reconstructing the initial distribution of pressure, PAT can produce highly informative data that reveals critical diagnostic details, making it a powerful tool in early disease detection and ongoing medical research.

Date: February 14, 2025.

²⁰²⁰ Mathematics Subject Classification. 35R30.

1.1. Mathematical model and stability issues. In the literature, the following simple model for the pressure wave dynamics, known as the *free space model*, is often considered. We assume that the pressure wave u is generated by an initial pressure u_0 , which is supported within a compact set $K \subset \mathbb{R}^3$. The wave dynamics is described by the wave equation:

(1)
$$\begin{cases} u_{tt} - c^2 \Delta u = 0, & \text{in } \mathbb{R}^3 \times [0, +\infty), \\ u(\cdot, 0) = u_0, & \text{in } \mathbb{R}^3, \\ u_t(\cdot, 0) = 0, & \text{in } \mathbb{R}^3, \end{cases}$$

where c = c(x) represents the speed of propagation in the biological tissue. Here u_t, u_{tt} denote $\partial_t u, \partial_t^2 u$, respectively. The pressure wave u is measured on a (smooth) acquisition surface $\Sigma \subset \mathbb{R}^3$ over a finite time interval [0, T], with $T < +\infty$. Additionally, we assume that K is located at a positive distance from Σ . The reconstruction problem in PAT then reduces to an inverse problem for the wave equation: given $u|_{\Sigma \times [0,T]}$, reconstruct the initial pressure u_0 in a stable manner.

In this paper, we focus on the case where the speed of propagation c is constant, and for simplicity, we assume $c \equiv 1$. For more detailed studies addressing the case of non-constant c, we refer the reader to [4, 49, 50, 14, 51, 52, 42]. Additionally, we highlight an alternative and possibly more accurate model, known as the *bounded space model* [21, 11, 37, 2, 33, 50, 20, 51, 7, 5], which incorporates the interaction of the transducers with the pressure wave through appropriate boundary conditions.

The ill-posedness of PAT is known to critically depend on the relationship between K, the compact set containing the support of the initial datum u_0 , and the acquisition surface Σ . Roughly speaking, if Σ is sufficiently large, the reconstruction problem becomes well-posed; otherwise, it remains ill-posed. This statement can be formalized using the following *visibility condition* for constant-speed waves.

Definition ([46]). Let $\Sigma \subset \mathbb{R}^3$ be a surface and let $K \subset \mathbb{R}^3$ be a compact subset with $d(K, \Sigma) > 0$. We say that the pair (K, Σ) satisfies the visibility condition if the following does not hold: there exists $\xi \in \mathbb{R}^3 \setminus \{0\}$ and open sets $\Omega_K, \Omega_\Sigma \subset \mathbb{R}^3$ with $\Omega_K \subset K$ and $\Omega_\Sigma \supset \Sigma$ such that, for every $x \in \Omega_K$, the line $\{x + t\xi : t \in \mathbb{R}\}$ does not intersect Ω_Σ .

See Fig. 1 for an example of a situation where the visibility condition is not satisfied.

The following is a negative result, demonstrating that, if the visibility condition is not satisfied, then conditional Hölder stability cannot be achieved with respect to any Sobolev norm.



Figure 1. Example of failure of the visibility condition. (a) The set K and the acquisition surface Σ . (b) A nonzero element ξ and the associated line bundle that does not intersect a neighbourhood Ω_{Σ} of Σ . (c) An open set Ω_K contained in the intersection of K and the line bundle.

Theorem ([46, Theorem 3.1]). Let U be the linear operator defined by $U: L^2(K) \to \mathcal{D}'(\Sigma \times [0,T]),^1$

mapping the initial datum u_0 to the restriction to $\Sigma \times [0,T]$ of the corresponding solution of the wave equation with constant velocity c.

Suppose that (K, Σ) does not satisfy the visibility condition. Then there do not exist constants $\mu, \delta, C > 0$ and $s_0, s_1 \ge 0$ such that

 $\|u_0\|_{L^2(K)} \le C \|Uu_0\|_{H^{s_0}(\Sigma \times [0,T])}^{\mu}, \quad \forall u_0 \in H^{s_1}(K) \text{ with } \|u_0\|_{H^{s_1}(K)} \le \delta.$

We also highlight the positive result in [49, Theorem 3], which states that a visibility condition similar to our definition is sufficient for Lipschitz-stable reconstruction with respect to appropriate Sobolev norms.

The visibility condition is closely related to the orientation of the singularities of u_0 , due to the propagation of singularities for the wave equation. Roughly speaking, the acquisition surface Σ must cover all directions orthogonal to the singularities to enable stable reconstruction of u_0 . Unfortunately, this condition might not be satisfied in practical scenarios with typical transducer configurations. The negative result mentioned above suggests that Sobolev norms may not adequately describe stable recovery results in the context of PAT with incomplete or partial data. This raises a natural question: could a different prior on the initial datum u_0 lead to a stable recovery result better suited for such scenarios?

1.2. Main contribution. The aim of this work is to obtain a stable recovery result (see Theorem 2.4 for the precise statement) for the reconstruction problem in partial

¹Here \mathcal{D}' is the space of distributions on $\Sigma \times [0,T]$, defined as the dual of $C_c^{\infty}(\Sigma \times [0,T])$.

data PAT using a wavelet sparse prior. We provide a brief overview of our result as follows.

We assume that the datum $u_0 \in L^2(B_1)$ is s-sparse with respect to a suitable wavelet orthonormal basis $(\phi_{j,n})_{(j,n)\in\Gamma}$, Γ being a suitable index set, – see Sec. 2.1 –, namely there exists $S \subset \Gamma$ with $|S| \leq s$ such that

(2)
$$u_0 = \sum_{(j,n)\in S} x_{j,n}\phi_{j,n}$$

for some coefficients $x_{j,n} \in \mathbb{C}$. Furthermore, we assume that the maximum scale j appearing in the above expansion is $j_0 \in \mathbb{N}$.

Let u be the pressure wave associated with the initial datum u_0 . Let Σ be a smooth surface embedded in \mathbb{R}^3 . We assume that the following stability estimates for the complete data on Σ hold for some sufficiently large T > 0:

(3)
$$c \|u_0\|_{L^2(\mathbb{R}^3)} \le \|u\|_{L^2(0,T;L^2(\Sigma))} \le C \|u_0\|_{L^2(\mathbb{R}^3)}, \\ \|u\|_{L^2(0,T;H^1(\Sigma))} \le C \|u_0\|_{H^1(\mathbb{R}^3)}.$$

for every smooth u_0 supported in K, where K is a fixed compact set containing the supports of all wavelets $(\phi_{j,n})_{(j,n)\in\Gamma}$ such that $d(K,\Sigma) > 0$. We will prove in Sec. 3.1 that (3) is satisfied in the case where the surface Σ is a sphere ∂B_R for some R > 0.

Instead of measuring u on the entire surface Σ , we proceed as follows: we partition Σ into a finite number of detectors $(E_i)_{i=1}^N$; the measurements are taken as a noisy version of local averages of u on only m randomly chosen detectors E_{i_1}, \ldots, E_{i_m} , where $m \leq N$. More precisely, we assume that $\varepsilon_k = \varepsilon_k(t)$ represents the noise on each detector E_{i_k} , and that the measurements are given by the time-dependent functions

$$y_k(t) \coloneqq \frac{1}{|E_{i_k}|} \int_{E_{i_k}} u(y,t) \,\mathrm{d}\sigma(y) + \varepsilon_k(t), \qquad t \in [0,T],$$

where $|\cdot|$ and $d\sigma$ denote the surface measure on Σ . We assume that the noise is controlled a priori by some noise level $\beta \geq 0$, i.e., that $\|\varepsilon_k\| \leq \beta$ with respect to some appropriate norm $\|\cdot\|$. The detectors used in the reconstruction procedure are chosen according to a random design – see Section 2.3.

We now state a simplified version of the main result, given by Theorem 2.4.

Theorem. Suppose the detectors $(E_i)_{i=1}^N$ satisfy the uniform eccentricity condition – see (12) –, and that

(4) $diam_{\mathbb{R}^3}(E_i) \lesssim 2^{-j_0}.$

Suppose also that

$$m \gtrsim j_0 s \cdot (\log \text{ factors}).$$

Let \hat{u} be a solution of the following ℓ^1 -minimization problem:

$$\min_{v_0} \sum_{j,n} |\langle v_0, \phi_{j,n} \rangle|: \qquad \frac{1}{m} \sum_{k=1}^m \left\| \frac{1}{|E_{i_k}|} \int_{E_{i_k}} v \, \mathrm{d}\sigma - y_k \right\|_{L^2(0,T)}^2 \le C\beta^2$$

where C > 0 is a suitable constant and the minimum is taken over

$$\operatorname{span}\{\phi_{j,n}\colon (j,n)\in\Gamma, j\leq j_0\}$$

and v is the solution of (1) with initial datum v_0 and $c \equiv 1$. Then, with overwhelming probability, the following recovery estimate holds:

$$\|u_0 - \widehat{u}\|_{L^2} \lesssim \beta.$$

In other words, the result states that we can achieve Lipschitz stable recovery of ssparse signals, provided the detectors are small enough relative to the signal resolution (specifically, relative to the highest wavelet scale index j_0 appearing in the expansion (2)), and the number of sampled detectors is proportional to j_0s , up to logarithmic factors. In Theorem 2.4, we also account for a possible sparsity defect and infinite resolution of u_0 by introducing appropriate sparsity and truncation errors. We also derive an extension of this result – see Theorem 2.7 – that can deal with more general sensing patterns.

Remark 1.1. If the sparsity level is sufficiently small, the number of detectors m used in the reconstruction is strictly smaller than the number of detectors N in the partition. Indeed, condition (4) implies that

$$N \gtrsim 2^{2j_0}$$
.

On the other hand, up to log factors, the number of detectors used in the reconstruction is given by

$$m \gtrsim j_0 s$$

Therefore, our result shows that it is possible to achieve stable recovery of sparse signals in the partial data regime of PAT.

1.3. Comparison with the literature. Obtaining stable recovery guarantees for ℓ^1 minimization relies on tools from compressed sensing (CS), a class of signal processing techniques that exploits signal sparsity to achieve stable reconstruction with few samples [18, 22, 27]. Since the advent of CS, numerous efforts have been made to develop CS-based strategies to accelerate the acquisition process in PAT [47, 43, 30, 48, 17, 13, 16, 10, 31, 12, 42, 6, 32]. Most cited works consider the following general measurement model:

(5)
$$y_k(t) = \langle u(\cdot, t), \psi_k \rangle_{L^2(\Sigma)},$$

where $\psi_k \in L^2(\Sigma)$ are suitable masks. In the literature, ψ_k are typically binary masks, i.e., functions on Σ taking values in $\{0, 1\}$ or $\{\pm 1\}$; this is similar in spirit to the type of measurements considered in this work. In some cases, the measurements are given by pointwise samples $u(x_k, \cdot)$ at specific locations $x_1, \ldots, x_m \in \Sigma$; such measurements can be approximated by (5) choosing ψ_k as rescaled indicator functions with small support, effectively providing local averages of $u(x, \cdot)$ around x_k .

The practical realization of these measurements can be achieved using different scanning systems, such as the Fabry-Pérot photoacoustic scanner [56] or mechanically scanned piezoelectric detectors. There are essentially two classes of scanning patterns. In single-point scanning, the masks ψ_k are localized in small regions concentrated around specific points on a grid – see, for instance, [47, 43]. To reduce coherence in the measurements, the mask locations are often chosen according to a random design. This more conventional approach is the focus of our method in Sec. 2.4. On the other hand, in pattern-interrogation scanning, a series of orthogonal masks ψ_k supported over the entire surface Σ is used, rather than focusing on specific locations. This approach speeds up acquisition in many scenarios and is adopted, for example, in [30, 48, 13, 16, 32]. We address this method in Sec. 2.5.

Reconstruction procedures using CS in PAT typically fall into two categories. The first, known as the one-step approach, aims to reconstruct the unknown signal u_0 directly from the measurements y_k – see, for instance, [47, 43, 13, 16]. The second, the two-step approach, first applies compressed sensing to reconstruct the full data $u|_{\Sigma \times [0,T]}$, which is then used for signal reconstruction via standard techniques such as time-reversal or back-projection. In the latter case, applying CS techniques requires enforcing sparsity in the measurements y_k ; this is typically achieved by processing the data with suitable sparsifying transformations—see, for example, [30, 48]. As argued in [30], the two-step approach has numerical advantages, as it avoids solving the wave equation in the first step, thereby reducing computational cost. However, it relies on the assumption that boundary data can be efficiently sparsified via an appropriate transformation.

Due to the complexity of the forward map in PAT, the interaction between the signal's sparsity and the sparsity of the measurements has so far defied a rigorous theoretical understanding. As a result, most existing research remains empirical, providing only partial answers regarding theoretical guarantees. In this work, we present, to the best of the author's knowledge, the first rigorous theoretical guarantees for PAT in the partial data regime, leveraging the sparsity of the signal itself with respect to a suitable wavelet basis. We also mention the work of [6], which shares a similar spirit with our study. There, the authors show that in many experimental setups, CS in PAT reduces to the well-known problem of reconstructing a sparse signal from a few samples of its Fourier coefficients. While this is of theoretical interest, [6] does not provide recovery guarantees such as those in Theorem 2.4, and

the performance of the proposed approach in PAT is only assessed via numerical simulations.

1.4. Main elements in the analysis. Theorem 2.4 critically depends on the general framework for compressed sensing in inverse problems developed in [8, 9]. In these works, the authors developed sufficiently flexible tools to study subsampled linear inverse problems with general vector-valued measurements and to derive precise recovery sample complexity estimates that relate three key quantities: the sparsity or compressibility of the signal, the number of measurements required for stable recovery, and the ill-posedness of the problem. In [9], the result is based on three elements:

- Stability bounds for the natural forward map U associated with the inverse problem, referred to as *quasi-diagonalization* bounds.
- A balancing property that controls the stability in the discretization of the natural forward map U, leading to a truncated forward map F.
- Coherence bounds for the measurement operators F_t with respect to the analysis dictionary $(\phi_{i,n})_{(i,n)\in\Gamma}$ used in the reconstruction.

The stability properties required for the main result – see Assumption 2.1 – are inspired by results from [26, 39]. In particular, we are able to prove that such stability estimates hold when Σ is a sphere as a consequence of a trace identity in [39] – see Proposition 2.2. The stability estimate in Lemma 3.3 is then obtained from Assumption 2.1 by complex interpolation; a proof of these lemmas is provided in the Appendix. The proof of the trace identity in [39] relies on a result from [26], which in turn makes essential use of the properties of the spherical mean Radon transform. Notice that, for a general smooth bounded domain $\Omega \subset \mathbb{R}^3$, the following estimate is easy to deduce:

$$||u||_{L^2(0,T;H^{1/2}(\partial\Omega))} \le C ||u_0||_{H^1(\mathbb{R}^3)},$$

where u_0 is supported in $K \subset \partial \Omega$. The trace identity from [39] shows that, in the case where Ω is a ball, such a loss of regularity of 1/2 in the Sobolev exponent does not occur. It is reasonable to expect that the same stability should hold also for more general smooth embedded surfaces.

Regarding the balancing property, in the case of PAT, it reduces to a bound of the following type – see Proposition 3.2:

$$\|(I - P_{\mathcal{F}})u\|_{L^{2}(0,T;L^{2}(\Sigma))} \leq \theta \|u_{0}\|_{L^{2}(\mathbb{R}^{3})} \qquad u_{0} \in \operatorname{span}_{\substack{(j,n)\\j \leq j_{0}}} \{\phi_{j,n}\},$$

where $P_{\mathcal{F}}$ is the orthogonal projection of a function in $L^2(0, T; L^2(\Sigma))$ onto the space of (time-dependent) piecewise constant functions with respect to the partition $(E_i)_{i=1}^N$ and $\theta \in (0, 1)$ is a sufficiently small constant. To obtain this estimate, we used ideas from [35] concerning approximation of boundary measurements with electrodes in

the context of the Calderón problem. Using a refined argument developed in [25], we obtain the bound:

$$\|(I - P_{\mathcal{F}})u\|_{L^{2}(0,T;L^{2}(\Sigma))} \lesssim \left(\max_{i} \operatorname{diam}_{\mathbb{R}^{3}}(E_{i})\right)^{1/2} \|u\|_{L^{2}(0,T;H^{1/2}(\Sigma))}$$

From here, additional ad hoc estimates are required, including leveraging the so-called Littlewood-Paley property of wavelets – we refer the reader to [44] for further details.

Finally, the coherence bounds from Proposition 3.4 exploit, in a crucial way, the construction of tensorized wavelets and Huygens' principle for the wave equation in odd dimensions. Using these elements, we can apply the result from [9, Theorem 2.4] – or, up to minor modifications, [8, Theorem 3.11] – to obtain Theorem 2.4.

1.5. Structure of the paper. The paper is organized as follows. In Sec. 2.1 we introduce the dictionary of wavelets used in the reconstruction and the related notion of sparsity. In Sec. 2.2, we discuss the model for the dynamics of the pressure wave and discuss some assumptions on the stability of the associated inverse wave problem. In Sec. 2.3, we introduce the discretization of measurements via the notion of detectors, and define the associated measurements. In Sec. 2.4, we state our main result (Theorem 2.4). In Sec. 2.5, we extend our main result to more general sensing systems considered in the literature (Theorem 2.7). In Sec. 3, we provide the proof of the results from Sec. 2; the proof of the more technical Lemma 3.3 is deferred to Appendix A.

2. Setting and main result

2.1. Wavelet dictionary and sparsity. Our goal is to reconstruct a signal in $L^2(B_1)$, where B_1 is the unit ball in \mathbb{R}^3 , that is compressible with respect to a suitable wavelet dictionary. We briefly recall the construction of compactly supported separable wavelets in \mathbb{R}^3 and define the space to which the input signal belongs. We refer the reader to [44, 41] and [9, Appendix A] for further details.

There exists an orthonormal basis of compactly supported elements $(\psi_n^3)_n \cup (\phi_{j,n,\varepsilon}^3)_{n,\varepsilon}$, where $n = (n_1, n_2, n_3) \in \mathbb{Z}^3$, $j \in \mathbb{N}$ and $\varepsilon = (\varepsilon_1, \varepsilon_2, \varepsilon_3) \in \{0, 1\}^3 \setminus \{(0, 0, 0)\}$, defined as follows:

(6)
$$\psi_n^3(x_1, x_2, x_3) \coloneqq \psi(x_1 - n_1)\psi(x_2 - n_2)\psi(x_3 - n_3), \phi_{j,n,\varepsilon}^3(x_1, x_2) \coloneqq 2^{3/2j}\phi^{\varepsilon_1}(2^jx_1 - n_1)\phi^{\varepsilon_2}(2^jx_2 - n_2)\phi^{\varepsilon_3}(2^jx_3 - n_3),$$

where $\phi^0 = \psi$ and $\phi^1 = \phi$ are compactly supported functions in $L^2(\mathbb{R})$; moreover, ϕ has zero mean. The functions ψ and ϕ are referred to as the scaling function and the mother wavelet of the dictionary, respectively.

In what follows, we will suppose that $\psi, \phi \in C^2$; such a choice is possible – see, for instance, [9, Proposition A.5]. In this case, the wavelet dictionary satisfies the

following *Littlewood-Paley property* [9, Proposition A.7]: for each |s| < 2, there exists constants c, C > 0 such that

(7)
$$c \|u\|_{H^s(\mathbb{R}^3)}^2 \leq \sum_n |\langle u, \psi_n^3 \rangle|^2 + \sum_{j,n,\varepsilon} 2^{2sj} |\langle u, \phi_{j,n,\varepsilon}^3 \rangle|^2 \leq C \|u\|_{H^s(\mathbb{R}^3)}^2, \quad u \in H^s(\mathbb{R}^3).$$

We consider a dictionary defined as follows: up to relabeling, we denote $(\psi_n^3)_n \cup (\phi_{j,n,\varepsilon}^3)_{j,n,\varepsilon}$ as $(\phi_{j,n})_{j,n}$ (j = 0 corresponding to the low frequency elements $(\psi_n^3)_n$ and j > 0 corresponding to the high frequencies elements $(\phi_{j,n,\varepsilon}^3)_{j,n,\varepsilon}$ and consider the index set Γ defined as

$$\Gamma \coloneqq \{(j,n): \operatorname{supp}(\phi_{j,n}) \cap B_1 \neq \emptyset\}.$$

We consider the following compact set:

(8)
$$K \coloneqq \bigcup_{(j,n)\in\Gamma} \operatorname{supp}(\phi_{j,n}).$$

We define the space

(9)
$$\mathcal{H}_1 \coloneqq \overline{\operatorname{span}}\{\phi_{j,n} \colon (j,n) \in \Gamma\}.$$

We also define the following index sets

$$\Lambda_j \coloneqq \{ (j', n) \in \Gamma \colon j' = j \}, \qquad \Lambda_{\leq j_0} \coloneqq \cup_{j \leq j_0} \Lambda_j,$$

the subspaces of \mathcal{H}_1

$$\mathcal{M}_{j} \coloneqq \operatorname{span}\{\phi_{j',n} \colon (j',n) \in \Lambda_{j}\}, \quad \mathcal{M}_{\leq j_{0}} \coloneqq \operatorname{span}\{\phi_{j,n} \colon (j,n) \in \Lambda_{\leq j_{0}}\}$$

and the corresponding orthogonal projections in \mathcal{H}_1

$$P_j \coloneqq P_{\mathcal{M}_j}, \qquad P_{\leq j_0} \coloneqq P_{\mathcal{M}_{\leq j_0}}, \qquad P_{\leq j_0}^{\perp} \coloneqq I - P_{\leq j_0}$$

We also remark that $|\Lambda_j| \simeq 2^{3j}$ for each j, so that

$$\log(|\Lambda_{\leq j_0}|) \asymp j_0$$

Finally, we define the analysis operator $\Phi: \mathcal{H}_1 \to \ell^2(\Gamma)$ as $\Phi u := (\langle u, \phi_{j,n} \rangle)_{j,n}$ and the error of best s-sparse approximation with respect to the ℓ^1 -norm as follows:

$$\sigma_s(u)_1 \coloneqq \inf\{\|\Phi u - x\|_1 \colon x \in \ell^2(\Gamma) \text{ is } s\text{-sparse}\},\$$

where by s-sparse we mean a sequence in $\ell^2(\Gamma)$ that has at most s nonzero components.

2.2. **PDE model for PAT.** Given a signal $u_0 \in L^2(K)$, where K is as in (8), we consider its evolution u = u(x, t) being the weak solution to the following initial value problem for the wave equation – see [3] and the references therein:

(10)
$$\begin{cases} u_{tt} - \Delta u = 0 & \text{in } \mathbb{R}^3 \times [0, +\infty), \\ u(\cdot, 0) = u_0 & \text{in } \mathbb{R}^3, \\ u_t(\cdot, 0) = 0 & \text{in } \mathbb{R}^3. \end{cases}$$

For our purposes, the solution can be defined via Fourier multipliers as

$$u(\cdot,t) = \cos\left((-\Delta)^{1/2}t\right)u_0 = \mathcal{F}^{-1}\left(\cos(2\pi|\cdot|t)\mathcal{F}u_0\right),$$

where \mathcal{F} denotes the Fourier transform, defined by $\mathcal{F}u(\xi) \coloneqq \int_{\mathbb{R}^3} u(x) \exp(-2\pi i x \cdot \xi) \, dx$. The solution also admits an explicit integral representation, known as *Kirchoff's formula* [24, Theorem 2, Section 2.4], valid for $u_0 \in C^2(\mathbb{R}^3)$:

(11)
$$u(x,t) = \frac{1}{4\pi t^2} \int_{\partial B_t(x)} \left(u_0(y) + \nabla u_0(y) \cdot (y-x) \right) \, \mathrm{d}\sigma(y)$$

In this case, $u \in C^2(\mathbb{R}^3 \times [0, +\infty))$.

For T > 0, we use $V: L^{2}(K) \to C^{0}([0,T]; L^{2}(\mathbb{R}^{3}))$ to denote the operator mapping an initial datum $u_{0} = u_{0}(x)$ to $u = u(x,t), x \in \mathbb{R}^{3}$ and $t \in [0,T]$, namely to the corresponding solution of the initial value problem (10).

In the sequel, we will be dealing with the restriction of the solution u to a smooth embedded surface $\Sigma \subset \mathbb{R}^3$ such that $d(K, \Sigma) > 0$. If $u_0 \in C_K^2(\mathbb{R}^3)$, where $C_K^2(\mathbb{R}^3)$ denotes the space of C^2 functions supported in K, then $u \in C^2(\mathbb{R}^3 \times [0, +\infty))$ and therefore the operator $U: C_K^2(\mathbb{R}^3) \to C^2(\Sigma \times [0, T])$, given by

$$Uu_0 \coloneqq Vu_0|_{\Sigma \times [0,T]},$$

is well-defined. We assume that the following stability bounds hold.

Assumption 2.1. There exists a compact set $K' \subset \mathbb{R}^3$, with $d(K', \Sigma) > 0$ and $K \subset int(K')$, and there exists constants c, C, T > 0 such that following stability estimates hold for every $u_0 \in C^2_{K'}(\mathbb{R}^3)$:

$$c \|u_0\|_{L^2(\mathbb{R}^3)} \le \|Uu_0\|_{L^2(0,T;L^2(\Sigma))} \le C \|u_0\|_{L^2(\mathbb{R}^3)}, \|Uu_0\|_{L^2(0,T;H^1(\Sigma))} \le C \|u_0\|_{H^1(\mathbb{R}^3)}.$$

Here $H^1(\Sigma)$ denotes the Sobolev space of L^2 functions (with respect to the metric induced by \mathbb{R}^3) on the manifold Σ that are square summable together with their Lie derivatives. This assumption implies in particular that it is possible to extend U by continuity and density to a bounded operator $U: L^2(K') \to L^2(0, T; L^2(\Sigma))$ such that $U(H^1_0(K')) \subset L^2(0, T; H^1(\Sigma))$. The operator U so defined is an isomorphism onto its image. Notice that the lower bound in the first inequality implies a restriction on T, which should be sufficiently large. The following Proposition, proved in Sec. 3.1, shows that Assumption 2.1 holds for spheres ∂B_R for R > 0; here B_R is the ball in \mathbb{R}^3 of radius R centered in the origin.

Proposition 2.2. Let R > 1 be such that $K' \subset B_R$, where K' is a compact set. There exists T > 0 and constants c, C > 0, depending only on R and on $d(K', \partial B_R)$, such that Assumption 2.1 is satisfied.

It is reasonable to expect that such stability estimates should hold also for more general smooth embedded surfaces $\Sigma \subset \mathbb{R}^3$, although we were unable to find specific references in the literature for such bounds.

2.3. Detectors and measurements. The measurements considered involve a finite number of *detectors* on Σ , which we identify with closed subsets $E_i \subset \Sigma$ with $|E_i| > 0$.

In order to derive our main result, we need to make some geometric assumptions on the detectors. In particular, we suppose that there exists a constant $C_{\text{ecc}} > 0$, fixed throughout the analysis, such that the following holds for every detector E_i :

(12)
$$\operatorname{diam}_{\mathbb{R}^3}(E_i) \le C_{\operatorname{ecc}} |E_i|^{1/2}$$

where the diameter is computed with respect to the Euclidean distance in \mathbb{R}^3 . This assumption is a sort of *uniformly bounded eccentricity* condition on the detectors. To convince the reader that this assumption is reasonable – at least for certain geometries –, we show in the next Proposition that a certain type of scaling (almost) preserves the eccentricity of detectors on the unit sphere $\mathbb{S}^2 \subset \mathbb{R}^3$, provided they are sufficiently small. We will provide a proof of the Proposition in Sec. 3.2.

Proposition 2.3. Let $\mu > 0$. There exists a constant $\delta = \delta(\mu) > 0$ such that the following holds. Let $\tilde{E} \subset B_{\delta}(0)$, where $B_{\delta}(0)$ is the ball of radius δ in \mathbb{R}^2 centered in 0, be such that

$$\operatorname{diam}_{\mathbb{R}^2}(\tilde{E}) \le C_{\operatorname{ecc}} \mathcal{L}^2(\tilde{E})^{1/2}$$

for some constant $C_{\text{ecc}} > 0$, where \mathcal{L}^2 is the Lebesgue measure in \mathbb{R}^2 . Let $p \in \mathbb{S}^2$, $t \in (0, 1]$ and

$$E_t \coloneqq \exp_n(t\tilde{E}),$$

where $\exp_p: T_p \mathbb{S}^2 \to \mathbb{S}^2$ is the exponential map with respect to the metric induced by \mathbb{R}^3 on \mathbb{S}^2 .²

Then

$$\operatorname{diam}_{\mathbb{R}^3}(E_t) \le (1+\mu)C_{\operatorname{ecc}}|E_t|^{1/2}$$

²We identify \mathbb{R}^2 with the tangent space $T_p \mathbb{S}^2$ via a linear isometry.

In what follows, we fix a family $\mathcal{F} = \{E_1, \ldots, E_N\}$ of closed subsets, referred to as *detectors*, on Σ that partition the surface in the following sense:

$$\Sigma = \bigcup_{i} E_i, \qquad |E_i \cap E_j| = 0, \ i \neq j.$$

We select *m* detectors E_{i_1}, \ldots, E_{i_m} via a random sampling procedure. More precisely, let $\nu = (\nu_1, \ldots, \nu_N)$ be the probability distribution defined on $\{1, \ldots, N\}$ by

(13)
$$\nu_i \coloneqq \frac{|E_i|}{|\Sigma|}$$

Notice that the probability of sampling a detector is proportional to its area; in other words, we choose larger detectors with higher probability. We then consider m i.i.d. samples $i_1, \ldots, i_m \sim \nu$ and the corresponding detectors E_{i_1}, \ldots, E_{i_m} .

The corresponding *measurements* are then given by

(14)
$$y_k(t) \coloneqq \frac{1}{|E_{i_k}|} \int_{E_{i_k}} U u_0(y, t) \,\mathrm{d}\sigma(y) + \varepsilon_k(t) \in L^2(0, T),$$

where $\varepsilon_k \in L^2(0,T)$ are functions modeling noise on the data.

2.4. Main result. We now state our main result.

Theorem 2.4. Consider the setting introduced in sections 2.1, 2.2, 2.3 and suppose that (12) is satisfied. Let $\Sigma \subset \mathbb{R}^3$ be a smooth embedded surface such that $d(K, \Sigma) > 0$, where K is as in (8), and suppose that Assumption 2.1 is satisfied. Then there exist constants μ, C_0, C_1, C_2, C_3 , depending only on T, on Σ , on $d(K, \Sigma)$, on the wavelet basis, on the constants c, C in Assumption 2.1, and on C_{ecc} , such that the following holds.

Consider $u_0 \in L^2(B_1)$. Suppose that

(15)
$$\operatorname{diam}_{\mathbb{R}^3}(E_i) \le \mu 2^{-j_0}, \qquad i = 1, \dots, N,$$

for some $j_0 \in \mathbb{N}$ and that $\|P_{\leq j_0}^{\perp} u_0\|_{L^2(\mathbb{R}^3)} \leq r$. Consider m i.i.d. samples i_1, \ldots, i_m from the distribution ν on $\{1, \ldots, N\}$ defined in (13). Let $(\varepsilon_k)_{k=1}^m \in L^2(0, T)$ be such that $\|\varepsilon_k\|_{L^2(0,T)} \leq \beta$ for $k = 1, \ldots, m$ and let $(y_k)_{k=1}^m$ be given by (14).

Consider a solution \hat{u} to the following minimization problem:

(16)
$$\min_{v \in \mathcal{M}_{\leq j_0}} \|\Phi v\|_{\ell^1} : \qquad \frac{1}{m} \sum_{k=1}^m \left\| \frac{1}{|E_{i_k}|} \int_{E_{i_k}} Uv \, \mathrm{d}\sigma - y_k \right\|_{L^2(0,T)}^2 \leq C_3 \eta^2,$$

where $\eta \coloneqq \beta + \max\{1, (\min_i |E_i|)^{-1/2}\} r$. Let $\gamma \in (0, 1)$. If

$$m \ge C_0 s \max\{j_0 \log^3 s, \log(1/\gamma)\},\$$

then, with probability exceeding $1 - \gamma$, the following holds:

(17)
$$\|u_0 - \hat{u}\|_{L^2} \le C_1 \frac{\sigma_s (P_{\le j_0} u_0)_1}{\sqrt{s}} + C_2 \left(\beta + \max\{1, (\min_i |E_i|)^{-1/2}\}r\right)$$

A few remarks are in order.

Remark 2.5. Condition (15) on the size of the detectors guarantees stable recovery for signals in $\mathcal{M}_{\leq j_0}$. This is a reasonable assumption: indeed, $\mathcal{M}_{\leq j_0}$ is generated by wavelets at resolution at most j_0 ; those at the highest resolution j_0 are supported in a set of diameter $\approx 2^{-j_0}$. It is plausible that the measurements should be given by averages on detectors of approximately the same size in order to get stable recovery.

Remark 2.6. The dependence of the recovery estimate (17) on the truncation level is given by

$$\max\{1, (\min_{i} |E_i|)^{-1/2}\} r$$

This quantity is optimized by choosing partitions with quasi-uniform detectors of maximal size, namely families $(E_i^{j_0})_{i=1}^{N_{j_0}}$ for each $j_0 \in \mathbb{N}$ such that

$$c2^{-2j_0} \le |E_i^{j_0}| \le C2^{-2j_0}, \quad \forall i = 1, \dots, N_{j_0},$$

where c, C > 0 are constants independent of j_0 . In this case, the error can be bounded by

$$\max\{1, (\min_{i} |E_i|)^{-1/2}\}r \lesssim 2^{j_0}r.$$

The proof of Theorem 2.4 is based on results from [8, 9]. As remarked after the statement of [8, Theorem 3.5], the abstract framework is suited for a uniform recovery result except for the truncation error – see [8, Proposition 5.8]. However, Theorem 2.4 can be easily converted to a uniform recovery result; this is due to the fact that the inversion of the full forward map U is well-posed due to Assumption 2.1. In particular, this implies that, with high probability, the sampled detectors E_{i_1}, \ldots, E_{i_m} achieve stable recovery of all s-sparse signals.

2.5. General sensing patterns. We can easily extend our result to other sensing systems that have been considered in the literature.

Our main result – Theorem 2.4 – assumes that each measurement is given by the averaged pressure wave on a single detector. In practice, it is possible to leverage the principles behind the so-called *single-pixel camera* systems [23, 28, 40] to achieve better compression rates – see, for instance, [34, 16]. These systems simplify the task of obtaining highly resolved spatial measurements by converting it into sequential recording in time using a fixed array of detectors. For these types of sensing patterns, multiple detectors activate at each measurement; the measurement is then given by a weighted sum of the averaged pressure wave on each detector.

We now show how it is possible to extend our framework to this setting. We assume, for simplicity, that there exists $C_u \ge 1$, fixed throughout the analysis, such that the detectors $\mathcal{F} = (E_i)_{i=1}^N$ satisfy the following *quasi-uniformity* assumption:

(18)
$$\frac{1}{C_u}|E_i| \le |E_j| \le C_u|E_i|, \qquad i, j = 1, \dots, N.$$

This implies in particular that

$$\frac{|\Sigma|}{NC_u} \le |E_i| \le \frac{|\Sigma|C_u}{N}.$$

We suppose that the pressure wave measurements on the detectors is corrupted by noise $\varepsilon_k \in L^2(0,T)$ for $k = 1, \ldots, m$.

For convenience of notation, we define the following averaging operators:

$$M_i: L^2(0,T; L^2(\Sigma)) \to L^2(0,T), \qquad M_i v(t) := \frac{1}{|E_i|} \int_{E_i} v(y,t) \,\mathrm{d}\sigma(y)$$

and the associated operator M defined by

$$Mv(t) \coloneqq (M_1v(t), \dots, M_Nv(t)) \in \left(L^2(0,T)\right)^N$$

We fix a unitary matrix $A \in \mathbb{C}^{N \times N}$.³ Let i_1, \ldots, i_m be m i.i.d. samples from the uniform distribution on $\{1, \ldots, N\}$. The measurements in the new setting are given by

(19)
$$y_k(t) \coloneqq P_{i_k} AMU u_0 + \varepsilon_k, \qquad k = 1, \dots, m,$$

where $P_i: (L^2(0,T))^N \to L^2(0,T)$ is the projection on the *i*-th component. Notice that, for A = I, the measurements reduce to the ones defined in (14) with $\nu_i \equiv 1/\sqrt{N}$, thanks to (18).

We now state the new result; a sketch of the proof is provided in Sec. 3.4.

Theorem 2.7. Consider the setting introduced in sections 2.1, 2.2, 2.3 and suppose that (12) and (18) are satisfied. Let $\Sigma \subset \mathbb{R}^3$ be a smooth embedded surface such that $d(K, \Sigma) > 0$, where K is as in (8), and suppose that Assumption 2.1 is satisfied. There exist constants μ, C_0, C_1, C_2, C_3 , depending only on T, on Σ , on $d(K, \Sigma)$, on the wavelet basis, on the constants c, C in Assumption 2.1, on C_{ecc} and on C_u , such that the following holds.

Consider $u_0 \in L^2(B_1)$. Suppose that (15) is satisfied for some $j_0 \in \mathbb{N}$ and that $\|P_{\leq j_0}^{\perp} u_0\|_{L^2(\mathbb{R}^3)} \leq r$. Consider m i.i.d. samples i_1, \ldots, i_m from the uniform distribution

³A more general result would hold for invertible matrices; in this case, the constants appearing in the estimates would also depend on $\max\{||A||, ||A^{-1}||\}$, where $||\cdot||$ denotes the operator norm.

on $\{1, \ldots, N\}$. Let $(\varepsilon_k)_{k=1}^m \in L^2(0,T)$ be such that $\|\varepsilon_k\|_{L^2(0,T)} \leq \beta$ for $k = 1, \ldots, m$ and let $(y_k)_{k=1}^m$ be given by (19). Let

(20)
$$B \coloneqq \max_{\substack{i=1,\dots,N\\(j,n)\in\Lambda_{\leq j_0}}} \|P_iAMU\phi_{j,n}\|_{L^2(0,T)}.$$

Consider a solution \hat{u} to the following minimization problem:

$$\min_{v \in \mathcal{M}_{\leq j_0}} \|\Phi v\|_{\ell^1} : \qquad \frac{1}{m} \sum_{k=1}^m \|P_{i_k} A M U v - y_k\|_{L^2(0,T)}^2 \leq C_3 \eta^2,$$

where $\eta \coloneqq \beta + \sqrt{N}r$. Let $\gamma \in (0, 1)$. If

(21)
$$m \ge C_0 \tau \max\{j_0 \log^3 \tau, \log(1/\gamma)\}, \quad \tau \coloneqq B^2 s,$$

then, with probability exceeding $1 - \gamma$, the following holds:

$$\|u_0 - \hat{u}\|_{L^2} \le C_1 \frac{\sigma_s (P_{\le j_0} u_0)_1}{\sqrt{s}} + C_2 (\beta + \sqrt{N}r).$$

The parameter B in (20) plays a crucial role in Theorem 2.7, as it affects the sample complexity in (21). It is closely related to the concept of *coherence* in compressed sensing. We now discuss the role of coherence in two different settings.

As previously noted, when A = I, the setting of Theorem 2.7 reduces to that of Theorem 2.4 with $\nu_i \equiv 1/\sqrt{N}$. By Proposition 3.4, we obtain that, in this case, B can be bounded by a constant independent of j_0 .⁴ This bound arises from the geometry of tensorized wavelets. Indeed, high-frequency wavelets exhibit low sensitivity to directionality; as a result, their energy propagates across a wide range of directions. Consequently, the corresponding pressure wave can be detected by localized measurements on a sparse array of detectors.

Now, suppose that Theorem 2.7 also holds when the wavelet dictionary $(\phi_{j,n})_{j,n}$ is replaced by a frame $(\phi_{j,n,l})_{j,n,l}$ whose elements exhibit higher sensitivity to directionality. Examples of such dictionaries include *curvelets* and *shearlets* [19, 29, 38]. In this case, due to the propagation of singularities for the wave equation, the energy of the pressure wave associated with high-frequency elements in the dictionary becomes localized to a small number of detectors aligned with specific directions. In other words, we expect the time-dependent vector $MU\phi_{j,n,l}$ to be sparse. For this reason, it is preferable to adopt a different sensing pattern that promotes incoherence in the measurements. One possible choice is to use a binary matrix A with components in $\{\pm 1/\sqrt{N}\}$; examples include, for instance, Bernoulli matrices and scrambled

$$P_i M U = |E_i|^{-1/2} F_i$$

⁴Indeed, notice that, with reference to the notation of Sec. 3.3, the following identity holds:

Hadamard matrices. Another possibility is provided by sparse matrices such as lossless expanders, for which theoretical CS guarantees exist in the literature. For further information, we refer the reader, for instance, [27] or the appendix in [30].

We notice that the general framework from [8, 9] applies only under the assumption that the sparsifying dictionary $(\phi_{j,n})_{j,n}$ is either an orthonormal basis or a Riesz system. As a result, it cannot accommodate redundant frames such as curvelets and shearlets. We leave such extensions to future work.

3. Proofs

In this section, we provide the proof of the statements from Sec. 2.

3.1. **Proof of Proposition 2.2.** The thesis easily follows from the following two identities, proved in [39, Theorem 1]:

$$\frac{R}{2} \int_{\mathbb{R}^3} |u_0(x)|^2 \,\mathrm{d}x = \int_0^{+\infty} \int_{\partial B_R} t |Uu_0(y,t)|^2 \,\mathrm{d}\sigma(y) \,\mathrm{d}t,$$
$$\frac{R}{2} \int_{\mathbb{R}^3} |\nabla_{\mathbb{R}^3} u_0(x)|^2 \,\mathrm{d}x = \int_0^T \int_{\partial B_R} t |\nabla_{\mathbb{R}^3} Uu_0(y,t)|^2 \,\mathrm{d}\sigma(y) \,\mathrm{d}t,$$

valid for every $u_0 \in C^{\infty}(B_R)$; here $\nabla_{\mathbb{R}^3}$ denotes the gradient with respect to the Euclidean metric in \mathbb{R}^3 in the spatial variable y. By density and continuity, it is clear that such identities hold also for $u_0 \in C^2(B_R)$.

If $u_0 \in C^2_{K'}(B_R)$, then $Uu_0(x,t) = 0$ for $x \in \partial B_R$ and $t \in \mathbb{R}^+ \setminus [d(K', \partial B_R), 2R]$. We deduce that

$$c \|u_0\|_{L^2(\mathbb{R}^3)} \le \|Uu_0\|_{L^2(0,T;L^2(\partial B_R))} \le C \|u_0\|_{L^2(\mathbb{R}^3)}$$

and also

(22)
$$\int_0^T \int_{\partial B_R} |\nabla_{\mathbb{R}^3} U u_0(y,t)|^2 \mathrm{d}\sigma(y) \mathrm{d}t \le 2C^2 ||u_0||^2_{H^1(\mathbb{R}^3)},$$

where $c = \sqrt{\frac{R}{2T}}$, $C = \sqrt{\frac{R}{2d(K',\Sigma)}}$ and T = 2R.

Notice that, for a smooth function v defined on \mathbb{R}^3 , the following identity holds

$$\nabla_{\Sigma}(v|_{\partial B_R}) = P_{\partial B_R} \nabla_{\mathbb{R}^3} v,$$

where $P_{\partial B_R}$ is the projection on the tangent bundle of ∂B_R . This, together with (22), implies that

$$\int_0^T \int_{\partial B_R} |\nabla_{\partial B_R} U u_0(y,t)|^2 \mathrm{d}\sigma(y) \mathrm{d}t \le \int_0^T \int_{\partial B_R} |\nabla_{\mathbb{R}^3} U u_0(y,t)|^2 \mathrm{d}\sigma(y) \mathrm{d}t$$
$$\le C^2 \|u_0\|_{H^1(\mathbb{R}^3)}^2,$$

which in turn implies the H^1 stability estimate in Assumption 2.1.

3.2. Proof of Proposition 2.3. Let $\delta \in (0, 1)$. We have that

$$d \exp_p 0 = I$$

Therefore, choosing possibly a smaller δ , we can suppose that

(23)
$$|\det(d\exp_p v)| \ge \frac{1}{1+\mu_0}, \qquad v \in T_p \mathbb{S}^2 \cap B_\delta(0),$$

where $\mu_0 \in (0, 1)$ is to be assigned later.

If $v, w \in B_{\delta}(0)$ and $\delta \leq \mu_0$, then

$$\cos(\|v\|) - \cos(\|w\|)| \le (\sin \delta) |\|v\| - \|w\|| \le \mu_0 \|v - w\|.$$

Moreover, choosing a possibly smaller δ , we can suppose that, if $v, w \in B_{\delta}(0) \setminus \{0\}$,

$$\frac{\sin(\|v\|)}{\|v\|} - \frac{\sin(\|w\|)}{\|w\|} \le \mu_0 ||v\| - ||w|| \le \mu_0 ||v - w||.$$

An explicit formula for the exponential map on \mathbb{S}^2 is given by

$$\exp_p(v) = \cos(\|v\|)p + \frac{\sin(\|v\|)}{\|v\|}v, \qquad v \in T_p \mathbb{S}^2 \setminus \{0\},$$

where $T_p \mathbb{S}^2$ is identified with p^{\perp} – see [1, Example 5.4.1]. Using the previous computations, we deduce that, for $v, w \in T_p \mathbb{S}^2 \cap B_{\delta}(0)$,

$$\|\exp_p(v) - \exp_p(w)\|^2 = |\cos(\|v\|) - \cos(\|w\|)|^2 + \left\|\frac{\sin(\|v\|)}{\|v\|}v - \frac{\sin(\|w\|)}{\|w\|}w\right\|^2 \le \left(\mu_0^2 + (1+\mu_0^2)^2\right)\|v - w\|^2,$$

which implies that, for $t \in (0, 1]$,

diam_{$$\mathbb{R}^3$$} $(E_t) \le \sqrt{\mu_0^2 + (1 + \mu_0^2)^2} \operatorname{diam}_{\mathbb{R}^2}(t\tilde{E}).$

By the scaling properties of the Euclidean distance and of the Lebesgue measure \mathcal{L}^2 with respect to dilations in \mathbb{R}^2 , we have that

diam_{$$\mathbb{R}^2$$} $(t\tilde{E}) \le C_{\text{ecc}}\mathcal{L}^2(t\tilde{E})^{1/2}, \quad t \in (0,1].$

By (23), we have that

$$\mathcal{L}^2(t\tilde{E}) \le (1+\mu_0)|E_t|.$$

Putting everything together, we have that

diam_{$$\mathbb{R}^3$$} $(E_t) \le \sqrt{\mu_0^2 + (1 + \mu_0^2)^2 (1 + \mu_0)^{1/2} C_{\text{ecc}} |E_t|^{1/2}}.$

The Proposition is proved by choosing a sufficiently small μ_0 such that

$$\sqrt{\mu_0^2 + (1 + \mu_0^2)^2 (1 + \mu_0)^{1/2}} \le 1 + \mu.$$

3.3. **Proof of the main result.** Our proof of Theorem 2.4 is based on [9, Theorem 2.4]; we briefly recall here the setup for the convenience of the reader.

The measurement procedure is modeled via a family of bounded measurement operators $(F_t)_{t\in\mathcal{D}}: \mathcal{H}_1 \to \mathcal{H}_2$ between Hilbert spaces $\mathcal{H}_1, \mathcal{H}_2$. In our case, \mathcal{H}_1 is given by (9), while it is convenient to write F_t as F_i for $i = 1, \ldots, N$, where

$$F_i u_0(t) \coloneqq |E_i|^{1/2} M_i U u_0 = \frac{1}{|E_i|^{1/2}} \int_{E_i} U u_0(y, t) \, \mathrm{d}\sigma(y).$$

The space \mathcal{D} that parametrizes the measurements corresponds then to $\{1, \ldots, N\}$ and \mathcal{H}_2 is $L^2(0,T)$. The sampling procedure is modeled via a probability distribution ν on \mathcal{D} ; in our case, it is given by the probability $\nu = (\nu_1, \ldots, \nu_N)$ on $1, \ldots, N$ defined by (13).⁵ The forward map $F: \mathcal{H}_1 \to (L^2(0,T))^N$ modeling the collection of all possible measurements is given by

$$Fu_0 \coloneqq (F_i u_0)_{i=1}^N \in (L^2(0,T))^N.$$

We now compute the norm of Fu_0 :

$$\begin{aligned} \|Fu_0\|_{(L^2(0,T))^N}^2 &= \sum_{i=1}^N \|F_i u_0\|_{L^2(0,T)}^2 \\ &= \sum_{i=1}^N \int_{\Sigma} \|F_i u_0\|_{L^2(0,T)}^2 \frac{\mathbb{1}_{E_i}(y)}{|E_i|} \,\mathrm{d}\sigma(y) \\ &= \int_0^T \int_{\Sigma} \left|\sum_{i=1}^N F_i u_0(t) \frac{\mathbb{1}_{E_i}(y)}{|E_i|^{1/2}}\right|^2 \,\mathrm{d}\sigma(y) \mathrm{d}t, \end{aligned}$$

where we carried the summation inside the square in the last equality using the fact that $|E_i \cap E_j| = 0$ for $i \neq j$. The previous formula shows that $||Fu_0||_{(L^2(0,T))^N}$ is given by $||P_{\mathcal{F}}Uu_0||_{L^2(0,T;L^2(\Sigma))}$, $P_{\mathcal{F}}$ being the orthogonal projection on $L^2(0,T;\mathcal{P}_{\mathcal{F}})$, where $\mathcal{P}_{\mathcal{F}}$ is the space of piecewise-constant functions in the spatial variable with respect to $\mathcal{F} = \{E_1, \ldots, E_N\}$. Explicitly, we have that

(24)
$$P_{\mathcal{F}}Uu_0(t,y) = \sum_{i=1}^N F_i u_0(t) \frac{\mathbb{1}_{E_i}(y)}{|E_i|^{1/2}}.$$

This implies that, up to an isomorphism, the forward map F can be identified with $P_{\mathcal{F}}U$, where $P_{\mathcal{F}}$ is a projection operator on $L^2(0,T;L^2(\Sigma))$. The map U is referred to as the *natural forward map* in [9, Section 2.4].

⁵In [9], the probability distribution was defined by a probability density function $f_{\nu}(t)$ with respect to another measure μ on \mathcal{D} , which in our case is the counting measure on $\{1, \ldots, N\}$. Then the correspondence between the notation of the present paper and the notation of [9] is given by $\nu_i = f_{\nu}(i)$.

The assumptions to be verified in order to apply the nonuniform bound case in [9, Theorem 2.4] are summarized in what follows.

(a) There exists constants c, C > 0 such that the following stability property holds:

(25)
$$\|Fu_0\|_{(L^2(0,T))^N}^2 \le C \|u_0\|_{L^2(K)}^2, \qquad u_0 \in \mathcal{H}_1, \\ \frac{c}{2} \|u_0\|_{L^2(K)}^2 \le \|Fu_0\|_{(L^2(0,T))^N}^2, \qquad u_0 \in \mathcal{M}_{\le j_0}.$$

(b) There exists a constant $B \ge 1$ such that the following *coherence bounds* holds:

(26)
$$||F_i\phi_{j,n}||_{L^2(0,T)} \le B\sqrt{\nu_i}, \quad i \in \{1,\dots,N\}, \ (j,n) \in \Lambda_{\le j_0}.$$

We now state a version of the abstract result [9, Theorem 2.4] in the nonuniform bound case adapted to the present context.

Theorem 3.1. Consider the previous setting. Fix $j_0 \in \mathbb{N}$ and $\gamma \in (0, 1)$. Consider:

- a signal $u_0 \in \mathcal{H}_1$;
- *i.i.d.* samples i₁,..., i_m ∈ {1,..., N} from ν = (ν₁,..., ν_N);
 measurements ỹ_k = F_{ik}u₀ + ε̃_k, k = 1,..., m, for some ε̃_k ∈ H₂;
- a sparsity level $s \geq 3$.

Moreover, suppose that the following assumptions are satisfied:

• the noise $\tilde{\varepsilon}_k$ satisfies

$$\max_{k=1,\dots,m} \|\nu_k^{-1/2} \tilde{\varepsilon}_k\|_{\mathcal{H}_2} \le \tilde{\beta}$$

(27)

(28)

for some $\tilde{\beta} \ge 0$; • the truncation error $u_R \coloneqq P_{\le j_0}^{\perp} u_0$ satisfies

$$\max_{i=1,\dots,N} \nu_i^{-1/2} \|F_i u_R\|_{\mathcal{H}_2} \le \tilde{r}, \qquad \|u_R\|_{\mathcal{H}_1} \le \tilde{r}$$

for some $\tilde{r} \geq 0$.

There exists constants $C_0, C_1, C_2, C'_3 > 0$, depending only on the constants c, C > 0in (25), such that the following holds. Let

$$m \ge C_0 \tau \max\{\log^3 \tau \log |\Lambda_{\le j_0}|, \log(1/\gamma)\}, \qquad \tau = B^2 s.$$

Let \hat{u} be a solution of

$$\min_{u \in \mathcal{M}_{\leq j_0}} \|\Phi u\|_{\ell^1} \colon \qquad \frac{1}{m} \sum_{k=1}^m \nu_k^{-1} \|F_{i_k} u_0 - y_k\|_{\mathcal{H}_2}^2 \leq (\tilde{\beta} + C_3' \tilde{r})^2.$$

Then, with probability greater than $1 - \gamma$, the following recovery estimate holds:

(29)
$$\|u_0 - \hat{u}\|_{\mathcal{H}_1} \le C_1 \frac{\sigma_s(P_{\le j_0} u_0)}{\sqrt{s}} + C_2(\tilde{\beta} + \tilde{r}).$$

As noticed in [9, Remark 2.5], condition (25), which is slightly weaker than the quasi-diagonalization condition in the statement of [9, Theorem 2.4], is sufficient for the theorem to hold.

Using [9, Proposition 2.12], we can reduce condition (a) to the following two conditions.

(a1) There exists constants c, C > 0 such that the following stability property holds:

(30)
$$c \|u_0\|_{L^2(K)}^2 \le \|Uu_0\|_{L^2(0,T;L^2(\Sigma))}^2 \le C \|u_0\|_{L^2(K)}^2, \quad u_0 \in \mathcal{H}_1,$$

where we recall that \mathcal{H}_1 was defined in (9).

(a2) The projection $\mathcal{P}_{\mathcal{F}}$ satisfies the following *balancing property*:

$$\|(I - \mathcal{P}_{\mathcal{F}})Uu_0\|_{L^2(0,T;L^2(\Sigma))}^2 \le \theta^2 \|u_0\|_{L^2(K)}^2, \qquad u_0 \in \mathcal{M}_{\le j_0}$$

for $\theta = \sqrt{c/2}$, where c is the constant in (30).

Therefore, the main part of the proof of Theorem 2.4 is to prove conditions (a1), (a2) and (b). Condition (a1) is satisfied by Assumption 2.1; the results corresponding to assumptions (a2) and (b) are stated in Proposition 3.2 and 3.4, respectively, and are proved below.

Proposition 3.2. Let $\Sigma \subset \mathbb{R}^3$ be a smooth embedded surface such that $d(K, \Sigma) > 0$, where K is as in (8). Suppose that Assumption 2.1 and (12) are satisfied. Let $\theta > 0$. Then there exists $\mu > 0$, depending only on θ , on the wavelet basis, on Σ , on $d(K, \Sigma)$, on the constants c, C in Assumption 2.1, and on C_{ecc} , such that, if the following condition holds

(31)
$$\operatorname{diam}_{\mathbb{R}^3}(E_i) \le \mu 2^{-j_0}, \quad i = 1, \dots, N,$$

for some $j_0 \in \mathbb{N}$, then the following inequality holds:

(32)
$$\|(I - \mathcal{P}_{\mathcal{F}})Uu_0\|_{L^2(0,T;L^2(\Sigma))} \le \theta \|u_0\|_{L^2(K)}, \qquad u_0 \in \mathcal{M}_{\le j_0}.$$

In the proof of Proposition 3.2, we need stability estimates with respect to the $H^{1/2}$ norm, which we state in the next Lemma. The proof of this result is provided in Appendix A.

Lemma 3.3. Let $\Sigma \subset \mathbb{R}^3$ be a smooth embedded surface and let K be a fixed compact set with $d(K, \Sigma) > 0$. Suppose that Assumption 2.1 holds. Then there a constant $C_1 > 0$, depending only on Σ and on $d(K, \Sigma)$, such that the following holds for $u_0 \in C_K^2(\mathbb{R}^3)$:

$$||Uu_0||_{L^2(0,T;H^{1/2}(\Sigma))} \le C_1 ||u_0||_{H^{1/2}(\mathbb{R}^3)}.$$

Here $H^{1/2}(\Sigma)$ denotes the corresponding Sobolev–Slobodeckij space – we refer the reader to [45], for instance, for a definition.

Proof of Proposition 3.2. Recall formula (24) for $P_{\mathcal{F}}U$. We now prove that, if (31) holds for some $\mu > 0$, then the following holds for $u_0 \in \mathcal{M}_{\leq j_0}$:

(33)
$$\|(I - P_{\mathcal{F}})Uu_0\|_{L^2(0,T;L^2(\Sigma))}^2 \le C'\mu \|u_0\|_{L^2(K)}^2,$$

for some constant C' > 0 which depends only on the wavelet basis, on Σ , on $d(K, \Sigma)$ and on C_{ecc} . Choosing $\mu \coloneqq \frac{\theta^2}{C'}$ will then imply (32), which concludes the proof. We proceed with the proof of (33). We have that

$$\|Uu_0 - P_{\mathcal{F}}Uu_0\|_{L^2(0,T;L^2(\Sigma))}^2$$

= $\sum_{i=1}^N \int_0^T \int_{E_i} \left| Uu_0(t,y) - \frac{1}{|E_i|} \int_{E_i} Uu_0(t,x) \,\mathrm{d}\sigma(x) \right|^2 \mathrm{d}\sigma(y) \mathrm{d}t$

We will estimate each term separately. We have that

$$\begin{split} &\int_{0}^{T} \int_{E_{i}} \left| Uu_{0}(t,y) - \frac{1}{|E_{i}|} \int_{E_{i}} Uu_{0}(t,x) \,\mathrm{d}\sigma(x) \right|^{2} \mathrm{d}\sigma(y) \mathrm{d}t \\ &= \int_{0}^{T} \int_{E_{i}} \left| \int_{E_{i}} \left(Uu_{0}(t,y) - Uu_{0}(t,x) \right) \frac{\mathrm{d}\sigma(x)}{|E_{i}|} \right|^{2} \mathrm{d}\sigma(y) \mathrm{d}t \\ &\leq \frac{1}{|E_{i}|} \int_{0}^{T} \int_{E_{i} \times E_{i}} |Uu_{0}(t,y) - Uu_{0}(t,x)|^{2} \,\mathrm{d}(\sigma \otimes \sigma)(x,y) \mathrm{d}t \\ &= \frac{1}{|E_{i}|} \int_{0}^{T} \int_{E_{i} \times E_{i}} |x - y|^{3} \frac{|Uu_{0}(t,y) - Uu_{0}(t,x)|^{2}}{|x - y|^{3}} \,\mathrm{d}(\sigma \otimes \sigma)(x,y) \mathrm{d}t \\ &\leq \frac{(\mathrm{diam}_{\mathbb{R}^{3}}(E_{i}))^{3}}{|E_{i}|} \int_{0}^{T} \int_{E_{i} \times E_{i}} \frac{|Uu_{0}(t,y) - Uu_{0}(t,x)|^{2}}{|x - y|^{3}} \,\mathrm{d}(\sigma \otimes \sigma)(x,y) \mathrm{d}t. \end{split}$$

We now use assumption (12) and (31) to deduce that

$$\begin{split} \int_{0}^{T} \int_{E_{i}} \left| Uu_{0}(t,y) - \frac{1}{|E_{i}|} \int_{E_{i}} Uu_{0}(t,x) \, \mathrm{d}\sigma(x) \right|^{2} \mathrm{d}\sigma(y) \mathrm{d}t \\ & \leq C_{\mathrm{ecc}}^{2} \mu 2^{-j_{0}} \int_{0}^{T} \int_{\Sigma \times \Sigma} \mathbb{1}_{E_{i} \times E_{i}}(x,y) \frac{|Uu_{0}(t,y) - Uu_{0}(t,x)|^{2}}{|x-y|^{3}} \, \mathrm{d}(\sigma \otimes \sigma)(x,y) \mathrm{d}t. \end{split}$$

Notice that the following inequality holds $(d\sigma \otimes d\sigma)$ -a.e.:

$$\sum_{i=1}^{N} \mathbb{1}_{E_i \times E_i} \le \mathbb{1}_{\Sigma \times \Sigma}.$$

Therefore, summing over i, we get

$$||Uu_0 - P_{\mathcal{F}}Uu_0||^2_{L^2(0,T;L^2(\Sigma))}$$

$$\leq C_{\rm ecc}^2 \mu 2^{-j_0} \int_0^T \int_{\Sigma \times \Sigma} \frac{|Uu_0(t, y) - Uu_0(t, x)|^2}{|x - y|^3} \, \mathrm{d}(\sigma \otimes \sigma)(x, y) \, \mathrm{d}t \\ \leq C_{\rm ecc}^2 \mu 2^{-j_0} \|Uu_0\|_{L^2(0, T; H^{1/2}(\Sigma))}^2.$$

Using the estimate from Lemma 3.3, we conclude that

$$\|Uu_0 - P_{\mathcal{F}}Uu_0\|_{L^2(0,T;L^2(\Sigma))}^2 \le C_{\text{ecc}}^2 C_1^2 \mu 2^{-j_0} \|u_0\|_{H^{1/2}(\mathbb{R}^3)}^2.$$

The Littlewood-Paley property (7) implies that

$$||u_0||^2_{H^{1/2}(\mathbb{R}^3)} \le C'' 2^{j_0} ||u_0||^2_{L^2(\mathbb{R}^3)}.$$

for some constant C'' > 0 depending only on the wavelet dictionary. We finally conclude that

$$\|Uu_0 - P_{\mathcal{F}}Uu_0\|_{L^2(0,T;L^2(\Sigma))}^2 \le C_{\text{ecc}}C_1^2 C''\mu \|u_0\|_{L^2(\mathbb{R}^3)}^2,$$

which proves (33).

The coherence bounds in (26) follow from the next Proposition.

Proposition 3.4. Let $\Sigma \subset \mathbb{R}^3$ be a smooth embedded surface such that $d(K, \Sigma) > 0$, where K is as in (8). Then there exists a constant $B_0 \ge 1$, depending only on T, on the wavelet basis, on $d(K, \Sigma)$ and on C_{ecc} , such that

$$||F_i\phi_{j,n}||_{L^2(0,T)} \le B_0|E_i|^{1/2}, \qquad i=1,\ldots,N.$$

In particular, (26) is satisfied with $B = B_0 |\Sigma|^{1/2}$.

Proof of Proposition 3.4. Let $u_{j,n} \in C^2(\mathbb{R}^3 \times [0, +\infty))$ denote the solution of (10) corresponding to the initial datum $\phi_{j,n} \in C^2_K(\mathbb{R}^3)$; in other words, using the notation from Section 2.2, we have that $u_{j,n} \coloneqq V\phi_{j,n}$.

Notice from (6) that the following estimates hold, where the implicit constants depend only on the wavelet dictionary:

(34)
$$\|\phi_{j,n}\|_{L^{\infty}(\mathbb{R}^3)} \lesssim 2^{3/2j}, \quad \|\nabla\phi_{j,n}\|_{L^{\infty}(\mathbb{R}^3)} \lesssim 2^{5/2j}, \quad (j,n) \in \Gamma.$$

Moreover, there exists a constant C > 0 such that, for every $(j, n) \in \Gamma$, there exists a ball $Q_{j,n}$ of radius $C2^{-j}$ such that

$$\operatorname{supp}(\phi_{j,n}) \subset Q_{j,n}.$$

Let $x_{j,n}$ be the center of $Q_{j,n}$. We adopt the following notation for $x \in \mathbb{R}^3$ and $t \ge 0$:

$$d_{j,n}(x) := \|x - x_{j,n}\|, \qquad D_{j,n}(x,t) := \mathbb{1}_{[d_{j,n}(x) - C2^{-j}, d_{j,n}(x) + C2^{-j}]}(t)$$

We now prove that, for $x \in \mathbb{R}^3$ and $t \ge 0$, the following holds for some constant C' > 0 depending only on C:

(35)
$$|\partial B_t(x) \cap Q_{j,n}| \le C' 2^{-2j} D_{j,n}(x,t).$$

22



Figure 2. The sets in the proof of Proposition 3.4. In red, the set $\partial B_t(x) \cap C_{j,n}$; in yellow, the set $\partial B_t(x) \cap Q_{j,n}$.

Indeed, clearly $\partial B_t(x) \cap Q_{j,n} = \emptyset$ if $t < d_{j,n}(x) - C2^{-j}$ or $t > d_{j,n}(x) + C2^{-j}$, and thus $|\partial B_t(x) \cap Q_{j,n}| = 0$ in this case. Therefore, to prove (35) we just need to find an upper bound of $|\partial B_t(x) \cap Q_{j,n}|$ for $t \in [d_{j,n}(x) - C2^{-j}, d_{j,n}(x) + C2^{-j}]$. We distinguish two cases.

(1) Suppose that $d_{j,n}(x) \leq C2^{-j}$. Then, for $t \leq d_{j,n}(x) + C2^{-j} \leq 2C2^{-j}$,

$$|\partial B_t(x) \cap Q_{j,n}| \le |\partial B_t(x)| = 4\pi t^2 \le 16\pi C^2 2^{-2j}$$

(2) Suppose that $d_{j,n}(x) > C2^{-j}$. Let $C_{j,n}$ be the simple cone – considered as a 3 dimensional solid – with vertex x whose boundary is tangent to $Q_{j,n}$ – see Fig. 2. Then the cross-section of $C_{j,n}$ subtends an angle 2θ , where

$$\sin \theta = \frac{C2^{-j}}{d_{j,n}(x)}.$$

The set $\partial B_t(x) \cap C_{j,n}$ is a spherical cap, whose area is

$$|\partial B_t(x) \cap C_{j,n}| = 2\pi (1 - \cos \theta) t^2 = 2\pi \left(1 - \sqrt{1 - \frac{C^2 2^{-2j}}{d_{j,n}(x)^2}} \right) t^2.$$

As $1 - \sqrt{1 - x} \le x$, we get that, for $t \le d_{j,n}(x) + C2^{-j} \le 2d_{j,n}(x)$,

$$|\partial B_t(x) \cap Q_{j,n}| \le |\partial B_t(x) \cap C_{j,n}| \le 2\pi \frac{C^2 2^{-2j}}{d_{j,n}(x)^2} t^2 \le 8\pi C^2 2^{-2j}$$

This proves (35). Equation (35) and (34) imply the following estimates:

$$\int_{\partial B_t(x)} |\phi_{j,n}(y)| \, \mathrm{d}\sigma(y) = \int_{\partial B_t(x) \cap Q_{j,n}} |\phi_{j,n}(y)| \, \mathrm{d}\sigma(y) \le C'' 2^{-j/2} D_{j,n}(x,t),$$

$$\int_{\partial B_t(x)} |\nabla \phi_{j,n}(y)| \, \mathrm{d}\sigma(y) = \int_{\partial B_t(x) \cap Q_{j,n}} |\nabla \phi_{j,n}(y)| \, \mathrm{d}\sigma(y) \le C'' 2^{j/2} D_{j,n}(x,t),$$

where C'' depends only on the wavelet dictionary and on C'.

For $t < d(K, \Sigma)$, we get that $u_{j,n}(\cdot, t) = 0$ on Σ ; for $t \ge d(K, \Sigma)$ and $x \in \Sigma$, using the explicit formula (11) for the solution of (10), we get that

$$\begin{aligned} |u_{j,n}(x,t)| &\leq \frac{1}{4\pi t^2} \int_{\partial B_t(x)} \left(|\phi_{j,n}(y)| + |\nabla \phi_{j,n}(y)| |y-x| \right) \, \mathrm{d}\sigma(y) \\ &\leq \frac{1}{4\pi t^2} \left(\int_{\partial B_t(x)} |\phi_{j,n}(y)| \, \mathrm{d}\sigma(y) + \operatorname{diam}_{\mathbb{R}^3}(\partial B_t(x)) \int_{\partial B_t(x)} |\nabla \phi_{j,n}(y)| \, \mathrm{d}\sigma(y) \right) \\ &\leq \frac{1}{4\pi t^2} \left(1 + \operatorname{diam}_{\mathbb{R}^3}(\partial B_t(x)) \right) C'' 2^{j/2} D_{j,n}(x,t) \\ &\leq \frac{1+2T}{4\pi d(K,\Sigma)^2} C'' 2^{j/2} D_{j,n}(x,t) \eqqcolon C'' 2^{j/2} D_{j,n}(x,t). \end{aligned}$$

We deduce that

$$\begin{aligned} \|F_i\phi_{j,n}\|_{L^2(0,T)}^2 &= \int_0^T \left|\frac{1}{|E_i|^{1/2}} \int_{E_i} u_{j,n}(x,t) \,\mathrm{d}\sigma(x)\right|^2 \mathrm{d}t \\ &\leq \frac{(C''')^2 2^j}{|E_i|} \int_0^T \left|\int_{E_i} D_{j,n}(x,t) \,\mathrm{d}\sigma(x)\right|^2 \mathrm{d}t \\ &\leq (C''')^2 2^j \int_{E_i} \int_0^T |D_{j,n}(x,t)|^2 \,\mathrm{d}t \mathrm{d}\sigma(x) \leq 2(C''')^2 C|E_i|, \end{aligned}$$

and we conclude.

Proof of Theorem 2.4. The idea is to apply Theorem 3.1. We have already argued that conditions (a1), (a2) and (b) are satisfied thanks to Assumption 2.1, Proposition 3.2 and Proposition 3.4, respectively.

We now establish a correspondence between the measurements and the noise in the setting of Theorem 2.4 with that of Theorem 3.1. In Theorem 3.1, the measurements are given by

$$\tilde{y}_k = F_{t_k} u_0 + \tilde{\varepsilon}_k,$$

where $F_{t_k} \in \mathcal{L}(\mathcal{H}_1, \mathcal{H}_2)$ is the measurement operator corresponding to the sample $t_k \in \mathcal{D}$ and $\tilde{\varepsilon}_k \in \mathcal{H}_2$ is an additive noise. In Theorem 2.4, instead, the measurements are given by

$$y_{k}(t) = \frac{1}{|E_{i_{k}}|} \int_{E_{i_{k}}} Uu_{0}(y, t) \,\mathrm{d}\sigma(y) + \varepsilon_{k}(t)$$
$$= |E_{i_{k}}|^{-1/2} \left(F_{i_{k}, T}u_{0} + |E_{i_{k}}|^{1/2} \varepsilon_{k}(t) \right).$$

Therefore the measurements and the noise in the two settings are related by the identities

(36)
$$y_k = |E_{i_k}|^{-1/2} \tilde{y}_k, \qquad \tilde{\varepsilon}_k = |E_{i_k}|^{1/2} \varepsilon_k.$$

Given this correspondence, we can now verify the assumptions on the noise and on the truncation errors. If $\|\varepsilon_k\|_{L^2(0,T)} \leq \beta$, then $\|\tilde{\varepsilon}_k\|_{L^2(0,T)} \leq |E_{i_k}|^{1/2}\beta$; therefore, condition (27) is satisfied in our case with $\tilde{\beta} = |\Sigma|^{1/2}\beta$.

The assumptions on the truncation error are given by (28). In our case, the measurement operators are uniformly bounded, as they are given by $F_i = f_{E_i} \circ U$ where f_{E_i} is the operator of unit norm defined by

$$f_{E_i}(v) \coloneqq \frac{1}{|E_i|^{1/2}} \int_{E_i} v, \qquad v \in L^2(0, T; L^2(\Sigma)).$$

Therefore, we get that, if $\|P_{\leq j_0}^{\perp} u_0\|_{\mathcal{H}_1} \leq r$, then

$$\sup_{i=1,\dots,N} \nu_i^{-1/2} \|F_i P_{\leq j_0}^{\perp} u_0\|_{(L^2(0,T))^N} \le |\Sigma|^{1/2} (\min_i |E_i|)^{-1/2} \|U\| r.$$

We conclude that (28) is satisfied with $\tilde{r} = \max\{1, |\Sigma|^{1/2} ||U|| (\min_i |E_i|)^{-1/2}\}$. Notice that ||U|| depends only on T and on Σ .

Finally, notice that in Theorem 3.1 the minimization problem to be solved is (29). In the PAT case, $\nu_k^{-1} = |\Sigma| |E_{i_k}|^{-1}$; therefore, the identity (36) implies that this problem is equivalent in our setting to

$$\min_{u \in \mathcal{M}_{\leq j_0}} \|\Phi u\|_1 \colon \quad \frac{1}{m} \sum_{k=1}^m \left\| \frac{1}{|E_{i_k}|} \int_{E_{i_k}} U u_0(y, \cdot) \,\mathrm{d}\sigma(y) - y_k \right\|_{L^2(0,T)}^2 \leq C_3 (\beta + \tilde{r})^2,$$

where $C_3 = C'_3 / |\Sigma|$, which is exactly (16).

Having established the correspondence of Theorem 3.1 with Theorem 2.4 in our setting, the result is proved. $\hfill \Box$

3.4. **Proof for general sensing patterns.** In this section, we outline a sketch of the proof of Theorem 2.7. Essentially, the proof follows along the lines of the proof of Theorem 2.4. The idea is always to apply Theorem 3.1 and verify that conditions (a1), (a2), (b) stated in Sec. 3.3 hold for suitable measurement operators and forward maps.

In this case, we define the measurement operators as

$$\tilde{F}_{i,T}u_0 \coloneqq \frac{1}{\sqrt{N}} P_i AMUu_0$$

The corresponding forward map is then given by

$$\tilde{F}_T u_0 \coloneqq \frac{1}{\sqrt{N}} AMU u_0.$$

Using the fact that A is a unitary matrix, we get that

$$\begin{split} \|\tilde{F}_{T}u_{0}\|_{(L^{2}(0,T))^{N}}^{2} &= \|\tilde{F}_{T}u_{0}\|_{L^{2}(0,T;\ell^{2}(\mathbb{C}^{N}))}^{2} = \frac{1}{N} \int_{0}^{T} |AMUu_{0}(t)|^{2} \,\mathrm{d}t \\ &= \frac{1}{N} \int_{0}^{T} |MUu_{0}(t)|^{2} \,\mathrm{d}t = \frac{1}{N} \|MUu_{0}\|_{(L^{2}(0,T))^{N}}^{2}. \end{split}$$

Explicitly, the operator on the RHS is given by

$$\left(\frac{1}{\sqrt{N}}MUu_0(t)\right)_i = \frac{1}{\sqrt{N|E_i|}} \frac{1}{\sqrt{|E_i|}} \int_{E_i} Uu_0(t,y) \,\mathrm{d}\sigma(y) = \frac{1}{\sqrt{N|E_i|}} F_i u_0(t).$$

Using (18), we get that, up to an isomorphism, $\frac{1}{\sqrt{N}}MUu_0(t)$ is given by the forward map from Sec. 3.3. Therefore, we conclude that condition (a) in this case follows as in the case of Theorem 2.4.

Moreover, condition (b) follows directly from (20), with $\nu_i \equiv 1/\sqrt{N}$. The other verifications concerning assumptions on the noise and on the truncation error follow exactly as in the proof of Theorem 2.4, leading to the validation of the hypotheses of Theorem 3.1, which can then be applied to prove Theorem 2.7.

Acknowledgments

Co-funded by the European Union (ERC, SAMPDE, 101041040, and Next Generation EU). Views and opinions expressed are however those of the authors only and do not necessarily reflect those of the European Union or the European Research Council. Neither the European Union nor the granting authority can be held responsible for them. The author is member of the "Gruppo Nazionale per l'Analisi Matematica, la Probabilità e le loro Applicazioni", of the "Istituto Nazionale di Alta Matematica". The research was supported in part by the MIUR Excellence Department Project awarded to Dipartimento di Matematica, Università di Genova, CUP D33C23001110001.

I would also like to thank Prof. Giovanni S. Alberti and Prof. Matteo Santacesaria, for introducing me to photoacoustic tomography and for their careful revision of the manuscript, and Prof. Rakesh, for the insightful discussion regarding stability estimates for inverse problems in hyperbolic PDEs.

References

- P.A. Absil, R. Mahony, and R. Sepulchre. Optimization Algorithms on Matrix Manifolds. Princeton University Press, 2009.
- [2] Sebastián Acosta and Carlos Montalto. Multiwave imaging in an enclosure with variable wave speed. *Inverse Problems*, 31, 2015.

- [3] M. Agranovsky, P. Kuchment, and L. Kunyansky. On reconstruction formulas and algorithms for the thermoacoustic tomography. In *Photoacoustic imaging and spectroscopy*, pages 89–102. CRC press, 2009.
- [4] Mark Agranovsky and Peter Kuchment. Uniqueness of reconstruction and an inversion procedure for thermoacoustic and photoacoustic tomography with variable sound speed. *Inverse Problems*, 23:2089 – 2102, 2007.
- [5] Giovanni Alberti, Yves Capdeboscq, and Yannick Privat. On the randomised stability constant for inverse problems. *Mathematics in Engineering*, 2:264–286, 02 2020.
- [6] Giovanni S. Alberti, Paolo Campodonico, and Matteo Santacesaria. Compressed sensing photoacoustic tomography reduces to compressed sensing for undersampled fourier measurements. *SIAM Journal on Imaging Sciences*, 14(3):1039–1077, 2021.
- [7] Giovanni S. Alberti and Yves Capdeboscq. Lectures on elliptic methods for hybrid inverse problems. 2018.
- [8] Giovanni S. Alberti, Alessandro Felisi, Matteo Santacesaria, and S. Ivan Trapasso. Compressed sensing for inverse problems and the sample complexity of the sparse Radon transform. *Journal* of the European Mathematical Society (to appear).
- [9] Giovanni S. Alberti, Alessandro Felisi, Matteo Santacesaria, and S. Ivan Trapasso. Compressed sensing for inverse problems II: applications to deconvolution, source recovery, and MRI. arXiv:2302.03577, 2025.
- [10] Giovanni S. Alberti and Matteo Santacesaria. Infinite dimensional compressed sensing from anisotropic measurements and applications to inverse problems in PDE. Applied and Computational Harmonic Analysis, 50:105–146, 2021.
- [11] Habib Ammari, Emmanuel Bossy, Vincent Jugnon, and Hyeonbae Kang. Mathematical modeling in photoacoustic imaging of small absorbers. SIAM Review, 52(4):677–695, 2010.
- [12] Stephan Antholzer, Johannes Schwab, Johnnes Bauer-Marschallinger, Peter Burgholzer, and Markus Haltmeier. NETT regularization for compressed sensing photoacoustic tomography. In *BiOS*, 2019.
- [13] Simon Arridge, Paul Beard, Marta Betcke, Ben Cox, Nam Huynh, Felix Lucka, Olumide Ogunlade, and Edward Zhang. Accelerated high-resolution photoacoustic tomography via compressed sensing. *Physics in Medicine & Biology*, 61(24):8908, dec 2016.
- [14] Zakaria Belhachmi, Thomas Glatz, and Otmar Scherzer. A direct method for photoacoustic tomography with inhomogeneous sound speed. *Inverse Problems*, 32(4):045005, mar 2016.
- [15] J. Bergh and J. Löfström. Interpolation Spaces: An Introduction. Grundlehren der mathematischen Wissenschaften. Springer Berlin Heidelberg, 2012.
- [16] Marta M. Betcke, Ben T. Cox, Nam Huynh, Edward Z. Zhang, Paul C. Beard, and Simon R. Arridge. Acoustic wave field reconstruction from compressed measurements with application in photoacoustic tomography. *IEEE Transactions on Computational Imaging*, 3(4):710–721, 2017.
- [17] P. Burgholzer, M. Sandbichler, F. Krahmer, T. Berer, and M. Haltmeier. Sparsifying transformations of photoacoustic signals enabling compressed sensing algorithms. In Alexander A. Oraevsky and Lihong V. Wang, editors, *Photons Plus Ultrasound: Imaging and Sensing 2016*, volume 9708, page 970828. International Society for Optics and Photonics, SPIE, 2016.
- [18] E.J. Candes, J. Romberg, and T. Tao. Robust uncertainty principles: exact signal reconstruction from highly incomplete frequency information. *IEEE Transactions on Information Theory*, 52(2):489–509, 2006.
- [19] Emmanuel J. Candès and David Donoho. New tight frames of curvelets and optimal representations of objects with c^2 singularities. Communications on Pure and Applied Mathematics, 57:219 – 266, 02 2004.

- [20] Olga Chervova and Lauri Oksanen. Time reversal method with stabilizing boundary conditions for photoacoustic tomography. *Inverse Problems*, 32(12):125004, nov 2016.
- [21] Benjamin T. Cox, Simon Robert Arridge, and Paul C. Beard. Photoacoustic tomography with a limited-aperture planar sensor and a reverberant cavity. *Inverse Problems*, 23:S95 S112, 2007.
- [22] D.L. Donoho. Compressed sensing. IEEE Transactions on Information Theory, 52(4):1289– 1306, 2006.
- [23] Marco F. Duarte, Mark A. Davenport, Dharmpal Takhar, Jason N. Laska, Ting Sun, Kevin F. Kelly, and Richard Baraniuk. Single-pixel imaging via compressive sampling. *IEEE Signal Process. Mag.*, 25:83–91, 2008.
- [24] Lawrence C. Evans. Partial Differential Equations. American Mathematical Society, 2nd edition, 2010.
- [25] Alessandro Felisi and Luca Rondi. Full discretization and regularization for the calderón problem. Journal of Differential Equations, 410:513–577, 2024.
- [26] David Finch and Sarah K. Patch. Determining a function from its mean values over a family of spheres. SIAM Journal on Mathematical Analysis, 35(5):1213–1240, 2004.
- [27] Simon Foucart and Holger Rauhut. A mathematical introduction to compressive sensing. In Applied and Numerical Harmonic Analysis, 2013.
- [28] Keisuke Goda, Kevin. K. Tsia, and Bahram Jalali. Serial time-encoded amplified imaging for real-time observation of fast dynamic phenomena. *Nature*, 458:1145–1149, 2009.
- [29] Kanghui Guo and Demetrio Labate. Optimally sparse multidimensional representation using shearlets. SIAM J. Math. Anal., 39(1):298–318, 2007.
- [30] Markus Haltmeier, Thomas Berer, Sunghwan Moon, and Peter Burgholzer. Compressed sensing and sparsity in photoacoustic tomography. *Journal of Optics*, 18, 2016.
- [31] Markus Haltmeier, Michael Sandbichler, Thomas Berer, Johannes Bauer-Marschallinger, Peter Burgholzer, and Linh V. Nguyen. A sparsification and reconstruction strategy for compressed sensing photoacoustic tomography. *The Journal of the Acoustical Society of America*, 143 6:3838, 2017.
- [32] Markus Haltmeier, Matthias Ye, Karoline Felbermayer, Florian Hinterleitner, and Peter Burgholzer. Design, implementation, and analysis of a compressed sensing photoacoustic projection imaging system. *Journal of Biomedical Optics*, 29, 2024.
- [33] Benjamin Robert Holman and Leonid A. Kunyansky. Gradual time reversal in thermo- and photo-acoustic tomography within a resonant cavity. *Inverse Problems*, 31, 2014.
- [34] Nam Huynh, Edward Z. Zhang, Marta M. Betcke, Simon Robert Arridge, Paul C. Beard, and Benjamin T. Cox. Single-pixel optical camera for video rate ultrasonic imaging. *Optica*, 2016.
- [35] Nuutti Hyvönen. Approximating idealized boundary data of electric impedance tomography by electrode measurements. *Mathematical Models and Methods in Applied Sciences*, 19:1185–1202, 2009.
- [36] Peter Kuchment and Leonid A. Kunyansky. Mathematics of thermoacoustic tomography. European Journal of Applied Mathematics, 19:191 224, 2007.
- [37] Leonid A. Kunyansky, Benjamin Robert Holman, and Benjamin T. Cox. Photoacoustic tomography in a rectangular reflecting cavity. *Inverse Problems*, 29, 2013.
- [38] Gitta Kutyniok and Wang-Q Lim. Compactly supported shearlets are optimally sparse. J. Approx. Theory, 163(11):1564–1589, 2011.
- [39] Irena Lasiecka and Roberto Triggiani. Trace regularity of the solutions of the wave equation with homogeneous neumann boundary conditions and data supported away from the boundary. *Journal of Mathematical Analysis and Applications*, 141:49–71, 1989.

- [40] Sixing Li, Xiaoyun Ding, Zhangming Mao, Yuchao Chen, Nitesh Nama, Feng Guo, Peng Li, Lin Wang, Craig E. Cameron, and Tony Jun Huang. Standing surface acoustic wave (ssaw)-based cell washing. *Lab on a chip*, 15 1:331–8, 2015.
- [41] Stéphane Mallat. A Wavelet Tour of Signal Processing. The Sparse Way. Elsevier/Academic Press, Amsterdam, 3rd edition, 2009.
- [42] Chase Mathison. Sampling in thermoacoustic tomography. Journal of Inverse and Ill-posed Problems, 28:881 – 897, 2019.
- [43] Jing Meng, Dong Liang, and Liang Song. Compressed sensing photoacoustic tomography in vivo in time and frequency domains. In Proceedings of 2012 IEEE-EMBS International Conference on Biomedical and Health Informatics, pages 717–720, 2012.
- [44] Yves Meyer. Wavelets and Operators. Cambridge University Press, Cambridge, 1992.
- [45] Eleonora Di Nezza, Giampiero Palatucci, and Enrico Valdinoci. Hitchhiker's guide to the fractional sobolev spaces. Bulletin Des Sciences Mathematiques, 136:521–573, 2011.
- [46] Linh V Nguyen. On singularities and instability of reconstruction in thermoacoustic tomography. Contemporary Mathematics, 559, 2011.
- [47] Jean Provost and Frédéric Lesage. The application of compressed sensing for photo-acoustic tomography. *IEEE Transactions on Medical Imaging*, 28(4):585–594, 2009.
- [48] M. Sandbichler, F. Krahmer, T. Berer, P. Burgholzer, and M. Haltmeier. A novel compressed sensing scheme for photoacoustic tomography. SIAM Journal on Applied Mathematics, 75(6):2475–2494, 2015.
- [49] Plamen Stefanov and Gunther Uhlmann. Thermoacoustic tomography with variable sound speed. *Inverse Problems*, 25:075011, 2009.
- [50] Plamen Stefanov and Yang Yang. Multiwave tomography in a closed domain: averaged sharp time reversal. *Inverse Problems*, 31, 2014.
- [51] Plamen Stefanov and Yang Yang. Multiwave tomography with reflectors: Landweber's iteration. Inverse Problems & Imaging, 11(2), 2017.
- [52] Jenni Tick, Aki Pulkkinen, and Tanja Tarvainen. Modelling of errors due to speed of sound variations in photoacoustic tomography using a Bayesian framework. *Biomedical Physics & Engineering Express*, 6, 2019.
- [53] Valery V. Tuchin. Handbook of optical biomedical diagnostics, second edition, volume 2: Methods, 2016.
- [54] Lihong V. Wang. Photoacoustic imaging and spectroscopy. Journal of Biomedical Optics, 15:059901, 2009.
- [55] Lihong V. Wang and Hsin-I Wu. Biomedical optics: Principles and imaging, 2008.
- [56] Edward Z. Zhang, Jan Laufer, and Paul C. Beard. Backward-mode multiwavelength photoacoustic scanner using a planar fabry-perot polymer film ultrasound sensor for high-resolution three-dimensional imaging of biological tissues. *Applied optics*, 47 4:561–77, 2008.

APPENDIX A. INTERPOLATION ESTIMATE

In this section, we provide a proof of the interpolation estimate from Lemma 3.3.

Proof of Lemma 3.3. The idea of the proof is to use the complex interpolation method to obtain stability with respect to $H^{1/2}$ norms using stability estimates in the L^2 and H^1 norms, respectively, from Assumption 2.1.

Let K' be the compact set from Assumption 2.1; recall that

 $K \subset \operatorname{int}(K').$

We also fix a finite atlas of Σ , given by $(V_i, \varphi_i)_{i=1}^n$, and a partition of unity $(\eta_i)_{i=1}^n \subset C^{\infty}(\Sigma)$ subordinate to it. From Assumption 2.1, we get that, for $i = 1, \ldots, n$ and $u_0 \in C^2_{K'}(\mathbb{R}^3)$,

(37)
$$\int_0^T \int_{\Sigma} |\eta_i U u_0(y,t)|^2 \, \mathrm{d}\sigma(y) \, \mathrm{d}t \le \|U u_0\|_{L^2(0,T;L^2(\Sigma))}^2 \le C^2 \|u_0\|_{L^2(\mathbb{R}^3)}^2,$$

and also

(38)

$$\begin{aligned}
\int_{0}^{T} \int_{\Sigma} |\nabla_{\Sigma} (\eta_{i} U u_{0}) (y, t)|^{2} d\sigma(y) dt \\
&\leq 2 \int_{0}^{T} \int_{\Sigma} |\nabla_{\Sigma} \eta_{i}|^{2} |U u_{0}(y, t)|^{2} d\sigma(y) dt \\
&+ 2 \int_{0}^{T} \int_{\Sigma} |\nabla V u_{0}(y, t)|^{2} d\sigma(y) dt \\
&\leq 2 C^{2} \|\nabla_{\Sigma} \eta_{i}\|_{L^{\infty}(\mathbb{R}^{3})}^{2} \|u_{0}\|_{L^{2}(\mathbb{R}^{3})}^{2} + 2 C_{1}^{2} \|u_{0}\|_{H^{1}(\mathbb{R}^{3})}^{2} \\
&\leq C_{2}^{2} \|u_{0}\|_{H^{1}(\mathbb{R}^{3})}^{2},
\end{aligned}$$

where $C_2 \coloneqq \sqrt{2} \left(C^2 \max_i \| \nabla_{\Sigma} \eta_i \|_{L^{\infty}(\mathbb{R}^3)}^2 + C_1^2 \right)^{1/2}$; the meaning of $\nabla_{\mathbb{R}^3}$ and ∇_{Σ} is the same as in Sec. 3.1. We now have that

$$\begin{split} \int_{0}^{T} \int_{\Sigma} |\eta_{i} U u_{0}(y,t)|^{2} \, \mathrm{d}\sigma(y) \mathrm{d}t \\ &= \int_{0}^{T} \int_{\varphi_{i}(V_{i})} |\eta_{i} U u_{0}(\varphi_{i}^{-1}(x),t)|^{2} |\det(D\varphi_{i}^{-1})(x)| \, \mathrm{d}x \mathrm{d}t \\ &\geq C_{3}^{2} \int_{0}^{T} \int_{\varphi_{i}(V_{i})} |\eta_{i} U u_{0}(\varphi_{i}^{-1}(x),t)|^{2} \, \mathrm{d}x \mathrm{d}t \\ &= C_{3}^{2} \|(\eta_{i} U u_{0}) \circ (\varphi_{i}^{-1} \otimes I)\|_{L^{2}(0,T;L^{2}(\mathbb{R}^{2}))}^{2}. \end{split}$$

where $C_3 \coloneqq \min_{\substack{x \in \varphi_i(V_i) \\ i=1,\dots,n}} |\det(D\varphi_i^{-1})(x)|^{1/2}$. This, together with (37), implies that, for $i = 1, \dots, n$ and $u_0 \in C^2_{K'}(\mathbb{R}^3)$,

(39)
$$\|(\eta_i U u_0) \circ (\varphi_i^{-1} \otimes I)\|_{L^2(0,T;L^2(\mathbb{R}^2))} \le C_4 \|u_0\|_{L^2(\mathbb{R}^3)},$$

where $C_4 \coloneqq C/C_3$.

Analogously, using (38), we get that, for $i = 1, \ldots, n$ and $u_0 \in C^2_{K'}(\mathbb{R}^3)$,

$$\| \left(\nabla_{\Sigma}(\eta_{i} U u_{0}) \right) \circ (\varphi_{i}^{-1} \otimes I) \|_{L^{2}(0,T;L^{2}(\mathbb{R}^{2}))} \leq C_{5} \| u_{0} \|_{H^{1}(\mathbb{R}^{3})},$$

where $C_5 := C_2/C_3$. For $v \in C^2_{V_i}(\Sigma)$, we have that

$$\nabla_{\Sigma}(v \circ \varphi_i^{-1})(x)| = |(D\varphi_i^{-1})^*(x)(\nabla_{\Sigma}v)(\varphi^{-1}(x))| \le C_6|(\nabla_{\Sigma}v)(\varphi^{-1}(x))|,$$

where $C_6 \coloneqq \max_{x \in \varphi_i(V_i)} \|D\varphi_i^{-1}(x)\|$; here the matrix norm $\|\cdot\|$ refers to the operator norm on $\ell^2(\mathbb{R}^2)$. This implies that, for $i = 1, \ldots, n$ and $u_0 \in \mathcal{D}_{K_{\epsilon}}(\mathbb{R}^3)$,

(40)
$$\begin{aligned} \|(\eta_{i}Uu_{0})\circ(\varphi_{i}^{-1}\otimes I)\|_{L^{2}(0,T;H^{1}(\mathbb{R}^{2}))}^{2}\\ &=\|(\eta_{i}Uu_{0})\circ(\varphi_{i}^{-1}\otimes I)\|_{L^{2}(0,T;L^{2}(\mathbb{R}^{2}))}^{2}\\ &+\|\nabla((\eta_{i}Uu_{0})\circ(\varphi_{i}^{-1}\otimes I))\|_{L^{2}(0,T;L^{2}(\mathbb{R}^{2}))}^{2}\\ &\leq C_{4}^{2}\|u_{0}\|_{L^{2}(\mathbb{R}^{3})}^{2}+C_{5}^{2}C_{6}^{2}\|u_{0}\|_{H^{1}(\mathbb{R}^{3})}^{2}\leq C_{7}^{2}\|u_{0}\|_{H^{1}(\mathbb{R}^{3})}^{2}\end{aligned}$$

where $C_7 := (C_4^2 + C_5^2 C_6^2)^{1/2}$. Let $\eta \in C^2(\mathbb{R}^3)$ be a smooth cutoff such that $\eta \in [0, 1], \eta|_K \equiv 1$ and $\operatorname{supp}(\eta) \subset K'$. Given $u_0 \in C^2(\mathbb{R}^3)$, we have that $\eta u_0 \in C^2_{K'}(\mathbb{R}^3)$. For every $i = 1, \ldots, n$, we consider the following linear operators

$$T_i u_0 \coloneqq \left(\eta_i U(\eta u_0)\right) \circ (\varphi_i^{-1} \otimes I),$$

defined for $u_0 \in C^2(\mathbb{R}^3)$. The stability estimates obtained in (39) and (40) imply that

$$\begin{aligned} \|T_{i}u_{0}\|_{L^{2}(0,T;L^{2}(\mathbb{R}^{2}))} &\leq C_{4}\|\eta u_{0}\|_{L^{2}(\mathbb{R}^{3})} \leq C_{4}\|u_{0}\|_{L^{2}(\mathbb{R}^{3})}, \\ \|T_{i}u_{0}\|_{L^{2}(0,T;H^{1}(\mathbb{R}^{2}))} &\leq C_{7}\|\eta u_{0}\|_{H^{1}(\mathbb{R}^{3})} \leq C_{7}C_{8}\|u_{0}\|_{H^{1}(\mathbb{R}^{3})}, \end{aligned}$$

where C_8 depends only on η .⁶ These estimates imply that T_i can be extended by density and continuity to a bounded linear operator $T_i: L^2(\mathbb{R}^3) \to L^2(0,T;L^2(\mathbb{R}^2))$ such that $T_i(H^1(\mathbb{R}^3)) \subset L^2(0,T; H^1(\mathbb{R}^2)).$

We can now apply the complex interpolation method [15, Theorem 4.1.2, Theorem 6.4.5] to conclude that

$$||T_i u_0||_{L^2(0,T;H^{1/2}(\mathbb{R}^2))} \le C_9 ||u_0||_{H^{1/2}(\mathbb{R}^3)},$$

where C_9 can be chosen, for instance, to be $\max(C_4, C_7C_8)$. This implies that, for $u_0 \in C^2_K(\mathbb{R}^3),$

$$\|(\eta_i U u_0) \circ (\varphi_i^{-1} \otimes I)\|_{L^2(0,T;H^{1/2}(\mathbb{R}^2))} \le C_9 \|u_0\|_{H^{1/2}(\mathbb{R}^3)},$$

as in this case $\eta u_0 = u_0$.

By definition of the $H^{1/2}(\Sigma)$ norm, there exists a constant $C_{10} > 0$, depending only on the atlas of Σ , such that, for $i = 1, \ldots, n$ and for $u_0 \in C^2_K(\mathbb{R}^3)$,

$$\begin{aligned} \|\eta_i U u_0\|_{L^2(0,T;H^{1/2}(\Sigma))} &\leq C_{10} \| \left(\eta_i U u_0\right) \circ \left(\varphi_i^{-1} \otimes I\right) \|_{L^2(0,T;H^{1/2}(\mathbb{R}^2))} \\ &\leq C_9 C_{10} \| u_0 \|_{H^{1/2}(\mathbb{R}^3)}. \end{aligned}$$

⁶Notice that it would not have been possible to obtain the bound $\|\eta u_0\|_{H^1(\mathbb{R}^3)} \lesssim \|u_0\|_{H^1(\mathbb{R}^3)}$ for a non-smooth cutoff η ; this motivates the necessity of considering the slightly bigger set K'.

We conclude that, for $u_0 \in C^2_K(\mathbb{R}^3)$,

$$\|Uu_0\|_{L^2(0,T;H^{1/2}(\Sigma))} \le \sum_{i=1}^n \|\eta_i Uu_0\|_{L^2(0,T;H^{1/2}(\Sigma))} \le nC_9C_{10}\|u_0\|_{H^{1/2}(\mathbb{R}^3)}.$$

This concludes the proof.

Malga Center, Department of Mathematics, University of Genoa, Via Dode-Caneso 35, 16146 Genova, Italy.

 $Email \ address: \verb"alessandro.felisi@edu.unige.it"$