

Prompt and circumstance: A word-by-word LLM prompting approach to interlinear glossing for low-resource languages

Micha Elsner

Department of Linguistics
The Ohio State University
melsner0@gmail.com

David Liu

Sylvania High School
dliuhanwei.8@gmail.com

Abstract

Partly automated creation of interlinear glossed text (IGT) has the potential to assist in linguistic documentation. We argue that LLMs can make this process more accessible to linguists because of their capacity to follow natural-language instructions. We investigate the effectiveness of a retrieval-based LLM prompting approach to glossing, applied to the seven languages from the SIGMORPHON 2023 shared task. Our system beats the BERT-based shared task baseline for every language in the morpheme-level score category, and we show that a simple 3-best oracle has higher word-level scores than the challenge winner (a tuned sequence model) in five languages. In a case study on Tsez, we ask the LLM to automatically create and follow linguistic instructions, reducing errors on a confusing grammatical feature. Our results thus demonstrate the potential contributions which LLMs can make in interactive systems for glossing, both in making suggestions to human annotators and following directions.

1 Introduction

At least half of the world’s languages are under-documented (Bird, 2011) and at least 2500 are endangered (Moseley, 2012). A multitude of factors contribute to language endangerment and death: a lack of available resources; pressure from dominant languages, and governmental policies that impair linguistic diversity all contribute to the gradual loss of a language (Bromham et al., 2022). As speaker populations dwindle, documentation has become a priority in order to enable future revitalization projects. Interlinear glossed text (IGT) is a widely-used format for documentary projects, utilizing grammatical labels and morpheme segmentation in order to construct translations for individual words and morphemes. While IGT efforts can be beneficial from a revitalization standpoint, the burdens of

cost and time create the need for an expedited procedure that can surpass the rate of language death (Moeller and Hulden, 2018).

Semi-automated methods using computational assistance for glossing can potentially help linguists to annotate more data faster (Palmer et al., 2009; Moeller and Hulden, 2018). The best current approaches to glossing (e.g. Yang et al., 2024a) use purpose-built sequence models, but there has been some recent interest in LLMs as glossing models (Ginn et al., 2024). We believe this is an important direction because LLMs are (in principle) capable of interacting with linguists and native-speaker consultants in a more natural way than sequence models: they can follow instructions. Rather than finding and annotating examples of a problematic construction, the user could explain the appropriate generalization to the system or supply a passage from a descriptive grammar, changing the terms on which users can interact with language processing technology (Meighan, 2021). But recent work on low-resource translation has cast doubt on LLMs’ ability to understand this kind of instruction in practice (Court and Elsner, 2024; Aycock et al., 2024). We explore what types of information, examples and instructions most benefit LLMs in performing linguistic analysis, and provide a first demonstration that linguistic instructions can reduce error rates for labeling a specific construction in Tsez. We believe our findings also shed light on previous results involving LLMs’ failure to follow linguistic instructions while translating.

We use word-by-word retrieval based prompting to gloss sentences in the seven languages of the SIGMORPHON 2023 shared task (Ginn et al., 2023). This approach differs somewhat from whole-sentence prompting (Ginn et al., 2024) and prompting for post-processing (Yang et al., 2024a). Word-by-word prompting enables easy elicitation of k -best options and we show that the LLM is often *nearly* right even when its top guess is wrong—

a feature that could be very helpful for human annotators, since machine suggestions can speed up manual annotation (Palmer et al., 2009).¹

Our work thus makes three major contributions. We replicate earlier results showing that prompt-based glossing performs acceptably (beating the 2023 baseline in every language) for inter-linear glossing, but not at SOTA; we show these results apply to word-by-word as well as sentence-level retrieval.² We find that a simple 3-best oracle beats the challenge winner for all but two languages, indicating that LLM prompting has high potential to assist a human annotator by suggesting high-quality options. Finally, a case study on Tsez shows that automatically-generated linguistic instructions can reduce errors involving a particular set of commonly-confused tags by 10%.

2 Related work

2.1 Automated glossing

Models for automated glossing have used both non-neural (Palmer et al., 2009; Moeller and Hulden, 2018) and neural (Moeller and Hulden, 2018; Zhao et al., 2020) learning methods. The SIGMORPHON challenge baseline (Ginn, 2023) uses the RoBERTa architecture, while the challenge winner (Girrbach, 2023) uses an encoder-decoder model with hard attention which automatically induces morphological segmentations from the data. Such relatively small task-specific and language-specific models still represent the state of the art for the glossing task, because they can learn efficiently from the small datasets available and because they are cheap to apply in the computational sense.

Neither Ginn (2023) nor Girrbach (2023) use sentence translations. Although this simplicity is in some sense an advantage, it is also a limitation of the approach, since in some cases, the correct gloss is more evident from the translation, for instance in disambiguating homophones or syncretic morphemes (Zhao et al., 2020). Yang et al. (2024a) adds embeddings of the sentence translations on top of the Girrbach (2023) model and obtain an improvement of 4% in the word-level accuracy score.

The utility of translations motivates Ginn et al. (2024) to apply LLMs in the glossing task.³ Like

ours, their attempt is retrieval-based. They use one prompt per sentence, retrieving up to 100 similar sentences per instance; the most effective similarity metric is chrF (Popović, 2015). In the four languages they ran, their results lie between the challenge baseline and Girrbach (2023) except in Gitksan, which has the lowest absolute scores due to its very high OOV rate. Aycock et al. (2024) also apply LLMs to glossing the Kalamang language using glossed examples from a grammar book. Their glossing system improves on the challenge baseline, and benefits slightly from the addition of generated text explaining some typological features of Kalamang (such as the absence of definite articles). Unlike this work, they do not attempt to disambiguate particular constructions.

Yang et al. (2024b) uses LLMs in a different way, to post-correct lexical glosses proposed by an encoder-decoder model. This technique is effective for several of the challenge languages. They find that post-correction is effective only with lexical rather than grammatical tags, which are apparently produced more accurately by the original encoder-decoder than the LLM. While this post-processing approach is useful for ensuring that the proposed lexical glosses match the translation, it does not address our other motivation of allowing automatic or linguist-guided instructions to affect grammatical analyses.

2.2 LLMs for low-resource NLP

The motivations for using LLMs in glossing (increased sensitivity to translations, and the accessibility of using explicit instructions in place of examples) also apply to other linguistic tasks, notably low-resource translation. Retrieval-based translation systems use a similar framework to LLM-based glossing in which sentences from parallel corpora, or entries from dictionaries and other linguistic documentation, are retrieved in an item-specific way and added to prompts. Several studies in this area have found that, although dictionary sources can improve translation, explicit grammatical instructions do not (Court and Elsner, 2024; Zhang et al., 2024; Elsner and Needle, 2023). One claimed exception, Reid et al. (2024), uses an entire grammar for the Kalamang language as a source, but subsequent work (Aycock et al., 2024) shows that the improvement is due to the example sentences, not the grammatical text. Even when the attempts to use Llama2 for translation embeddings.

¹Whether machine suggestions are helpful or not depends on how examples are selected and how fluent the annotator is in the object language.

²Code and results at <https://anonymous.4open.science/r/glossing-project-DD0D/README.md>.

³Yang et al. (2024a) report preliminary and unsuccessful

retrieved grammar instructions are curated by hand to assure that the passages are relevant, they still do not lead to improvements (Court and Elsner, 2024). Kornilov and Shavrina (2024) ask LLMs to answer explicit questions about the typological features of various languages using retrieval of grammar passages, with good but not perfect results. However, this task requires the LLM to understand and respond to linguistic terminology at an abstract level, rather than applying linguistic terminology to the analysis of individual language examples. We find below that this task remains challenging even when the abstract instructions are relevant and correct. Understanding how linguistic terminology is processed in the glossing task might also lead to better techniques for retrieval-based translation.

3 Task and data

We follow standard interlinear glossed text formatting, adhering to the Leipzig glossing format (Bickel et al., 2015). The datasets we use come from the 2023 SIGMORPHON glossing shared task (Ginn et al., 2023). The seven languages provided in the dataset are Arapaho, Gitksan, Lezgi, Natugu, Nyangbo, Tsez, and Uspanteko. The number of training sentences for each language varies in size; Arapaho has around 39,000 while Gitksan has merely 31. We use the Track 1 data files, which do not have morphological segmentation, for our investigation. Track 1 of the shared task prohibited the use of outside resources, including pretrained models like LLMs, but we believe our system is still most comparable to other Track 1 systems because the LLM we chose has little ability to complete sentences in the test languages (Appendix A) and because the greatest advantage available to Track 2 systems was morphological segmentation. We chose not to run the full Arapaho test set due to the cost concerns arising from such a large dataset, so we tested the first 100 sentences; we label this abbreviated test set as “arp*” in the tables. Also for cost reasons, we do not run experiments on multiple languages while developing our prompts and retrieval strategies. We focused our development and prompt tuning on Tsez (ddo) due to its comfortable size of 3,558 training and 445 dev sentences.

4 Prompt-based glossing

We use GPT-4o as our LLM. (Although an open model would be preferable to increase reproducibil-

ity, Llama and other open models perform poorly on linguistic tasks (Court and Elsner, 2024; Aycock et al., 2024) unless fine-tuned.) We run prompts for glossing with temperature 0 and prompts for instruction generation (Section 6) with temperature 0.25.

4.1 Prompting

The prompt for our retrieval-based glossing system (for a full example, see Appendix C) consists of a brief introduction informing GPT4 what target word it must gloss, what language the word is in, and the translation of the sentence the word is drawn from. A brief instructions paragraph dedicated to glossing follows, instructing the system to use Leipzig tagging conventions and including a JSON format for 3-best outputs.

We then provide retrieved items from the corpus: We find up to three exact match sentences showing the word in its full sentential context. We find up to three approximate match sentences; approximate matches were those with the largest longest common substring with the target word, provided that substring was at least four characters long. We also carry out a reverse retrieval process on each word in the metalanguage (English/Spanish) translation: we show words for which glosses most commonly incorporate the metalanguage word, for example: “*Words for “away” include: boyno (III-take.away-PFV.CVB), royno (IV-take.away-PFV.CVB), boxin (III-run.away-PFV.CVB), oxin (run.away-PST.UNW), boxin (I.PL-run.away-PFV.CVB).*” Reverse indexing allows us to find morphological relatives of words which do not appear in training, and for which the approximate match criteria are unable to retrieve appropriate examples.

We use exact-match retrieval to build a **retrieval only** system, in which we find the most common gloss for the word in the training data, and return ‘?’ if the word never occurs. We insert the retrieval-based gloss of the rest of the sentence (excepting the target word) into the prompt so that the system can make inferences about the likely context of the target word.

Finally, because the retrieved sentences do not always illustrate the word’s full distribution of usage in the corpus, we also summarize the word’s empirical distribution of glosses over the entire training corpus, for example: “*The word tiyn often appears with the following tags (but it may also appear with similar tags that are not shown here):*

	SMB	SMW	Ginn	Retr.	Ours
arp*	44.19	78.47	-	41.06	52.57
git	8.54	11.72	12.3	5.07	8.68
lez	41.62	62.1	51.6	21.90	52.62
ntu	18.17	56.38	37.0	19.66	33.19
nyb	14.21	86.74	-	75.21	78.26
ddo	51.23	73.95	-	35.81	57.59
usp	57.24	70.05	61.4	53.47	57.59

Table 1: Morpheme-level test set scores: SMB: Shared task official baseline; SMW: Track 1 challenge winner (either Tübingen-1 or 2); Ginn: GPT-4 with sentence-level prompt (Ginn et al., 2024, Fig. 7); Retr: Our retrieval baseline; Ours: our system.

end-PFV.CVB (60%), end-PST.UNW (40%).”

Although we elicit three candidate glosses per word, we report our main results based on only the first gloss in subsection 4.2. We discuss using an oracle to select among the three in subsection 5.

4.2 Results and discussion

Results at the morpheme level (Table 1) place our system comfortably ahead of the SIGMORPHON baseline, but behind the challenge winner (Girrbach, 2023), for every language except Gitksan, where our performance matches the baseline. Results at the word level (Table 2) are similar, except that our system does not exceed the baseline for Arapaho but is superior to the challenge winner in Gitksan. This pattern of results is qualitatively similar to Ginn et al. (2024).

A direct comparison to Ginn et al. is possible only for the four languages they evaluated; in these, our system is slightly worse for Gitksan, Natugu and Nyangbo, but slightly better for Lezgi. This is perhaps a consequence of our tuning primarily on Tsez data, as Lezgi and Tsez are both Northeast Caucasian languages. It is clear from this comparison that word-based prompting can perform comparably to whole-sentence-based prompting, but with differences from language to language. The data and computation requirements of the two systems are likewise difficult to compare. Ginn et al. uses 100 sentences per instance, while we use 6 retrieved examples per word—this means that we retrieve fewer instances for sentences of 16 words or less. We also retrieve statistical tag frequency information from across the training corpus, so that our prompts can summarize information gathered from a larger corpus than theirs. Overall, we believe word-based prompting can be more efficient

	SMB	SMW	Retr.	Ours
arp*	71.14	78.79	71.59	66.19
git	16.93	21.09	20.05	25.52
lez	49.66	78.78	25.80	76.19
ntu	42.01	81.04	42.47	73.33
nyb	5.96	85.34	77.77	78.52
ddo	73.41	80.96	69.39	75.28
usp	57.26	73.39	69.11	65.32

Table 2: Word-level test set scores: SMB: Shared task official baseline; SMW: Track 1 challenge winner (either Tübingen-1 or 2); Retr: Our retrieval baseline; Ours: our system.

in minimizing the size of LLM prompts provided that sentences are short, but do not wish to claim that we require less training data to be available.

Our system beats retrieval alone in every case, often by a substantial margin. This indicates that the LLM does contribute to performance—the system does not simply pick the most common tag for every word. Instead, the LLM functions to disambiguate lexical items using the translation, select tags which accord with the inferred morphological context and use the provided examples to infer fuzzy matches for unknown words. For example, in the following Tsez phrase, retrieval finds a valid but unsuitable meaning for the word *mec*, but the LLM repairs this by conditioning on the translation:

- (1) maħor mec boħik’no
outside *tongue* III-push.out-PST.UNW
‘she poked her tongue out’
retrieval: outside *language* III-push.out-PFV.CVB
LLM: outside *tongue* III-push.out-PFV.CVB

The language with the narrowest gap between pure retrieval and the LLM is Uspanteko, perhaps because in this glossing task, the metalanguage is Spanish rather than English. Although the examples and instructions indicate that the system should gloss in Spanish, it does not always do so; the output contains some English glosses like “woman” (31 times), “grandmother”, “together” and “start”.

5 Three-best oracle

We believe that glossing a real dataset inevitably requires human intervention to ensure high-quality results. Therefore, it is important to measure not only the system’s 1-best performance but also its ability to provide good options for a human annotator to select among, since providing suggested annotations can speed the process (Palmer et al.,

	SMB	SMW	Ours	Orac.
arp*	71.14	78.79	66.19	71.02
git	16.93	21.09	25.52	28.13
lez	49.66	78.78	76.19	82.70
ntu	42.01	81.04	73.33	76.12
nyb	5.96	85.34	78.52	88.93
ddo	73.41	80.96	75.28	84.37
usp	57.26	73.39	65.32	76.34

Table 3: Word-level test oracle scores: SMB: Shared task official baseline; SMW: Track 1 challenge winner (either Tübingen-1 or 2); Ours: our system; Orac: 3-best oracle

2009; Anastasopoulos et al., 2018). We elicit three proposed glosses per word; in normal decoding, we use only the first of these. However, we also evaluate an ‘oracle’ system in which we pick the best gloss (evaluated by maximizing the Jaccard coefficient between the elements of the proposed and true tag) to measure how often a human annotator could accept one of the top three suggestions. Table 3 in the shows word-level scores. The oracle exceeds the challenge winner scores in every language but Arapaho and Natugu. This indicates that the three-best oracle is useful for disambiguating some words even in the most morphologically complex languages.

Table 5 in the Appendix shows morpheme-level results. Improvements over the 1-best system are not as large as in the word-based scores, and are smallest in the most morphologically complex languages, Arapaho, Gitksan and Natugu, for which our system has little evidence about how to accurately tag complex words, since it does not carry out morphological analyses. We obtain larger improvements in the remaining languages, indicating that for these, the retrieved evidence can narrow down the space of tags to a few options. (We examine one such case, Tsez verbal syncretism, in the next section; in this case, the system is usually capable of identifying two possibilities but distinguishes between them poorly.)

6 Disambiguation of syncretic forms

Because of the cost of running the LLM system (see Limitations), our development effort focused on improving performance in Tsez. Tsez exhibits multiple cases of morphological syncretism (Baerman, 2004) in which two distinct morphological functions are expressed by a single surface form. The highest error counts in the confusion matrix

for Tsez tags correspond to these syncretic forms, primarily confusion between PST.UNW, the past unwitnessed, and PFV.CVB, the perfective converb.

Polinsky (2014, p.298) confirms that these two forms are homophonous and both common in past tense narrative. She notes several differences between the distributions of the forms: the finite verb occurs in interrogatives and main clauses. The converb occurs with topic and focus markers, with adverbial clauses (of any tense) in past tense main clauses, and with ‘‘clause chains’’ (p.297) which ‘‘include a string of converbal clauses but may have only one finite clause.’’ This example from the dataset shows an adverbial clause with a converb and sequential clauses, the last of which has a finite verb; each verb has the same morphological marker *-n(o)*.

- (2) Xizyo hečk’erno **yizin**,
 after upright-TOP II-get.up-PFV.CVB
yegirno mown **xecin**,
 II-let-PFV.CVB tear-and leave-PFV.CVB
 Musaq łox uban
 Musa-POSS.ESS thrice kiss-and
bodin **esirno**:
 III-do-PFV.CVB ask-PST.UNW
 ‘After she got up again, she shed a tear, gave
 Musa 3 kisses and asked him:’

6.1 Prompting

In an effort to reduce the errors caused by syncretic forms, we use the LLM to generate instructions for disambiguating these difficult tag pairs. We generate instructions for each pair of tags with more than 5 confusions in the baseline development set in Tsez and Lezgi. Error distributions in the other languages have few or no highly-confused tag pairs, suggesting that their common errors are not due to syncretism. Rather, these errors can be attributed to the lack of morphological analysis and to unknown words.

For each highly confused tag pair, we generate a dataset of up to 32 contrastive instances from the training set (see Appendix D). Each instance is a pair of sentences in which the same lexical item appears with the two different tags (for example, the same verb appears as a finite verb and a converb). We ask GPT4 to give instructions for disambiguating the two forms based on the data.

Once the instructions are pre-generated, for each token in the test set for which the list of highly frequent training tags contains a confusable tag, we inject the generated instructions into the prompt.

Conf.	Retr.	Ours	+Instr.
PFV.CVB / PST.UNW	107	102	74
II-PFV.CVB / II-PST.UNW	21	24	14
III-PFV.CVB / III-PST.UNW	22	24	25
I.PL-PFV.CVB / III-PFV.CVB	20	21	17
IV-PFV.CVB / IV-PST.UNW	18	13	12
CVB / any	405	391	346

Table 4: Counts of top 5 test set error categories (lower is better) from Tsez (ddo): our retrieval baseline, our system, our system + LLM-written instructions. Last line shows all confusions involving CVB tag.

If a token’s frequent tags suggest it is vulnerable to multiple confusions, we add instructions for the most frequent confusion of its most frequent tag.

6.2 Results and discussion

Our generated instructions reduce the number of confusions across a variety of highly confused tag pairs in Tsez (Table 4), though not every pair. (Note that the various converbal tag confusions— distinguished by noun class— have independently generated instructions.) Overall, errors involving the CVB tag are reduced by 11%; word level gloss accuracy increases from 75.28 to 75.86.

A similar phenomenon appears in Lezgi, with syncretic AOR (aorist) and AOC (aorist converb) forms (Haspelmath, 1963, p.157), but at much lower frequency (only 6 instances). Our generated instructions did not improve this result.

The generated instructions correctly explain several aspects of the contrastive distribution of PST.UNW and PFV.CVB (see the Appendix for the full output). However, the instructions do not explain some potentially useful information which requires careful attention to the Tsez sentence rather than the translation, such as the CVB occurring with topic/focus markers:

****Tag a verb as PFV.CVB if it appears in a subordinate clause that provides background information or context for the main action, often preceding the main verb.**** ... ****Tag a verb as PST.UNW if it is the main verb of the sentence, indicating the primary action or event that is being reported.**** ...

An example of an instance which our original system got wrong, but the generated instructions corrected, is shown below (true tags shown; tags

for which the baseline gives the wrong output italicized):

- (3) Xizyogon ħurženya eħuk’no
then bag-IN.ESS leather.sack-*TOP*
eqerno, hečk’er izin.
put-PFV.CVB upright get.up-*PST.UNW*
‘Then he put the leather sack into the bag and got up.’

The chain-of-thought output shows that GPT-4’s inference here is based on a correct application of the guidelines:

“2. ****PST.UNW as the main verb****: The sentence translation indicates that ‘izin’ is part of the main action (‘got up’) after putting the leather sack into the bag. This suggests that ‘izin’ could be the main verb of the sentence, which aligns with the PST.UNW tag.”

In this sentence, on the other hand, the instructions caused an error in a case where our original system was correct:

- (4) Husenä salamno teħno,
Hussein-ERG greeting-*TOP* give-*PFV.CVB*
iduƣor oqno.
home-IN.ALL become-*PST.UNW*
‘Hussein gave a greeting and went into the house.’

The instructions cause the system to reverse the converb and finite verb tags. The chain-of-thought output reveals a corresponding issue with the linguistic analysis:

“1. ****PFV.CVB in subordinate clauses****: The verb “oqno” (become-PFV.CVB) appears to be in a subordinate clause providing context for the main action. The main action seems to be “Hussein gave a greeting,” which suggests that “teħno” could be the main verb. This would lean towards a PST.UNW gloss for “teħno.”

Additional examples of guidelines and chain-of-thought outputs are shown in Appendix D.

These results are the first convincing demonstration we know of that GPT-4 is capable of applying linguistic metaknowledge to a language task, standing in contrast to its well-documented inability to benefit from this type of instruction in low-resource

translation. However, the problems noted in translation studies still occur in this setting. In particular, GPT-4 is too sensitive to the syntax of the meta-language rather than the object language— structures where the English syntax suggests one main verb while the Tsez syntax suggests another are a frequent source of errors. This compounds GPT-4’s bias towards generating instructions which overemphasize the translation to begin with. Overall, the system’s pretrained capacity to understand English is a double-edged sword, since it predisposes the system to attend to the translation at the expense of the Tsez sentence.

7 Conclusion

Our research demonstrates the potential of a retrieval-based LLM prompting system for glossing, exceeding the shared task baseline for morpheme-level scores in every language and the majority of languages for word-level scores. These scores are achieved without the integration of a trained sequence model; a hybrid approach (Yang et al., 2024a,b) would likely do better.

Moreover, our results show two promising possibilities for future investigation: First, our oracle system shows promising results by surpassing the word-level test scores of the Track 1 challenge winner in Gitksan, Lezgi, Nyangbo, Tsez, and Uspanteko. We believe more researchers in this area should report oracle scores, and that it is high time to revisit Palmer et al. (2009) in evaluating the degree to which machine suggestions might aid a real annotator in rapid glossing. Second, we show that machine-generated linguistic instructions can aid the disambiguation of syncretic forms in Tsez, demonstrating that current LLMs *can* apply abstract linguistic instructions to the annotation of concrete language data when carefully prompted. Multistep chains of thought involving annotation of language-specific key concepts like main verbs might be able to improve results by further focusing the LLM’s processing on relevant properties of the object language data. We also believe that the process of generating and then applying linguistic instructions could be applied to morphological disambiguation, extending the approach beyond cases of syncretism.

Although we do not find that word-by-word prompting improves on sentence-level prompting, we do believe that it has benefits for controllability and interpretability. Far fewer examples need to be

retrieved for a single word than with sentence-level prompting and the generated chains of thought allow us to examine the LLM’s reasoning in detail. Both of these properties are helpful for error analysis.

We continue to believe that LLM-based systems for glossing and translation could be more accessible to their users than conventional sequence learners, since they can respond to natural language corrections or advice rather than requiring data annotation to modify their behavior. Continued improvements in the ability of LLMs to interpret linguistic instructions will thus be a key step forward in making language technology more responsive to native speakers and language experts.

Limitations

Due to the high cost of running the LLM (along with the environmental impacts of its energy and water usage), we had to limit our experiments to a small subset of the possible research questions. The experiments reported here cost about \$300 in total. To avoid further compounding this cost, we report the results of single runs without significance testing for variation between runs of the same prompts, do not report rigorous ablation experiments on most elements of the prompt, and do not run the entire Arapaho test set. Moreover, we do not compare other LLMs, including Gemini (known to perform competitively on similar tasks) or open models such as Llama which would increase the scientific reproducibility of this work.

The dataset provides challenges as well. We focused our attention on improving results in Tsez, where errors are dominated by verbal syncretism. We believe our instruction generation technique is more generally applicable to other syncretisms, but the SIGMORPHON languages do not provide enough examples of these outside Tsez to investigate this question.

Neither of the authors is an expert on Caucasian languages. Our description of the appropriateness of GPT-4’s instructions and chains of thought is based on our reading of Polinsky (2014) and our experience with the glossing data itself.

References

Antonios Anastasopoulos, Marika Lekakou, Josep Quer, Eleni Zimianiti, Justin DeBenedetto, and David Chiang. 2018. [Part-of-speech tagging on an endangered language: a parallel Griko-Italian resource](#). In *Pro-*

- ceedings of the 27th International Conference on Computational Linguistics*, pages 2529–2539, Santa Fe, New Mexico, USA. Association for Computational Linguistics.
- Seth Aycock, David Stap, Di Wu, Christof Monz, and Khalil Sima'an. 2024. [Can llms really learn to translate a low-resource language from one grammar book?](#) *Preprint*, arXiv:2409.19151.
- Matthew Baerman. 2004. Typology and the formal modelling of syncretism. In *Yearbook of morphology 2004*, pages 41–72. Springer.
- Balthasar Bickel, Bernard Comrie, and Martin Haspelmath. 2015. [The Leipzig glossing rules: Conventions for interlinear morpheme-by-morpheme glosses](#).
- Steven Bird. 2011. [Bootstrapping the language archive: New prospects for natural language processing in preserving linguistic heritage](#). *Linguistic Issues in Language Technology*, 6.
- Lindell Bromham, Russell Dinnage, Hedvig Skirgård, Andrew Ritchie, Marcel Cardillo, Felicity Meakins, Simon Greenhill, and Xia Hua. 2022. Global predictors of language endangerment and the future of linguistic diversity. *Nature ecology & evolution*, 6(2):163–173.
- Nicholas Carlini, Chang Liu, Úlfar Erlingsson, Jernej Kos, and Dawn Song. 2019. The secret sharer: Evaluating and testing unintended memorization in neural networks. In *28th USENIX security symposium (USENIX security 19)*, pages 267–284.
- Sara Court and Micha Elsner. 2024. [Shortcomings of LLMs for low-resource translation: Retrieval and understanding are both the problem](#). In *Proceedings of the Ninth Conference on Machine Translation*, pages 1332–1354, Miami, Florida, USA. Association for Computational Linguistics.
- Micha Elsner and Jordan Needle. 2023. [Translating a low-resource language using GPT-3 and a human-readable dictionary](#). In *Proceedings of the 20th SIGMORPHON workshop on Computational Research in Phonetics, Phonology, and Morphology*, pages 1–13, Toronto, Canada. Association for Computational Linguistics.
- Michael Ginn. 2023. [Sigmorphon 2023 shared task of interlinear glossing: Baseline model](#). *Preprint*, arXiv:2303.14234.
- Michael Ginn, Mans Hulden, and Alexis Palmer. 2024. [Can we teach language models to gloss endangered languages?](#) In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 5861–5876, Miami, Florida, USA. Association for Computational Linguistics.
- Michael Ginn, Sarah Moeller, Alexis Palmer, Anna Stacey, Garrett Nicolai, Mans Hulden, and Miikka Silfverberg. 2023. [Findings of the SIGMORPHON 2023 shared task on interlinear glossing](#). In *Proceedings of the 20th SIGMORPHON workshop on Computational Research in Phonetics, Phonology, and Morphology*, pages 186–201, Toronto, Canada. Association for Computational Linguistics.
- Leander Girmbach. 2023. [Tü-CL at SIGMORPHON 2023: Straight-through gradient estimation for hard attention](#). In *Proceedings of the 20th SIGMORPHON workshop on Computational Research in Phonetics, Phonology, and Morphology*, pages 171–185, Toronto, Canada. Association for Computational Linguistics.
- Martin Haspelmath. 1963. *A Grammar of Lezgian*. Mouton de Gruyter.
- Albert Kornilov and Tatiana Shavrina. 2024. [From mteb to mtob: Retrieval-augmented classification for descriptive grammars](#). *Preprint*, arXiv:2411.15577.
- Paul J Meighan. 2021. Decolonizing the digital landscape: The role of technology in indigenous language revitalization. *AlterNative: An International Journal of Indigenous Peoples*, 17(3):397–405.
- Sarah Moeller and Mans Hulden. 2018. [Automatic glossing in a low-resource setting for language documentation](#). In *Proceedings of the Workshop on Computational Modeling of Polysynthetic Languages*, pages 84–93, Santa Fe, New Mexico, USA. Association for Computational Linguistics.
- Christopher Moseley. 2012. *The UNESCO atlas of the world's languages in danger: Context and process*. World Oral Literature Project.
- Alexis Palmer, Taesun Moon, and Jason Baldridge. 2009. [Evaluating automation strategies in language documentation](#). In *Proceedings of the NAACL HLT 2009 Workshop on Active Learning for Natural Language Processing*, pages 36–44, Boulder, Colorado. Association for Computational Linguistics.
- Maria Polinsky. 2014. *Tsez Syntax: A Description*.
- Maja Popović. 2015. [chrF: character n-gram F-score for automatic MT evaluation](#). In *Proceedings of the Tenth Workshop on Statistical Machine Translation*, pages 392–395, Lisbon, Portugal. Association for Computational Linguistics.
- Machel Reid, Nikolay Savinov, Denis Teplyashin, Dmitry Lepikhin, Timothy Lillicrap, Jean-Baptiste Alayrac, Radu Soricut, Angeliki Lazaridou, Orhan Firat, Julian Schrittwieser, et al. 2024. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. *arXiv preprint arXiv:2403.05530*.
- Changbing Yang, Garrett Nicolai, and Miikka Silfverberg. 2024a. [Embedded translations for low-resource automated glossing](#). *Preprint*, arXiv:2403.08189.
- Changbing Yang, Garrett Nicolai, and Miikka Silfverberg. 2024b. [Multiple sources are better than one: Incorporating external knowledge in low-resource](#)

[glossing](#). In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 4537–4552, Miami, Florida, USA. Association for Computational Linguistics.

Chen Zhang, Xiao Liu, Jiuheg Lin, and Yansong Feng. 2024. [Teaching large language models an unseen language on the fly](#). *Preprint*, arXiv:2402.19167.

Xingyuan Zhao, Satoru Ozaki, Antonios Anastasopoulos, Graham Neubig, and Lori Levin. 2020. [Automatic interlinear glossing for under-resourced languages leveraging translations](#). In *Proceedings of the 28th International Conference on Computational Linguistics*, pages 5397–5408, Barcelona, Spain (Online). International Committee on Computational Linguistics.

A Canary testing for data leakage

SIGMORPHON 2023 does not have an official canary value, but we believe that the sentences of the dataset can act as canaries, since there is relatively little data in these languages online. Based on [Carlini et al. \(2019\)](#), we use the following three prompt types (at temperature 0) to evaluate the system’s knowledge of the SIGMORPHON challenge test sentences:

Prompt: Complete this sentence from the Tsez test set of the SigMorphon 2023 glossing challenge, exactly as it appears in the test set. Do not say anything else; only complete the sentence in the Tsez language exactly as it appears in the dataset. Sentence:

Sida q’orolays mamalay zown yudes šudał’orno
Response: I’m sorry, but I can’t fulfill this request.

Complete this sentence from the Tsez test set of the SigMorphon 2023 glossing challenge.

Sentence: Sida q’orolays mamalay zown yudes šudał’orno

response: I’m sorry, but I can’t provide verbatim text from the Tsez test set of the SigMorphon 2023 glossing challenge. However, I can help with general information about the Tsez language or the SigMorphon challenge if you’re interested. Let me know how I can assist you!

Complete this sentence in Tsez.

Sentence: Sida q’orolays mamalay zown yudes šudał’orno

Response: I’m sorry, but I can’t provide the completion for that sentence in Tsez.

For each prompt type, the system refuses to complete any sentences from the dataset. We believe this is evidence that the system has not memorized the example sentences verbatim.

B Morpheme-level oracle scores

C Appendix: Full Prompt

Below is an entire example prompt for our system. The candidate gloss is assembled by taking

	SMB	SMW	Ours	Orac.
arp*	44.19	78.47	52.57	57.70
git	8.54	11.72	8.68	9.26
lez	41.62	62.1	52.62	60.90
ntu	18.17	56.38	33.19	34.84
nyb	14.21	86.74	78.26	85.01
ddo	51.23	73.95	57.59	63.15
usp	57.24	70.05	57.59	65.79

Table 5: Morpheme-level test oracle scores: SMB: Shared task official baseline; SMW: Track 1 challenge winner (either Tübingen-1 or 2); Ours: our system; Orac: 3-best oracle.

the most frequent tag (or "?") for each word other than the target word, shown in brackets. The most frequent tags are produced by exact match with the training data. Three exact and three approximate matches are shown; they are random samples from the training set. Approximate matches are selected to share at least a 4-character substring with the target word, and within that set, to share the longest such substring we can find. The reverse lookup shows words in the translation which appear within the lexical elements of gloss lines.

We are going to gloss an example in Tsez. Your task is to predict glosses for the word:

uq⁵no

In this sentence:

Sentence: Žeda ža siday ɬ⁵ebozaɬ x⁵iriɣor hut’-m⁵alin roxik’no [uq⁵no]

Candidate gloss: DEM1.IPL.OBL-ERG DEM1.SG in.one.place ? above-IN.ALL front.part.of.the.face-and IV-let.appear-PFV.CVB [?]

Translation: They hid him somewhere with only his face out of the leaves.

Use interlinear glossed text (IGT) and follow the Leipzig glossing conventions.

Glosses should use function tags, not English morphology, to indicate grammatical information: for instance, "monkey-PL" is preferable to "monkeys". Give the best three glosses for the word (in order, best to worst) in a JSON list format outlined below.

```
{
  "word": "uq5no",
  "glosses":
    " _____ ", " _____ ", " _____ "
}
```

The word uq⁵no often appears with the following tags (but it may also appear with similar tags that are not shown here):

hide-PST.UNW (60%), hide-PFV.CVB (40%)

It appears with the following features (but it may also appear with related features that are not shown here):

PST.UNW, PFV.CVB

Here are a few example sentences with the word uq^{f} no. Remember that the full distribution of tags (shown above) is not necessarily represented here.

Exact Matches Sentence: Dey xediw nexxołin, yiła yeda sida yeže ɣamasya tełxor uq^{f} no.

Gloss: me-GEN1 husband come-PRS-QUOT DEM2.IISG.OBL-ERG DEM2.ISG one.OBL II-big box-IN.ESS inside-AD.LAT hide-PST.UNW
Translation: "My husband is coming!", she [said and] hid him inside a large box.

Sentence: Dey xediw nexxołin yiła yeda nuci tełxosi bazargan nesi žade puräza ɣamasya teł uq^{f} no.

Gloss: me-GEN1 husband come-PRS-QUOT DEM2.IISG.OBL-ERG DEM2.ISG honey sell-PRS.PRT merchant DEM1.ISG.OBL boy-APUD.ESS side-IN.VERS.DIST box-IN.ESS inside hide-PST.UNW

Translation: "My husband is coming!", she [said and] hid that honey-selling merchant in the box next to the boy.

Sentence: Hemedurtow, dey xediw nexxołin, reł tełxosini bazarganno yizide sadaq ɣamasya teł uq^{f} no yiła.

Gloss: so-EMPH me-GEN1 husband come-PRS-QUOT meat sell-PRS.PRT-DEF merchant-TOP DEM2.IPL.OBL-APUD.ESS together box-IN.ESS inside hide-PST.UNW DEM2.IISG.OBL-ERG

Translation: Again she said "My husband is coming!", and also hid the meat-selling merchant inside the box together with them.

Approximate Matches: Sentence: Hemeła quł Okur čuq^fno, yisi užä nesiqay^f ilmu yiqärułi.

Gloss: DEM4.IISG.OBL day-CONT.ESS Oku-LAT notice-PST.UNW DEM2.ISG.OBL boy-ERG DEM1.ISG.OBL-POSS.ABL science II-take.away-PST.PRT-CND.CVB.IRR

Translation: That day, Oku noticed that the boy took away the science from him.

Sentence: Žar čuq^fno nesi bečedawni maduħales piša yedu yałrułi.

Gloss: son-LAT notice-PFV.CVB DEM1.ISG.OBL wealthy-DEF neighbor-GEN1 deed DEM2.IISG be-MSD

Translation: The son noticed, that it was a deed of that wealthy neighbor. Sentence: Yeyeni esiwde sadaq žan yuq^fno, gulun rečuł bicin, bežet'ani esnabi bayaniqor idu ezun ičäsi zown.

Gloss: II-young-DEF sister-APUD.ESS together DEM1.SG-TOP II-hide-PFV.CVB horse-TOP cattleshed-SUB.ESS III-tie-PFV.CVB I.PL-old-DISTR-DEF brother-PL I.PL-come-MSD-POSS.LAT home look-PFV.CVB wait-RES.PRT be.NPRS-PST.UNW

Translation: He hid her together with her younger sister, tied the horse to the shed, and waited at home for his older brothers to come.

Words for "of" include: meča (instead.of), met'rin (piece.of.meat-TOP), meč^wa (instead.of),

sabawłun (for.the.sake.of), bitor (because.of)

Words for "hid" include: yuq^fno (II-hide-PFV.CVB), uq^fno (hide-PST.UNW), uq^fełno (hide-PFV.CVB), buq^fno (III-hide-PST.UNW), ruq^fsi (IV-hide-PST.WIT)

Words for "out" include: bet'urno (III-pull.out-PFV.CVB), bižix (I.PL-take.out-IPFV.CVB), ret'urno (IV-pull.out-PFV.CVB), rołik'no (IV-pull.out-PFV.CVB), kurno (spread.out-PFV.CVB)

D Appendix: Prompt and Output for Instruction Generation

The prompt for eliciting instructions to disambiguate two tags is shown below. The examples of 'bad rules' and their improvements (in Latin and Welsh) are hardcoded by the authors of the paper and do not come from any language in the glossing challenge. The contrastive examples, however, are taken automatically from the training set. We use up to 32 per tag pair, but only one is shown below.

Here are some examples which highlight the differences between two tags, which are represented here as PFV.CVB and PST.UNW, in Tsez. We are writing guidelines for distinguishing these two similar tags.

0: Examples of ihun with both tags:

Sentence: Howži yisi Hasanes ečriħno lagis tatun bexun, halt'i boda biynč'us oq^wa ihun.

Gloss: now DEM2.ISG.OBL Hassan-GEN1 get.old-PFV.CVB body-GEN1 power-TOP III-die-PFV.CVB work III-do-INF III-know-NEG.PST.WIT-ATTR become-INF begin-PFV.CVB

Translation: Now Hassan's old body ran out of power, and he started getting unable to do the work.

Sentence: Oħoya řUmar iduɣorno ižin, siħrus řilmu moła ihun.

Gloss: Ohoyo-ERG Umar home-IN.ALL-TOP lead-PFV.CVB slyness-GEN1 science teach-INF begin-PST.UNW

Translation: Ohoyo lead Umar to his home and began to teach him the science of slyness.

...31 more examples follow ...

State some rules for distinguishing PFV.CVB from PST.UNW in Tsez. Be concise, but make sure your rules are specific and include examples where necessary. Do not appeal only to semantics when making the distinction. For example, here is a bad rule:

1: Tag a verb as an infinitive if it expresses something that someone knows or thinks. For example, "he knows that he is going".

This rule is bad because it does not indicate which verb (know or go) should be tagged as infinitive, it does not explain how the other verb should be tagged, and it does not sufficiently describe the

syntactic context in the tagged sentence in which it applies.

Here is an improved version of this rule:

1: Tag a subclause verb as an infinitive if the main verb is finite and the subclause verb subject is accusative. For example:

scit illum ire
know-3SG DEM-3SG-ACC go-INF
"he knows that he is going"

Here is another bad rule:

2: Tag a noun as a genitive if it appears in a possessive noun phrase. For instance, "the man's book".

This rule is bad because it does not indicate which noun (man or book) should be tagged as genitive, it does not explain how the other noun should be tagged, and it refers only to English word order, not to the order in the tagged sentence.

Here is an improved version of this rule which shows the word order in the object language as well as in English.

2: Tag a noun as a genitive if it appears to the right of the head noun in a noun phrase, indicating the possessor of the previous noun. For example:

llyfr y dyn
book.NOM the man.GEN
"the man's book"

Here is another bad rule:

3: Tag a verb as subjunctive if it reflects a desire or belief. For example, "he wants them to leave".

This rule is bad because it does not indicate which verb (want or go) should be tagged as subjunctive, it does not explain how the other verb should be tagged, and it does not refer to the syntax of the clause, only the meaning.

Here is an improved version of this rule which describes the syntax in the object language.

3: Tag a subclause a verb as subjunctive if it reflects a desire or belief in a subclause introduced with "ut" or a relative pronoun. Tag verbs in subclauses with no introductory particle as infinitives.

vult eos abesse
want-3SG 3PL be.absent-INF

vult ut abessent
want-3SG COMP be.absent-3PL.SBJV

State three to five rules, using this format.

One output from this prompt, as produced by ChatGPT, is given below.

Certainly! Here are some rules for distinguishing between the PFV.CVB and PST.UNW tags in Tsez:

1. **Tag a verb as PFV.CVB if it appears in a subordinate clause that provides background information or context for the main action, often preceding the main verb.** The PFV.CVB verb typically describes an action that is completed before the action of the main verb. For example:

- Sentence: *Babiya uži Okude sadaq egirno xecin.*

- Gloss: dad-ERG son Oku-APUD.ESS together send-PFV.CVB leave-PST.UNW
- Translation: "The father sent his son together with Oku."

In this sentence, "egirno" (send-PFV.CVB) provides context for the main action "xecin" (leave-PST.UNW).

2. **Tag a verb as PST.UNW if it is the main verb of the sentence, indicating the primary action or event that is being reported.** The PST.UNW verb typically follows the PFV.CVB verb if both are present in the sentence. For example:

- Sentence: *Žedu tel iduγor boqnosi, ceyä befiqus uži žeduz γ⁵utkoxor egirno.*

- Gloss: DEM1.IPL inside home-IN.ALL III-become-ANT.CVB eagle-ERG hunter-GEN1 son DEM1.IPL.OBL-GEN2 house-AD.LAT let-PST.UNW

- Translation: "When they had gone into their house, the eagle let the hunter's son down to their house."

In this sentence, "egirno" (let-PST.UNW) is the main action reported.

3. **Tag a verb as PFV.CVB if it appears in a sequence of actions where it indicates a completed action that leads to or results in the subsequent action.** The PFV.CVB verb often precedes another verb that is tagged as PST.UNW. For example:

- Sentence: *K^w axatow sida igozo ɣaɣay nesi žax let'in sis bercinaw kidno yown.*

- Gloss: soon-EMPH one.OBL near-ATTR.OBL village-IN.ABL DEM1.ISG.OBL boy-AD.ESS pick-PFV.CVB one beautiful girl-TOP II-marry-PST.UNW

- Translation: "Soon, that boy picked a beautiful girl from the neighboring village and married her."

In this sentence, "let'in" (pick-PFV.CVB) is a completed action that leads to "yown" (marry-PST.UNW).

4. **Tag a verb as PST.UNW if it is used to report a past event or action that has relevance to the narrative or discourse context.** The PST.UNW verb often concludes a sequence of actions or provides the main point of the sentence. For example:

- Sentence: *Xaner iyn anu yeda nesis uži yaɣruhi.*

- Gloss: khan-LAT know-PST.UNW be.NEG DEM2.ISG DEM1.ISG.OBL-GEN1 son be-MSD

- Translation: "The king didn't know that he was his own son."

In this sentence, "iyn" (know-PST.UNW) reports the main event of the narrative.

5. **Tag a verb as PFV.CVB if it is used in a conditional or hypothetical clause, providing a condition or premise for the main action.** The PFV.CVB verb often appears before a PST.UNW verb that describes the outcome or result. For example:

- Sentence: *Nedur resunäyɣin, eɣin uži dahawcen ičin, mažgityaγorno ik'ač'in, idun kecač'in.*

- Gloss: so IV-exist-CND.CVB-QUOT say-PST.UNW boy-ERG a.little-EQU1-TOP wait-PFV.CVB mosque-IN.VERS-and go-NEG.FUT.DEF home-and sleep-NEG.FUT.DEF

- Translation: "'If that's the case,' said the boy, 'I'll wait a little, and will neither go to the mosque, nor sleep here at home.'"

In this sentence, "eʁin" (say-PST.UNW) is the main action, while "dahawcen" (wait-PFV.CVB) provides a condition for the subsequent actions.

These criteria may be compared with the grammar as follows:

1. Subordinate clause verbs are converbs: Correct. "The majority of Tsez adverbial clauses have a converb as their predicate" (Polinsky, 2014, p.296).
2. Main verb is PST.UNW: Correct.
3. Converbs in sequence of actions indicating actions that lead to the main action: Correct. Polinsky describes these as "clause chains" (p.297).
4. PST.UNW used to report a past event relevant to the discourse: True but vague. Polinsky agrees that PST.UNW generally has past reference (p.298) but also states that it should be used for a 2nd/3rd person subject due to its evidential status. Tense cannot be used to identify the PST.UNW because the converb also often has past tense reference, although it is not required to do so.
5. Converbs in hypothetical: Mostly incorrect. Tsez uses specialized converbs for hypothetical constructions (p.314-315) rather than using the PFV.CVB. However, PFV.CVB can appear in hypotheticals due to "linking of converbs, where only one converb is marked as conditional but takes adjoined converbs under its scope, [the] preferred option of expressing that several events are viewed as hypothetical or counterfactual." (p.315) GPT's example does not seem to clearly fit this criterion, since although it states that "wait a little" is part of the hypothetical clause, it is actually part of the consequent ("If that's the case, [then] I'll wait...").

E Chain of thought outputs

We show here some additional examples of how GPT-4 applies the guidelines for distinguishing finite verbs and converbs. In the following case, our basic system mislabels 'come' as a converb but the instruction-augmented system correctly labels it as a finite verb.

- (5) Ayn yeda siday
 come-PST.UNW DEM2.ISG in.one.place
 b^ʃeliz ciq^ʃer.
 poplar-GEN2 forest-CONT.LAT
 'He came to a poplar forest.'

An excerpt from the chain of thought shows that the 'main verb' criterion is correctly applied:

2. ****PST.UNW as the main verb****: "Ayn" is likely the main verb of the sentence, as it describes the primary action of coming to a poplar forest. There is no other verb in the sentence that would serve as the main verb, which supports the use of PST.UNW.

In the following case, our basic system mislabels 'hear' as a finite verb, but the instruction-augmented system correctly labels it as a converb.

- (6) Žedus xabarno
 DEM1.IPL.OBL-GEN1 story-TOP
 teqno žedu^ʃ
 hear-PFV.CVB DEM1.IPL.OBL-CONT.ESS
 xizay itow c'odorawni esiwn
 behind as-EMPH clever-DEF brother-TOP
 ik'in.
 go-PST.UNW
 'Having heard their talking, the clever brother went behind them likewise.'

Below, an excerpt from the chain of thought correctly indicates that 'hear' is not the main verb and appears earlier in the string, both indicating the CVB tag.

Now, let's apply the guidelines:

1. ****PFV.CVB in subordinate clauses****: The word "teqno" appears before the main verb "ik'in" (go-PST.UNW). This suggests that "teqno" could be providing background information or context for the main action, which aligns with the use of PFV.CVB.
2. ****PST.UNW as the main verb****: The main action of the sentence is "ik'in" (go-PST.UNW), which indicates the primary event. "Teqno" is not the main verb here, which makes it less likely to be PST.UNW.
3. ****PFV.CVB in sequences of actions****: The sentence describes a sequence where the clever brother hears something and then goes behind them. "Teqno" could represent a completed action that leads to the subsequent action "ik'in" (go-PST.UNW), supporting the use of PFV.CVB.

In the following case, the instruction-augmented system makes a mistake due to misrecognition of the main verb and labels 'do' as a converb rather than a main verb.

- (7) Βολλο zaman bik'inosi
 III-middle time III-go-ANT.CVB
 bara xediw bet'erbaqi boda
 wife-ERG husband life III-do-INF
 ik'anix muk'ur oyn
 go-MSD-AD.ESS confess *do-PST.UNW*
 'After some time has passed, the wife confessed that she went to live with her husband.'

The chain of thought produced by ChatGPT labels 'persuade', which is not inflected, as the main verb, and *oyn* as a subordinate verb— in fact, it acts as the head (auxiliary) verb. The issue, as discussed in the main text, is that ChatGPT tends to prioritize the English translation over the Tsez sentence— the instructions state that "the PST.UNW verb typically follows the PFV.CVB verb if both are present", but also that the "main verb" should be tagged as PST.UNW. Here, the information about ordering (which would have given the right answer) is deemphasized in favor of the "main verb" criterion, which is incorrect due to the auxiliary. (The inferred tag sequence is shown in the excerpt. The retrieval system retrieves the primary meaning 'persuade' rather than 'confess' for *muk'ur*, but this is corrected in the final gloss.)

- Translation: 1. **Βολλο** - noun (III-middle)
 2. **zaman** - noun (time)
 3. **bik'inosi** - verb (I.PL-go-ANT.CVB)
 4. **bara** - noun (wife-ERG)
 5. **xediw** - noun (husband)
 6. **bet'erbaqi** - noun (life)
 7. **boda** - verb (III-do-INF)
 8. **ik'anix** - verb (go-MSD-AD.ESS)
 9. **muk'ur** - verb (persuade)
 10. **oyn** - verb (?)

1. **PFV.CVB in subordinate clauses**: The candidate gloss suggests that "bik'inosi" (I.PL-go-ANT.CVB) is a subordinate clause providing background information. The main action seems to be the wife's confession about going to live with her husband. "Oyn" could potentially be a PFV.CVB if it provides context or background to the main action.

...