Representation Learning on Out of Distribution in Tabular Data

Achmad Ginanjar¹² Xue Li¹ Priyanka Singh¹ Wen Hua³ Abstract this issue, such as noise inje

The open-world assumption in model development suggests that a model might lack sufficient information to adequately handle data that is entirely distinct or out of distribution (OOD). While deep learning methods have shown promising results in handling OOD data through generalization techniques, they often require specialized hardware that may not be accessible to all users. We present TCL, a lightweight yet effective solution that operates efficiently on standard CPU hardware. Our approach adapts contrastive learning principles specifically for tabular data structures, incorporating full matrix augmentation and simplified loss calculation. Through comprehensive experiments across 10 diverse datasets, we demonstrate that TCL outperforms existing models, including FT-Transformer and ResNet, particularly in classification tasks, while maintaining competitive performance in regression problems. TCL achieves these results with significantly reduced computational requirements, making it accessible to users with limited hardware capabilities. This study also provides practical guidance for detecting and evaluating OOD data through straightforward experiments and visualizations. Our findings show that TCL offers a promising balance between performance and efficiency in handling OOD prediction tasks, which is particularly beneficial for general machine learning practitioners working with computational constraints. The code for our experiment can be found online (attached for submision)

1. Introduction

The open-world assumption in machine learning presents a significant challenge: models often lack sufficient information to effectively handle data that differs substantially from their training distribution, known as out-ofdistribution (OOD) data. When encountering OOD data, models typically experience a marked decline in performance (Hsu et al., 2020; Hendrycks & Gimpel, 2016), compromising their reliability in real-world applications. While various generalization techniques exist to address this issue, such as noise injection through deep learning methods, these solutions often come with substantial computational requirements.

A particular challenge emerges in the context of modern machine learning: many advanced algorithms are optimized for specialized hardware like GPUs or TPUs (Hwang, 2018), creating a significant barrier for users with limited computational resources. This hardware dependency has led to what some researchers call the "democratization gap" in artificial intelligence (Ahmed & Wahed, 2020), where cutting-edge solutions become inaccessible to a broader user base relying on standard computing infrastructure.

While OOD detection has been extensively researched (Lee et al., 2020a), with notable contributions such as MCCD (Lee et al., 2020c), OpenMax (Bendale & Boult, 2016), Monte Carlo Dropout (Gal & Ghahramani, 2016), and ODIN (Liang et al., 2017), the specific challenge of prediction tasks for OOD data in tabular datasets remains relatively unexplored. Traditional tree-based models, despite their proven reliability with tabular data (Grinsztajn et al., 2022), show significant performance degradation when confronted with OOD samples, as demonstrated in our experiments.

Our research makes three key contributions to address these challenges:

- We provide a comprehensive, step-by-step framework for implementing existing methods to detect, separate, evaluate, and visualize OOD data using real-world datasets.
- 2. We conduct a thorough assessment of current tabular machine learning algorithms' capabilities in handling OOD data, establishing a benchmark for future research.
- We introduce Tabular Contrastive Learning (TCL), a novel approach that offers both efficiency and flexibility while achieving competitive performance, particularly designed for users with limited computational resources.

TCL, Figure 1, builds upon the principles of contrastive learning (Chen et al., 2020; Ucar et al., 2021) but is specifically optimized for tabular data structures. Our approach



Tabular Contrastive Learning

Figure 1: Tabular Contrastive Learning (TCL). The data [x] is duplicated $([x]_1, [x]_2)$ and noise is added. Both duplicates are then encoded and decoded to compute the loss. During inference, TCL only uses the encoder to produce new data [x]' that enhances supervised learning performance $f([x]') \to Y$. The decoder is omitted during inference and used only for training.

offers several advantages: computational efficiency compared to state-of-the-art models, flexibility in integration with various supervised learning algorithms, and robust performance across different types of prediction tasks.

Through extensive experimentation, we demonstrate that TCL delivers superior performance while maintaining efficiency, as measured by a higher speed/accuracy trade-off score (Huang et al., 2017) compared to existing models. This makes TCL particularly valuable for general machine learning practitioners who face computational constraints while requiring reliable performance on OOD data.

2. Related Work

The study of out-of-distribution (OOD) data handling spans multiple research directions, each contributing to our understanding of model behavior and robustness. This section reviews key developments in OOD detection, representation learning for tabular data, and contrastive learning approaches.

2.1. OOD detection

Recent years have seen significant advances in OOD detection methodologies. Traditional approaches like ODIN (Liang et al., 2017) and OpenMax (Bendale & Boult, 2016) established foundational techniques for identifying OOD samples. Monte Carlo Dropout (Gal & Ghahramani, 2016)introduced uncertainty estimation as a means of OOD detection, while MCCD (Lee et al., 2020a) advanced the field with density-based detection methods. However, these methods primarily focus on detection rather than prediction tasks, leaving a gap in handling OOD data post-detection.

Our work primarily utilizes OpenMax and Temperature Scaling. While the original algorithms are not new, both algorithms have received the latest updates and provide better support under PyTorch-ood (Kirchheim et al., 2022) compared to MCCD (Lee et al., 2020b).

2.2. Tabular data prediction

Neural Network-based Methods:

Multilayer Perceptron (MLP) (Ruck et al., 1990; Gorishniy et al., 2023): A simple deep learning method designed for tabular datasets.

Self-Normalizing Neural Networks (SNN) (Klambauer et al., 2017): Employs SELU activation to enhance the training of deeper neural networks.

Advanced Architectures:

Feature Tokenizer Transformer / FT-Transformer (Vaswani et al., 2017): Modifies the transformer model for tabular datasets, consistently achieving excellent performance.

Residual Network / ResNet (Li et al., 2018): Employs parallel hidden layers to effectively capture intricate feature interactions.

Deep Cross Network / DCN V2 (Wang et al., 2020): Integrates a feature-crossing component alongside linear layers and multiplications.

Automatic Feature Interaction / AutoInt(Song et al., 2018): Utilizes attention mechanisms applied to feature embeddings.

Neural Oblivious Decision Ensembles / NODE (Popov et al., 2019): Represents a differentiable ensemble of oblivious decision trees. Tabular Network / TabNet (Arık & Pfister, 2019): Implements a recurrent design with periodic adjustments to feature weights, emphasizing an attention framework.

Ensemble Methods:

GrowNet (Badirli et al., 2020): This method applies gradient boosting to less robust multi-layer perceptrons (MLPs), primarily for tasks involving classification and regression. **Gradient Boosting Decision Tree (GBDT)** (Grinsztajn et al., 2022) :

XGBoost: A tree-based ensemble technique that utilizes second-order gradients and regularization to avoid overfitting while enhancing computational efficiency.

LightGBM: A rapid and memory-efficient boosting framework that employs histogram-based algorithms and a leafwise tree growth approach for quicker training.

CatBoost: A gradient boosting implementation tailored for categorical features, featuring built-in ordered boosting to minimize prediction shifts.

These models have demonstrated varying degrees of success in predicting tabular data. However, their performance on out-of-distribution data remains a critical area for investigation. We include the mentioned models as our base model.

2.3. Tabular contrastive learning

SubTab (Ucar et al., 2021) and SCARF (Bahri et al., 2022) are a contrastive learning model designed specifically for tabular datasets. They operate under a concept similar to the core idea of contrastive learning for images as described in SimCLR (Chen et al., 2020). SubTab and SCARF compute contrastive loss using either cosine or Euclidean distance. Both methods are not designed for out-of-distribution problems. We include both methods in our comparison.

CFL (Ginanjar et al., 2024) is a federated learning algorithm designed to address vertical partitioning within data silos. CFL investigates the potential of applying contrastive learning to vertically separated data without requiring data exchange. CFL integrates weights by recognizing that the data is derived from a global imaginary dataset that is vertically partitioned. CFL employs contrastive learning as a strategy for black-box learning. CFL emphasizes cooperative learning across different silos. In this research, we examine learning from local data with OOD, an area that has not been previously investigated by CFL. While CFL operates within a federated learning framework, our focus is on standard tabular data. Despite having a similar name, CFL incorporates partial data augmentation as part of its federated learning approach and resembles image contrastive learning. Conversely, TCL utilizes complete matrix augmentation to accommodate tabular data.

3. Problem Statement

We consider the pair of $D_{train} = D_{in}$ and $D_{test} = D_{ood}$. A training dataset D_{train} is drawn from a source distribution P_{train} . A model must perform effectively not only on data from this training distribution but also on samples drawn from different test distributions P_{test} , where significant distributional shifts may occur. This requirement for robust performance must be balanced against strict computational constraints, represented by a budget B*B* that limits the computational resources available for both training and inference.

The core of our problem can be expressed as finding a function $f: x \to y$ that maximizes the efficiency score $S_{eff} = \frac{\max P_{ood}}{\min t} = \frac{1/\min E(x,y)_{D_{ood}}}{\min t}$, defined as the ratio of OOD performance to computational time. This optimization must be achieved while ensuring the model operates within our specified computational budget and maintains a minimum acceptable performance threshold α .

4. Proposed Method

4.1. Core Components

Data Augmentation

TCL employs a dual augmentation strategy where each input data point x generates two augmented versions, denoted as $\{x^1, x^2\} = \operatorname{Aug}(x)$. These augmentations undergo controlled noise injection to create slightly varied representations of the same data point. The augmented pairs serve as the foundation for the contrastive learning process.

Full Matrix Augmentation

Unlike traditional approaches like SimCLR or SubTab, which typically rely on data slicing, TCL adopts a more comprehensive strategy by utilizing the complete original data matrix for representation learning. This holistic approach allows for the preservation of all feature interactions, enabling a deeper understanding of how different features relate to one another. It also captures global data patterns, which can provide significant insights into the overall structure of the dataset. Furthermore, TCL maintains the structural relationships within the data, ensuring that the intrinsic connections among various data points are not lost in the learning process.

Encoder-Decoder Architecture

TCL utilizes a two-component architecture consisting of an encoder $(E : x; \omega^e \to x^e)$ and a decoder $(P : x^e; \omega^p \to x^p)$. The encoder is responsible for transforming input data into a compressed latent representation, with its parameters optimized for efficient feature extraction. On the other hand, the decoder reconstructs the original data from this latent space, although its parameters are not utilized dur-

ing inference; they are only employed during the training process.

4.2. Loss Function Design

TCL follows CFL that employs a composite loss function that combines three components $L_t(x) = (L_r(x) + L_c(x) + L_d(x))$

Loss Components:

Reconstruction Loss $L_r(x) = \frac{1}{N} \sum_n^N MSE(\hat{x}, x)$ Distance Loss $L_d(x) = \frac{1}{N} \sum_n^N MSE(x^{e1}, x^{e2})$ Simplified Contrastive Loss $L_c(x) = MSE([0], dot(x^{e1} \cdot x^{e2}))/\mathcal{T}$

TCL simplifies the contrastive loss calculation by using dot product similarity instead of traditional Euclidean distance, enhancing both computational efficiency and training speed. The optimization objective during training is:

$$\min L_t(.;\omega^e,\omega^p) = \min \frac{1}{J} \sum_{j=1}^J L_t(P(E(.;\omega^e);\omega^p))$$
(1)

5. TCL Algorithm

The TCL process consists of several steps. First, a minibatch of N samples is drawn from the dataset. For each sample in the batch, two augmented views are created, each with added noise. Although both views originate from the same data, they differ due to the augmentation processes applied. These augmented views are then passed through an encoder network to obtain their encoded representations. Subsequently, a decoder is applied to these encoded representations. The loss function calculates the difference between the two augmented views. By minimizing this loss, the noisy data is effectively consolidated. Since TCL employs a full matrix representation, the process brings together the noisy data row by row, resulting in generalized data that enhance the inference performance.

During the training phase, TCL processes data by utilizing both its encoder and decoder components. It computes all three components of loss, enabling the model to update its parameters effectively to minimize the total loss. In contrast, during the inference phase, TCL relies solely on the encoder component. A model replaces decoder during inference. The model can be any conventional, such as logistic, or deep learning, such as MLP.

6. Experiment

6.1. Datasets

We utilize 10 diverse tabular datasets: Adult (Becker & Kohavi, 1996), Helena (Guyon et al., 2019), Jannis (Guyon et al., 2019), Higgs Small (Baldi et al., 2014), Aloi (Geusebroek et al., 2005), Cover Type (Blackard & Dean, 2000), California Housing (Pace & Barry, 1997), Year (Bertin-Mahieux et al., 2011), Yahoo (Chapelle & Chang, 2011), and Microsoft(Qin & Liu, 2013).

6.2. OOD Detection

To identify and handle out-of-distribution data, we employed two detection methods: OpenMax (Bendale & Boult. 2016) and TemperatureScaling (Platt et al., 1999). These methods were systematically applied to each dataset to transform the data and establish appropriate thresholds for OOD detection. Through careful observation of the graphs generated by the OOD detection algorithms, we manually determined these thresholds by selecting specific points along the tail of the distribution. Using these established thresholds, we separated the data into two distinct sets: D_{in}^M and D_{ood}^N , where M and N represent the total number of samples in each set, with their sum constituting the complete dataset $(D_{in} + D_{ood} = D)$. By design, we anticipated and confirmed that the in-distribution set would be larger than the OOD set M > N. To validate our separation approach, we employed linear regression as a verification method. The effectiveness of this separation was then evaluated by comparing model performance across both sets, where we consistently observed the expected pattern of decreased performance on the OOD set compared to the in-distribution data $f : D_{in} > f : D_{ood}$, confirming the successful identification of out-of-distribution samples.

The process results two distinct datasets: D_{in} , D_{ood} . We use these sets by designating D_{in} them as our training dataset while D_{ood} serving as our test dataset. This separation allows us to evaluate our model's performance on out-of-distribution data in a controlled manner.

6.3. Prediction ON OOD Dataset

Thi study uses seven baseline models, including several deep learning approaches specifically designed for tabular data: FT-T, DCN2, GrowNet, ResNet, MLP, AutoInt, and TabR-MLP. We also incorporated two recent contrastive learning implementations for tabular data—SubTab (Ucar et al., 2021) and SCARF (Bahri et al., 2022)—which share similar methodological foundations with our proposed TCL approach. It is worth noting that we had to exclude FT-Transformer from certain dataset evaluations due to its computational intensity exceeding our hardware capabilities. In addition, we included GBDT models in our comparative analysis to provide a broader perspective.

While most models were trained using an NVIDIA H100 GPU, we deliberately conducted TCL training on CPU hardware only to demonstrate our method's effectiveness under hardware constraints, highlighting its practical applicability in resource-limited environments.

7. Results

7.1. OOD Detection

Our analysis of OOD detection, as detailed in Table 1, reveals distinct performance patterns across different experimental settings. In the standard setting outlined in Section a of Table 1, the training and test results indicate comparable performance levels, demonstrating the model's consistency under normal conditions. Conversely, in the OOD setting discussed in Section b, we observe a significant performance decrease of 20% in classification tasks, while regression tasks yield negative r^2 scores. These findings clearly illustrate the challenging nature of OOD prediction.

7.2. Models Performance

The comprehensive model comparison presented in Table 2 reveals several key findings. Notably, the TCL model consistently outperforms other models across various datasets, demonstrating particularly strong performance in classification tasks while also maintaining competitive results in regression problems.

In contrast, specific models exhibit notable weaknesses. For instance, GrowNet tends to underperform when evaluated on the Adult and Yahoo datasets. Similarly, DCN V2 shows limitations on the California Housing dataset. Overall, other models typically display comparable performance across the datasets examined.

When compared to the GBDT method, TCL demonstrates superior performance across most datasets, particularly in classification tasks, as shown in Table 3. Among the classification problems, the adult dataset stands out with a relatively higher score compared to other datasets. This indicates that the adult dataset requires less generalization during prediction, which explains why TCL performs slightly below CatBoost in this case. Notably, CatBoost dominates in four datasets, outperforming any other GBDT algorithm.

7.3. Training Efficiency

Table 4 presents the training durations for the top three deep learning models, each characterized by unique features and training processes. A total of seven models—FT-T, DCN 2, GrowNet, ResNet, MLP, AutoInt, and TabR-MLP—underwent extensive parameter tuning. The complete tuning process for the Yahoo and Microsoft datasets spanned five days. For FT-T and ResNet, a single training time was recorded after completing the tuning phase. In the case of TCL, which involves unsupervised training, the recorded time reflects the duration required for each model to stabilize its loss using a batch size of 256, typically achieved within approximately 15 epochs. Notably, TCL demonstrates a relatively short training time.

7.4. Efficiency Trade-offs

The speed/accuracy trade-off analysis from Table 5 reveals important distinctions between high-performance models and the advantages of TCL. Among the high-performance models, both the FT-Transformer and ResNet demonstrate excellent F1 and RMSE scores; however, they are notably resource-intensive. The FT-Transformer features a complex architecture that leads to exponential growth in computational demands, whereas ResNet operates with multiple parallel subnetworks that require heavy filtering.

In contrast, TCL offers several advantages with its simpler MLP-like architecture. It employs narrow layers in both the encoder and decoder, as well as a single hidden layer combined with a normalization layer. This design results in a superior speed-to-accuracy trade-off that stands out among competing models. The only drawback to TCL is that it requires double the training time due to the pair operations involved. Nonetheless, these results clearly demonstrate TCL's effectiveness as a lightweight yet powerful solution for out-of-distribution prediction tasks, making it particularly valuable in resource-constrained environments.

8. Conclusion

Our research highlights that the selection of models for managing out-of-distribution (OOD) tabular data hinges on two key factors: performance needs and resource availability. In terms of performance, TCL demonstrates superior results in classification tasks on OOD data while maintaining competitive efficiency metrics and operating effectively on CPU hardware. On the other hand, traditional models like ResNet and FT-Transformer exhibit strong overall performance but come with significant computational demands, including a reliance on GPU resources, which limits their accessibility. The distinction in hardware requirements is notable, as TCL's ability to function efficiently on CPUs makes it more accessible to a wider range of users compared to ResNet and FT-Transformer, which are constrained by their need for GPUs.

Several promising areas for future research have been identified. One key direction is the integration of continual learning, which holds a potential for performance enhancement through continuous adaptation and the exploration of dynamic learning approaches. Another area is optimization, where further refinement of the contrastive learning process and investigations into efficiency improvements could yield significant benefits. Expanding the application domains of TCL is also crucial, with opportunities to test its performance on more diverse, domain-specific tabular datasets and validate its effectiveness in various real-world scenarios. Additionally, interpretability research remains an important focus, emphasizing the development of meth-

Table 1: T	he OOD de	etection settings.	Performances are	results of model	trained with	linear regression ((r^2) and logistic
regression	(accuracy)	When OOD da	taset is separated	and used as test	dataset in $(^b)$	the performance	of the model is
decreased.	Where Det	for detector, O f	or openMax, T for	TemperatureScal	lling, and Nor	m for normalisation	on applied.

				ID Accu	racy ^a	OOD Ac	ccuracy ^b
Dataset	Det	Norms	Threshold	Train	Test	Train	Test
						ID	OOD
Adult	0	L2	0.1628	0.7825	0.783	0.7978	0.2674
Helena	0	L1	0.045	0.1945	0.1966	0.1464	0.0475
Jannis	Т	L1	-0.02	0.5619	0.5639	0.5772	0.4742
Higgs small	0	L1	0.042	0.6222	0.6168	0.6226	0.5684
Aloi	0	L1	0.016	0.2606	0.2325	0.3282	0.0711
Covtype	Т	L1	-0.035	0.6046	0.6043	0.6035	0.4354
California	0	L1	0.11	0.3334	0.1806	0.4771	-6.0335
Year	0	L2	0.045	0.1686	0.167	0.1697	-0.7141
Yahoo	T	L1	1.46E-03	0.3256	0.3262	0.3255	-0.2978
Microsoft	Т	L1	-8.30E-03	0.0456	0.0441	0.0473	-0.8418

Table 2: Experiment result. F1 score for classification and RMSE for regression. Datasets with (*) mean a regression problem. Models with (^c) are contrastive learning based models.

	AD↑	HE↑	JA↑	HI↑	AL↑	CO↑	CA*↓	YE*↓	YA*↓	MI*↓
FT-T	0.782	0.153	0.572	0.738	0.407	-	0.867	6.461	-	-
DCN2	0.744	0.129	0.542	0.710	0.414	0.58	2.602	7.054	0.645	0.746
GrowNet	0.465	-	-	0.685	-	-	0.969	7.605	1.01	0.769
ResNet	0.652	0.10	0.574	0.753	0.437	0.694	0.892	6.496	0.639	0.736
MLP	0.508	0.146	0.561	0.753	0.326	0.617	0.894	6.488	0.657	0.741
AutoInt	0.78	0.133	0.549	0.719	0.401	0.608	0.89	6.673	-	0.739
TabR-MLP	0.688	0.165	0.541	0.753	0.429	0.688	2.677	2e5	1.285	0.79
TCL^{c}	0.831	0.154	0.575	0.758	0.447	0.880	0.843	6.491	0.652	0.738
$Scarf^{c}$	0.720	0.00	0.122	0.308	0.00	0.091	-	-	-	-
SubTab ^c	0.714	0.146	0.504	0.602	0.322	0.59	1.012	6.668	0.656	0.744

Table 3: Experiment result of TCL compared to GBDT. F1 score for classification and RMSE for regression. Datasets with (*) mean a regression problem. Model with (c) means contrastive learning based model, models with (x) mean GBDT based models.

-	AD↑	HE↑	JA↑	HI↑	AL↑	CO↑	CA*↓	YE*↓	YA*↓	MI*↓
TCL^{c}	0.831	0.154	0.575	0.758	0.447	0.880	0.843	6.491	0.652	0.738
Lightgbm ^x	0.591	0.080	0.432	0.609	0.177	0.219	0.848	6.565	0.661	0.740
CatBoost ^x	0.927	0.152	0.533	0.718	-	0.753	0.827	6.622	0.655	0.733
XGB^x	0.925	0.127	0.532	0.739	0.328	0.700	0.845	6.867	0.654	0.739

Table 4: Table of training duration in second of each dataset. Datasets with (*) means a regression problem. All model except for TCL are trained with GPU. TCL were trained with CPU

	AD↓	HE↓	JA↓	HI↓	AL↓	CO↓	CA*↓	YE*↓	YA*↓	MI*↓
FT-T	1027	130	155	94	1205	-	88	1290	-	-
ResNet	2.1e+02	32	21	56	44	618	15	236	284	950
TCL	15	23	23	38	40	330	7	240	620	820

Table 5: A speed/accuracy trade off matrix $S = \frac{P}{t}$ where P performance matrix used and t is time in	second required. A
higher result is better. Datasets with (*) mean a regression problem.	

	AD	HE	JA	HI	AL	CO	CA*	YE*	YA*	MI*
FT-T	0.00076	0.0012	0.0037	0.0079	0.00034	-	0.013	0.00012	-	-
ResNet	0.0031	0.0031	0.027	0.013	0.0099	0.0011	0.075	0.00065	0.0055	0.0014
TCL	0.055	0.0066	0.025	0.028	0.0199	0.0026	0.16	0.00064	0.0024	0.0016

ods to enhance model

References

- Ahmed, N. and Wahed, M. The de-democratization of ai: Deep learning and the compute divide in artificial intelligence research, 2020. URL https://arxiv.org/ abs/2010.15581.
- Arık, S. and Pfister, T. Tabnet: Attentive interpretable tabular learning. 35th AAAI Conference on Artificial Intelligence, AAAI 2021, 8A:6679–6687, 8 2019. ISSN 2159-5399. doi: 10.1609/aaai.v35i8.16826. URL https: //arxiv.org/abs/1908.07442v5.
- Badirli, S., Liu, X., Xing, Z., Bhowmik, A., Doan, K., and Keerthi, S. S. Gradient boosting neural networks: Grownet. 2 2020. URL https://arxiv.org/ abs/2002.07971v2.
- Bahri, D., Jiang, H., Tay, Y., and Metzler, D. SCARF: SELF-SUPERVISED CONTRASTIVE LEARNING USING RANDOM FEATURE CORRUPTION. In *ICLR* 2022 - 10th International Conference on Learning Representations, 2022.
- Baldi, P., Sadowski, P., and Whiteson, D. Searching for exotic particles in high-energy physics with deep learning. *Nature Communications*, 5:4308, 2014. doi: 10.1038/ncomms5308.
- Becker, B. and Kohavi, R. Adult. UCI Machine Learning Repository, 1996. DOI: https://doi.org/10.24432/C5XW20.
- Bendale, A. and Boult, T. E. Towards open set deep networks. Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition, 2016-December:1563–1572, 12 2016. ISSN 10636919. doi: 10.1109/CVPR.2016.173.
- Bertin-Mahieux, T., Ellis, D. P., Whitman, B., and Lamere, P. The million song dataset. In *Proceedings of the* 12th International Conference on Music Information Retrieval (ISMIR 2011), pp. 591–596, Miami, Florida, USA, October 2011. URL http://ismir2011. ismir.net/papers/0S6-1.pdf.

- Blackard, J. A. and Dean, D. J. Comparative accuracies of artificial neural networks and discriminant analysis in predicting forest cover types from cartographic variables. *Computers and Electronics in Agriculture*, 24(3): 131–151, 2000. doi: 10.1016/S0168-1699(99)00046-0.
- Chapelle, O. and Chang, Y. Yahoo! learning to rank challenge overview. In Proceedings of the Learning to Rank Challenge, volume 14 of Proceedings of Machine Learning Research, pp. 1–24. PMLR, 2011. URL http://proceedings.mlr.press/v14/ chapelle11a.html.
- Chen, T., Kornblith, S., Norouzi, M., and Hinton, G. A simple framework for contrastive learning of visual representations. pp. 1597–1607, 11 2020. ISSN 2640-3498. URL https://proceedings.mlr. press/v119/chen20j.html.
- Gal, Y. and Ghahramani, Z. Dropout as a bayesian approximation: Representing model uncertainty in deep learning, 6 2016. ISSN 1938-7228. URL https://proceedings.mlr.press/v48/gal16.html.
- Geusebroek, J.-M., Burghouts, G. J., and Smeulders, A. W. M. The amsterdam library of object images. *International Journal of Computer Vision*, 61(1):103–112, 2005. doi: 10.1023/B:VISI.0000042993.50813.60.
- Ginanjar, A., Li, X., and Hua, W. Contrastive federated learning with tabular data silos, 2024. URL https: //arxiv.org/abs/2409.06123.
- Gorishniy, Y., Rubachev, I., Kartashev, N., Shlenskii, D., Kotelnikov, A., and Babenko, A. Tabr: Tabular deep learning meets nearest neighbors in 2023, 2023. URL https://arxiv.org/abs/2307.14338.
- Grinsztajn, L., Oyallon, E., and Varoquaux, G. Why do tree-based models still outperform deep learning on typical tabular data? *Advances in Neural Information Processing Systems*, 35:507–520, dec 2022.
- Guyon, I., Sun-Hosoya, L., Boullé, M., Escalante, H. J., Escalera, S., Liu, Z., Jajetic, D., Ray, B., Saeed, M., Sebag, M., Statnikov, A., Tu, W.-W., and Viegas, E. Analysis of the automl challenge series 2015-2018. In *AutoML*, Challenges in Machine Learning. Springer, 2019.

- Hendrycks, D. and Gimpel, K. A baseline for detecting misclassified and out-of-distribution examples in neural networks. 5th International Conference on Learning Representations, ICLR 2017 - Conference Track Proceedings, 10 2016. URL https://arxiv.org/ abs/1610.02136v3.
- Hsu, Y.-C., Shen, Y., Jin, H., and Kira, Z. Generalized odin: Detecting out-of-distribution image without learning from out-of-distribution data, 2020.
- Huang, J., Rathod, V., Sun, C., Zhu, M., Korattikara, A., Fathi, A., Fischer, I., Wojna, Z., Song, Y., Guadarrama, S., and Murphy, K. Speed/accuracy trade-offs for modern convolutional object detectors, 2017.
- Hwang, T. Computational power and the social impact of artificial intelligence. *SSRN Electronic Journal*, 2018. doi: 10.2139/ssrn.3147971.
- Kirchheim, K., Filax, M., and Ortmeier, F. Pytorch-ood: A library for out-of-distribution detection based on pytorch. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops*, pp. 4351–4360, June 2022.
- Klambauer, G., Unterthiner, T., Mayr, A., and Hochreiter, S. Self-normalizing neural networks. 31st Conference on Neural Information Processing Systems, 2017.
- Lee, D., Yu, S., and Yu, H. Multi-Class Data Description for Out-of-distribution Detection. *Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 1362–1370, aug 2020a. doi: 10.1145/3394486.3403189. URL https://dl. acm.org/doi/10.1145/3394486.3403189.
- Lee, D., Yu, S., and Yu, H. Multi-class data description for out-of-distribution detection, 2020b. URL https: //github.com/donalee/DeepMCDD.
- Lee, D., Yu, S., and Yu, H. Multi-class data description for out-of-distribution detection. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, KDD '20, pp. 1362–1370, New York, NY, USA, 2020c. Association for Computing Machinery. ISBN 9781450379984. doi: 10.1145/3394486.3403189. URL https://doi.org/10.1145/3394486.3403189.
- Li, B., Wei, W., Ferreira, A., and Tan, S. Rest-net: Diverse activation modules and parallel subnets-based cnn for spatial image steganalysis. *IEEE Signal Processing Letters*, 25(5):650–654, 2018.
- Liang, S., Li, Y., and Srikant, R. Enhancing the reliability of out-of-distribution image detection in neural networks. 6th International Conference on Learning Representations, ICLR 2018 - Conference Track Proceedings,

6 2017. URL https://arxiv.org/abs/1706. 02690v5.

- Pace, R. K. and Barry, R. Sparse spatial autoregressions. *Statistics & Probability Letters*, 33(3):291–297, 1997.
- Platt, J. et al. Probabilistic outputs for support vector machines and comparisons to regularized likelihood methods. *Advances in large margin classifiers*, 10(3):61–74, 1999.
- Popov, S., Morozov, S., and Babenko, A. Neural oblivious decision ensembles for deep learning on tabular data. 8th International Conference on Learning Representations, ICLR 2020, 9 2019. URL https://arxiv.org/ abs/1909.06312v2.
- Qin, T. and Liu, T.-Y. Introducing LETOR 4.0 datasets. arXiv preprint arXiv:1306.2597, 2013. URL https: //arxiv.org/abs/1306.2597.
- Ruck, D. W., Rogers, S. K., and Kabrisky, M. Feature selection using a multilayer perceptron. *Journal of neural network computing*, 2(2):40–48, 1990.
- Song, W., Shi, C., Xiao, Z., Duan, Z., Xu, Y., Zhang, M., and Tang, J. Autoint: Automatic feature interaction learning via self-attentive neural networks. *International Conference on Information and Knowledge Management, Proceedings*, 10:1161–1170, 10 2018. doi: 10.1145/3357384.3357925. URL http://arxiv.org/abs/1810.11921http: //dx.doi.org/10.1145/3357384.3357925.
- Ucar, T., Hajiramezanali, E., and Edwards, L. Subtab: Subsetting features of tabular data for self-supervised representation learning. volume 23, 2021.
- Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., and Polosukhin, I. Attention is all you need. *Advances in neural information* processing systems, 30, 2017.
- Wang, R., Shivanna, R., Cheng, D. Z., Jain, S., Lin, D., Hong, L., and Chi, E. H. Dcn v2: Improved deep and cross network and practical lessons for web-scale learning to rank systems. *The Web Conference 2021 - Proceedings of the World Wide Web Conference, WWW 2021*, pp. 1785–1797, 8 2020. doi: 10.1145/3442381.3450078. URL http://arxiv.org/abs/2008.13535http: //dx.doi.org/10.1145/3442381.3450078.