

How Do LLMs Acquire New Knowledge? A Knowledge Circuits Perspective on Continual Pre-Training

Yixin Ou[♣], Yunzhi Yao[♣], Ningyu Zhang^{♣*}, Hui Jin[♡],
Jiacheng Sun[♡], Shumin Deng[♣], Zhenguo Li[♡], Huajun Chen^{♣♦*}

[♣]Zhejiang University [♡]Huawei Noah’s Ark Lab

[♣]National University of Singapore, NUS-NCS Joint Lab, Singapore

[♦]Zhejiang Key Laboratory of Big Data Intelligent Computing
{ouyixin, zhangningyu, huajunsir}@zju.edu.cn

Abstract

Despite exceptional capabilities in knowledge-intensive tasks, Large Language Models (LLMs) face a critical gap in understanding how they internalize new knowledge, particularly how to structurally embed acquired knowledge in their neural computations. We address this issue through the lens of knowledge circuit evolution, identifying computational subgraphs that facilitate knowledge storage and processing. Our systematic analysis of circuit evolution throughout continual pre-training reveals several key findings: (1) the acquisition of new knowledge is influenced by its relevance to pre-existing knowledge; (2) the evolution of knowledge circuits exhibits a distinct phase shift from formation to optimization; (3) the evolution of knowledge circuits follows a deep-to-shallow pattern. These insights not only advance our theoretical understanding of the mechanisms of new knowledge acquisition in LLMs, but also provide potential implications for improving continual pre-training strategies to enhance model performance¹.

1 Introduction

Knowledge is a cornerstone of intelligence, shaping how humanity perceives the world, interacts with others, and navigates daily life (Choi, 2022; Chen, 2023). Recent studies (Brown et al., 2020; OpenAI, 2023; Dubey et al., 2024; DeepSeek-AI et al., 2024; Yang et al., 2024; Zhao et al., 2023; Wu et al., 2024) on Large Language Models (LLMs) have demonstrated their ability to capture factual knowledge from pre-training corpus and encapsulate it as extensive parametric knowledge, empowering their remarkable capabilities in numerous knowledge-intensive tasks (Wang et al., 2024; Cao et al., 2024), as well as in developing higher-order capabilities like reasoning (Qiao et al., 2023; Huang and Chang,

* Corresponding Author.

¹Code and data will be available at <https://github.com/zjunlp/DynamicKnowledgeCircuits>.




Figure 1: Illustration of our findings: **Phase shift** from formation to optimization in the evolution of knowledge circuits, each phase characterized by distinct features at the performance, topology, and component levels.

2023). Nevertheless, these powerful models still struggle with knowledge updates, especially with regard to the dynamic nature of world knowledge that evolves after the cut-off date of the pre-training corpus (Zhang et al., 2023; Mousavi et al., 2024). Extensive efforts focus on developing advanced techniques for injecting new knowledge into LLMs (Jang et al., 2022; Jiang et al., 2024; Mecklenburg et al., 2024; Ovadia et al., 2024; Chen et al., 2024a), yet the absence of a well-defined mechanism for new knowledge acquisition in LLMs continues to hinder further progress in this area.

Recent works introduce mechanistic interpretability techniques to uncover knowledge mechanisms in LLMs. Allen-Zhu and Li (2024a) adopts probing methods to examine the storage and extraction of factual knowledge encoded in hidden states of language models. Kim et al. (2024) introduces the concept of knowledge entropy to examine how the integration of knowledge of LLMs evolves during the pre-training phase. However, previous works typically treat knowledge blocks as isolated components and often focus on identifying specific blocks that store particular knowledge. In

contrast, Yao et al. (2024) move beyond isolated components and explore the computation graph to uncover knowledge circuits, investigating cooperation between different components to understand how knowledge is stored and expressed.

In this paper, we investigate the mechanism of new knowledge acquisition in LLMs from the perspective of knowledge circuits. By analyzing the evolution of knowledge circuits throughout continual pre-training, we uncover several interesting findings, as illustrated in Figure 1.

Key findings of the paper are summarized as:

- (§4.1) The acquisition of new knowledge is significantly influenced by its relevance to pre-existing knowledge, with relevant new knowledge being integrated more efficiently than completely new knowledge.
- (§4.2) In the process of knowledge acquisition, the evolution of knowledge circuits exhibits a distinct phase shift from formation to optimization, each marked by unique structural and behavioral characteristics;
- (§4.3) The evolution of knowledge circuits follows a deep-to-shallow pattern, where mid-to-deeper layers first develop the extraction function, and later, lower layers enrich their knowledge representations.

These findings offer valuable insights into the mechanisms by which LLMs adapt their internal structures to acquire new knowledge. This understanding not only informs potential strategies for enhancing the continual learning capabilities of LLMs but also provides a solid foundation for improving their adaptability across diverse domains.

2 Background

2.1 Circuit Theory

Circuit as Computational Subgraph Delving into the Transformer architecture (Vaswani et al., 2017), all computations in a Transformers-based language model as a connected directed acyclic graph, denoted as \mathcal{G} . This graph represents the flow of information from the input of the language model to the token unembedding, where activations are projected back to vocabulary space. Various components of a language model, including attention heads and multi-layer perceptrons (MLPs), are defined as the nodes of this graph, denoted as N . The edges of this graph, denoted as E , are

the weighted connections between these components, encompassing residual connections, attention mechanisms, and projections. In the context of Mechanistic Interpretability (MI), which aims to understand the inner workings of advanced Transformer-based language models (Rai et al., 2024; Ferrando et al., 2024; Bereska and Gavves, 2024; Sharkey et al., 2025), a **circuit** is conceptualized as a sparse computational subgraph $\mathcal{C} \subset \mathcal{G}$ within a language model whose computations are most relevant to the whole model’s behaviour on the specific task (Olah et al., 2020; Elhage et al., 2021; Wang et al., 2023; Marks et al., 2024). A circuit \mathcal{C} usually contains a selection of nodes $N_{\mathcal{C}} \subset N$ and edges $E_{\mathcal{C}} \subset E$ necessary for the specific task, expressed as $\mathcal{C} = \langle N_{\mathcal{C}}, E_{\mathcal{C}} \rangle$.

Circuit Discovery The goal of circuit discovery is to identify a computational subgraph that represents the whole model’s behavior on a specific task. Many studies adopt causal mediation analysis to localize critical nodes or edges within language models in order to identify and verify circuits. Conmy et al. (2023) adopts activation patching and proposes ACDC. Syed et al. (2023) introduces Edge Attribution Patching (EAP) to make a linear approximation of activation patching, which assigns an importance score to each edge.

2.2 Knowledge Circuits

Unlike previous works (Dai et al., 2022; Geva et al., 2021, 2023; Meng et al., 2022) that treat the knowledge blocks as isolated components, Yao et al. (2024) introduce a novel perspective: knowledge circuits. They hypothesize that the cooperation between multiple components unveils implicit knowledge representation in LLMs. An identified knowledge circuit is considered a computational subgraph that faithfully represents specific knowledge domains within the model’s parametric memory. As such, it should be capable of independently reproducing the behavioral patterns or performance of the entire model with respect to the corresponding tasks. However, Yao et al. (2024) concentrates exclusively on the knowledge that already stored in the language model, without investigating the process by which LLMs acquire knowledge. In this work, we aim to advance the concept of knowledge circuits by investigating their dynamics throughout continual pre-training.

3 Methodology

3.1 Dataset Construction

Given the challenges of conducting mechanistic interpretability analysis on Internet-scale corpus, we perform controlled experiments on synthetic data, following Allen-Zhu and Li (2024a, 2023, 2024b). We focus on factual knowledge that can be represented as triples of the form (s, r, a) containing subject s , relation r , and attribute a . We synthesize a pool of fictional knowledge entities based on heuristic rules using ChatGPT, ensuring that these fictional biographical knowledge is unavailable to LLMs in the pre-training phase. Each knowledge entity is first assigned a unique name as the subject, and then associated with five relations—*birthdate*, *city*, *major*, *university* and *company*—and corresponding attributes. To convert these entities into textual knowledge for training data, we fill them in predefined templates. Considering real-world data scenarios and the perspectives of analysis, we further customize the training corpus from two aspects: *knowledge type* and *knowledge frequency*.

Knowledge Type We classify the new knowledge that the language model may need to acquire into two categories. One involves knowledge that already exists in the model’s parameters but requires further learning of specific aspects (e.g., new relations). This type of knowledge is referred to as *relevant new knowledge* and denoted as K_{rel} . The other type of knowledge is absent from the model’s parameters, which is referred to as *completely new knowledge* and denoted as K_{compl} .

Knowledge Frequency Considering the long-tail distribution of knowledge in real-world data, we model the frequency of knowledge entities in the corpus to follow an exponential distribution. This ensures that the corpus for continual pre-training contains both high-frequency knowledge as well as long-tail knowledge.

More details of the pipeline of dataset construction are provided in Appendix A.

3.2 Model Training

To conduct the knowledge acquisition experiment, we use three series of typical decoder-only LLMs to yield consistent findings on different architectures: *GPT-2*, *Llama*, and *Phi*. We continually pre-train the base models using a standard next-token prediction objective on the corpus described

in Section 3.1. Further details on the training configuration can be found in Appendix B.

3.3 Circuit Discovery

To facilitate the discovery of circuits over multiple checkpoints throughout continual pre-training, we select EAP-IG (Hanna et al., 2024) from a range of circuit discovery techniques (Conmy et al., 2023; Syed et al., 2023; Ferrando and Voita, 2024; Hanna et al., 2024), which assigns an importance score to each edge, balancing efficiency and faithfulness. Given an edge $e = (u, v) \in E$ between nodes $u \in N$ and $v \in N$ with clean and corrupted activations z_u and z'_u , EAP-IG scores the importance of e as:

$$S(e) = (z'_u - z_u) \frac{1}{m} \sum_{k=1}^m \frac{\partial L(z' + \frac{k}{m}(z - z'))}{\partial z_v} \quad (1)$$

where z refers to a sequence of token embeddings for one input, z' refers to the token embeddings of the distinct, baseline input, and m refers to the number of integrated gradient steps; we set $m = 5$ as suggested by Hanna et al. (2024). More details of circuit discovery are provided in Appendix C.

After scoring all edges within a language model using EAP-IG, we identify a circuit by selecting the top n edges with the highest absolute score as in Syed et al. (2023), ensuring that the selected edges collectively achieve over 70% of the whole model’s performance on the specific task. Specifically, we retain 8k, 20k, 50k, and 50k edges for GPT-2 Small, GPT-2 Medium, TinyLlama, and Phi-1.5, respectively.

4 Analyzing the Evolution of Knowledge Circuits throughout Training

Once we have identified the knowledge circuits, we delve deeper into the changes within the circuits, examining the transitions in the roles and behaviors of nodes and edges. Specifically, we conduct the analysis from three perspectives: *performance*, *topology*, and *components*.

4.1 Performance Analysis

An identified knowledge should be capable of independently reproducing the behavioral patterns or performance of the whole model with respect to the corresponding tasks. This property can be evaluated by examining whether the identified knowledge circuit aligns with the underlying algorithm implemented by the model. Following Yao et al. (2024), we employ the Hit@10 metric to measure




Figure 2: **Hit@10** of the performance of knowledge circuits in GPT-2 Small, GPT-2 Medium and Phi-1.5 throughout training. Left: Performance for circuits discovered by different types of knowledge, where K_{rel} and K_{compl} represent **relevant new knowledge** and **completely new knowledge**, respectively. Right: Performance for circuits discovered by different frequencies of knowledge, where **Low-freq**, **Medium-freq**, and **High-freq** represent knowledge with frequencies in the ranges $[1, 2)$, $[2, 5)$ and $(5, 27]$, respectively. Note that we smooth the curves using a window size of 3 epochs for all settings.

the rank of the target token among the top 10 predicted tokens throughout training process:

$$\text{Hit@10} = \frac{1}{|D_{\text{test}}|} \sum_{i=1}^{|D_{\text{test}}|} \mathbb{I}(\text{rank}_a \leq 10) \quad (2)$$

where $|D_{\text{test}}|$ denotes the test set size, a the target attribute, and rank_a the rank of the first token of target attribute a in vocabulary space. To evaluate completeness, we assess the identified circuit’s standalone performance on a held-out test set, which is filtered by the same knowledge type and frequency as the validation set for circuit discovery.

The results depicted in Figure 2 reveal a consistent growth pattern in the Hit@10 metric until it approach its upper bound, which demonstrates the sustained knowledge acquisition capability of knowledge circuits throughout continual pre-training. Notably, the K_{rel} performance curve consistently lies above the curve for K_{compl} , suggesting that LLMs exhibit preferential learning efficiency when assimilating knowledge extensions within existing conceptual frameworks, as opposed to acquiring completely new knowledge. These patterns persist in the whole model evaluation in Appendix D, suggesting that knowledge circuits capture general learning dynamics rather than isolated phenomena in LLMs.

Takeaway: Knowledge Relevance Principle

The acquisition of new knowledge is influenced by its relevance to pre-existing knowledge. LLMs exhibit learning efficiency advantages when acquiring relevant new knowledge versus completely new knowledge.

This insight could motivate **the utilization of data curriculums in continual pre-training**, by organizing the data in a way that mimics the structure and distribution of the original corpus, thereby enabling the model to integrate new information more efficiently (Yıldız et al., 2024; Parmar et al., 2024; Chen et al., 2024b).

Another notable observation in Figure 2 is that the performance of knowledge circuits is positively correlated with knowledge frequency. We further evaluate the performance of knowledge circuits by transferring them to a test set with different knowledge frequencies, as detailed in Appendix E. The results imply that the poor performance of knowledge circuits for low-frequency knowledge may stem from insufficient knowledge representations, rather than fundamental capacity limitations of circuits. This suggests that **strategies focused on reactivating long-tail knowledge**, such as knowledge augmentation, may improve knowledge retention in LLMs over time (Allen-Zhu and Li, 2024a).

4.2 Topology Analysis

In this section, we examine the dynamics of knowledge circuits through a topological lens, employing graph-theoretical metrics to analyze how the circuit subgraphs evolve throughout the training process.

4.2.1 Structural Consistency

We first quantify the structural consistency of knowledge circuits by measuring the Jaccard Similarity between edge sets (Figure 3) and node sets (Figure 11 in Appendix) within knowledge circuits at intermediate checkpoints relative to the final circuit. Both metrics exhibit a consistent monotonic upward trend throughout training, indicating that the knowledge circuits become increasingly similar to the final circuit. This convergence pattern suggests an evolutionary process where knowledge circuits progressively stabilize their core architecture as knowledge acquisition progresses. Based on the observed trends, we hypothesize that the process of knowledge acquisition is driven by topological centralization within knowledge circuits, with a small subset of critical edges and nodes gaining dominance in the flow of information.

4.2.2 Topological Centralization

To validate the hypothesis, we define a knowledge circuit entropy metric quantifying edge importance concentration, drawing on the concepts of uncertainty and information content from probability theory and information theory. The more centralized the topology of the knowledge circuit, the more the importance weights become concentrated on a few critical edges, resulting in a lower knowledge circuit entropy. To calculate the entropy of a knowledge circuit $\mathcal{C} = \langle N_{\mathcal{C}}, E_{\mathcal{C}} \rangle$, we first normalize the absolute value of the importance of each edge $e \in E_{\mathcal{C}}$, scored by EAP-IG in equation (1):

$$P(e) = \frac{S(e)}{\sum_{e' \in E_{\mathcal{C}}} S(e')}, \quad \forall e \in E_{\mathcal{C}} \quad (3)$$

The circuit entropy is then calculated as:

$$H(\mathcal{C}) = - \sum_{e \in E_{\mathcal{C}}} P(e) \log P(e) \quad (4)$$

Our results in Figure 3 show a stable downward trend in the knowledge circuit entropy metric for edges in the subgraph across all models, suggesting that the identified knowledge circuits become increasingly centralized, with the importance of critical edges growing as knowledge acquisition

progresses. We also observe that the downward trend of the knowledge circuit entropy slows down significantly after a certain turning point during the training of all models. For example, turning points are observed in GPT-2 Small, GPT-2 Medium, TinyLlama, and Phi-1.5 at epoch 7, epoch 4, epoch 1, and epoch 1, respectively. We attribute this interesting phenomenon to **a phase shift in the evolution of knowledge circuits** across continual pre-training. In the initial *formation phase* of knowledge circuits, less efficient knowledge circuits gradually take shape within the models, resulting in a rapid decrease in circuit entropy. At the phase shift points, the knowledge circuits reach a status of stability where the most critical nodes and edges have been involved. In the subsequent *optimization phase*, the topology composed critical nodes and edges becomes more stable, while the computations within these components are being optimized to represent and retrieve the knowledge more efficiently, leading to a slowdown in the rate of decrease in circuit entropy.

It's no coincidence that we also observe consistent phase shift points in the structural consistency of the nodes and edges in knowledge circuits throughout continual pre-training in Figure 3 and Figure 11, which signal a slowdown in the rate of structural convergence. This further confirms a reduction in the topological changes of the knowledge circuits, with subsequent performance improvements primarily attributed to the refinement and optimization of the efficiency of the existing structure.

Takeaway: Biphase Circuit Evolution

The evolution of knowledge circuits exhibits a distinct phase shift from formation to optimization, each marked by unique structural and behavioral characteristics.

This finding suggests that **the knowledge circuit state could serve as a valuable tracking status for the continual pre-training process**, enabling more informed adjustments to the training method or data in response to different phases. We leave this potential direction for future research.

4.2.3 Aligning Topology with Specific Knowledge Circuits

To clarify the influence of the topology of knowledge circuits on performance, we conduct a detailed examination of the knowledge circuits at several key training checkpoints. Specifically, we




Figure 3: Top: **Edges Jaccard Similarity** of intermediate knowledge circuits with the circuits at the final checkpoint. Bottom: **Knowledge Circuit Entropy** of knowledge circuits throughout training. K_{rel} and K_{compl} represent relevant new knowledge and completely new knowledge, respectively. Low-freq, Medium-freq, and High-freq represent knowledge with frequencies in the ranges $[1, 2)$, $[2, 5]$ and $(5, 27]$, respectively.




Figure 4: Hit@10 of the performance of aligned knowledge circuits in GPT-2 Small throughout training. *Init*, *Before*, *After*, *Last* represents the circuits whose topologies align with those at the initial checkpoint, the checkpoint before the phase shift, the checkpoint after the phase shift, and the final checkpoint, respectively. *Original* represents the original knowledge circuits at each checkpoint. Note that we smooth the curves using a window size of 3 epochs.

focus on the knowledge circuits at the initial checkpoint, the checkpoint immediately before the phase shift point, the checkpoint immediately after the phase shift point, and the last checkpoint. We align the topology of the knowledge circuits at each checkpoint throughout training with those of focus and then evaluate the performance for aligned circuits employing the Hit@10 metric as in §4.1. The results in Figure 4 reveal that the performance of all aligned circuits remain unchanged during the formation phase. However, each circuit begins to improve its performance during the optimization phase, with those aligned with the post-phase-shift topologies (*After* and *Last*) ultimately performing, on average, 54% better than those aligned with the pre-phase-shift topologies (*Init* and *Before*).




Figure 5: Proportion of **specialized attention heads** in all nodes of the knowledge circuits throughout training for GPT-2 Small and GPT-2 Medium. Note that we smooth the curves using a window size of 3 epochs.

This observation suggests the evolution of the topology of knowledge circuits at the phase shift point plays a crucial role in improving circuit performance. More examination of the relationship between this topological evolution and the evolution of components will be provided in §4.3.1.

4.3 Components Analysis

After analyzing the dynamics of the knowledge circuits at the overall topology level, we may further seek to understand how the components within these circuits evolve throughout training.

4.3.1 Evolutionary Pattern of Components

Specialized Nodes We first zoom into the specialized nodes within knowledge circuits to investigate the underlying factors driving the evolution of knowledge circuit. Recent studies have identified a set of specialized attention heads (Zheng et al., 2024; Ferrando et al., 2024) that directly contribute to factual recall in Transformer-based LLMs, in-




Figure 6: Top: Layer distribution of **mover head** in the knowledge circuits in GPT-2 Small throughout training. Bottom: Layer distribution of **relation head** in the knowledge circuits in GPT-2 Small throughout training.

cluding the mover head, relation head, and mixture head (Lv et al., 2024; Merullo et al., 2024; Chughtai et al., 2024). More detailed definitions and methodology for identifying these specialized attention heads are provided in Appendix G. We check the emergence and track the proportion of these specialized attention heads in all possible nodes of the knowledge circuits throughout training, and present our results in Figure 5. We observe that during the circuit formation phase, mover heads gradually emerge from nearly zero, while the proportion of relation heads decreases until the phase shift. In the circuit optimization phase, the proportion of all kinds of attention heads stabilizes. The proportion of mixture heads remains stable throughout training. We further examine the layer-wise distribution of mover heads and relation heads within knowledge circuits throughout training. Our results in Figure 6 (and Figure 13 in Appendix) reveal that the increase in mover heads and the decrease in relation heads primarily occur in the mid-to-deeper layers during the circuit formation phase.

Activated Edges Next, we investigate how the nodes within knowledge circuits propagate information to subsequent components through the edges. Specifically, we analyze the variation in edge activation patterns across different layers of the network throughout training. We quantify the edge activation ratio for each layer by calculating the proportion of edges originating from that layer




Figure 7: **Layer distribution of the edges activation ratio** within the knowledge circuits in GPT-2 Small.

within the knowledge circuit, relative to all possible edges originating from that layer in the whole model². Our results in Figure 7 (and Figure 12 in Appendix) reveal that, during the circuit formation phase, the edges activation ratios in the lower layers gradually decrease, while those in the mid-to-deeper layers exhibit a corresponding increase. However, as training progresses, a transition occurs around the phase shift point, where the edge activation ratios begin to stabilize.

Evolutionary Pattern The observed pattern in the evolution of specialized nodes and activated edges within knowledge circuits aligns with the factual recall mechanism in LLMs described by Geva et al. (2023). Specifically, the lower MLP layers specialize in encoding attribute-rich subject representations, while attention heads in the mid-to-deeper layers are responsible for extracting the relevant attributes for a given subject from these lower-level representations. Based on this, we can conclude the evolutionary pattern of knowledge circuits at the component level. During the early training phase of circuit formation, the focus is primarily on developing the extraction function within the nodes of the mid-to-deeper layers of the knowledge circuits. This is reflected in the increased emergence of mover heads and activated edges, along with a decrease in the presence of relation heads in these layers. This process continues until the extraction function is fully established at the phase shift point, as demonstrated by the similar performance advantage of circuits aligned with the post-phase-shift topologies over those aligned with the pre-phase-shift topologies in Figure 4. In the subsequent training phase of circuit optimization, the focus shifts to enriching knowledge representations in the lower layers, evidenced by a stabilized

²Note that we exclude the activation ratio for the last layer, as the small denominator causes the ratio to be an outlier, potentially blurring the overall trends in the activation patterns observed across layers.

topology and component structure, but with a rapid improvement in the performance of knowledge circuits in Figure 2 and Figure 4.

Takeaway: Deep-to-Shallow Pattern

The evolution of knowledge circuits follows a deep-to-shallow pattern, where mid-to-deeper layers first develop the extraction function, and later, lower layers enrich their knowledge representations.

4.3.2 Changes in Vocabulary Space

To gain a more nuanced understanding of the information flow, we track the layer-wise changes in both the rank and probability of the target attribute token at the last token position when unembedding the intermediate layer’s output into the vocabulary space throughout training. Additional results for other models are provided in Appendix F. The results in Figure 8 reveal that the occurrence of the early decoding phenomenon (nostalgebraist, 2020)—where the target token is already present in the residual stream by the mid-to-later layers—is closely associated with the phase shift in the evolution of knowledge circuits. During the circuit formation phase, the mid-to-deeper layers exhibit low ranks and probabilities for the target token, suggesting that the attention heads in these layers have not yet effectively extracted the target attribute in the residual stream due to the insufficient training. However, in the subsequent circuit optimization phase, the extraction function has already been developed in the mid-to-deeper layers, while the lower layers continue to enrich their knowledge representations for subjects, as evidenced by the occurrence of early decoding phenomenon.

5 Related Work

New Knowledge Acquisition Previous studies (Chang et al., 2024) explore new knowledge acquisition in LLMs with various behavioral interpretability techniques, which characterizes model behavior without revealing insights into the internal workings. Recent works introduce mechanistic interpretability techniques to advance related research even further. Allen-Zhu and Li (2024a) adopt probing methods to examine the storage and extraction of factual knowledge encoded in hidden states of language models. Building on studies that treat feed-forward layers as a key-value memory (Geva et al., 2021; Dai et al., 2022), Kim




Figure 8: Top: **Rank of the target attribute token** when unembedding the intermediate layer’s output into vocabulary space at the last token position throughout training for GPT-2 Small. Bottom: The corresponding **probability of the target attribute token**.

et al. (2024) introduce the concept of knowledge entropy to examine how LLMs’ knowledge integration evolves during the pre-training phase. In this paper, we seek to uncover the internal mechanism of new knowledge acquisition in LLMs by investigating the dynamics of knowledge circuits within LLMs throughout continual pre-training.

Mechanistic Interpretability With the rise of LLMs, Mechanistic Interpretability (MI) has gained prominence for reverse-engineering Transformer-based language models to decode their internal computations (Rai et al., 2024; Ferrando et al., 2024; Bereska and Gavves, 2024; Singh et al., 2024; Sharkey et al., 2025). Early MI research identifies features that consistently activate for specific input properties as elementary computational units. While such studies reveal phenomena such as polysemanticity and enable applications like knowledge editing (Yao et al., 2023; Zhang et al., 2024a; Hase et al., 2024) and steering (Turner et al., 2023), they offer limited insights into how features interact to drive model behaviors. This gap motivates circuit analysis (Elhage et al., 2021; Yao et al., 2024), which investigates computational pathways between Transformer components. Most similar to our work, Tigges et al. (2024) examines general circuits formation during pre-training, while our work focuses on the evolution of knowledge circuits throughout continual pre-training.

6 Conclusion

In this paper, we present a novel perspective on new knowledge acquisition of LLMs through an investigation into the evolution of knowledge circuits throughout continual pre-training. Through comprehensive analysis at performance, topology, and components levels, we reveal several key insights. We believe these insights will contribute to more efficient and effective continual pre-training of LLMs, while also uncovering the mechanisms behind new knowledge acquisition in LLMs.

Limitations

Model Architectures Our paper investigates the evolution of knowledge circuits solely in decoder-only Transformer LMs, due to their excellent performance and wide range of applications. We omit other Transformer variants, such as encoder-decoder and encoder-only models, from our analysis. Additionally, due to limitations in both computational resources and the circuit discovery method, we do not analyze models with larger parameter sizes than 1.3B, which typically employ Grouped Query Attention (Ainslie et al., 2023). However, Tigges et al. (2024) suggests that circuit analyses conducted on small models can provide insights that still apply over model scales.

Training Techniques We adopt the standard next-token prediction objective for continual pre-training of the base models in our experiments, as it is the most prevalent approach for enabling LLMs to acquire new knowledge. However, numerous studies (Jiang et al., 2024; Mecklenburg et al., 2024) focus on designing novel training techniques to enhance the efficiency and effectiveness of LLMs in acquiring new knowledge. We do not analyze the impact of these additional training techniques on the evolution of knowledge circuits.

References

Joshua Ainslie, James Lee-Thorp, Michiel de Jong, Yury Zemlyanskiy, Federico Lebrón, and Sumit Sanghai. 2023. [GQA: training generalized multi-query transformer models from multi-head checkpoints](#). In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, EMNLP 2023, Singapore, December 6-10, 2023*, pages 4895–4901. Association for Computational Linguistics.

Zeyuan Allen-Zhu and Yuanzhi Li. 2023. [Physics of language models: Part 3.2, knowledge manipulation](#). *CoRR*, abs/2309.14402.

Zeyuan Allen-Zhu and Yuanzhi Li. 2024a. [Physics of language models: Part 3.1, knowledge storage and extraction](#). In *Forty-first International Conference on Machine Learning, ICML 2024, Vienna, Austria, July 21-27, 2024*. OpenReview.net.

Zeyuan Allen-Zhu and Yuanzhi Li. 2024b. [Physics of language models: Part 3.3, knowledge capacity scaling laws](#). *CoRR*, abs/2404.05405.

Leonard Bereska and Efstratios Gavves. 2024. [Mechanistic interpretability for ai safety - a review](#). *Transactions on Machine Learning Research*.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. [Language models are few-shot learners](#). In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*.

Boxi Cao, Hongyu Lin, Xianpei Han, and Le Sun. 2024. [The life cycle of knowledge in big language models: A survey](#). *Mach. Intell. Res.*, 21(2):217–238.

Hoyeon Chang, Jinho Park, Seonghyeon Ye, Sohee Yang, Youngkyung Seo, Du-Seong Chang, and Min-joon Seo. 2024. [How do large language models acquire factual knowledge during pretraining?](#) *CoRR*, abs/2406.11813.

Howard Chen, Jiayi Geng, Adithya Bhaskar, Dan Friedman, and Danqi Chen. 2024a. [Continual memorization of factoids in large language models](#). *CoRR*, abs/2411.07175.

Huajun Chen. 2023. [Large knowledge model: Perspectives and challenges](#). *CoRR*, abs/2312.02706.

Jie Chen, Zhipeng Chen, Jiapeng Wang, Kun Zhou, Yutao Zhu, Jinhao Jiang, Yingqian Min, Wayne Xin Zhao, Zhicheng Dou, Jiaxin Mao, Yankai Lin, Ruihua Song, Jun Xu, Xu Chen, Rui Yan, Zhewei Wei, Di Hu, Wenbing Huang, and Ji-Rong Wen. 2024b. [Towards effective and efficient continual pre-training of large language models](#).

Yejin Choi. 2022. [Knowledge is power: Symbolic knowledge distillation, commonsense morality, & multimodal script knowledge](#). In *WSDM '22: The Fifteenth ACM International Conference on Web Search and Data Mining, Virtual Event / Tempe, AZ, USA, February 21 - 25, 2022*, page 3. ACM.

Bilal Chughtai, Alan Cooney, and Neel Nanda. 2024. [Summing up the facts: Additive mechanisms behind factual recall in llms](#). *CoRR*, abs/2402.07321.

- Arthur Conmy, Augustine N. Mavor-Parker, Aengus Lynch, Stefan Heimersheim, and Adrià Garriga-Alonso. 2023. [Towards automated circuit discovery for mechanistic interpretability](#). In *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*.
- Damai Dai, Li Dong, Yaru Hao, Zhifang Sui, Baobao Chang, and Furu Wei. 2022. [Knowledge neurons in pretrained transformers](#). In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2022, Dublin, Ireland, May 22-27, 2022*, pages 8493–8502. Association for Computational Linguistics.
- DeepSeek-AI, Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, Damai Dai, Daya Guo, Dejian Yang, Deli Chen, Dongjie Ji, Erhang Li, Fangyun Lin, Fucong Dai, Fuli Luo, Guangbo Hao, Guanting Chen, Guowei Li, H. Zhang, Han Bao, Hanwei Xu, Haocheng Wang, Haowei Zhang, Honghui Ding, Huajian Xin, Huazuo Gao, Hui Li, Hui Qu, J. L. Cai, Jian Liang, Jianzhong Guo, Jiaqi Ni, Jiashi Li, Jiawei Wang, Jin Chen, Jingchang Chen, Jingyang Yuan, Junjie Qiu, Junlong Li, Junxiao Song, Kai Dong, Kai Hu, Kaige Gao, Kang Guan, Kexin Huang, Kuai Yu, Lean Wang, Lecong Zhang, Lei Xu, Leyi Xia, Liang Zhao, Litong Wang, Liyue Zhang, Meng Li, Miaojun Wang, Mingchuan Zhang, Minghua Zhang, Minghui Tang, Mingming Li, Ning Tian, Panpan Huang, Peiyi Wang, Peng Zhang, Qiancheng Wang, Qihao Zhu, Qinyu Chen, Qiushi Du, R. J. Chen, R. L. Jin, Ruiqi Ge, Ruisong Zhang, Ruizhe Pan, Runji Wang, Runxin Xu, Ruoyu Zhang, Ruyi Chen, S. S. Li, Shanghao Lu, Shangyan Zhou, Shanhuang Chen, Shaoqing Wu, Shengfeng Ye, Shengfeng Ye, Shirong Ma, Shiyu Wang, Shuang Zhou, Shuiping Yu, Shunfeng Zhou, Shuting Pan, T. Wang, Tao Yun, Tian Pei, Tianyu Sun, W. L. Xiao, and Wangding Zeng. 2024. [Deepseek-v3 technical report](#). *CoRR*, abs/2412.19437.
- Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, Arun Rao, Aston Zhang, Aurélien Rodriguez, Austen Gregerson, Ava Spataru, Baptiste Rozière, Bethany Biron, Binh Tang, Bobbie Chern, Charlotte Caucheteux, Chaya Nayak, Chloe Bi, Chris Marra, Chris McConnell, Christian Keller, Christophe Touret, Chunyang Wu, Corinne Wong, Cristian Canton Ferrer, Cyrus Nikolaidis, Damien Allonsius, Daniel Song, Danielle Pintz, Danny Livshits, David Esiobu, Dhruv Choudhary, Dhruv Mahajan, Diego Garcia-Olano, Diego Perino, Dieuwke Hupkes, Egor Lakomkin, Ehab AlBadawy, Elina Lobanova, Emily Dinan, Eric Michael Smith, Filip Radenovic, Frank Zhang, Gabriel Synnaeve, Gabrielle Lee, Georgina Lewis Anderson, Graeme Nail, Grégoire Mialon, Guan Pang, Guillem Cucurell, Hailey Nguyen, Hannah Korevaar, Hu Xu, Hugo Touvron, Iliyan Zarov, Imanol Arrieta Ibarra, Isabel M. Kloumann, Ishan Misra, Ivan Evtimov, Jade Copet, Jaewon Lee, Jan Geffert, Jana Vranes, Jason Park, Jay Mahadeokar, Jeet Shah, Jelmer van der Linde, Jennifer Billock, Jenny Hong, Jenya Lee, Jeremy Fu, Jianfeng Chi, Jianyu Huang, Jiawen Liu, Jie Wang, Jiecao Yu, Joanna Bitton, Joe Spisak, Jongsoo Park, Joseph Rocca, Joshua Johnstun, Joshua Saxe, Junteng Jia, Kalyan Vasuden Alwala, Kartikeya Upasani, Kate Plawiak, Ke Li, Kenneth Heafield, Kevin Stone, and et al. 2024. [The llama 3 herd of models](#). *CoRR*, abs/2407.21783.
- Nelson Elhage, Neel Nanda, Catherine Olsson, Tom Henighan, Nicholas Joseph, Ben Mann, Amanda Askell, Yuntao Bai, Anna Chen, Tom Conerly, et al. 2021. [A mathematical framework for transformer circuits](#). *Transformer Circuits Thread*.
- Javier Ferrando, Gabriele Sarti, Arianna Bisazza, and Marta R. Costa-jussà. 2024. [A primer on the inner workings of transformer-based language models](#). *CoRR*, abs/2405.00208.
- Javier Ferrando and Elena Voita. 2024. [Information flow routes: Automatically interpreting language models at scale](#). In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing, EMNLP 2024, Miami, FL, USA, November 12-16, 2024*, pages 17432–17445. Association for Computational Linguistics.
- Mor Geva, Jasmijn Bastings, Katja Filippova, and Amir Globerson. 2023. [Dissecting recall of factual associations in auto-regressive language models](#). In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, EMNLP 2023, Singapore, December 6-10, 2023*, pages 12216–12235. Association for Computational Linguistics.
- Mor Geva, Roei Schuster, Jonathan Berant, and Omer Levy. 2021. [Transformer feed-forward layers are key-value memories](#). In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing, EMNLP 2021, Virtual Event / Punta Cana, Dominican Republic, 7-11 November, 2021*, pages 5484–5495. Association for Computational Linguistics.
- Michael Hanna, Sandro Pezzelle, and Yonatan Belinkov. 2024. [Have faith in faithfulness: Going beyond circuit overlap when finding model mechanisms](#). *CoRR*, abs/2403.17806.
- Peter Hase, Thomas Hofweber, Xiang Zhou, Elias Stengel-Eskin, and Mohit Bansal. 2024. [Fundamental problems with model editing: How should rational belief revision work in llms?](#) *CoRR*, abs/2406.19354.
- Jie Huang and Kevin Chen-Chuan Chang. 2023. [Towards reasoning in large language models: A survey](#). In *Findings of the Association for Computational Linguistics: ACL 2023, Toronto, Canada, July 9-14,*

- 2023, pages 1049–1065. Association for Computational Linguistics.
- Joel Jang, Seonghyeon Ye, Sohee Yang, Joongbo Shin, Janghoon Han, Gyeonghun Kim, Stanley Jungkyu Choi, and Minjoon Seo. 2022. [Towards continual knowledge learning of language models](#). In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net.
- Zhengbao Jiang, Zhiqing Sun, Weijia Shi, Pedro Rodríguez, Chunting Zhou, Graham Neubig, Xi Victoria Lin, Wen-tau Yih, and Srinu Iyer. 2024. [Instruction-tuned language models are better knowledge learners](#). In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2024, Bangkok, Thailand, August 11-16, 2024*, pages 5421–5434. Association for Computational Linguistics.
- Jiyeon Kim, Hyunji Lee, Hyowon Cho, Joel Jang, Hyeonbin Hwang, Seungpil Won, Youbin Ahn, Dohaeng Lee, and Minjoon Seo. 2024. [Knowledge entropy decay during language model pretraining hinders new knowledge acquisition](#). *CoRR*, abs/2410.01380.
- Yuanzhi Li, Sébastien Bubeck, Ronen Eldan, Allie Del Giorno, Suriya Gunasekar, and Yin Tat Lee. 2023. [Textbooks are all you need II: phi-1.5 technical report](#). *CoRR*, abs/2309.05463.
- Ang Lv, Kaiyi Zhang, Yuhan Chen, Yulong Wang, Lifeng Liu, Ji-Rong Wen, Jian Xie, and Rui Yan. 2024. [Interpreting key mechanisms of factual recall in transformer-based language models](#). *CoRR*, abs/2403.19521.
- Samuel Marks, Can Rager, Eric J. Michaud, Yonatan Belinkov, David Bau, and Aaron Mueller. 2024. [Sparse feature circuits: Discovering and editing interpretable causal graphs in language models](#). *CoRR*, abs/2403.19647.
- Nick Mecklenburg, Yiyu Lin, Xiaoxiao Li, Daniel Holstein, Leonardo O. Nunes, Sara Malvar, Bruno Silva, Ranveer Chandra, Vijay Aski, Pavan Kumar Reddy Yannam, Tolga Aktas, and Todd Hendry. 2024. [Injecting new knowledge into large language models via supervised fine-tuning](#). *CoRR*, abs/2404.00213.
- Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. 2022. [Locating and editing factual associations in GPT](#). In *Advances in Neural Information Processing Systems 35: Annual Conference on Neural Information Processing Systems 2022, NeurIPS 2022, New Orleans, LA, USA, November 28 - December 9, 2022*.
- Jack Merullo, Carsten Eickhoff, and Ellie Pavlick. 2024. [Circuit component reuse across tasks in transformer language models](#). In *The Twelfth International Conference on Learning Representations, ICLR 2024, Vienna, Austria, May 7-11, 2024*. OpenReview.net.
- Seyed Mahed Mousavi, Simone Alghisi, and Giuseppe Riccardi. 2024. [Is your LLM outdated? benchmarking llms & alignment algorithms for time-sensitive knowledge](#). *CoRR*, abs/2404.08700.
- Neel Nanda and Joseph Bloom. 2022. [Transformerlens](https://github.com/TransformerLensOrg/TransformerLens). <https://github.com/TransformerLensOrg/TransformerLens>.
- nostalgebraist. 2020. [interpreting gpt: the logit lens](#). *AI Alignment Forum*.
- Christopher Olah, Nick Cammarata, Ludwig Schubert, Gabriel Goh, Michael Petrov, and Shan Carter. 2020. [Zoom in: An introduction to circuits](#). *Distill*.
- OpenAI. 2023. [GPT-4 technical report](#). *CoRR*, abs/2303.08774.
- Oded Ovadia, Menachem Brief, Moshik Mishaeli, and Oren Elisha. 2024. [Fine-tuning or retrieval? comparing knowledge injection in llms](#). In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing, EMNLP 2024, Miami, FL, USA, November 12-16, 2024*, pages 237–250. Association for Computational Linguistics.
- Jupinder Parmar, Sanjev Satheesh, Mostofa Patwary, Mohammad Shoeybi, and Bryan Catanzaro. 2024. [Reuse, don't retrain: A recipe for continued pretraining of language models](#). *arXiv*, (arXiv:2407.07263). ArXiv:2407.07263 [cs].
- Shuofei Qiao, Yixin Ou, Ningyu Zhang, Xiang Chen, Yunzhi Yao, Shumin Deng, Chuanqi Tan, Fei Huang, and Huajun Chen. 2023. [Reasoning with language model prompting: A survey](#). In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), ACL 2023, Toronto, Canada, July 9-14, 2023*, pages 5368–5393. Association for Computational Linguistics.
- Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. 2019. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9.
- Daking Rai, Yilun Zhou, Shi Feng, Abulhair Saparov, and Ziyu Yao. 2024. [A practical review of mechanistic interpretability for transformer-based language models](#). *CoRR*, abs/2407.02646.
- Lee Sharkey, Bilal Chughtai, Joshua Batson, Jack Lindsey, Jeff Wu, Lucius Bushnaq, Nicholas Goldowsky-Dill, Stefan Heimersheim, Alejandro Ortega, Joseph Bloom, et al. 2025. Open problems in mechanistic interpretability. *arXiv preprint arXiv:2501.16496*.
- Chandan Singh, Jeevana Priya Inala, Michel Galley, Rich Caruana, and Jianfeng Gao. 2024. [Rethinking interpretability in the era of large language models](#). *arXiv preprint arXiv:2402.01761*.
- Aaquib Syed, Can Rager, and Arthur Conmy. 2023. [Attribution patching outperforms automated circuit discovery](#). *CoRR*, abs/2310.10348.

- Curt Tigges, Michael Hanna, Qinan Yu, and Stella Biderman. 2024. [LLM circuit analyses are consistent across training and scale](#). *CoRR*, abs/2407.10827.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, Aurélien Rodriguez, Armand Joulin, Edouard Grave, and Guillaume Lample. 2023a. [Llama: Open and efficient foundation language models](#). *CoRR*, abs/2302.13971.
- Hugo Touvron, Louis Martin, Kevin Stone, Peter Albert, Amjad Almahairi, Yasmine Babaei, Nikolay Bashlykov, Soumya Batra, Prajwal Bhargava, Shruti Bhosale, Dan Bikel, Lukas Blecher, Cristian Canton-Ferrer, Moya Chen, Guillem Cucurull, David Esiobu, Jude Fernandes, Jeremy Fu, Wenyin Fu, Brian Fuller, Cynthia Gao, Vedanuj Goswami, Naman Goyal, Anthony Hartshorn, Saghar Hosseini, Rui Hou, Hakan Inan, Marcin Kardas, Viktor Kerkez, Madian Khabsa, Isabel Kloumann, Artem Korenev, Punit Singh Koura, Marie-Anne Lachaux, Thibaut Lavril, Jenya Lee, Diana Liskovich, Yinghai Lu, Yuning Mao, Xavier Martinet, Todor Mihaylov, Pushkar Mishra, Igor Molybog, Yixin Nie, Andrew Poulton, Jeremy Reizenstein, Rashi Rungta, Kalyan Saladi, Alan Schelten, Ruan Silva, Eric Michael Smith, Ranjan Subramanian, Xiaoqing Ellen Tan, Binh Tang, Ross Taylor, Adina Williams, Jian Xiang Kuan, Puxin Xu, Zheng Yan, Iliyan Zarov, Yuchen Zhang, Angela Fan, Melanie Kambadur, Sharan Narang, Aurélien Rodriguez, Robert Stojnic, Sergey Edunov, and Thomas Scialom. 2023b. [Llama 2: Open foundation and fine-tuned chat models](#). *CoRR*, abs/2307.09288.
- Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David Udell, Juan J Vazquez, Ulisse Mini, and Monte MacDiarmid. 2023. [Activation addition: Steering language models without optimization](#). *arXiv e-prints*, pages arXiv–2308.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. 2017. [Attention is all you need](#). In *Advances in Neural Information Processing Systems 30: Annual Conference on Neural Information Processing Systems 2017, December 4-9, 2017, Long Beach, CA, USA*, pages 5998–6008.
- Kevin Ro Wang, Alexandre Variengien, Arthur Conmy, Buck Shlegeris, and Jacob Steinhardt. 2023. [Interpretability in the wild: a circuit for indirect object identification in GPT-2 small](#). In *The Eleventh International Conference on Learning Representations, ICLR 2023, Kigali, Rwanda, May 1-5, 2023*. OpenReview.net.
- Mengru Wang, Yunzhi Yao, Ziwen Xu, Shuofei Qiao, Shumin Deng, Peng Wang, Xiang Chen, Jia-Chen Gu, Yong Jiang, Pengjun Xie, Fei Huang, Huajun Chen, and Ningyu Zhang. 2024. [Knowledge mechanisms in large language models: A survey and perspective](#). In *Findings of the Association for Computational Linguistics: EMNLP 2024, Miami, Florida, USA, November 12-16, 2024*, pages 7097–7135. Association for Computational Linguistics.
- Xingyu Wu, Sheng-Hao Wu, Jibin Wu, Liang Feng, and Kay Chen Tan. 2024. [Evolutionary computation in the era of large language model: Survey and roadmap](#). *CoRR*, abs/2401.10034.
- An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiayi Yang, Jingren Zhou, Junyang Lin, Kai Dang, Keming Lu, Keqin Bao, Kexin Yang, Le Yu, Mei Li, Mingfeng Xue, Pei Zhang, Qin Zhu, Rui Men, Runji Lin, Tianhao Li, Tingyu Xia, Xingzhang Ren, Xuancheng Ren, Yang Fan, Yang Su, Yichang Zhang, Yu Wan, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, and Zihan Qiu. 2024. [Qwen2.5 technical report](#). *CoRR*, abs/2412.15115.
- Yunzhi Yao, Peng Wang, Bozhong Tian, Siyuan Cheng, Zhoubo Li, Shumin Deng, Huajun Chen, and Ningyu Zhang. 2023. [Editing large language models: Problems, methods, and opportunities](#). In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, EMNLP 2023, Singapore, December 6-10, 2023*, pages 10222–10240. Association for Computational Linguistics.
- Yunzhi Yao, Ningyu Zhang, Zekun Xi, Mengru Wang, Ziwen Xu, Shumin Deng, and Huajun Chen. 2024. [Knowledge circuits in pretrained transformers](#). *CoRR*, abs/2405.17969.
- Çağatay Yıldız, Nishaanth Kanna Ravichandran, Prishruit Punia, Matthias Bethge, and Beyza Ermis. 2024. [Investigating continual pretraining in large language models: Insights and implications](#).
- Ningyu Zhang, Yunzhi Yao, Bozhong Tian, Peng Wang, Shumin Deng, Mengru Wang, Zekun Xi, Shengyu Mao, Jintian Zhang, Yuansheng Ni, Siyuan Cheng, Ziwen Xu, Xin Xu, Jia-Chen Gu, Yong Jiang, Pengjun Xie, Fei Huang, Lei Liang, Zhiqiang Zhang, Xiaowei Zhu, Jun Zhou, and Huajun Chen. 2024a. [A comprehensive study of knowledge editing for large language models](#). *CoRR*, abs/2401.01286.
- Peiyuan Zhang, Guangtao Zeng, Tianduo Wang, and Wei Lu. 2024b. [Tinyllama: An open-source small language model](#). *CoRR*, abs/2401.02385.
- Zihan Zhang, Meng Fang, Ling Chen, Mohammad-Reza Namazi-Rad, and Jun Wang. 2023. [How do large language models capture the ever-changing world knowledge? A review of recent advances](#). In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing, EMNLP 2023, Singapore, December 6-10, 2023*, pages 8289–8311. Association for Computational Linguistics.
- Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang, Xiaolei Wang, Yupeng Hou, Yingqian Min, Beichen Zhang, Junjie Zhang, Zican Dong, Yifan Du, Chen Yang, Yushuo Chen, Zhipeng Chen, Jinhao

Jiang, Ruiyang Ren, Yifan Li, Xinyu Tang, Zikang Liu, Peiyu Liu, Jian-Yun Nie, and Ji-Rong Wen. 2023. *A survey of large language models*. *CoRR*, abs/2303.18223.

Zifan Zheng, Yezhaohui Wang, Yuxin Huang, Shichao Song, Mingchuan Yang, Bo Tang, Feiyu Xiong, and Zhiyu Li. 2024. *Attention heads of large language models: A survey*. *CoRR*, abs/2409.03752.

Appendix

A Dataset Construction

Given the challenges of conducting mechanistic interpretability analysis on Internet-scale corpus, we perform controlled experiments on synthetic data, following Allen-Zhu and Li (2024a, 2023, 2024b). We focus on factual knowledge that can be represented as triples of the form (s, r, a) containing subject s , relation r , and attribute a . For example, a piece of factual knowledge such as "Donald Trump is 78 years old" can be represented as $(Donald\ Trump, age, 78)$.

We synthesize a pool of fictional knowledge entities based on heuristic rules using ChatGPT, ensuring that these fictional biographical knowledge is unavailable to LLMs in the pre-training phase. Each knowledge entity is first assigned a unique name as the subject. Each name follows the format "*first_name middle_name last_name*", where the components are randomly and independently sampled from a uniform distribution. We use ChatGPT to generate possible values for first name, middle name, and last name, as listed in Table 3.

Additionally, there are five associated relations—*birth date*, *city*, *major*, *university* and *company*—which are randomly sampled from their corresponding pools of possible attributes for each relation. The *birthdate* relation offers 30 (1 to 30) \times 12 (January to December) \times 126 (1900 to 2025) possibilities. The corresponding pools of possible attributes for the other four relations are as generated by ChatGPT, as listed in Table 4~7.

To convert these entities into textual knowledge for training data, we populate predefined templates with the attribute values. For each attribute, one of 50 corresponding templates is randomly selected to enhance the diversity of the corpus. The sentences corresponding to each relation of the same subject are then randomly shuffled to form the biography segment of the subject. An example is provided below:

"Liora Shane Driscoll's birth is celebrated annually on 5 December, 1935. Liora Shane Driscoll is situated in Newport News, VA. Liora Shane Driscoll is an expert in the making in Agronomy. Liora Shane Driscoll is an alumni member of North Carolina State University. Liora Shane Driscoll is a worker at Google."

Knowledge Type We classify the new knowledge that the language model may need to ac-

quire into two categories. One involves knowledge that already exists in the model’s parameters but requires further learning of specific aspects (e.g., new relations). This type of knowledge is referred to as *relevant new knowledge* and denoted as K_{rel} . The other type of knowledge is completely new, absent from the model’s parameters, which is referred to as *completely new knowledge* and denoted as K_{compl} . To simulate real-world data scenarios, we set the knowledge type ratio as $|K_{\text{rel}}| : |K_{\text{compl}}| = 1 : 4$. Specifically, for complete new knowledge, we exclusively use synthetic fictional knowledge entities. For relevant new knowledge entities, we extract a set of celebrity names from Wikipedia, which are highly likely to appear in pre-training, and then sample fictional attributes for these entities.

Knowledge Frequency Considering the long-tail distribution of knowledge in real-world data, we model the frequency of knowledge entities in the corpus to follow an exponential distribution. This ensures that the corpus for continual pre-training contains both high-frequency knowledge as well as long-tail knowledge. We classify portions of the corpus based on frequency: Knowledge entities with a frequency greater than 5 in the corpus are classified as high-frequency knowledge, those with a single occurrence as low-frequency knowledge, and the remaining entities as medium-frequency knowledge.

We set the number of all individuals appearing in the training corpus to 50,000, with their frequency following an exponential distribution between 1 and 27. This finally result in 133,408 biography segments, with a total length of 10 million tokens and an average length of 76.8 tokens per biography segment.

B Training Configuration

GPT-2 We adopt the standard GPT-2 (Radford et al., 2019) implementation available on Huggingface, including GPT-2 Small and GPT-2 Medium.

Llama Given the huge experimental cost associated with the original Llama (Touvron et al., 2023a,b; Dubey et al., 2024), which typically have parameters exceeding 7 billion, we perform surrogate experiments using a relatively small model, TinyLlama (Zhang et al., 2024b). TinyLlama adopts exactly the same architecture and tokenizer as Llama 2, but with only 1.1 billion parameters,

facilitating more efficient experimentation.

Phi We adopt Phi-1.5 (Li et al., 2023) with 1.3 billion parameters.

For continual-pre training, we use a constant learning rate schedule without warmup. Our learning rate is set to match the learning rate of the base model at the end of its pre-training phase. We train using the AdamW optimizer with $\beta_1 = 0.9$, $\beta_2 = 0.95$, $\epsilon = 1e - 6$, and a weight decay of 0.1. We perform gradient accumulation for every 4 steps. We present several key statistics of the base models and more hyperparameters that are altered in our experiments in Table 1.

All of our continual pre-training experiments are runned on 2 NVIDIA-A100 GPUs.

C Circuit Discovery

Tasks Unlike previous works that investigate circuits on simple but general tasks such as Indirect Object Identification (IOI) and Greater-Than, our paper focuses on knowledge circuits that are capable of performing the task of factual recall. In a factual recall task, the objective is to predict a target attribute a given a subject-relation pair (s, r) . To ensure a sufficiently rich vocabulary space for the first token of the target attribute, we construct the factual recall tasks based on three relations mentioned in §3.1: *city*, *major*, and *company*. The templates for converting a subject-relation pair (s, r) into a query string for each factual recall task are listed in Table 2. A typical circuits task consists of minimal pairs of clean and corrupted inputs. For clean inputs, we randomly sample 300 examples from the training corpus for each knowledge type and frequency as the validation set D_{val} for circuit discovery. In our experiments, we observe that continually increasing the size of D_{val} only adds to the runtime for circuit discovery without improving the quality of the discovered circuits. The corresponding corrupted inputs are independently sampled from the training corpus to match the length of the subject tokens in each clean input.

Loss The metric for circuit tasks assesses how closely the language model outputs align with clean input, as opposed to corrupted input. In our circuit discovery experiments, we evaluate the performance of circuits using the logit difference: the logit of the correct attribute minus the logit of the corrupted attribute. We then convert the task metric M into a loss function by defining

Architecture	Model	Statistics			Hyperparameters			
		size	nodes	edges	block_size	batch_size	learning_rate	epochs
GPT-2	GPT-2 Small	124M	158	32,491	1,024	32	1e-3	25
	GPT-2 Medium	355M	410	231,877	1,024	16	1e-3	15
Llama	TinyLlama-v1.1	1.1B	728	742,996	2,048	4	4e-5	10
Phi	Phi-1.5	1.3B	794	886,597	2,048	2	2e-4	7

Table 1: Statistics and hyperparameters of models used in the continual pre-training experiments.

Relation	Template
<i>city</i>	<i>s lives in the city of</i>
<i>major</i>	<i>s majors in the field of</i>
<i>company</i>	<i>s works for the company of</i>

Table 2: Templates for the factual recall task on relations.

$L(x) = -M(x)$, as shown in Eq. 1.

We make modifications to the TransformerLens library (Nanda and Bloom, 2022) and EAP-IG library (Hanna et al., 2024) to implement the circuit discovery method and conduct all the analysis experiments.

D Whole Model Performance

We examine the whole model’s performance for knowledge acquisition by monitoring two type of accuracies during training process. First, we track the model’s next-token prediction accuracy on the first token of each attribute during training. This metric reflects how well the model acquires and memorizes the knowledge. The second metric is calculated on downstream query tasks in cloze-style for each attribute, such as "*s lives in the city of ___*", where the accuracy reflects the model’s ability to generate an exact match for the correct attribute. Our results in Figure 9 illustrate that both accuracy metrics increase until they reach their upper limits, reflecting the model’s ongoing acquisition of new knowledge during continual pre-training. Another interesting observation is that the accuracy curve for K_{rel} consistently lies above the curve for K_{compl} on both metrics, suggesting that relevant new knowledge is easier for LLMs to acquire than completely new knowledge.

E Transfer Performance of Knowledge Circuits between Frequency

To investigate the differences in the capacities of knowledge circuits identified using validation

data filtered by knowledge frequency, we analyze the transfer performance of these circuits on held-out test sets with varying transferred knowledge frequencies. For example, if a knowledge circuit is identified using validation data filtered by high-frequency knowledge, denoted as High-freq Circuit, its transfer performance is evaluated on test sets filtered by medium-frequency and low-frequency knowledge, respectively.

Our results in Figure 10 reveal that knowledge circuits identified using knowledge of different frequencies perform comparably when evaluated on test sets of the same frequency. Notably, knowledge circuits discovered using high-frequency knowledge exhibit relatively poor performance on the low-frequency test set, whereas circuits identified using low-frequency knowledge perform comparably to high-frequency circuits on the high-frequency test set. This finding suggests that there is no inherent difference in the capability of circuits for the same task; rather, their effectiveness is primarily determined by the representation of knowledge shaped by frequency.

F Changes in Vocabulary Space

We present our results for the layer-wise changes in the rank and probability of the target attribute token at the final token position when unembedding the intermediate layer’s output into the vocabulary space throughout the training of GPT-2 Small on the high-frequency set in §4.3.2. Additionally, we provide the full results of all knowledge frequencies for GPT-2 Small in Figure 15. We also provide the full results for GPT-2 Medium (Figure 16) and TinyLlama (Figure 17).




Figure 9: Accuracy curves across continual pre-training. K_rel and K_compl represent relevant new knowledge and completely new knowledge, respectively. First-token Acc stands for the model’s next-token prediction accuracy on the first token of each attribute, while Query Acc stands for the generation accuracy on downstream query tasks for each attribute.




Figure 10: Hit@10 of the transfer performance of knowledge circuits in GPT-2 Small and GPT-2 Medium throughout training. Low-freq Circuit, Medium-freq Circuit, and High-freq Circuit represent knowledge circuits identified by knowledge with the frequencies in the ranges $[1, 2)$, $[2, 5)$ and $(5, 27]$, respectively. Note that we smooth the curves using a window size of 3 epochs for all settings.




Figure 11: **Nodes Jaccard Similarity** of intermediate knowledge circuits with the circuits at the final checkpoint. K_rel and K_compl represent relevant new knowledge and completely new knowledge, respectively. Low-freq, Medium-freq, and High-freq represent knowledge with frequencies in the ranges $[1, 2)$, $[2, 5)$ and $(5, 27]$, respectively.




Figure 12: **Layer distribution of the edges activation ratio** within the knowledge circuits in GPT-2 Medium.

G Specialized Attention Heads within Knowledge Circuits

G.1 Definitions of Specialized Attention Heads

When zooming into the discovered knowledge circuits, we can find several specialized attention heads in the model that play a crucial role in the final prediction. These include the mover head, relation head, and mixture head (Chughtai et al., 2024).

Mover head Attention head that focuses on the final token of the context and attends strongly to the subject tokens in the context, functioning as a mover to transfer information and extract attributes pertaining to the subject from the enriched subject representation.

Relation head Attention head that focuses on the final token of the context and attends strongly to the relation tokens in the context for a particular relation and extract many relation-related attribute tokens.

Mixture head Attention Head that attends to both the relation tokens and the subject tokens in the context. It behaves as a combination of the two, performing the role of both Mover Head and Relation Head simultaneously.

G.2 Identification of Specialized Attention Heads

In this section, we provide details on how to identify mover heads, relation heads, and mixture heads in LLMs. We re-implement the methodology described in Chughtai et al. (2024) since the original

code has not been made publicly available by the authors. We will update our implementation once the source code is released.

Building on the Direct Logit Attribution (DLA) technique, which measures the direct effect of individual model components on model outputs, Chughtai et al. (2024) move beyond and propose DLA by source token group. This technique is based on the observation that attention head outputs are a weighted sum of outputs corresponding to distinct attention source positions (Elhage et al., 2021). This approach is useful for quantifying how a source token group directly affects the logits through individual attention heads.

With a specific factual recall task where the relation held constant, we aggregate over the validation set D_{val} for circuit discovery on the task, an attention head is classified as mover head if:

$$\left| \frac{\sum_{i=1}^{|D_{\text{val}}|} \text{DLA}_s(Q_i)}{\sum_{i=1}^{|D_{\text{val}}|} \text{DLA}_r(Q_i)} \right| > \tau \quad (5)$$

where i denotes the i -th entity in D_{val} , Q_i denotes the relation-specific query string for entity i as shown in Table 2, $\text{DLA}_s(Q_i)$ denotes DLA attributed to subject tokens, and $\text{DLA}_r(Q_i)$ denotes DLA attributed to relation tokens. Relatively, an attention head is classified as relation head if:

$$\left| \frac{\sum_{i=1}^{|D_{\text{val}}|} \text{DLA}_s(Q_i)}{\sum_{i=1}^{|D_{\text{val}}|} \text{DLA}_r(Q_i)} \right| < \frac{1}{\tau} \quad (6)$$

where threshold τ is set to be 10 as suggested in Chughtai et al. (2024). Remaining attention heads in LLMs are classified as mixture heads, behaving as a combination of mover head and relation head.

H Forgetting Analysis for Knowledge Circuits

To analyze the model’s forgetting of acquired knowledge, we conduct an additional continual pre-training experiment. We first construct new training corpus following the same pipeline described in §3.1, and then initialize training from the final checkpoint of the previous knowledge acquisition experiment on GPT-2 Small. We monitor structural consistency changes for knowledge circuits throughout 10 training epochs.

Our results in Figure 14 reveal that knowledge circuits demonstrate structural reconfiguration capacity, with the identified circuits dynamically adjusting more than 60% of their edges to accommodate new knowledge. However, data replay interventions, which involve the periodic replacement of




Figure 13: Left: Layer distribution of **mover head** in the knowledge circuits in GPT-2 Medium throughout training. Right: Layer distribution of **relation head** in the knowledge circuits in GPT-2 Medium throughout training.




Figure 14: Edges Jaccard Similarity of intermediate knowledge circuits with the circuits at the final checkpoint of the previous knowledge acquisition experiment.

a fixed ratio of original training samples, successfully mitigate knowledge forgetting by reactivating circuit components. This evidence suggests that LLMs maintain latent reactivation potential even after apparent behavioral forgetting — a property we term knowledge circuit elasticity.




Figure 15: Top: **Rank of the target attribute token** when unembedding the intermediate layer’s output into vocabulary space at the last token position throughout training for GPT-2 Small. Bottom: **Probability of the target attribute token** when unembedding the intermediate layer’s output into vocabulary space at the last token position throughout training for GPT-2 Small. Low-freq, Medium-freq, and High-freq represent knowledge with frequencies in the ranges $[1, 2)$, $[2, 5)$ and $(5, 27]$, respectively.




Figure 16: Top: **Rank of the target attribute token** when unembedding the intermediate layer’s output into vocabulary space at the last token position throughout training for GPT-2 Medium. Bottom: **Probability of the target attribute token** when unembedding the intermediate layer’s output into vocabulary space at the last token position throughout training for GPT-2 Medium. Low-freq, Medium-freq, and High-freq represent knowledge with frequencies in the ranges $[1, 2)$, $[2, 5)$ and $(5, 27]$, respectively.




Figure 17: Top: **Rank of the target attribute token** when unembedding the intermediate layer’s output into vocabulary space at the last token position throughout training for TinyLlama. Bottom: **Probability of the target attribute token** when unembedding the intermediate layer’s output into vocabulary space at the last token position throughout training for TinyLlama. Low-freq, Medium-freq, and High-freq represent knowledge with frequencies in the ranges $[1, 2)$, $[2, 5)$ and $(5, 27]$, respectively.

Name	Possible Values
First Name	Aarav, Abbott, Aberdeen, Abilene, Acey, Adair, Adelia, Adriel, Afton, Aida, Ainsley, Aislinn, Alaric, Albin, Alden, Aleah, Alessandra, Alistair, Allegra, Alphonse, Althea, Amaury, Ambrose, Amelina, Amias, Anatole, Anders, Ansel, Anthea, Antonella, Anwen, Arden, Ariadne, Aric, Arlen, Armand, Armando, Arwen, Asa, Astra, Atticus, Aubrey, Auden, Aurelia, Aurora, Aveline, Aviana, Azariah, Baird, Basil, Bayard, Beauregard, Bellamy, Belvedere, Benedict, Bennett, Berenice, Bertram, Blaine, Blair, Blythe, Boaz, Bodhi, Boniface, Bram, Branwen, Brenna, Briar, Briony, Broderick, Bromley, Bronson, Cadence, Cael, Caelan, Caius, Caledon, Calista, Calliope, Callum, Calyx, Cambria, Camellia, Candela, Caspian, Cassian, Cassiopeia, Castor, Cecily, Celeste, Celestia, Cerelia, Cerys, Chalcedony, Chandra, Charlton, Cicero, Cillian, Clemence, Clementine, Cleo, Clio, Clovis, Colton, Conall, Conrad, Corbin, Cordelia, Cormac, Cosima, Cressida, Crispin, Cybele, Cyril, Dahlia, Damaris, Daphne, Darby, Darcy, Dario, Davina, Deirdre, Delaney, Delphine, Demelza, Desmond, Dexter, Dimitri, Dinah, Dorian, Dulcie, Eamon, Earlene, Eben, Edeline, Edmund, Eldon, Eleri, Elia, Elian, Elias, Elodie, Eloise, Elowen, Ember, Emeline, Emrys, Endellion, Ender, Ephraim, Erasmus, Esme, Eulalia, Evadne, Evander, Everard, Everett, Fable, Fanchon, Farrah, Faye, Felix, Fern, Finlay, Fiora, Fletcher, Florian, Forsythia, Freya, Frida, Gable, Galen, Gareth, Garnet, Garrick, Gelsey, Gemma, Genever, Genevieve, Ginevra, Grady, Griffin, Guinevere, Hadley, Halcyon, Hale, Harlan, Hart, Haven, Hawthorne, Hazel, Heath, Helena, Hesper, Hollis, Honora, Hyacinth, Idris, Ilaria, Ilona, Imara, Indigo, Ingrid, Ione, Iris, Isadora, Isolde, Ivor, Jago, Jareth, Jarvis, Jemima, Jericho, Jocasta, Jolyon, Jorah, Jory, Jovan, Jubilee, Jules, Junia, Juniper, Kael, Kaia, Kalista, Kalliope, Katriel, Keir, Kenna, Kerensa, Keturah, Keziah, Kieran, Kirby, Kismet, Kit, Knox, Kyrie, Lachlan, Lark, Larkin, Laszlo, Leda, Leif, Lennox, Leonie, Leopold, Leta, Linnea, Liora, Livia, Llewellyn, Locke, Lorcan, Lorelei, Lorna, Lucian, Lysandra, Lysander, Mabel, Macey, Maeve, Magnolia, Malachi, Malin, Manon, Marcel, Marcellus, Maren, Marius, Marisol, Maris, Mathis, Matilda, Mavis, Maximilian, Meadow, Merrick, Merritt, Micaiah, Micah, Mira, Mireille, Mireya, Mirren, Morrigan, Muir, Nadia, Nadine, Nairne, Nara, Nash, Navi, Naylor, Neve, Nico, Nina, Noble, Nolan, Nora, Nova, Nyssa, Oberon, Octavia, Odessa, Oisín, Oleander, Olwen, Onyx, Ophelia, Orion, Orla, Orson, Osiris, Osric, Otilie, Ozias, Paisley, Paloma, Pax, Paz, Penelope, Peregrine, Persephone, Phaedra, Phineas, Phoenix, Pippa, Poppy, Portia, Posy, Primrose, Quill, Quinlan, Rafferty, Rain, Rainer, Raphael, Raven, Reeve, Reinette, Renata, Rhea, Rhiannon, Rhys, Riona, Roderick, Romilly, Rowan, Roxana, Rufus, Sable, Sabine, Saffron, Sage, Salem, Samara, Sancia, Saoirse, Sarai, Saskia, Selah, Seneca, Seraphina, Seren, Severin, Shai, Shiloh, Sibyl, Sidonie, Silas, Simeon, Simone, Sinclair, Sol, Solange, Sorrel, Sparrow, Stellan, Sullivan, Sylvain, Sybil, Sylvana, Tallulah, Tamsin, Tansy, Tarquin, Taryn, Tavish, Tegan, Thaddeus, Thelma, Theodora, Theron, Thorin, Thorne, Thora, Tiernan, Tristan, Tullia, Ursula, Valencia, Valerian, Vanya, Vesper, Vianne, Violetta, Virgil, Waverly, Wendell, Willa, Windsor, Winston, Wisteria, Wren, Wynn, Xanthe, Xavier, Xenia, Xerxes, Yara, Yasmin, Yelena, Ysabel, Yvaine, Zahra, Zara, Zephyr, Zinnia, Ziva, Zora
Middle Name	Abel, Abram, Ace, Adele, Ainsley, Alaric, Alcott, Alden, Allegra, Amara, Amethyst, Anders, Ansel, Arden, Arlo, Arrow, Asa, Asher, Aster, Astrid, Atticus, Auden, Aurora, Austen, Axel, Baird, Basil, Bay, Beau, Beck, Blaise, Blake, Blythe, Boden, Bodhi, Boone, Bram, Bran, Briar, Briggs, Brooks, Calla, Calvin, Caspian, Cassian, Cedar, Celeste, Chance, Channing, Cleo, Clove, Clyde, Cohen, Colt, Cove, Crew, Crosby, Cyrus, Dane, Dante, Dashiell, Dawn, Dax, Dean, Delta, Dimitri, Dove, Drake, Dune, Echo, Eden, Edison, Elara, Elian, Ellis, Elowen, Ember, Emrys, Eos, Esme, Evangeline, Ever, Everest, Ewan, Eyre, Fable, Fairfax, Fallon, Faye, Fenton, Fern, Finnian, Fleur, Flynn, Forrest, Fox, Gage, Gale, Garnet, Gideon, Gray, Greer, Halcyon, Hale, Harlow, Haven, Hawk, Hayes, Hollis, Hope, Hugo, Idris, Iker, Indigo, Ines, Iona, Iris, Isla, Iver, Jace, Jade, Jagger, Jem, Jet, Joaquin, Jude, Jules, Kai, Kane, Kash, Keats, Keira, Kellen, Kendrick, Kepler, Kian, Kit, Knox, Lake, Lark, Laurel, Layne, Leif, Lennox, Lester, Levi, Liam, Lila, Linnea, Locke, Lorcan, Lore, Luca, Lucian, Lux, Lyric, Maeve, Magnus, Maia, Malcolm, March, Maren, Marlow, Mason, Maverick, Meadow, Mercer, Merrick, Mica, Milan, Milo, Monroe, Moon, Nash, Nico, Noble, Noor, North, Oak, Oberon, Odette, Oisín, Oleander, Onyx, Opal, Orion, Otis, Otto, Pace, Parker, Pax, Paz, Penn, Perry, Phoenix, Pierce, Pine, Poe, Poet, Poppy, Porter, Prosper, Quill, Quincy, Rain, Reed, Reeve, Remy, Rex, Rhea, Ridge, Riven, Roan, Rogue, Roman, Rook, Rowan, Rune, Sable, Sage, Sailor, Saxon, Scout, Sequoia, Shane, Shiloh, Sierra, Sloane, Sol, Solstice, Soren, Sparrow, Star, Stone, Storm, Story, Sullivan, Sylvan, Talon, Tamsin, Tate, Teague, Teal, Thane, Thatcher, Thorn, Thornton, Tide, Torin, True, Vail, Valor, Veda, Vesper, Vince, Violette, Wade, Waverly, Wells, West, Wilder, Willow, Winter, Wren, Wynn, Xander, Xanthe, Xavier, Yara, York, Yule, Zane, Zara, Zephyr, Zinnia
Last Name	Abernathy, Ainsworth, Alberts, Ashcroft, Atwater, Babcock, Bader, Bagley, Bainbridge, Balfour, Barkley, Barlowe, Barnhill, Biddle, Billingsley, Birkett, Blakemore, Bleeker, Bliss, Bonham, Boswell, Braddock, Braithwaite, Briggs, Brockman, Bromley, Broughton, Burkhardt, Cadwallader, Calloway, Carmichael, Carrington, Cavanaugh, Chadwick, Chamberlain, Chilton, Claffey, Claypool, Clifton, Coffey, Colfax, Colquitt, Conway, Copley, Cotswold, Creighton, Crenshaw, Crowder, Culpepper, Cunningham, Dallimore, Darlington, Davenport, Delaney, Devlin, Doolittle, Dover, Driscoll, Dudley, Dunleavy, Eldridge, Elston, Fairfax, Farnsworth, Fitzgerald, Fitzroy, Flanders, Fleetwood, Gainsborough, Gatling, Goddard, Goodwin, Granger, Greenfield, Griffiths, Harcourt, Hargrove, Harkness, Haverford, Hawkins, Hawthorne, Heathcote, Holbrook, Hollingworth, Holloway, Holmes, Holtz, Howland, Ingles, Jardine, Kenworthy, Kingsley, Langford, Latham, Lathrop, Lockhart, Lodge, Loxley, Lyndon, MacAlister, MacGregor, Mansfield, Marston, Mather, Middleton, Millington, Milton, Montague, Montgomery, Montoya, Morgenthal, Mortimer, Nash, Newcomb, Newkirk, Nightingale, Norwood, Oakley, Ormsby, Osborne, Overton, Pemberton, Pennington, Percival, Pickering, Prescott, Prichard, Quimby, Radcliffe, Rafferty, Rainier, Ramsay, Rawlins, Renshaw, Ridley, Rivers, Rockwell, Roosevelt, Rothschild, Rutherford, Sanderson, Sedgwick, Selwyn, Severance, Sheffield, Sheridan, Sherwood, Shields, Sinclair, Slater, Somerset, Standish, Stanton, Stoddard, Stokes, Stratford, Strickland, Sutherland, Sutton, Talmadge, Tanner, Tennyson, Thackeray, Thatcher, Thorne, Thurston, Tilden, Townsend, Trent, Trevelyan, Trumbull, Underhill, Vanderbilt, Vandermeer, Vickers, Wadsworth, Wakefield, Walpole, Waring, Warwick, Weatherford, Webster, Wharton, Whittaker, Wickham, Wiggins, Wilcox, Winslow, Winthrop, Wolcott, Woodruff, Wycliffe, Yardley, Yates, Yeats, Yule, Zeller, Zimmerman

Table 3: All possible values generated for the first name, middle name and last name.

Relation	Possible Attributes
City	"Princeton, NJ", "New York, NY", "Los Angeles, CA", "Chicago, IL", "Houston, TX", "Phoenix, AZ", "Philadelphia, PA", "San Antonio, TX", "San Diego, CA", "Dallas, TX", "San Jose, CA", "Austin, TX", "Jacksonville, FL", "Fort Worth, TX", "Columbus, OH", "San Francisco, CA", "Charlotte, NC", "Indianapolis, IN", "Seattle, WA", "Denver, CO", "Washington, DC", "Boston, MA", "El Paso, TX", "Nashville, TN", "Detroit, MI", "Oklahoma City, OK", "Portland, OR", "Las Vegas, NV", "Memphis, TN", "Louisville, KY", "Baltimore, MD", "Milwaukee, WI", "Albuquerque, NM", "Tucson, AZ", "Fresno, CA", "Mesa, AZ", "Sacramento, CA", "Atlanta, GA", "Kansas City, MO", "Colorado Springs, CO", "Miami, FL", "Raleigh, NC", "Omaha, NE", "Long Beach, CA", "Virginia Beach, VA", "Oakland, CA", "Minneapolis, MN", "Tulsa, OK", "Arlington, TX", "Tampa, FL", "New Orleans, LA", "Wichita, KS", "Cleveland, OH", "Bakersfield, CA", "Aurora, CO", "Anaheim, CA", "Honolulu, HI", "Santa Ana, CA", "Riverside, CA", "Corpus Christi, TX", "Lexington, KY", "Stockton, CA", "Henderson, NV", "Saint Paul, MN", "St. Louis, MO", "Cincinnati, OH", "Pittsburgh, PA", "Greensboro, NC", "Anchorage, AK", "Plano, TX", "Lincoln, NE", "Orlando, FL", "Irvine, CA", "Newark, NJ", "Toledo, OH", "Durham, NC", "Chula Vista, CA", "Fort Wayne, IN", "Jersey City, NJ", "St. Petersburg, FL", "Laredo, TX", "Madison, WI", "Chandler, AZ", "Buffalo, NY", "Lubbock, TX", "Scottsdale, AZ", "Reno, NV", "Glendale, AZ", "Gilbert, AZ", "Winston-Salem, NC", "North Las Vegas, NV", "Norfolk, VA", "Chesapeake, VA", "Garland, TX", "Irving, TX", "Hialeah, FL", "Fremont, CA", "Boise, ID", "Richmond, VA", "Baton Rouge, LA", "Spokane, WA", "Des Moines, IA", "Tacoma, WA", "San Bernardino, CA", "Modesto, CA", "Fontana, CA", "Santa Clarita, CA", "Birmingham, AL", "Oxnard, CA", "Fayetteville, NC", "Moreno Valley, CA", "Rochester, NY", "Glendale, CA", "Huntington Beach, CA", "Salt Lake City, UT", "Grand Rapids, MI", "Amarillo, TX", "Yonkers, NY", "Aurora, IL", "Montgomery, AL", "Akron, OH", "Little Rock, AR", "Huntsville, AL", "Augusta, GA", "Port St. Lucie, FL", "Grand Prairie, TX", "Columbus, GA", "Tallahassee, FL", "Overland Park, KS", "Tempe, AZ", "McKinney, TX", "Mobile, AL", "Cape Coral, FL", "Shreveport, LA", "Frisco, TX", "Knoxville, TN", "Worcester, MA", "Brownsville, TX", "Vancouver, WA", "Fort Lauderdale, FL", "Sioux Falls, SD", "Ontario, CA", "Chattanooga, TN", "Providence, RI", "Newport News, VA", "Rancho Cucamonga, CA", "Santa Rosa, CA", "Peoria, AZ", "Oceanside, CA", "Elk Grove, CA", "Salem, OR", "Pembroke Pines, FL", "Eugene, OR", "Garden Grove, CA", "Cary, NC", "Fort Collins, CO", "Corona, CA", "Springfield, MO", "Jackson, MS", "Alexandria, VA", "Hayward, CA", "Clarksville, TN", "Lancaster, CA", "Lakewood, CO", "Palmdale, CA", "Salinas, CA", "Hollywood, FL", "Pasadena, TX", "Sunnyvale, CA", "Macon, GA", "Pomona, CA", "Escondido, CA", "Killeen, TX", "Naperville, IL", "Joliet, IL", "Bellevue, WA", "Rockford, IL", "Savannah, GA", "Paterson, NJ", "Torrance, CA", "Bridgeport, CT", "McAllen, TX", "Mesquite, TX", "Syracuse, NY", "Midland, TX", "Pasadena, CA", "Murfreesboro, TN", "Miramar, FL", "Dayton, OH", "Fullerton, CA", "Olathe, KS", "Orange, CA", "Thornton, CO", "Roseville, CA", "Denton, TX", "Waco, TX", "Surprise, AZ", "Carrollton, TX", "West Valley City, UT", "Charleston, SC", "Warren, MI", "Hampton, VA", "Gainesville, FL", "Visalia, CA", "Coral Springs, FL", "Columbia, SC", "Cedar Rapids, IA", "Sterling Heights, MI", "New Haven, CT", "Stamford, CT", "Concord, CA", "Kent, WA", "Santa Clara, CA", "Elizabeth, NJ", "Round Rock, TX", "Thousand Oaks, CA", "Lafayette, LA", "Athens, GA", "Topeka, KS", "Simi Valley, CA", "Fargo, ND"

Table 4: All possible attributes generated for *city* relation.

Relation	Possible Attributes
Major	Accounting, Actuarial Science, Advertising, Aerospace Engineering, African American Studies, Agribusiness, Agricultural Engineering, Agriculture, Agronomy, Animal Science, Anthropology, Applied Mathematics, Architecture, Art History, Arts Management, Astronomy, Astrophysics, Athletic Training, Atmospheric Sciences, Biochemistry, Bioengineering, Biological Sciences, Biology, Biomedical Engineering, Biotechnology, Botany, Broadcast Journalism, Business Administration, Business Analytics, Business Economics, Business Information Systems, Chemical Engineering, Chemistry, Civil Engineering, Classics, Cognitive Science, Communication Studies, Communications, Comparative Literature, Computer Engineering, Computer Science, Construction Management, Counseling, Creative Writing, Criminal Justice, Criminology, Culinary Arts, Cybersecurity, Dance, Data Science, Dietetics, Digital Media, Drama, Earth Sciences, Ecology, Economics, Education, Electrical Engineering, Elementary Education, Engineering Physics, Engineering Technology, English, Entrepreneurship, Environmental Engineering, Environmental Science, Environmental Studies, Exercise Science, Fashion Design, Fashion Merchandising, Film Studies, Finance, Fine Arts, Fisheries and Wildlife, Food Science, Forensic Science, Forestry, French, Game Design, Genetics, Geography, Geology, German, Global Studies, Graphic Design, Health Administration, Health Education, Health Informatics, Health Sciences, Healthcare Management, History, Horticulture, Hospitality Management, Human Development, Human Resources Management, Human Services, Industrial Engineering, Information Systems, Information Technology, Interior Design, International Business, International Relations, Journalism, Kinesiology, Labor Studies, Landscape Architecture, Latin American Studies, Law, Legal Studies, Liberal Arts, Linguistics, Management, Management Information Systems, Marine Biology, Marketing, Mass Communications, Materials Science, Mathematics, Mechanical Engineering, Media Studies, Medical Technology, Medicine, Microbiology, Molecular Biology, Music, Music Education, Music Performance, Neuroscience, Nursing, Nutrition, Occupational Therapy, Oceanography, Operations Management, Optometry, Organizational Leadership, Paleontology, Paralegal Studies, Pharmacy, Philosophy, Photography, Physical Education, Physical Therapy, Physics, Physiology, Political Science, Pre-Dental, Pre-Law, Pre-Med, Pre-Pharmacy, Pre-Veterinary, Psychology, Public Administration, Public Health, Public Policy, Public Relations, Quantitative Analysis, Radiologic Technology, Real Estate, Recreation Management, Religious Studies, Renewable Energy, Respiratory Therapy, Risk Management, Robotics, Rural Studies, Sales, Social Work, Sociology, Software Engineering, Spanish, Special Education, Speech Pathology, Sports Management, Statistics, Supply Chain Management, Sustainability, Telecommunications, Theater, Tourism Management, Toxicology, Transportation, Urban Planning, Veterinary Medicine, Victimology, Video Production, Web Development, Wildlife Conservation, Women's Studies, Zoology

Table 5: All possible attributes generated for *major* relation.

Relation	Possible Attributes
Company	Apple, Microsoft, Amazon, Google, Facebook, Berkshire Hathaway, Visa, Johnson & Johnson, Walmart, Procter & Gamble, Nvidia, JPMorgan Chase, Home Depot, Mastercard, UnitedHealth Group, Verizon Communications, Pfizer, Chevron, Intel, Cisco Systems, Merck & Co., Coca-Cola, PepsiCo, Walt Disney, AbbVie, Comcast, Bank of America, ExxonMobil, Thermo Fisher Scientific, McDonald's, Nike, AT&T, Abbott Laboratories, Wells Fargo, Amgen, Oracle, Costco Wholesale, Salesforce, Medtronic, Bristol-Myers Squibb, Starbucks, IBM, NextEra Energy, Broadcom, Danaher, Qualcomm, General Electric, Honeywell, Citigroup, Lockheed Martin, Union Pacific, Goldman Sachs, Raytheon Technologies, American Express, Boeing, Texas Instruments, Gilead Sciences, S&P Global, Deere & Company, Charles Schwab, Colgate-Palmolive, General Motors, Anthem, Philip Morris International, Caterpillar, Target, Intuitive Surgical, Northrop Grumman, Booking Holdings, ConocoPhillips, CVS Health, Altria Group, Eli Lilly and Company, Micron Technology, Fiserv, BlackRock, American Tower, General Dynamics, Lam Research, Zoetis, Applied Materials, Elevance Health, T-Mobile US, Automatic Data Processing, Marsh & McLennan, Mondelez International, Kroger, Crown Castle, Cigna, Analog Devices, FedEx, CSX, Uber Technologies, Moderna, Truist Financial, Kraft Heinz, HCA Healthcare, Dominion Energy, Cognizant Technology Solutions, Occidental Petroleum, Regeneron Pharmaceuticals, Freeport-McMoRan, eBay, O'Reilly Automotive, Southern Company, Duke Energy, Sherwin-Williams, PayPal, Nucor, Gartner, AutoZone, Cheniere Energy, ServiceNow, Constellation Brands, Discover Financial, U.S. Bancorp, Public Storage, Aflac, Lennar, Johnson Controls, Tyson Foods, Sempra Energy, Southwest Airlines, Las Vegas Sands, McKesson, Baxter International, KLA Corporation, Monster Beverage, Archer Daniels Midland, Eaton, Paccar, Illumina, Intercontinental Exchange, Clorox, Capital One Financial, Estee Lauder, Hess, Becton Dickinson, Parker-Hannifin, Cummins, Ameriprise Financial, Fidelity National Information Services, State Street, Xilinx, Chipotle Mexican Grill, Expeditors International, Roper Technologies, L3Harris Technologies, M&T Bank, Alcoa, Live Nation Entertainment, Marriott International, Norfolk Southern, DISH Network, Akamai Technologies, Fortinet, Ball Corporation, Corning, Nordstrom, CMS Energy, Nasdaq, BorgWarner, Liberty Media, Sealed Air, PulteGroup, General Mills, Ross Stores, Hewlett Packard Enterprise, Host Hotels & Resorts, Hilton Worldwide, Snap-on, Zebra Technologies, Leidos, Lincoln National, Weyerhaeuser, CarMax, Rockwell Automation, Allstate, Entergy, NRG Energy, AutoNation, LyondellBasell, Omnicom Group, HollyFrontier, Western Digital, International Flavors & Fragrances, Eastman Chemical, Xcel Energy, Xylem, Ansys, IPG Photonics, Digital Realty, First Solar, Jacobs Engineering, Cognex, Ingersoll Rand, Fastenal, Allegion, LKQ, AMETEK, WABCO Holdings, Keysight Technologies

Table 6: All possible attributes generated for *company* relation.

Relation	Possible Attributes
University	<p>Massachusetts Institute of Technology, Harvard University, Stanford University, California Institute of Technology, University of Chicago, Princeton University, Columbia University, Yale University, University of Pennsylvania, University of California, Berkeley, University of California, Los Angeles, University of Michigan, Ann Arbor, Duke University, Johns Hopkins University, Northwestern University, New York University, University of California, San Diego, University of Southern California, Cornell University, Rice University, University of California, Santa Barbara, University of Washington, University of Texas at Austin, University of Wisconsin-Madison, University of Illinois at Urbana-Champaign, University of North Carolina at Chapel Hill, Washington University in St. Louis, University of Florida, University of Virginia, Carnegie Mellon University, Emory University, Georgetown University, University of California, Irvine, University of Notre Dame, University of Rochester, Boston College, Boston University, Ohio State University, Pennsylvania State University, University of Miami, Purdue University, University of Minnesota, University of Maryland, Michigan State University, University of Colorado Boulder, University of Pittsburgh, University of Arizona, University of Utah, University of California, Davis, University of Massachusetts Amherst, Indiana University Bloomington, University of Connecticut, University of Iowa, University of Missouri, University of Kansas, University of Kentucky, University of Tennessee, University of Alabama, University of Oklahoma, University of Oregon, University of Nebraska-Lincoln, University of South Carolina, University of New Hampshire, University of Vermont, University of Delaware, University of Rhode Island, University of Arkansas, Auburn University, Baylor University, Brigham Young University, Clemson University, Colorado State University, Drexel University, Florida State University, George Washington University, Howard University, Iowa State University, Kansas State University, Louisiana State University, Marquette University, Mississippi State University, North Carolina State University, Northeastern University, Oklahoma State University, Oregon State University, Rutgers University, San Diego State University, Southern Methodist University, Stony Brook University, Syracuse University, Temple University, Texas A&M University, Texas Tech University, Tulane University, University of Alabama at Birmingham, University of Central Florida, University of Cincinnati, University of Dayton, University of Denver, University of Georgia, University of Houston, University of Idaho, University of Louisville, University of Maryland, Baltimore County, University of Memphis, University of Mississippi, University of Nevada, Las Vegas, University of New Mexico, University of North Texas, University of San Francisco, University of South Florida, University of Texas at Dallas, University of Toledo, University of Tulsa, University of Wyoming, Villanova University, Virginia Tech, Wake Forest University, West Virginia University, Wichita State University, Worcester Polytechnic Institute, Xavier University, Yeshiva University, American University, Arizona State University, Arkansas State University, Ball State University, Boise State University, Bowling Green State University, Bradley University, California Polytechnic State University, California State University, Long Beach, Central Michigan University, Chapman University, City University of New York, Claremont McKenna College, Clark University, College of William & Mary, DePaul University, Eastern Michigan University, Fairfield University, Florida Atlantic University, Fordham University, Hofstra University, Illinois Institute of Technology, James Madison University, Loyola Marymount University, Loyola University Chicago, Miami University, Middlebury College, New Jersey Institute of Technology, Northern Arizona University, Northern Illinois University, Pepperdine University, Pomona College, Rensselaer Polytechnic Institute, Rhode Island School of Design, Rollins College, Saint Louis University, San Francisco State University, San Jose State University, Santa Clara University, Seattle University, Seton Hall University, Southern Illinois University, Stevens Institute of Technology, SUNY College of Environmental Science and Forestry, SUNY Polytechnic Institute, Texas Christian University, The New School, Towson University, Trinity College, Trinity University, Tufts University, Union College, University at Albany, University at Buffalo, University of Akron, University of Alabama in Huntsville, University of Alaska Anchorage, University of Alaska Fairbanks, University of Baltimore, University of Bridgeport, University of Central Arkansas, University of Charleston, University of Dayton, University of Detroit Mercy, University of Evansville, University of Hartford, University of La Verne, University of Mary Washington, University of Michigan-Dearborn, University of Michigan-Flint, University of Montana, University of Nebraska Omaha, University of Nevada, Reno, University of North Dakota, University of North Florida, University of Northern Colorado, University of Redlands, University of Richmond, University of Saint Joseph, University of San Diego, University of Scranton, University of Sioux Falls, University of South Alabama, University of Southern Mississippi, University of St. Thomas, University of Tampa, University of the Pacific, University of the Sciences, University of Toledo, University of West Georgia, University of Wisconsin-Eau Claire, University of Wisconsin-Green Bay, University of Wisconsin-La Crosse, University of Wisconsin-Milwaukee, University of Wisconsin-Oshkosh, University of Wisconsin-Platteville, University of Wisconsin-River Falls, University of Wisconsin-Stevens Point, University of Wisconsin-Stout, University of Wisconsin-Superior, University of Wisconsin-Whitewater, Ursinus College, Utah State University, Valparaiso University, Vanderbilt University, Vassar College, Villanova University, Virginia Commonwealth University, Wabash College, Wagner College, Wayne State University, Webster University, Weber State University, Wellesley College, Wentworth Institute of Technology, Wesleyan University, Western Carolina University, Western Kentucky University, Western Michigan University, Western Washington University, Westminster College, Whitman College, Whittier College, Willamette University, Williams College, Wittenberg University, Wofford College, Woodbury University, Wright State University, Xavier University, Yale University, York College of Pennsylvania</p>

Table 7: All possible attributes generated for *university* relation.