METAFOR: A Hybrid Metaheuristics Software Framework for Single-Objective Continuous Optimization Problems

CHRISTIAN CAMACHO-VILLALÓN^{*}, Department of Knowledge Technologies, Jožef Stefan Institute, Slovenia and Institut de Recherches Interdisciplinaires et de Développements en Intelligence Artificielle (IRIDIA), Université Libre de Bruxelles, Belgium

MARCO DORIGO and THOMAS STÜTZLE, Institut de Recherches Interdisciplinaires et de Développements en Intelligence Artificielle (IRIDIA), Université Libre de Bruxelles, Belgium

Hybrid metaheuristics are powerful techniques for solving difficult optimization problems that exploit the strengths of different approaches in a single implementation. For algorithm designers, however, creating hybrid metaheuristic implementations has become increasingly challenging due to the vast number of design options available in the literature and the fact that they often rely on their knowledge and intuition to come up with new algorithm designs. In this paper, we propose a modular metaheuristic software framework, called **METAFOR**, that can be coupled with an automatic algorithm configuration tool to automatically design hybrid metaheuristics. **METAFOR** is specifically designed to hybridize Particle Swarm Optimization, Differential Evolution and Covariance Matrix Adaptation–Evolution Strategy, and includes a local search module that allows their execution to be interleaved with a subordinate local search. We use the configuration tool i race to automatically generate 17 different metaheuristic implementations and evaluate their performance on a diverse set of continuous optimization problems. Our results show that, across all the considered problem classes, automatically generated hybrid implementations are able to outperform configured single-approach implementations, while these latter offer advantages on specific classes of functions. We provide useful insights on the type of hybridization that works best for specific problem classes, the algorithm components that contribute to the performance of the algorithms, and the advantages and disadvantages of two well-known instance separation strategies, creating stratified training set using a fix percentage and leave-one-class-out cross-validation.

Additional Key Words and Phrases: Metaheuristic Framework, Automated Algorithm Design

ACM Reference Format:

1 INTRODUCTION

Continuous optimization problems are ubiquitous in many areas of science and technology, including engineering, finance, education, e-commerce and healthcare, to name a few. In a *d*-dimensional continuous optimization problem,

Authors' Contact Information: Christian Camacho-Villalón, Department of Knowledge Technologies, Jožef Stefan Institute, Ljubljana, Slovenia and Institut de Recherches Interdisciplinaires et de Développements en Intelligence Artificielle (IRIDIA), Université Libre de Bruxelles, Brussels, Belgium, christian.camacho.villalon@ijs.si; Marco Dorigo, mdorigo@ulb.ac.be; Thomas Stützle, thomas.stuetzle@ulb.be, Institut de Recherches Interdisciplinaires et de Développements en Intelligence Artificielle (IRIDIA), Université Libre de Bruxelles, Brussels, Belgium.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

the goal is to find a *d*-dimensional vector that minimizes a continuous objective function. Due to their complexity, many continuous optimization problems cannot be efficiently approached using traditional analytical methods, such as gradient search or the Hessian matrix computation. These methods often have limitations when continuous optimization problems involve multimodal, non-differentiable functions [1], nonlinear constraints and/or a large number of dimensions [23, 68], or when the objective function is not explicitly given, as in the case when it is computed using a computer simulation [3].

To tackle difficult optimization problems of all kinds, researchers have proposed techniques, such as heuristics or metaheuristics [30, 32, 46, 92], which are capable of finding "good solutions" in a "reasonable time", but offer no guarantee about the optimality of the solutions generated. Among the two largest groups of metaheuristics that can be used to tackle continuous optimization problems are *evolutionary computation* (EC) [28, 45, 84, 87, 88], which include techniques such as evolution strategies (ESs) [83, 87], genetic algorithms (GAs) [33, 45], and differential evolution (DE) [93]; and *swarm intelligence* (SI) [11, 25, 54], which includes techniques such as particle swarm optimization (PSO) [26, 53], ant colony optimization (ACO) [57, 63, 91] and artificial bee colonies [51, 52]. Most evolutionary computation and swarm intelligence metaheuristics are population-based, i.e., they handle multiple solutions at the same time in order to perform a parallel exploration of the search space.

In this paper, we consider some of the most successful population-based metaheuristics and investigate how they can be combined to create high-performance hybrid implementations for single-objective continuous optimization problems using an automatic design approach. The automatic design approach consist in delegating the task of designing and configuring a metaheuristic implementations to an automatic algorithm configuration tool, e.g., ParamILS [49], SMAC [48] or irace [64, 65], rather than to a human algorithm designer. This approach has already been used to design various state-of-the-art metaheuristics, including stochastic local search [29, 77], multi-objective evolutionary algorithms [6, 7], DE [98], CMA–ES [22, 61], ACO [59, 66, 67], and PSO [15, 73]. However, there are relatively few papers investigating how to automatically combine the strengths of multiple metaheuristics into single implementations [10, 62]. In this work we develop a metaheuristic software framework that allows users to instantiate hybrid metaheuristics to solve continuous optimization problems in a robust and efficient manner.

Our main contribution is the development of a metaheuristic software framework called **METAFO**R, which stands for **META**heuristic **F**ramework for **O**ptimization in Real domains, and incorporates more than one hundred components proposed in the literature for PSO, covariance matrix adaptation–ES (CMA–ES), DE and local search (LS) algorithms. **METAFO**R allows users not only to replicate many state-of-the-art variants of these metaheuristics, including many of their hybrids, but also to combine their components in new ways using a flexible algorithm template specifically designed for combining population-based metaheuristics with a local search procedure. Due to its modular design, **METAFO**R can be easily extended with more components allowing users to try novel ideas and assess their usefulness in a systematic manner. Also, **METAFO**R is a parameterized framework: executing it with different parameters results in different implementations, which facilitates its integration with automatic algorithm configuration tools to explore its design space and find high-performance implementations.

We defined two machine learning-type training scenarios (one in which we included only a fixed percentage of 75% of the problem instances and another in which we left out an entire problem class) and used irace to automatically generate 17 implementations of PSO, CMA–ES and DE, which we experimentally compared using an heterogeneous benchmark set of 50 continuous functions. The benchmark set includes unimodal, multimodal and hybrid composition functions, mathematical transformations (rotation, translation and scaling) and varying dimensionalities (from

50 to 1250 dimensions). We find that automatically generated hybrids involving CMA–ES perform better than singleapproach implementations across the entire set of 50 functions, whereas configured single-approach implementations of DE excel in functions with a large number of dimensions. We study the differences in the algorithms designs and discuss how these differences contribute to the differences in their performance.

The rest of this paper is structured as follows. Section 2 provides an overview of PSO, CMA–ES, DE and LS algorithms and briefly discusses the fundamentals of automatic design. Section 3 reviews the literature on hybrid implementations combining PSO, CMA–ES and DE. In Section 4, we introduce **METAFO**R and describe the way it has been designed. In Section 5, we experimentally compare default, configured and hybrid implementations of PSO, CMA–ES and DE created using **METAFO**R. Finally, in Section 6, we conclude the paper and provide ideas for future research.

2 CONTINUOUS OPTIMIZATION PROBLEMS, METAHEURISTICS, AND AUTOMATIC DESIGN

Without loss of generality, in a continuous optimization problem, the goal is to minimize a *d*-dimensional continuous objective function $f : S \subseteq \mathbb{R}^d \to \mathbb{R}$ by finding a vector \vec{o} in the search space *S*, such that $\forall \vec{x} \in S$, $f(\vec{o}) \leq f(\vec{x})$. The search space *S* is a subset of \mathbb{R}^d in which a solution is represented by a real-valued vector \vec{x} , and each component x_j of \vec{x} is constrained by a lower and upper bound: $lb_j \leq x_j \leq ub_j$, for $j = 1, \ldots, d$. Although there are many different approaches that can be used to deal with continuous optimization problems [24], in our work we focused on PSO, CMA–ES, DE and LS algorithms, which are among the best performing ones reported in the literature [60, 90]. The main characteristic of PSO, CMA–ES and DE is that they are population-based metaheuristics, that is, at each iteration, they keep a population of solutions and perform a parallel exploration-exploitation of the search space. Differently, local search algorithms, such as multiple trajectory search local search [97], make small changes to a single solution based on a step-size parameter that determines how far a new candidate solution will be created. Since population-based metaheuristics and local search have complementary characteristics, they are often combined to create algorithms that are better equipped to solve difficult optimization problems [31, 62, 71, 72].

2.1 Population-based metaheuristics

2.1.1 Particle Swarm Optimization. In particle swarm optimization (PSO) [26, 53], particles try to discover the region of the search space where the best quality solutions are located by moving in directions that are estimated based on the best locations that they and their neighboring particles have visited in the past. The standard version of PSO (StaPSO) [89] uses a computational model composed of three main elements: (i) a *cognitive component* that allows each particle *i* in the swarm to memorize the best position it has visited so far, called personal best position \vec{p}^i ; (ii) a *social component* that allows a particle to know the best position \vec{l}^i ever found by any of the particles in its neighborhood; and (iii) a *velocity update rule* and a *position update rule* that specify how the particles move in the search space and that are defined respectively as follows:

$$\vec{v}_{t+1}^{i} = \omega \vec{v}_{t}^{i} + \varphi_{1} U_{1t}^{i} \left(\vec{p}_{t}^{i} - \vec{x}_{t}^{i} \right) + \varphi_{2} U_{2t}^{i} \left(\vec{l}_{t}^{i} - \vec{x}_{t}^{i} \right) \quad \text{for } i = 1, \dots, n,$$

$$\tag{1}$$

$$\vec{x}_{t+1}^i = \vec{x}_t^i + \vec{v}_{t+1}^i, \tag{2}$$

where n is the number of particles.

The position of the particles (vectors \vec{x}), which represent candidate solutions to the optimization problem, are updated in every iteration *t* of the algorithm by computing a new velocity vector (Equation 1) that is added to their current positions (Equation 2). The computation of a particle's new velocity makes use of two random diagonal matrices, U_{1t}^i Manuscript submitted to ACM and U_{2t}^i , to introduce diversity to the particle's movement, and of three real parameters, ω , φ_1 and φ_2 , that control, respectively, the influence of the previous velocity (also called the particle's inertia), of the cognitive component and of the social component. The role of vectors \vec{p}_t and \vec{l}_t in the velocity update rule is to combine the knowledge acquired by each particle during the search with the knowledge of the best-informed individual in the neighborhood of the particle.

2.1.2 Covariance Matrix Adaptation–Evolution Strategy. The evolution strategy (ES) with covariance matrix adaptation (CMA–ES) [36, 41] is a ES in which the complete covariance matrix of the normal mutation distribution is adapted at execution time. The main idea in ESs is to simulate the process by which a population of μ parents (solutions) undergoes recombination and mutation to generate λ offspring (new solutions). Then, a selection operator is applied to choose a subset of these solutions to form the population for the next iteration. CMA–ES is similar to the Quasi-Newton method [75] in the sense that it is a second-order estimator that iteratively estimates a positive definite matrix, specifically the covariance matrix. However, unlike the Quasi-Newton method, CMA–ES does not use approximate gradients, nor does it assume their existence. The standard CMA–ES implementation [37, 38] is composed of three main steps.

The first step, *random sampling*, consist in sampling a population of λ solutions from a multivariate normal distribution \mathcal{N} with mean $\vec{m} \in \mathbb{R}^d$ and covariance $\mathbf{C} \in \mathbb{R}^{d \times d}$, as shown in the following equation:

$$\vec{x}_{t+1}^i = \vec{m}_t + \sigma_t \times \mathcal{N}(0, C_t) \quad \text{for } i = 1, \dots, \lambda, \tag{3}$$

where \vec{x}_{t+1}^i is a vector representing the *i*-th individual in the population, and $\sigma_t > 0$ is the standard deviation that controls the sampling radius or step-size.

In the second step, weighted intermediate recombination, the λ individuals are ranked in ascending order and the μ best ones are selected to update the mean of the sampling distribution. The equation describing this process is the following:

$$\vec{m}_{t+1} = \sum_{i=1}^{\mu} w^i \vec{x}_{t+1}^{(i|\lambda)},\tag{4}$$

where $w^1 \ge w^2 \ge \ldots w^{\mu} > 0$, $\sum_{i=1}^{\mu} w^i = 1$, and $\vec{x}_{t+1}^{(i|\lambda)}$ denotes the *i*-th ranked individual of the λ solutions sampled using Equation 3. The weights w^i are decreased logarithmically using:

$$w^{i} = \log\left(\frac{\lambda - 1}{2} + 1\right) - \log(i) \text{ for } i = 1, \dots, \mu.$$
 (5)

The last step is the *covariance matrix adaptation*. The process of adapting the covariance matrix for the next iteration uses a combination of rank-one update (i.e., the mean of the estimated covariance matrices using a single selected step, namely the "evolution path") and the rank- μ update (i.e., the mean of the estimated covariance matrices from all previous iterations). The update of the covariance matrix is done as follows:

$$\mathbf{C}_{t+1} = (1 - c_{\text{cov}})\mathbf{C}_t + \frac{c_{\text{cov}}}{\mu_{\text{cov}}} \underbrace{\vec{p}_{t+1}^c (\vec{p}_{t+1}^c)^T}_{\text{rank-one update}} + c_{\text{cov}} \left(1 - \frac{1}{\mu_{\text{cov}}}\right) \underbrace{\sum_{i=1}^{\mu} w^i \vec{y}_{t+1}^{(i|\lambda)} (\vec{y}_{t+1}^{(i|\lambda)})^T}_{\text{rank-}\mu \text{ update}}, \tag{6}$$

where $c_{cov} \in [0, 1]$ is the learning rate for the covariance matrix update, μ_{cov} is used to determine the weighting between the rank-one and rank- μ update, \vec{p}_{t+1}^c is the evolution path (i.e., the search path the algorithm takes over a number of iterations and it is expressed as a sum of consecutive steps of \vec{m}), and $\vec{y}_{t+1}^{(i|\lambda)} = (\vec{x}_{t+1}^{(i|\lambda)} - \vec{m}_t)/\sigma_t$. For a detailed explanation of how to compute the evolution path \vec{p}_{t+1}^c and the new step-size σ_{t+1} , we refer the reader to [38, 39]. Manuscript submitted to ACM 2.1.3 Differential Evolution. Differential Evolution (DE) [82, 93] is another evolutionary approach, though it is often regarded as distinct because it incorporates concepts that are similar to those found in SI methods. DE implements a mutation operator, called *differential mutation*, that is similar to the moves in the Nelder-Mead simplex search method [74]. The differential mutation operator consists of selecting three solutions from the population, computing the difference of the first two solutions and multiplying it by a scaling factor, and then adding the scaled vector difference to the third solution. More formally, in DE, the mutation operator is defined as follows:

$$\vec{m}^i = \vec{x}^a + \beta \cdot (\vec{x}^b - \vec{x}^c),\tag{7}$$

where i = 1, ..., n denotes the *i*th individual in a population of *n* solutions, β is the scaling factor and vectors $\vec{x}^a \neq \vec{x}^b \neq \vec{x}^c$ are the three solutions randomly chosen from the population. Vector \vec{x}^a , which is referred to as *base vector* and can be selected in many ways, has to be different from the solution in the population for which it is targeted, that is, vector \vec{x}^i , which is referred to as *target vector*. The result of applying Equation 7 is a vector called *mutant vector*, indicated as \vec{m}^i .

The creation of the mutant vector is followed by recombination, in which the mutant vector (\vec{m}^i) is recombined with target vector (\vec{x}^i) to create a *trial vector* \vec{u}^i . The equation to apply recombination and obtain the trial vector is the following:

$$u^{i,k} = \begin{cases} m^{i,k}, & \text{if } (\mathcal{U}[0,1] \ge p_a) \lor (k = k^i_{rand}) \\ x^{i,k}, & \text{otherwise} \end{cases}, \ \forall k, \forall i, \end{cases}$$
(8)

where k = 1, ..., d allows to iterate between the values of the vectors, $\mathcal{U}[0, 1]$ is a random number sampled from a uniform distribution, d is the number of dimensions of continuous optimization problem, p_a is a real parameter in the range [0, 1] that controls the fraction of values copied from the mutant vector into the trial vector, and k_{rand}^i is a randomly chosen dimension that ensures that the trial vector is not a duplicate of the target vector. The newly generated trial vector \vec{u}^i only replaces the target vector \vec{x}^i in the population if it has better quality, otherwise is discarded. Also, as indicated in Equation 8, the mutation and recombination operators are iteratively applied for every solution in the population.

2.2 Local search strategies for continuous optimization problems

Among the best-known local search algorithms proposed to tackle continuous optimization problems are the Nelder-Mead Simplex algorithm [74], the Powell's conjugate directions set algorithm [79], and the BOBYQA algorithm [81] (also by Powell). In this paper, we consider the more recent multiple trajectory search local search (MTSIs) algorithm [97]. The choice of MTSIs was motivated by the excellent results obtained by various hybrid algorithms for continuous optimization that integrate this local search [56, 62].

The MTSIs algorithm starts by generating a candidate solution $\vec{s} = (s_1, s_2, ..., s_d)$ uniformly at random inside the search range. The initial step size ss is set to $ss = 0.5 \times (ub_j - lb_j)$, where 0.5 is a default value [97] and ub and lb are, respectively, the upper and lower bounds of dimension j. MTSIs visits the dimensions of the problem in a fixed order, searching one dimension at a time. For $j = 1 \dots d$, MTSIs proceeds as follows. First, the value s_j is modified as $s'_j = s_j - ss$ and the resulting solution s' is evaluated. If f(s') < f(s), then $s_j = s'_j$ and the search continues in dimension j+1; otherwise, $s''_j = s_j + 0.5 \times ss$ and the candidate solution s'' is evaluated. If f(s'') < f(s), then $s_j = s'_j$ and the search continues in dimension j + 1. However, if both s'_j and s''_j do not improve over s_j , then s_j remains unchanged and the same process is applied to dimension j + 1. If no improvement is found in any of the dimensions during one iteration Manuscript submitted to ACM

of MTSIs, the next iteration uses only half the value of the step size, i.e., $ss_{t+1} = ss_t/2$. In our implementation of MTSIs, the maximum number of iterations in one execution of MTSIs is determined by the parameter MTSLS-iterations.

2.3 Automatic design of metaheuristic implementations

Automatic design [17] has been proposed as an alternative to manual design, with the goal of reducing the burden on algorithm designers who have to deal with the problem of creating metaheuristic implementations that meet certain performance requirements. In automatic design [17, 94], generating effective algorithm designs is treated as an optimization problem, focused on discovering high-performing combinations of algorithm components and parameter settings. By using an automatic design approach, algorithm designers do not have to deal themselves with the tasks of composing many different metaheuristic designs, assessing their performance and selecting the best ones, since these tasks are delegated to an automatic algorithm configuration tool (AACT). The AACT can systematically explore the design space of a metaheuristic until it finds one that meets the user's needs or until a maximum computational budget is exhausted.

The AACT used in this paper is irace [64, 65], which implements an *iterated racing* approach. The iterated racing approach [8, 69] is based on the idea of performing sequential statistical testing in order to create a sampling model that can be refined by iteratively "racing" candidate configurations and discarding those that perform poorly. The way in which irace works can be summarized as follows. First, it samples candidate configurations from the parameter space and evaluates these configurations on a set of instances using a racing procedure, where each configuration is tested on one instance at a time. Then, irace eliminates the statistically inferior configurations based on Friedman's non-parametric two-way analysis of variance by ranks. Throughout the configuration process, which proceeds sequentially within a given computational budget, irace adjusts the sampling distribution to favor the best configurations identified so far. This process is repeated iteratively until a computational budget is exhausted and irace returns the configuration that performed best on the training instances.

3 PREVIOUS WORKS ON HYBRIDIZATION AND AUTOMATIC DESIGN

The goal of creating hybrid metaheuristics is to exploit the strengths that different optimization techniques can offer to solve optimization problems [9, 13, 34, 94, 96]. In the following, we discuss the main ideas proposed in hybrids of PSO, CMA–ES and DE, as well as some modular metaheuristic software frameworks that have been proposed to study these metaheuristics and their hybrids in an automatic design context. Note, however, that this review of the literature is by no means exhaustive, as we focus on papers proposing ideas that are particularly amenable to be implemented in **METAFO**R, such as single-objective hybrids and not overly complicated hybrids.

3.1 PSO and DE hybrids

Hendtlass proposed an algorithm called swarm differential evolution algorithm (SDEA) [43]. SDEA works mainly as the standard PSO algorithm, but intermittently applies the DE mutation operator to the particles' current solutions to avoid local minima. Zhang and Xie proposed an algorithm called DEPSO, in which the standard PSO is applied during even iterations of the algorithm, and the DE mutation operator is applied to the particles' personal best during odd iterations [101]. Das *et al.* proposed a hybrid algorithm in which the personal component of the velocity update rule of the standard PSO is modified based on the mutation operator of DE [20]. In [76], Omran *et al.* introduced a modified version of Hendtlass' SDEA that uses a probabilistic approach based on the "barebones" PSO. In their algorithm, with probability p_r , particles update their position using the barebones PSO position update rule and add a vector difference, Manuscript submitted to ACM and with probability $1 - p_r$, they update their position to the personal best of a randomly selected particle. Pant *et al.* introduced a two-phase hybrid version of DE that uses PSO as perturbation mechanism [78]. Pant *et al.*'s algorithm follows the usual DE procedure up to the point where the trial vector is generated; if the trial vector is rejected, the algorithm applies the PSO velocity and position update rules to generate a new solution. Epitropakis *et al.* proposed to evolve the social and cognitive components of a swarm by applying the three usual DE operators (i.e., mutation, recombination and selection) to the personal best positions particles (i.e., vectors \vec{p}^i in Equation 1) [27].

3.2 PSO and CMA-ES hybrids

One of the earliest PSO-ESs hybrids is the "particle swarm guided evolution strategy" proposed by Hsieh et al. [47]. Although this approach is not properly based on CMA-ES, the authors introduced the idea that ESs can be used to focus on exploiting good quality solutions, while PSO can be used to focus on performing effective search space exploration. Müller et al. proposed to run multiple CMA-ES instances in parallel considering each instance as an individual particle in PSO [72]. The proposed algorithm is divided into two phases: a CMA-ES phase, which follows the usual CMA-ES algorithm, and a PSO phase, where the best solutions found by each CMA-ES instance applies the standard PSO velocity and position update rules. The equation to adapt the covariance matrix of CMA-ES was modified to combine the local information gathered by a CMA-ES with the global information of PSO. Müller et al. also added a bias to the mean of the sampling distribution of CMA-ES in the following cases: (i) when the instance has already converged to a local minimum located far from the the global best solution, and (ii) when the instance is different from the one that produced the global best solution and the step-size has fallen below a certain threshold. In [99], Peilan et al. introduced a hybrid, three-phase algorithm that uses multiple populations and two different versions of PSO, the standard PSO and a PSO with time windows (PSOtw). In PSOtw, particles can only access their personal best if it is within a certain time window tw given in number of iterations. The first phase of Peilan et al.'s algorithm consists in applying PSOtw by each population for a number of iterations; in the second phase, the best and second best solutions in each population are selected to create a temporary population P_t ; in the third phase and last, the standard PSO and CMA-ES algorithms are applied one after the other to P_t for a number of function evaluations and the best solutions in P_t are selected for the next iteration.

3.3 CMA-ES and DE hybrids

Kämpf and Robinson proposed to execute CMA–ES and DE in sequential order, with CMA–ES followed by DE [50]. The elite solutions found by CMA–ES are input to DE, but since DE uses a larger population size compared to CMA–ES, the DE population is completed with randomly created solutions. Ghosh *et al.* introduced a hybrid algorithm that incorporates the operators of DE into the structure of CMA–ES [31]. The standard mechanism of CMA–ES is used in each iteration to sample new solutions from a multivariate normal distributions, after which the population is handled as in DE. At each iteration, Ghosh *et al.*' algorithm performs the following steps: (i) update the mean of the sampling distribution; (ii) adapt the covariance matrix; (iii) create a population of mutants using components from the eigen decomposition of the covariance matrix; and (iv) apply the crossover and selection operators of the usual DE algorithm. In [35], Guo and Yang proposed a crossover operator that allows individuals to exchange information between the target vector and the mutant vector using the eigenvector basis instead of the natural basis, thus rotating the coordinate system and making the algorithm rotation invariant. In [42], He and Zhou presented a hybrid algorithm based on a new mutation operator and a simplified step-size control rule. The mutation operator used the information of previously rejected solutions and a Gaussian distribution to sample probabilistically "better" solutions. The standard Manuscript submitted to ACM

covariance matrix update of CMA–ES was modified to include only the rank- μ update, and not the rank-one update. He and Zhou also added a local search that takes place only if there are still at least 10% of the total number of function evaluations available by the time the algorithm has converged. Chen and Liu proposed a hybrid algorithm in which DE is used to break the stagnation state of CMA–ES [18]. The algorithm measures the average fitness improvement of the solutions after each iteration of CMA–ES and, when the average falls below a predefined threshold, DE is executed to regenerate the population. To make sure that the new solutions obtained by DE are redistributed in the search space, only the offspring are selected for survival.

3.4 Modular metaheuristic software frameworks for PSO, CMA-ES and DE

Metaheuristic software frameworks (MSFs) that can be used to automatically generate implementations of PSO, CMA– ES and DE have already been proposed in the literature: PSO-X [15], autoCMAES [22], autoDE [98] and modP-SODE [10]. Both PSO-X, autoCMAES and autoDE are parameterized MSFs that allow users to create many different implementations by simply changing the parameters used to execute the framework. This aspect makes them particularly suitable for an automatic design context, as they can be easily coupled with an AACT tool such as irace. On the other hand, the main drawback of these MSFs is that they only contain components of a specific metaheuristic, PSO, CMA–ES and DE, respectively.

The modular modPSODE framework is, to the best of our knowledge, the only MSF specifically developed for creating PSO and DE hybrids in an automatic design context [10]. Unfortunately, it has two important downsides: (i) a limited number of components of PSO and DE compared to PSO-*X* and autoDE; and (ii) lack of flexibility to combine components at a fine-grained level. The modPSODE framework is based on the idea of simultaneously generating two populations, one using PSO components and the other using DE components, and combining them into a single population that is then reduced to a predefined population size using a selection operator. This type of hybridization is not particularly useful to explore the interaction of PSO components in DE and vice-versa.

4 THE METAFOR SOFTWARE FRAMEWORK

METAFO[®] is composed of three main modules: a PSO module (**PSOmod**), which includes algorithm components of PSO to update solutions by adding a velocity vector; a DE module (**DEmod**), which includes algorithm components of DE to update solutions using differential mutation, recombination and selection; and a CMA–ES module (**CMA-ESmod**), which includes algorithm components of CMA–ES to update solutions by applying random sampling, recombination and covariance matrix adaptation. **METAFO**[®] also includes a local search module (**LSmod**), which allows the execution of **PSOmod**, **DEmod** and **CMA-ESmod** to be interleaved with a local search (MTSIs or CMA–ES) for a number of function evaluations (FEs) and then resume with the main algorithm execution.

PSOmod, **DEmod** and **CMA-ESmod** can be used standalone or in combination with other modules by selecting specific components from them. As an example, with **METAFO** \mathbb{R} it is possible to create a hybrid DE–PSO implementation that combines the differential mutation of DE with the velocity update rule of PSO, and runs CMA–ES as local search for a number of FEs. The way in which **PSOmod**, **DEmod** and **CMA-ESmod** interact with each other is controlled by the algorithm component Execution. Execution operates at a high level in **METAFO** \mathbb{R} and contains the necessary options for creating different types of hybrid implementations (e.g., component-based, multiple phases, etc.). We will now provide a detailed description of the modules that comprise **METAFO** \mathbb{R} . We use a sans-serif font to indicate both the algorithm components implemented in the framework and their available options.

4.1 PSOmod

PSOmod includes all the algorithm components and implementation options as the original PSO-X framework [15].¹ The two top-level algorithm components of **PSOmod** are Population and Topology. Population handles the number of solutions (particles) in the implementation and has three options available: Pop-constant, Pop-incremental and Pop-time-varying. When Pop-incremental or Pop-time-varying are used, the user has to specify the way new solutions added to the population are initialized, which is done via the algorithm component Initialization using option Inithorizontal or Init-random. The Topology algorithm component determines the way particles connect to each other and it can be implemented in seven different ways: Top-fully-connected, Top-hierarchical, Top-Von Neumann, Top-ring, Top-random edge, Top-time-varying and Top-wheel; each option providing different connectivity and information transfer speed to the swarm.

In **PSOmod**, the components involved in the computation of a particle's new velocity vector (\vec{v}_{t+1}^i) are combined using a generalized velocity update rule, which is defined as follows:

$$\vec{v}_{t+1}^i = \omega_1 \vec{v}_t^i + \omega_2 \operatorname{DNPP}(i, t) + \omega_3 \operatorname{Pert}_{\mathsf{rand}}(i, t), \tag{9}$$

where ω_1 , ω_2 and ω_3 are three real parameters in the range [0, 1] used to control the influence of each term in the equation, \vec{v}_t^i is the velocity of the particle *i* at iteration *t*, DNPP is an algorithm component that determines the type of mapping from a particle's current position to the next one, and Pert_{rand} is an optional algorithm component to add a perturbation vector. **PSOmod** provides nine options for computing the value of ω_1 , most commonly known as the inertia weight (IW). Three of these options update their value at regular intervals of the algorithm execution based on predefined schedules (IW-linear decreasing, IW-linear increasing and IW-random), whereas the other six options update their value adaptively, based on information gathered from the option process (IW-self-regulating, IW-adaptive based on velocity, IW-double exponential self-adaptive, IW-rank-based, IW-success-based and IW-convergence-based). The parameters ω_2 and ω_3 , which regulate the influence of DNPP and Pert_{rand}, respectively, can either be set equal to ω_1 or determined using the IW-random and IW-constant options.

The options for implementing the DNPP algorithm component are DNPP-rectangular, DNPP-spherical, DNPPstandard, DNPP-discrete, DNPP-Gaussian and DNPP-Cauchy–Gaussian. The DNPP-rectangular option is the most commonly used in PSO variants, including the *standard* PSO [54], the *fully-informed* PSO [70] and the *locally convergent rotationally invariant* PSO [12], and it was used as the basis for the DNPP-spherical option, proposed for the *standard* PSO–2011 [19, 100]. In the case of DNPP-standard, DNPP-discrete, DNPP-Gaussian and DNPP-Cauchy–Gaussian, they were proposed for the so-called simple dynamic PSO algorithms, whose main characteristic is that they do not use the previous velocity vector or the random diagonal matrices. The algorithm component Vector-Basis, which is not part of the original PSO-*X* framework, works in combination with DNPP. Vector-Basis uses the eigenvector information of the population covariance matrix to rotate the coordinate system, with the goal of making the implementation invariant to rotated search spaces. Vector-Basis can be implemented using the option VB-natural, where no changes are made to the coordinate system, or the option VB-eigenvector, where the vectors involved in the computation of the DNPP are rotated in the direction of the eigenvector basis.

When DNPP is implemented as DNPP-rectangular or DNPP-spherical, the user has to indicate the options for the Random Matrices (Mtx), Model of influence (Mol) and Acceleration Coefficients (AC) components. Mtx refers to the different ways in which the random matrices can be constructed, such as Mtx-random diagonal, Mtx-random linear,

¹For specific details about the implementation of the algorithm components included in the PSO-X framework, we refer the reader to the original paper [15] and supplementary material [14].

Mtx-exponential map, Mtx-Euclidean rotation_{one} (rotation in plane), Mtx-Euclidean rotation_{all} (rotation in all possible planes) and Mtx-Increasing group-based. Model of influence specifies which neighbor solutions influence a particle movement. The available options for this component are Mol-best-of-neighborhood (only the best neighbor), Mol-fully informed (all of its the neighbors and all with same weight) and Mol-ranked fully informed (all of its neighbors, but the higher its quality, the more weight it has). AC manages the computation of the parameters φ_1 and φ_2 (see Equation 1) and offers four options for this purpose: AC-constant, AC-random, AC-time-varying and AC-extrapolated.

PSOmod has five optional algorithm components: $Pert_{info}$, $Pert_{rand}$, Velocity Clamping. Unstuck Velocity and Ig-nore Pbest. Both $Pert_{info}$ and $Pert_{rand}$ apply a perturbation to the components of the generalized velocity update rule (Equation 9) – $Pert_{info}$ does it to the vectors involved in the computation of the selected DNPP option, whereas $Pert_{rand}$ generates a random vector that is added directly to a particle's new velocity. The options available for implementing $Pert_{info}$ are $Pert_{info}$ -Gaussian, $Pert_{info}$ -Lévy and $Pert_{info}$ -uniform, while the options for implementing $Pert_{rand}$ are $Pert_{rand}$ -rectangular and $Pert_{rand}$ -noisy. When $Pert_{info}$ and $Pert_{rand}$ are used, the user has to select the strategy to compute the magnitude of the perturbation (variable pm), which is done via the algorithm component Perturbation Magnitude (PM) using options PM-constant value, PM-Euclidean distance, PM-obj.func. distance and PM-success rate.

The algorithm components Velocity Clamping and Unstuck Velocity limit the size of the velocity vectors of the particles. Velocity Clamping halves the magnitude of the velocity vector when its value exceeds the bounds of the search space, while Unstuck Velocity re-initializes the velocity vector when $||\vec{v}_t^i|| + ||\vec{l}_t^i - \vec{x}_t^i|| \le 10^{-3}$, where $||\cdot||$ denotes the L² norm of a vector. The component Ignore Pbest allows particles to ignore their personal best vectors and to use instead their current positions in the computation of the velocity and position update rules. Despite Ignore Pbest is not a common design choice in most PSO implementations, the motivation to include it in **METAFOR** is the large number of "novel" metaphor-based metaheuristic proposed in recent years (e.g., Grey Wolf Optimizer, Moth-Flame Algorithm and Whale Optimization Algorithm) that seem to be based on PSO [2, 16]. Our goal is that, with **METAFOR**, users can also replicate some of these "novel" metaheuristic and evaluate their performance in a systematic manner.

4.2 CMA-ESmod

CMA-ESmod was developed based on the implementation of CMA-ES publicly available from its creator's website.² **CMA-ESmod** allows to implement the algorithm components proposed in some of the best-known variants of CMA-ES, including the *standard*-CMA-ES *with intermediate recombination* [40], the *separable*-CMA-ES [86] and the *restart*-CMA-ES *with increasing population size* [4]. **CMA-ESmod** is composed of four main algorithm components: CMAESpopulation, which handles the number of solutions in the implementation; CMAES-Mtx, which specifies the way the covariance matrix is adapted; CMAES-restart, which restarts the algorithm based on criteria related to the range of improvement of the solutions found by the population; and CMAES-recombination-weights, which specifies the weighing mechanism used by recombination.

In **CMA-ESmod**, the size of the population is controlled using the CMAES-population algorithm component. The two options available for implementing this component are CMAES-pop-constant, where the size of the population remains the same throughout the algorithm execution, and CMAES-pop-incremental, where it increases according to a multiplication factor. The initial population size (denoted by $\lambda_{t=0}$) and the number of parents selected for recombination (denoted by μ_t) are computed using $\lambda_{t=0} = 4 + \lfloor \text{cmaes}_\text{par}_\text{a} \ln(d) \rfloor$ and $\mu_t = \lambda_t/\text{cmaes}_\text{par}_\text{b}$, where cmaes_par_a

²http://www.cmap.polytechnique.fr/ñikolaus.hansen/cmaes_inmatlab.html#code

Manuscript submitted to ACM

and cmaes_par_b are two real parameters in the range [1, 10] and [1, 5], respectively. To sample the initial population (Equation 3), the initial step size is computed as $\sigma_{t=0} = \text{cmaes}_{\text{par}_c}[lb_j, ub_j]$, where cmaes_par_c is a real parameter in the range (0, 1) and lb_j and ub_j are the lower and upper bounds of dimension *j*. When CMAES-pop-incremental is used, the size of the population is updated according to the following equation:

$$\lambda_{t+1} = \begin{cases} \text{cmaes_par_d} * \lambda_t, & \text{if CMAES-restart} = \text{true} \\ \lambda_t, & \text{otherwise} \end{cases}, \tag{10}$$

where cmaes_par_d is a real parameter in the range [1, 4] that controls the velocity at which the population grows, and CMAES-restart (described below) determines the moment at which the increments take place.

The CMAES-Mtx algorithm component allows to adapt the covariance matrix in three different ways, CMAES-Mtx-covariance, CMAES-Mtx-diagonal and CMAES-Mtx-cov-then-diag. The CMAES-Mtx-covariance option is the one described in Equation 6, where the adaptation of the covariance matrix is done using a combination of the rank-one update and the rank- μ update. CMAES-Mtx-diagonal is a low complexity alternative for CMAES-Mtx intended for separable functions, where the covariances are assumed to be zeros; therefore, instead of the full covariance matrix, CMAES-Mtx-diagonal uses a diagonal matrix similar to matrices U_1 and U_2 in PSO (see Equation 1). The CMAES-Mtx-cov-then-diag option allows to start the implementation using CMAES-Mtx-covariance, and then, after $2 + 100 \times \frac{d}{\sqrt{\lambda}}$ FEs to switch to CMAES-Mtx-diagonal.

When used in the implementation, the algorithm component CMAES-restart performs two actions: first, it reinitializes the mean of the random sampling with a randomly generated solution; second, if CMAES-pop-incremental is used, it increases the population size according to Equation 10. CMAES-restart is a boolean algorithm component that becomes true if either the range of improvement of (i) all function values of the most recent generation, (ii) the best solution found in the last $[10 + round(30d/\lambda)]$ generations, or (iii) the standard deviation of the normal distribution falls below a certain threshold. **CMA-ESmod** keeps the information related to (i), (ii) and (iii) in variables stopTolFun, stopTolFunHist and stopTolX, respectively, and iteratively verifies the conditions that make CMAESrestart = true, namely: stopTolFun $\leq 10^{cmaes}par_e$, stopTolFunHist $\leq 10^{cmaes}par_f$, or stopTolX $\leq 10^{cmaes}par_g$, where cmaes_par_e, cmaes_par_f and cmaes_par_g are real parameters in the range [-20, -6].

The last algorithm component in **CMA-ESmod** is CMAES-recombination-weights. This component is used to specify the weighting scheme used during recombination and it can be implemented using options CMAES-RW-logarithmic, CMAES-RW-linear-decreasing and CMAES-RW-equal. The CMAES-RW-logarithmic option is the one shown in Equation 5, where weights decrease in a logarithmic fashion. Differently, CMAES-RW-linear-decreasing is defined as $w^i = (\lambda - i - 1)/\sum_{k=0}^{\mu-1} (\lambda - k)$ for $i = 1 \dots \mu$, and CMAES-RW-equal is defined as $w^i = 1/\mu$ for all *i*.

4.3 DEmod

DEmod was developed considering some of the most popular variants of DE published in the literature [21, 98]. DE implementations are typically referred to using a mnemonic of the form DE/term_2/term_3/term_4, where term_2 indicates the way in which the base vector is chosen, term_3 indicates the number of vector differences added to the base vector, and term_4 indicates the number of values donated by the mutant vector (see Section 2.1.3 for details). Some popular variants of DE indicated using their mnemonics are DE/rand/1/bin (classic DE), DE/target-to-best/1/bin, and DE/rand/1/exp. The implementations created with **DEmod** can be referred to in a similar way using the following

extended mnemonic:

where DE-Base Vector, DE-vector-differences and DE-Recombination refer to the same concepts as *term_2*, *term_3* and *term_4* in the original mnemonic, DE-Vectors indicates the solution vectors used to compute the vector differences, and Vector-Basis indicates the vector basis used in the implementation. In **DEmod**, the population is handled using the algorithm component Population (already described in Section 4.1) with the exact same options available (i.e., Pop-constant, Pop-incremental and Pop-time-varying).

The algorithm component DE-Base Vector determines the way the base vector (vector \vec{x}^a in Equation 7) is chosen. DE-Base Vector provides five options for its implementation: BV-random, BV-best, BV-target-to-best, BV-directedrandom and BV-directed-best. The first three options are the most commonly used in popular DE variants. In BVrandom the base vector is chosen at random; in BV-best the base vector is the best-so-far solution; and in BV-targetto-best the base vector lies between the target vector and the best-so-far solution. The implementation options BVdirected-random and BV-directed-best seek to incorporate information from the objective function into the creation of the mutant vector. When options BV-directed-random and BV-directed-best are used, the creation of the mutant vector is done as follows:

$$\vec{m}^{i} = \vec{x}^{a} + \frac{\beta}{2} \cdot (\vec{x}^{a} - \vec{x}^{b} - \vec{x}^{c}),$$
(12)

where \vec{x}^a , \vec{x}^b and \vec{x}^c are chosen at random, with $f(\vec{x}^a) \leq \{f(\vec{x}^b), f(\vec{x}^c)\}$. The only difference between BV-directedbest and BV-directed-random is that, in BV-directed-best, \vec{x}^a is the best solution found so far. The numerical parameter $\beta \in (0, 1]$ scales the vector differences added to the base vector and is divided by the number of vector differences when there are more than one, as shown in Equation 12.

The number of vector differences added to a base vector is computed by the algorithm component DE-vectordifferences. Although most implementations of DE only add one or two vector differences, DE-vector-differences allows to add up to a quarter of the population size as vector differences. In practice, DE-vector-differences takes into account the option implemented for DE-Base Vector and assigns to each individual in the population the set of solutions that will be used to create its mutant vector. Also, when options Pop-incremental or Pop-time-varying are used, DE-vector-differences adjusts the number of vector differences according to the current population size.

The DE-Recombination component specifies the type of recombination (RCB) used in the implementation. The options available for implementing DE-Recombination are RCB-binomial and RCB-exponential. The option RCB-binomial, a.k.a. uniform random, is the one shown in Equation 8 in Section 2.1.3, where the number of values donated by the mutant vector follows a binomial distribution. Differently, in the RCB-exponential (or two-point modulo), the number of values donated by the mutant vector follows an exponentially distributed random variable. The fraction of values copied from the mutant vector into the trial vector during recombination is controlled by the parameter p_a (see Equation 8), whose value is a real number in the range [0, 1].

In addition to the typical algorithm components used in DE implementations, **DEmod** includes components DE-Vectors and Vector-Basis. The algorithm component DE-Vectors allows to use different types of solutions when creating a mutant vector. The options available to implement DE-Vectors are V-positions, which uses the current solutions (most DE implementations used this option); V-pbest, where individuals keep track of their the personal best solutions and use them to compute the mutant vector (an idea borrowed from PSO); and V-mixture, which uses a combination of the current and personal best solutions. On the other hand, the algorithm component Vector-Basis allows to rotate

the coordinate system of the vectors involved in DE-Recombination. The two options available for the Vector-Basis component are VB-natural, which uses the natural basis (i.e., no rotation is performed), and VB-eigenvector, which computes the eigenvector basis of the population and uses it to perform the rotation. When VB-eigenvector is used, the mutant and target vectors are rotated in the direction of the eigenvector before applying DE-Recombination, and then, after DE-Recombination takes place, they are rotated back to the natural basis to apply selection.

DEmod has two algorithm components specifically designed to facilitate the creation of component-based PSO and DE hybrids. The first one, DE-Recompute Velocity specifies the type of update performed to the velocity vector (\vec{v}_t^i) when DE, which has precedence over PSO in component-based PSO and DE hybrids, finds a better solution. In this case, the velocity vector of the particle does not correspond anymore to its position, which can negatively impact the application of PSO. To fix this issue, DE-Recompute Velocity recomputes the velocity vector of the particle according to one of the following strategies: RV-goBack (proposed by Boks *et al.* [10]), where \vec{v}_t^i is recomputed as the difference between the new solution found by the application of DE ($\vec{x}_t^{i,\text{DE-new}}$) and the previous current solution (\vec{x}_t^i), that is, $\vec{v}_t^i = \vec{x}_t^{i,\text{DE-new}} - \vec{x}_t^i$; RV-random, where \vec{v}_t^i is regenerated at random; RV-position, where $\vec{v}_t^i = \vec{x}_t^i$; and RV-none, where no update is done to \vec{v}_t^i . The second algorithm component, called PSO-only-on-fail, is the one proposed in the DE-PSO hybrid by Pant *et al.* [78]. As its name suggests, PSO-only-on-fail is used to specify that PSO is applied only when DE failed to produce a new better solution. Since the number of FEs used per iteration by components-based hybrids of DE and PSO is twice the size of the population, PSO-only-on-fail can lower this number by preventing the application of PSO after \vec{x}_t^i has already been improved by DE.

4.4 LSmod

LSmod allows to interleave the execution of **PSOmod**, **DEmod** and **CMA-ESmod** with a subordinate local search. The execution of the local search algorithm is controlled by two parameters, LS-budget and LS-divide. LS-budget, which is a real number in the range (0, 1], indicates what percentage of the total number of FEs is allocated to local search, whereas LS-divide, which is an integer in the range [1, 100], specifies the number of independent runs of the local search in the implementation. For example, setting LS-budget = 0.25 and LS-divide = 10 produces 10 independent runs of the local search, where each run has a maximum budget of $(0.25 \cdot \text{total number of function evaluations})/10$. If the local search algorithm reaches the value of LS-divide without finishing its budget, **LSmod** adds extra runs, one at a time per iteration, until there is no more budget available.

The two local search algorithms that can be implemented using **LSmod** are CMA–ES and MTSIs. Although the implementation of CMA–ES as local search is also done via **CMA-ESmod** with the exact same available options and parameters (see Section 4.2), each CMA–ES instance is treated independently in **METAFO** \mathbb{R} . In other words, in a single **METAFO** \mathbb{R} implementation, it is possible to have two instances of CMA–ES, one as (or part of) the main optimization algorithm, and another as local search, each with its own algorithm components and parameter values. Whatever the type of implementation, **LSmod** uses as input for the local search algorithm the best solution found so far (\vec{x}^{best}), which in the case of CMA–ES is used as mean for the random sampling, and in the case of MTSIs as starting solution.

The implementation of MTSIs works as described in Section 2.2 and has three parameters associated: MTSLS-init-ss, which is the initial step size, MTSLS-iterations, which is an integer in the range [1, 3] that determines the number of iterations per run of MTSIs, and MTSLS-bias, which is a real number in the range [-1, 1] that controls how close a randomly generated solution is to \vec{x}^{best} . In our implementation of MTSIs, solutions that exceed the boundaries of the search space are penalized by adding the sum of the squares of their offsets to the function evaluation. This ensures that the farther a solution is from the search space, the greater the penalty it incurs. At the end of each iteration, MTSIs Manuscript submitted to ACM

tests for convergence using $|f(\vec{s}) - f(\vec{s}')| \le 10^{-20}$, where \vec{s} is the initial solution and \vec{s}' the improved solution. If the convergence test is positive, the value of MTSLS-init-ss is reinitialized to a random number sampled from $\mathcal{U}[0.3, 0.6]$. After completing one iteration, if no improvement was made or if the improvement was smaller than 10^{-20} , MTSls generates a random starting solution for the next iteration as follows: $s_j = \mathcal{U}[lb_j, ub_j] + ((1 - \text{MTSLS-bias}) \cdot \mathcal{U}[0, 1] + \text{MTSLS-bias}) \cdot (x_i^{\text{best}} - \mathcal{U}[lb_i, ub_j])$ for $j = 1 \dots d$.

4.5 The Execution algorithm component

Based on the literature review in Section 3, we developed an algorithm component called Execution that allows to replicate the way in which hybrids of PSO, CMA–ES and DE are created. The three options available to implement Execution are EXE-component-based, EXE-probabilistic and EXE-multiple phases. The EXE-component-based option (available for each module when used standalone and for **PSOmod** and **DEmod** when used together) allows users to compose an algorithm by selecting individual algorithm components from different modules.

Differently, in the EXE-probabilistic option (available only for **PSOmod** and **DEmod**), each module is applied probabilistically based on parameter $pr \in [0, 1]$, so that the probability of updating a solution using the first module is pr and the probability of updating it using the second module is 1 - pr. EXE-probabilistic provides three options to sample random numbers to compare with the value of pr, EXE-PB-uniform, which uses a uniform distribution $\mathcal{U}(0, 1)$, EXE-PB-normal, which uses a normal distribution $\mathcal{N}(0, \text{par_std})$, and EXE-PB-levy, which uses a Lévy distribution $\mathcal{L}(0, \text{par_std}, \gamma_t)$. In both EXE-PB-normal and EXE-PB-levy, the mean of the distribution is 0 and the standard deviation is controlled by the parameter par_std. In the case of EXE-PB-levy, γ_t is a real parameter that controls the sharpness of the distribution and its value is sampled from a discrete uniform distribution $\mathcal{U}\{10, 20\}$, so that the probability of generating a random value in the tail of the distribution varies iteration by iteration—see [85] for details.

EXE-multiple phases (available for all four modules) is similar to EXE-probabilistic, but instead of a probability, the user gives a computational budget *xb* to each module that determines the number of consecutive FEs the module can use. EXE-multiple phases divides the total number of FEs among the different modules based on their assigned budget *xb* and applies each module until *xb* is over, one module after the other, e.g., **PSOmod**, followed by **DEmod**, followed by **CMA-ESmod**.

4.6 Algorithm template used by METAFOR

In **METAFO**[®], the algorithm components that make up a metaheuristic implementation are combined using Algorithm 1. As shown in line 1 of Algorithm 1, after receiving the set of parameters II, the first action performed by **METAFO**[®] is to validate their values and dependence. The procedure VALIDATE() checks that the set of parameters input by the user are within the defined limits and that there are no conflicting or missing options. For example, if the user executes **METAFO**[®] indicating the use of **CMA-ESmod** and **DEmod**, but the parameters needed to create the implementation are incomplete or their values are out range, VALIDATE() stops the execution and prints out the missing, conflicting and/or out-of-range values. If VALIDATE() ends successfully, it creates an object called config that stores the options with which **METAFO**[®] is executed. **METAFO**[®] has implemented different ways to access config.getLS retrieves the set of parameters used by **LSmod**, and config.getDynamic retrieves the set of algorithm components and parameters whose value change over time, such as Top-time-varying, CMAES-pop-incremental, CMAES-Mtx-cov-then-diag, etc.

Algorithm I High-level structure of the algorithm template used by METAFOR	
Require: Set of parameters (II)	
1: config ← VALIDATE(II, PSOmod, DEmod, CMA-ESmod, LSmod)	
2: exec ← SetExecutionMode(config.get(Execution))	
3: pop \leftarrow INITIALIZE(config.get(Population), config.getDynamic)	
4: repeat	
5: for $i \leftarrow 1$ to size(pop) do	
6: $pop^{i} \leftarrow UPDATESOLUTION(pop^{i}, exec)$	
7: end for	
8: best ← GetBestSolution(pop)	
9: if LSmod is enabled then	
10: PerformLocalSearch(best, config.getLS)	
11: end if	
12: apply Re-initialization > optic	mal
13: pop ← UPDATEPOPULATIONPARAMETERS(config.get(Population), config.getDynamic)	
14: $exec \leftarrow UpdateExecutionParameters(exec)$	
15: until termination criterion is met	
16: return best	

In line 2, the procedure SETEXECUTIONMODE() is performed to initialize the variables required by the algorithm component Execution, such as the probability pr and the execution budget xb. Then, in line 3, the procedure INITIAL-IZE() creates the initial population (pop) and initializes the variables and structures needed to handle the population throughout the execution. INITIALIZE() also takes care of the structures and variables required by dynamic algorithm components, such as variable t_schedule which is used to determine when connections are removed from Top-timevarying.

The main optimization process takes place inside the loop that goes from line 4 to line 15. In line 6, the UPDATESO-LUTION() procedure is applied to each individual in the population based on the type of Execution implemented and the modules selected by the user. When exec is set to EXE-component-based, the same set of components is applied to every individual until the termination criterion is met. When exec is set to EXE-probabilistic, the specific set of components applied to an individual alternates probabilistically based on the parameter pr. Finally, when exec is set to EXE-multiple phases, two or three different modules are applied in a pipeline, where each module is assigned its own budget xb, and the execution of a module begins only after the budget of the previous module is exhausted. The UP-DATESOLUTION() procedure also handles the update of the variable associated to each solution (e.g., the personal best solution vectors) and the algorithm components options that have to update solution-wise (e.g., IW-self-regulating, PM-success rate and DE-vector-differences). In line 8, after updating the population, the best solution is kept in the variable best.

In line 9, METAFOR checks whether LSmod is enabled and, if this is the case, the procedure PERFORMLOCALSEARCH() is executed in line 10 using the best solution as input. If the local search algorithm finds an improved solution, PER-FORMLOCALSEARCH() updates best with the new solution. In line 12, the optional component Re-initialization takes place. There are two options for implementing Re-initialization: RI-change and RI-similarity. RI-change re-initializes the population if either of the following conditions is verified: (i) if the standard deviation of the solutions falls below 10^{-3} , or (ii) if the total change in the objective function over the last $(10 \cdot d)/\text{size}(\text{pop})$ iterations is less than 10^{-8} . The RI-similarity option computes the Euclidean distance between a solution and \vec{x}^{best} and re-initializes those solutions whose distance to \vec{x}^{best} is lower than 10⁻³. Finally, in lines 13–14, METAFOR updates the variables and structures related to the population (pop) and the execution (exec). The procedure UPDATEPOPULATIONPARAMETERS() also takes Manuscript submitted to ACM

care of the dynamic algorithm components whose values have to be updated iteration-wise (e.g., Pop-incremental, Top-time-varying and CMAES-Mtx-cov-then-diag).

METAFO[®] has a total of 104 parameters, of which 53 belong to **PSOmod**, 5 to **DEmod**, 9 to **CMA-ESmod**, 15 to **LSmod**, 7 to the algorithm component Execution and 15 are shared by several modules (e.g. Population, Vector-Basis, Re-initialization, etc.). As shown below in Table 3, the actual number of parameters used in our automatically created implementations vary from as few as 10 parameters (e.g., CMAES_{LDOUT}) to 32 parameters (e.g., PSO-CMAES_{250UT}). In **METAFO**[®], optional algorithm components can simply be omitted from the set of execution parameters when they are not going to be used in the implementation.

5 EXPERIMENTAL STUDY

We conducted experiments on a set of 50 continuous functions belonging to the CEC'05 and CEC'14 "Special Session on Single Objective Real-Parameter Optimization" [58, 95] and to the Soft Computing (SOCO'10) "Test Suite on Scalability of Evolutionary Algorithms and other Metaheuristics for Large Scale Continuous Optimization Problems" [44].³ The goal of using a benchmark set of functions composed of various test suites is to include as many as possible of the characteristics that make continuous optimization problems difficult, such as mathematical transformations (e.g., translations and rotations), multiple local optima and non-separable objective functions. As shown in Table 1, our benchmark set is composed of 12 unimodal functions (f_{1-12}), 14 multimodal functions (f_{13-26}), 14 hybrid functions (f_{27-40}), and 10 hybrid composition functions (f_{41-50}). With the exception of f_{41} , none of the hybrid composition functions is separable, and functions f_{42-50} include an additional rotation in the objective function.

5.1 Benchmark functions

In addition to evaluating the performance of the algorithms on the characteristics aforementioned, we are interested in their scalability, especially for problems with more than 100 dimensions. In order to test how well the algorithms scale to large dimensional (LD) problems, we use the functions of the SOCO'10 test suite ($f_{1,5,6,8-11,13,15,17,19,27-34}$) with 200, 500 and 1 000 dimensions. In contrast to the CEC'2005 and CEC'2014 test suites, which are primarily designed to test the performance of the algorithms on highly complex, multimodal functions, the SOCO'10 test suite contains problems whose complexity is mainly due to their large size.

5.2 Experimental setup

Our experimental study involves two phases: a *training phase*, where we use *irace* with different training instances to create and configure a number of algorithms; and a *testing phase*, where we run the algorithms on different sets functions and measure aspects related to their performance. To guarantee that the training set and the testing sets are different enough, we excluded the CEC'14 functions from the training set, and use only the CEC'05 and SOCO'10 test suites to define two different training scenarios. For the first scenario, we created a training set of 88 functions by randomly selecting 75% of the functions in the CEC'05 test suite and 75% of the functions in the SOCO'10 test suite, where the selected CEC'05 functions use $d = \{10, 30, 50\}$ and the selected SOCO'10 functions use $d = \{500, 1000\}$. We refer to this first scenario as 250UT, since "25%" of the total number of instances were left "out" from the training set. For the second scenario, we consider a leave-one-class-out cross-validation approach by creating a training set of 107 functions where all the functions from both test suites are included but only with a low dimensional number. In other

³Due to space limitation, we refer the reader to the provided references for a complete description of the benchmark functions. Manuscript submitted to ACM

f#	Name	Search Range	Suite	f#	Name	Search range	Suite
f_1	Shifted Sphere	[-100,100]	SOCO'10	f_{26}	Shifted Rotated HGBat	[-100,100]	CEC'14
f_2	Shifted Rotated High Conditioned Elliptic	[-100,100]	CEC'14	<i>f</i> 27	Hybrid Function 1 (N = 2)	[-100,100]	SOCO'10
f3 f4 f5 f6 f7 f8 f9 f10 f11	Shifted Rotated Bent Cigar Shifted Rotated Discus Shifted Schwefel 2.2.1 Shifted Schwefel 1.2 Shifted Schwefel 1.2 Shifted Schwefel 2.22 Shifted Extended f_{10} Shifted Bohachevsky Shifted Schaffer	[-100,100] [-100,100] [-65.533,65.536] [-100,100] [-100,100] [-100,100] [-100,100] [-100,100]	CEC'14 CEC'14 SOCO'10 SOCO'10 CEC'05 SOCO'10 SOCO'10 SOCO'10	f28 f29 f30 f31 f32 f33 f34 f35 f36	Hybrid Function 2 (N = 2) Hybrid Function 3 (N = 2) Hybrid Function 4 (N = 2) Hybrid Function 7 (N = 2) Hybrid Function 8 (N = 2) Hybrid Function 10 (N = 2) Hybrid Function 10 (N = 3) Hybrid Function 1 (N = 3)	$ \begin{bmatrix} -100, 100 \\ [-5,5] \\ [-10, 10] \\ [-100, 100] \\ [-100, 100] \\ [-5,5] \\ [-10, 10] \\ [-100, 100] \\ [-100, 100] \end{bmatrix} $	SOCO'10 SOCO'10 SOCO'10 SOCO'10 SOCO'10 SOCO'10 CEC'14 CEC'14
f_{12}	Shchwefel 2.6 Global Optimum on Bounds	[-100,100]	CEC'05	f37	Hybrid Function 3 (N = 4)	[-100,100]	CEC'14
$f_{13} \\ f_{14} \\ f_{15} \\ f_{16} \\ f_{17} \\ f_{18} \\ f_{19}$	Shifted Ackley Shifted Rotated Ackley Shifted Rosenbrock Shifted Rotated Rosenbrock Shifted Griewank Shifted Rotated Griewank Shifted Rastrigin	[-32,32] [-100,100] [-100,100] [-100,100] [-600,600] [-100,100] [-100,100]	SOCO'10 CEC'14 SOCO'10 CEC'14 SOCO'10 CEC'14 SOCO'10	$\begin{array}{c} f_{38} \\ f_{39} \\ f_{40} \\ f_{41} \\ f_{42} \\ f_{43} \\ f_{44} \end{array}$	Hybrid Function 4 (N = 4) Hybrid Function 5 (N = 5) Hybrid Function 6 (N = 5) Hybrid Composition Function Rotated Hybrid Composition Function Rotated Hybrid Composition F.	[-100,100] [-100,100] [-100,100] [-5,5] [-5,5] [-5,5] [-5,5]	CEC'14 CEC'14 CEC'14 CEC'05 CEC'05 CEC'05 CEC'05
f_{20}	Shifted Rotated Rastrigin	[-100,100]	CEC'14	f_{45}	Global Opt.	[-5,5]	CEC'05
$f_{21} \\ f_{22} \\ f_{23} \\ f_{24}$	Shifted Schwefel Shifted Rotated Schwefel Shifted Rotated WeierStrass Shifted Rotated Katsuura	[-100,100] [-100,100] [-100,100] [-100,100]	CEC'14 CEC'14 CEC'05 CEC'14	f46 f47 f48 f49	Rotated H. Comp. F. with the Gbl. Opt. On the Bounds Rotated Hybrid Composition Function Rotated H. Comp. F. with High Condition Num. Matrix Non-Continuous Rotated Hybrid Composition Func- tion	[-5,5] [-5,5] [-5,5] [-5,5]	CEC'05 CEC'05 CEC'05 CEC'05
f_{25}	Shifted Rotated HappyCat	[-100,100]	CEC'14	f_{50}	Rotated Hybrid Composition Function	[-5,5]	CEC'05

Table 1. Benchmark functions

Table 2. Percentage of functions of each class in scenarios 250UT, LDOUT and in the CEC'05, CEC'14 and SOCO'10 test suites.

Scenario/Suite	# of Functions	UNI (%)	MUL (%)	HYB and HCP (%)	ROT (%)	LD (%)	Separable (%)	d Range
250UT	88	24.75	32.75	42.5	36	31	17	$f_{\text{CEC'05}} d = \{10, 30, 50\}, \\ f_{\text{SOCO}} d = \{500, 1000\}$
LDOUT	107	28.5	28.5	43	36	0	16	$f_{\text{CEC'05}} d = \{10, 30\},\$ $f_{\text{SOCO}} d = \{50, 100, 500\}$
CEC'05 CEC'14 SOCO'10	25 per <i>d</i> 22 per <i>d</i> 19 per <i>d</i>	20 14 37	36 59 21	44 27 42	16 63 0	0 0 100	12 9 21	$d = \{2, 10, 30, 50\}$ $d = \{2, 10, 30, 50, 100\}$ $d = \{10, \dots, \infty\}$

words, we left out the large dimensional class and included the 25 functions of the CEC'05 suite with $d = \{10, 30\}$ and the 19 functions of the SOCO'10 suite with $d = \{50, 100, 200\}$. We refer to this second scenario as LDOUT, where LDO stands for "largest dimensions out". In Table 2, we show the percentage of functions of each class included in each training scenario and in the CEC'05, CEC'14 and SOCO'10 test suites.

To design and configure the algorithms in our comparison, we used irace with different computational budgets. In the case of CMA-ES and DE, where the number of parameters is relatively small (less than 15 parameters), we used irace with a budget of 10 000 executions, and in the case of PSO and **METAFO**, which have 59 and 104 parameters, respectively, we used irace with a budget of 30 000 and 50 000 executions. In addition to these algorithms, we used irace with a budget of 30 000 executions to create three hybrid implementations, a PSO-DE hybrid, a DE-CMA-ES hybrid and a PSO-CMA-ES hybrid. Our rationale was that, rather than manually selecting specific hybrids of PSO, CMA-ES and DE for our comparison, it would be far more insightful to evaluate the performance of automatically generated hybrid implementations using the algorithm components and execution modes already implemented in **METAFO**. By combining the seven parameter spaces (**METAFO**, CMA-ES, DE, PSO, PSO-DE hybrid, DE-CMA-ES hybrid and PSO-CMA-ES hybrid) and the two training scenarios (250UT and LDOUT), we produce a total of **14** Manuscript submitted to ACM **algorithms**. In the following sections, we study the performance of the 14 automatically created algorithms and **3 default variants** of PSO, CMA–ES and DE using parameter settings.

In the reminder of this paper, we use the following abbreviations: "MTF " for the implementations created using the entire search space of **METAFO**R, "StdPSO " for the Standard PSO algorithm, "DFT" for implementations using default parameter values, "UNI" for the unimodal functions (f_{1-12}), "MUL" for the multimodal functions (f_{13-26}), "HYB" for the hybrid functions (f_{27-40}), "HCP" for the hybrid composition functions (f_{41-50}), "ROT" for the rotated functions ($f_{2-4,6,14,16,18,20,22-26,42-50}$), "SHU" for the shifted unimodal functions in the SOCO'10 test suite ($f_{1,5,6,8-11}$). We also use " $f_{CEC'05}$ ", " $f_{CEC'14}$ " and " f_{SOCO} " to refer, respectively, to the CEC'05, CEC'14 and SOCO'10 test suite, and we use " $f_{BENCHMARK}$ " to refer to the benchmark set of 50 function shown in Table 1. The algorithm components and parameter settings of the **17 algorithms** included in our comparison are shown in Table 3.

Table 3. Parameter settings of the algorithms included in the comparison.

Algorithm	Settings
MTF _{250UT}	EXE-multiple phases (CMA-ESmod , $xb_1 = 0.8265$, DEmod , $xb_2 = 0.3535$), cmaes_par_a = 4.2552, cmaes_par_b = 2.2402, cmaes_par_c = 0.6247, cmaes_par_d = 3.6447, cmaes_par_e = -18.3449, cmaes_par_f = -19.0782, cmaes_par_g = -14.4971, CMAES-Mtx-diagonal, CMAES-RW-logarithmic, BV-best, DE-vector-differences = 0.1198, RCB-binomial, $p_a = 0.4783$, $\beta = 0.5197$, VB-eigenvector, V-positions, Pop-constant (pop _{ini} = 324).
MTF _{LDOUT}	EXE-multiple phases (CMA-ESmod , $xb_1 = 0.9154$, DEmod , $xb_2 = 0.1573$, LSmod , LS-budget = 0.579 and LS-divide = 3), MTSIs (MTSLS-bias = -0.0549, MTSLS-init-ss = 0.3892, MTSLS-iterations = 1.6483), cmaes_par_a = 7.7473, cmaes_par_b = 1.9539, cmaes_par_c = 0.6037, cmaes_par_d = 2.3443, cmaes_par_e = -19.7597, cmaes_par_f = -17.1491, cmaes_par_g = -12.1016, CMAES-Mtx-cov-then-diag, CMAES-RW-logarithmic, BV-directed-random, DE-vector-differences = 0.0488, RCB-binomial, $p_a = 0.8117$, $\beta = 0.3273$, VB-natural, V-positions, Pop-constant (pop _{<i>ini</i>} = 252), RI-similarity.
CMAES _{DFT}	EXE-component-based (CMA-ESmod), cmaes_par_a = 3, cmaes_par_b = 2, cmaes_par_c = 0.5, cmaes_par_d = 2, cmaes_par_e = -12 , cmaes_par_f = -20 , cmaes_par_g = -12 , CMAES-Mtx-covariance, CMAES-RW-logarithmic.
CMAES _{250UT}	$\label{eq:expectation} EXE-component-based (CMA-ESmod), cmaes_par_a = 9.3314, cmaes_par_b = 3.9293, cmaes_par_c = 0.1237, cmaes_par_d = 3.7189, cmaes_par_e = -14.5256, cmaes_par_f = -15.7226, cmaes_par_g = -16.3546, CMAES-Mtx-diagonal, CMAES-RW-logarithmic.$
CMAES _{LDOUT}	EXE-component-based (CMA-ESmod), cmaes_par_a = 3.6811, cmaes_par_b = 2.8753, cmaes_par_c = 0.1583, cmaes_par_d = 3.8432, cmaes_par_e = -19.9498, cmaes_par_f = -19.7584, cmaes_par_g = -14.4405, CMAES-Mtx-diagonal, CMAES-RW-logarithmic.
$\mathrm{DE}_{\mathrm{DFT}}$	EXE-component-based (DEmod), VB-natural, BV-best, DE-vector-differences = 1, RCB-binomial, $p_a = 0.5$, $\beta = 0.9$, Pop-constant (pop _{ini} = d).
DE _{250UT}	EXE-component-based (DEmod), VB-natural, BV-best, DE-vector-differences = 0.0151, RCB-exponential, $p_a = 0.3566$, $\beta = 0.2614$, Pop-time-varying (pop _{ini} = 39, pop _{min} = 39, pop _{max} = 132, pop _{seh} = 26, Init-random).
DELDOUT	EXE-component-based (DEmod), VB-natural, BV-best, DE-vector-differences = 0.1711, RCB-exponential, $p_a = 0.2105$, $\beta = 0.197$, Pop-incremental (pop _{min} = 46, pop _{max} = 69, pop _{add} = 5, Init-horizontal).
StdPSO _{DFT}	EXE-component-based (PSOmod), DNPP-rectangular, Top-fully-connected, Mol-best-of-neighborhood, Mtx-random diagonal, IW-constant ($\omega_1 = 0.749$), $\omega_2 = 1$, Pop-constant (pop_ <i>ini</i> = 40), $\varphi_1 = 1.496180$, $\varphi_2 = 1.496180$, Velocity Clamping.
PSO- X_{250UT}	EXE-component-based (PSOmod), VB-natural, DNPP-standard, Top-wheel, Mol-ranked fully informed, $\varphi_1 = 0.0967$, $\varphi_2 = 0.9359$, IW-rank-based ($\omega_{1,min} = 0.6134$, $\omega_{1,max} = 0.944$), $\omega_2 = \omega_1$, $\omega_3 = 1$, Pert _{info} -Gaussian (PM-success rate, $pm_1 = 0.211$, $par_sc_1 = 46$, $par_sc_1 = 24$), Pert _{rand} -rectangular (PM-success rate $pm_2 = 0.498$, $par_sc_2 = 45$, $par_sc_2 = 42$), Pop-incremental ($pop_{min} = 5$, $pop_{max} = 20$, $pop_{add} = 2$, Init-horizontal).
$PSO-X_{LDOUT}$	EXE-component-based (PSOmod), VB-natural, DNPP-rectangular, Mol-best-of-neighborhood, Top-time-varying (par_tSch = 8), AC- extrapolated, IW-linear decreasing ($\omega_{1,min} = 0.1156$, $\omega_{1,max} = 0.4517$, $\omega_{sch} = 5$), $\omega_2 = IW$ -random, Pert _{info} -Lévy (PM-success rate, PM ₁ = 0.8248, par_sc ₁ = 2, par_fc ₁ = 32), Mtx-Euclidean rotation _{one} (par_angle = 7), Pop-incremental (pop _{min} = 2, pop _{max} = 34, add(pop) = 8, Init-random), Velocity Clamping, Unstuck Velocity, RI-change.
PSO-DE _{250UT}	EXE-multiple phases (DEmod , $xb_1 = 0.7385$, PSOmod , $xb_2 = 0.9477$, EXE-PB-uniform, par_std= 0.7304) VB-natural, IW-constant ($\omega_1 = 0.0205$), $\omega_2 = IW$ -random, DNPP-Gaussian, Mol-best-of-neighborhood, Top-time-varying (par_tSch = 9), BV-target-to-best, DE-vector-differences = 0.0477, RCB-exponential, $p_a = 0.8266$, $\beta = 0.7779$, V-mixture, Pop-constant (pop _{ini} = 24).
PSO-DE _{LDOUT}	EXE-probabilistic (DEmod , $xb_1 = 0.6355$, PSOmod , $xb_2 = 0.6838$), EXE-PB-levy (par_std= 0.4762), VB-natural, DNPP-Gaussian, Top-Von Neumann, Mol-best-of-neighborhood, IW-success-based ($\omega_{1,min} = 0.1178$, $\omega_{1,max} = 0.6264$), $\omega_2 = 1$, BV-best, DE-vector-differences = 0.0801, RCB-exponential, $p_a = 0.3857$, $\beta = 0.3817$, V-positions, Pop-time-varying (pop _{ini} = 29, pop _{min} = 18, pop _{max} = 253, pop _{sch} = 71, Init-random).

Table 3 (Continued.)

Algorithm	Settings
DE-CMAES _{250UT}	EXE-multiple phases (CMA-ESmod , $xb_1 = 0.8695$, DEmod , $xb_2 = 0.2598$), cmaes_par_a = 7.7115, cmaes_par_b = 1.4923, cmaes_par_c = 0.4212, cmaes_par_d = 3.4793, cmaes_par_e = -18.5851, cmaes_par_f = -18.072, cmaes_par_g = -14.2609, CMAES-Mtx-cov-then-diag, CMAES-RW-logarithmic, BV-random, DE-vector-differences = 0.1683, RCB-exponential, $p_a = 0.9742$, $\beta = 0.339$, V-positions, VB-natural, Pop-constant (pop _{ini} = 66), RI-similarity.
DE-CMAES _{LDOUT}	EXE-multiple phases (CMA-ESmod , $xb_1 = 0.8677$, DEmod , $xb_2 = 0.7543$), cmaes_par_a = 4.2166, cmaes_par_b = 1.7168, cmaes_par_c = 0.1898, cmaes_par_d = 3.4845, cmaes_par_e = -19.8045, cmaes_par_f = -19.7732, cmaes_par_g = -18.6365, CMAES-Mtx-diagonal, CMAES-RW-logarithmic, VB-eigenvector, BV-directed-random, DE-vector-differences = 0.1658, RCB-binomial, $p_a = 0.96$, $\beta = 0.5775$, V-positions, Pop-constant (pop _{<i>ini</i>} = 459).
PSO-CMAES _{250UT}	EXE-multiple phases (CMA-ESmod , $xb_1 = 0.9695$, PSOmod , $xb_2 = 0.2238$), VB-natural, DNPP-Cauchy–Gaussian (random_neighbor, parm_r = 0.4139), Top-Von Neumann, Mol-fully informed, IW-double exponential self-adaptive ($\omega_{1,max} = 0.2985$), $\omega_2 = 0.2569$, Pert _{info} -Lévy (PM-constant value, $pm_1 = 0.2303$), cmaes_par_a = 9.0134, cmaes_par_b = 1.2005, cmaes_par_c = 0.7269, cmaes_par_d = 3.1025, cmaes_par_e = -19.9248, cmaes_par_f = -19.8913, cmaes_par_g = -17.4091, CMAES-Mtx-cov-then-diag, CMAES-RW-logarithmic, Pop-time-varying (pop_{ini} = 181, pop_{min} = 38, pop_{max} = 367, pop_{sch} = 23, Init-horizontal), RI-change.
PSO-CMAES _{ldout}	EXE-multiple phases (CMA-ESmod , $xb_1 = 0.9543$, PSOmod , $xb_2 = 0.2452$), VB-natural, DNPP-Cauchy-Gaussian (random_neighbor, parm_r = 0.7225), Top-time-varying, Mol-fully informed, par_tSch = 10), IW-constant ($\omega_1 = 0.9485$), $\omega_2 = \omega_1$, cmaes_par_a = 8.3477, cmaes_par_b = 2.3073, cmaes_par_c = 0.8218, cmaes_par_d = 2.9854, cmaes_par_e = -19.3423, cmaes_par_f = -19.4916, cmaes_par_g = -19.1069, CMAES-Mtx-cov-then-diag, CMAES-RW-logarithmic, Pop-incremental (pop _{min} = 22, pop _{max} = 489, pop _{add} = 1, Init-horizontal), RI-similarity.

* Conditional parameters and variables are shown inside brackets, preceded by the algorithm components on which they depend.

For the testing phase, we perform 50 independent runs of each of the 17 algorithms on each function and report the median (MED) solution produced by the algorithms, the median solution error (MEDerr) with respect to the best solution found by any of them, the median absolute deviation (MAD) and the wall-clock execution time in seconds. In all cases, the algorithms were stopped after reaching $5\,000 \times d$ objective FEs or a wall-clock time of 600 seconds for $d \le 50, 1\,800$ seconds for $50 < d \le 100, 6\,000$ seconds for $100 < d \le 500$, and 9 000 seconds for $500 < d \le 1\,000$. Both the tuning and the testing of the algorithms were done on dual core AMD Epyc Rome 7452 running at 2.2 GHz with 512 Kb cache size under Rocks Mamba GNU/Linux CentOS 6.3. The version of irace is 3.5. **METAFO** \mathbb{R} is coded in C++, was compiled using gcc 9.4.0 and its source code is publicly available from: https://github.com/clcamachov/METAFOR.

5.3 Analysis of Results

We divide our experiments into three parts. In the first part, we investigate the advantages that hybrid designs have over default and configured single-approach implementations. Our goal is to identify both the approaches that work best for each class of functions and the main algorithm components responsible for their performance. To do this, we compare the result obtained by nine variants of PSO, CMA–ES and DE with the six automatically generated hybrids of these approaches on $f_{\text{BENCHMARK}}$ with d = 50.

In the second part of our experiments, we compare the configured and hybrid implementations of PSO, CMA–ES and DE with the automatically generated MTF implementations. The purpose of this analysis is to know the extent of the benefits of exploring the entire parameter space of **METAFO** \mathbb{R} , which has a larger number of parameters compared to the rest of the algorithms and requires a larger computational budget, versus fine-tuning implementations whose main design choices were manually selected by their algorithm designers. For this analysis, we consider the functions f_{1-40} in $f_{\text{BENCHMARK}}$ with d = 100 and f_{41-50} in $f_{\text{BENCHMARK}}$ with d = 50.

In the third part of our experimental analysis, we study the algorithms based on how well they generalize to other kinds of problems involving different combinations of characteristics from those used to train them. Since our configured and hybrid implementations were trained using different sets of function instances, we expect the implementations to exhibit different degrees of generalization to functions that were not included in their training sets. Therefore, by comparing the performance of the algorithms on different function classes, we intend to highlight the primary advantages and limitations of the two training strategies. For this analysis, we also consider the six configured single-approach implementations, the six PSO, CMA–ES and DE hybrids, and the two MTF implementations on the 22 functions of $f_{CEC'14}$ with $d = \{50, 100\}$ and the 19 functions of f_{SOCO} with $d = \{750, 1250\}$.

To facilitate the calculation of the MED, MEDerr and MAD metrics (reported in the tables below) and to have suitable scales to visualize the results in box-plots (reported in the supplementary material of this article), we limit the maximum (worst) value returned by any of the algorithms to 1.00e + 10. In particular, in functions $f_{3,8,15,28,30,32,36}$, not all algorithms were able to improve their initial solution, which is on the order of 1.00e + 308, resulting in extremely large numbers in some cases. The limit of 1.00e + 10 was set based on the results of the worst performing configured algorithms and it is at least one order of magnitude higher than any of the worst returned values. In the supplementary material of the article, we include both raw data, processed data with a limit value of 1.00e + 10, and the scripts we used for post-processing for replicability purposes.

Tables 4 to 9 show the averages of the MED, MEDerr, MAD and the ranking of the algorithms grouped by function classes. The correspondence between classes of functions and the functions listed in Table 1 is the following: in Tables 4 and 5, UNI (f_{1-12}), MUL (f_{13-26}), HYB (f_{27-40}), HCP (f_{41-50}), ROT ($f_{2-4,6,14,16,18,20,22-26,42-50}$); and in Tables 8 and 9, SHU ($f_{1,5,6,8-11}$), MUL ($f_{13,15,17,19}$) and HYB (f_{27-34}). In the case of Tables 6 and 7, the functions listed in the tables are those defined for $f_{CEC'14}$ [58] (listed only in the supplementary material of the article) and are grouped as follows: UNI (f_{1-3}), MUL (f_{4-16}), HYB (f_{17-22}), ROT ($f_{1-7,9-16}$). The grouping ALL corresponds to all functions listed in the table, except for Table 5, where ALL corresponds to functions f_{1-40} with d = 100.

The limits for the scalability of the functions vary across test suites: for those belonging to $f_{\text{CEC'05}}$, the limit is d = 50, for those belonging to $f_{\text{CEC'14}}$, the limit is d = 100, and for those belonging to f_{SOCO} , the limit is arbitrarily large. In the row "Wilcoxon test", we use the symbol \approx to indicate those cases in which the Wilcoxon test with confidence at 0.95 using Bonferroni's correction did not return a p-value lower than $\alpha = 0.05$, and the symbol + to indicate those cases in which the difference was significant (i.e., $p < \alpha$). The statistical tests were conducted to the complete data sets of MED, MEDerr and MAD values. Finally, in the row "Wins", we show the number of times each algorithm found the best solution. Even though we include the number of "wins" for competitive comparison, our analysis primarily relies on more robust performance metrics, such as rankings and statistical tests.

5.3.1 To hybridize, or not to hybridize — which approach works best? One of the main questions we want to explore in this work is how hybrid algorithms compare to single-approach implementations. To answer this question, we compare the results obtained by the configured and default variants of PSO, CMA–ES and DE with that of their automatically generated PSO–DE hybrid, DE–CMA–ES hybrid and PSO–CMA–ES hybrid on $f_{\text{BENCHMARK}}$ with d = 50 (Table 4). We focus on the functions with d = 50 because this is the largest dimension available for all 50 functions in $f_{\text{BENCHMARK}}$.

Table 4. Average median (Av.MED), average median error (Av.MEDerr) and average median absolute deviation (Av.MAD) obtained by the algorithms on functions f_{1-50} with d = 50.

	f#	CMAES (DFT)	CMAES (250UT)	CMAES (LDOUT)	DE (DFT)	DE (250UT)	DE (LDOUT)	StdPSO (DFT)	PSO-X (250UT)	PSO-X (LDOUT)	PSO- DE (250UT)	PSO- DE (LDOUT)	DE- CMAES (250UT)	DE- CMAES (LDOUT)	PSO- CMAES (250UT)	PSO- CMAES (LDOUT)
	Wins (MED)	13	7	6	0	11	10	0	2	3	11	18	6	8	12	9
INI	Av.MED	0.00e+00	2.26e+00	9.08e+00	1.83e+09	2.91e+06	3.13e+06	8.44e+08	1.06e+05	2.10e+05	1.71e+06	2.18e+06	1.72e+01	5.60e+02	1.42e+02	0.00e+00
	Av.Ranking	7.75	5.58	3.83	14.92	9.08	8.75	13.33	10.33	10.42	6.75	8.58	6.83	5.33	6.42	4.67
MUL	Av.MED	3.15e+03	3.19e+03	3.13e+03	6.67e+08	6.08e+03	5.86e+03	2.63e+08	4.03e+03	3.69e+03	3.29e+03	3.36e+03	3.05e+03	3.12e+03	3.06e+03	3.02e+03
	Av.Ranking	7.31	7.58	5.96	14.92	9.23	8.08	13.00	11.92	10.15	6.81	6.12	6.23	6.35	6.12	5.77
HYB	Av.MED	8.31e+02	2.40e+03	8.11e+02	6.19e+08	1.43e+06	6.64e+05	1.09e+08	1.54e+04	1.55e+04	2.77e+04	2.49e+04	8.30e+02	8.11e+02	8.05e+02	8.30e+02
	Av.Ranking	4.30	4.60	5.00	10.18	7.53	7.90	11.03	10.72	9.47	8.40	8.65	8.10	9.15	9.07	9.40
HCP	Av.MED	5.09e+02	5.57e+02	5.62e+02	1.07e+03	6.24e+02	6.46e+02	8.54e+02	7.75e+02	6.86e+02	6.62e+02	5.85e+02	4.62e+02	4.71e+02	4.63e+02	5.50e+02
	Av.Ranking	1.78	2.66	3.78	5.88	6.06	7.12	8.44	8.92	9.14	9.82	10.60	10.62	11.76	12.36	13.12
ROT	Av.MED	1.34e+03	1.39e+03	1.38e+03	5.44e+08	1.58e+06	1.71e+06	4.60e+08	5.87e+04	1.16e+05	9.34e+05	1.19e+06	1.29e+03	1.33e+03	1.30e+03	1.32e+03
	Av.Ranking	5.55	6.05	5.64	14.27	10.82	11.32	13.41	11.09	9.41	8.82	9.55	5.59	5.59	5.36	5.27
ALL	Av.MED	1.30e+03	1.80e+03	1.31e+03	8.25e+08	1.13e+06	9.52e+05	3.14e+08	3.15e+04	5.63e+04	4.20e+05	5.32e+05	1.27e+03	1.42e+03	1.30e+03	1.28e+03
	Av.Ranking	6.84	6.48	5.70	14.62	9.52	9.04	13.36	11.70	10.00	7.18	7.42	6.08	6.16	6.00	5.48
١	Wilcoxon test	~	*	*	+	+	*	+	+	+	+	*	*	~	*	
	Wins (MEDerr)	13	7	6	0	11	10	0	2	3	11	18	6	8	12	9
INI	Av.MEDerr	0.00e+00	2.26e+00	9.08e+00	1.83e+09	2.91e+06	3.13e+06	8.44e+08	1.06e+05	2.10e+05	1.71e+06	2.18e+06	1.72e+01	5.60e+02	1.42e+02	0.00e+00
	Av.Ranking	7.75	5.58	3.83	14.92	9.08	8.75	13.33	10.33	10.42	6.75	8.58	6.83	5.33	6.42	4.67
MUL	Av.MEDerr	2.17e+02	2.59e+02	1.99e+02	6.67e+08	3.15e+03	2.93e+03	2.63e+08	1.10e+03	7.59e+02	3.60e+02	4.31e+02	1.18e+02	1.92e+02	1.31e+02	9.13e+01
	Av.Ranking	7.31	7.58	5.96	14.92	9.23	8.08	13.00	11.92	10.15	6.81	6.12	6.23	6.35	6.12	5.77
HYB	Av.MEDerr	5.66e+01	1.63e+03	3.72e+01	6.19e+08	1.43e+06	6.63e+05	1.09e+08	1.46e+04	1.48e+04	2.69e+04	2.41e+04	5.61e+01	3.68e+01	3.10e+01	5.53e+01
	Av.Ranking	4.30	4.60	5.00	10.18	7.53	7.90	11.03	10.72	9.47	8.40	8.65	8.10	9.15	9.07	9.40
HCP	Av.MEDerr	8.61e+01	1.34e+02	1.39e+02	6.50e+02	2.01e+02	2.24e+02	4.31e+02	3.53e+02	2.63e+02	2.39e+02	1.62e+02	3.88e+01	4.79e+01	4.03e+01	1.28e+02
	Av.Ranking	1.78	2.66	3.78	5.88	6.06	7.12	8.44	8.92	9.14	9.82	10.60	10.62	11.76	12.36	13.12
ROT	Av.MEDerr	1.11e+02	1.60e+02	1.47e+02	5.44e+08	1.58e+06	1.71e+06	4.60e+08	5.75e+04	1.14e+05	9.32e+05	1.19e+06	6.49e+01	9.70e+01	7.47e+01	9.56e+01
	Av.Ranking	5.55	6.05	5.64	14.27	10.82	11.32	13.41	11.09	9.41	8.82	9.55	5.59	5.59	5.36	5.27
ALL	Av.MEDerr	1.01e+02	5.97e+02	1.04e+02	8.25e+08	1.13e+06	9.51e+05	3.14e+08	3.03e+04	5.51e+04	4.18e+05	5.31e+05	6.49e+01	2.14e+02	9.18e+01	7.20e+01
	Av.Ranking	6.84	6.48	5.70	14.62	9.52	9.04	13.36	11.70	10.00	7.18	7.42	6.08	6.16	6.00	5.48
١	Wilcoxon test	≈	*	*	+	+	~	+	+	+	+	≈	~	≈	*	
	Wins (MAD)	5	7	7	3	9	9	1	2	1	9	16	6	10	10	12
INI	Av.MAD	0.00e+00	1.98e+00	6.80e+02	2.97e+07	2.59e+06	9.11e+05	3.97e+06	1.92e+04	1.77e+04	3.64e+05	2.26e+05	1.72e+01	1.87e+02	1.42e+02	0.00e+00
	Av.Ranking	7.67	7.25	5.42	12.58	9.17	8.92	12.92	10.50	11.08	7.00	8.33	6.58	5.08	5.67	4.92
MUL	Av.MAD	4.01e+01	4.19e+01	4.11e+01	7.70e+02	2.35e+02	2.01e+02	1.25e+08	5.52e+01	5.86e+01	3.14e+01	3.68e+01	3.38e+01	4.96e+01	2.60e+01	4.14e+01
	Av.Ranking	8.15	7.04	6.85	12.81	8.88	7.92	12.96	10.69	9.88	7.81	6.27	5.92	6.96	5.19	5.73
HYB	Av.MAD	1.43e+01	1.82e+02	4.09e+01	2.34e+08	1.33e+06	2.96e+05	1.29e+07	5.51e+03	3.04e+03	2.59e+03	4.06e+03	2.24e+01	1.59e+01	3.73e+00	2.31e+01
	Av.Ranking	5.38	4.75	5.72	9.15	7.03	6.80	10.93	10.28	9.45	9.10	8.07	7.85	9.12	8.80	9.12
HCP	Av.MAD	8.05e+01	3.92e+01	7.50e+01	5.58e+01	2.02e+01	3.08e+01	9.60e+01	8.14e+01	7.07e+01	1.18e+01	2.48e+01	3.13e+00	7.80e+00	2.05e+01	4.71e+01
	Av.Ranking	2.28	2.96	3.92	5.36	5.78	6.52	8.30	8.94	9.06	9.90	10.06	10.62	11.82	12.36	13.08
ROT	Av.MAD	5.31e+01	3.16e+01	5.01e+01	1.62e+07	1.41e+06	4.97e+05	2.16e+06	1.03e+04	9.55e+03	1.98e+05	1.23e+05	1.86e+01	2.13e+01	1.71e+01	4.00e+01
	Av.Ranking	7.18	6.59	6.55	11.55	10.23	9.59	12.55	10.82	9.27	9.45	7.55	5.91	6.32	5.45	4.86
ALL	Av.MAD	3.40e+01	7.62e+01	2.04e+02	7.74e+07	1.02e+06	3.08e+05	4.22e+07	6.28e+03	5.19e+03	8.81e+04	5.54e+04	2.17e+01	6.61e+01	4.76e+01	2.97e+01
	Av.Ranking	7.98	6.96	6.72	12.44	9.06	8.26	13.10	11.00	10.14	7.88	6.76	5.80	6.40	5.50	5.32
١	Wilcoxon test	≈	≈	\approx	+	+	≈	+	+	+	≈	\approx	\approx	≈	\approx	

The first thing to note in Table 4 is that, while two of the three hybrids (namely DE–CMA–ES hybrid and PSO–CMA–ES hybrid) ranked better that most single-approach implementations across all functions, in the case of the Manuscript submitted to ACM

three variants of CMA–ES and DE_{LDOUT} , the differences in performance were not statistically significant. Based on the MED and MEDerr metrics, the algorithm with the highest ranking across all functions is PSO–CMAES_{LDOUT}, the second-best is CMAES_{LDOUT}, and the third-best is PSO–CMAES_{250UT}. However, when we split the result by classes of functions, we observe that PSO–CMAES_{LDOUT} ranks either first or second in the UNI, MUL and ROT functions, but it is among the worst ranked in the HYB and HCP functions, where it was outperformed by the two PSO–DE hybrids, the two DE–CMA–ES hybrids and the three CMA–ES variants.

In both the HYB and HCP functions, the best ranked algorithm was $CMAES_{DFT}$. Based on the Av.MEDerr obtained by PSO-CMAES_{LDOUT}, which is similar to that of $CMAES_{DFT}$ in the HYB functions and one order of magnitude higher in the HCP functions, PSO-CMAES_{LDOUT} seems to be able to get close to the best solution, but fails to converge to it. The lack of convergence of PSO-CMAES_{LDOUT} to the best solution is caused by the use of algorithm components heavily biased toward exploration, such as random_neighbor, a large value of $\omega_1 = 0.9485$ and RI-similarity (see Table 3). In particular, RI-similarity, which re-initializes solutions whose Euclidean distance to \vec{x}^{best} is lower than 10^{-3} , seems counterproductive at latest stages of the optimization process. In the case of PSO-CMAES_{250UT}, the implementation of PSO also uses components with a strong exploration bias (e.g., Pert_{info}-Lévy and RI-change), which hinder the ability of the algorithm to converge to the global optimum.

An interesting finding is that all three CMA–ES variants performed as well as any of the automatically generated hybrids, including the implementation of CMA–ES using default parameter settings. Although both CMAES_{250UT} and CMAES_{LDOUT} produce better MED solutions and have smaller MEDerrs than CMAES_{DFT} across all functions, CMAES_{DFT} ranks first in both metrics in the HYB and HCP functions. There are two main reasons that explain these results. The first one is that our implementation of CMAES_{DFT} is not the basic (μ , λ)-CMA–ES, but the restart-CMA–ES with increasing population size, most commonly known as IPOP-CMA–ES [4]. In the original IPOP-CMA–ES, the parameter values were determined based on factors such as the dimensionality of the problem (e.g., $\lambda_{t=0} = 4 + \lfloor 3 \ln(d) \rfloor$) and detailed empirical analyses conducted on a limited set of simple test functions (e.g., stopToIFun = 10⁻¹²). Our method for creating and configuring CMAES_{250UT} and CMAES_{LDOUT} builds upon the parameterized formulation of IPOP-CMA–ES introduced by Liao *et al.* [60]. It involves employing irace to identify combinations of algorithm components and parameter settings that achieve the best generalization across the training instances. This explains why the automatically generated CMAES_{250UT} and CMAES_{LDOUT} produce on average better MED and MEDerrs values than CMAES_{DFT}.

However, the main reason why CMAES_{DFT} performs better than any of the compared algorithms on the HYB and HCP functions is that, unlike CMAES_{250UT} and CMAES_{LDOUT}, which use the less computationally expensive CMAES-Mtx-diagonal component, CMAES_{DFT} uses the more computationally expensive (but also more accurate) CMAES-Mtx-covariance. As discussed in [86], the algorithm component CMAES-Mtx-diagonal provides a similar performance to CMAES-Mtx-covariance on separable functions; however, on non-separable functions, it can negatively impact the quality of the solutions found by the algorithm, especially for functions with highly complicated landscapes, such as HYB and HCP functions. Although it is not completely clear why none of the automatically generated hybrids or configured implementations make use of CMAES-Mtx-covariance in their design, we believe this is due to the constraint we put on the execution time of the algorithms. By constraining the execution of the algorithms using wall-clock time, the more computationally intensive implementations generated by irace were less likely to complete their execution within the available function evaluations (FEs). This approach inherently favored the use of less computationally demanding components, such as CMAES-Mtx-diagonal instead CMAES-Mtx-cov-then-diag, in the algorithms designs.

Several notable algorithmic differences exist among CMAES_{DFT}, CMAES_{250UT} and CMAES_{LDOUT}, which merit detailed discussion. Two minor differences are the initial population size ($\lambda_{t=0}$), which is approx. 2.5 times larger in Manuscript submitted to ACM CMAES_{250UT} than in CMAES_{DFT} and CMAES_{LDOUT}, and the number of parents selected for recombination, which is half of the population size in CMAES_{DFT} and about a quarter of the population size in CMAES_{250UT} and CMAES_{LDOUT}. CMAES_{DFT} uses an initial step size ($\sigma_{t=0} = 0.5$) that is almost four times larger than the one used in CMAES_{250UT} and CMAES_{LDOUT} ($\sigma_{t=0} \approx 0.14$), resulting in a more diverse initial population in CMAES_{DFT} compared to CMAES_{250UT} and CMAES_{LDOUT}. Another difference is that both CMAES_{250UT} and CMAES_{LDOUT} have higher thresholds for triggering a restart than CMAES_{DFT}. However, after restarting, the size of their populations increases by a factor of ≈ 4 , whereas in CMAES_{DFT}, it grows by a factor of 2.

Among the six hybrid implementations, the combination that produced the best overall results was PSO and CMA– ES, followed by the combination of DE and CMA–ES, and finally, the combination of PSO and DE. Both the type of hybridization (i.e., the option used for the algorithm component Execution) and the order in which the modules are applied in the implementations (see Table 3 for details) were selected by irace. In the case of PSO–DE_{250UT}, the algorithm includes a DE phase (allotted 46% of the FEs) followed by a PSO phase (allotted 56% of the FEs), and in the case of PSO–DE_{LDOUT}, the algorithm iteratively alternates between DE and PSO with a 50-50% chance. In the case of PSO–CMAES_{250UT} and PSO–CMAES_{LDOUT}, which use the algorithm component EXE-multiple phases, applying CMA– ES first and DE second turned out to be a better strategy than applying DE first and CMA–ES second. This was also the case for DE–CMAES_{250UT} and DE–CMAES_{LDOUT}, where CMA–ES is applied before DE. As discussed in Section 3, although applying CMA–ES before PSO or DE is not unusual in CMA–ES hybrids, it seems a little counterintuitive to us because DE and PSO are often regarded as techniques with enhanced exploration capabilities than exploitation.

The algorithms ranked best according to the MAD metric are the two PSO-CMA-ES hybrids, followed by the two DE-CMA-ES hybrids, followed by CMAES_{LDOUT}. As opposed to the MED and MEDerr, which provide information about the quality of the solutions, the MAD measures the variability of the results obtained by the algorithms across several independent runs. In other words, the MAD is a measure of the robustness of the algorithms. According to this metric, the overall performance of the CMA-ES implementations was less competitive. Specifically, CMAES_{DFT} was outperformed by all six hybrid algorithms, while both CMAES_{250UT} and CMAES_{LDOUT} demonstrated performance comparable to that of PSO-DE_{LDOUT}. Nevertheless, the ranking of the algorithms per classes of function according to the MAD metric are consistent with the MED and MEDerr rankings per function classes, that is, PSO-CMAES_{LDOUT} ranked first in the UNI, ROT and ALL functions, second in the MUL functions and among the last ones in the HYB and HCP functions, whereas CMAES_{DFT} ranked second and first on the HYB and HCP functions, respectively.

The primary conclusion from this first part of our study is that, although single-approach algorithms such as CMA– ES can achieve excellent results across a diverse set of problems—particularly with complex objective functions—hybrid implementations incorporating CMA–ES are more robust and yield superior overall results compared to using CMA– ES alone. Allocating between 55% and 75% of the computational budget to CMA–ES and the rest to either a PSO or DE seems to be a good strategy for hybridization. Another conclusion of our study is that single-approach implementations of PSO and DE are less performing than their hybrid counterparts, in particular those that use default parameter values, which ranked consistently among the last places. Note, however, that, in the case of DE_{LDOUT} (similarly to CMA–ES), we did not find any significant differences in its performance compared to the best algorithm (PSO–CMAES_{LDOUT}) across the entire set of functions, and DE_{LDOUT} showed to be as competitive as any of the hybrid implementations on the MUL, HYB and HCP functions. In Section 5.3.3, we study the algorithmic design of DE_{LDOUT} in more detail and create a link between its performance on HYB and HCP functions and on functions with large dimensionality. Finally, although it can only be observed in Tables 4 and 5 in the supplementary material of the article, we found an inverse relationship between the number of dimensions in the functions and the performance of CMAES_{DFT}. According to the MED and Manuscript submitted to ACM MEDerr metrics, on average across all function classes, CMAES_{DFT} ranked behind the other two CMA–ES variants and all hybrids in $f_{\text{BENCHMARK}}$ with d = 100, and second to last in f_{SOCO} with d = 200.

5.3.2 Exploring new hybrid designs versus exploiting implementations with a fixed design — what is the trade-off? To understand how exploring the entire search space of **METAFO** \mathbb{R} compares to fine-tuning implementations with predefined design choices, we create two implementations, MTF_{250UT} and MTF_{LDOUT}, considering the 104 parameters of the framework. In this section, we report the results obtained by the two MTF implementations, the six configured CMA-ES, DE and PSO implementations, and the six PSO-DE hybrid, DE-CMA-ES hybrid and PSO-CMA-ES hybrid on functions f_{1-40} with d = 100 and f_{41-50} with d = 50. We excluded the default variants from the compared algorithms in this section to focus our analysis on comparing the performance of automatically created algorithms using different design spaces; however, in the supplementary material, we report the complete set of results obtained by the 17 algorithms on $f_{\text{BENCHMARK}}$ with $d = \{50, 100, 200, 500, 1000\}$.

Table 5. Average median (Av.MED), average median error (Av.MEDerr) and average median absolute deviation (Av.MAD) obtained by the algorithms on functions f_{1-40} with $\mathbf{d} = 100$ and f_{41-50} (HCP) with $\mathbf{d} = 50$.

	f#	MTF (250UT)	MTF (LDOUT)	CMAES (250UT)	CMAES (LDOUT)	DE (250UT)	DE (LDOUT)	PSO-X (250UT)	PSO-X (LDOUT)	PSO- DE (250UT)	PSO- DE (LDOUT)	DE- CMAES (250UT)	DE- CMAES (LDOUT)	PSO- CMAES (250UT)	PSO- CMAES (LDOUT)
	Wins (MED)	4	11	4	9	8	7	0	1	7	12	3	7	9	5
INN	Av.MED	4.44e+03	2.37e+04	1.02e+04	3.45e+03	3.52e+07	2.49e+07	3.28e+05	7.80e+05	1.22e+07	1.16e+07	3.28e+03	3.68e+03	1.75e+0 3	2.42e+03
	Av.Ranking	6.92	6.25	7.42	4.50	9.25	9.25	10.92	11.58	9.00	8.75	7.42	5.17	6.42	5.00
MUL	Av.MED	6.30e+03	6.13e+03	6.58e+03	6.55e+03	1.11e+04	1.25e+04	9.84e+03	7.55e+03	7.49e+03	7.95e+03	6.19e+03	6.24e+03	6.23e+03	6.21e+03
	Av.Ranking	7.62	5.15	8.65	6.54	9.65	7.96	12.23	10.81	7.81	6.65	6.85	6.69	6.69	5.92
HYB	Av.MED	5.07e+03	1.31e+04	8.22e+03	4.34e+03	1.18e+07	6.15e+06	2.63e+04	3.32e+04	6.22e+04	7.20e+04	4.77e+03	3.75e+03	3.44e+0 3	4.48e+03
	Av.Ranking	3.52	2.95	4.97	5.25	6.32	6.42	9.07	9.07	8.75	8.60	9.53	10.07	10.55	11.12
HCP	Av.MED	5.54e+02	4.62e+02	5.57e+02	5.62e+02	6.24e+02	6.46e+02	7.75e+02	6.86e+02	6.62e+02	5.85e+02	4.62e+0 2	4.71e+02	4.63e+02	5.50e+02
	Av.Ranking	2.40	2.56	3.56	4.72	6.18	7.24	8.24	8.50	9.24	9.92	9.90	11.14	11.70	12.42
ROT	Av.MED	5.73e+03	2.34e+04	1.32e+04	4.46e+03	3.25e+07	2.29e+07	2.96e+05	7.19e+05	1.12e+07	1.07e+07	5.48e+03	4.14e+03	4.11e+0 3	5.01e+03
	Av.Ranking	6.08	5.92	6.92	4.46	12.00	11.62	10.08	9.77	9.31	10.31	6.00	4.92	5.62	4.77
ALL	Av.MED	5.60e+03	1.43e+04	8.60e+03	5.12e+03	1.50e+07	9.76e+06	1.11e+05	2.49e+05	3.68e+06	3.51e+06	5.09e+03	4.85e+03	4.15e+0 3	4.74e+03
	Av.Ranking	7.40	5.53	8.03	5.95	9.68	8.55	11.90	11.07	8.22	7.47	6.82	6.12	6.38	5.58
١	Wilcoxon test	≈		~	*	+	+	+	+	+	+	*	×	*	≈
	Wins (MEDerr)	4	11	4	9	8	7	0	1	7	12	3	7	9	5
INN	Av.MEDerr	4.40e+03	2.37e+04	1.01e+04	3.41e+03	3.52e+07	2.49e+07	3.28e+05	7.80e+05	1.22e+07	1.16e+07	3.23e+03	3.64e+03	1.70e+0 3	2.38e+03
	Av.Ranking	6.92	6.25	7.42	4.50	9.25	9.25	10.92	11.58	9.00	8.75	7.42	5.17	6.42	5.00
MUL	Av.MEDerr	4.15e+02	2.41e+02	6.88e+02	6.59e+02	5.24e+03	6.57e+03	3.96e+03	1.66e+03	1.60e+03	2.06e+03	3.00e+02	3.55e+02	3.46e+02	3.21e+02
	Av.Ranking	7.62	5.15	8.65	6.54	9.65	7.96	12.23	10.81	7.81	6.65	6.85	6.69	6.69	5.92
HYB	Av.MEDerr	3.06e+03	1.11e+04	6.21e+03	2.33e+03	1.18e+07	6.15e+06	2.43e+04	3.12e+04	6.02e+04	7.00e+04	2.76e+03	1.74e+03	1.43e+0 3	2.47e+03
	Av.Ranking	3.52	2.95	4.97	5.25	6.32	6.42	9.07	9.07	8.75	8.60	9.53	10.07	10.55	11.12
HCP	Av.MEDerr	1.37e+02	4.61e+01	1.41e+02	1.46e+02	2.08e+02	2.30e+02	3.59e+02	2.69e+02	2.45e+02	1.68e+02	4.52e+0 1	5.43e+01	4.67e+01	1.34e+02
	Av.Ranking	2.40	2.56	3.56	4.72	6.18	7.24	8.24	8.50	9.24	9.92	9.90	11.14	11.70	12.42
ROT	Av.MEDerr	2.23e+03	1.99e+04	9.67e+03	9.56e+02	3.25e+07	2.29e+07	2.92e+05	7.16e+05	1.12e+07	1.07e+07	1.98e+03	6.33e+02	6.04e+0 2	1.51e+03
	Av.Ranking	6.08	5.92	6.92	4.46	12.00	11.62	10.08	9.77	9.31	10.31	6.00	4.92	5.62	4.77
ALL	Av.MEDerr	2.62e+03	1.13e+04	5.61e+03	2.14e+03	1.50e+07	9.76e+06	1.08e+05	2.46e+05	3.67e+06	3.51e+06	2.12e+03	1.88e+03	1.18e+0 3	1.76e+03
	Av.Ranking	7.40	5.53	8.03	5.95	9.68	8.55	11.90	11.07	8.22	7.47	6.82	6.12	6.38	5.58
١	Wilcoxon test	≈		~	~	+	+	+	+	+	+	~	~	~	≈
_	Wins (MAD)	3	11	1	6	9	6	0	1	9	10	2	3	6	6
Z	Av.MAD	4.86e+02	22.66e+03	4.90e+03	5.34e+02	1.69e+07	2.25e+06	1.79e+04	3.38e+04	3.44e+06	3.17e+05	1.60e+03	5.45e+02	1.54e+03	2.00e+03

Wilcoxon test

 \approx

≈

 \approx

+

+

	f#	MTF (250UT)	MTF (LDOUT)	CMAES (250UT)	CMAES (LDOUT)	DE (250UT)	DE (LDOUT)	PSO-X (250UT)	PSO-X (LDOUT)	PSO- DE (250UT)	PSO- DE (LDOUT)	DE- CMAES (250UT)	DE- CMAES (LDOUT)	PSO- CMAES (250UT)	PSO- CMAES (LDOUT)
	Av.Ranking	6.42	6.42	7.58	4.67	8.92	8.50	11.42	11.58	8.67	8.58	7.00	5.42	5.92	6.33
MUL	Av.MAD	1.66e+02	3.95e+01	1.02e+02	2.33e+02	4.13e+02	3.58e+02	5.51e+02	1.36e+02	1.55e+02	1.45e+02	5.33e+01	2.48e+02	3.77e+01	6.12e+01
	Av.Ranking	6.77	4.62	7.27	7.81	8.35	8.88	11.92	10.54	8.12	7.58	5.42	7.54	5.92	6.23
HYB	Av.MAD	1.49e+03	1.33e+03	1.27e+03	2.25e+03	9.74e+06	1.62e+06	2.94e+03	2.91e+03	5.87e+03	1.71e+04	1.13e+03	1.04e+03	2.43e+02	1.47e+03
	Av.Ranking	3.28	2.70	4.50	5.25	6.12	6.88	8.85	8.50	8.85	9.20	8.88	10.45	10.68	11.22
HCP	Av.MAD	1.28e+02	1.95e+00	3.92e+01	7.50e+01	2.02e+01	3.08e+01	8.14e+01	7.07e+01	1.18e+01	2.48e+01	3.13e+00	7.80e+00	2.05e+01	4.71e+01
	Av.Ranking	2.54	2.42	3.84	4.76	5.88	6.58	8.10	8.34	9.20	9.36	9.98	11.16	11.66	12.36
ROT	Av.MAD	3.84e+02	1.57e+03	3.44e+03	4.37e+02	1.56e+07	2.08e+06	1.33e+04	2.98e+04	3.18e+06	2.90e+05	1.34e+03	5.31e+02	1.21e+03	1.76e+02
	Av.Ranking	5.08	5.15	6.38	6.08	10.31	11.38	10.46	10.77	9.08	10.15	5.54	6.08	5.38	4.00
ALL	Av.MAD	7.68e+02	1.31e+03	1.98e+03	1.09e+03	8.73e+06	1.28e+06	6.55e+03	1.13e+04	1.03e+06	1.01e+05	9.24e+02	6.47e+02	5.67e+02	1.18e+03
	Av.Ranking	6.70	5.25	7.15	6.95	8.60	8.97	11.88	10.68	8.12	8.00	5.82	7.00	5.78	6.10

+

+

 \approx

+

 \approx

 \approx

 \approx

 \approx

Table 5 (Continued.)

As shown in Table 5, according to the MED and MEDerr metrics, the algorithm with the best overall performance was MTF_{LDOUT}, followed by PSO–CMAES_{LDOUT}, followed by CMAES_{LDOUT}; and according to the MAD metric, the best algorithm was MTF_{LDOUT}, followed by DE–CMAES_{250UT} and finally PSO–CMAES_{250UT}. For all three performance metrics, the second- and third-best ranked algorithms exhibited slightly superior performance than MTF_{LDOUT} on the UNI and ROT functions, whereas MTF_{LDOUT} was the clear winner in the MUL and HYB functions. The results shown in Table 5 also suggest that single-approach and hybrids involving DE and PSO are less competitive than single-approach and hybrids involving CMA–ES. This finding is supported by the average rankings across all functions and the Wilcoxon test using Bonferroni's correction, which returned a p-value lower than $\alpha = 0.05$ for DE_{250UT}, DE_{LDOUT}, PSO-X_{250UT}, PSO-X_{250UT} and PSO–CMAES_{LDOUT}. Another important finding is that the algorithms trained on the LDOUT scenario produce better results in the UNI, MOD and ROT functions, whereas those trained on the 250UT scenario were better in the HYB and HCP functions. In Section 5.3.3, we study in detail the impact that different training strategies have on the performance of the algorithms.

In the case of PSO–CMAES_{LDOUT} and PSO–CMAES_{250UT}, which were among the top three algorithms in $f_{\text{BENCHMARK}}$ with d = 50, we observe that their inability to converge to the best solution on the HYB and HCP functions becomes increasingly problematic as the number of dimensions increases. To try to understand why, we analyze the MED and MEDerr values obtained by PSO–CMAES_{LDOUT} and PSO–CMAES_{250UT} on the HYB and HCP functions. Based on their MED and MEDerr, both per function and on average, PSO–CMAES_{LDOUT} and PSO–CMAES_{250UT} yield results comparable to those of the top-ranked algorithms in most cases. However, as noted in Section 5.3.1, while PSO–CMAES_{LDOUT} and PSO–CMAES_{250UT} appear effective in identifying the search region containing the optimal solution, they struggle to converge to the solution itself. In our opinion, this is due to the use of CMAES-Mtx-cov-then-diag, which forces the algorithms to switch from the more accurate CMAES-Mtx-covariance to the less accurate CMAES-Mtx-diagonal after $2 + 100 \times \frac{d}{\sqrt{\lambda}}$ FEs. Although the algorithmic design of PSO–CMAES_{LDOUT} and PSO–CMAES_{250UT} is well suited to UNI, MUL and ROT functions, it lacks the right exploration-exploitation balance to solve the most complicated HYB and HCP functions, which, based on our experiments, require an algorithmic design that allows intensive exploitation of the search space in the final stages of the optimization process.

We also study the main designs aspects of MTF_{250UT} and MTF_{LDOUT} . As shown in Table 3, the two MTF implementations are essentially CMA-ES-DE hybrids, but they have a number of design choices that make them unique. In MTF_{250UT} , the implementation of CMA-ES (allotted $\approx 62\%$ of the FEs) is quite similar to CMAES_{DFT}, except for the choice of the algorithm component CMAES-Mtx, which is implemented using CMAES-Mtx-diagonal, resulting in a faster, although less precise variant of CMA-ES compared to CMAES_{DFT}. To compensate for any possible lack of exploitation capabilities, the implementation of DE in MTF_{250UT} uses components BV-best and VB-eigenvector, where BV-best bias the search towards the best solution found so far, and VB-eigenvector (which is similar to the use of CMAES-Mtx-covariance in CMA-ES) provides MTF_{250UT} with a mechanism to effectively tackle rotated search spaces.

Of the two MTF implementations, only MTF_{LDOUT} includes a local search. MTF_{LDOUT} uses three modules, **CMA-ESmod**, **DEmod** and **LSmod**, where each module is allocated, respectively, about 34%, 6% and 60% of the total number of FEs. The implementation of CMA–ES in MTF_{LDOUT} is also similar to $CMAES_{DFT}$, except for two aspects. The first one is the use of the CMAES-Mtx-cov-then-diag option, which allows the algorithm to take advantage of the information provided by the covariance matrix for a number of FEs and then switch to the faster diagonal matrix. The second aspect is a higher tolerance for the range of improvement of all function values of the most recent generation (i.e., stopTolFun), which means that this implementation of CMA–ES allows solution to remain for longer in the population before restarting.

The most salient aspect of MTF_{LDOUT} is the use of the local search algorithm MTSIs, which is executed after CMA–ES and is assigned more than half of the computational budget. The parameter settings of MTSIs are roughly the same used by its authors in [97]. However, the way in which DE and MTSIs interact with each other is quite interesting and has two main distinctive features. The first feature is the obvious bias toward exploitation that results from allocating a much larger number of FEs to MTSIs than to DE in each iteration. The second feature is the use of BV-directed-random, RI-similarity and a large crossover rate ($p_a = 0.81$) in the implementation of DE, which allows it to generate solutions far away from the region where MTSIs is locally searching. By combining these two features, MTF_{LDOUT} can perform an intensive exploitation of the best solution found so far, while keeping some degree of exploration of the search space up until the end of the optimization process.

5.3.3 Generalizing to unseen problems — which training strategy is the best? Our final analysis focuses on comparing the two training scenarios, 250UT and LDOUT, and identifying their main advantages and disadvantages. As mentioned in Section 5.2, the scenarios 250UT and LDOUT differ in the set of functions available for irace to train the algorithms. We use a "machine learning"-type approach to select the functions in each scenario: in the case of 250UT, we randomly selected a fixed percentage of 75% of the test functions of each class to form a stratified training set, and in the case of LDOUT, we used a leave-one-class-out cross-validation approach to train the algorithms excluding the "large dimensional" (LD) class from the training set. In practice, the training set of 250UT contains 88 functions that were selected using $(f_{1,3-7,9-12,14-17,19-23,25} \subset f_{CEC'05} \times d = \{10, 30, 50\}) \cup (f_{1,3-6,9-11,13-15,17-19} \subset f_{SOCO} \times d = \{500, 1000\})$, whereas the training set of LDOUT contains 107 functions that were selected using $(f_{1-25} \subset f_{CEC'05} \times d = \{10, 30\}) \cup (f_{1-19} \subset f_{SOCO} \times d = \{50, 100, 200\})$. In Table 2, we show the composition of each scenario in terms of functions classes.

Although no single instance separation strategy is optimal for training metaheuristic algorithm, each strategy represents a trade-off between generalization and specialization. When we defined scenarios 250UT and LDOUT, our intuition was that, since all classes of functions are represented in 250UT, from UNI to LD, 250UT should produce algorithms that generalize better at the expense of a lower solution quality. In contrast, for LDOUT, we hypothesized that it would Manuscript submitted to ACM produce algorithms specialized in complex low-dimensional functions, albeit with limited scalability. In the previous sections, we identified two trends associated with the use of different training instances. The first trend, observed in the aggregated data for ALL functions in Tables 4 and 5, shows that, on average, algorithms trained on LDOUT achieve superior MED, MEDerr and MAD values compared to those trained on 250UT. The second trend, which is the opposite of the first, applies specifically to the results for the HYB and HCP functions, where algorithms trained on 250UT consistently outperform those trained on LDOUT.

To determine whether the performance differences in the HYB functions increases with the number of dimension—suggesting a connection between the second trend and the fact that 250UT includes dimensional functions—we compare the distance in Av.Ranking obtained by each pair of 250UT-LDOUT algorithms in the HYB functions. The aggregated values obtained for all pairs were 0.88, in the functions with d = 50, and 0.92, in the functions with d = 100. The fact that these two values are similar indicates that the differences in performance between the algorithms trained on 250UT and those trained on LDOUT remain constant despite the increase in the number of dimensions. Based on the fact that (i) the main difference between 250UT and LDOUT is that 250UT includes functions with large dimensionality and (ii) each pair of 250UT-LDOUT algorithms performs similarly well independently of the dimensionality of the functions, we conclude that the set of components that are useful for solving LD functions, we provide further evidence supporting this thesis.

Generalization of the algorithms trained on 250UT and LDOUT to $f_{CEC'14}$. To measure the ability of the algorithms to generalize to other types of functions, we compare their performance on the 22 functions of the $f_{CEC'14}$ with $d = \{50, 100\}$. The $f_{CEC'14}$ has 22 functions, of which 3 are UNI, 13 are MUL, 6 are HYB, and 20 are ROT (see Table 2). As indicated in Table 6, based on the MED and MEDerr metrics, the top-performing algorithms across all functions in $f_{CEC'14}$ with d = 50 are MTF_{LDOUT} and PSO-CMAES_{LDOUT} (tied for first place), followed by PSO-CMAES_{250UT} and CMAES_{LDOUT}. Although both MTF_{LDOUT} and PSO-X_{LDOUT} ranked first, we found statistically significant differences in favor of MTF_{LDOUT} in five cases (DE_{250UT}, DE_{LDOUT}, PSO-X_{250UT}, PSO-X_{LDOUT} and PSO-DE_{250UT}), while in the case of PSO-CMAES_{LDOUT} the statistical test showed differences in only two cases, DE_{250UT} and PSO-X_{250UT}. Based on the data per function class in Table 6, MTF_{LDOUT} performs quite well in the MUL, HYB and ROT functions, but is outperformed by CMAES_{LDOUT} and the two PSO-CMA-ES hybrid in the UNI functions. In the case of PSO-CMA-ES hybrid, its performance is particularly good in the ROT functions, but again poor in the HYB functions, where it is the worst ranked algorithm.

	f#	MTF (250UT)	MTF (LDOUT)	CMAES (250UT)	CMAES (LDOUT)	DE (250UT)	DE (LDOUT)	PSO-X (250UT)	PSO-X (LDOUT)	PSO- DE (250UT)	PSO- DE (LDOUT)	DE- CMAES (250UT)	DE- CMAES (LDOUT)	PSO- CMAES (250UT)	PSO- CMAES (LDOUT)
	Wins (MED)	1	5	2	7	1	0	2	2	1	4	2	4	5	4
IND	Av.MED	0.00e+00	2.80e+03	9.03e+00	0.00e+00	1.16e+07	1.25e+07	4.18e+05	8.35e+05	6.84e+06	8.72e+06	0.00e+00	0.00e+00	0.00e+00	0.00e+00
	Av.Ranking	3.33	5.67	7.00	2.00	12.00	13.00	9.67	10.67	10.33	13.33	6.67	3.67	4.67	3.33
MUL	Av.MED	3.26e+03	3.26e+03	3.42e+03	3.35e+03	4.60e+03	4.92e+03	4.33e+03	6.42e+03	3.88e+03	6.69e+03	3.27e+03	3.35e+03	3.28e+03	3.24e+03
	Av.Ranking	7.31	5.62	7.19	6.19	12.12	10.69	12.00	10.00	8.69	7.69	6.44	7.00	6.38	5.88
HYB	Av.MED	1.91e+03	8.82e+03	5.14e+03	1.73e+03	3.07e+06	1.42e+06	3.28e+04	3.32e+04	5.93e+04	5.33e+04	1.78e+03	1.73e+03	3 1.73e+03	1.77e+03
	Av.Ranking	2.82	2.86	4.00	4.23	7.14	7.55	8.55	8.14	8.73	9.86	9.55	10.18	10.55	11.95

Table 6. Average median (Av.MED), average median error (Av.MEDerr) and average median absolute deviation (Av.MAD) obtained by the algorithms on the 22 functions of the CEC'14 test suite with d = 50.

-															
	f#	MTF (250UT)	MTF (LDOUT)	CMAES (250UT)	CMAES (LDOUT)	DE (250UT)	DE (LDOUT)	PSO-X (250UT)	PSO-X (LDOUT)	PSO- DE (250UT)	PSO- DE (LDOUT)	DE- CMAES (250UT)	DE- CMAES (LDOUT)	PSO- CMAES (250UT)	PSO- CMAES (LDOUT)
ROT	Av.MED	1.68e+03	2.29e+03	1.76e+03	1.74e+03	2.49e+06	2.68e+06	9.17e+04	1.81e+05	1.47e+06	1.87e+06	1.69e+03	1.73e+03	1.70e+03	1.67e+03
	Av.Ranking	5.86	5.57	6.57	5.64	12.14	11.93	10.93	10.07	9.71	9.71	6.64	6.07	6.43	5.14
ALL	Av.MED	2.68e+03	5.26e+03	3.81e+03	2.68e+03	2.56e+06	2.16e+06	7.01e+04	1.27e+05	9.53e+05	1.21e+06	2.64e+03	2.68e+03	2.64e+03	2.62e+03
	Av.Ranking	6.68	5.50	6.82	5.86	12.27	11.14	11.68	9.91	8.86	8.86	6.23	6.18	5.73	5.50
1	Wilcoxon test Wilcoxon test	* *	~	* *	* *	+ +	+ ≈	+ +	+ ≈	+ ≈	* *	* *	* *	* *	~
	Wins (MEDerr)	1	5	2	7	1	0	2	2	1	4	2	4	5	4
INI	Av.MEDerr	0.00e+00	2.80e+03	9.03e+00	0.00e+00	1.16e+07	1.25e+07	4.18e+05	8.35e+05	6.84e+06	8.72e+06	0.00e+00	0.00e+00	0.00e+00	0.00e+00
	Av.Ranking	3.33	5.67	7.00	2.00	12.00	13.00	9.67	10.67	10.33	13.33	6.67	3.67	4.67	3.33
MUL	Av.MEDerr Av.Ranking	1.17e+02 7.31	1.19e+02 5.62	2.73e+02 7.19	2.10e+02 6.19	1.46e+03 12.12	1.78e+03 10.69	1.18e+03 12.00	3.28e+03 10.00	7.42e+02 8.69	3.55e+03 7.69	1.23e+02 6.44	2.03e+02 7.00	1.37e+02 6.38	9.42e+01 5.88
HYB	Av.MEDerr	2.50e+02	7.16e+03	3.48e+03	6.45e+01	3.07e+06	1.42e+06	3.11e+04	3.15e+04	5.77e+04	5.17e+04	1.17e+02	6.59e+01	6.36e+01	1.09e+02
	Av.Ranking	2.82	2.86	4.00	4.23	7.14	7.55	8.55	8.14	8.73	9.86	9.55	10.18	10.55	11.95
ROT	Av.MEDerr	7.38e+01	6.87e+02	1.54e+02	1.32e+02	2.49e+06	2.68e+06	9.01e+04	1.79e+05	1.47e+06	1.87e+06	8.07e+01	1.24e+02	9.50e+01	5.91e+01
	Av.Ranking	5.86	5.57	6.57	5.64	12.14	11.93	10.93	10.07	9.71	9.71	6.64	6.07	6.43	5.14
ALL	Av.MEDerr	1.54e+02	2.73e+03	1.28e+03	1.54e+02	2.56e+06	2.16e+06	6.76e+04	1.24e+05	9.51e+05	1.21e+06	1.15e+02	1.50e+02	1.07e+02	9.45e+01
	Av.Ranking	6.68	5.50	6.82	5.86	12.27	11.14	11.68	9.91	8.86	8.86	6.23	6.18	5.73	5.50
1	Wilcoxon test Wilcoxon test	*	~	* *	* *	+ +	+ ≈	+ +	+ ≈	+ ≈	* *	* *	~ ~	* *	~
	Wins (MAD)	0	4	3	1	0	0	1	0	0	3	0	4	4	3
INI	Av.MAD	0.00e+00	6.89e+02	7.93e+00	0.00e+00	1.04e+07	3.64e+06	7.53e+04	6.97e+04	1.45e+06	9.01e+05	0.00e+00	0.00e+00	0.00e+00	0.00e+00
	Av.Ranking	4.33	5.67	7.00	3.33	12.33	12.67	10.00	10.33	10.67	13.00	6.67	3.00	3.67	2.33
MUL	Av.MAD	3.60e+01	4.08e+01	4.51e+01	4.42e+01	2.58e+02	3.21e+02	4.86e+01	1.23e+03	1.33e+02	1.86e+03	3.66e+01	5.30e+01	2.81e+01	4.45e+01
	Av.Ranking	8.12	4.94	7.12	7.44	10.00	9.50	10.25	10.44	7.75	7.88	7.38	6.06	5.31	6.00
HYB	Av.MAD	8.68e+01	1.86e+03	3.87e+02	5.71e+01	2.85e+06	6.35e+05	1.18e+04	6.48e+03	5.54e+03	8.68e+03	4.79e+01	3.11e+01	5.28e+00	4.56e+01
	Av.Ranking	2.32	3.18	3.59	5.23	6.27	7.00	8.09	8.82	8.82	9.86	9.59	10.18	10.77	11.36
ROT	Av.MAD	2.16e+01	1.65e+02	1.91e+01	2.01e+01	2.22e+06	7.81e+05	1.61e+04	1.50e+04	3.12e+05	1.93e+05	2.72e+01	2.74e+01	1.10e+01	2.61e+01
	Av.Ranking	7.43	5.07	7.14	6.36	11.29	10.36	10.29	10.07	8.57	9.43	7.50	5.07	5.29	4.71
ALL	Av.MAD	5.05e+01	7.02e+02	1.53e+02	4.63e+01	2.32e+06	6.99e+05	1.40e+04	1.16e+04	2.00e+05	1.26e+05	3.84e+01	4.36e+01	1.96e+01	4.28e+01
	Av.Ranking	6.95	5.55	6.95	7.00	10.73	10.00	10.41	10.64	8.14	8.68	6.77	5.41	5.18	5.00
١	Wilcoxon test	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	≈	

Table 6 (Continued.)

Regarding the robustness of the algorithms, measured by their MAD value, the results are consistent with those obtained by the algorithms on the MED and MEDerr metrics. In particular, PSO-CMAESLDUT showed greater robustness in the UNI, ROT and ALL functions, while MTFLDOUT showed greater robustness in the MUL functions. It should be noted that although $f_{\text{CEC'14}}$ was reserved for testing only, the functions $f_{1,4-10,15,16} \in f_{\text{CEC'14}}$ are the same as the functions $f_{3,6-14} \in f_{CEC'05}$. This means that 7 of the 88 functions in the 250UT training set are also present in the $f_{CEC'14}$ test set, with 6 functions belonging to the MUL class and 1 function belonging to the UNI class. In the cases of the training set LDOUT and the test set $f_{CEC'14}$, there is no overlap because LDOUT excludes dimensions 50 and 100, and these are the dimensions we consider for the analysis using $f_{CEC'14}$. Despite the overlap between 250UT and $f_{CEC'14}$, we found no evidence that the algorithms trained on 250UT had an advantage on the MUL functions over those trained on LDOUT.

Manuscript submitted to ACM

Table 7. Average median (Av.MED), average median error (Av.MEDerr) and average median absolute deviation (Av.MAD) obtained by the algorithms on the 22 functions of the CEC'14 test suite with d = 100.

	f#	MTF (250UT)	MTF (LDOUT)	CMAES (250UT)	CMAES (LDOUT)	DE (250UT)	DE (LDOUT)	PSO-X (250UT)	PSO-X (LDOUT)	PSO- DE (250UT)	PSO- DE (LDOUT)	DE- CMAES (250UT)	DE- CMAES (LDOUT)	PSO- CMAES (250UT)	PSO- CMAES (LDOUT)
	Wins (MED)	4	4	4	8	1	1	1	2	2	4	3	6	8	5
INI	Av.MED	8.80e+03	8.57e+04	4.07e+04	2.38e+03	1.41e+08	9.93e+07	1.26e+06	3.10e+06	4.87e+07	4.64e+07	8.10e+03	2.11e+03	2.03e+03	6.07e+03
	Av.Ranking	5.00	6.00	7.00	2.33	12.67	12.33	9.00	11.33	10.33	13.00	5.67	2.67	4.33	3.33
MUL	Av.MED	6.75e+03	6.78e+03	7.04e+03	7.02e+03	9.23e+03	9.07e+03	8.74e+03	9.23e+03	7.61e+03	1.01e+04	6.63e+0 3	6.69e+03	6.68e+03	6.65e+03
	Av.Ranking	7.56	6.50	7.38	6.00	12.00	10.25	11.56	10.00	8.56	8.12	6.88	7.06	6.69	6.44
HYB	Av.MED	1.08e+04	2.80e+04	1.76e+04	9.18e+03	2.54e+07	1.32e+07	5.60e+04	7.09e+04	1.33e+05	1.54e+05	1.02e+04	8.01e+03	7.36e+03	9.58e+03
	Av.Ranking	2.64	3.55	3.91	4.27	7.23	7.50	8.27	8.27	9.05	9.86	9.68	10.09	10.59	11.59
ROT	Av.MED	5.33e+03	2.17e+04	1.23e+04	4.14e+03	3.01e+07	2.13e+07	2.75e+05	6.68e+05	1.04e+07	9.94e+06	5.09e+03	3.84e+03	3.82e+03	4.66e+03
	Av.Ranking	6.64	6.43	6.71	5.07	12.00	11.64	10.64	10.50	9.43	10.21	6.57	6.00	6.57	5.64
ALL	Av.MED	8.92e+03	2.48e+04	1.56e+04	7.71e+03	2.73e+07	1.77e+07	1.95e+05	4.50e+05	6.68e+06	6.38e+06	8.56e+03	7.09e+03	6.87e+03	8.11e+03
	Av.Ranking	7.05	6.50	6.95	5.36	12.23	10.73	11.23	10.32	9.05	9.18	6.32	6.00	5.86	5.68
1	Wilcoxon test	: ≈	≈	≈		+	≈	+	+	≈	~	~	≈	≈	≈
	Wins (MEDerr)	4	4	4	8	1	1	1	2	2	4	3	6	8	5
INI	Av.MEDerr	8.63e+03	8.53e+04	4.03e+04	2.20e+03	1.41e+08	9.93e+07	1.26e+06	3.10e+06	4.87e+07	4.64e+07	7.94e+03	1.93e+03	1.85e+03	5.90e+03
	Av.Ranking	5.00	6.00	7.00	2.33	12.67	12.33	9.00	11.33	10.33	13.00	5.67	2.67	4.33	3.33
MUL	Av.MEDerr	4.41e+02	4.70e+02	7.33e+02	7.03e+02	2.92e+03	2.76e+03	2.43e+03	2.92e+03	1.30e+03	3.80e+03	3.18e+02	3.78e+02	3.67e+02	3.40e+02
	Av.Ranking	7.56	6.50	7.38	6.00	12.00	10.25	11.56	10.00	8.56	8.12	6.88	7.06	6.69	6.44
HYB	Av.MEDerr	6.47e+03	2.37e+04	1.33e+04	4.87e+03	2.54e+07	1.32e+07	5.17e+04	6.66e+04	1.29e+05	1.50e+05	5.88e+03	3.70e+03	3.05e+03	5.27e+03
	Av.Ranking	2.64	3.55	3.91	4.27	7.23	7.50	8.27	8.27	9.05	9.86	9.68	10.09	10.59	11.59
ROT	Av.MEDerr	2.07e+03	1.85e+04	8.98e+03	8.88e+02	3.01e+07	2.13e+07	2.71e+05	6.65e+05	1.04e+07	9.94e+06	1.84e+03	5.88e+02	5.62e+02	1.40e+03
	Av.Ranking	6.64	6.43	6.71	5.07	12.00	11.64	10.64	10.50	9.43	10.21	6.57	6.00	6.57	5.64
ALL	Av.MEDerr	3.52e+03	1.93e+04	1.02e+04	2.30e+03	2.73e+07	1.77e+07	1.90e+05	4.45e+05	6.68e+06	6.37e+06	3.16e+03	1.68e+03	1.45e+03	2.70e+03
	Av.Ranking	7.05	6.50	6.95	5.36	12.23	10.73	11.23	10.32	9.05	9.18	6.32	6.00	5.86	5.68
١	Wilcoxon test	≈	≈	~		+	×	+	+	~	*	*	×	~	≈
	Wins (MAD)	3	5	1	6	2	1	1	1	4	2	2	2	3	6
INI	Av.MAD	9.83e+02	6.71e+03	1.45e+04	8.90e+02	6.77e+07	9.00e+06	5.71e+04	1.29e+05	1.38e+07	1.26e+06	5.68e+03	1.20e+03	5.14e+03	6.47e+02
	Av.Ranking	4.33	6.00	7.00	2.00	12.67	11.33	10.00	11.00	10.33	13.00	6.00	3.33	4.33	3.67
MUL	Av.MAD	1.77e+02	2.13e+02	1.09e+02	2.47e+02	3.69e+02	3.43e+02	2.40e+02	4.06e+02	1.54e+02	1.18e+03	6.02e+01	2.65e+02	4.09e+01	5.83e+01
	Av.Ranking	6.75	5.69	6.94	8.19	9.94	9.69	11.56	9.50	8.56	8.44	6.12	8.25	6.38	5.56
HYB	Av.MAD	3.15e+03	2.85e+03	2.71e+03	4.79e+03	2.09e+07	3.48e+06	6.13e+03	6.19e+03	1.26e+04	3.66e+04	2.42e+03	2.21e+03	5.16e+02	3.15e+03
	Av.Ranking	2.55	2.91	3.82	4.59	6.55	7.23	8.05	7.91	9.27	10.05	9.00	10.64	11.00	11.50
ROT	Av.MAD	3.57e+02	1.46e+03	3.20e+03	4.06e+02	1.45e+07	1.93e+06	1.23e+04	2.77e+04	2.95e+06	2.69e+05	1.24e+03	4.93e+02	1.13e+03	1.64e+02
	Av.Ranking	5.79	6.14	6.93	6.79	10.14	10.93	11.21	10.36	9.00	10.14	6.64	7.36	6.29	4.64
ALL	Av.MAD	1.25e+03	1.85e+03	2.91e+03	1.80e+03	1.59e+07	2.33e+06	9.88e+03	1.96e+04	1.88e+06	1.83e+05	1.58e+03	1.03e+03	8.90e+02	1.13e+03
	Av.Ranking	6.36	5.95	6.64	7.05	10.32	10.32	11.36	9.55	8.73	9.41	5.91	7.45	5.68	5.05
1	Wilcoxon test	≈	≈	≈	≈	+	≈	+	≈	≈	≈	≈	≈	≈	

Now we focus on the results in $f_{CEC'14}$ with d = 100 (Table 7). Based on the MED and MEDerr metrics, the best performing algorithm is CMAES_{LDOUT}, followed by PSO–CMAES_{250UT} and PSO–CMAES_{LDOUT} (both tied for second place), and finally DE–CMAES_{LDOUT}. The analysis by function class shows that CMAES_{LDOUT} is the best algorithm for the UNI, MUL, and ROT functions, and fourth for the HYB functions, where it is outperformed by the two MTF hybrids and CMAES_{250UT}. The performance of CMAES_{LDOUT} is clearly superior to most of the compared algorithms based on

MED and MEDerr, but has a higher variability in its results. According to the MAD metric, the most robust algorithm is PSO-CMAES_{LDOUT}, followed by PSO-CMAES_{250UT}, and finally DE-CMAES_{250UT}, while CMAES_{LDOUT} ranks seventh.

After comparing the results obtained by the algorithms on the $f_{\text{BENCHMARK}}$ (Tables 4 and 5) and $f_{\text{CEC'14}}$ (Tables 6 and 7) with d = 50 and d = 100, we found consistency in their rankings for median solution quality (MED), median solution error (MEDerr), and median absolute deviation (MAD) on both dimensions. In the two benchmarks, the best results over all function sets are obtained by MTF, PSO–CMA–ES hybrid, and CMA–ES, and the worst results are obtained by PSO, DE, and PSO–DE hybrid. Also, for both $f_{\text{BENCHMARK}}$ and $f_{\text{CEC'14}}$, we found that (i) on average, the algorithms trained on LDOUT outperform those trained on 250UT, and (ii) for the HYB functions, the algorithms trained on 250UT outperform those trained on LDOUT. These results suggest that both training scenarios produce algorithms with similar generalization capabilities when it comes to functions with features such as multimodality, mathematical transformations, and function hybridization.

Generalization of the algorithms trained on 250UT and LDOUT to f_{SOCO} . So far, we have analyzed the performance of the algorithms only on functions with low to medium dimensionality. The goal of this final analysis is to compare the performance of the algorithms using functions with a much larger scale, namely 750 and 1 250 dimensions. For this purpose, we performed experiments on f_{SOCO} , which consists of 19 freely scalable functions, of which 7 are shifted unimodal (SHU) functions, 4 are MUL functions, and 8 are HYB functions.

Table 8. Average median (Av.MED), average median error (Av.MEDerr) and average median absolute deviation (Av.MAD) obtained by the algorithms on the 19 functions of the SOCO'10 test suite with d = 750.

	f#	MTF (250UT)	MTF (LDOUT)	CMAES (250UT)	CMAES (LDOUT)	DE (250UT)	DE (LDOUT)	PSO-X (250UT)	PSO-X (LDOUT)	PSO- DE (250UT)	PSO- DE (LDOUT)	DE- CMAES (250UT)	DE- CMAES (LDOUT)	PSO- CMAES (250UT)	PSO- CMAES (LDOUT)
	Wins (MED)	0	0	2	2	4	0	1	0	0	0	2	1	8	0
SHU	Av.MED	1.43e+09	1.43e+09	1.43e+09	1.43e+09	4.03e+05	3.69e+05	4.98e+04	1.43e+09	1.43e+09	1.43e+09	1.43e+09	1.43e+09	1.43e+09	1.43e+09
	Av.Ranking	5.57	7.14	5.71	5.86	8.14	10.86	9.00	13.00	11.29	11.57	5.29	8.00	6.14	5.29
MUL	Av.MED	7.83e+04	7.75e+04	7.91e+04	8.00e+04	7.34e+04	2.00e+09	3.37e+05	2.00e+09	1.26e+05	7.93e+04	7.46e+04	7.81e+04	7.42e+04	7.59e+04
	Av.Ranking	7.91	6.00	6.73	7.64	5.36	12.45	11.73	14.00	8.73	7.09	4.09	6.91	3.36	5.09
HYB	Av.MED	1.11e+09	1.11e+09	4.51e+04	4.57e+04	4.19e+04	2.22e+09	7.01e+04	4.44e+09	6.42e+04	4.70e+04	1.11e+09	4.46e+04	1.11e+09	1.11e+09
	Av.Ranking	4.53	4.00	4.53	6.00	4.79	8.58	8.95	10.53	8.53	8.16	8.21	9.89	8.89	10.47
ALL	Av.MED	1.05e+09	1.05e+09	5.26e+08	5.26e+08	1.69e+05	1.58e+09	1.14e+0 5	3.16e+09	5.26e+08	5.26e+08	1.05e+09	5.26e+08	1.05e+09	1.05e+09
	Av.Ranking	7.11	6.47	6.32	7.11	6.37	11.84	10.79	13.63	9.79	8.47	4.47	7.37	4.26	5.11
1	Wilcoxon test	: ≈	≈	≈	≈	\approx	\approx	~	+	≈	≈	≈	≈		≈
	Wins (MEDerr)	0	0	2	2	4	0	1	0	0	0	2	1	8	0
SHU	Av.MEDerr	1.43e+09	1.43e+09	1.43e+09	1.43e+09	3.70e+05	3.36e+05	1.71e+0 4	1.43e+09	1.43e+09	1.43e+09	1.43e+09	1.43e+09	1.43e+09	1.43e+09
	Av.Ranking	5.57	7.14	5.71	5.86	8.14	10.86	9.00	13.00	11.29	11.57	5.29	8.00	6.14	5.29
MUL	Av.MEDerr	9.97e+03	9.14e+03	1.07e+04	1.16e+04	5.03e+03	2.00e+09	2.69e+05	2.00e+09	5.77e+04	1.10e+04	6.28e+03	9.76e+03	5.88e+03	7.51e+03
	Av.Ranking	7.91	6.00	6.73	7.64	5.36	12.45	11.73	14.00	8.73	7.09	4.09	6.91	3.36	5.09
HYB	Av.MEDerr	1.11e+09	1.11e+09	6.82e+03	7.36e+03	3.58e+03	2.22e+09	3.17e+04	4.44e+09	2.58e+04	8.70e+03	1.11e+09	6.26e+03	1.11e+09	1.11e+09
	Av.Ranking	4.53	4.00	4.53	6.00	4.79	8.58	8.95	10.53	8.53	8.16	8.21	9.89	8.89	10.47
ALL	Av.MEDerr	1.05e+09	1.05e+09	5.26e+08	5.26e+08	1.38e+05	1.58e+09	8.41e+04	3.16e+09	5.26e+08	5.26e+08	1.05e+09	5.26e+08	1.05e+09	1.05e+09
	Av.Ranking	7.11	6.47	6.32	7.11	6.37	11.84	10.79	13.63	9.79	8.47	4.47	7.37	4.26	5.11
١	Vilcoxon test	: ≈	≈	*	≈	*	*	*	+	*	≈	≈	*		≈
	Wins (MAD)	4	4	2	3	1	3	0	6	1	1	2	3	2	5
SHU	Av.MAD	3.63e+03	3.56e+03	3.84e+03	2.33e+0 3	2.19e+04	3.61e+03	3.38e+04	7.42e+04	2.51e+03	4.12e+04	5.20e+03	2.87e+03	3.07e+03	4.26e+03
	Av.Ranking	5.86	5.86	6.43	6.57	10.14	10.71	11.00	12.71	9.43	10.57	6.57	6.71	5.14	5.29

	f#	MTF (250UT)	MTF (LDOUT)	CMAES (250UT)	CMAES (LDOUT)	DE (250UT)	DE (LDOUT)	PSO-X (250UT)	PSO-X (LDOUT)	PSO- DE (250UT)	PSO- DE (LDOUT)	DE- CMAES (250UT)	DE- CMAES (LDOUT)	PSO- CMAES (250UT)	PSO- CMAES (LDOUT)
MUL	Av.MAD	7.63e+02	3.40e+02	6.62e+02	3.29e+0 2	6.57e+02	1.16e+03	7.70e+04	5.80e+03	9.19e+03	3.69e+03	6.54e+02	5.94e+02	6.35e+02	6.99e+02
	Av.Ranking	6.82	5.73	5.73	6.00	8.91	8.18	12.18	9.27	10.18	9.00	5.27	7.55	6.55	5.45
HYB	Av.MAD	4.00e+02	2.00e+02	3.76e+02	1.98e+02	9.69e+02	3.12e+03	9.03e+03	3.76e+04	4.94e+03	2.26e+03	3.77e+02	3.81e+02	3.91e+02	4.00e+02
	Av.Ranking	3.16	3.63	3.89	5.37	7.11	7.32	9.05	8.00	9.68	9.21	8.37	10.58	10.37	10.21
ALL	Av.MAD	1.55e+03	1.41e+03	1.60e+03	9.56e+02	8.53e+03	3.02e+03	3.51e+04	4.65e+04	5.52e+03	1.64e+04	2.10e+03	1.24e+03	1.32e+03	1.76e+03
	Av.Ranking	6.58	5.84	6.00	6.42	9.32	9.42	11.79	10.11	9.95	9.74	5.58	7.05	5.84	5.42
١	Vilcoxon test	≈	~	~	~	~	×	+	~	~	~	~	×	~	

Table 8 (Continued.)

In Table 8 we report the results of the algorithms on f_{SOCO} with dimension 750. Based on MED and MEDerr performance metrics, the best performing algorithms across all functions are PSO-CMAES_{250UT}, followed by DE-CMAES_{250UT} and PSO-CMAES_{LDOUT}. The analysis of results per function class shows that PSO-CMAES_{LDOUT} and DE-CMAES_{250UT} are tied for the first place for the SHU functions, PSO-CMAES_{250UT} is ranked first in the MUL functions and MTF_{LDOUT} is ranked first in the HYB functions. It is also interesting to note that the trend observed earlier, where the algorithms trained on LDOUT consistently outperform those trained on 250UT across all functions, is partially reversed in this set of benchmark functions. In fact, with the exception of MTF and PSO-DE hybrids, the algorithms trained on 250UT obtained better MED and MEDerr values than those trained on LDOUT; and this effect is particularly notable for DE.

Although the statistical test did not find a significant difference in the performance of the algorithms based on the MED and MEDerr values (with the exception of PSO- X_{LDOUT}), the number of "wins" of the algorithm gives us an indication of how competitive they are. The number of "wins" refers to the number of times the algorithm obtained the lowest MED, MEDerr or MAD value. As shown in Table 8, PSO–CMAES_{250UT} obtained the best value 8 times, DE_{250UT} 6 times, the two CMA–ES and PSO–CMAES_{250UT} 2 times and PSO- X_{250UT} and DE–CMAES_{LDOUT} 1 time each. The number of "wins", while useful for competitive testing, is not necessarily a reliable performance metric on its own due to its sensitivity to the precision of algorithms in objective functions with mathematical transformations. This means that if no precision is defined, only the algorithm that comes closest to the optimum will be awarded a "win", even if the differences in solution with other algorithms are negligible.

Another noteworthy finding from the experiments on f_{SOCO} with LD is the difference in performance between $\text{DE}_{250\text{UT}}$ and DE_{LDOUT} . While $\text{DE}_{250\text{UT}}$ is competitive with the best-ranked algorithms on the MUL, HYB and ALL functions, ranking either third or fourth, DE_{LDOUT} is among the worst-ranked algorithms on all function classes. However, the two DE implementations differ only in a few design choices. Both DE implementations use the VB-natural and BV-best algorithm components and have similar values for the crossover rate (p_a) and the scaling factor (β), although these are slightly higher in the case of $\text{DE}_{250\text{UT}}$ (see Table 3). The main differences between $\text{DE}_{250\text{UT}}$ and DE_{LDOUT} are the algorithm components Population and DE-vector-differences. In the case of $\text{DE}_{250\text{UT}}$, the population is handled by Pop-time-varying, which is updated every 26 iterations and varies between 39 and 132 solutions. Since the percentage of DE-vector-differences in $\text{DE}_{250\text{UT}}$ is 0.0151, the algorithm adds only one vector difference when the population size is less than 100, and two vector differences when it is greater than or equal to 100. Compared to $\text{DE}_{250\text{UT}}$, the implementation of DE_{LDOUT} uses a larger DE-vector-differences value (0.1711) and a smaller population size, starting with 46 solutions and ending with 69 solutions. Therefore, from the fifth iteration, when $\text{DE}_{250\text{UT}}$ reaches its maximum population size, each individual in the population will add 12 vector differences to compute its trail vector.

Based on the results of DE_{250UT} and DE_{LDOUT} on $f_{\text{BENCHMARK}}$ (Tables 4 to 5) and on $f_{\text{CEC'14}}$ (Tables 6 to 7) with $d = \{50, 100\}$, where both implementations gave similar results, with DE_{LDOUT} slightly better than DE_{250UT} on average, the performance of DE does not seem to be particularly sensitive to the options used for the Population and DE-vector-differences components. However, in large dimensional search spaces, as in the case of f_{SOCO} with d = 750, the Population and DE-vector-differences components have a strong impact on the performance of DE. In practice, on complex multimodal search spaces with less than 100 dimensions, a good strategy is to implement DE using a population of about 75 individuals and adding a maximum of 15% of the population as vector differences. However, when the number of dimensions is greater than 100, the performance of DE can be improved by slightly increasing the population size and reducing the number of vector differences to one or at most two.

Finally, in Table 9, we show the results obtained by the algorithms on f_{SOCO} with 1250 dimensions. The bestranked algorithms across the entire set of functions, based on the MED and MEDerr performance metrics, are DE– CMAES_{250UT}, first place, PSO–CMAES_{250UT}, second place, and MTF_{LDOUT}, third place. Similarly to f_{SOCO} with 750 dimensions, DE–CMAES_{250UT} and PSO–CMAES_{250UT} obtained the best results overall and PSO–CMAES_{250UT} also in the MUL functions; however, in the SHU and HYB functions, MTF_{250UT} was clear winner, outperforming the first and second place by a significant margin. In terms of scoring the higher number of "wins" for the MED and MEDerr metrics, the best performing algorithm is PSO–CMAES_{250UT}, 8 times, followed by DE–CMAES_{250UT}, 4 times, the two MTF, 3 times, CMAES_{250UT} and DE_{250UT}, 2 times, and finally CMAES_{LDOUT}, PSO- X_{250UT} and PSO–CMAES_{LDOUT}, 1 times each. We found a statistical significant difference in favor of PSO–CMAES_{250UT} with respect to PSO–DE_{250UT}, PSO– DE_{LDOUT} and DE–CMAES_{LDOUT}, in the MED and MEDerr results. The results obtained by the algorithms on the MAD metric indicate that MTF, CMA–ES, DE–CMA–ES hybrid, PSO–CMA–ES hybrid, DE_{LDOUT} and, PSO- X_{LDOUT} exhibit comparable robustness, with CMAES_{LDOUT} and PSO–CMAES_{LDOUT} outperforming the others. In contrast, DE_{250UT}, PSO- X_{250UT} and PSO–DE hybrid display variability in their outcomes.

Table 9. A	Average median	(Av.MED), a	verage median e	error (Av.MEDe	rr) and average	e median	absolute deviation	(Av.MAD) o	btained
by the alg	gorithms on the	19 functions	s of the SOCO'10) test suite with	d = 1250.				

	f#	MTF (250UT)	MTF (LDOUT)	CMAES (250UT)	CMAES (LDOUT)	DE (250UT)	DE (LDOUT)	PSO-X (250UT)	PSO-X (LDOUT)	PSO- DE (250UT)	PSO- DE (LDOUT)	DE- CMAES (250UT)	DE- CMAES (LDOUT)	PSO- CMAES (250UT)	PSO- CMAES (LDOUT)
	Wins (MED)	3	3	2	1	2	0	1	0	0	0	4	0	8	1
SHU	Av.MED	1.43e+09	1.43e+09	1.43e+09	1.43e+09	1.05e+06	1.43e+09	1.43e+09	1.52e+06	1.43e+09	1.43e+09	1.43e+09	1.43e+09	1.43e+09	1.43e+09
	Av.Ranking	4.86	5.00	5.86	5.71	8.29	12.00	9.71	11.00	10.57	11.14	5.29	12.71	6.86	5.43
MUL	Av.MED	1.32e+05	1.31e+05	1.33e+05	1.35e+05	9.16e+05	2.00e+09	1.92e+08	2.00e+09	1.72e+08	4.26e+08	1.27e+0 5	2.00e+09	1.27e+05	1.29e+05
	Av.Ranking	5.91	4.73	6.91	7.00	7.09	11.91	9.73	12.73	10.09	10.18	3.55	13.36	3.45	4.73
HYB	Av.MED	1.11e+09	1.11e+09	1.11e+09	1.11e+09	9.11e+06	2.22e+09	2.47e+07	3.33e+09	1.28e+09	1.17e+09	1.11e+09	3.33e+09	1.11e+09	1.11e+09
	Av.Ranking	3.32	3.32	4.74	5.53	5.74	8.26	8.05	9.95	9.53	10.11	7.74	12.53	8.74	10.16
ALL	Av.MED	1.05e+09	1.05e+09	1.05e+09	1.05e+09	4.91e+06	2.11e+09	5.89e+08	2.11e+09	1.18e+09	1.19e+09	1.05e+09	2.63e+09	1.05e+09	1.05e+09
	Av.Ranking	5.53	4.79	6.42	6.53	7.58	11.89	9.84	12.16	10.21	10.53	4.11	13.11	4.58	4.89
١	Wilcoxon test	*	~	~	~	\approx	~	~	~	+	+		+	~	≈
	Wins (MEDerr)	3	3	2	1	2	0	1	0	0	0	4	0	8	1
SHU	Av.MEDerr	1.43e+09	1.43e+09	1.43e+09	1.43e+09	9.61e+05	1.43e+09	1.43e+09	1.43e+06	1.43e+09	1.43e+09	1.43e+09	1.43e+09	1.43e+09	1.43e+09
	Av.Ranking	4.86	5.00	5.86	5.71	8.29	12.00	9.71	11.00	10.57	11.14	5.29	12.71	6.86	5.43
MUL	Av.MEDerr	8.06e+03	6.40e+03	8.84e+03	1.04e+04	7.92e+05	2.00e+09	1.92e+08	2.00e+09	1.72e+08	4.26e+08	2.89e+03	2.00e+09	2.88e+03	4.15e+03
	Av.Ranking	5.91	4.73	6.91	7.00	7.09	11.91	9.73	12.73	10.09	10.18	3.55	13.36	3.45	4.73
YB	Av.MEDerr	1.11e+09	1.11e+09	1.11e+09	1.11e+09	9.04e+06	2.22e+09	2.46e+07	3.33e+09	1.28e+09	1.17e+09	1.11e+09	3.33e+09	1.11e+09	1.11e+09

	f#	MTF (250UT)	MTF (LDOUT)	CMAES (250UT)	CMAES (LDOUT)	DE (250UT)	DE (LDOUT)	PSO-X (250UT)	PSO-X (LDOUT)	PSO- DE (250UT)	PSO- DE (LDOUT)	DE- CMAES (250UT)	DE- CMAES (LDOUT)	PSO- CMAES (250UT)	PSO- CMAES (LDOUT)
	Av.Ranking	3.32	3.32	4.74	5.53	5.74	8.26	8.05	9.95	9.53	10.11	7.74	12.53	8.74	10.16
ALL	Av.MEDerr	1.05e+09	1.05e+09	1.05e+09	1.05e+09	4.84e+06	2.11e+09	5.89e+08	2.11e+09	1.18e+09	1.19e+09	1.05e+09	2.63e+09	1.05e+09	1.05e+09
	Av.Ranking	5.53	4.79	6.42	6.53	7.58	11.89	9.84	12.16	10.21	10.53	4.11	13.11	4.58	4.89
١	Wilcoxon test	≈	~	~	≈	≈	~	≈	~	+	+		+	~	≈
	Wins (MAD)	4	3	2	4	0	4	2	4	2	2	3	5	4	6
SHU	Av.MAD	3.35e+04	2.12e+04	4.09e+04	1.92e+04	4.03e+04	5.88e+04	3.73e+04	3.00e+05	2.50e+04	5.18e+04	1.83e+04	6.53e+06	5.53e+0 3	2.39e+04
	Av.Ranking	5.14	5.86	8.57	4.00	9.57	11.00	8.86	10.71	9.57	9.57	6.29	13.00	6.29	6.14
MUL	Av.MAD	4.87e+02	4.55e+02	1.07e+03	8.30e+02	6.42e+05	5.13e+04	4.86e+08	8.09e+03	9.98e+08	4.18e+08	4.16e+0 2	27.39e+05	1.00e+04	7.14e+02
	Av.Ranking	5.18	4.73	6.64	5.55	10.18	9.91	10.45	8.18	11.00	10.82	6.18	10.18	6.64	4.36
HYB	Av.MAD	5.66e+02	4.03e+02	2 4.19e+03	6.78e+02	1.46e+08	6.44e+04	3.05e+07	4.67e+04	2.82e+08	8.04e+08	4.63e+02	6.84e+05	5.58e+03	4.84e+02
	Av.Ranking	2.95	3.37	4.63	4.84	7.16	7.74	8.32	8.00	9.79	10.42	9.16	11.47	9.79	10.05
ALL	Av.MAD	1.26e+04	8.00e+03	1.71e+04	7.39e+03	6.94e+07	6.37e+04	1.42e+08	1.35e+05	3.96e+08	4.91e+08	7.00e+03	2.92e+06	4.78e+0 3	9.04e+03
	Av.Ranking	5.05	5.16	7.37	4.89	9.95	10.42	10.00	8.74	10.47	10.26	6.21	11.42	6.58	4.89
1	Wilcoxon test Wilcoxon test	*	≈ ≈	≈ ≈	~	+ ≈	≈ ≈	+ ≈	≈ ≈	+ ≈	+ +	* *	* *	≈ ≈	~

Table 9 (Continued.)

Based on the results shown in Tables 8 and 9, we observe strong differences in the generalization capabilities of the algorithms when transitioning from low-dimensional to high-dimensional search spaces. In particular, CMAES_{LDOUT} and MTF_{LDOUT}, which obtained the best results on functions with dimensions $d = \{50, 100\}$, were outperformed by DE–CMAES_{250UT} and PSO–CMAES_{250UT} on functions with dimensions $d = \{750, 1250\}$. The implementations with better generalization in terms of scalability are PSO–CMAES_{LDOUT} and PSO–CMAES_{250UT}, which perform similarly on average on $f_{\text{BENCHMARK}}$, $f_{\text{CEC'14}}$, and f_{SOCO} irrespective of problem dimensionality. However, they consistently underperformed on HYB functions across all cases. Finally, we found that the algorithms trained on 250UT performed better than those trained on LDOUT on both HYB and LD functions, suggesting that the algorithm components useful for tackling HYB functions are also useful for tackling LD functions.

6 CONCLUSIONS

In this article, we have proposed **METAFO**, a metaheuristic software framework for PSO, CMA-ES, DE and LS algorithms applicable to single-objective continuous optimization problems. The main advantage of **METAFO**, is that it enables the creation of high-performance metaheuristic implementations using an automatic design approach, i.e., the selection of algorithm components and parameter settings in the implementation is done using an automatic algorithm configuration tool, such as irace, instead of relying on the expertise and intuition of a human algorithm designer. To develop **METAFO**, we considered a component-based architecture and four main modules (**PSOmod**, **DEmod** and **CMA-ESmod**), resulting in a total of 104 parameters, each representing either an algorithm component or a numerical parameter related to the use of a component. **METAFO**, allows three different types of hybridization, EXE-component-based, EXE-probabilistic and EXE-multiple phases, which were selected based on a brief literature review of prominent hybrids of PSO, CMA-ES and DE. The three main metaheuristic approaches included in **METAFO** (PSO, CMA-ES and DE) can be used alone or in combination, allowing users not only to replicate hundreds of single-approach and hybrid algorithms already proposed in the literature, but also to generate many new implementations never proposed before.

We have shown experimentally that **METAFO**R can be used to create implementations that outperform the state of the art on various metrics, as well as to create implementations that are tailored to specific problem classes. We compared a total of 17 algorithms and studied two popular "machine-learning"-type instance separation strategies often used in automatic design, namely the creation of a stratified training set using a fixed percentage (250UT) and leave-one-class-out cross-validation (LD0UT). Although neither instance separation strategy can be considered better than the other, we found that 250UT works well for HYB and LD functions, while LD0UT is a good strategy for lowdimensional functions with smoother search spaces, such as UNI and MUL functions. Also, based on the design of the best performing algorithms in our experimental study, we have identified strategies that can be used to guide the design of hybrid metaheuristics.

Of course, our work also has limitations and could be improved in a number of ways. One limitation is the fact that the number of components available in the literature is enormous, and it is impossible to imagine including all of them in **METAFO**. Another limitation is the type of hybridization currently available in **METAFO**. In particular, to keep things manageable, we have omitted some of the most complex types of hybridization and a number of components that can potentially provide better results. For future improvements to our work, we are considering the following: (i) incorporating other metaheuristic and local search approaches, such as artificial bee colony [5] and Powell's BOBYQA and NEWUOA [80, 81]; (ii) exploring hybridization with ML techniques, including deep learning and reinforcement learning hybrids; and (iii) integrating components from other metaheuristic software frameworks that have demonstrated their utility in experimental studies [55].

ACKNOWLEDGMENTS

Christian L. Camacho-Villalón acknowledges support from the SMASH postdoctoral fellowship program of Slovenia from which he is a MSCA fellow. Marco Dorigo and Thomas Stützle acknowledge support from the Belgian F.R.S.-FNRS, of which they are Research Directors.

REFERENCES

- [1] Niclas Andréasson, Anton Evgrafov, and Michael Patriksson. 2020. An Introduction to Continuous Optimization: Foundations and Fundamental Algorithms. Courier Dover Publications, Mineola, New York.
- [2] Claus Aranha, Christian Leonardo Camacho-Villalón, Felipe Campelo, Marco Dorigo, Rubén Ruiz, Marc Sevaux, Kenneth Sörensen, and Thomas Stützle. 2022. Metaphor-based Metaheuristics, a Call for Action: the Elephant in the Room. Swarm Intelligence 16, 1 (2022), 1–6. https://doi.org/10.1007/s11721-021-00202-9
- [3] Charles Audet and Warren Hare. 2017. Derivative-free and blackbox optimization. Springer, Berlin, Heidelberg, Germany.
- [4] Anne Auger and Nikolaus Hansen. 2005. A restart CMA evolution strategy with increasing population size. In Proceedings of the 2005 Congress on Evolutionary Computation (CEC 2005). IEEE Press, Piscataway, NJ, 1769–1776.
- [5] Doğan Aydın, Gürcan Yavuz, Serdar Özyön, Celal Yasar, and Thomas Stützle. 2017. Artificial Bee Colony Framework to Non-convex Economic Dispatch Problem with Valve Point Effects: A Case Study. In *GECCO'17 Companion*, Peter A. N. Bosman (Ed.). ACM Press, New York, NY, 1311– 1318.
- [6] Leonardo CT Bezerra, Manuel López-Ibáñez, and Thomas Stützle. 2020. Automatically Designing State-of-the-Art Multi-and Many-Objective Evolutionary Algorithms. Evolutionary Computation 28, 2 (2020), 195–226.
- [7] Leonardo César Teonácio Bezerra, Manuel López-Ibáñez, and Thomas Stützle. 2016. Automatic Component-Wise Design of Multi-Objective Evolutionary Algorithms. IEEE Transactions on Evolutionary Computation 20, 3 (2016), 403–417. https://doi.org/10.1109/TEVC.2015.2474158
- [8] Mauro Birattari, Zhi Yuan, Prasanna Balaprakash, and Thomas Stützle. 2010. F-Race and Iterated F-Race: An Overview. In Experimental Methods for the Analysis of Optimization Algorithms, Thomas Bartz-Beielstein, Marco Chiarandini, Luís Paquete, and Mike Preuss (Eds.). Springer, Berlin, Germany, 311–336.
- [9] Christian Blum and Günther R. Raidl. 2016. Hybrid Metaheuristics-Powerful Tools for Optimization. Springer, Berlin, Germany.
- [10] Rick Boks, Hao Wang, and Thomas Bäck. 2020. A modular hybridization of particle swarm optimization and differential evolution. In GECCO'20 Companion, Carlos Artemio Coello Coello (Ed.). ACM Press, New York, NY, 1418–1425. https://doi.org/10.1145/3377929.3398123

METAFOR: A Hybrid Metaheuristics Software Framework for Continuous Optimization Problems

- [11] Eric Bonabeau, Marco Dorigo, and Guy Theraulaz. 1999. Swarm intelligence: from natural to artificial systems. Oxford university press, New York, NY.
- [12] Mohammad Reza Bonyadi and Zbigniew Michalewicz. 2014. A locally convergent rotationally invariant particle swarm optimization algorithm. Swarm Intelligence 8, 3 (2014), 159–198. https://doi.org/10.1007/s11721-014-0095-1
- [13] Laura Calvet, Jésica de Armas, David Masip, and Angel A Juan. 2017. Learnheuristics: hybridizing metaheuristics with machine learning for optimization with dynamic inputs. Open Mathematics 15, 1 (2017), 261–280.
- [14] Christian Leonardo Camacho-Villalón, Marco Dorigo, and Thomas Stützle. 2021. PSO-X: A Component-Based Framework for the Automatic Design of Particle Swarm Optimization Algorithms: Supplementary material. http://iridia.ulb.ac.be/supp/IridiaSupp2021-001/.
- [15] Christian Leonardo Camacho-Villalón, Marco Dorigo, and Thomas Stützle. 2022. PSO-X: A Component-Based Framework for the Automatic Design of Particle Swarm Optimization Algorithms. *IEEE Transactions on Evolutionary Computation* 26, 3 (2022), 402–416. https://doi.org/10.1109/TEVC.2021.3102863
- [16] Christian Leonardo Camacho-Villalón, Marco Dorigo, and Thomas Stützle. 2023. Exposing the grey wolf, moth-flame, whale, firefly, bat, and antlion algorithms: six misleading optimization techniques inspired by bestial metaphors. *International Transactions in Operational Research* 30, 6 (2023), 2945–-2971. https://doi.org/10.1111/itor.13176
- [17] Christian Leonardo Camacho-Villalón, Thomas Stützle, and Marco Dorigo. 2023. Designing New Metaheuristics: Manual versus Automatic Approaches. Intelligent Computing 2, 0048 (2023), 1–15. https://doi.org/10.34133/icomputing.0048
- [18] Zhe Chen and Yuanxing Liu. 2022. Individuals redistribution based on differential evolution for covariance matrix adaptation evolution strategy. Scientific Reports 12, 1 (2022), 986.
- [19] Maurice Clerc. 2011. Standard Particle Swarm Optimisation from 2006 to 2011. open archive HAL hal-00764996. HAL.
- [20] Swagatam Das, Amit Konar, and Uday K Chakraborty. 2005. Improving particle swarm optimization with differentially perturbed velocity. In Proceedings of the 7th annual conference on Genetic and evolutionary computation. ACM Press, New York, NY, 177–184.
- [21] Swagatam Das and Ponnuthurai N. Suganthan. 2011. Differential Evolution: A Survey of the State-of-the-art. IEEE Transactions on Evolutionary Computation 15, 1 (Feb. 2011), 4–31.
- [22] Jacob de Nobel, Diederick Vermetten, Hao Wang, Carola Doerr, and Thomas Bäck. 2021. Tuning as a means of assessing the benefits of new ideas in interplay with existing algorithmic modules. In *GECCO'21 Companion*, Francisco Chicano (Ed.). ACM Press, New York, NY, 1375–1384. https://doi.org/10.1145/3449726.3463167
- [23] Kalyanmoy Deb. 2012. Optimization for engineering design: Algorithms and examples. PHI Learning Pvt. Ltd., New Delhi, India.
- [24] Javier Del Ser, Eneko Osaba, Daniel Molina, Xin-She Yang, Sancho Salcedo-Sanz, David Camacho, Swagatam Das, Ponnuthurai N Suganthan, Carlos A Coello Coello, and Francisco Herrera. 2019. Bio-inspired computation: Where we stand and what's next. Swarm and Evolutionary Computation 48 (2019), 220–250.
- [25] M. Dorigo and M. Birattari. 2007. Swarm Intelligence. Scholarpedia 2, 9 (2007), 1462. http://www.scholarpedia.org/article/Swarm_intelligence
- [26] Russell Eberhart and James Kennedy. 1995. A New Optimizer Using Particle Swarm Theory. In Proceedings of the Sixth International Symposium on Micro Machine and Human Science. IEEE Press, Piscataway, NJ, 39–43.
- [27] Michael G Epitropakis, Vassilis P Plagianakos, and Michael N Vrahatis. 2012. Evolving cognitive and social experience in particle swarm optimization through differential evolution: a hybrid approach. *Information Sciences* 216 (2012), 50–92.
- [28] David B. Fogel, Alvin J. Owens, and Michael J. Walsh. 1966. Artificial Intelligence Through Simulated Evolution. John Wiley & Sons, Chichester, UK.
- [29] Alberto Franzin and Thomas Stützle. 2019. Revisiting simulated annealing: A component-based analysis. Computers & Operations Research 104 (2019), 191-206. https://doi.org/10.1016/j.cor.2018.12.015
- [30] Michel Gendreau and Jean-Yves Potvin (Eds.). 2019. Handbook of Metaheuristics. International Series in Operations Research & Management Science, Vol. 272. Springer, New York, NY.
- [31] Saurav Ghosh, Swagatam Das, Subhrajit Roy, SK Minhazul Islam, and Ponnuthurai N Suganthan. 2012. A differential covariance matrix adaptation evolutionary algorithm for real parameter optimization. *Information Sciences* 182, 1 (2012), 199–219.
- [32] Fred Glover. 1986. Future Paths for Integer Programming and Links to Artificial Intelligence. Computers & Operations Research 13, 5 (1986), 533-549.
- [33] David Edward Goldberg. 1989. Genetic Algorithms in Search, Optimization and Machine Learning. Addison-Wesley, Boston, MA, USA.
- [34] Crina Grosan and Ajith Abraham. 2007. Hybrid evolutionary algorithms: methodologies, architectures, and reviews. In Hybrid evolutionary algorithms. Springer, Cham, 1–17.
- [35] Shu-Mei Guo and Chin-Chang Yang. 2014. Enhancing differential evolution utilizing eigenvector-based crossover operator. IEEE Transactions on Evolutionary Computation 19, 1 (2014), 31–49.
- [36] Michael Pilegaard Hansen. 1997. Tabu search for multiobjective optimization: MOTS. In Proceedings of the 13th International Conference on Multiple Criteria Decision Making (MCDM'97), J. Climaco (Ed.). Springer Verlag, Berlin, Heidelberg, Germany, 574–586.
- [37] Nikolaus Hansen. 2006. The CMA evolution strategy: a comparing review. In Towards a new evolutionary computation. Springer, Berlin, Heidelberg, Germany, 75–102.
- [38] Nikolaus Hansen. 2016. The CMA evolution strategy: A tutorial. CoRR abs/1604.00772 (2016), 1–39. arXiv:1604.00772 http://arxiv.org/abs/1604.00772

- [39] Nikolaus Hansen, Dirk V Arnold, and Anne Auger. 2015. Evolution strategies. In Springer handbook of computational intelligence. Springer, Berlin, Germany, 871–898.
- [40] Nikolaus Hansen, Sibylle D Müller, and Petros Koumoutsakos. 2003. Reducing the time complexity of the derandomized evolution strategy with covariance matrix adaptation (CMA-ES). Evolutionary computation 11, 1 (2003), 1–18.
- [41] Nikolaus Hansen and A. Ostermeier. 2001. Completely derandomized self-adaptation in evolution strategies. Evolutionary Computation 9, 2 (2001), 159–195. https://doi.org/10.1162/106365601750190398
- [42] Xiaoyu He and Yuren Zhou. 2018. Enhancing the performance of differential evolution with covariance matrix self-adaptation. Applied Soft Computing 64 (2018), 227–243.
- [43] Tim Hendtlass. 2001. A combined swarm differential evolution algorithm for optimization problems. In Engineering of Intelligent Systems: 14th International Conference on Industrial and Engineering Applications of Artificial Intelligence and Expert Systems, IEA/AIE 2001 Budapest, Hungary, June 4–7, 2001 Proceedings 14. Springer, Berlin, Germany, 11–18.
- [44] Francisco Herrera, Manuel Lozano, and D. Molina. 2010. Test suite for the special issue of Soft Computing on scalability of evolutionary algorithms and other metaheuristics for large scale continuous optimization problems. http://sci2s.ugr.es/eamhco/.
- [45] John Henry Holland. 1975. Adaptation in Natural and Artificial Systems. University of Michigan Press, Ann Arbor, Michigan, United States.
- [46] Holger H. Hoos and Thomas Stützle. 2005. Stochastic Local Search–Foundations and Applications. Morgan Kaufmann Publishers, San Francisco, CA.
- [47] Chang-Tai Hsieh, Chih-Ming Chen, and Ying-ping Chen. 2007. Particle swarm guided evolution strategy. In Proceedings of the 9th annual Conference on Genetic and Evolutionary Computation. ACM Press, New York, NY, 650–657.
- [48] Frank Hutter, Holger H. Hoos, and Kevin Leyton-Brown. 2011. Sequential Model-Based Optimization for General Algorithm Configuration. In Learning and Intelligent Optimization, 5th International Conference, LION 5, Carlos A. Coello Coello (Ed.). Lecture Notes in Computer Science, Vol. 6683. Springer, Heidelberg, Germany, Heidelberg, Germany, 507–523.
- [49] Frank Hutter, Holger H. Hoos, Kevin Leyton-Brown, and Thomas Stützle. 2009. ParamILS: An Automatic Algorithm Configuration Framework. Journal of Artificial Intelligence Research 36 (Oct. 2009), 267–306.
- [50] Jérôme Henri Kämpf and Darren Robinson. 2009. A hybrid CMA-ES and HDE optimisation algorithm with application to solar energy potential. Applied Soft Computing 9, 2 (2009), 738–745.
- [51] Dervis Karaboga et al. 2005. An idea based on honey bee swarm for numerical optimization. Technical Report. Technical report-tr06, Erciyes university, engineering faculty, computer
- [52] Dervis Karaboga and Bahriye Basturk. 2007. A powerful and efficient algorithm for numerical function optimization: artificial bee colony (ABC) algorithm. Journal of Global Optimization 39, 3 (2007), 459–471.
- [53] James Kennedy and Russell Eberhart. 1995. Particle swarm optimization. In Proceedings of ICNN'95-International Conference on Neural Networks, Vol. 4. IEEE, Piscataway, NJ, 1942–1948.
- [54] J. Kennedy, R. C. Eberhart, and Y. Shi. 2001. Swarm Intelligence. Morgan Kaufmann Publishers, San Francisco, CA, San Francisco, CA.
- [55] Ana Kostovska, Diederick Vermetten, Peter Korošec, Sašo Džeroski, Carola Doerr, and Tome Eftimov. 2024. Using Machine Learning Methods to Assess Module Performance Contribution in Modular Optimization Frameworks. Evolutionary computation (2024), 1–28.
- [56] Antonio LaTorre, Santiago Muelas, and José-María Peña. 2011. A MOS-based dynamic memetic differential evolution algorithm for continuous optimization: a scalability test. Soft Computing 15, 11 (2011), 2187–2199.
- [57] Guillermo Leguizamón and Carlos A Coello Coello. 2010. An Alternative ACO R Algorithm for Continuous Optimization Problems. In Swarm Intelligence: 7th International Conference, ANTS 2010, Brussels, Belgium, September 8-10, 2010. Proceedings 7. Springer, Berlin, Heidelberg, Germany, 48–59.
- [58] J.J. Liang, B.Y. Qu, and Ponnuthurai N. Suganthan. 2013. Problem definitions and evaluation criteria for the CEC 2014 special session and competition on single objective real-parameter numerical optimization. Technical Report. Computational Intelligence Laboratory, Zhengzhou University, Zhengzhou China and Technical Report, Nanyang Technological University, Singapore.
- [59] Tianjun Liao, Daniel Molina, Marco A. Montes de Oca, and Thomas Stützle. 2014. A Note on the Effects of Enforcing Bound Constraints on Algorithm Comparisons using the IEEE CEC'05 Benchmark Function Suite. Evolutionary Computation 22, 2 (2014), 351–359.
- [60] Tianjun Liao, Daniel Molina, and Thomas Stützle. 2015. Performance Evaluation of Automatically Tuned Continuous Optimizers on Different Benchmark Sets. Applied Soft Computing 27 (2015), 490–503.
- [61] Tianjun Liao, Marco A. Montes de Oca, and Thomas Stützle. 2013. Computational results for an automatically tuned CMA-ES with increasing population size on the CEC'05 benchmark set. Soft Computing 17, 6 (2013), 1031–1046. https://doi.org/10.1007/s00500-012-0946-x
- [62] Tianjun Liao and Thomas Stützle. 2013. Benchmark results for a simple hybrid algorithm on the CEC 2013 benchmark set for real-parameter optimization. In Proceedings of the 2013 Congress on Evolutionary Computation (CEC 2013). IEEE Press, Piscataway, NJ, 1938–1944.
- [63] Tianjun Liao, Thomas Stützle, Marco A. Montes de Oca, and Marco Dorigo. 2014. A Unified Ant Colony Optimization Algorithm for Continuous Optimization. European Journal of Operational Research 234, 3 (2014), 597–609.
- [64] Manuel López-Ibáñez, Jérémie Dubois-Lacoste, Leslie Pérez Cáceres, Thomas Stützle, and Mauro Birattari. 2016. The irace package: Iterated Racing for Automatic Algorithm Configuration. Operations Research Perspectives 3 (2016), 43–58. https://doi.org/10.1016/j.orp.2016.09.002
- [65] Manuel López-Ibáñez, Jérémie Dubois-Lacoste, Thomas Stützle, and Mauro Birattari. 2011. The irace package, Iterated Race for Automatic Algorithm Configuration. Technical Report TR/IRIDIA/2011-004. IRIDIA, Université Libre de Bruxelles, Belgium.

http://iridia.ulb.ac.be/IridiaTrSeries/IridiaTr2011-004.pdf

- [66] Manuel López-Ibáñez and Thomas Stützle. 2012. The Automatic Design of Multi-Objective Ant Colony Optimization Algorithms. IEEE Transactions on Evolutionary Computation 16, 6 (2012), 861–875. https://doi.org/10.1109/TEVC.2011.2182651
- [67] Manuel López-Ibáñez, Thomas Stützle, and Marco Dorigo. 2017. Ant Colony Optimization: A Component-Wise Overview. In Handbook of Heuristics, Rafael Martí, Panos M. Pardalos, and Mauricio G. C. Resende (Eds.). Springer International Publishing, Berlin, Heidelberg, Germany, 1–37. https://doi.org/10.1007/978-3-319-07153-4_21-1
- [68] David G Luenberger, Yinyu Ye, et al. 2016. Linear and Nonlinear Programming. Springer, Cham.
- [69] O. Maron and A. W. Moore. 1997. The Racing Algorithm: Model Selection for Lazy Learners. Artificial Intelligence Research 11, 1-5 (1997), 193-225.
- [70] Rui Mendes, James Kennedy, and José Neves. 2004. The fully informed particle swarm: simpler, maybe better. IEEE Transactions on Evolutionary Computation 8, 3 (2004), 204–210.
- [71] Daniel Molina, Manuel Lozano, Ana M Sánchez, and Francisco Herrera. 2011. Memetic algorithms based on local search chains for large scale continuous optimisation problems: MA-SSW-Chains. Soft Computing 15 (2011), 2201–2220.
- [72] Christian L Muller, Benedikt Baumgartner, and Ivo F Sbalzarini. 2009. Particle swarm CMA evolution strategy for the optimization of multi-funnel landscapes. In 2009 IEEE Congress on Evolutionary Computation. IEEE, Piscataway, NJ, 2685–2692.
- [73] Antonio J Nebro, Manuel López-Ibáñez, José García-Nieto, and Carlos A Coello Coello. 2023. On the automatic design of multi-objective particle swarm optimizers: experimentation and analysis. Swarm Intelligence 18 (2023), 105–139.
- [74] John A Nelder and Roger Mead. 1965. A simplex method for function minimization. The computer journal 7, 4 (1965), 308-313.
- [75] Jorge Nocedal and Stephen J. Wright. 2006. Numerical Optimization (second ed.). Springer, Berlin, Heidelberg, Germany.
- [76] Mahamed GH Omran, Andries P Engelbrecht, and Ayed Salman. 2007. Differential evolution based particle swarm optimization. In 2007 IEEE Swarm Intelligence Symposium. IEEE, Piscataway, NJ, 112–119.
- [77] Federico Pagnozzi and Thomas Stützle. 2019. Automatic design of hybrid stochastic local search algorithms for permutation flowshop problems. European Journal of Operational Research 276, 2 (2019), 409–421.
- [78] Millie Pant, Radha Thangaraj, Crina Grosan, and Ajith Abraham. 2008. Hybrid differential evolution-particle swarm optimization algorithm for solving global optimization problems. In 2008 Third International Conference on Digital Information Management. IEEE, Piscataway, NJ, 18–24.
- [79] Michael JD Powell. 1964. An efficient method for finding the minimum of a function of several variables without calculating derivatives. The computer journal 7, 2 (1964), 155–162.
- [80] Michael JD Powell. 2002. UOBYQA: unconstrained optimization by quadratic approximation. Mathematical Programming 92, 3 (2002), 555-582.
- [81] Michael JD Powell. 2006. The NEWUOA software for unconstrained optimization without derivatives. In Large-scale nonlinear optimization. Springer, Berlin, Heidelberg, Germany, 255–297.
- [82] Kenneth Price, Rainer M. Storn, and Jouni A. Lampinen. 2005. Differential Evolution: A Practical Approach to Global Optimization. Springer, New York, NY, New York, NY.
- [83] I. Rechenberg. 1971. Evolutionsstrategie: Optimierung technischer Systeme nach Prinzipien der biologischen Evolution. Ph. D. Dissertation. Department of Process Engineering, Technical University of Berlin.
- [84] I. Rechenberg. 1973. Evolutionsstrategie: Optimierung technischer Systeme nach Prinzipien der biologischen Evolution. Frommann-Holzboog, Stuttgart, Germany.
- [85] Toby J Richer and Tim Blackwell. 2006. The Lévy particle swarm. In Proceedings of the 2006 Congress on Evolutionary Computation (CEC 2006). IEEE Press, Piscataway, NJ, 808–815.
- [86] Raymond Ros and Nikolaus Hansen. 2008. A simple modification in CMA-ES achieving linear time and space complexity. In Parallel Problem Solving from Nature–PPSN X: 10th International Conference, Dortmund, Germany, September 13-17, 2008. Proceedings 10. Springer, Berlin, Heidelberg, Germany, 296–305.
- [87] Hans-Paul Schwefel. 1977. Numerische Optimierung von Computer-Modellen mittels der Evolutionsstrategie. Birkhäuser, Basel, Switzerland.
- [88] Hans-Paul Schwefel. 1981. Numerical Optimization of Computer Models. John Wiley & Sons, Inc., Chichester, UK.
- [89] Yuhui Shi and Russell Eberhart. 1998. A modified particle swarm optimizer. In Proceedings of the 1998 IEEE International Conference on Evolutionary Computation (ICEC'98), Patrick K. Simpson, Karen Haines, Jacek Zurada, and David Fogel (Eds.). IEEE Press, Piscataway, NJ, 69–73.
- [90] Urban Škvorc, Tome Eftimov, and Peter Korošec. 2019. CEC real-parameter optimization competitions: Progress from 2013 to 2018. In 2019 IEEE congress on evolutionary computation (CEC). IEEE, Piscataway, NJ, 3126–3133.
- [91] K. Socha and Marco Dorigo. 2008. Ant Colony Optimization for Continuous Domains. European Journal of Operational Research 185, 3 (2008), 1155–1173. https://doi.org/10.1016/j.ejor.2006.06.046
- [92] Kenneth Sörensen and Fred Glover. 2013. Metaheuristics. In Encyclopedia of Operations Research and Management Science (3 ed.), Saul I Gass and Michael C Fu (Eds.). Springer Verlag, Berlin, Heidelberg, Germany, 960–970.
- [93] Rainer Storn and Kenneth Price. 1997. Differential Evolution A Simple and Efficient Heuristic for Global Optimization over Continuous Spaces. Journal of Global Optimization 11, 4 (1997), 341–359.
- [94] Thomas Stützle and Manuel López-Ibáñez. 2019. Automated Design of Metaheuristic Algorithms. See [30], 541–579. https://doi.org/10.1007/978-3-319-91086-4_17
- [95] Ponnuthurai N. Suganthan, Nikolaus Hansen, J. J. Liang, Kalyanmoy Deb, Y. P. Chen, A. Auger, and S. Tiwari. 2005. Problem definitions and evaluation criteria for the CEC 2005 special session on real-parameter optimization. Technical Report. Nanyang Technological University, Singapore.

- [96] E-G. Talbi (Ed.). 2013. Hybrid Metaheuristics. Studies in Computational Intelligence, Vol. 434. Springer Verlag, Berlin, Heidelberg, Germany. http://www.springer.com/engineering/computational+intelligence+and+complexity/book/978-3-642-30670-9
- [97] Lin-Yu Tseng and Chun Chen. 2008. Multiple trajectory search for large scale global optimization. In 2008 IEEE congress on evolutionary computation (IEEE world congress on computational intelligence). IEEE, Piscataway, NJ, 3052–3059.
- [98] Diederick Vermetten, Fabio Caraffini, Anna V Kononova, and Thomas Bäck. 2023. Modular differential evolution. In Proceedings of the Genetic and Evolutionary Computation Conference. ACM Press, New York, NY, 864–872.
- [99] Peilan Xu, Wenjian Luo, Xin Lin, Yingying Qiao, and Tao Zhu. 2019. Hybrid of PSO and CMA-ES for global optimization. In 2019 IEEE congress on evolutionary computation (CEC). IEEE, Piscataway, NJ, 27–33.
- [100] Mauricio Zambrano-Bigiarin, Maurice Clerc, and Rodrigo Rojas. 2013. Standard particle swarm optimisation 2011 at cec-2013: A baseline for future pso improvements. In Proceedings of the 2013 Congress on Evolutionary Computation (CEC 2013). IEEE Press, Piscataway, NJ, 2337–2344.
- [101] Wen-Jun Zhang and Xiao-Feng Xie. 2003. DEPSO: hybrid particle swarm with differential evolution operator. In SMC'03 Conference Proceedings. 2003 IEEE International Conference on Systems, Man and Cybernetics. Conference Theme-System Security and Assurance (Cat. No. 03CH37483), Vol. 4. IEEE, Piscataway, NJ, 3816–3821.