Florian Frank 🖂 💿

Friedrich-Alexander-Universität Erlangen-Nürnberg, Germany

# Stefan Milius ⊠ Friedrich-Alexander-Universität Erlangen-Nürnberg, Germany

#### Jurriaan Rot 🖂 🗅

Institute for Computing and Information Sciences, Radboud University, Nijmegen, the Netherlands

# Henning Urbat 🖂 🗅

Friedrich-Alexander-Universität Erlangen-Nürnberg, Germany

#### — Abstract

Automata over infinite alphabets have emerged as a convenient computational model for processing structures involving data, such as nonces in cryptographic protocols or data values in XML documents. We introduce active learning methods for *bar automata*, a species of automata that process finite data words represented as bar strings, which are words with explicit name binding letters. Bar automata have pleasant algorithmic properties. We develop a framework in which *every* learning algorithm for standard deterministic or nondeterministic finite automata over finite alphabets can be used to learn bar automata, with a query complexity determined by that of the chosen learner. The technical key to our approach is the algorithmic handling of  $\alpha$ -equivalence of bar strings, which allows to bridge the gap between finite and infinite alphabets. The principles underlying our framework are generic and also apply to bar Büchi automata and bar tree automata, leading to the first active learning methods for data languages of infinite words and finite trees.

2012 ACM Subject Classification Theory of Computation  $\rightarrow$  Formal Languages

Keywords and phrases Data Languages, Nominal Sets, Languages with Binders, Automata Learning

**Funding** Florian Frank: Supported by the Deutsche Forschungsgemeinschaft (DFG) as part of the Research and Training Group 2475 "Cybercrime and Forensic Computing" (393541319/GRK2475/2-2024)

Stefan Milius: Supported by the DFG (German Research Foundation) – project number 419850228 Henning Urbat: Supported by the DFG (German Research Foundation) – project number 470467389

# 1 Introduction

Active automata learning is a family of techniques for inferring an automaton from a blackbox system, by interacting with this system and making observations about its behaviour. Originally introduced by Angluin [3], the celebrated  $L^*$  algorithm allows to effectively learn deterministic finite automata in this way. Since her work, automata learning has been combined with model checking and conformance testing techniques [45], turning it into an effective tool for bug finding. Indeed, automata learning algorithms have been used to analyze and learn models of network protocols (e.g. [21–23]), legacy code [5,50], embedded software [51] and interfaces of software components [28]; see [30,54] for further references.

In addition, Angluin's original  $L^*$  algorithm has been improved in various ways. State-ofthe-art algorithms such as TTT [32] and  $L^{\#}$  [55] may substantially reduce the number of queries needed during learning. Orthogonally there have been numerous extensions of L\*-type algorithms to models beyond classical deterministic finite automata, including for example nondeterministic finite automata [9], Mealy machines [40], quantitative automata [6,27], tree automata [19,35], automata for languages of infinite words [4,20,38,39], and, most relevant for this paper, automata over infinite alphabets, namely register automata [2,10,12,18],

2

data automata [15] and nominal automata [42,43]. Infinite alphabets represent data, for example, nonces in cryptographic protocols [37], data values in XML documents [44], object identities [25], or parameters of method calls [29]. The principal challenge for all learning algorithms for data languages is to cleverly represent infinite data by finite means.

In the present paper, we study the theoretical and algorithmic aspects of active learning of *bar automata*, a species of non-deterministic automata for data languages introduced in recent years in versions for finite data words (*bar word automata*) [49], infinite data words (*bar Büchi automata*) [52] and finite data trees (*bar tree automata*) [47]. Bar automata yield a finite representation of corresponding nominal models with explicit name allocation, namely regular non-deterministic nominal automata (RNNAs) [49], Büchi RNNAs [52] and regular non-deterministic nominal tree automata (RNTAs) [52], respectively. For Büchi RNNAs and RNTAs, these exact correspondences are new results (Theorem 3.11), and the constructions underlying the proof will feature crucially in our learning algorithms.

The key difference between bar automata and other models for data languages, such as non-deterministic register automata [33, 34] or the equivalent non-deterministic nominal orbit-finite automata [8], is the use of *binding transitions* while at the same time restricting to finite (rather than orbit-finite) branching. In this way, bar automata retain a reasonable level of expressivity; they correspond to a proper subclass of non-deterministic register automata and are incomparable to deterministic ones. The central feature of bar automata are their very pleasant algorithmic properties: most notably, the language inclusion problem is decidable in space polynomial in the size of the automata and exponential in their *degree*, which corresponds to the number of registers. This is in sharp constrast to standard nondeterministic register automata where inclusion is undecidable for automata with more than two registers [33] (or one register in terms of the definition by Demri und Lazić [16]).

The standard semantics of bar automata is at the level of *bar languages*. For instance, bar word automata consume *bar strings*, which are finite words formed from *plain letters a* and *bar letters* |*a* with *a* taken from an infinite domain  $\mathbb{A}$  of names (representing data values). Intuitively, a bar string is a pattern that determines how letters are read from the input and stored in memory for future comparison, where an occurrence of |*a* is interpreted as reading an input letter and binding this letter to the name *a*. Accordingly, bar word languages are sets of bar strings modulo an obvious notion of  $\alpha$ -equivalence induced by capture avoiding renaming of bound letters. Bar word languages can be interpreted as data word languages (i.e. sets of words over  $\mathbb{A}$  without bar letters) in two ways corresponding to two slightly different disciplines of  $\alpha$ -renaming of bound names: *global freshness* means that binding transitions read names which have not occured before (as in session automata [11]), and *local freshness* means that names are not currently stored in memory (as in register automata). Similar principles apply to bar languages of infinite bar strings and bar trees, which are trees over a finite signature where every symbol is annotated with a bar/plain letter.

Our main contribution is an active learning method for bar automata that applies uniformly to bar word, bar Büchi and bar tree automata. More specifically, we demonstrate that *any* learning algorithm for classical automata over (in)finite words or trees can be extended to a learning algorithm for the associated type of bar automata; our extension is agnostic to the choice of the underlying learning algorithm. The key technical idea to our approach is to reduce the problem of learning an unknown bar language to learning a canonical representation over a restricted, finite subalphabet. This representation, whose language is closed under  $\alpha$ -equivalence w.r.t. to the finite subalphabet, is itself a regular language over a finite alphabet, making it amenable to classical learning.

However, this reduction is far from immediate: there is a mismatch in the types of

counterexamples that the learner receives. To see this, let us recall Angluin's minimally adequate teacher (MAT) framework, which allows the learner to pose membership queries ('is this input in the language?') and equivalence queries ('is this hypothesis automaton  $\mathcal{H}$  correct?') to an oracle. For equivalence queries, the oracle returns a counterexample whenever  $\mathcal{H}$  is incorrect. This is precisely where the difficulty lies: this counterexample may not be useful to learn the canonical representation of the language over the subalphabet.

The core ingredient to match these counterexamples and resolve this mismatch is to effectively find  $\alpha$ -equivalent words over the subalphabet. We therefore introduce new techniques for checking  $\alpha$ -equivalence of (in)finite bar strings and bar trees. Our methods for deciding  $\alpha$ -equivalence are non-trivial and, moreover, of independent interest, as they do not just arise in automata learning but potentially also in other algorithms handling bar automata, such as minimization, reduction, or model checking. By combining these techniques for  $\alpha$ -equivalence and our reductions with known algorithms for learning word/tree automata or automata over infinite words, we thus obtain learning algorithms for bar languages over each of these variants. By learning bar automata and interpreting them under local or global freshness semantics, our algorithms can be understood as learning data languages. The classes of data languages learnable in this way are incomparable to existing learning algorithms for register or nominal automata; see 'Related Work' below and Section 3.3.

In summary, the main contributions of this paper are twofold: (1) We give a reduction of the problem of learning bar automata to that of learning classical automata for regular languages of finite words, infinite words, or finite trees; and (2) we develop an approach for effectively checking  $\alpha$ -equivalence of finite and infinite bar strings as well as bar trees.

**Related Work.** Learning automata models for data languages of finite words without explicit binding is an active area of research. Bollig et al. [10] introduced a learning algorithm for *session automata*, which are register automata requiring some data values to be *fresh* for the whole string. They are equivalent to a subclass of bar word automata under global freshness [49]. Their learning algorithm uses a somewhat similar idea to ours in that it reduces the learning problem to the  $L^*$  algorithm for deterministic finite automata. Our algorithm can learn a non-deterministic, hence more succinct representation of session automata.

Cassel et al. [12] and Dierl et al. [18] learn 'determinate' register automata on finite words, which are semantically equivalent to deterministic ones and are incomparable to bar automata under local freshness. Similarly, Aarts et al. [1] learn deterministic register automata with outputs which are again incomparable to bar automata under local freshness. Moerman et al. [42, 43] present learning algorithms for deterministic nominal automata as well as for *residual* non-deterministic nominal automata on finite words. Residual nominal automata are incomparable to bar automata under local freshness (Example 3.13).

To the best of our knowledge, there is no prior work on learning either Büchi or tree data languages. Our contributions yield learning algorithms for subclasses of both kinds.

# 2 Active Automata Learning

Automata learning is about systematically inferring an automaton for an unknown language  $L_{\mathsf{T}}$ . Most approaches are based on Angluin's framework [3] of a minimally adequate teacher (MAT), a game between a learner that aims to infer  $L_{\mathsf{T}}$ , and a teacher that the learner can ask for pieces of information about  $L_{\mathsf{T}}$ . To this end, the learner runs an algorithm generating a sequence  $\mathcal{H}_1, \mathcal{H}_2, \mathcal{H}_3, \ldots$  of automata (hypotheses) that yield increasingly improved approximations of  $L_{\mathsf{T}}$ . To improve the current hypothesis  $\mathcal{H}_i$ , the learner can direct

two types of questions to the teacher: membership queries ('is a given input in  $L_{\mathsf{T}}$ ?') and equivalence queries ('is the hypothesis  $\mathcal{H}_i$  correct, i.e. accepting  $L_{\mathsf{T}}$ ?'). The teacher's reply to an equivalence query is either 'Yes', in which case the learner has successfully inferred  $L_{\mathsf{T}}$ , or a counterexample, that is, an input on which  $\mathcal{H}_i$  and  $L_{\mathsf{T}}$  differ. Note that inputs of membership queries are chosen by the learner, making this setting active. In contrast, in passive learning only a fixed set of examples of elements and non-elements of  $L_{\mathsf{T}}$  is given. Active learning has been studied for numerous automata models. We consider three cases:

**Finite Automata.** A (non-)deterministic finite automaton (DFA/NFA)  $\mathscr{A} = (Q, A, \rightarrow, q_0, F)$ is given by a finite set Q of states, a finite input alphabet A, an initial state  $q_0 \in Q$ , final states  $F \subseteq Q$  and a transition relation  $\rightarrow \subseteq Q \times A \times Q$ , which in the deterministic case forms a function from  $Q \times A$  to Q. The language  $L_0(\mathscr{A}) \subseteq A^*$  accepted by  $\mathscr{A}$  is the set of all finite words  $w = a_1 \cdots a_n$  for which there exists an accepting run, that is, a sequence of transitions  $q_0 \xrightarrow{a_1} q_1 \xrightarrow{a_2} \cdots \xrightarrow{a_n} q_n$  ending in a final state. Languages accepted by finite automata are called *regular*. In MAT-based learning algorithms for finite automata, one assumes an unknown regular language  $L_{\mathsf{T}} \subseteq A^*$  (with known alphabet A) and admits the learner to put the following types of queries to the teacher: **Membership Queries (MQ):** Given  $w \in A^*$ , is  $w \in L_{\mathsf{T}}$ ?

Equivalence Queries (EQ): Given a hypothesis (i.e. a finite automaton)  $\mathcal{H}$ , is  $L_0(\mathcal{H}) = L_T$ ? If not, then the teacher returns a word in the symmetric difference<sup>1</sup>  $L_0(\mathcal{H}) \oplus L_T$ .

The classical learning algorithm for DFAs is Angluin's  $L^*$  [3], which learns the minimal DFA for  $L_T$  with a number of queries polynomial in the number of states of that DFA and the maximum length of the counterexamples provided by the teacher. Several improvements of L<sup>\*</sup> have been proposed [32, 36, 48, 55], based on clever counterexample handling and/or enhanced data structures for representing the information gained so far. Additionally, L<sup>\*</sup> has been extended by Bollig et al. [9] to a learning algorithm NL<sup>\*</sup> for NFAs.

**Büchi Automata.** A Büchi automaton is an NFA  $\mathscr{A} = (Q, A, \rightarrow, q_0, F)$  interpreted over infinite words. The language  $L_0(\mathscr{A}) \subseteq A^{\omega}$  accepted by  $\mathscr{A}$  is given by those infinite words  $w = a_1 a_2 a_3 \cdots$  with an accepting run, that is, an infinite sequence of transitions  $q_0 \xrightarrow{a_1} q_1 \xrightarrow{a_2} q_2 \xrightarrow{a_3} \cdots$  where some final state occurs infinitely often. Languages accepted by Büchi automata are called *regular*  $\omega$ -languages. Any such language is uniquely determined by its *ultimately periodic words*, i.e. words of the form  $uv^{\omega}$  with  $u \in A^*$  and  $v \in A^+$  [41]. An ultimately periodic word  $uv^{\omega}$  can be finitely represented by the pair (u, v); this representation is not unique since different pairs  $(u_1, v_1)$  and  $(u_2, v_2)$  may satisfy  $u_1v_1^{\omega} = u_2v_2^{\omega}$ .

Learning an unknown regular  $\omega$ -language  $L_{\mathsf{T}} \subseteq A^{\omega}$  in the MAT framework involves Membership Queries (MQ): Given  $(u, v) \in A^* \times A^+$ , is  $uv^{\omega} \in L_{\mathsf{T}}$ ?

Equivalence Queries (EQ): Given a hypothesis (i.e. a Büchi automaton)  $\mathcal{H}$ , is  $L_0(\mathcal{H}) = L_T$ ? If not, then the teacher returns a pair  $(u, v) \in A^* \times A^+$  such that  $uv^{\omega} \in L_0(\mathcal{H}) \oplus L_T$ .

There are active learning algorithms for regular  $\omega$ -languages that infer Büchi automata [20] or their representation via families of DFAs [4,38]). These build on the standard L<sup>\*</sup> to learn the set of ultimately periodic words of  $L_{T}$ , from which a Büchi automaton can be derived.

**Tree Automata.** A signature  $\Sigma$  is a set of symbols  $f, g, h, \cdots$  each with a finite arity  $n \in \mathbb{N}$ . We denote an *n*-ary symbol f by f/n. A  $\Sigma$ -tree is a finite ordered tree where every node

<sup>&</sup>lt;sup>1</sup> Recall that the symmetric difference of two sets X and Y is given by  $X \oplus Y = X \setminus Y \cup Y \setminus X$ .

is labeled with some symbol  $f \in \Sigma$  and its number of successors is the arity of f. Thus,  $\Sigma$ -trees correspond to syntax trees, or equivalently terms over the signature  $\Sigma$ . We write  $\mathcal{T}_{\Sigma}$  for the set of  $\Sigma$ -trees. A *(non-)deterministic bottom-up finite tree automaton (DFTA/NFTA)*  $\mathscr{A} = (Q, \Sigma, \Delta, F)$  is given by a finite set Q of states, a finite signature  $\Sigma$ , a set  $F \subseteq Q$  of final states, and a transition relation  $\Delta \subseteq (\coprod_{f/n \in \Sigma} Q^n) \times Q$ , which in the deterministic case forms a function from  $\coprod_{f/n \in \Sigma} Q^n$  to Q. The *language*  $L_0(\mathscr{A}) \subseteq \mathcal{T}_{\Sigma}$  accepted by  $\mathscr{A}$  is given by those  $\Sigma$ -trees t with an accepting run, i.e. where the nodes of t can be labeled with states from Q in such a way that the labels respect transitions (if the node  $f(t_1, \ldots, t_n)$  has label q and  $t_1, \ldots, t_n$  have labels  $q_1, \ldots, q_n$  then  $((f, q_1, \ldots, q_n), q) \in \Delta)$  and the root is labeled with a final state. Languages accepted by finite tree automata are called *regular tree languages*.

Learning an unknown regular tree language  $L_{\mathsf{T}} \subseteq \mathcal{T}_{\Sigma}$  in the MAT framework involves **Membership Queries** (**MQ**): Given  $t \in \mathcal{T}_{\Sigma}$ , is  $t \in L_{\mathsf{T}}$ ?

Equivalence Queries (EQ): Given a hypothesis (i.e. tree automaton)  $\mathcal{H}$ , is  $L_0(\mathcal{H}) = L_T$ ?. If not, then the teacher returns a tree  $t \in L_0(\mathscr{A}) \oplus L_T$ .

Active learning algorithms for regular tree languages have been studied by Drewes and Högberg [19] for DFTAs, and later extended by Kasprzik [35] to (residual) NFTAs.

# **3** Bar Languages and Automata

We aim to extend the scope of the above learning algorithms to languages and automata over infinite alphabets, namely *bar languages* and *bar automata*. We next review several versions of bar languages, and their associated automata models, introduced in earlier work [47,49,52].

# 3.1 Nominal Sets

Bar languages are most conveniently presented within the framework of nominal sets [46], which offers an abstract approach to dealing with notions of name binding,  $\alpha$ -equivalence and freshness. Let us recall some basic terminology from the theory of nominal sets.

For the rest of the paper, we fix a countably infinite set  $\mathbb{A}$  of *names*, which for our purposes play the role of *data values*. A *finite permutation of*  $\mathbb{A}$  is a bijective map  $\pi: \mathbb{A} \to \mathbb{A}$  such that  $\pi(a) = a$  for all but finitely many  $a \in \mathbb{A}$ . We denote by  $\mathsf{Perm}(\mathbb{A})$  the group of all finite permutations, with multiplication given by composition. The group  $\mathsf{Perm}(\mathbb{A})$  is generated by the *transpositions*  $(a \ b)$  for  $a \neq b \in \mathbb{A}$ ; recall that  $(a \ b)$  swaps a and b, while fixing all  $c \in \mathbb{A} \setminus \{a, b\}$ . A  $\mathsf{Perm}(\mathbb{A})$ -set is a set X equipped with a group action  $\cdot: \mathsf{Perm}(\mathbb{A}) \times X \to X$ , denoted by  $(\pi, x) \mapsto \pi \cdot x$ . A subset  $S \subseteq \mathbb{A}$  supports the element  $x \in X$  if  $\pi \cdot x = x$  for every  $\pi \in \mathsf{Perm}(\mathbb{A})$  such that  $\pi(a) = a$  for all  $a \in S$ . A *nominal set* is a  $\mathsf{Perm}(\mathbb{A})$ -set Xsuch that every element  $x \in X$  has a finite support. This implies that x has a least finite support, denoted by  $\mathsf{supp} x \subseteq \mathbb{A}$ . A name  $a \in \mathbb{A}$  is *fresh* for x, denoted a # x, if  $a \notin \mathsf{supp} x$ . Intuitively, we think of an element x of a nominal set as some sort of syntactic object (e.g. a string, tree, term) and of  $\mathsf{supp} x \subseteq \mathbb{A}$  as the (finite) set of names occurring freely in x.

A subset Y of a nominal set X is *equivariant* if  $y \in Y$  implies  $\pi \cdot y \in Y$  for all  $\pi \in \mathsf{Perm}(\mathbb{A})$ . We write  $X \times Y$  for the cartesian product of a pair X, Y of nominal sets with coordinatewise action. Given a nominal set X equipped with an equivariant equivalence relation  $\approx \subseteq X \times X$ , we write  $X/\approx$  for the nominal quotient set with the group action  $\pi \cdot [x]_{\approx} = [\pi \cdot x]_{\approx}$ .

Abstraction sets play a vital role in the theory of nominal sets and provide semantics for binding mechanisms [24]. Given a nominal set X, we define the equivariant equivalence relation  $\approx$  on  $\mathbb{A} \times X$  by  $(a, x) \approx (b, y)$  iff  $(a \ c) \cdot x = (b \ c) \cdot y$  for some, or equivalently all, fresh names c. The abstraction set  $[\mathbb{A}]X$  is the nominal quotient set  $(\mathbb{A} \times X)/\approx$ . The  $\approx$ -equivalence class of  $(a, x) \in \mathbb{A} \times X$  is denoted by  $\langle a \rangle x$ . We may think of  $\approx$  as an

abstract notion of  $\alpha$ -equivalence and of  $\langle a \rangle x$  as binding the name a in x. Indeed, we have  $\operatorname{supp}(\langle a \rangle x) = \operatorname{supp} x \setminus \{a\}$  (while  $\operatorname{supp}(a, x) = \{a\} \cup \operatorname{supp} x$ ), as expected in binding constructs.

▶ **Example 3.1.** The set A with the Perm(A)-action  $\pi \cdot a = \pi(a)$  is a nominal set, as is the set A<sup>\*</sup> of finite words over A with the letterwise action  $\pi \cdot (a_1 \cdots a_n) = \pi(a_1) \cdots \pi(a_n)$ . The least support of  $a_1 \cdots a_n \in A^*$  is the set  $\{a_1, \ldots, a_n\}$  of its letters. For  $a, b \in A$  we have  $\langle a \rangle aa = \langle b \rangle bb$  in the abstraction set  $[A]A^*$ , but  $\langle a \rangle ab \neq \langle b \rangle bb$  if  $a \neq b$ .

# 3.2 Bar Languages

We will work with languages of finite words, infinite words, and finite trees with binding constructs, called *bar word languages* [49], *bar*  $\omega$ -*languages* [52], and *bar tree languages* [47]. Bar languages represent *data languages*, i.e. languages over the infinite alphabet A.

**Data and Bar Word Languages.** A bar string is a finite word over A (the data domain) where a bar symbol ('1') might precede names to indicate that the next letter is bound until the end of the word. Intuitively, a bar string can be seen as a pattern that determines the way letters are read from the input: an occurrence of |a| corresponds to reading a letter from the input and binding this letter to the name a, while a free (i.e. unbound) occurrence of a means that a occurs literally in the input. Bound names can be *renamed*, giving rise to a notion of  $\alpha$ -equivalence of bar strings. The new name must be *fresh*, i.e. cannot occur freely in the scope of the binding. For instance, in ba|bab the | binds the letter b in |bab. The string ba|bab therefore is  $\alpha$ -equivalent to ba|cac, but not to ba|aaa, since a occurs freely in |bab.

These intuitions are formalized as follows. We put  $\overline{\mathbb{A}} = \mathbb{A} \cup \{ |a| | a \in \mathbb{A} \}$  and refer to elements  $|a \text{ of } \overline{\mathbb{A}} \text{ as } bar names$ , and to elements  $a \in \mathbb{A}$  as plain names. A bar string is a finite word  $w = \alpha_1 \cdots \alpha_n \in \overline{\mathbb{A}}^*$ , with length |w| = n. We turn  $\overline{\mathbb{A}}$  into a nominal set with the group action given by  $\pi \cdot a = \pi(a)$  and  $\pi \cdot |a| = |\pi(a)$ ; then also  $\overline{\mathbb{A}}^*$  is a nominal set with group action  $\pi \cdot (\alpha_1 \cdots \alpha_n) = (\pi \cdot \alpha_1) \cdots (\pi \cdot \alpha_n)$ . We define  $\alpha$ -equivalence on bar strings to be the equivalence relation generated by  $w|av \equiv_{\alpha} w|bu$  if  $\langle a \rangle v = \langle b \rangle u$  in  $[\mathbb{A}]\overline{\mathbb{A}}^*$ , and write  $[w]_{\alpha}$  for the  $\alpha$ -equivalence class of w. A name a is free in a bar string w if there is an occurrence of the plain name a in w that is to the left of the first occurrence (if any) of |a. We write  $\mathsf{FN}(w)$  for the set of free names in w. A bar string w is closed if  $\mathsf{FN}(w) = \emptyset$ . It is clean if all bar names |a| in w are pairwise distinct, and for all bar names |a| in w one has  $a \notin \mathsf{FN}(w)$ .

**Example 3.2.** We have  $FN(ba|bab) = \{a, b\}$ , and  $ba|bab \equiv_{\alpha} ba|cac$  for all  $c \neq a$ .

Finite bar strings give rise to three different types of languages:

▶ **Definition 3.3.** A data word language or literal word language is, respectively, a subset of  $\mathbb{A}^*$  or  $\mathbb{\bar{A}}^*$ . A bar word language is a literal language  $L \subseteq \mathbb{\bar{A}}^*$  closed under  $\alpha$ -equivalence, that is, if  $w \in L$  and  $w \equiv_{\alpha} w'$  then  $w' \in L$ .

▶ Remark 3.4. Schröder et al. [49] defined bar word languages as subsets of the quotient  $\overline{\mathbb{A}}^*/\equiv_{\alpha}$ . This definition is equivalent to ours: A bar word language  $L \subseteq \overline{\mathbb{A}}^*$  can be identified with the subset  $L' \subseteq \overline{\mathbb{A}}^*/\equiv_{\alpha}$  given by  $L' = \{[w]_{\alpha} \mid w \in L\}$ , and conversely every  $L' \subseteq \overline{\mathbb{A}}^*/\equiv_{\alpha}$  yields the bar word language  $L = \{w \in \overline{\mathbb{A}}^* \mid [w]_{\alpha} \in L'\}$ . These constructions are mutually inverse. An analogous remark also applies to bar  $\omega$ -languages and bar tree languages introduced below. We prefer the present definition, as it allows for simpler notation.

Every bar word language  $L \subseteq \overline{\mathbb{A}}^*$  can be converted into a data word language by interpreting name binding as reading either *globally fresh* letters (letters that have not been read before)

or *locally fresh* letters (letters not currently stored in memory). These two interpretations arise from two disciplines of  $\alpha$ -renaming as known from  $\lambda$ -calculus [7], with global freshness corresponding to a discipline of *clean* renaming where bound names are never shadowed and *local freshness* corresponding to an unrestricted naming discipline that allows shadowing. Formally, let  $ub(w) \in \mathbb{A}^*$  emerge from  $w \in \mathbb{A}^*$  by erasing all bars; for example, ub(balbab) =*babab*. Then the data languages  $D(L) \subseteq \mathbb{A}^*$  and  $N(L) \subseteq \mathbb{A}^*$  are defined by

$$D(L) = \{\mathsf{ub}(w) \mid w \in L\} \quad \text{and} \quad N(L) = \{\mathsf{ub}(w) \mid w \in L, w \text{ is clean}\}.$$
(1)

Thus D(L) and N(L) yield, respectively, a local and global freshness interpretation of L.

The operator N is injective (in fact, preserves and reflects inclusion) on bar word languages containing only closed bar strings [49, Lemma A.3]. Hence, such bar languages can be identified with their corresponding data languages under global freshness semantics.

**Data and Bar**  $\omega$ -Languages. In addition to finite bar strings, we also consider *infinite bar* strings, which are infinite words over  $\overline{\mathbb{A}}$ . We let  $\overline{\mathbb{A}}^{\omega}$  denote the set of infinite bar strings; unlike  $\overline{\mathbb{A}}^*$  this is not a nominal set under the letterwise group action since infinite bar strings need not be finitely supported. Free names are defined analogously to finite bar strings. Moreover, the notion of  $\alpha$ -equivalence extends to infinite bar strings [52] as follows:

▶ **Definition 3.5.** Two infinite bar strings  $v, w \in \overline{\mathbb{A}}^{\omega}$  are  $\alpha$ -equivalent (notation  $v \equiv_{\alpha} w$ ) iff  $v_n \equiv_{\alpha} w_n$  holds for all  $n \in \mathbb{N}$ , where  $v_n$  and  $w_n$  are the prefixes of length n of v and w.

Like in the case of finite bar strings, we obtain three types of languages:

▶ **Definition 3.6.** A data  $\omega$ -language or literal  $\omega$ -language is, respectively, a subset of  $\mathbb{A}^{\omega}$  or  $\overline{\mathbb{A}}^{\omega}$ . A bar  $\omega$ -language is a literal  $\omega$ -language closed under  $\alpha$ -equivalence.

Conversions of bar  $\omega$ -languages into data  $\omega$ -languages under global and local freshness are analogous to the case of bar word languages; see Urbat et al. [52] for details.

**Data and Bar Tree Languages.** Lastly, we consider *bar tree languages*, recently introduced by Prucker and Schröder [47] (under the name *alphatic tree languages*) as a common generalization of bar word languages and classical tree languages. We fix a finite signature  $\Sigma$ . A *bar*  $\Sigma$ -*tree* is a tree over the (infinite) signature  $\overline{\mathbb{A}} \times \Sigma$  that contains one symbol  $\alpha f/n$ for every  $\alpha \in \overline{\mathbb{A}}$  and every  $f/n \in \Sigma$ .<sup>2</sup> We write  $\mathcal{T}_{\overline{\mathbb{A}}}(\Sigma)$  for the set of bar  $\Sigma$ -trees, and  $\mathcal{T}_{S}(\Sigma) \subseteq \mathcal{T}_{\overline{\mathbb{A}}}(\Sigma)$  for the subset of bar trees using only letters from  $S \subseteq \overline{\mathbb{A}}$ . Then  $\mathcal{T}_{\overline{\mathbb{A}}}(\Sigma)$  forms a nominal set with the expected group action  $\pi \cdot (\alpha f(t_1, \ldots, t_n)) = (\pi \cdot \alpha) \cdot f(\pi \cdot t_1, \ldots, \pi \cdot t_n)$ . We obtain a notion of  $\alpha$ -equivalence of bar  $\Sigma$ -trees by having  $\equiv_{\alpha}$  as the least congruence on  $\mathcal{T}_{\overline{\mathbb{A}}}(\Sigma)$  generated by  $|a.f(t_1, \ldots, t_n) \equiv_{\alpha} |b.f(t'_1, \ldots, t'_n)|$  whenever  $\langle a \rangle t_i = \langle b \rangle t'_i$  for  $1 \leq i \leq n$ . The set  $\mathsf{FN}(t)$  of free names of a bar  $\Sigma$ -tree t is defined recursively in the expected way, namely by  $\mathsf{FN}(a.f(t_1, \ldots, t_n)) = \{a\} \cup \bigcup_{i=1}^n \mathsf{FN}(t_i)$  and  $\mathsf{FN}(|a.f(t_1, \ldots, t_n)) = (\bigcup_{i=1}^n \mathsf{FN}(t_i)) \setminus \{a\}$ . We again work with three different types of languages:

▶ **Definition 3.7.** A data tree language or literal tree language is, respectively, a subset of  $\mathcal{T}_{\mathbb{A}}(\Sigma)$  or  $\mathcal{T}_{\overline{\mathbb{A}}}(\Sigma)$ . A bar tree language is a literal tree language closed under  $\alpha$ -equivalence

Conversions of bar tree languages into data tree languages under global and local freshness are analogous to the case of bar word languages; see Prucker and Schröder [47] for details.

<sup>&</sup>lt;sup>2</sup> Prucker and Schröder used the notation  $\nu a.f$  instead of |a.f|; we prefer the latter for consistency.

▶ **Remark 3.8.** In the following, the term *bar language* refers to either type of language (bar word language, bar  $\omega$ -language, bar tree language) introduced above. Given a bar language L, we write  $L \upharpoonright \overline{\mathbb{A}}_0$  for its restriction to the subalphabet  $\overline{\mathbb{A}}_0 \subseteq \overline{\mathbb{A}}$ , that is,

 $L \upharpoonright \overline{\mathbb{A}}_0 = L \cap S$  where  $S \in \{\overline{\mathbb{A}}_0^*, \overline{\mathbb{A}}_0^\omega, \mathcal{T}_{\overline{\mathbb{A}}_0}(\Sigma)\}.$ 

# 3.3 Bar Automata

While data languages are commonly represented by register automata [33], or equivalent automata over nominal sets [8], their representation by bar languages allows for an alternative and conceptually much simpler approach: every standard automata model for languages over finite alphabets can be used as a model for bar languages by restricting to finite alphabets  $\overline{\mathbb{A}}_0 \subseteq \overline{\mathbb{A}}$ , i.e. finite sets of bar names and plain names, and reinterpreting the usual accepted language up to  $\alpha$ -equivalence. This principle has been implemented for classical finite automata, Büchi automata and tree automata (Section 2) and leads to the following notions:

- ▶ **Definition 3.9.** 1. A bar DFA/bar NFA [49] is a DFA/NFA  $\mathscr{A}$  with finite input alphabet  $\overline{\mathbb{A}}_0 \subseteq \overline{\mathbb{A}}$ . The literal language  $L_0(\mathscr{A}) \subseteq \overline{\mathbb{A}}_0^*$  accepted by  $\mathscr{A}$  is the usual accepted language. The bar language  $L_\alpha(\mathscr{A}) \subseteq \overline{\mathbb{A}}^*$  accepted by  $\mathscr{A}$  is the closure of  $L_0(\mathscr{A})$  under  $\alpha$ -equivalence, that is,  $L_\alpha(\mathscr{A}) = \{w \in \overline{\mathbb{A}}^* \mid \exists w' \in L_0(\mathscr{A}). w \equiv_\alpha w'\}.$
- 2. A bar Büchi automaton [52] is a Büchi automaton  $\mathscr{A}$  with finite input alphabet  $\overline{\mathbb{A}}_0 \subseteq \overline{\mathbb{A}}$ . The literal language  $L_0(\mathscr{A}) \subseteq \overline{\mathbb{A}}_0^{\omega}$  accepted by  $\mathscr{A}$  is the usual accepted language. The bar language  $L_{\alpha}(\mathscr{A}) \subseteq \overline{\mathbb{A}}^{\omega}$  accepted by  $\mathscr{A}$  is its closure under  $\alpha$ -equivalence.
- **3.** A bar DFTA/NFTA [47] over the finite signature  $\Sigma$  is a DFTA/NFTA  $\mathscr{A}$  over the signature  $\overline{\mathbb{A}}_0 \times \Sigma$  for some finite subset  $\overline{\mathbb{A}}_0 \subseteq \overline{\mathbb{A}}$ . The literal language  $L_0(\mathscr{A}) \subseteq \mathcal{T}_{\overline{\mathbb{A}}_0}(\Sigma)$  accepted by  $\mathscr{A}$  is the usual accepted language. The bar language  $L_{\alpha}(\mathscr{A}) \subseteq \mathcal{T}_{\overline{\mathbb{A}}}(\Sigma)$  is its closure under  $\alpha$ -equivalence.
- ▶ **Remark 3.10.** 1. We let the term *bar automaton* refer to either automaton type above. A *bar word/tree automaton* means either a bar DFA/DFTA or bar NFA/NFTA.
- 2. The use of the *standard* semantics for literal languages enables the use of existing learning algorithms for classical models as a building block for learning bar languages.

While our learning algorithms in Section 5 operate purely on bar automata, it is worth discussing how bar automata relate to models of *nominal automata* (i.e. automata with nominal sets of states and transitions) and *register automata* (i.e. automata with registers for storing and comparing data values).

**Connection to Nominal Automata with Name Allocation.** Under their bar language semantics, all types of bar automata defined above admit an equi-expressive model of non-deterministic nominal automata with explicit name allocation, namely RNNAs [49], Büchi RNNAs [52] and RNTAs [47] (see the appendix for formal definitions):

▶ **Theorem 3.11.** Bar word automata, bar Büchi automata and bar tree automata are equivalent, under bar language semantics, to RNNAs, Büchi RNNAs and RNTAs, respectively.

The equivalence of bar word automata and RNNAs is due to Schröder et al. [49], while for the other two cases only the direction from nominal to bar automata was known [47, 52]; the reverse directions are new results and proved in the appendix.

In a nutshell, the above equivalences emerge as follows. A bar automaton with states Q and alphabet  $\overline{A}_0$  can be converted into a bar language equivalent RNNA/Büchi RNNA/RNTA

whose states are given by the nominal set  $Q \times \mathbb{A}^{\$k}$ , where  $k = |\bar{\mathbb{A}}_0|$  and  $\mathbb{A}^{\$k}$  denotes the nominal set of all partial injective functions from k to  $\mathbb{A}$  (corresponding to partial assignments of pairwise distinct data values to k registers) under the pointwise group action. Such a nominal automaton can be interpreted as a register automaton with control states Q and kregisters for storing data values. Unlike standard register automata, it features transitions for reading bar letters. Conversely, every RNNA/Büchi RNNA/RNTA can be converted into a bar language equivalent bar automaton by restricting to states with finite support  $\bar{\mathbb{A}}_0$ , where  $\bar{\mathbb{A}}_0 \subseteq \bar{\mathbb{A}}$  is chosen large enough such that each state has a support of size at most  $|\bar{\mathbb{A}}_0|$ .

**Connection to Nominal Automata and Register Automata.** Under their data language semantics, bar NFAs relate to standard models of nominal automata and register automata (without name allocation) for data word languages. Specifically, under local freshness, they correspond to *non-guessing* and *name-dropping* non-deterministic nominal automata [8]. The latter are equivalent to *name-dropping* non-deterministic register automata with non-deterministic reassignment [34]. Under global freshness, bar automata are expressively equivalent to *session automata* [10]. For more details on these correspondences, see [49, Sec. 6].

▶ Remark 3.12. Bar DFAs and bar NFAs are expressively equivalent under both bar language and (local or global freshness) data language semantics, since bar NFAs can be determinized via the usual power set construction without changing the literal language. The same applies to (bottom-up) bar DFTAs and bar NFTAs. This is not a contradiction to the fact that non-deterministic nominal/register automata are generally not determinizable [33]: the translations between bar automata and nominal/register automata do not preserve determinism, that is, the nominal/register automaton corresponding to a given deterministic bar automaton may be non-deterministic.

Consequently, while our learning algorithms infer bar automata, they can also be used to learn the corresponding nominal/register automata. Let us remark that in terms of scope, our learning algorithms are incomparable to existing algorithms for deterministic and nondeterministic nominal/register automata:

**Example 3.13.** Consider the following bar NFA over  $\overline{A}_0 := \{|a, b, c, d, a, b, c\}$ :

$$\xrightarrow[]{a} \qquad \qquad |c, a, b \qquad \qquad |d, b, c \\ \xrightarrow[]{a} \qquad \qquad |a \qquad q_1 \xrightarrow{|b \qquad Q_2} a \qquad q_3 \xrightarrow{|c \qquad Q_4} b \rightarrow q_5 \xrightarrow{c} (q_f)$$

Its literal language  $L_0 \subseteq \overline{\mathbb{A}}_0^{\star}$  is given by the regular expression  $|a|a|b(|c+a+b)^*a|c(|d+b+c)^*bc$ , and its bar language  $L \subseteq \overline{\mathbb{A}}^{\star}$  consists of all bar strings  $\alpha$ -equivalent to some bar string in  $L_0$ . The bar language L can be learned using our algorithm in Section 5 (like every bar language accepted by some bar NFA), and by learning L we can also infer its corresponding data language under local freshness semantics, which is given by

$$D(L) = \{ uabvacwbc \mid u, v, w \in \mathbb{A}^*, a \neq b, b \neq c \in \mathbb{A} \}.$$

This data language is not accepted by any deterministic nominal/register automaton, hence existing learning algorithms for such automata [2, 12, 18, 43] are not able to learn it. It is also not *residual* in the sense of Moerman and Sammartino [42], so that their algorithm  $\nu NL^*$  for learning non-deterministic nominal automata (which only guarantees termination for residual data languages) does not apply; see appendix. On the other hand, there exist data

languages accepted by deterministic nominal automata that do not allow *name-dropping* [49], or residual non-deterministic nominal automata that require *guessing* [42, Sec. 3], and hence are not expressible by bar NFAs. This means that our learning algorithm applies to classes of data languages orthogonal to the classes captured by previous algorithms.

We conclude this section with the important observation that  $\alpha$ -renaming is computable at the level of bar automata. A bar automaton  $\mathscr{A}$  is *closed* if its literal language is closed under  $\alpha$ -equivalence with respect to the finite alphabet  $\overline{\mathbb{A}}_0$ , that is,  $L_0(\mathscr{A}) = L_{\alpha}(\mathscr{A}) \upharpoonright \overline{\mathbb{A}}_0$ . Closure can always be achieved, at the price of an exponential blowup of the number of states w.r.t. the alphabet size:

▶ **Proposition 3.14.** For every bar automaton over  $\overline{\mathbb{A}}_0$  with *n* states, there exists a closed bar automaton over  $\overline{\mathbb{A}}_0$  with  $\mathcal{O}(n \cdot 2^{|\overline{\mathbb{A}}_0| \cdot (\log |\overline{\mathbb{A}}_0|+1)})$  states accepting the same bar language.

This is essentially a consequence of the proof of Theorem 3.11: converting a bar automaton into an equivalent RNNA/Büchi RNNA/RNTA and back yields a closed bar automaton.

▶ Corollary 3.15. For every bar language L accepted by some bar automaton over  $\overline{A}_0$ , the language  $L \upharpoonright \overline{A}_0$  is regular.

This result is the key to our approach to learning bar languages, as it enables a reduction to learning corresponding regular languages. To achieve this, we need to bridge the gap between literal and bar languages, which requires the algorithmic handling of  $\alpha$ -equivalence.

# 4 Checking $\alpha$ -Equivalence

At the heart of our learning algorithms for bar automata presented in Section 5, and an essential requirement for their effective implementation, is a method to check finite bar strings, ultimately periodic bar strings and bar trees for  $\alpha$ -equivalence. In the following we develop a suitable version of *De Bruijn levels* [14], originally introduced as a canonical representation of  $\lambda$ -terms. In this way,  $\alpha$ -equivalence reduces to syntactic equality.

**Finite Bar Strings.** In the case of bar strings, the idea of De Bruijn levels is to replace all bound occurrences of some name, as well as the preceding occurrence of the bar letter creating the binding, with a suitable natural number, while leaving free names as they are. This yields a canonical representation of bar strings up to  $\alpha$ -equivalence.

▶ Definition 4.1 (De Bruijn Normal Form). Given a bar string  $w = \alpha_1 \cdots \alpha_n \in \overline{\mathbb{A}}^*$ , its *De* Bruijn normal form  $nf(w) = \beta_1 \cdots \beta_n \in (\mathbb{A} + \mathbb{N})^*$  is a word of the same length as w over the alphabet  $\mathbb{A} + \mathbb{N}$ , with  $\beta_i$  defined inductively as follows:

**1.**  $\beta_i = \alpha_i$  if  $\alpha_i \in \mathbb{A}$  and  $\alpha_i$  is not preceded by any occurrence of  $|\alpha_i|$  in w;

2.  $\beta_i = k$  if  $\alpha_i \in \mathbb{A}$  and  $\beta_j = k$  where  $j = \max\{j < i \mid \alpha_j = |\alpha_i\};$ 

**3.**  $\beta_i = k + 1$  if  $\alpha_i$  is a bar name and  $\alpha_1 \cdots \alpha_{i-1}$  contains k bar names.

► **Example 4.2.** The  $\alpha$ -equivalent bar strings w = |ac|bb|aa and w' = |dc|aa|aa have the same normal form, namely nf(w) = 1c2233 = nf(w').

The normal form nf(w) can be computed from w letter by letter in polynomial time and linear-logarithmic space (for representing natural numbers) in the length of w.

▶ Proposition 4.3. Two finite bar strings  $v, w \in \overline{\mathbb{A}}^*$  are  $\alpha$ -equivalent iff nf(v) = nf(w).

As an immediate consequence, we have

**Corollary 4.4.** The  $\alpha$ -equivalence of finite bar strings is decidable in polynomial time.

Indeed, to decide whether two given bar strings  $v, w \in \overline{\mathbb{A}}^*$  are  $\alpha$ -equivalent, it suffices to compute their normal forms nf(v) and nf(w) and check for syntactic equality.

**Infinite Bar Strings.** De Bruijn normal forms for infinite bar strings could be defined in the same way as for finite bar strings. However, this normal form does not preserve ultimate periodicity (for instance,  $(|aa)^{\omega}$  has the normal form  $112233\cdots$ ). A modified normal form that does preserve it, is invariant under  $\alpha$ -renaming, and the representation of ultimately periodic bar strings via pairs of finite bar strings seems hard to achieve.

Nonetheless, we can check ultimately periodic bar strings for  $\alpha$ -equivalence by reducing to the finite case. Intuitively, given  $u_1v_1^{\omega}$  and  $u_2v_2^{\omega}$ , since  $v_1$  and  $v_2$  are repeated infinitely often, plain names in  $v_i$  are either free, refer back to  $u_i$  or to the directly preceeding repetition of  $v_i$ . This observation leads to the following proposition:

▶ **Proposition 4.5.** Two ultimately periodic bar strings  $u_i v_i^{\omega}$  (i = 1, 2) with  $|u_1| = |u_2|$  are  $\alpha$ -equivalent iff their prefixes  $p_i = u_i v_i^{2\ell_i}$  are  $\alpha$ -equivalent, where  $\ell_1 = |v_2|$  and  $\ell_2 = |v_1|$ .

The exponents  $2\ell_i$  make sure that (a)  $p_1$  and  $p_2$  have the same length, (b) for every pair of positions  $i_1$  in  $v_1$  and  $i_2$  in  $v_2$ , there is a position j in  $p_1$  and  $p_2$  where the letters at  $i_1$ and  $i_2$  'meet', and (c) that position j can be chosen such that there is a full copy of  $v_i$  in  $p_i$  preceeding it. Note that (a) and (b) would already be achieved by taking just  $\ell_i$  as the exponent, and the factor 2 then achieves (c) while maintaining (a) and (b).

▶ Corollary 4.6. The  $\alpha$ -equivalence of ultimately periodic bar strings (represented as pairs of finite words) is decidable in polynomial time.

**Bar Trees.** For the case of bar trees, the De Bruijn level notation can be reduced to that for bar strings: the normal form of a bar tree is simply given by the bar string normal form computed for every individual branch.

- ▶ **Definition 4.7.** 1. Given the finite signature  $\Sigma$ , a *De Bruijn*  $\Sigma$ -*tree* is a tree over the signature  $(\mathbb{A} + \mathbb{N}) \times \Sigma$  with symbols  $\alpha f/n$  and k f/n for  $\alpha \in \overline{\mathbb{A}}$ ,  $k \in \mathbb{N}$  and  $f/n \in \Sigma$ .
- 2. Given a bar  $\Sigma$ -tree  $t \in \mathcal{T}_{\overline{\mathbb{A}}}(\Sigma)$ , its *De Bruijn normal form*  $\mathsf{nf}(t)$  is a De Bruijn  $\Sigma$ -tree of the same shape as t. For every node x of t with label  $\alpha.f$ , the corresponding node of  $\mathsf{nf}(t)$  has the label  $\beta.f$  with  $\beta \in \overline{\mathbb{A}} + \mathbb{N}$  determined as follows: let  $\alpha_1.f_1, \cdots, \alpha_n.f_n, \alpha.f$  be the sequence of node labels occurring on the path from the root of t to x, and take  $\beta$  to be the last letter of the bar string normal form  $\mathsf{nf}(\alpha_1 \cdots \alpha_n \alpha) \in (\overline{\mathbb{A}} + \mathbb{N})^*$ .

It is readily verified that the computation of the Bruijn normal form can be performed in polynomial time in the number of nodes of the given tree. Just like in the case of bar strings, normal forms capture  $\alpha$ -equivalence:

▶ **Proposition 4.8.** Two bar trees  $s, t \in \mathcal{T}_{\mathbb{A}}(\Sigma)$  are  $\alpha$ -equivalent iff  $\mathsf{nf}(s) = \mathsf{nf}(t)$ .

Therefore, we conclude with

**Corollary 4.9.** The  $\alpha$ -equivalence of bar trees is decidable in polynomial time.



**Figure 1** Learner  $L_{\alpha}$  with internal learner L, teaching assistant TA and teacher T.

# 5 Learning Bar Languages

With the technical preparation of the previous sections at hand, we present the main contribution of our paper: a learning algorithm for bar languages.

▶ Notation 5.1. In the following, we fix an *unknown* bar word/ $\omega$ -/tree language  $L_{\mathsf{T}}$  recognizable by some bar word/Büchi/tree automaton with finite alphabet  $\overline{\mathbb{A}}_0$ .<sup>3</sup>

Our learning algorithm follows Angluin's MAT framework (Section 2), that is, it describes the strategy of a *learner*  $L_{\alpha}$  that interacts with a *teacher* T in order to infer a bar automaton over  $\bar{A}_0$  accepting  $L_{T}$ . As usual,  $L_{\alpha}$  can direct membership and equivalence queries to T, which in the present setting take the following form:

Membership Queries (MQ<sub> $\alpha$ </sub>): Given a finite bar string/ultimately periodic bar string/bar tree  $w \in \overline{\mathbb{A}}^*/\overline{\mathbb{A}}^\omega/\mathcal{T}_{\overline{\mathbb{A}}}(\Sigma)$ , is  $w \in L_{\mathsf{T}}$ ?

Equivalence Queries (EQ<sub> $\alpha$ </sub>): Given a bar automaton  $\mathcal{H}$ , is  $L_{\alpha}(\mathcal{H}) = L_{\mathsf{T}}$ ? If not, then  $\mathsf{T}$  provides a counterexample, that is, a finite bar string/ultimately periodic bar string/bar tree  $w_{\mathsf{T}} \in \bar{\mathbb{A}}^*/\bar{\mathbb{A}}^{\omega}/\mathcal{T}_{\overline{\mathfrak{A}}}(\Sigma)$  in the symmetric difference  $L_{\alpha}(\mathcal{H}) \oplus L_{\mathsf{T}}$ .

We assume that  $L_{\alpha}$  is aware of the finite alphabet  $\overline{\mathbb{A}}_0$  of the unknown bar automaton. Interpreting bar automata as register automata (Section 3.3), this boils down to the number of registers being known. In Section 6, we describe how to learn  $L_{\mathsf{T}}$  without this information.

The learner  $L_{\alpha}$  consists of two components, depicted in Figure 1. The first component is an *arbitrary* MAT-based learner L for standard regular word/ $\omega$ -/tree languages over  $\bar{\mathbb{A}}_0$ that infers a finite automaton/Büchi automaton/tree automaton using a finite number of membership queries (MQ) and equivalence queries (EQ). The learner L may, for instance, execute any of the learning algorithms discussed in Section 2. The precise choice of L's algorithm affects the query complexity of  $L_{\alpha}$ , but not its correctness and termination.

The second component of  $L_{\alpha}$  is a *teaching assistant* (TA) that internally interacts with L and externally interacts with the teacher T. In the interaction with L, the TA emulates a teacher for the language  $L_{T} \upharpoonright \overline{A}_{0}$ ; recall from Corollary 3.15 that this is a regular language. To achieve this, the TA turns each query (MQ) and (EQ) of L into a corresponding query

<sup>&</sup>lt;sup>3</sup> In the tree case, this means a language/automaton over the signature  $\bar{\mathbb{A}}_0 \times \Sigma$  for a finite signature  $\Sigma$ .

 $(MQ_{\alpha})$  and  $(EQ_{\alpha})$  for the teacher T. Subsequently, the TA translates T's answer back to a form that L can process. In more detail, the TA proceeds as shown in Figure 1:

- A membership query (MQ) by L (given by a bar string/ultimately periodic bar string/bar tree  $w \in \overline{\mathbb{A}}_0^* / \overline{\mathbb{A}}_0^\omega / \mathcal{T}_{\overline{\mathbb{A}}_0}(\Sigma)$ ) and its answer are relayed unchanged between L and T.
- For an equivalence query (EQ) by L with hypothesis  $\mathcal{H}$  (a bar word automaton/bar Büchi automaton/bar tree automaton over  $\overline{\mathbb{A}}_0$ ), the query itself is relayed unchanged to T. If  $\mathcal{H}$ is correct (i.e.  $L_{\alpha}(\mathcal{H}) = L_{\mathsf{T}}$ ), then the learner  $\mathsf{L}_{\alpha}$  successfully terminates. Otherwise T returns a counterexample  $w_{\mathsf{T}} \in \overline{\mathbb{A}}^*/\overline{\mathbb{A}}^{\omega}/\mathcal{T}_{\overline{\mathbb{A}}}(\Sigma)$  in the symmetric difference  $L_{\alpha}(\mathcal{H}) \oplus L_{\mathsf{T}}$ .
- The TA cannot simply relay the counterexample  $w_{\mathsf{T}}$  to the internal learner L because the latter expects a counterexample over the finite alphabet  $\bar{\mathbb{A}}_0$ . Therefore,  $w_{\mathsf{T}}$  needs to be suitably processed. First, the TA picks any bar string/ultimately periodic bar string/bar tree w over the finite alphabet  $\bar{\mathbb{A}}_0$  that is  $\alpha$ -equivalent to  $w_{\mathsf{T}}$  (step 1 in Figure 1). Note that such w always exists because the bar languages  $L_{\alpha}(\mathcal{H})$  and  $L_{\mathsf{T}}$  are both accepted by bar automata over  $\bar{\mathbb{A}}_0$ . Second, w is chosen to be in the literal language of the hypothesis  $\mathcal{H}$  if possible (step 2 in Figure 1), and then returned to L.

We will explain below how w and w' in steps 1 and 2 can be effectively computed by the TA. First, let us prove that the algorithm of Figure 1 indeed learns a bar automaton for  $L_{T}$ :

► Theorem 5.2 (Correctness). Suppose that the internal learner L needs  $M(L_T \upharpoonright \overline{\mathbb{A}}_0)$  membership and  $E(L_T \upharpoonright \overline{\mathbb{A}}_0)$  equivalence queries to learn a finite automaton/Büchi automaton/tree automaton for the regular language  $L_T \upharpoonright \overline{\mathbb{A}}_0$ . Then  $L_\alpha$  learns a bar automaton for  $L_T$  with at most  $M(L_T \upharpoonright \overline{\mathbb{A}}_0)$  membership and  $E(L_T \upharpoonright \overline{\mathbb{A}}_0)$  equivalence queries.

**Proof.** Clearly, if the learner  $L_{\alpha}$  terminates, then it has inferred a correct bar automaton for the unknown bar language  $L_{T}$ . Thus, we only need to establish  $L_{\alpha}$ 's query complexity. As indicated above, the key observation is that all answers the internal learner L receives from the TA correspond to answers of a teacher for the regular language  $L_{T} \upharpoonright \overline{A}_{0}$ ; that is,

- 1. If L asks a membership query  $w \in \overline{\mathbb{A}}_0^* / \overline{\mathbb{A}}_0^\omega / \mathcal{T}_{\overline{\mathbb{A}}_0}(\Sigma)$ , the TA answers 'Yes' iff  $w \in L_{\mathsf{T}} \upharpoonright \overline{\mathbb{A}}_0$ .
- 2. If L asks an equivalence query with hypothesis  $\mathcal{H}$  (a bar automaton over  $\overline{A}_0$ ), then the answer of the TA (if any) is an element of the symmetric difference  $L_0(\mathcal{H}) \oplus (L_T \upharpoonright \overline{A}_0)$ .

Note that the TA might not answer an equivalence query by L at all: if  $\mathcal{H}$  satisfies  $L_{\alpha}(\mathcal{H}) = L_{\mathsf{T}}$ , then  $\mathsf{L}_{\alpha}$  successfully terminates without running L to completion. The claimed complexity bound for  $\mathsf{L}_{\alpha}$  is then immediate: Since  $\mathsf{L}_{\alpha}$  simply forwards each of L's membership and equivalence queries to T, the total number of  $\mathsf{L}_{\alpha}$ 's queries is at most  $M(L_{\mathsf{T}} \upharpoonright \bar{\mathbb{A}}_0)$  and  $E(L_{\mathsf{T}} \upharpoonright \bar{\mathbb{A}}_0)$ , respectively. It remains to prove the statements in 1 and 2.

Proof of Item 1. Since a membership query w by  $\mathsf{L}$  is a bar string/ultimately periodic bar string/bar tree over  $\overline{\mathbb{A}}_0$ , we have  $w \in L_{\mathsf{T}} \upharpoonright \overline{\mathbb{A}}_0$  iff  $w \in L_{\mathsf{T}}$ . Therefore T's answer to the query ' $w \in L_{\mathsf{T}}$ ?', which the TA forwards to  $\mathsf{L}$ , is also a correct answer for  $\mathsf{L}$ 's query ' $w \in L_{\mathsf{T}} \upharpoonright \overline{\mathbb{A}}_0$ ?'. Proof of Item 2. Suppose that  $\mathcal{H}$  is an incorrect hypothesis for  $L_{\mathsf{T}}$ , that is,  $L_{\alpha}(\mathcal{H}) \neq L_{\mathsf{T}}$ , so that T returns an element  $w_{\mathsf{T}}$  of the symmetric difference  $L_{\alpha}(\mathcal{H}) \oplus L_{\mathsf{T}}$  to  $\mathsf{L}_{\alpha}$ . Let  $w \equiv_{\alpha} w_{\mathsf{T}}$ be the  $\alpha$ -equivalent bar string/ultimately periodic bar string/bar tree over  $\overline{\mathbb{A}}_0$  chosen by the TA in step 1. We consider the following two cases:

- Case 1:  $w_{\mathsf{T}} \in L_{\mathsf{T}} \setminus L_{\alpha}(\mathcal{H})$ . Then  $w \in L_{\mathsf{T}} \setminus L_{\alpha}(\mathcal{H})$  because both  $L_{\mathsf{T}}$  and  $L_{\alpha}(\mathcal{H})$  and hence  $L_{\mathsf{T}} \setminus L_{\alpha}(\mathcal{H})$  are closed under  $\alpha$ -equivalence. Since  $w \notin L_{\alpha}(\mathcal{H})$ , there exists no  $w' \in L_0(\mathcal{H})$  such that  $w' \equiv_{\alpha} w$ , so the TA returns w to L after step 2. Then  $w \in (L_{\mathsf{T}} \upharpoonright \bar{\mathbb{A}}_0) \setminus L_0(\mathcal{H})$ , in particular  $w \in L_0(\mathcal{H}) \oplus (L_{\mathsf{T}} \upharpoonright \bar{\mathbb{A}}_0)$  as claimed.
- Case 2:  $w_{\mathsf{T}} \in L_{\alpha}(\mathcal{H}) \setminus L_{\mathsf{T}}$ . Then  $w \in L_{\alpha}(\mathcal{H}) \setminus L_{\mathsf{T}}$ , analogous to Case 1. Since  $w \in L_{\alpha}(\mathcal{H})$ , there exists  $w' \in L_0(\mathcal{H})$  such that  $w' \equiv_{\alpha} w$ . The TA picks one such w' in step 2 and

returns it to L. Note that  $w' \notin L_{\mathsf{T}}$  because  $w \notin L_{\mathsf{T}}$  and  $L_{\mathsf{T}}$  is closed under  $\alpha$ -equivalence. Therefore  $w' \in L_0(\mathcal{H}) \setminus (L_{\mathsf{T}} \upharpoonright \bar{\mathbb{A}}_0)$ , whence  $w' \in L_0(\mathcal{H}) \oplus (L_{\mathsf{T}} \upharpoonright \bar{\mathbb{A}}_0)$  as claimed.

It remains to address the implementation of steps 1 and 2 in Figure 1 by the TA.

Computing representatives over  $\overline{\mathbb{A}}_0$  (step 1). To compute an  $\alpha$ -equivalent word  $w \equiv_{\alpha} w_{\mathsf{T}}$  over the finite alphabet  $\overline{\mathbb{A}}_0$ , the TA proceeds as follows.

For a finite bar string/bar tree  $w_{\mathsf{T}}$  over  $\overline{\mathbb{A}}$ , non-derministically guess a finite bar string/bar tree w over the finite alphabet  $\overline{\mathbb{A}}_0$  of equal length/shape, and then check  $w_{\mathsf{T}}$  and w for  $\alpha$ -equivalence by computing the De Bruijn normal forms (Corollaries 4.4 and 4.9). This computation requires non-deterministic polynomial time with respect to the size of  $w_{\mathsf{T}}$ .

For the case of an ultimately periodic infinite bar string  $w_{\mathsf{T}} = uv^{\omega}$ , a normal form is not available (Section 4), so we use an alternative (and less efficient) approach for computing w. Let  $\bar{\mathbb{A}}_1 = \{\alpha \in \bar{\mathbb{A}} \mid \alpha \text{ occurs in } w_{\mathsf{T}}\}$ . First, build a Büchi automaton with finite alphabet  $\bar{\mathbb{A}}_0 \cup \bar{\mathbb{A}}_1$  that accepts only  $w_{\mathsf{T}}$  (with  $\mathcal{O}(|uv|)$  states). Construct its closure, that is, a Büchi automaton accepting all infinite bar strings  $w \equiv_{\alpha} w_{\mathsf{T}}$  over  $\bar{\mathbb{A}}_0 \cup \bar{\mathbb{A}}_1$ , which needs  $\mathcal{O}(|uv| \cdot 2^{(|\bar{\mathbb{A}}_0|+|\bar{\mathbb{A}}_1|)\cdot(\log(|\bar{\mathbb{A}}_0|+|\bar{\mathbb{A}}_1|)+1)})$  states (Proposition 3.14), and restrict its input alphabet to  $\bar{\mathbb{A}}_0$  by removing all  $\bar{\mathbb{A}}_1 \setminus \bar{\mathbb{A}}_0$ -transitions. The resulting Büchi automaton  $\mathscr{A}$ accepts the language  $L_0(\mathscr{A}) = \{w \in \bar{\mathbb{A}}_0^{\omega} \mid w \equiv_{\alpha} w_{\mathsf{T}}\}$ . Thus, it remains to look for some ultimately periodic word w in  $L_0(\mathscr{A})$ . This is standard: perform a depth-first search to detect a cycle in  $\mathscr{A}$  (with label  $v_1$ ) that contains a final state and is reachable from the initial state (via some path with label  $u_1$ ). Then  $w = u_1v_1^{\omega}$  is an ultimately periodic bar string contained in  $L_0(\mathscr{A})$ . Overall, this algorithm uses space linear in |uv| and exponential in  $|\bar{\mathbb{A}}_0|$  and  $|\bar{\mathbb{A}}_1|$ .

**Checking membership up to**  $\alpha$ -equivalence (step 2). Lastly, we explain how to decide, for w computed in step 1, whether there exists an  $\alpha$ -equivalent  $w' \in L_0(\mathcal{H})$ .

For the case of finite bar strings/trees, non-deterministically guess a bar string/tree w' of the same length/shape as w and verify that  $w' \equiv_{\alpha} w$  via the Bruijn normal form as before. Moreover, verify that the bar automaton  $\mathcal{H}$  literally accepts w' by guessing an accepting run. This requires non-deterministic polynomial time with respect to |w|.

Again, a different approach is needed for ultimately periodic infinite bar strings. Take the Büchi automaton  $\mathscr{A}$  constructed above with  $\mathcal{O}(|uv| \cdot 2^{(|\bar{\mathbb{A}}_0|+|\bar{\mathbb{A}}_1|) \cdot (\log(|\bar{\mathbb{A}}_0|+|\bar{\mathbb{A}}_1|)+1)})$  states and accepting  $L_0(\mathscr{A}) = \{w \in \bar{\mathbb{A}}_0^{\omega} \mid w \equiv_{\alpha} w_{\mathsf{T}}\}$ , and check the intersection  $L_0(\mathscr{A}) \cap L_0(\mathscr{H})$  non-emptiness. This is achieved by searching for an ultimately periodic word in  $L_0(\mathscr{A}) \cap L_0(\mathscr{H})$ , where a Büchi automaton for the intersection can be formed via a standard product construction. In total, this requires space linear in the length of the counterexample and the number of states of the hypothesis, and again exponential in  $|\bar{\mathbb{A}}_0|$  and  $|\bar{\mathbb{A}}_1|$ .

# 6 Handling Unknown Input Alphabets

Finally, we discuss how to lift the previous requirement of having a known finite alphabet generating the unknown bar language  $L_{\mathsf{T}}$ . The idea is to run the learner  $L_{\alpha}$  with any finite alphabet  $\overline{\mathbb{A}}_0 \subseteq \overline{\mathbb{A}}$ . In case  $L_{\alpha}$  gets stuck, it knows that the present alphabet is too small and reboots the learning process with a suitably extended alphabet. Details are as follows.

Initially,  $L_{\alpha}$  is executed (running the learning algorithm of Figure 1) with the trivial alphabet  $\overline{\mathbb{A}}_0 = \emptyset$ . If a correct hypothesis is found, then  $L_{\alpha}$  successfully terminates. If T delivers a counterexample  $w_{\mathsf{T}}$ , then it may occur in the computation of step 1 that no  $w \equiv_{\alpha} w_{\mathsf{T}}$ 

over  $\overline{\mathbb{A}}_0$  is found. In this case,  $\overline{\mathbb{A}}_0$  is extended to a larger finite alphabet  $\overline{\mathbb{A}}_0 \subseteq \overline{\mathbb{A}}'_0 \subseteq \overline{\mathbb{A}}$ such that a representative w of  $w_{\mathsf{T}}$  over  $\overline{\mathbb{A}}'_0$  exists; we explain below how to compute a suitable  $\overline{\mathbb{A}}'_0$ . Then  $L_\alpha$  restarts with the new alphabet  $\overline{\mathbb{A}}'_0$ . This process of alphabet extension and restarting  $L_\alpha$  is repeated each time step 1 gets stuck. At some stage, the current alphabet is large enough to generate the unknown bar language  $L_{\mathsf{T}}$ , and then  $L_\alpha$  successfully runs to completion.

It remains to explain how to extend the current  $\overline{\mathbb{A}}_0$  to a larger  $\overline{\mathbb{A}}'_0$ . In the case of finite bar strings/trees, compute the De Bruijn normal form of  $w_{\mathsf{T}}$  and choose the extension  $\overline{\mathbb{A}}_0 \subseteq \overline{\mathbb{A}}'_0$  to be a smallest possible alphabet such that some  $w \equiv_{\alpha} w_{\mathsf{T}}$  over  $\overline{\mathbb{A}}'_0$  exists. The number of bar and plain letters that need to be added to  $\overline{\mathbb{A}}_0$  can be read off the normal form.

In the case of infinite bar strings, construct a Büchi automaton accepting the closure of the ultimately periodic bar string  $w_{\mathsf{T}}$  with respect to the alphabet  $\bar{\mathbb{A}}_0 \cup \bar{\mathbb{A}}_1$ , where  $\bar{\mathbb{A}}_1$  is the set of letters appearing in  $w_{\mathsf{T}}$  (cf. Section 5), and then search for a smallest subalphabet  $\bar{\mathbb{A}}_0 \subseteq \bar{\mathbb{A}}'_0 \subseteq (\bar{\mathbb{A}}_0 \cup \bar{\mathbb{A}}_1)$  such that this closure contains some ultimately periodic bar string over  $\bar{\mathbb{A}}'_0$ . Note that  $\bar{\mathbb{A}}'_0$  necessarily contains all free names of  $w_{\mathsf{T}}$ .

This process of iterated alphabet extension approximates a fitting alphabet from below, ending at a smallest possible  $\overline{\mathbb{A}}_0$  that generates  $L_{\mathsf{T}}$ , that is, such that  $L_{\mathsf{T}}$  is the closure of  $L_{\mathsf{T}} \upharpoonright \overline{\mathbb{A}}_0$  under  $\alpha$ -equivalence. To estimate the query complexity of the above algorithm, let us introduce some notation. We write M(L) and E(L) for the number of membership and equivalence queries required by the internal learner  $\mathsf{L}$  to learn a regular language L. Moreover, for  $k \in \mathbb{N}$  we put  $M_k = \max\{M(L_{\mathsf{T}} \upharpoonright \overline{\mathbb{A}}_0) \mid \overline{\mathbb{A}}_0 \subseteq \overline{\mathbb{A}}, |\overline{\mathbb{A}}_0| = k\}$ ; similarly for  $E_k$ .

▶ **Theorem 6.1** (Correctness). Let *n* be the least cardinality of any finite alphabet  $\overline{\mathbb{A}}_0 \subseteq \overline{\mathbb{A}}$  generating  $L_{\mathsf{T}}$ . Then the above extended learning algorithm infers a bar automaton for  $L_{\mathsf{T}}$  with at most  $\sum_{k=0}^{n} M_k$  membership queries and  $\sum_{k=0}^{n} E_k$  equivalence queries.

**Proof.** Let  $n_i$  be the size of the finite alphabet used in the *i*th iteration of  $L_{\alpha}$ . Since the alphabet grows in every iteration, we have  $0 = n_0 < \ldots < n_k = n$ , where k + 1 is the total number of iterations. The number of membership queries in the *i*th iteration is at most  $M_{n_i}$ , and so the total number of membership queries is at most  $\sum_{i=0}^{k} M_{n_i} \leq \sum_{i=0}^{n} M_i$ . The same reasoning applies to equivalence queries.

▶ Remark 6.2. An alternative to restarting the learner  $L_{\alpha}$  (and hence the internal learner L) each time the alphabet grows is to use a learner L that can handle *dynamically growing input alphabets*, that is, can process counterexamples that are not over the current finite alphabet [31]. In requiring such types of learners beforehand, the TA procedure presents counterexamples to L using the minimal number of additional letters. The learner L then needs to handle the *grown* alphabet internally and proceed. This method potentially saves queries compared to a restart but restricts the class of possible learners significantly. To the best of our knowledge, learners for dynamically growing alphabets have only been studied in the case of deterministic automata over finite words.

# 7 Conclusion and Future Work

We have investigated the learnability of bar word languages, bar  $\omega$ -languages and bar tree languages in Angluin's minimally adequate teacher (MAT) framework. For this purpose, we have introduced a learning algorithm  $L_{\alpha}$  which relies on an arbitrary MAT-based learner for standard word/ $\omega$ -/tree languages over finite alphabets. Its query complexity is completely determined by the underlying learner. In addition, one of its key ingredients is an efficient

procedure for checking  $\alpha$ -equivalence of bar strings/terms. For the latter, we have developed a suitable version of *De Bruijn levels* [14] reducing the problem to checking syntactic equality.

There are various directions for future work. When learning bar  $\omega$ -languages, we currently compute closures of bar automata, which is not needed in the cases of finite bar strings and trees where we instead guess a suitable De Bruijn normal form. It remains to investigate whether a guessing approach is possible in the infinite case; as a technical prerequisite, this would require a suitable normal form for ultimately periodic bar strings.

Looking at data languages (bar languages under local freshness), a further question is whether we can efficiently learn such languages without needing an explicit representation as bar automata, and in particular without needing associated membership and equivalence queries. The key challenge is that the local freshness operator is not injective, so that there is no straightforward back-and-forth translation between bar and data languages. A related question arises for the global freshness semantics, where the operator is also not injective.

Another open problem is the possibility of conformance testing for bar automata, which is a common approach for implementing equivalence queries in a practical black-box learning setting (e.g. [54]). Likewise, passive learning of bar languages is an open problem.

An alternative to the approach of the present paper would be to develop learning algorithms directly at the level of bar automata or equivalent models such as RNNAs, instead of reducing them to standard learning algorithms for non-data languages. We believe that the categorical approaches to automata learning [26,53] would be a good starting point.

#### — References -

- Fides Aarts, Paul Fiterau-Brostean, Harco Kuppens, and Frits Vaandrager. Learning register automata with fresh value generation. In Martin Leucker, Camilo Rueda, and Frank D. Valencia, editors, *Theoretical Aspects of Computing - ICTAC 2015*, volume 9399 of *Lecture Notes in Computer Science*, pages 165–183. Springer, Cham, 2015. doi:10.1007/978-3-319-25150-9\_ 11.
- 2 Fides Aarts, Faranak Heidarian, Harco Kuppens, Petur Olsen, and Frits W. Vaandrager. Automata learning through counterexample guided abstraction refinement. In Dimitra Giannakopoulou and Dominique Méry, editors, *FM 2012: Formal Methods*, volume 7436 of *Lecture Notes in Computer Science*, pages 10–27. Springer, Berlin, Heidelberg, 2012. doi:10.1007/978-3-642-32759-9\_4.
- 3 Dana Angluin. Learning regular sets from queries and counterexamples. Information and Computation, 75(2):87–106, 1987. doi:10.1016/0890-5401(87)90052-6.
- 4 Dana Angluin and Dana Fisman. Learning regular omega languages. Theoretical Computer Science, 650:57-72, 2016. doi:10.1016/j.tcs.2016.07.031.
- 5 Kousar Aslam, Loek Cleophas, Ramon R. H. Schiffelers, and Mark van den Brand. Interface protocol inference to aid understanding legacy software components. *Software and Systems Modeling*, 19(6):1519–1540, 2020. doi:10.1007/s10270-020-00809-2.
- 6 Borja Balle and Mehryar Mohri. Learning weighted automata. In Andreas Maletti, editor, Algebraic Informatics. CAI 2015, volume 9270 of Lecture Notes in Computer Science, pages 1-21. Springer, Cham, 2015. doi:10.1007/978-3-319-23021-4\_1.
- 7 Hendrik Pieter Barendregt. The lambda calculus its syntax and semantics, volume 103 of Studies in logic and the foundations of mathematics. North-Holland, 1985.
- 8 Mikołaj Bojańczyk, Bartek Klin, and Sławomir Lasota. Automata theory in nominal sets. Logical Methods in Computer Science, 10(3), 2014. doi:10.2168/LMCS-10(3:4)2014.
- 9 Benedikt Bollig, Peter Habermehl, Carsten Kern, and Martin Leucker. Angluin-style learning of NFA. In Craig Boutilier, editor, IJCAI 2009, Proceedings of the 21st International Joint Conference on Artificial Intelligence, IJCAI'09, pages 1004—-1009. Morgan Kaufmann Publishers Inc., 2009.

- 10 Benedikt Bollig, Peter Habermehl, Martin Leucker, and Benjamin Monmege. A fresh approach to learning register automata. In Marie-Pierre Béal and Olivier Carton, editors, *Developments* in Language Theory. DLT 2013, volume 7907 of Lecture Notes in Computer Science, pages 118–130. Springer, Berlin, Heidelberg, 2013. doi:10.1007/978-3-642-38771-5\_12.
- 11 Benedikt Bollig, Peter Habermehl, Martin Leucker, and Benjamin Monmege. A robust class of data languages and an application to learning. *Logical Methods in Computer Science*, 10(4), 2014. doi:10.2168/LMCS-10(4:19)2014.
- 12 Sofia Cassel, Falk Howar, Bengt Jonsson, and Bernhard Steffen. Active learning for extended finite state machines. Formal Aspects of Computing, 28(2):233-263, 2016. doi:10.1007/ s00165-016-0355-5.
- 13 Hubert Comon, Max Dauchet, Rémi Gilleron, Florent Jacquemard, Denis Lugiez, Christof Löding, Sophie Tison, and Marc Tommasi. Tree Automata Techniques and Applications. HAL INRIA, 2008. hal-03367725.
- 14 N.G de Bruijn. Lambda calculus notation with nameless dummies, a tool for automatic formula manipulation, with application to the church-rosser theorem. *Indagationes Mathematicae* (*Proceedings*), 75(5):381–392, 1972. doi:10.1016/1385-7258(72)90034-0.
- 15 Normann Decker, Peter Habermehl, Martin Leucker, and Daniel Thoma. Learning transparent data automata. In Gianfranco Ciardo and Ekkart Kindler, editors, Application and Theory of Petri Nets and Concurrency. PETRI NETS 2014, volume 8489 of Lecture Notes in Computer Science, pages 130–149. Springer, Cham, 2014. doi:10.1007/978-3-319-07734-5\_8.
- 16 Stéphane Demri and Ranko Lazić. LTL with the freeze quantifier and register automata. ACM Transactions on Computational Logic, 10(3):16:1–16:30, 2009. doi:10.1145/1507244.1507246.
- 17 François Denis, Aurélien Lemay, and Alain Terlutte. Residual finite state automata. Fundamenta Informaticae, 51(4):339–368, 2002. doi:10.3233/FUN-2002-51402.
- 18 Simon Dierl, Paul Fiterau-Brostean, Falk Howar, Bengt Jonsson, Konstantinos Sagonas, and Fredrik Tåquist. Scalable tree-based register automata learning. In Bernd Finkbeiner and Laura Kovács, editors, Tools and Algorithms for the Construction and Analysis of Systems. TACAS 2024, volume 14571 of Lecture Notes in Computer Science, pages 87–108. Springer, Cham, 2024. doi:10.1007/978-3-031-57249-4\_5.
- 19 Frank Drewes and Johanna Högberg. Learning a regular tree language from a teacher. In Zoltán Ésik and Zoltán Fülöp, editors, *Developments in Language Theory. DLT 2003*, volume 2710 of *Lecture Notes in Computer Science*, pages 279–291. Springer, Berlin, Heidelberg, 2003. doi:10.1007/3-540-45007-6\_22.
- 20 Azadeh Farzan, Yu-Fang Chen, Edmund M. Clarke, Yih-Kuen Tsay, and Bow-Yaw Wang. Extending automated compositional verification to the full class of omega-regular languages. In C. R. Ramakrishnan and Jakob Rehof, editors, *Tools and Algorithms for the Construction* and Analysis of Systems. TACAS 2008, volume 4963 of Lecture Notes in Computer Science, pages 2–17. Springer, Berlin, Heidelberg, 2008. doi:10.1007/978-3-540-78800-3\_2.
- 21 Paul Fiterau-Brostean, Ramon Janssen, and Frits W. Vaandrager. Combining model learning and model checking to analyze TCP implementations. In Swarat Chaudhuri and Azadeh Farzan, editors, *Computer Aided Verification. CAV 2016*, volume 9780 of *Lecture Notes in Computer Science*, pages 454–471. Springer, Cham, 2016. doi:10.1007/978-3-319-41540-6\_25.
- 22 Paul Fiterau-Brostean, Bengt Jonsson, Konstantinos Sagonas, and Fredrik Tåquist. Automatabased automated detection of state machine bugs in protocol implementations. In 30th Annual Network and Distributed System Security Symposium, NDSS 2023. The Internet Society, 2023. doi:10.14722/ndss.2023.23068.
- 23 Paul Fiterau-Brostean, Toon Lenaerts, Erik Poll, Joeri de Ruiter, Frits W. Vaandrager, and Patrick Verleg. Model learning and model checking of SSH implementations. In Proceedings of the 24th ACM SIGSOFT International SPIN Symposium on Model Checking of Software (SPIN 2017), pages 142–151. ACM, 2017. doi:10.1145/3092282.3092289.

- 24 Murdoch J. Gabbay and Andrew M. Pitts. A new approach to abstract syntax involving binders. In Proceedings of the 14th Annual IEEE Symposium on Logic in Computer Science (LICS 1999), pages 214–224. IEEE Computer Society, 1999. doi:10.1109/LICS.1999.782617.
- 25 Radu Grigore, Dino Distefano, Rasmus Petersen, and Nikos Tzevelekos. Runtime verification based on register automata. In Nir Piterman and Scott A. Smolka, editors, *Tools and Algorithms for the Construction and Analysis of Systems. TACAS 2013*, volume 7795 of *Lecture Notes in Computer Science*, pages 260–276. Springer, Berlin, Heidelberg, 2013. doi: 10.1007/978-3-642-36742-7\_19.
- 26 Gerco van Heerdt, Tobias Kappé, Jurriaan Rot, Matteo Sammartino, and Alexandra Silva. A categorical framework for learning generalised tree automata. In Helle Hvid Hansen and Fabio Zanasi, editors, *Coalgebraic Methods in Computer Science. CMCS 2022*, volume 13225 of *Lecture Notes in Computer Science*, pages 67–87. Springer, Cham, 2022. doi: 10.1007/978-3-031-10736-8\_4.
- 27 Gerco van Heerdt, Clemens Kupke, Jurriaan Rot, and Alexandra Silva. Learning weighted automata over principal ideal domains. In Jean Goubault-Larrecq and Barbara König, editors, Foundations of Software Science and Computation Structures. FoSSaCS 2020, volume 12077 of Lecture Notes in Computer Science, pages 602–621. Springer, Cham, 2020. doi: 10.1007/978-3-031-10736-8\_4.
- 28 Falk Howar, Malte Isberner, Bernhard Steffen, Oliver Bauer, and Bengt Jonsson. Inferring semantic interfaces of data structures. In Tiziana Margaria and Bernhard Steffen, editors, Leveraging Applications of Formal Methods, Verification and Validation. Technologies for Mastering Change. ISoLA 2012, volume 7609 of Lecture Notes in Computer Science, pages 554–571. Springer, Berlin, Heidelberg, 2012. doi:10.1007/978-3-642-34026-0\_41.
- 29 Falk Howar, Bengt Jonsson, and Frits Vaandrager. Combining black-box and white-box techniques for learning register automata. In Bernhard Steffen and Gerhard Woeginger, editors, Computing and Software Science: State of the Art and Perspectives, volume 10000 of Lecture Notes in Computer Science, pages 563–588. Springer, Cham, 2019. doi:10.1007/978-3-319-91908-9\_26.
- 30 Falk Howar and Bernhard Steffen. Active automata learning in practice. In Amel Bennaceur, Reiner Hähnle, and Karl Meinke, editors, Machine Learning for Dynamic Software Analysis: Potentials and Limits, volume 11026 of Lecture Notes in Computer Science, pages 123–148. Springer, Cham, 2018. doi:10.1007/978-3-319-96562-8\_5.
- 31 Malte Isberner, Falk Howar, and Bernhard Steffen. Inferring automata with state-local alphabet abstractions. In Guillaume Brat, Neha Rungta, and Arnaud Venet, editors, NASA Formal Methods. NFM 2013, volume 7871 of Lecture Notes in Computer Science, pages 124–138. Springer, Berlin, Heidelberg, 2013. doi:10.1007/978-3-642-38088-4\_9.
- 32 Malte Isberner, Falk Howar, and Bernhard Steffen. The TTT algorithm: A redundancy-free approach to active automata learning. In Borzoo Bonakdarpour and Scott A. Smolka, editors, Runtime Verification. RV 2014, volume 8734 of Lecture Notes in Computer Science, pages 307–322. Springer, Cham, 2014. doi:10.1007/978-3-319-11164-3\_26.
- 33 Michael Kaminski and Nissim Francez. Finite-memory automata. Theoretical Computer Science, 134(2):329–363, 1994. doi:10.1016/0304-3975(94)90242-9.
- 34 Michael Kaminski and Daniel Zeitlin. Finite-memory automata with non-deterministic reassignment. International Journal of Foundations of Computer Science, 21(5):741-760, 2010. doi:10.1142/S0129054110007532.
- 35 Anna Kasprzik. Four one-shot learners for regular tree languages and their polynomial characterizability. *Theoretical Computer Science*, 485:85–106, 2013. doi:10.1016/j.tcs.2013.01.003.
- 36 Michael J. Kearns and Umesh Vazirani. An Introduction to Computational Learning Theory. The MIT Press, 1994.

- 37 Klaas Kürtz, Ralf Küsters, and Thomas Wilke. Selecting theories and nonce generation for recursive protocols. In Proceedings of the 2007 ACM workshop on Formal methods in security engineering (FMSE 2007), pages 61–70. ACM, 2007. doi:10.1145/1314436.1314445.
- 38 Yong Li, Yu-Fang Chen, Lijun Zhang, and Depeng Liu. A novel learning algorithm for büchi automata based on family of dfas and classification trees. *Information and Computation*, 281:104678, 2021. doi:10.1016/j.ic.2020.104678.
- 39 Oded Maler and Amir Pnueli. On the learnability of infinitary regular sets. Information and Computation, 118(2):316-326, 1995. doi:10.1006/inco.1995.1070.
- 40 Tiziana Margaria, Oliver Niese, Harald Raffelt, and Bernhard Steffen. Efficient test-based model generation for legacy reactive systems. In *Proceedings of the Ninth IEEE International High-Level Design Validation and Test Workshop (HLDVT 2004)*, pages 95–100. IEEE Computer Society, 2004. doi:10.1109/HLDVT.2004.1431246.
- 41 Robert McNaughton. Testing and generating infinite sequences by a finite automaton. Information and Control, 9(5):521–530, 1966. doi:10.1016/S0019-9958(66)80013-X.
- 42 Joshua Moerman and Matteo Sammartino. Residuality and learning for nondeterministic nominal automata. Logical Methods in Computer Science, 18(1), 2022. doi:10.46298/ lmcs-18(1:29)2022.
- 43 Joshua Moerman, Matteo Sammartino, Alexandra Silva, Bartek Klin, and Michał Szynwelski. Learning nominal automata. In Proceedings of the 44th ACM SIGPLAN Symposium on Principles of Programming Languages (POPL '17), pages 613–625. ACM, 2017. doi:10.1145/ 3009837.3009879.
- Frank Neven, Thomas Schwentick, and Victor Vianu. Finite state machines for strings over infinite alphabets. ACM Transactions on Computational Logic, 5(3):403-435, 2004. doi:10.1145/1013560.1013562.
- 45 Doron A. Peled, Moshe Y. Vardi, and Mihalis Yannakakis. Black box checking. Journal of Automata, Languages and Combinatorics, 7(2):225-246, 2002. doi:10.25596/JALC-2002-225.
- 46 Andrew M. Pitts. Nominal Sets: Names and Symmetry in Computer Science, volume 57 of Cambridge Tracts in Theoretical Computer Science. Cambridge University Press, 2013.
- 47 Simon Prucker and Lutz Schröder. Nominal tree automata with name allocation. In Rupak Majumdar and Alexandra Silva, editors, 35th International Conference on Concurrency Theory (CONCUR 2024), volume 311 of Leibniz International Proceedings in Informatics (LIPIcs), pages 35:1-35:17. Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2024. doi: 10.4230/LIPIcs.CONCUR.2024.35.
- 48 Ronald L. Rivest and Robert E. Schapire. Inference of finite automata using homing sequences. Information and Computation, 103(2):299–347, 1993. doi:10.1006/inco.1993.1021.
- 49 Lutz Schröder, Dexter Kozen, Stefan Milius, and Thorsten Wißmann. Nominal automata with name binding. In Javier Esparza and Andrzej S. Murawski, editors, *Foundations of Software Science and Computation Structures. FoSSaCS 2017*, volume 10203 of *Lecture Notes in Computer Science*, pages 124–142. Springer, Berlin, Heidelberg, 2017. doi:10.1007/ 978-3-662-54458-7\_8.
- 50 Mathijs Schuts, Jozef Hooman, and Frits W. Vaandrager. Refactoring of legacy software using model learning and equivalence checking: An industrial experience report. In Erika Ábrahám and Marieke Huisman, editors, *Integrated Formal Methods. IFM 2016*, volume 9681 of *Lecture Notes in Computer Science*, pages 311–325. Springer, Cham, 2016. doi: 10.1007/978-3-319-33693-0\_20.
- Wouter Smeenk, Joshua Moerman, Frits Vaandrager, and David N. Jansen. Applying automata learning to embedded control software. In Michael Butler, Sylvain Conchon, and Fatiha Zaïdi, editors, Formal Methods and Software Engineering. ICFEM 2015, volume 9407 of Lecture Notes in Computer Science, pages 67–83. Springer, Cham, 2015. doi:10.1007/978-3-319-25423-4\_5.
- 52 Henning Urbat, Daniel Hausmann, Stefan Milius, and Lutz Schröder. Nominal büchi automata with name allocation. In Serge Haddad and Daniele Varacca, editors, *32nd International*

Conference on Concurrency Theory (CONCUR 2021), volume 203 of Leibniz International Proceedings in Informatics (LIPIcs), pages 4:1–4:16. Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2021. doi:10.4230/LIPIcs.CONCUR.2021.4.

- 53 Henning Urbat and Lutz Schröder. Automata learning: An algebraic approach. In *Proceedings* of the 35th Annual ACM/IEEE Symposium on Logic in Computer Science (LICS '20), pages 900–914. ACM, 2020. doi:10.1145/3373718.3394775.
- 54 Frits Vaandrager. Model learning. Communications of the ACM, 60(2):86–95, 2017. doi: 10.1145/2967606.
- 55 Frits Vaandrager, Bharat Garhewal, Jurriaan Rot, and Thorsten Wißmann. A new approach for active automata learning based on apartness. In Data Fisman and Grigore Rosu, editors, *Tools and Algorithms for the Construction and Analysis of Systems. TACAS 2022*, volume 13243 of *Lecture Notes in Computer Science*, pages 223–243. Springer, Cham, 2022. doi: 10.1007/978-3-030-99524-9\_12.

# Appendix

This appendix contains proof details omitted in the paper. In particular, we explain the connection between bar automata and nominal automata.

# A Details for Section 3

**More on Nominal Sets.** We recall additional terminology from the theory of nominal sets, which is needed for some of the proofs and constructions presented in the sequel.

An element x of a nominal set X is equivariant if it has an empty support, i.e.  $\operatorname{supp}(x) = \emptyset$ , while a subset X of a nominal set Y is equivariant if  $\pi \cdot x \in X$  for all  $x \in X$  and  $\pi \in \operatorname{Perm}(\mathbb{A})$ . A map  $f: X \to Y$  between nominal sets is equivariant if  $f(\pi \cdot x) = \pi \cdot f(x)$  for all  $x \in X$ and  $\pi \in \operatorname{Perm}(\mathbb{A})$ , which implies  $\operatorname{supp} f(x) \subseteq \operatorname{supp} x$  for all  $x \in X$ . Similarly, a subset X has support S if  $\pi \cdot x \in X$  for all  $x \in X$  and permutations  $\pi$  such that  $\pi(a) = a$  for all  $a \in S$ . X is uniformly finitely supported if  $\bigcup_{x \in X} \operatorname{supp}(x)$  is finite, in which case X is also finitely supported. A uniformly finitely supported equivariant set consists of only elements that are themselves equivariant.

The coproduct of nominal sets  $X_i$   $(i \in I)$  is given by their disjoint union  $\prod_{i \in I} X_i = \{(i, x) \mid i \in I, x \in X_i\}$  with groups action inherited from the  $X_i$ , that is,  $\pi \cdot (i, x) = (i, \pi \cdot x)$ .

Given a nominal set X, the *orbit* of an element  $x \in X$  is the set  $\{\pi \cdot x \mid \pi \in \mathsf{Perm}(\mathbb{A})\}$ . The orbits form a partition of X. A nominal set is *orbit-finite* if it has finitely many orbits. For every finite set  $S \subseteq \mathbb{A}$ , an orbit-finite nominal set contains only finitely many elements supported by S. The *degree* of an orbit-finite nominal set X is  $\deg(X) = \max_{x \in X} |\mathsf{supp}(x)|$ .

▶ **Example A.1.** The nominal set  $\mathbb{A}^*$  has infinitely many orbits; its equivariant subsets  $\mathbb{A}^n$  (words of a fixed length *n*) are orbit-finite. For instance,  $\mathbb{A}^2$  has the two orbits  $\{aa : a \in \mathbb{A}\}$  and  $\{ab : a \neq b \in \mathbb{A}\}$ . Another example of an orbit-finite nominal set is

 $\mathbb{A}^{\#n} = \{a_1 \dots a_n \mid a_i \neq a_j \text{ for } i \neq j\},\$ 

an equivariant subset of  $\mathbb{A}^n$  with just a single orbit. Both  $\mathbb{A}^{\# n}$  and  $\mathbb{A}^n$  have degree n.

**Details for Theorem 3.11.** We prove the claim that all bar automata (bar NFAs/bar Büchi automata/bar NFTAs) have an equi-expressive nominal model in more detail. The claim was proven for bar NFAs and regular non-deterministic nominal automata (RNNA) in the original paper by Schröder et al. [49, Corollary 5.14], but for both bar Büchi automata [52, Proof of Thm. 6.2] as well as bar NFTAs [47, Proof of Thm. 6.3] only one direction (nominal to

bar automaton) was shown. We begin by recalling basic definitions for both Büchi RNNAs and regular nominal tree automata (RNTA), and then show that every bar automaton has a corresponding nominal automaton accepting the same bar language.

**Büchi Automata** First, we recall the necessary nominal automata from [47, 49, 52]:

- ▶ Definition A.2 (RNNA [49] and Büchi RNNA [52]). 1. An RNNA A = (Q, R, q<sub>0</sub>, F) is given by an orbit-finite nominal set Q of states, an equivariant relation R ⊆ Q × Ā × Q specifying transitions, an initial state q<sub>0</sub> ∈ Q and an equivariant set F ⊆ Q of final states. We write q <sup>σ</sup>→ q' if (q, σ, q') ∈ R. The transitions are subject to two conditions:
  - **a.**  $\alpha$ -invariance: if  $q \xrightarrow{|a|} q'$  and  $\langle a \rangle q' = \langle b \rangle q''$ , then  $q \xrightarrow{|b|} q''$ .
  - **b.** Finite branching up to  $\alpha$ -invariance: For every  $q \in Q$  the sets  $\{(a,q') \mid q \xrightarrow{a} q'\}$  and  $\{\langle a \rangle q' \mid q \xrightarrow{a} q'\}$  are finite (equivalently, uniformly finitely supported).
- 2. A Büchi RNNA is an RNNA  $A = (Q, R, q_0, F)$  accepting infinite bar strings as follows: Given  $w = \sigma_1 \sigma_2 \cdots \in \overline{\mathbb{A}}^{\omega}$  and a state  $q \in Q$ , a run for w from q is an infinite sequence of transitions  $q \xrightarrow{\sigma_1} q_1 \xrightarrow{\sigma_2} \cdots$ . The run is accepting if  $q_n$  is final for infinitely many  $n \in \mathbb{N}$ . The state q accepts w if there is an accepting run for w from q, and A accepts w if its initial state  $q_0$  does. The literal ( $\omega$ -)language  $L_0(A)$  is defined by all infinite bar strings accepted by A, while its bar ( $\omega$ -)language  $L_{\alpha}(A) = \{w' \in \overline{\mathbb{A}}^{\omega} \mid \exists w \in L_0(A) : w' \equiv_{\alpha} w\}$  is the closure of  $L_0(A)$ .

The idea of the constructions below is rather simple: We add *registers* to each state of the bar automaton over  $\overline{\mathbb{A}}_0$ , namely one for every plain name  $a_i \in \overline{\mathbb{A}}_0 \cap \mathbb{A}$  of the alphabet. We then consider the  $a_i$ -transitions in the bar automaton as a 'placeholder' for the value stored in the corresponding register. Bar transitions *can* but do not need to store names and are extended with respect to  $\alpha$ -equivalence. The resulting nominal state set will be one of all partial injective maps, i.e. partial register assignments. In more detail:

▶ **Definition A.3.** For  $n \in \mathbb{N}$ , we write  $\mathbf{n} = \{1, \ldots, n\}$ . We denote by  $\mathbb{A}^{\$n}$  the nominal set of all *partial injective maps* from  $\mathbf{n}$  to  $\mathbb{A}$ , with the pointwise group action. The support of r is  $\{r(x) \mid x \in \mathsf{dom}(r)\}$ , where  $\mathsf{dom}(r)$  is the *domain* of r, i.e. the set of all  $x \in \mathbf{n}$  for which r(x) is defined. The nominal set  $\mathbb{A}^{\$n}$  has  $2^n$  orbits, one for each possible domain. A partial injective map  $\overline{r} \in \mathbb{A}^{\$n}$  extends  $r \in \mathbb{A}^{\$n}$ , denoted  $r \leq \overline{r}$ , if  $\mathsf{dom}(r) \subseteq \mathsf{dom}(\overline{r})$  and r and  $\overline{r}$  coincide on  $\mathsf{dom}(r)$ , that is,  $r(x) = \overline{r}(x)$  for all  $x \in \mathsf{dom}(r)$ . Given  $A \subseteq \mathsf{supp}(r)$ , we write  $r|^A$  for the restriction of r to A. Note that r extends  $r|^A$  and that  $\mathsf{supp}(r|^A) = A$ .

▶ **Construction A.4.** Given a bar Büchi automaton  $A = (Q, \overline{\mathbb{A}}_0, \rightarrow, q_0, F)$  such that  $k := |\overline{\mathbb{A}}_0 \cap \mathbb{A}|$  and  $\overline{\mathbb{A}}_0 \cap \mathbb{A} = \{a_1, \ldots, a_k\}$ , we construct the Büchi RNNA  $\overline{A} = (\overline{Q}, \rightarrow', \overline{q_0}, \overline{F})$  as follows:

- $\overline{Q} := \coprod_{q \in Q} \mathbb{A}^{\mathbf{s}_k};$
- $\overline{q_0} = (q_0, (i \mapsto a_i));$
- $\overline{F} := \coprod_{a \in F} \mathbb{A}^{\mathbf{s}_{\mathbf{k}}};$  and
- transitions  $\rightarrow'$ :
  - $= (q,r) \xrightarrow{b}{\to}' (q',r') \text{ iff } \exists i \leqslant k : r(i) = b \land q \xrightarrow{a_i} q' \land r' \leqslant r;$
  - =  $(q, r) \xrightarrow{ib}{}'(q', r')$  iff there is an  $\alpha \in \overline{\mathbb{A}}_0 \setminus \mathbb{A}$  such that: (i)  $q \xrightarrow{\alpha} q'$ ; (ii) for all  $i \leq k$  if r'(i) = b then  $\alpha = |a_i;$  (iii) for all  $i \in \operatorname{dom}(r')$ : r'(i) = b or r'(i) = r(i); and (iv) if  $\alpha = |a_i|$  and  $i \in \operatorname{dom}(r')$  hold for some i, then r'(i) = b.

▶ Proposition A.5. Let  $A = (Q, \overline{A}_0, \rightarrow, q_0, F)$  be a bar Büchi automaton and  $\overline{A} = (\overline{Q}, \rightarrow', \overline{q_0}, \overline{F})$ the Büchi RNNA of Construction A.4. Then,  $L_{\alpha}(A) = L_0(\overline{A})$ .

**Proof.** ' $\subseteq$ ': Let  $w \equiv_{\alpha} w' \in L_0(A)$  and  $(q_i \xrightarrow{\alpha'_i} q_{i+1})_{i \in \mathbb{N}}$  be an accepting run for  $w' = \alpha'_0 \alpha'_1 \alpha'_2 \cdots \in \overline{A}^{\omega}_0$ . We construct an accepting run for  $w = \alpha_0 \alpha_1 \alpha_2 \cdots \in \overline{A}^{\omega}$ . We define  $r_0: \mathbf{k} \to \mathbb{A}, i \mapsto a_i$  and for all  $i = 1, 2, \ldots$  the map

$$r_{i} \colon \mathbf{k} \to \mathbb{A}, j \mapsto \begin{cases} \mathsf{ub}(\alpha_{i-1}) &, \text{ if } \alpha_{i-1}' = \mathsf{la}_{j} \text{ and } \mathsf{ub}(\alpha) \in \mathsf{FN}(\alpha_{i}\alpha_{i+1}\cdots) \\ r_{i-1}(j) &, \text{ if } \alpha_{i-1} \neq \mathsf{lr}_{i-1}(j) \text{ and } r_{i}(j) \in \mathsf{FN}(\alpha_{i}\alpha_{i+1}\cdots) \\ \bot &, \text{ otherwise.} \end{cases}$$

This results in a run  $((q_i, r_i) \xrightarrow{\alpha_i} (q_{i+1}, r_{i+1}))_{i \in \mathbb{N}}$  for w. Acceptance is obvious by construction of  $\overline{A}$ . Regarding validity, we see that for all  $i \in \mathbb{N} \setminus \{0\}$ ,  $r_i(j)$  is set to some  $\beta \in \mathsf{FN}(\alpha_i \alpha_{i+1} \cdots)$ occurring at positions  $\alpha_k$  such that  $\alpha'_k = a_j$  and not defined if there is no such  $\beta$ . This is obvious from the definition of  $r_i$ . With this, we see that all  $(q_i, r_i) \xrightarrow{\alpha_i} (q_{i+1}, r_{i+1})$  are indeed valid transitions in  $\overline{A}$ .

 $(\supseteq)$ : We simply prove that any accepted infinite bar string  $w \in L_0(\overline{A})$  is  $\alpha$ -equivalent to an accepted infinite bar string of A. Let  $((q_i, r_i) \xrightarrow{\alpha_i} {}'(q_{i+1}, r_{i+1}))_{i \in \mathbb{N}}$  be an accepted run of  $w = \alpha_0 \alpha_1 \alpha_2 \cdots \in \overline{\mathbb{A}}^{\omega}$  in  $\overline{A}$ . Then every transition  $(q_i, r_i) \xrightarrow{\alpha_i} (q_{i+1}, r_{i+1})$  has a corresponding transition  $q_i \xrightarrow{\alpha'_i} q_{i+1}$  with  $\alpha'_i \in \overline{A}_0$  in A. The precise choice of these  $\alpha_i$ 's is irrelevant, i.e. we only assume that each  $\alpha'_i$  witnesses the existential quantifiers in the definition of the transitions  $\xrightarrow{\alpha_i}$ '. However, the mentioned choice is miniscule and affects only with those bar names not immediately stored in a register: Indeed, if  $\alpha_i \in \mathbb{A}$ , there must be some  $j \leq k$  with  $r_i(j) = \alpha_i$ , thereby fixing  $\alpha'_i = a_j$ . If  $\alpha_i \notin \mathbb{A}$  and  $r_{i+1}(j) = \mathsf{ub}(\alpha_i)$ holds for some  $j \leq k$ , then  $\alpha'_i = |a_j|$  is fixed (by condition (ii)). Lastly, if  $\alpha_i \notin \mathbb{A}$  and  $\mathsf{ub}(\alpha_i)$ is unequal to every  $r_{i+1}(j)$ , we see that  $\mathsf{ub}(\alpha_i)$  also does not occur freely in  $\alpha_{i+1}\alpha_{i+2}\cdots$  by a direct consequence of the definition of plain transitions, thus giving an inconsequential choice overall. This run is also accepting by design. We therefore only have to show  $\alpha$ -equivalence of w and  $w' = \alpha'_0 \alpha'_1 \alpha'_2 \cdots$  by definition, that is,  $\alpha$ -equivalence of the prefixes of length n inductively: The base case (n = 0) obviously holds. For the induction step, assume that  $w_n = \alpha_0 \cdots \alpha_{n-1} \equiv_{\alpha} \alpha'_0 \cdots \alpha'_{n-1} = w'_n$  by induction hypothesis. We show  $w_{n+1} \equiv_{\alpha} w'_{n+1}$ . We consider the cases where  $\alpha_n \notin \mathbb{A}$  and  $\alpha_n \in \mathbb{A}$ : The former case holds trivially by definition and Proposition 4.3. For the latter case, if  $\alpha_n \in \mathbb{A}$ , that is,  $(q_n, r_n) \xrightarrow{\alpha_n} (q_{n+1}, r_{n+1})$  and  $\alpha_n = b \in \mathbb{A}$ , there must be some  $j \leq k$ , such that  $r_n(j) = b$  and  $q_n \xrightarrow{a_j} q_{n+1}$ , as well as  $r_{n+1} \leqslant r_n$ . Thus,  $\alpha'_n = a_j$ . There are now two possibilities:

- 1. There has been a prior *b*-transition with a corresponding  $|a_j$ -transition. Then, both indices in the De Bruijn normal form (Proposition 4.3) of  $w_{n+1}$  and  $w'_{n+1}$  must be equal (namely to the index of the last such corresponding transition).
- 2. There has been no prior *b*-transition with corresponding  $|a_j$ -transitions. Thus,  $b = a_j = r_0(j)$  and  $a_j$  is free in  $w_{n+1}$ .  $a_j$  is then also free in  $w'_{n+1}$ , since by condition (iv), if there had been an  $\alpha'_k = |a_j|$  with k < n, the corresponding  $\alpha_k = |c|$  would have been stored in  $r_k(j)$  and all subsequent  $r_i(j)$ 's. This results in the desired  $\alpha$ -equivalence.

By induction, we see that  $w \equiv_{\alpha} w'$  and thus also  $L_{\alpha}(\bar{A}) = L_{\alpha}(A)$ .

▶ Remark A.6. Let  $\overline{\mathbb{A}}_0 \subseteq \overline{\mathbb{A}}$  be a finite alphabet of size  $k_0$  and  $k_1 := |\overline{\mathbb{A}}_0 \cap \mathbb{A}|$ . Then, the Büchi RNNA of Construction A.4 has a degree of  $k_1 \leq k_0$  and  $|Q| \cdot 2^{k_1}$  orbits.

**Tree Automata** While the previously introduced tree automata were bottom-up, its nominal variant of *regular non-deterministic tree automata* (*RNTA*) is top-down. A bar (top-down) non-deterministic finite tree automaton  $A = (Q, \bar{A}_0, \Sigma, q_0, \Delta)$  has an *initial state*  $q_0$  instead

of a set of final states and its transition relation  $\Delta \subseteq Q \times \overline{\mathbb{A}}_0 \times (\coprod_{f/n \in \Sigma} Q^n)$  consists of rewrite rules of the form

$$q(\alpha.f(x_1,\ldots,x_n)) \to \alpha.f(q_1(x_1),\ldots,q_n(x_n)).$$

A run for a tree  $t \in \mathcal{T}_{\overline{A}_0}(\Sigma)$  from  $q \in Q$  is a tree  $\operatorname{run}(t)$  over the signature  $Q \times \overline{A}_0 \times \Sigma$  subject to the following conditions:

- 1. Every node  $\alpha f(t_1, \ldots, t_n)$  in t corresponds to one node  $q \alpha f(t_1', \ldots, t_n')$  in run(t) at the same position and vice versa.
- 2. Every node  $q.\alpha.f(q_1.t_1,\ldots,q_n.t_n)$  in run(t) has a corresponding rewrite rule

$$q(\alpha.f(x_1,\ldots,x_n)) \to \alpha.f(q_1(x_1),\ldots,q_n(x_n)) \in \Delta.$$

**3.** The root node is annotated by q.

A tree  $t \in \mathcal{T}_{\overline{A}_0}(\Sigma)$  is accepted by A iff there is a run for t from  $q_0$ . It is well-known (cf. [13, Thm. 8]) that top-down and bottom-up NFTAs are expressively equivalent by reversing all rewrite rules, swapping final and initial states, and reducing those to a single one. For the proof of equivalence to RNTA, we will only use top-down NFTA for the rest of this section.

▶ Definition A.7 (RNTA [47]). 1. A (top-down) RNTA  $A = (Q, \Sigma, q_0, \Delta)$  is given by an orbit-finite nominal set of states, a finite signature  $\Sigma$ , an initial state  $q_0 \in Q$  and an equivariant set  $\Delta$  of *rewrite rules* of the form

$$q.(\gamma.f(x_1,\ldots,x_n)) \to \gamma.f(q_1(x_1),\ldots,q_n(x_n)),$$

where  $q_1, \ldots, q_n, q \in Q, \gamma \in \overline{\mathbb{A}}, f/n \in \Sigma$  and the  $x_i$  are variables. The rewrite rules are subject to two conditions:

**a.**  $\alpha$ -invariance: For  $q, q_1, \ldots, q_n, q'_1, \ldots, q'_n \in Q$ , if  $\langle a \rangle q_i = \langle b \rangle q'_i$  for all  $1 \leq i \leq n$ , then

$$q(|a.f(x_1,\ldots,x_n)) \to |a.f(q_1(x_1),\ldots,q_n(x_n)) \in \Delta$$
 implies  
$$q(|b.f(x_1,\ldots,x_n)) \to |b.f(q_1'(x_1),\ldots,q_n'(x_n)).$$

**b.** Finite branching up to  $\alpha$ -equivalence: For  $q \in Q$  and  $f/n \in \Sigma$ , the sets

$$\{(a, q_1, \dots, q_n) \mid q(a.f(x_1, \dots, x_n)) \to a.f(q_1(x_1), \dots, q_n(x_n)) \in \Delta\} \text{ and } \{\langle a \rangle (q_1, \dots, q_n) \mid q(|a.f(x_1, \dots, x_n)) \to |a.f(q_1(x_1), \dots, q_n(x_n)) \in \Delta\}$$

are finite (equivalently, uniformly finitely supported).

2. Rewrite rules in RNTAs are applied as with classical (top-down) NFTAs mentioned above. A state  $q \in Q$  accepts a term t if there is a run for t from q. The literal (tree) language  $L_0(A)$  is defined by all terms  $t \in \mathcal{T}_{\overline{A}}(\Sigma)$  accepted by A, while its bar (tree) language  $L_{\alpha}(A) = \{ t' \in \mathcal{T}_{\overline{\mathbb{A}}}(\Sigma) \mid \exists t \in L_0(A) : t' \equiv_{\alpha} t \} \text{ is the closure of } L_0(A).$ 

► Construction A.8. Given a bar top-down NFTA  $A = (Q, \overline{A}_0, \Sigma, q_0, \Delta)$  such that  $k := |\overline{\mathbb{A}}_0 \cap \mathbb{A}|$  and  $\overline{\mathbb{A}}_0 \cap \mathbb{A} = \{a_1, \ldots, a_k\}$ , we construct the RNTA  $\overline{A} = (\overline{Q}, \Sigma, \overline{q_0}, \Delta')$ as follows:

- $\begin{array}{ll} & \overline{Q} := \coprod_{q \in Q} \mathbb{A}^{\$ \mathbf{k}}; \\ & \overline{q_0} = (q_0, (i \mapsto a_i)); \end{array}$
- $\overline{F} := \coprod_{q \in F} \mathbb{A}^{\mathbf{\$k}}; \text{ and}$ rewrite rules  $\Delta'$  (for  $f/n \in \Sigma$ ):

 $\begin{array}{ll} & (q,r)(b.f(x_1,\ldots,x_n)) \to b.f((q_1,r_1)(x_1),\ldots,(q_n,r_n)(x_n)) \in \Delta' \text{ iff there is an } i \leqslant k \\ & \text{such that:} \\ & * r(i) = b; \\ & * \text{ for all } j \leqslant n: r_j \leqslant r; \text{ and} \\ & * q(a_i.f(x_1,\ldots,x_n)) \to a_i.f(q_1(x_1),\ldots,q_n(x_n)) \in \Delta. \\ & = (q,r)(\mathrm{lb}.f(x_1,\ldots,x_n)) \to \mathrm{lb}.f((q_1,r_1)(x_1),\ldots,(q_n,r_n)(x_n)) \in \Delta' \text{ iff there is an } \alpha \in \overline{A}_0 \setminus A \text{ such that:} \\ & * \text{ for all } j \leqslant n, i \leqslant k: \text{ if } r_j(i) = b, \text{ then } \alpha = |a_i; \\ & * \text{ for all } j \leqslant n, i \leqslant k: \text{ if } \alpha = |a_i \text{ and } i \in \mathrm{dom}(r_j), \text{ then } r_j(i) = b; \\ & * \text{ for all } j \leqslant n, i \in \mathrm{dom}(r_j): r_j(i) \in \{b, r(i)\}; \text{ and} \\ & * q(\alpha.f(x_1,\ldots,x_n)) \to \alpha.f(q_1(x_1),\ldots,q_n(x_n)) \in \Delta. \end{array}$ 

▶ Proposition A.9. Let  $A = (Q, \overline{A}_0, \Sigma, q_0, \Delta)$  be a bar (top-down) NFTA and  $\overline{A} = (\overline{Q}, \Sigma, \overline{q_0}, \Delta')$  be the RNTA of Construction A.8. Then,  $L_{\alpha}(A) = L_0(\overline{A})$ .

**Proof.** ' $\subseteq$ ': Let  $t \in L_{\alpha}(A)$ , that is,  $t \equiv_{\alpha} t' \in L_0(A)$  and  $\operatorname{run}(t')$  be the run of t'. We translate this run to a run for t in  $\overline{A}$  by defining a recursive function  $t: \mathbb{A}^{\$\mathbf{k}} \times \mathcal{T}_{Q \times \overline{\mathbb{A}}_0}(\Sigma) \to \mathcal{T}_{\overline{Q} \times \overline{\mathbb{A}}}(\Sigma)$  via

$$\mathsf{t}(r,\alpha'.f(t_1',\ldots,t_n')) = (q,r).(\alpha.f(\mathsf{t}(r_1,t_1'),\ldots,\mathsf{t}(r_n,t_n'))),$$

where  $\alpha f$  is the corresponding node to  $\alpha' f$  in t. The  $r_i \in \mathbb{A}^{\mathbf{k}}$  are defined pointwise, we have

$$r_i \colon \mathbf{k} \to \mathbb{A}, j \mapsto \begin{cases} \mathsf{ub}(\alpha) &, \text{ if } \alpha' = |a_j \text{ and } a_j \in \mathsf{FN}(t'_i) \\ r(j) &, \text{ if } \alpha \neq |r(j) \text{ and } r(j) \in \mathsf{FN}(t_i) \\ \bot &, \text{ otherwise.} \end{cases}$$

We readily verify that  $t(r_0, t')$  is a run for t from  $\overline{q_0}$ : Conditions 1 and 3 are satisfied by construction. Regarding condition 2 for an arbitrary node  $(q, r) \cdot \alpha \cdot f((q_1, r_1) \cdot t_1, \dots, (q_n, r_n) \cdot t_n)$ in  $t(r_0, t')$ , we check that there is a rewrite rule

$$(q,r)(\alpha.f(x_1,\ldots,x_n)) \to \alpha.f((q_1,r_1)x_1,\ldots,(q_n,r_n)x_n) \in \Delta'.$$

This is obvious for  $\alpha \in \overline{\mathbb{A}} \setminus \mathbb{A}$ , while for  $\alpha \in \mathbb{A}$  it follows directly from the definition of  $r_0$ and all subsequent  $r_i$ 's. Thus,  $t \in L_0(\overline{A})$ .

' $\supseteq$ ': We show that any  $t \in L_0(\overline{A})$  is  $\alpha$ -equivalent to some  $t' \in L_0(A)$ . Let  $\operatorname{run}(t)$  be the run for t in  $\overline{A}$ , then by condition 2 all nodes  $(q, r).\alpha.f((q_1, r_1).t_1, \ldots, (q_n, r_n).t_n)$  come from rewrite rules  $q(\alpha'.f(x_1, \ldots, x_n)) \to \alpha'.f(q_1(x_1), \ldots, q_n(x_n))$  in A. Thus, replacing any  $\alpha$  in t by the corresponding  $\alpha'$  results in some  $t' \in L_0(A)$ .  $\alpha$ -Equivalence is readily verified using the De Bruijn normal form Proposition 4.8 as well as conditions on rewrite rules in  $\overline{A}$ . (The proof follows the structure and idea of the one in Proposition A.5)

▶ **Remark A.10.** Let  $\overline{\mathbb{A}}_0 \subseteq \overline{\mathbb{A}}$  be a finite alphabet of size  $k_0$  and  $k_1 := |\overline{\mathbb{A}}_0 \cap \mathbb{A}|$ . Then, the RNTA of Construction A.8 has a degree of  $k_1 \leq k_0$  and  $|Q| \cdot 2^{k_1}$  orbits.

**Proof of Proposition 3.14.** This follows directly from Theorem 3.11: Let  $\overline{\mathbb{A}}_0$  be of cardinality  $k_0$  and  $k_1 := |\overline{\mathbb{A}}_0 \cap \mathbb{A}|$  and n be the number of states of the bar automaton A. We translate A to the equi-expressive nominal one  $\overline{A}$  (Constructions A.4, A.8 and [49, Constr. 5.10]), such that  $L_0(\overline{A}) = L_\alpha(A)$ .  $\overline{A}$  has  $n \cdot 2^{k_1}$  orbits and a degree of  $k_1$ . Afterward, we translate  $\overline{A}$  back to a bar automaton over  $\overline{\mathbb{A}}_0$  with  $\mathcal{O}(n \cdot 2^{k_1} \cdot 2^{k_0 \cdot \log(k_0)}) \subseteq \mathcal{O}(n \cdot 2^{k_0 \cdot (\log(k_0)+1)})$  states.

This translation is layed out (together with the respective complexity) in the papers on the corresponding nominal automaton [49, Thm. 5.13], [52, Proof of Thm. 6.2] and [47, Proof of Thm. 6.3].

**Details for Example 3.13.** We begin by recalling necessary notions to make our argument from Moerman and Sammartino [42]:

▶ **Definition A.11** ([17, 42]). Given a data language  $L \subseteq \mathbb{A}^*$  and a data word  $u \in \mathbb{A}^*$ , we define the *derivative of* L *w.r.t.* u by  $u^{-1}L := \{v \mid uv \in L\}$ . The set of all derivatives is defined by  $\mathsf{Der}(L) := \{u^{-1}L \mid u \in \mathbb{A}^*\}$ .

▶ Definition A.12 ([42, Defn. 2.7]). A nominal automaton is *residual* if all states accept derivatives of the language of the automaton. A data language L is *residual* if there is a residual nominal automaton accepting L.

- ▶ Definition A.13 ([42, Defn. 4.3]). 1. For some nominal set X, we consider the nominal set  $\mathscr{P}_{\mathsf{fs}}(X)$  of finitely supported subsets as a Boolean algebra where all necessary operations  $(\land, \lor, \neg)$  and the finitely supported join  $\bigvee : \mathscr{P}_{\mathsf{fs}}(\mathscr{P}_{\mathsf{fs}}(X)) \to \mathscr{P}_{\mathsf{fs}}(X)$  are equivariant.
- 2. Let  $Y \subseteq \mathscr{P}_{\mathsf{fs}}(X)$  be equivariant and  $y \in Y$ . Then, y is *join-irreducible in* Y if  $y = \bigvee \mathscr{Y} \implies y \in \mathscr{Y}$  for every finitely supported  $\mathscr{Y} \subseteq Y$ . The subset of all join-irreducible elements of Y is defined by  $\mathsf{JI}(Y) := \{y \in Y \mid y \text{ is join-irreducible in } Y\}.$
- **3.** A subset  $Y \subseteq \mathcal{P}_{\mathsf{fs}}(X)$  generates a subset  $Z \subseteq \mathcal{P}_{\mathsf{fs}}(X)$  if  $Z \subseteq \{ \bigvee y \mid y \subseteq Y \text{ f.s.} \}$ .

▶ Theorem A.14 ([42, Thm. 4.10]). A data language L is residual iff the set JI(Der(L)) is orbit-finite and generates Der(L).

We consider the data language

 $D(L) = \{ uabvacwbc \mid u, v, w \in \mathbb{A}^*, a \neq b, b \neq c \in \mathbb{A} \}.$ 

There is the following infinite ascending chain of derivatives in the poset  $\mathsf{Der}(D(L))$ :

$$D(L) \subsetneq a^{-1}D(L) \subsetneq ba^{-1}D(L) \subsetneq cba^{-1}D(L) \subsetneq \cdots$$
(2)

To reject residuality of D(L), we prove that all derivatives in Equation (2) are join-irreducible, whence  $\mathsf{JI}(\mathsf{Der}(L))$  is not orbit-finite.

▶ Lemma A.15 (Join-Irreducibleness). All the derivatives in Equation (2) are join-irreducible.

**Proof.** Consider  $w = a_k \cdots a_1 a_0 \in \mathbb{A}^*$  with  $k \ge 2$  and all  $a_i$  distinct. We show that  $w^{-1}D(L)$  is join-irreducible in Der(D(L)). For this, we notice that  $u^{-1}D(L) \subseteq w^{-1}D(L)$  holds iff u is a suffix of w. The direction " $\Leftarrow$ " is simple, since any prefix may be skipped ( $\mathbb{A}^*$ ). So suppose then that u is not a prefix of w, i.e. that there no v such that  $w \ne vu$ . Knowing this, there exists an  $i \ge 0$  with  $x \ne a_i$  and u contains the suffix  $xa_{i-1} \cdots a_0$ . Choose a fresh  $a_{-1}$ . If  $x = a_k$  for some k, let  $c := a_{k-1}$ , otherwise choose c fresh.

With this choice, we see that  $a_{-1}xca_{i-1}c \in u^{-1}D(L)$ . We then show  $a_{-1}xca_{i-1}c \notin w^{-1}D(L)$  by exhaustion: If x does not occur in w, then c is fresh for w, which means that all letters in  $wa_{-1}xca_{i-1}c$  are unique except for  $a_{i-1}$  which occurs twice even with different successors, which do not occur after the last pair with  $a_{i-1}$ . Therefore,  $a_{-1}xca_{i-1}c \notin w^{-1}D(L)$ . If  $x = a_k$  for some k, and therefore  $c = a_{k-1}$ , then  $wa_{-1}xca_{i-1}c$  mentions  $a_k$  and  $a_{i-1}$  twice, and  $a_{k-1}$  trice, however not in the form required by D(L), since the different

successors of the repeated letters are not repeated. Therefore,  $a_{-1}xca_{i-1}c \notin w^{-1}\mathcal{L}_{\alpha,\mathsf{lf}}$ . We have thus shown the following:

$$\{u \mid u^{-1}D(L) \subseteq w^{-1}D(L)\} = \{u \mid u \text{ is a suffix of } w\}.$$

Now consider  $X = \bigvee \{u^{-1}D(L) \mid u \text{ is a strict suffix of } w\}$  and see that  $X \neq w^{-1}D(L)$ , since  $a_k a_0 a_{k-1} a_0 \in w^{-1}D(L) \setminus X$ , thereby making  $w^{-1}D(L)$  join-irreducible.

**Corollary A.16.** The language D(L) is not residual.

▶ Remark A.17. There is another notion of *non-guessing residuality* mentioned by Moerman and Sammartino [42], which is a subset of the aformentioned residuality requiring the residual automaton to be *non-guessing*. While D(L) is accepted by a *non-guessing* nominal automaton (Section 3.3), it cannot be accepted by a (non-guessing) residual automaton. Overall, the modified version of  $\nu$ NL<sup>\*</sup> ([42]) cannot ensure termination for the data language D(L) due to its non-residuality.

# B Details for Section 4

We prove that the normal form for bar strings is stable under permutations and concatenations to the left:

▶ Lemma B.1. Let  $w \in \overline{\mathbb{A}}^*$  be a bar string and  $\pi \in \text{Perm}(\mathbb{A})$  a permutation. Then  $nf(\pi \cdot w) = \pi \cdot nf(w)$ , where permutations act trivially on natural numbers.

**Proof.** Let  $w = \alpha_1 \cdots \alpha_n$ ,  $\operatorname{nf}(w) = \beta_1 \cdots \beta_n$  and  $\operatorname{nf}(\pi \cdot w) = \gamma_1 \cdots \gamma_n$  be defined as above. We show that  $\gamma_i = \pi \cdot \beta_i$  holds for all *i* by case distinction: If  $\beta_i \in A$ , then  $\alpha_i$  is free in w as is  $\pi(\alpha_i)$  in  $\pi \cdot w$ . Therefore,  $\gamma_i = \pi(\alpha_i) = \pi(\beta_i)$ . If  $\beta_i = k$  and *k* does not occur in  $\beta_1 \cdots \beta_{i-1}$ , then  $\alpha_i = |a \in \overline{A}$  and  $\alpha_1 \cdots \alpha_{i-1}$  contain k-1 bar names. However, so does  $\pi \cdot (\alpha_1 \cdots \alpha_{i-1})$  and  $\pi \cdot \alpha_i = |\pi(a) \in \overline{A}$ . Therefore,  $\gamma_i = k = \pi \cdot \beta_i$ . Lastly, if  $\beta_i = k$  and *k* occurs in  $\beta_1 \cdots \beta_{i-1}$ , let j < i denote the smallest index with  $\beta_j = k$ . Existence of such a *j* is obvious by design. Additionally,  $\alpha_i \in A$  and  $\alpha_j = |\alpha_i|$ . Then,  $\pi(\alpha_i) \in A$  and  $\pi \cdot \alpha_j = |\pi(\alpha_i)$  and there is no index  $\ell > j$  with  $\pi \cdot \alpha_\ell = |\pi(\alpha_i)$ . Therefore,  $\gamma_j = k$  (by the argument before) and  $\gamma_i = k$ .

▶ **Remark B.2.** Note that for a permutation  $\pi$  that does not change any free letters of the word w, we have  $nf(w) = nf(\pi \cdot w)$ .

▶ Lemma B.3. Let  $v, w, x \in \overline{\mathbb{A}}^*$  be bar strings. If nf(w) = nf(v), then nf(xw) = nf(xv).

**Proof.** Let  $w = \alpha_1 \cdots \alpha_n$ ,  $x = \beta_1 \cdots \beta_k$ ,  $\mathsf{nf}(x) = \gamma_1 \cdots \gamma_k$  and  $\mathsf{nf}(w) = \gamma'_1 \cdots \gamma'_n$ . Then  $\mathsf{nf}(xw) = \delta_1 \cdots \delta_{n+k}$  is given as follows: For  $1 \leq i \leq k$ , we have  $\delta_i = \gamma_i$ . Let  $\ell = \max\{\gamma_i \in \mathbb{N} \mid 1 \leq i \leq k\}$ . If  $\gamma'_{i-k} \in \mathbb{N}$ , then  $\delta_i = \gamma'_{i-k} + \ell$ . This is easily seen, since if  $\gamma'_{i-k} = j$  and if j does not occur in  $\gamma'_1 \cdots \gamma'_{i-k-1}$ , there is a bar name in w at position i - k and j - 1 bar names occur prior to it. Since the prefix x has  $\ell$  bar names, there is still a bar name in xw at position i but now there are  $j - 1 + \ell$  bar names prior to this position. Similarly, if  $\gamma'_{i-k} = j$  occurs in  $\gamma'_1 \cdots \gamma'_{i-k-1}$  first at position m < i - k, then there is a plain name in w at position i - k that corresponds to the bar name at position m such that this bar name does not occur between positions m and i - k. The prefix again does not change anything in this situation besides increasing the level from j to  $j + \ell$  because there are  $\ell$  more bar names before position m. This makes the above definition the De Bruin normal form for xw, which depends only on  $\mathsf{nf}(w)$  and  $\mathsf{nf}(x)$ . Therefore,  $\mathsf{nf}(xw) = \mathsf{nf}(xv)$ , since  $\mathsf{nf}(w) = \mathsf{nf}(v)$ .

**Proof of Proposition 4.3.** ( $\Rightarrow$ ): Let  $w \equiv_{\alpha} v$  be in one step, that is,  $w = |aw' \equiv_{\alpha} |bv' = v$  by  $\langle a \rangle w' = \langle b \rangle v'$ . This is without loss of generality, since syntactic equality is transitive and prefixes do not change equality of normal forms (Lemma B.3). Thus, we have some fresh  $c \in \mathbb{A}$  such that  $(a \ c) \cdot w' = (b \ c) \cdot v'$  and also  $(a \ c) \cdot w = (b \ c) \cdot v$ . By Lemma B.1 and Remark B.2, we see that  $\mathsf{nf}(w) = \mathsf{nf}((a \ c) \cdot w) = \mathsf{nf}((b \ c) \cdot v) = \mathsf{nf}(v)$ .

( $\Leftarrow$ ): We first show that given bar strings w = xu and v = xy with longest joint prefix x and identical normal form  $\mathsf{nf}(w) = \mathsf{nf}(v) = \gamma_1 \cdots \gamma_n$ , either w = v or two  $\alpha$ -equivalent w' = x'u' and v' = x'y' exist, i.e.  $w \equiv_{\alpha} w'$  and  $v \equiv_{\alpha} v'$ , such that |x'| > |x|. This implies the statement using an iterative process. If |x| = |w|, then w = v by design, so assume |x| < |w| and  $w \neq v$ . Because x is the longest joint prefix of w and v, and both normal forms are equal  $(\mathsf{nf}(w) = \mathsf{nf}(v))$ , we see that both u and y start with different bar names, say |a| and |b| for  $a \neq b$ . Let the level, i.e. the value in the normal form, of those bar names be  $\ell$ . Let  $c \in \mathbb{A}$  be a fresh name for w and v, then both  $xu \equiv_{\alpha} x((a \ c) \cdot u)$  and  $xy \equiv_{\alpha} x((b \ c) \cdot y)$  are  $\alpha$ -equivalences. Additionally, it is easy to verify that both  $x((a \ c) \cdot u) = \alpha_1 \cdots \alpha_n$  and  $x((b \ c) \cdot y) = \beta_1 \cdots \beta_n$  coincide up to the index j where  $\gamma_j = \ell + 1$ . Thus, we obtain the decomposition  $x' = \alpha_1 \cdots \alpha_{j-1}, u' = \alpha_j \cdots \alpha_n$  and  $y' = \beta_j \cdots \beta_n$ . Because of the construction of the De Bruijn normal form, we have |x'| > |x|. Thus, we arrive at a sequence of  $\alpha$ -equivalent strings proving the equivalence  $w \equiv_{\alpha} v$ .

# **Proof of Proposition 4.5.**

**Proof.** The 'only if'-direction is trivial by definition of  $\alpha$ -equivalence on infinite bar strings. For the 'if'-direction, we assume  $p_1 \equiv_{\alpha} p_2$  and show  $(u_1 v_1^{\omega})_n \equiv_{\alpha} (u_2 v_2^{\omega})_n$  for every  $n \in \mathbb{N}$ . Let *m* be the length of  $p_1$  (and  $p_2$ ), then  $(u_1 v_1^{\omega})_n \equiv_{\alpha} (u_2 v_2^{\omega})_n$  holds for every  $n \leq m$ . For n > m, we show equality of the De Bruijn normal forms  $\mathsf{nf}((u_1 v_1^{\omega})_n) = \alpha_1 \cdots \alpha_n$  and  $\mathsf{nf}((u_2 v_2^{\omega})_n) = \beta_1 \cdots \beta_n$  (Proposition 4.3). We have equality of  $\alpha_i$  and  $\beta_i$  for  $i \leq m$  by assumption. For i > m, suppose  $\alpha_i \neq \beta_i$ . We proceed by case distinction.

- 1. Suppose that  $\alpha_i, \beta_i \in \mathbb{A}$ . This means that there are free letters  $a \neq b$  at position i in  $(u_1v_1^{\omega})_n$  and  $(u_2v_2^{\omega})_n$  occurring by design in  $v_1$  or  $v_2$  at some positions  $i_1$  and  $i_2$ . However, note that due to the length of each  $p_i$ , every combination of positions of  $v_1$  and  $v_2$  occurs somewhere in the finite prefixes  $p_1$  and  $p_2$  at the same positions. In other words, there must be a position j < m in  $(u_1v_1^{\omega})_n$  and  $(u_2v_2^{\omega})_n$  with the letters of position  $i_1$  or  $i_2$  in  $v_1$  or  $v_2$ , respectively. Since both letters are free at position i, they must be free at position j, thereby contradicting the  $\alpha$ -equivalence of  $p_1$  and  $p_2$ .
- 2. Suppose that  $\alpha_i \in \mathbb{A}$  and  $\beta_i \in \mathbb{N}$ . This also contradicts our assumption of  $p_1 \equiv_{\alpha} p_2$ : This means that at position *i* there is a free letter  $a \in \mathbb{A}$  in  $(u_1v_1^{\omega})_n$  and a bar name or bound letter in  $(u_2v_2^{\omega})_n$ . Suppose that they occur at positions  $i_1$  and  $i_2$  in  $v_1$  and  $v_2$ , respectively. Again, due to the length of  $p_1$  and  $p_2$ , there must be a position  $|u_1| + \max\{|v_1|, |v_2|\} < j < m$ , where positions  $i_1$  and  $i_2$  in  $v_1$  and  $v_2$  occur. Clearly the letter *a* at position *j* in the first prefix is again free, leading to direct contradiction, if the letter at position  $i_2$  in  $v_2$  is a bar name. If the letter at position  $i_2$  in  $v_2$  is plain (and bound), then the corresponding bar name for position *i* occurs either in  $u_2$ , the directly preceeding iteration of  $v_2$  (whence in  $v_2$  after position  $i_2$ ), or in  $v_2$  before position  $i_2$ . Since the position *j* also plain and bound, contradicting the presumed  $\alpha$ -equivalence of  $p_1$ and  $p_2$ . The case  $\alpha_i \in \mathbb{N}$  and  $\beta_i \in \mathbb{A}$  follows analogously.
- 3. Suppose that  $\alpha_i \neq \beta_i \in \mathbb{N}$ . The case where there is a bar name in one string and a plain name in the other at position *i*, follows analogously from the previous case. Therefore, suppose that there are two bar names at position *i* in  $(u_1 v_1^{\omega})_n$  and  $(u_2 v_2^{\omega})_n$ . Since the

indices of bar names indicate the number of other bar names before that position in the bar string, there must be a position j < i, where there is a bar name in one string and a plain name in the other, leading to a contradiction as shown in the previous case. Lastly, if two plain names occur at position i in  $(u_1v_1^{\omega})_n$  and  $(u_2v_2^{\omega})_n$  (and by design in  $v_j$  at position  $i_j$  for j = 1, 2), we see that either there is a position j < m (repeating the positions  $i_1$  and  $i_2$ ) with  $\alpha_j \neq \beta_j \in \mathbb{N}$  leading directly to a contradiction or there is some position in between where there is a bar name in one and plain name in the other, leading to a contradiction as shown in the previous case.

Therefore, we have  $\alpha_i = \beta_i$ . By Proposition 4.3, we conclude that  $(u_1v_1^{\omega})_n \equiv_{\alpha} (u_2v_2^{\omega})_n$  holds, as desired.

▶ Lemma B.4. De Bruijn normal forms for bar  $\Sigma$ -trees are stable under permutations:  $\pi \cdot nf(t) = nf(\pi \cdot t)$  for  $\pi \in Perm(\mathbb{A})$  and  $t \in \mathcal{T}_{\mathbb{A}}(\Sigma)$ .

**Proof.** We show the desired equality node by node: Let  $\gamma . f(t_1, \ldots, t_n)$  ( $\gamma \in \mathbb{A} + \mathbb{N}, f/n \in \Sigma$ ) be a node in  $\mathsf{nf}(\pi \cdot t)$  corresponding to nodes  $\pi(\alpha) . f(\pi \cdot t'_1, \ldots, \pi \cdot t'_n)$  ( $\alpha \in \overline{\mathbb{A}}$ ) in  $\pi \cdot t$ ,  $\alpha . f(t'_1, \ldots, t'_n)$  in t and  $\delta . f(t''_1, \ldots, t''_n)$  ( $\delta \in \mathbb{A} + \mathbb{N}$ ) in  $\mathsf{nf}(t)$ . We show  $\gamma = \pi \cdot \delta$  by case distinction:

If  $\delta \in \mathbb{A}$ , then  $\alpha$  is a free occurrence in t, thereby making  $\pi(\alpha)$  a free occurrence in  $\pi \cdot t$ , which implies that  $\gamma = \pi(\delta)$ .

If  $\delta = k$  and there is no prior node  $k.g(s_1, \ldots, s_m)$  for  $g/m \in \Sigma$  in the branch from the root of nf(t), then  $\alpha = |a \in \overline{\mathbb{A}}$  and there are k - 1 bar names before the node in the branch from the root of t. Since the same number of bar names also occur in  $\pi \cdot t$ , we have  $\gamma = k$ .

Lastly, we consider the case where  $\delta = k$  and there is a prior node  $k.g(s_1, \ldots, s_m)$  for  $g/m \in \Sigma$  in the brach from the root of nf(t). Let  $k.g(s_1, \ldots, s_m)$  be the earliest of those nodes. The corresponding node  $\beta.g(s'_1, \ldots, s'_m)$  in t has  $\beta = |a \in \overline{\mathbb{A}}$ , making  $\alpha = a$ . In  $\pi \cdot t$ , the corresponding node is  $|\pi(a).g(s''_1, \ldots, s''_m)$ , and this is the last node with  $|\pi(a)$  in the branch from the root to  $\pi(\alpha).f$ . As in the argument for the previous case, the node corresponding to k.g in  $nf(\pi \cdot t)$  is also k.g, hence  $\gamma = k$ .

▶ **Remark B.5.** Similarly to Remark B.2, we see that for a permutation  $\pi$  that does not change any free letters of the tree t, we have  $nf(t) = nf(\pi \cdot t)$ .

▶ Lemma B.6. Let C be a context with k holes and  $s_1, \ldots, s_k$  as well as  $t_1, \ldots, t_k$  be bar  $\Sigma$ -trees satisfying  $nf(s_i) = nf(t_i)$  for  $1 \leq i \leq k$ . Then,  $nf(C[s_1, \ldots, s_k]) = nf(C[t_1, \ldots, t_k])$ .

**Proof.** We show the desired equality of normal forms node by node: Let  $\ell_i$  for  $1 \leq i \leq k$  denote the number of bar names in C in the branch from the root to the *i*-th hole. It is evident that nodes  $\gamma.f(u_1,\ldots,u_m)$ , for  $\gamma \in \mathbb{A} + \mathbb{N}$ ,  $f/m \in \Sigma$ , corresponding to nodes in the context are equal in both normal forms. Let  $\gamma.f(u_1,\ldots,u_m)$  for  $\gamma \in \mathbb{A} + \mathbb{N}$ ,  $f/m \in \Sigma$  in  $\mathsf{nf}(C[s_1,\ldots,s_k])$  be a node corresponding to  $\alpha.f(u'_1,\ldots,u'_m)$  in  $s_i$  for  $1 \leq i \leq k$  and to  $\delta.f(u''_1,\ldots,u''_m)$  in  $\mathsf{nf}(s_i) = \mathsf{nf}(t_i)$ . We shall now prove that  $\gamma$  only depends on  $\mathsf{nf}(s_i)$  and C. We proceed by case distinction:

Firstly, if  $\delta \in \mathbb{N}$ , then we show  $\gamma = \delta + \ell_i$ . Indeed, if  $\alpha = |a \in \overline{\mathbb{A}}$ , then there are  $\delta - 1$  bar names in  $s_i$  on the branch from the root to the node  $\alpha.f$ . Thus, we have  $\delta - 1 + \ell_i$  bar names in  $C[s_1, \ldots, s_k]$  on the branch from the root to this node  $\alpha.f$ . Hence, by definition  $\gamma = \delta + \ell_i$ . If  $\alpha$  is a plain name bound by a bar name in  $s_i$  in the branch from the root to the node, then that bar name is replaced with the number  $\delta + \ell_i$  in  $\mathsf{nf}(C[s_i, \ldots, s_k])$ ; in symbols:  $\gamma = \delta + \ell_i$ .

Secondly, if  $\delta \in \mathbb{A}$  and there is no node  $|\delta g|$  in the branch from the root to hole *i* in the context *C*, then  $\delta$  remains free in the branch from the root to the node in  $C[s_1, \ldots, s_k]$ . Thus, we have  $\gamma = \delta$ .

Lastly, if  $\delta \in \mathbb{A}$  and there is a node  $|\delta g|$  in the branch from the root to hole *i* in the context C, then take the last of these. In fact, this (last) node corresponds to j.g in  $nf(C[s_1, \ldots, s_k])$ . Thus, we have  $\gamma = j$ .

This finishes our argument that  $\gamma$  only depends on  $\mathsf{nf}(s_i)$  and C. Since  $\mathsf{nf}(s_i) = \mathsf{nf}(t_i)$  for all  $i = 1, \ldots, k$ , we can thus conclude that  $\mathsf{nf}(C[s_1, \ldots, s_k])$  and  $\mathsf{nf}(C[t_1, \ldots, t_k])$ , as desired.

**Proof of Proposition 4.8.** ( $\Rightarrow$ ): Let  $s \equiv_{\alpha} t$  in one step at the root, that is,  $s = |a.f(s_1, \ldots, s_n)$ ,  $|b.f(t_1, \ldots, t_n) = t$  for  $a, b \in \mathbb{A}$ ,  $f/n \in \Sigma$  and  $s_i, t_i \in \mathcal{T}_{\mathbb{A}}(\Sigma)$  with  $\langle a \rangle (s_1, \ldots, s_n) = \langle b \rangle (t_1, \ldots, t_n)$ . This is without loss of generality, since contexts do not change the equality of normal forms (Lemma B.6). Therefore, we have a fresh  $c \in \mathbb{A}$  such that  $(a \ c) \cdot s_i = (b \ c) \cdot t_i$  for all  $1 \leq i \leq n$  and thus also  $(a \ c) \cdot s = (b \ c) \cdot t$ . By Lemma B.4 and Remark B.5, we see that

$$nf(s) = nf((a \ c) \cdot s) = nf((b \ c) \cdot t) = nf(t).$$

( $\Leftarrow$ ): Let  $\mathsf{nf}(s) = \mathsf{nf}(t)$ . We show  $s \equiv_{\alpha} t$  using an iterative process as follows. If s = t, then we are done. Otherwise, let C be the maximal context such that  $s = C[s_1, \ldots, s_k]$  and  $t = C[t_1, \ldots, t_k]$ . By the maximality of C and since  $\mathsf{nf}(s) = \mathsf{nf}(t)$ , we know that there exist  $s_j$  and  $t_j$  such that  $s_j = |a.f(s'_1, \ldots, s'_n)$  and  $t_j = |b.f(t'_1, \ldots, t'_n)$  for  $a \neq b \in \mathbb{A}$  and  $f/n \in \Sigma$ . Now choose a  $c \in \mathbb{A}$  fresh for both  $s_j$  and  $t_j$ . Then, we have  $s_j \equiv_{\alpha} (a \ c) \cdot s_j$  and  $t_j \equiv_{\alpha} (b \ c) \cdot t_j$ and, moreover,  $(a \ c) \cdot s_j$  and  $(b \ c) \cdot t_j$  coincide in the root node |c.f. Thus, we have a non-trivial context C', say with i holes, such that  $s_j \equiv_{\alpha} C'[s_1^j, \ldots, s_i^j]$  and  $t_j \equiv_{\alpha} C'[t_1^j, \ldots, t_i^j]$ . Therefore we have a non-trivial context C'' which is strictly bigger than C and such that

$$s \equiv_{\alpha} C''[s_1, \dots, s_{j-1}, s_1^j, \dots, s_i^j, s_{j+1}, \dots, s_k] \text{ and } t \equiv_{\alpha} C''[t_1, \dots, t_{j-1}, t_1^j, \dots, t_i^j, t_{j+1}, \dots, t_k].$$

If the two right-hand sides are equal, then we are done. Otherwise, we continue to pick Now either the two right-hand sides are equal or we continue as before. By the finiteness of s and t, this eventually yields  $s \equiv_{\alpha} t$ .