Qubit-Based Framework for Quantum Machine Learning: Bridging Classical Data and Quantum Algorithms

Bhavna Bose and Saurav Verma

Mukesh Patel School of Technology Management and Engineering, SVKM's NMIMS

This paper dives into the exciting and rapidly growing field of quantum computing, explaining its core ideas, current progress, and how it could revolutionize the way we solve complex problems. It starts by breaking down the basics, like qubits, quantum circuits, and how principles like superposition and entanglement make quantum computers fundamentally different-and far more powerful for certain tasks—than the classical computers we use today. We also explore how quantum computing deals with complex problems and why it's uniquely suited for challenges classical systems struggle to handle. A big part of this paper focuses on Quantum Machine Learning (QML), where the strengths of quantum computing meet the world of artificial intelligence. By processing massive datasets and optimizing intricate algorithms, quantum systems offer new possibilities for machine learning. We highlight different approaches to combining quantum and classical computing, showing how they can work together to produce faster and more accurate results. Additionally, we explore the tools and platforms available—like TensorFlow Quantum, Qiskit, and PennyLane-that are helping researchers and developers bring these theories to life. Of course, quantum computing isn't without its hurdles. Challenges like scaling up hardware, correcting errors, and keeping qubits stable are significant roadblocks. Yet, with rapid advancements in cloud-based platforms and innovative technologies, the potential of quantum computing feels closer than ever. This paper aims to offer readers a clear and comprehensive introduction to quantum computing, its role in machine learning, and the immense possibilities it holds for the future of technology.

1 Introduction

Machine learning has transformed the data analytics industry like never before. With availability of a variety of data in large volumes at high velocity, i.e., 'Big Data', significant insights can be drawn. As the volume of data increases, so does the difficulty in processing it. There is a need for systems that can efficiently process large data sets, using complex algorithms, in real time and with high accuracy. In our fast-paced world, the industry is driven by the urge to speed up processed and make them more efficient and safe. Quantum computing provides a platform to achieve this, with a few caveats! Quantum physics has been around for quite some time. However, Shor's algorithm [49] catapulted the interest in Quantum Computing. Fig. 1 shows the progress of Quantum research from 1982 to 2024.

Quantum computing research has grown in leaps and bounds.Google and IBM are the two front runners in this Quantum race. In just a couple of years IBM has successfully developed a quantum computer capable of running up to 5000 two qubit gate operations. [32] . In December 2024, Google launched their breakthrough 105 Qubit Quantum chip called Willow.[1]. This latest development has tackled a very important challenge in Quantum computing of error reduction and decoherence as we increase the number of Qubits. These advancements have accelerated the growth in Quantum research and development.

Consider the performance of an algorithm as a function of the amount of time spent in solving the problem. As size of the input increases, high

Bhavna Bose: bhavna.bose@nmims.edu



Figure 1: Quantum computing timeline

degree polynomial functions grow much slower than quadratic functions as shown in Fig 2. Quantum systems provide speedups in this area.



Figure 2: Comparison of time complexities based on number of inputs

Classical systems store single information in a single bit i.e. 0 or 1. In contrast, quantum computers store information in qubits shown using the Dirac notation $ket\psi$ written as $|\psi\rangle$. Each single qubit stores information about two states 0 and 1. However, on measurement, the qubit collapses to a single state i.e. 0 or 1. This means that in the intermediate process fewer qubits (N) can be used to process more (2^N) data. All this is possible due to the duality of a quantum particle.

This does not mean that classical computers will become obsolete. It is quite the opposite! The current research (as we will see the next section) is working on a symbiotic interaction between Quantum computers and Classical computers. Also as seen from Fig. 2, quantum computing offers speedups for a particular class of problems. Each processing paradigm has its strength and by harnessing the strength of both systems, solutions of traditionally unsolvable problem can be attempted.

Just as quantum computing offers unique solutions to many unsolvable problems, quantum computing faces its unique challenges. [51], discusses the many challenges faced in the development of quantum computing based systems. These include hardware scalability, decoherence, and limited gate operations to name a few. Even with the tremendous work done in the development of quantum hardware by industry giants like IBM and Google, we are at least half a decade away before practical quantum systems will be available.

1.1 Related Literature

The work done in [10, 36, 48] gives an idea about different applications of machine learning, quantum information processing and the overlap between these two fields. For those seeking an entry point into the topics of Quantum Machine Learning (QML), [23] serves as a valuable resource, while [15] emphasizes algorithmic complexity and theoretical foundations through illustrative examples of QML techniques.

Further exploration into Quantum Neural Networks (QNN) is provided by [14] and [35], which compare key QNN architectures, summarize their characteristics, and offer broader context within this domain. Additionally, [22] demonstrates examples of quantum enhancements to Machine Learning and Artificial Intelligence. Among introductory texts, the monograph by [56] stands out as the most comprehensive resource, presenting significant discoveries in Quantum Machine Learning alongside a thorough introduction to both classical machine learning and quantum computing. Similarly, [47] delves into well-established techniques, offering a detailed overview of the field.

A unique perspective is provided by [54], which explores QML's applications in robotics while also addressing classical QML concepts. Recent works have begun to propose specific application scenarios for QML. For instance, [46] discusses how novel QNN architectures could address numerical challenges in finance, while [58] examines the potential of quantum neural networks to enhance medical image recognition. Physics remains the most prominent area for QML applications, with [13] offering a comprehensive review. Conversely, other cross-disciplinary applications have seen less significant contributions from QML, as noted by [45].

This work aims to an introduction to Quantum Machine Learning (QML). It covers foundational concepts, classical Quantum approaches integrating the existing systems with Quantum mechanisms, a proposed framework for implementing QML and suggesting resources for further exploration. Rather than striving for exhaustive coverage, the goal is to equip readers with sufficient background and guidance for deeper study.

This paper is organized as follows: Section 2 introduces the basic concepts of quantum computing starting from Qubits till problem complexity. Section 3 discusses quantum computation with an introduction to Quantum Circuits and their modeling. Section 4 is briefly discusses the steps involved in machine learning, while Section 5 dives into quantum machine learning discussing the phases/steps to collaboratively use classical and quantum techniques. Section 6 discusses an implementation framework for of Quantum machine learning algorithms. Section 7 gives an overview of some quantum computing platforms available currently. Finally, Section 8 concludes the paper.

2 Introduction to Quantum Computing

In this section we will discuss the building block of Quantum systems, Qubits and the problem types which can be solved using the Quantum approach.

2.1 Qubits

Qubits, are the basic building block of a quantum computing system. Qubits in quantum computers are analogous to bits in classical systems. Qubits are quantum particles and can be implemented using many physical particles like superconducting qubits, trapped ion qubits, quantum dots, photons, neutral atoms to name a few.

The different types of qubits used in quantum computing today are listed below:

- Superconducting qubits: Superconducting materials like aluminum, niobium and tantalum are used to make the qubits. As extremely low temperatures, they enable fast and fine tuned computations.
- Trapped ion qubits: Qubits implemented as trapped ion particles can stay for longer periods without being disrupted by environmental noise and less errors in measurements.
- Quantum dots: they are nanoscale semiconductor particles. The electron in a Quantum

Dot and confined in a very small three dimensional space making their energy levels discrete and measurable.

- Photons: Photons are light particles which exhibit the phenomena of entanglement and superposition. Also, due to their weak interactions with surrounding environments they more immune to noise.
- Neutral atoms: Neutral atoms are atoms with equal number of electrons and protons, making them stabe for quantum communications. Quantum information is encoded in the internal states of these atoms.

Table 1 gives a summary of the different types of qubits and the companies building Quantum Processing Units (QPUs) using that technology.

The spin and amplitude of the qubits carry information. To achieve this, the qubits have to be kept at very low temperatures, just above absolute zero (-459 degrees Fahrenheit), to be able to control their behavior (i.e. spin and amplitude). The main challenge to quantum computing is the difficulty in maintaining such low temperatures. Even with a slight increase in temperature, the quantum particle (qubit) with change its state i.e. loose its value also called decoherence.[34] Classical bits do not loose their information i.e they maintain their state over time. However, qubits loose their state very quicky i.e. loose coherence in less that $300\mu s$![7] The low coherence implies that all computations must be completed before the qubit becomes decoherent. Decoherence forces the developers to create circuits and algorithms which will come to the final result very fast and accurately which aligns to the need of the the consumers too. It is a win-win situation !

2.2 Classical Vs Quantum Complexity

As discussed in the previous section, problems which can be solved efficiently with the classical computers, do not require to migrate to the more computationally expensive quantum systems. Then the question arises , which kind of problems are apt for quantum computations ? To answer the question, computational complexity of the problems needs to be explored. This section will discuss the different computation complexity classes. Computational complexity refers to the time and space required to compute a problem which is normally a function of the number of inputs i.e. input size. Fig. 3 shows the set of decision problems that require a certain amount of time and space.

- Exponential Space Problems (EXPSPACE) : The space required to solve problems in this class is an exponential fuction of the number of inputs.
- Exponential Time Problems (EXPTIME) : The time required to solve problems in this class is an exponential fuction of the number of inputs.
- Polynomial Space Problems (PSPACE) : The space required to solve problems in this class is a polynomial function of the number of inputs.
- Polynomial time problems (P): Problems in this class can be solved in polynomial time as the input size increases.
- Non deterministic Polynomial time Problems (NP): Problems in the category cannot be solved in polynomial time. However, a solution to these problems can be verified in polynomial time.
- NP-complete problems: Problems in this class are the most difficult problems in NP and have no known polynomial solution. This is where famous problems like the traveling salesman and the game Soduku live.
- Bounded-error Polynomial Problems (BPP): which can be solved within some error threshold by a probabilistic classical computer in polynomial time.
- Bounded-error Quantum Polynomial Problems (BQP): This is the quantum equivalent of BPP. It is the class of decision problems solvable by a quantum computer in polynomial time with a small chance of error.

3 Quantum Logic

Quantum computing paradigm has certain core differences which makes it attractive. Due to the concepts of entanglement, superposition and superdense coding, quantum algorithms provide

	IBM built the Eagle quantum computer with 127 qubits. [33]	
Superconducting qubits	Google's Sycamore [2]	
	Rigetti's Aspen-M-2 [19]	
	QuantWare's built Crescendo and Soprano [41]	
	Quantinuum [40]	
Trapped ion qubits	IonQ [29]	
	Alpine Quantum Technologies [55]	
	Oxford Ionics [28]	
	Diraq [21]	
Quantum dots	Quobly [42]	
	Quantum Motion [37]	
	Xanadu [57]	
Photons	ORCA Computing [17]	
	QuantumComputing Inc [26]	
	PsiQuantum [39]	
	Pasqal [38]	
Neutral atoms	Atom Computing [16]	
	QColdQuanta [27]	
	QuEra [18]	

Table 1: Qubit technology and Companies working on building QPUs using that technology.

significant speedups to solve problems considered unsolvable earlier. As opposed to bits, qubits can be evaluated to a 0 or a 1 based on the probability of geting the two values, i.e. a qubit is a linear function of 0 and 1 values. A qubit is represented by the equation Eq. 1

$$\left|\psi\right\rangle = \alpha \left|0\right\rangle + \beta \left|1\right\rangle \tag{1}$$

where $\alpha,\beta\in\mathbb{C}$ are the popabilites of evaluating a qubit to 0 or 1 repectively. Thus $|\alpha|^2+|\beta|^2=1.$ This means that during the intermediate computations, a qubit can be in a combination of $|0\rangle$ or $|1\rangle$. Once measured, the Qubit will evaluate to either a 0 or 1 classical bit value.

In an *n*-qubit system, there are 2^n probability amplitudes, which might suggest an enormous amount of information. The reality is that the measurements we can perform limit how much information we can actually extract. This idea is captured by Holevo's bound, which tells us that *n* qubits can encode, at most, *n* bits of information. [25].

3.1 Quantum Circuits

Classical computations are performed by applying logic gates to the input bits. The logic gates transform the state of the bits based on certain rules.

Analogously, gates are applied to qubits to perform certain computations and give results.

Much like classical logic gates, a quantum logic gate transforms, the input A to A' based on a transformation function applied to it through the logic gate. We usually denote a quantum state as $|\psi\rangle = \alpha |0\rangle + \beta |1\rangle$. When the quantum logic gate is applied to the quantum input state $|\psi\rangle$, it transforms to $|\psi'\rangle = \alpha |0'\rangle + \beta |1'\rangle$. As this is a valid quantum state, the condition $|\alpha'|^2 + |\beta'|^2 = 1$ is satisfied. [56].

Listed in Table. 2. are few quantum gates with their symbols and transformation matrices.

3.2 Quantum Circuit Model

The key components of a quantum circuit as illustrated in Fig. 4 are:

1. Classical Resources: Quantum circuit can be considered to be divided into two parts: Classical part and Quantum part. The true



Figure 3: Complexity Classes

strength of a quantum system is harnessed by leveraging the strengths of both the computation paradigms and integrating both the systems.

2. State Space: Similar to bits in classical systems, quantum computers work on a number of qubits. The qubits occupy a state space , which is a 2^n dimensional Hilbert Space, where n is the number of Qubits.

A computational basis state $|x\rangle$ corresponds to the binary number x where

$$\begin{aligned} |x\rangle &= |x_1, x_2, ..., x_n\rangle \ , \\ x &= x_1 x_2 ..n x_n \ \text{and} \\ x_i &= 0, 1 \end{aligned}$$

3. Prepare the state space: The computational

basis states $|x_1, x_2, ..., x_n\rangle$ are prepared in atmost *n* steps.

- 4. Apply gates and compute: Once the system is in its initial state, Quantum gates are applides to the required Qubits as per the model/ problem solution and computations are preformed.
- 5. Measure the results: After the computations, the results are measured in the computational basis state $|x_i\rangle$. The results are measured classically as x_i corresponding to $|x_i\rangle$

Model is illustrated in Fig.4

Gate Name	Symbol	Matrix Representation	Equation
Hadamard	$ \psi\rangle$ H $ \psi'\rangle$	$\frac{1}{\sqrt{2}} \begin{bmatrix} 1 & 1\\ 1 & -1 \end{bmatrix}$	$\left \psi' ight angle = rac{lpha+eta}{\sqrt{2}}\left 0 ight angle + rac{lpha-eta}{\sqrt{2}}\left 1 ight angle$
Pauli-X	$ \psi\rangle$ X $ \psi'\rangle$	$\begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}$	$\left \psi'\right\rangle = \alpha \left 1\right\rangle + \beta \left 0\right\rangle$
Pauli-Y	$ \psi\rangle$ Y $ \psi'\rangle$	$\begin{bmatrix} 0 & -i \\ i & 0 \end{bmatrix}$	$\left \psi' ight angle=ilpha\left 1 ight angle-ieta\left 0 ight angle$
Pauli-Z	$ \psi\rangle$ Z $ \psi'\rangle$	$\begin{bmatrix} 1 & 0 \\ 0 & -1 \end{bmatrix}$	$\left \psi'\right\rangle = \alpha \left 0\right\rangle - \beta \left 1\right\rangle$

Table 2: Quantum Gates, Symbols, Matrices and Resultant Equation Input Qubit is $\left|\psi\right\rangle=\alpha\left|0\right\rangle+\beta\left|1\right\rangle$



Figure 4: Quantum Circuit Model

4 Machine Learning

Machine learning tries to mimic the human nature of learning from past experiences to react to new stimuli. What this means is, based all the past data collected, a model is developed which then gives a prediction of the outcome. The prediction is probabilistic and rarely 100% accurate. Machine learning involves seven steps[31] as shown in Fig. 5.

5 Quantum Machine Learning(QML)

5.1 Introduction to QML

Machine learning relies heavily on probabilities. This is what makes Quantum systems a good candidate for machine learning application as Quantum Computing also, basically relies on calculating the probability of getting to a particular state. Quantum computers due their strength in handling vast quantities of data and parallel processing [31] by Deutch Algorithm, can aid in machine learning tasks. The power of Quantum computing can be leveraged in Machine learning to give 4 combinations of approaches: The work done in [30] discusses these 4 approaches as shown in Table 3:

The choice of using the classical approach or quantum approach requires some analysis. As mentioned before, quantum computing algorithms give a clear advantage over classical systems for algorithms with very high sample complexity[47]. Quantum approaches due to their probabilistic nature sometimes are more robust to noise than classical algorithms. [12, 20]. Some metrics used in quantum - classical model selection are computational complexity, sample

Approach	Concept	Working	Example
Classical- Classical (CC):	These are regular algorithms that take inspiration from quantum mechanics.	They run on normal computers and work with everyday data, but use ideas from quantum computing to improve performance.	Algorithms de- signed based on quantum concepts, like optimization techniques that mimic quantum behavior but run on classical systems.
Classical- Quantum (CQ):	Here, quantum computing is used to process traditional (classical) data.	Quantum algorithms, or adaptations of existing machine learning algorithms, are applied to classical data in a way that aims to outperform regular computer algorithms.	A quantum ver- sion of a neural network that pro- cesses data like images or text, hoping to solve problems faster than classical computers.
Quantum- Classical (QC):	Classical machine learning is used to make sense of quantum data.	Quantum computers generate complex quantum data, and then classical machine learning algorithms are used to analyze this data to extract useful information.	Using traditional machine learning techniques to pre- dict the behav- ior of quantum systems based on quantum data.
Quantum- Quantum (QQ):	Both the algorithms and the data are purely quantum.	Quantum algorithms work directly with quantum data to find patterns or insights, making full use of quantum states.	A quantum algo- rithm designed to learn from quantum states for tasks like op- timizing quantum systems or recog- nizing quantum patterns.

Table 3:	Different	approaches	to	QML
Tuble 0	Different	approactics		Q.I.I.E



Figure 5: Machine Learning Steps

complexity, robustness to noise, circuit depth (number of layers), accuracy and optimum bias variance tradeoff. [24].

The most common approach for implementing QML is the the CQ setting. The two ways to implement QML is the CQ setting are[47]:

- The translational approach: Some parts of the classical algorithms are translated i.e. run using Quantum approaches. The choice of using classical or quantum approach is which approach will give better performance (accuracy or speed wise).
- The exploratory approach: The algorithms are run entirely on quantum systems and may not have any quantum counterpart.

5.2 Quantum Data Encoding

The work done in [43],[9] discuss the quantum data encoding methods used to prepare the data

to be input to a machine learning algorithm. The three approaches discussed are:

5.2.1 Basis Encoding

In this method the qubits are directly mapped to the bit values i.e. bit 0 and 1 will be represented as $|0\rangle$ and $|1\rangle$ respectively. A classical number 110 can be represented as the quantum state $|110\rangle$:

$$|110\rangle = \alpha |1\rangle \otimes \beta |1\rangle \otimes \gamma |0\rangle, \qquad (2)$$

where α , β , and γ are the information stored in the form of probability amplitudes for each qubit state.

5.2.2 Superposition encoding

As the name suggests, in this encoding scheme, the qubit state is encoded as a superposition of the basis states.

$$|110\rangle = \sqrt{\frac{1}{3}} |100\rangle + \sqrt{\frac{1}{3}} |010\rangle + \sqrt{\frac{1}{3}} |001\rangle , \quad (3)$$

$$|78\rangle = \sqrt{\frac{1}{2}} |1001110\rangle + \sqrt{\frac{1}{2}} |0100111\rangle, \quad (4)$$

5.2.3 Angle encoding

When the Qubits are represented on the bloch sphere, the probabilities of basis states are the phase shift from the X,Y and Z axes. Thus in angle encoding, the classical data is represented as a phase shift. Quantum gates use rotation operations around different axes (X, Y, or Z) for changing the quantum state.

The rotation around the X, Y and Z axis denoted as $R_x(\theta), R_y(\theta)$ and $R_y(\theta)$ respectively and is shown in Equations 5.6 and 7.

$$R_x(\theta) = e^{-i\theta X/2} = \begin{bmatrix} \cos(\theta/2) & -i\sin(\theta/2) \\ -i\sin(\theta/2) & \cos(\theta/2) \end{bmatrix}$$
(5)

$$R_y(\theta) = e^{-i\theta Y/2} = \begin{bmatrix} \cos(\theta/2) & -\sin(\theta/2) \\ \sin(\theta/2) & \cos(\theta/2) \end{bmatrix}$$
(6)

$$R_z(\theta) = e^{-i\theta Z/2} = \begin{bmatrix} e^{-i\theta/2} & 0\\ 0 & e^{i\theta/2} \end{bmatrix}$$
(7)

5.2.4 Amplitude encoding

In this scheme, classical information is encoded in the probability amplitudes of quantum state. If the number of values to be represented is n, then the number of qubits required are $log_2(n)$. The values of probabilities of each qubit state is the square root of the data value divided by the square root of the sum of squares of all the n data values. The quantum state can be represented as:

$$|\psi(X)\rangle = \sum_{i=1}^{n} x_i |i\rangle \tag{8}$$

where x_i is the *i*-th element of the vector X, and $|i\rangle$ denotes the computational basis states of the qubits. For this example, n = 4, and the coefficients x_i correspond to the values [1.2, 2.7, 1.1, 0.5]. Each term is square-normalized by dividing it by the square root of the sum of squares of all elements. For the vector X = [1.2, 2.7, 1.1, 0.5], the normalization factor is:

$$\sqrt{\sum_{i=1}^{n} x_i^2} = \sqrt{1.2^2 + 2.7^2 + 1.1^2 + 0.5^2} = \sqrt{10.19}$$
(9)

The normalized quantum state is:

$$\begin{aligned} |\psi\rangle &= \frac{\sqrt{1.2}}{\sqrt{10.19}} |00\rangle + \frac{\sqrt{2.7}}{\sqrt{10.19}} |01\rangle \\ &+ \frac{\sqrt{1.1}}{\sqrt{10.19}} |10\rangle + \frac{\sqrt{0.5}}{\sqrt{10.19}} |11\rangle. \end{aligned} (10)$$

6 Implementation of QML Algorithms

In their work [44], the authors have suggested the framework to implement Hybrid Quantum Classical algorithms. As discussed previously, Quantum computing can work in tandem with classical system in 4 ways i.e. CC,QC,CQ and QQ. Normally, a hybrid quantum algorithm contains 3 parts: the classical part, quantum part and the interface between the classical and quantum systems as shown in Fig.6 The data encoding, application of Oracle, amplitude adjustment and Optimization steps are repeated multiple times in the range of thousands of iterations to give reliable results.

6.1 Quantum Computation

The quantum part comprises of mapping the algorithm to an actual circuit with quantum gates. The steps involved in this process, shown on the left side of Fig. 6 in red, are:

- 1. Decide the number of qubits required and set them to the basis state of $|0\rangle$.
- 2. Apply the Hadamard Gate to create a uniform superposition of all possible states of the qubits.
- 3. Encode the the resultant states using any of the encoding techniques mentioned in 5.2.
- 4. Apply quantum gates to implement the Quantum Oracle function (U_f) on the encoded qubits.
- 5. The result after applying the Oracle function is stored in all or few of the Qubits.



Figure 6: Framework to implement the Quantum Machine learning.

- 6. The amplitudes of the undesired states are reduced to increase the probability of the getting the desired result.
- 7. The final values are measured. As discussed earlier, on measurement, the state of a Qubits collapses to classical bit value. The binary value will depend on the probability of each state.

6.2 Classical Computation

In the classical component, classical values obtained are optimised using classical techniques. The steps involved, shown on the right hand side of Fig. 6 in cyan, are:

- 1. The final qubit values are measured classically. The binary value obtained on measurement will depend on the quantum probability of each state.
- 2. In this step, the values are iteratively modified based on the problem statement and expected results. This is done to increase the probability of correct results. Error correction and mitigation strategies are applied for better results.

6.3 Interface between Quantum and Classical systems

This phase is shown in Fig. 6 in the violet boxes.

- 1. Data Encoding: The binary bits are encoded using any one of the encoding techniques discussed in Section 5.2.
- 2. Measurement: The Qubits are measured where they take a binary value of 0 or 1.

7 Tools available for Quantum Computing

Quantum computing has opened doors to solving the problems earlier considered unsolvable. This also poses a threat to our existing system security. All this has sparked a keen interest in Quantum research. A number of tools are available to develop and run quantum algorithms. Some of the tools are tabulated in Table 4.

Table 4: Quantum Development Toolkits

SDK /	Language	Hardware	Platform
Library			/ Cloud
			Service
IBM	Python	IBM Quan-	IBM Quan-
\mathbf{Qiskit}	U U	tum hard-	tum Expe-
[5]		ware	rience
Google	Python	Google's	Google
Cira ^[3]	U	quantum	Quantum
		hardware	ĂI
Ms	Ω#	Supports	Azure
ODK	~ 11 ⁻	multiple	Quantum
[52]		hardware	Quantum
[02]		providers	
		through	
		Azure	
Bigotti	PyOuil	Rigetti's	Bigetti
Forest	i yogun	supercon	Quantum
[50]		ducting	Cloud
[00]		quantum	Cloud
		quantum	
T	D+1	Wenles	T Fl
Tensor	Python	works on	Tensorriow
Flow		quantum	ecosystem
Quan-		nardware	
$\operatorname{tum}\left[11\right]$		Cine libraria	
V	D (1		V 1
Xanadu D	Python	Xanadu's	Xanadu
Penny-		pnotonic	Cloud
Lane [8]		processors	T O
D-	Python	D-Wave	Leap Quan-
Wave		quantum	tum Cloud
Ocean		computers	
5DK			
[JJ]	Deethere	<u>C</u>	N _ 4
Open Earresta	Fytnon	Compatible	nlatform
		with Uirq,	platiorm-
[4]		QISKIU,	specific
		and other	
		trameworks	
Amazon	Python	Multiple	Amazon
Braket		QPUs and	Web Ser-
[6]		simulators	vices

8 Conclusion

Quantum computing is more than just a breakthrough in technology—it's a whole new way of thinking about how we solve problems. By harnessing the strange yet powerful properties of quantum mechanics, quantum computers can tackle challenges that classical systems simply can't handle. From optimizing complex systems to analyzing massive datasets, the potential impact on industries like healthcare, finance, and artificial intelligence is staggering. But this isn't a technology we'll see in full force tomorrow. Building practical quantum computers is hard. Qubits, the building blocks of quantum systems, are delicate and prone to errors. Scaling up to larger, more reliable systems will take time and innovation. Even so, companies like IBM and Google have already made impressive strides with powerful quantum processors. Meanwhile, cloud platforms like Amazon Braket and Microsoft Azure Quantum are making quantum computing tools accessible to more people, speeding up the pace of discovery and development.

In machine learning, quantum computing offers unique ways to improve existing algorithms and solve new types of problems. Hybrid systems—where quantum and classical computers work together—are showing how these two worlds can complement each other. Libraries and frameworks, like Qiskit and TensorFlow Quantum, are making it easier for developers and researchers to experiment with quantum ideas in practical ways.

The potential of quantum computing is undeniable despite the numerous challenges. The future of quantum computing will depend not only on solving technical problems but also on collaborations across science, industry, and policymaking. It's a journey, but one filled with incredible promise. If progress continues at its current pace, quantum computing could soon transform the way we live, work, and think about technology.

References

[1] Rajeev Acharya and Abanin. et. al Quantum error correction below the surface code threshold. Nature, 122024.DOI: 10.1038/s41586-024-08449y. URL https://doi.org/10.1038/ s41586-024-08449-y.

- [2] Google Quantum AI. Quantum Computer | Google Quantum AI — quantumai.google. https://quantumai.google/ quantumcomputer, 2024. [Accessed 11-11-2024].
- [3] Google Quantum AI. Cirq Google Quantum AI — quantumai.google. https:// quantumai.google/cirq, 2024. [Accessed 27-12-2024].
- [4] Google Quantum AI. OpenFermion Google Quantum AI — quantumai.google. https: //quantumai.google/openfermion, 2024.
 [Accessed 27-12-2024].
- [5] Gadi Aleksandrowicz, Thomas Alexander, Panagiotis Barkoutsos, Luciano Bello, Yael Ben-Haim, David Bucher, F Jose Cabrera-Hernández, Jorge Carballo-Franquis, Adrian Chen, Chun-Fu Chen, et al. Qiskit: An open-source framework for quantum computing. *Accessed on: Mar*, 16: 61, 2019. URL "https://zenodo.org/ records/2562111".
- [6] Amazon Web Services (AWS). Amazon braket — aws.amazon.com/braket/. https: //aws.amazon.com/braket/, 2024. [Accessed 12-11-2024].
- [7] Mustafa Bal, Akshay A Murthy, Shaojiang Zhu, Francesco Crisa, Xinyuan You, Ziwen Huang, Tanay Roy, Jaeyel Lee, David van Zanten, Roman Pilipenko, Ivan Nekrashevich, Andrei Lunin, Daniel Bafia, Yulia Krasnikova, Cameron J Kopas, Ella O Lachman, Duncan Miller, Josh Y Mutus, Matthew J Reagor, Hilal Cansizoglu, Jayss Marshall, David P Pappas, Kim Vu, Kameshwar Yadavalli, Jin-Su Oh, Lin Zhou, Matthew J Kramer, Florent Lecocq, Dominic P Goronzy, Carlos G Torres-Castanedo, P Graham Pritchard, Vinayak P Dravid, James M Rondinelli, Michael J Bedzyk, Mark C Hersam, John Zasadzinski, Jens Koch, James A Sauls, Alexander Romanenko, and Anna Grassellino. Systematic improvements in transmon qubit coherence enabled by niobium surface encapsulation. Npj Quantum Inf., 10(1), April 2024. DOI: https://doi.org/10.1038/s41534-024-00840-x.
- [8] Ville Bergholm, Josh Izaac, Maria Schuld,

Christian Gogolin, Shahnawaz Ahmed, Vishnu Ajith, M Sohaib Alam, Guillermo Alonso-Linaje, B AkashNarayanan, Ali Asadi, et al. Pennylane: Automatic differentiation of hybrid quantum-classical computations. *arXiv preprint arXiv:1811.04968*, 2018. DOI: 10.48550/arXiv.1811.04968.

- [9] Bhattaraprot Bhabhatsatam and Sucha Smanchat. Hybrid quantum encoding: Combining amplitude and basis encoding for enhanced data storage and processing in quantum computing. In 2023 20th International Joint Conference on Computer Science and Software Engineering (JCSSE), pages 512–516, 2023. DOI: 10.1109/JC-SSE58229.2023.10201947.
- [10] Jacob Biamonte, Peter Wittek, Nicola Pancotti, Patrick Rebentrost, Nathan Wiebe, and Seth Lloyd. Quantum machine learning. *Nature*, 549(7671):195–202, 2017. DOI: https://doi.org/10.1038/nature23474.
- [11] Michael Broughton, Guillaume Verdon, Trevor McCourt, Antonio J. Martinez, Jae Hyeon Yoo, Sergei V. Isakov, Philip Massey, Ramin Halavati, Murphy Yuezhen Niu, Alexander Zlokapa, et al. Tensorflow quantum: A software framework for quantum machine learning. *TBD*, 03 2020.
- [12] Nader H Bshouty and Jeffrey C Jackson. Learning dnf over the uniform distribution using a quantum example oracle. In Proceedings of the eighth annual conference on Computational learning theory, pages 118–127, 1995. DOI: https://doi.org/10.1137/S0097539795293123.
- [13] Giuseppe Carleo, Ignacio Cirac, Kyle Cranmer, Laurent Daudet, Maria Schuld, Naftali Tishby, Leslie Vogt-Maranto, [2 and Lenka Zdeborová. Machine learning and the physical sciences. *Reviews of Modern Physics*, 91(4):045002, 2019. DOI: https://doi.org/10.1103/RevModPhys.91.045002.
- [14] Simantini Chakraborty, Tamal Das, Saurav Sutradhar, Mrinmoy Das, and Suman Deb. An analytical review of quantum neural network models and relevant research. In 2020 5th International Conference on Communication and Electronics Systems (IC-CES), pages 1395–1400. IEEE, 2020. DOI: 10.1109/ICCES48766.2020.9137960.
- [15] Carlo Ciliberto, Mark Herbster, Alessan-

dro Davide Ialongo, Massimiliano Pontil, Andrea Rocchetto, Simone Severini, and Leonard Wossnig. Quantum machine learning: a classical perspective. *Pro*ceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences, 474(2209):20170551, 2018. DOI: https://doi.org/10.1098/rspa.2017.0551.

- [16] Atom Computing. Home Atom Computing - atom-computing.com. https:// atom-computing.com/, 2024. [Accessed 12-11-2024].
- [17] ORCA Computing. Home | ORCA Computing — orcacomputing.com. https:// orcacomputing.com/, 2024. [Accessed 11-11-2024].
- [18] QuEra Computing. Quantum Computing with Neutral Atoms | QuEra — quera.com. https://www.quera.com/, 2024. [Accessed 12-11-2024].
- [19] Rigetti Computing. Rigetti QCS qcs.rigetti.com. https://qcs.rigetti. com/qpus, 2024. [Accessed 11-11-2024].
- [20] Andrew W. Cross, Graeme Smith, and John A. Smolin. Quantum learning robust against noise. *Phys. Rev. A*, 92: 012327, Jul 2015. DOI: 10.1103/Phys-RevA.92.012327. URL https://link.aps. org/doi/10.1103/PhysRevA.92.012327.
- [21] Diraq. Diraq diraq.com. https://diraq. com/, 2024. [Accessed 11-11-2024].
- [22] Vedran Dunjko and Hans J Briegel. Machine learning & artificial intelligence in the quantum domain: a review of recent progress. *Reports on Progress in Physics*, 81(7):074001, 2018. DOI: https://doi.org/10.1088/1361-6633/aab406.
- [23] Vedran Dunjko and Peter Wittek. A non-review of quantum machine learning: trends and explorations. *Quantum Views*, 4:32, 2020. DOI: https://doi.org/10.22331/qv-2020-03-17-32.
- [24] Trevor Hastie, Robert Tibshirani, Jerome Friedman, Trevor Hastie, Robert Tibshirani, and Jerome Friedman. High-dimensional problems: p n. The Elements of Statistical Learning: Data Mining, Inference, and Prediction, pages 649–698, 2009. URL "https: //www.sas.upenn.edu/~fdiebold/ NoHesitations/BookAdvanced.pdf".
- [25] Alexander Semenovich Holevo. Bounds for

the quantity of information transmitted by a quantum communication channel. *Problemy Peredachi Informatsii*, 9(3):3–11, 1973. DOI: https://doi.org/10.22331/q-2023-04-13-978.

- [26] Quantum Computing Inc. Quantum Computing Inc — quantum computinginc.com. https://quantumcomputinginc. com/, 2024. [Accessed 12-11-2024].
- [27] Infleqtion. ColdquantaLabs Infleqtion infleqtion.com. https://www.infleqtion. com/coldquantalabs, 2024. [Accessed 12-11-2024].
- [28] Oxford Ionics. Oxford Ionics | High Performance Quantum Computing — oxionics.com. https://www.oxionics.com/, 2024. [Accessed 11-11-2024].
- [29] IonQ. IonQ | Trapped Ion Quantum Computing — ionq.com. https://ionq.com/, 2024. [Accessed 11-11-2024].
- [30] Abhishek Jadhav, Akhtar Rasool, and Manasi Gyanchandani. Quantum machine learning: Scope for real-world problems. Procedia Computer Science, 218: 2612-2625, 2023. ISSN 1877-0509. DOI: https://doi.org/10.1016/j.procs.2023.01.235. URL https://www.sciencedirect. com/science/article/pii/ S1877050923002351. International Conference on Machine Learning and Data Engineering.
- [31] Gareth James, Daniela Witten, Trevor Hastie, Robert Tibshirani, and Jonathan Taylor. An introduction to statistical learning: With applications in python. Springer Nature, 2023. DOI: https://doi.org/10.1007/978-3-031-38747-0.
- [32] Ryan Mandelbaum Jay Gambetta. IBM Quantum delivers on 2022 100x100 performance challenge | IBM Quantum Computing Blog — ibm.com. https://www.ibm.com/ quantum/blog/qdc-2024, 2024. [Accessed 14-11-2024].
- [33] Jay Gambetta Jerry Chow, Oliver Dial. breaks IBM Quantum the 100-qubit processor barrier IBM Quan-Computing tum Blog ibm.com. https://www.ibm.com/quantum/blog/ 127-qubit-quantum-processor-eagle, 2024. [Accessed 11-11-2024].
- [34] Ian Smalley Josh Schneider. What Is Quantum Computing? | IBM —

ibm.com. https://www.ibm.com/topics/ quantum-computing#:~:text=Quantum% 20computers%20use%20circuits%20with, individual%20units%20of%20quantum% 20information, 2024. [Accessed 11-11-2024].

- [35] Abu Kamruzzaman, Yousef Alhwaiti, Avery Leider, and Charles C Tappert. Quantum deep learning neural networks. In Advances in Information and Communication: Proceedings of the 2019 Future of Information and Communication Conference (FICC), Volume 2, pages 299–311. Springer, 2020. DOI: https://doi.org/10.1007/978-3-030-12385-7_24.
- [36] Nimish Mishra, Manik Kapil, Hemant Rakesh. Amit Anand, Nilima Mishra. Aakash Warke, Soumya Sarkar, Sanchayan Dutta, Sabhyata Gupta, Aditya Prasad Dash, et al. Quantum machine learning: A review and current status. Data Management, Analytics and Innovation: Proceedings of ICD-MAI 2020. Volume 2, pages 101–145, DOI: https://doi.org/10.1007/978-2021.981-15-5619-7 8.
- [37] Quantum Motion. Quantum Motion Homepage — quantummotion.tech. https:// quantummotion.tech/, 2024. [Accessed 11-11-2024].
- [38] Pasqal. Homepage Pasqal pasqal.com. https://www.pasqal.com/, 2024. [Accessed 12-11-2024].
- [39] PsiQuantum. PsiQuantum-Building the World's First Useful Quantum Computer - psiquantum.com. https://www.psiquantum.com/, 2024. [Accessed 12-11-2024].
- [40] Quantinuum. Quantinuum | Accelerating Quantum Computing — quantinuum.com. https://www.quantinuum.com/, 2024. [Accessed 11-11-2024].
- [41] QuantWare. Accelerating the advent of the quantum computer | QuantWare — quantware.com. https://www.quantware.com/, 2024. [Accessed 11-11-2024].
- [42] Quobly. Quobly, shaping a better digital future — quobly.io. https://quobly.io/, 2024. [Accessed 11-11-2024].
- [43] Minati Rath and Hema Date. Quantum data encoding: a comparative anal-

ysis of classical-to-quantum mapping techniques and their impact on machine learning accuracy. *EPJ Quantum Technology*, 11(1), October 2024. ISSN 2196-0763. DOI: 10.1140/epjqt/s40507-024-00285-3. URL http://dx.doi.org/10. 1140/epjqt/s40507-024-00285-3.

- [44] Minati Rath et al. Quantum-assisted simulation: A framework for designing machine learning models in the quantum computing domain. arXiv preprint arXiv:2311.10363, 2023.
- [45] Matthias Rupp, O Anatole Von Lilienfeld, and Kieron Burke. Guest editorial: Special topic on data-enabled theoretical chemistry. The Journal of chemical physics, 148(24), 2018. DOI: https://doi.org/10.1063/1.5043213.
- [46] Takayuki Sakuma. Application of deep quantum neural networks to finance. *arXiv* preprint arXiv:2011.07319, 2020.
- [47] Maria Schuld and Francesco Petruccione. Supervised Learning with Quantum Computers. Springer Publishing Company, Incorporated, 1st edition, 2018. ISBN 3319964232.
- [48] Maria Schuld, Ilya Sinayskiy, and Francesco Petruccione. An introduction to quantum machine learning. Contemporary Physics, 56(2):172–185, 2015. DOI: https://doi.org/10.1080/00107514.2014.964942.
- [49] Peter W Shor. Algorithms for quantum computation: discrete logarithms and factoring. In Proceedings 35th annual symposium on foundations of computer science, pages 124–134. IEEE, 1994. DOI: https://doi.org/10.1109/SFCS.1994.365700.
- [50] Robert S Smith, Michael J Curtis, and William J Zeng. A practical quantum instruction set architecture. arXiv preprint arXiv:1608.03355, 2016. DOI: 10.48550/arXiv.1608.03355.
- [51] Sandeep Kumar Sood and Pooja. Quantum computing review: A decade of research. *IEEE Transactions on Engineer*ing Management, 71:6662–6676, 2024. DOI: 10.1109/TEM.2023.3284689.
- [52] Krysta Svore, Alan Geller, Matthias Troyer, John Azariah, Christopher Granade, Bettina Heim, Vadym Kliuchnikov, Mariia Mykhailova, Andres Paz, and Martin Roetteler. Q# enabling scalable quan-

tum computing and development with a high-level dsl. In *Proceedings of the real world domain specific languages work-shop 2018*, pages 1–10, 2018. DOI: https://doi.org/10.1145/3183895.3183901.

- [53] D-Wave Systems. D-Wave Ocean Software Documentation; Ocean Documentation 8.1.0 documentation — docs.ocean.dwavesys.com. https://docs.ocean.dwavesys.com/en/ stable/, 2024. [Accessed 27-12-2024].
- [54] Prateek Tandon, Stanley Lam, Ben Shih, Tanay Mehta, Alex Mitev, and Quantum robotics: Zhiyang Ong. A primer on current science and future perspectives. Springer, 2017. DOI: https://doi.org/10.2200/S00746ED1V01Y201612QMC02
- [55] Alpine Quantum Technologies. Home AQT
 Alpine Quantum Technologies aqt.eu. https://www.aqt.eu/, 2024. [Accessed 11-11-2024].
- [56] Peter Wittek. Quantum machine learning: what quantum computing means to data mining. Academic Press, 2014. ISBN 9780128009536.
- [57] Xanadu. Xanadu | Welcome to Xanadu xanadu.ai. https://www.xanadu.ai/, 2024. [Accessed 11-11-2024].
- [58] Dong Yumin, Mingqiu Wu, and Jinlei Zhang. Recognition of pneumonia image based on improved quantum neural network. *IEEE Access*, 8:224500–224512, 2020. DOI: https://doi.org/10.1109/ACCESS.2020.3044 697.