Identifying Bug Inducing Commits by Combining Fault Localisation and Code Change Histories

Gabin An, Jinsu Choi, Jingun Hong, Naryeong Kim, Shin Yoo

Abstract-A Bug Inducing Commit (BIC) is a code change that introduces a bug into the codebase. Although the abnormal or unexpected behavior caused by the bug may not manifest immediately, it will eventually lead to program failures further down the line. When such a program failure is observed, identifying the relevant BIC can aid in the bug resolution process, because knowing the original intent and context behind the code change, as well as having a link to the author of that change, can facilitate bug triaging and debugging. However, existing BIC identification techniques have limitations. Bisection can be computationally expensive because it requires executing failing tests against previous versions of the codebase. Other techniques rely on the availability of specific post hoc artifacts, such as bug reports or bug fixes. In this paper, we propose a technique called FONTE that aims to identify the BIC with a core concept that a commit is more likely to be a BIC if it has more recently modified code elements that are highly suspicious of containing the bug. To realise this idea, FONTE leverages two fundamental relationships in software: the failure-to-code relationship, which can be quantified through fault localisation techniques, and the code-to-commit relationship, which can be obtained from version control systems. Our empirical evaluation using 206 real-world BICs from open-source Java projects shows that FONTE significantly outperforms state-of-the-art BIC identification techniques, achieving up to 45.8% higher MRR. We also report that the ranking scores produced by FONTE can be used to perform weighted bisection. Finally, we apply FONTE to a large-scale industry project with over 10M lines of code, and show that it can rank the actual BIC within the top five commits for 87% of the studied real batch-testing failures, and save the BIC inspection cost by 32% on average.

Index Terms—Bug Inducing Commit, Commit Level Fault Localisation, Fault Localisation, Code Change History, Bisection, Batch Testing

I. INTRODUCTION

I N modern software development workflows based on Continuous Integration/Continuous Deployment (CI/CD), numerous developers simultaneously participate in the development of a single project, and multiple code changes (or commits) are continuously integrated into a shared repository. In such an environment, when an abnormal program behavior (i.e., program failure) is observed during the testing process or when a field failure occurs after release, the QA or development teams analyse and categorise the issue, assign it to the most suitable developer, who then performs debugging activities (this process is referred to as the bug resolution process). During the software development process,

the commits that contain buggy source code, which eventually leads to program failures, are known as Bug Inducing Commits (BICs) [1]. For a particular program failure, knowing which commit in the change history is more likely to be a BIC can provide significant advantages in effectively performing the bug resolution process. Firstly, it can streamline the bug assignment phase by enabling the effective assignment of a newly discovered bug to the right team or developers. This is facilitated by the connection between commits and their respective authors, coupled with the fact that 78% of bugs are ultimately fixed by the developers who originally introduced them [2]. Secondly, it can assist in both automated and manual debugging activities. Prior work has shown that simply reverting BICs may suffice for bug fixes [3], [4], and BIC information can be utilized to improve the accuracy of Fault Localisation (FL) techniques [5]. Furthermore, the knowledge of BICs has been demonstrated to aid developers in manual debugging efforts [5], [6]. Finally, it can reduce testing costs, especially in batch testing failure scenarios where tests are executed against a cumulative batch of changes to reduce overall testing costs, but some tests fail [7]. In such cases, knowing the relative suspiciousness of commits in the batch can expedite the identification of the specific commit that caused the failure, potentially reducing the number of test executions required compared to the standard bisection (we show this through our experiment in the later of this paper).

1

Recognising the usefulness of identifying BICs for a given failure, multiple BIC identification techniques have been proposed, which can be broadly categorised into two distinct groups. The first group employs a conventional approach known as bisection [8], which conducts a binary search over the commit history, systematically evaluating each past program snapshot to identify whether it manifests the buggy behavior or not. The evaluation process can be performed either manually or through an automated execution of the test cases that reveal the bug. However, even with automation, the bisection process can incur significant computational overhead if building and testing a specific program version is resourceintensive [5]. The second group consists of Information Retrieval (IR)-based BIC identification techniques [2], [9], also known as changeset/commit-level fault localisation. These approaches reformulate BIC identification as an IR problem. While various information about the failure in a textual format, such as a bug report, is treated as a query, the commits are considered as documents. The approaches then identify the BIC by directly assessing the lexical or semantic similarity between the bug report and the commits. Although IR-based approaches do not incur the computational costs associated

Gabin An, Jinsu Choi, Naryeong Kim, and Shin Yoo are with the School of Computing, KAIST, Daehak-ro 291, Daejeon, South Korea.

E-mail: {gabin.an, jinsuchoi, kimnal1234, shin.yoo}@kaist.ac.kr. Jingun Hong is with SAP Labs Korea, Seoul, South Korea.

E-mail: jingun.hong@sap.com.



Fig. 1. A comparison of BIC identification methods, highlighting the distinctions between FONTE, Bisection and IR-based Techniques, and their relationships with failure information, code elements, and commits.

with their dynamic counterparts (e.g., building and testing), they have limitations. These techniques can only leverage textual information, making it challenging to capture complex failure behaviors. Additionally, their effectiveness heavily relies on the quality and completeness of the bug reports. Other than these two groups, there is a family of BIC identification techniques represented by the SZZ algorithm [1] and its variants, but they are not applicable during the debugging time as they require a Bug Fixing Commit (BFC) as input.

In this paper, we introduce FONTE¹, a novel unsupervised approach for identifying BICs that is efficient, flexible, and available during the debugging phase. As shown in Figure 1, unlike bisection and the IR-based BIC identification methods that attempt to directly assess the relevance between the commit and the failure (or bug report), FONTE first quantifies the relevance of code elements to the failure, computed by a FL technique [10], and maps these code-level scores to the commit level using the change history of the code elements. This process extends existing FL techniques beyond their traditional spatial domain (i.e., the location within the code) to a temporal one (i.e., the commit in the history of the codebase). Compared to the bisection approach, FONTE requires examining only the present buggy code version where the bug manifests, making it more efficient. Additionally, FONTE has the ability to incorporate a wide array of failure-specific information, from test coverage to bug reports, since it is compatible with any FL technique that yields quantitative suspiciousness scores, such as Spectrum-based Fault Localisation (SBFL) or Information-Retrieval-based Fault Localisation (IRFL). Consequently, we expect that FONTE can naturally benefit from future advancements in FL techniques, as its design allows for seamless integration of novel FL approaches.

We evaluate FONTE using a benchmark of 206 real-world Java bugs from Defects4J [11] and their ground-truth BICs, comprising 67 from an existing BIC dataset [6], and 139 that are manually curated by us. The results demonstrate that the ranking performance of FONTE, when combined with the Ochiai SBFL technique, significantly outperforms state-of-the-art IR-based BIC identification techniques, achieving up to 45.8% higher Mean Reciprocal Rank (MRR). Furthermore, we propose a weighted bisection algorithm that leverages the commit scores produced by FONTE during the search process. Our findings show that weighted bisection can reduce the number of search iterations for 98% of the cases compared to the standard bisection, respectively. Finally, we also apply

FONTE to the historical CI data of SAP HANA, showcasing its practical applicability in an industry setting.

This paper presents an extended version of our previously published work [12]. The main extensions and contributions over the original work are summarised as follows:

- Evaluating Various Code History Tracking Tools: While FONTE is compatible with any method-level code history tracking tool, our previous work only used the git log command to obtain the code-commit relationship. This extended study makes use of the recently proposed code change tracking tools, CodeShovel [13] and CodeTracker [14], in addition to git log and reports their effectiveness regarding the search space reduction and recall, and also the efficiency of collecting code history.
- Evaluating Diverse Failure-Code Relationships: The previous work uses only SBFL to measure the failure-code relationships in the experiment. This extended study incorporates not only SBFL but also IRFL to establish the relationships between a failure and code elements when applying FONTE, and compare FONTE's performance based on the underlying FL technique. Furthermore, the inclusion of IRFL enables a fairer comparison between our methodology and other IR-based approaches for BIC identification.
- More Realistic Assessment of FL Accuracy's Effect on FONTE's Performance: Previously, to study the impact of FL accuracy on FONTE's effectiveness, SBFL's performance was artificially weakened by removing some tests from the test suite. In this extended work, since we incorporate both IRFL and SBFL with FONTE, we directly evaluate FONTE's performance in relation to the inherent accuracy of the underlying FL techniques. This approach provides a more authentic assessment without the need for artificial manipulations.
- Richer Evaluation Dataset: We have expanded the BIC dataset from the initial 130 bugs in our previous paper [12] to 206 bugs for a more comprehensive and diverse evaluation. This extended dataset contains bugs from all 16 Java projects that use Git as their version control system in the Defects4J 2.0 benchmark [11], whilst the previous dataset contained bugs from 11 projects. The reproducing package of FONTE with the new dataset is publicly available at our GitHub repository².

The remainder of the paper is structured as follows. Section II explains the research context of this paper and defines the basic notations. Section III and IV propose FONTE and the novel weighted bisection method, respectively. Section V describes the empirical settings for FONTE along with the research questions, and Section VI presents the results. Section VII shows the application results of FONTE to the batch testing scenario in industry software. Section VIII addresses the threats to validity, and Section IX covers the related work of FONTE. Finally, Section X concludes.

II. BACKGROUND

This section provides the background of this paper.

A. Research Context

The debugging process is typically initiated by observing a failure that reveals the presence of a bug in the software. Prior research indicates that a single failing test case is often the most commonly available information when debugging begins [15]. Even when users report a field failure, the debugging activities typically commence with reproducing the failure [16]–[18]. This is because failure-triggering test cases are essential for confirming whether the bug has been successfully fixed or not. Once a program failure is observed and reproduced, identifying the BIC responsible for the failure can contribute to a more efficient bug triage process [19] and aid developers in better understanding the context of the buggy behaviour [2].

While some BIC identification techniques [9], [19] rely on information derived from failures, such as stack traces or exception messages (in a textual format), these sources may only be indirectly linked to the contents of actual BICs. Since commits are directly coupled to specific locations in the source code, our approach focuses on leveraging the actual coverage of the failing tests as the primary source of information. Our previous work [20] has shown that the coverage of failing test executions, referred to as *failure coverage*, can effectively reduce the search space for BICs. By simply filtering out any commit that is not related to the evolution of code elements covered by the failing tests, the search spaces for 703 bugs in the Defects4J v2.0 benchmark [11] were reduced to an average of 12.4% of their original size. This significant reduction rate suggests that failure coverage has the potential to provide a solid foundation for a BIC identification technique available during the debugging phase.

The objective of this work is to accurately identify the BIC using solely the information available at the onset of debugging, immediately following the observation and reproduction of a test failure. Building upon our previous technique for reducing the BIC search space [20], we introduce an approach that can precisely quantify the relevance of each commit within the reduced search space to the observed failure. Rather than directly measuring the relevance of commits to a failure, our method leverages two fundamental types of relationships, namely the failure-code relationship and the code-commit relationship, and combines these relationships to derive the failure-commit relationships.

B. Basic Notations

Let us define the following properties of a program P:

- A set of commits $C = \{c_1, c_2, \ldots\}$ made to P
- A set of code elements $E = \{e_1, e_2, \ldots\}$ of P, such as statements or methods
- A set of test cases *T* = {*t*₁, *t*₂, ...} where *T_F* ⊆ *T* is a set of failing test cases

We assume that there is at least one failing test case, i.e., $|T_F| > 0$, and the bug responsible for the failure resides in



Fig. 2. The three-stage process of FONTE from the reduction of the BIC search space to the final commit scoring stage.

the source code, i.e., some elements in E cause the failure of T_F . We also define the following relations on sets C, T, and E:

- A relation Cover ⊆ T × E defines the relation between test cases and code elements in the program P. For every t ∈ T and e ∈ E, (t, e) ∈ Cover if and only if the test t covers e during the execution.
- A relation Evolve ⊆ C × E defines the relation between past commits and code elements in the program P. For every c ∈ C and e ∈ E, (c, e) ∈ Evolve if and only if the commit c is in the change history of the code element e.

As our ultimate goal is to find the BIC in C, we aim to design a scoring function $s: C \to \mathbb{R}$ that gives higher scores to commits that have a higher probability of being the BIC.

III. FONTE: AUTOMATED BIC IDENTIFICATION VIA DYNAMIC, SYNTACTIC, AND HISTORICAL ANALYSIS

This paper presents FONTE, a technique to automatically identify the BIC, based on the assumption that *a commit is more likely to be a bug inducing commit if it introduced or modified a code element that is more relevant to the observed failure.* The key idea behind FONTE is that the relevancy of the code elements to the observed failures can be quantified using existing FL techniques [10], such as SBFL or IRFL, while the association of commits with code elements can be obtained by employing change history tracking tools, such as git log, CodeShovel [13], or CodeTracker [14]. Figure 2 illustrates the three stages of FONTE, which are described below:

- 1) FONTE identifies all potentially buggy code elements using the coverage of failing test cases and discards the commits that are irrelevant to those code elements [20].
- FONTE additionally filters out the semantic-preserving commits that contain only style changes to the suspicious files using AST-level comparisons.
- FONTE computes suspiciousness scores of the remaining commits to rank the commits in terms of potential responsibility for the failure.

The rest of this section describes each stage in more detail.

A. Stage 1: Filtering Out Failure-Irrelevant Commits

Using the notations defined in Section II-B, we can represent the failure-coverage-based BIC search space reduction [20] as follows. First, let $E_F \subseteq E$ denote the set of all code elements that are covered by the failing test cases:

```
100 -74,7 +74,7 00 import org.apache.commons.lang.
      exception.NestableRuntimeException;
2
    * @author Phil Steitz
    * @author Pete Gieser
    * @since 2.0
   * @version $Id: StringEscapeUtils.java,v 1.26
5
       2003/09/07 14:32:34 psteitz Exp $
   * @version $Id: StringEscapeUtils.java,v 1.27
6 +
       2003/09/13 03:23:24 psteitz Exp $
    */
7
8
  public class StringEscapeUtils {
10 @@ -242,7 +242,9 @@ public class StringEscapeUtils {
11
        } else {
            switch (ch)
12
                case '\'':
13
                    if (escapeSingleQuote) out.write('\\');
14 -
15 +
                     if (escapeSingleQuote) {
                        out.write('\\');
16 +
17 +
                     out.write('\'');
18
19
                    break;
                case '"':
20
```

Fig. 3. Changes by the commit 5814f50 in Defects4J Lang-46

$$E_F = \bigcup_{t \in T_F} \{ e \in E | (t, e) \in \mathsf{Cover} \}$$
(1)

Subsequently, we obtain $C_F \subseteq C$, a set of commits that are involved in the evolution of at least one code element in E_F :

$$C_F = \bigcup_{e \in E_F} \{ c \in C | (c, e) \in \mathsf{Evolve} \}$$
(2)

Then, all commits not contained in C_F can be discarded from our BIC search space because the changes introduced by those commits are not related to any code element executed by failing executions. Consequently, the BIC search space is reduced from C to C_F .

B. Stage 2: Filtering Out Semantic-Preserving Commits

The reduced set of candidate BICs, C_F , may still contain *semantic-preserving commits*, i.e., commits that do not introduce any semantic change to the suspicious code elements. These commits can be further excluded from the BIC search space, as they cannot have altered the functional behaviour of the program so thus cannot introduce a bug [21]. An example of such a commit is shown in Figure 3, which modifies the comments and encloses the single statement in the *if* block.

We use the file-level AST level comparison [22] to identify whether a given commit $c \in C_F$ is a semantic-preserving commit or not. First, we identify the set of failure-relevant source files, S, that are modified by the commit c and covered by the failing test cases. Formally, any file in S contains at least one code element in:

$$E_{F,c} = \{ e \in E_F | (c, e) \in \mathsf{Evolve} \}$$
(3)

Subsequently, for each file $s \in S$, we compare the ASTs derived from s before and after the commit c.³ If the ASTs

 TABLE I

 Example of the voting power of code elements

Code Element		e_1	e_2	e_3	e_4	e_5
Score		1.0	0.6	0.6	0.6	0.3
$rank_{max}$ $rank_{dense}$		1 1	4 2	4 2	4 2	5 3
vote	$ \begin{array}{l} \alpha=0,\tau=\max\\ \alpha=1,\tau=\max\\ \alpha=0,\tau=\mathrm{dense}\\ \alpha=1,\tau=\mathrm{dense} \end{array} $	1.00 1.00 1.00 1.00	0.25 0.15 0.50 0.30	0.25 0.15 0.50 0.30	0.25 0.15 0.50 0.30	0.20 0.06 0.33 0.10

are identical for all files in S, we consider the commit c as a semantic-preserving commit. Note that this approach does not guarantee 100% recall, as it is possible for two source files to yield different ASTs while sharing the same semantic. However, it can safely prune the search space due to its soundness, i.e., if it identifies a commit as semantic-preserving, it is guaranteed to be semantic-preserving. Consequently, the search space for BIC can be further reduced to $C_{BIC} = C_F \setminus C_{SP}$, in which C_{SP} denotes all identified semantic-preserving commits in C_F .

It is worth noting that during this phase, there is also the option to consider discarding the refactoring changes [23] as well, in the same manner as RA-SZZ [24]. However, existing tools for detecting refactoring code, such as RefDiff [25], do not guarantee 100% precision, which introduces the risk of mistakenly excluding semantic-changing commits. Therefore, to guarantee the completeness of the narrowed-down BIC search space, FONTE only employs reliable AST-level comparisons.

C. Stage 3: Scoring Commits using FL Scores and Code Change History

After reducing the search space, the remaining task is to evaluate how likely it is that each commit within C_{BIC} is responsible for the observed failure. As mentioned earlier, our basic intuition is that if a commit had created, or modified, more suspicious code elements for the observed failures, it is more likely to be a BIC.

The suspiciousness of code elements can be quantified via an FL technique. For example, we can apply SBFL [10] using the coverage of the test suite T: note that SBFL uses only test coverage and result information, both of which are available at the time of observing a test failure. Assuming that we are given the suspiciousness scores, let $susp: E_F \to \mathbb{R}^{\geq 0}$ be the mapping function from each suspicious code element in E_F to its non-negative FL score.⁴ To convert the code-level scores to the commit level, we propose a voting-based commit scoring model where the FL score of a code element is distributed to its relevant commits. The model has two main components: rank-based voting power and depth-based decay.

Rank-based Voting Power: Recent work [26]–[28] showed that, when aggregating FL scores from finer granularity elements (e.g., statements) to a coarser level (e.g., methods), it

³The AST comparison information per file for each commit can be computed and stored promptly upon its creation, and if consistently updated in CI environments, there is no additional cost associated with computing it when applying FONTE.

⁴The constraint of FL-score being non-negative is adopted for the sake of simplicity. Note that any FL results can be easily transformed so that the lowest score is 0.

is better to use the *relative rankings* from the original level only, rather than directly using the raw scores. The actual aggregation takes the form of voting: the higher the ranking of a code element is in the original level, the more votes it is assigned with for the target level. Subsequently, each code element casts its votes to the related elements in the target level. We adopt this voting-based method to aggregate the statement-level FL scores to commits. The *voting power* of each code element e based on their FL rankings (and scores) as follows:

$$vote(e) = \frac{\alpha * susp(e) + (1 - \alpha) * 1}{rank_{\tau}(e)}$$
(4)

where $\alpha \in \{0, 1\}$ is a hyperparameter that decides whether to use the suspiciousness value ($\alpha = 1$) as a numerator or not ($\alpha = 0$), and τ a hyperparameter that defines the tiebreaking scheme. We vary $\tau \in \{\max, dense\}$: the max tiebreaking scheme gives the lowest (worst) rank in the tied group to all tied elements, while dense gives the highest but does not skip any ranks after ties. By design, $\tau = \max$ will penalise tied elements more severely than $\tau = \text{dense}$. The example in Table I shows how the hyperparameters affect voting. Note that the relative order between FL scores is preserved in the voting power regardless of hyperparameters, i.e., vote(e) > vote(e')if and only if susp(e) > susp(e').

Depth-based Decay: Wen et al. [2] showed that using the information about commit time can boost the accuracy of the BIC identification. Similarly, Wu et al. [3] observed that the commit time of crash-inducing changes is closer to the reporting time of the crashes. Based on those findings, we hypothesise that *older commits are less likely to be responsible for the currently observed failure*, because if an older commit was a BIC, it is more likely that the resulting bug has already been found and fixed. To capture this intuition, our approach diminishes the voting impact of a program element for older commits that have greater historical depths. The historical depth of a commit *c*, with respect to a code element $e \in E_{F,c}$ (Equation (3)), is defined as follows:

$$depth(e,c) = |\{c' \in C_{BIC}| \\ (c',e) \in \mathsf{Evolve} \land c'.time > c.time\}|$$
(5)

which is essentially a count of the commits in the set C_{BIC} that are relevant to a particular code element e and are more recent than the commit c.

Bringing it all together, we use the following model to assign a score to each commit c in C_{BIC} :

$$commitScore(c) = \sum_{e \in E_F^c} vote(e) * (1 - \lambda)^{depth(e,c)}$$
(6)

where $\lambda \in [0,1)$ is the decay factor: when $\lambda = 0$, there is no penalty for older commits. Figure 4 shows the example of calculating the score of commits when $\lambda = 0.1$.

Finally, based on *commitScore*, the commit scoring function $s: C \to \mathbb{R}^{\geq 0}$ of FONTE is defined as follows:

$$s(c) = \begin{cases} commitScore(c) & \text{if } c \in C_{BIC} \\ 0 & \text{otherwise} \end{cases}$$



Fig. 4. Example of computing the commit scores when $\lambda = 0.1$



Fig. 5. Example of applying the weighted bisection to Math-87

IV. WEIGHTED BISECTION

Bisection is a traditional way of finding the BIC by repeatedly narrowing down the search space in half using binary search: it is also equipped in popular Version Control Systems (VSCs), e.g., git bisect or svn-bisect. A standard bisection is performed as follows: given the last *good* and earliest *bad* versions of a program, it iteratively checks whether the midpoint of those two versions, referred to as a *pivot*, contains the bug. If there is a bug, the earliest bad point is updated to the pivot, otherwise, the last good point is updated to the pivot. If there is a bug-revealing test case that can automatically check the existence of a bug, this search process can be fully automated.

However, as pointed out in previous work [19], even though the bug existence check can be automated, each bisect iteration may still require a significant amount of time and computing resources, especially when the program is large and complex, or the bug-revealing test takes a long time to execute. Since a lengthy bisection process can block the entire debugging pipeline, we aim to explore whether the bisection can be accelerated using the commit score information.

We propose a *weighted* bisection algorithm, where the search pivot is set to a commit that will halve *the amount of remaining commit scores* instead of *the number of remaining commits*, in order to to check the point of greatest ambiguity where the chances of finding the BIC in two directions (before and after the commit) are almost equal. For example, let

Algorithm 1: Weighted Bisection Algorithm

Input: Array of commits C **Input:** Commit score (weight) function $s: C \to \mathbb{R}^{\geq 0}$ **Output:** Bug inducing commit $c \in C$ **Precondition:** C[i] is newer than C[j] if and only if i < j**Postcondition:** bad + 1 = good1 $C' \leftarrow$ empty list; 2 for $c \in C$ do if s(c) > 0 then 3 // Extract Subarray with Positive Scores Append c to C'; 4 5 bad, good $\leftarrow 0, |C'|$ 6 while bad + 1 < good do $\texttt{pivot} \gets$ 7 $\underset{p=\text{bad}+1}{\operatorname{argmin}_{p=\text{bad}+1}^{\operatorname{good}-1} |\sum_{i=\text{bad}}^{p-1} s(C'[i]) - \sum_{i=p}^{\operatorname{good}-1} s(C'[i])| }$ if The target bug is detected in C'[pivot] then 8 $\texttt{bad} \leftarrow \texttt{pivot}$ else 10 $\texttt{good} \gets \texttt{pivot}$ 11 12 return C'[bad]

us consider the example in Figure 5 that shows the score distribution of the commits in the reduced BIC search space of Math-87 in Defects4J. For Math-87, the score distribution is biased towards a small number of recent commits including the real BIC (marked in red) with the third-highest score. In this case, simply using the midpoint as a search pivot might not be a good choice because all highly suspicious commits still remain together on one side of the split search space: as a result, the standard bisection requires five iterations to finish. Alternatively, if we pivot at the commit that halves the amount of remaining scores, the bisection reaches the actual BIC more quickly, completing the search in three iterations.

Algorithm 1 presents the weighted bisection algorithm. It takes as input a chronologically sorted array of commits C and a commit score function $s \in C \to \mathbb{R}^{\geq 0}$, which assigns non-negative scores to each commit, and returns the BIC. First, it extracts a subarray C' from C, containing only the commits with positive scores (Lines 1-4). Assuming that at least one BIC exists in the sorted sequence C', the earliest bad index bad is initialized to 0, representing the index of the most recent commit (Line 5). Since all commits in C'are BIC candidates, the last good index good is set to the (virtual) index immediately after the oldest commit (Line 5). The algorithm then iteratively selects a new pivot index from the range [bad + 1, good - 1], until there are no remaining commits between bad and good (Line 6). The pivot selection is performed such that it minimizes the difference between the sum of scores on the left side (not including pivot) and the sum of scores on the right side (including pivot) (Line 7). Once a new pivot is selected, the commit C'[pivot] is inspected for the bug, either by executing the bug-revealing tests or through manual inspection (Line 8). If the bug is detected (i.e., the pivot is a bad commit), the bad index is updated to pivot (Line 9); otherwise (i.e., the pivot is a good commit), the good index is updated to pivot (Line 11). Finally, when the loop terminates, the algorithm returns

the identified BIC at the bad index (Line 12).

It is worth noting that this algorithm is a *generalised* version of the standard bisection: the standard bisection method can be considered a special case of the weighted bisection algorithm where s is a non-zero constant function, assigning the same non-zero value to all commits, e.g., $\forall c \in C : s(c) = 1.0$.

V. EVALUATION SETUP

This section describes the dataset used for evaluation (Section V-A), the details of FONTE's implementation (Section V-B), and our research questions along with their experimental protocols (Section V-C).

A. Dataset of Bug Inducing Commits

We choose Defects4J v2.0.0 [11], a collection of 835 realworld bugs in Java open-source programs, as the source of our experimental subjects. While Defects4J provides test suites containing the bug-revealing tests for every bug, as well as the entire commit history for each buggy version, it lacks the BIC information for each bug.

We, therefore, start with a readily-available BIC dataset for 91 Defects4J bugs⁵ constructed by Wen et al. [6]. This dataset was created by running the bug-revealing test cases on the past versions and finding the earliest buggy version that makes the tests fail. However, in our experiment, we are forced to exclude 24 out of 91 data points. Since FONTE is implemented using Git, it cannot trace the commit history of nine bugs from the JFreeChart project which uses SVN as its version control system. Further, we exclude 14 data points that are shown to be inaccurate by previous work [20]. Lastly, Time-23 is also discarded, because we found that the identified commit in the dataset does not contain any change to code, but only to the license comments. The detailed reasons can be found in our repository. In summary, we make use of 67 ground-truth BICs from this dataset.

The original dataset of 67 ground-truth BICs identified by Wen et al. [6] encompasses bugs from only four out of the 17 projects in Defects4J. To expand the evaluation dataset, we have manually compiled an additional set of groundtruth BICs. Two authors independently pinpointed the BIC for each bug by examining bug reports, symptoms of failures, and patches provided by developers. To minimize the effort required for manual inspection, our initial focus was on all Defects4J bugs where the narrowed down BIC search space, C_{BIC} , comprised ten or fewer potential BICs. This process led to a consensus on 70 instances, which were then included in the dataset. Furthermore, we identified ground-truth BICs for more bugs, mainly from software projects that initially had minimal or no BIC data. An additional 76 data points, on which the authors agreed, were also incorporated. In summary, a total of 206 data points (67 from Wen et al. + 146 manually curated - 7 overlapped) are used for the evaluation of FONTE. Table II shows the number of ground-truth BICs for each software project, before and after the manual curation of the additional dataset compared to the initial dataset from Wen et

⁵https://github.com/justinwm/InduceBenchmark

TABLE II

DISTRIBUTION OF GROUND-TRUTH BICS ACROSS SOFTWARE PROJECTS: A COMPARISON BETWEEN THE INITIAL DATASET TAKEN FROM WEN ET AL. [6] AND THE AUGMENTED DATASET AFTER MANUAL DATA CURATION.

Project	# BICs		
	Wen et al. [6]	Augmented	
Cli	0	15	
Closure	35	36	
Codec	0	3	
Collections	0	2	
Compress	0	5	
Csv	0	13	
Gson	0	4	
JacksonCore	0	5	
JacksonDatabind	0	6	
JacksonXml	0	2	
Jsoup	0	35	
JxPath	0	4	
Lang	6	29	
Math	21	40	
Mockito	0	1	
Time	5	6	
Total	67	206	

 TABLE III

 EXAMPLE OF RELEVANT TEST SELECTION (Time-15)

Failing Test (T_F)
org.joda.time.field.TestFieldUtils::testSafeMultiplyLongInt
Classes Covered by the Failing Test
org.joda.time.field.FieldUtils org.joda.time.IllegalFieldValueException
Relevant Tests $(T \setminus T_F)$
org.joda.time.Test IllegalFieldValueException ::testGJCutover org.joda.time.Test IllegalFieldValueException ::testJulianYearZero org.joda.time.Test IllegalFieldValueException ::testOtherConstructors org.joda.time.Test IllegalFieldValueException ::testReadablePartialValidate org.joda.time.Test IllegalFieldValueException ::testSetText org.joda.time.Test IllegalFieldValueException ::testStipDateTimeField org.joda.time.Test IllegalFieldValueException ::testSvipDateTimeField org.joda.time.Test IllegalFieldValueException ::testVerifyValueBounds org.joda.time.field.Test FieldUtils ::testSafeAddInt org.joda.time.field.Test FieldUtils ::testSafeAddLong org.joda.time.field.Test FieldUtils ::testSafeMultiplyLongLong org.joda.time.field.Test FieldUtils ::testSafeSubtractLong

al. [6]. The combined BIC dataset and the provenance of each data point are available in our repository for further scrutiny.

B. Implementation Details of FONTE

1) Basic Properties: We apply FONTE at the statementlevel granularity. Following the notations in Section II-B, Eis a set of statements composing the target buggy program. The initial BIC search space, C, is set to all commits from the very first commit up to the commit corresponds to the buggy version⁶. From the developer-written test cases, we only use the bug-revealing (i.e., failing) test cases as well as their relevant test cases as T. A test case is considered relevant if and only if its full name contains the name of at least one class executed by the failing test cases. Table III shows the example of the relevant test selection.

⁶revision.id.buggy in Defects4J

2) Construction of the Cover relation: To construct the Cover relation between T and E, we measure the statementlevel coverage of each test case in T using Cobertura v2.0.3 which is included in Defects4J.

3) Construction of the Evolve relation: To establish the Evolve relationship between C and E, it is necessary to track the commit history for each code element. For this purpose, we utilise the git log command⁷ in line with our prior research [20]. In addition to git log, we explored using CodeShovel [13] and CodeTracker [14], which are advanced tools for retrieving the history of method changes.

Please note that for each statement, we retrieve the commit history of its enclosing method and create the Evolve relations between the statements and the retrieved commits to ensure high recall for commit histories. This is also to deal with omission bugs [29]: if a bug is caused by omission of some statements, we cannot trace the log of the missing statements because they literally do not exist in the current version. In that case, tracing the log of the neighbouring statements (in the enclosing method) will enable to find the inducing commit, as the method that encloses the omission bug should have been covered by the failing tests [20].

4) Detection of Semantic-Preserving Commits: In Stage 2, before comparing the ASTs before and after a commit, we use OpenRewrite v7.21.0⁸ to ensure the same coding standard between the two versions of files. More specifically, we use the Cleanup recipe⁹ that fixes any errors that violate CheckStyle rules.¹⁰ This ensures that trivial differences between two versions that do not lead to semantic differences are ignored: a good example is a commit in Lang, which is shown in Figure 3. To compare ASTs after formatting the files, we use the isomorphism test of GumTree v3.0.0 [22] that has time complexity of O(1).

5) Fault Localisation: In theory, any FL technique that produces suspiciousness scores (or rankings) can be plugged into FONTE. In this paper, we use two representative FL techniques, SBFL and IRFL.

• SBFL: We use a widely-used SBFL formula, Ochiai [30], which can be expressed in our context as follows:

$$Ochiai(e) = \frac{|\{t \in T_F | (t, e) \in \mathsf{Cover}\}|}{\sqrt{|T_F| * |\{t \in T | (t, e) \in \mathsf{Cover}\}|}}$$

By definition, Ochiai(e) > 0 if and only if $e \in E_F$ (Equation (1)).

• IRFL: We employ an unsupervised statement-level IRFL technique, Blues, which was proposed in a recent APR study [31] and builds upon on BLUiR [32], an unsupervised file-level IRFL technique. We directly utilise the pre-computed Blues suspiciousness scores for the Defects4J bugs available in their replication package.

 $^7 \rm git$ log -C -M -L<start_line>,<end_line>:<file>. The flags -C and -M are used for detecting file renaming, copying, or moving across versions.

⁸https://github.com/openrewrite/rewrite

⁹https://docs.openrewrite.org/reference/recipes/java/cleanup

¹⁰https://checkstyle.sourceforge.io/

TABLE IV

Evaluation of code history tracking tools, focusing on the average reduction in BIC search space size, the validity ratio, and the average time taken to compile commit histories. The Validity Ratio represents the proportion of bugs for which the actual BIC is located within the reduced search space C_{BIC} .

History Tracking Tool	Reduction Ratio (After Stage 1, Stage 2)	Validity Ratio	Duration
git log	11.3%, 11.0%	$\begin{array}{r} \mathbf{100\%} \ (= \frac{206}{206}) \\ 99.0\% \ (= \frac{204}{206}) \\ 98.5\% \ (= \frac{203}{206}) \end{array}$	27.3s
CodeShovel	11.8%, 11.1%		521.0s
CodeTracker	11.1% , 10.9%		738.3s

6) Hyperparameters: In our experiments, we investigate the effects of varying hyperparameters: $\alpha \in \{0,1\}$ and $\tau \in \{\max, dense\}$ for Equation (4), and $\lambda \in \{0.1, 0.2, 0.3\}$ for Equation (6).

C. Research Questions

We ask the following research questions in this paper:

- RQ1. How accurately does FONTE find the BIC?
- **RQ2.** Does FONTE outperform other BIC identification approaches?
- **RQ3.** How efficient is the weighted bisection compared to the standard bisection?

VI. RESULTS

This section describes the evaluation methodology used to investigate each research question, along with the findings.

A. RQ1. Effectiveness of FONTE

To evaluate the efficacy of FONTE, we pose three subsidiary questions focusing on its search space reduction capabilities, its performance in ranking BICs, and the impact of the ranking-based voting scheme and depth-based decay.

RQ1-1. Search Space Reduction (Stage 1&2)

To what extent do the first two stages of FONTE reduce the search space?

Evaluation Protocol To determine the extent to which Stages 1 and 2 can narrow down the BIC search space, we calculate the reduction ratio of the BIC search space after Stage 1 $(|C_{susp}|/|C|)$, and Stage 2 $(|C_{BIC}|/|C|)$. Under a consistent methodology for measuring test coverage failures, the process of reducing the search space is influenced solely by the choice of code history tracking tools, which establish the Evolve (or code-commit) relation. Consequently, we report the outcomes of search space reduction using git log, CodeShovel [13], and CodeTracker [14]. Additionally, we verify the presence of the actual BIC within the narrowed search space, $|C_{BIC}|$, as a basic validity test, and measure the time taken to collect the commit histories using each tool to access the efficiency.

Results Table IV presents a comparative analysis of commit counts filtered through the initial two stages of FONTE, using different code history tracking tools. git log and Code-Tracker are the most efficient, reducing the commit count

to 11.3% and 11.1% after the first stage, respectively, and further down to 11.0% and 10.9% after the second stage. CodeShovel shows a slightly less efficient reduction, with 11.8% of commits remaining after the first stage and 11.1% after the second. The Validity Ratio is highest for git log at 100%. This means git log successfully retained the actual BIC in all evaluated instances. In contrast, CodeShovel and CodeTracker have slightly lower Validity Ratios at 99.0% and 98.5%, respectively, indicating that these tools occasionally produce incorrect commit histories, which is detailed in our artifect, which affects their reliability in retaining the BIC throughout the reduction process. The Duration it takes for each tool to compile the commit histories is also noted, with git log being the fastest at 27.3 seconds on average, followed by CodeShovel at 521.0 seconds, and CodeTracker being the slowest at 738.3 seconds. This evaluation highlights the trade-offs between accuracy, efficiency, and effectiveness in reducing the BIC search space among the different tools.

Answer to RQ1-1 On average, the BIC search space was narrowed down to approximately 11% of its initial size, indicating that the choice of code history tracking tool had only a minimal impact on the reduction ratio. Among the evaluated tools, git log stands out for its reliability and efficiency.

RQ1-2. Ranking Performance (Stage 3)

How effectively does the third stage of FONTE identify the BIC within the narrowed search space?

Evaluation Protocol If the scoring mechanism of FONTE is effective, BICs will receive *higher* scores compared to those changes that are not responsible for bugs. Therefore, to assess the performance of FONTE, we employ two widely recognized ranking-based metrics.

- Mean Reciprocal Rank (MRR) [33]: The average reciprocal rank of the BIC (*higher is better*)
- Accuracy@n (Acc@n): The percentage of bugs where the ranking of the ground-truth BIC is within the top *n* positions (*higher is better*)

In situations where multiple elements share identical scores, we apply the max-tiebreaker approach, which conservatively allocates the worst rankings to these tied elements. Additionally, we compare the performance of FONTE against a *random baseline* to ascertain whether the ranking algorithm performs significantly better than random chance. In a scenario where n commits exist in the reduced search space, the expected rank of a BIC under random conditions would be $\frac{1+n}{2}$. We report the MRR and Acc@n values for this baseline.

Since git log demonstrated both reliable and efficient performance in RQ1-1, we use it to establish the Evolve relation for the remaining experiments. Additionally, we evaluate FONTE with diverse settings to answer this question. As a base FL technique for FONTE, we employ either SBFL or IRFL, as described in Section V-B5, in combination with diverse hyperparameter configurations outlined in Section V-B6.

Results Table V details the effectiveness of FONTE in ranking BICs when integrated with two distinct FL techniques: IRFL and SBFL. The evaluation spans a range of hyperparameters

TABLE V THE BIC RANKING PERFORMANCE OF FONTE COMBINED WITH IRFL AND SBFL, ACROSS VARIOUS HYPERPARAMETER CONFIGURATIONS

Hyperparameters		FONTE with IRFL			FONTE with SBFL			
λ	α	$ \tau$	MRR	Acc@1	Acc@5	MRR	Acc@1	Acc@5
0.1 0	dense max	0.453 0.445	30.6% 28.6%	62.6% 65.0%	0.474 0.481	31.6% 32.0%	67.5% 68.9%	
	1	dense max	0.433 0.432	27.2% 27.2%	63.6% 63.1%	0.475 0.473	30.6% 31.6%	70.4% 69.9%
0.2	0	dense max	0.445 0.446	29.1% 28.6%	61.7% 64.6%	0.460 0.475	28.6% 30.6%	68.4% 69.4%
	1	dense max	0.434 0.436	27.7% 28.2%	62.6% 62.6%	0.465 0.465	29.1% 30.1%	70.4% 69.4%
0.2	0	dense max	0.445 0.434	29.1% 26.7%	61.7% 62.6%	0.451 0.471	27.7% 30.6%	68.0% 69.4%
0.5	1	dense max	0.421 0.422	25.2% 25.2%	62.1% 62.1%	0.458 0.459	28.2% 28.6%	69.4% 68.9%
Random Baseline		0.150	1.5%	32.5%	0.150	1.5%	32.5%	



Fig. 6. Performance comparison of FONTE when integrated with IRFL and SBFL, categorised based on whether IRFL outperforms SBFL (IRFL wins), they have equal performance (draw), or SBFL outperforms IRFL (SBFL wins)

and is quantified using three metrics: MRR, Acc@1, and Acc@5. The top-performing results for each FL technique and metric are denoted in bold within the table.

Generally, FONTE, regardless of the settings used, consistently exceeds the performance of the random baseline, demonstrating its strong capability to accurately identify the actual BIC among the potential commits in the reduced search space. With IRFL, FONTE achieves its best MRR at 0.453 and its highest Acc@1 at 30.6%. The best Acc@5 is 65.0%. In the SBFL configuration, FONTE attains its best MRR of 0.481, an Acc@1 of 32.0%, and an Acc@5 of 70.4%. The hyperparameter setting of $\lambda = 0.1$ consistently delivers superior results compared to other λ values. Examining the voting hyperparameters *alpha* and *tau*, for IRFL, the setting of $\alpha = 0$ and $\tau =$ dense demonstrates strong MRR and Acc@1 scores, while $\alpha = 0$ and $\tau = \max$ is notable for its Acc@5. Conversely, for SBFL, the combination of $\alpha = 0$ and $\tau = \max$ is notable for higher MRR and Acc@1, whereas $\alpha = 1$ and $\tau =$ dense is distinguished by its Acc@5 results.

We also observe that the integration of FONTE with SBFL yields superior results compared to combining it with IRFL. This advantage can be largely attributed to the higher FL accuracy of SBFL (using the Ochiai method) over IRFL (using the Blues method). When examining the average rankings of buggy methods across the analyzed bugs, IRFL outperforms SBFL in only 14.6% (30 out of 206) of the cases, whereas SBFL surpasses IRFL in 60.0% (123 out of 206) of the cases. Figure 6 demonstrates that the performance of FONTE

9

TABLE VI Performance evaluation of three variants of Fonte with key features ablated: without Rank-based Voting Power, without Depth-based Decay, and without both features

	MRR	Acc@1	Acc@5
Fonte with IRFL ($\alpha = 0, \tau = \text{dense}, \lambda = 0.1$)	0.453	30.6%	62.6%
- w/o Ranking-based Voting Power	0.404	24.8%	57.3%
- w/o Depth-based Decay	0.422	27.7%	60.7%
- w/o Both	0.378	24.3%	52.9%
Fonte with SBFL ($\alpha = 0, \tau = \max, \lambda = 0.1$)	0.481	32.0%	68.9%
- w/o Ranking-based Voting Power	0.446	29.1%	61.7%
- w/o Depth-based Decay	0.447	29.1%	64.6%
- w/o Both	0.414	27.7%	55.3%

combined with IRFL outperforms that combined with SBFL in cases where IRFL outperforms SBFL, and vice versa. This overall trend indicates that more accurate FL results are likely to lead to better accuracy of FONTE in ranking BIC. Therefore, it is anticipated that FONTE will further benefit from advancements in more accurate and advanced FL techniques in the future.

Answer to RQ1-2: FONTE demonstrates high effectiveness in identifying the BIC within the narrowed search space. When combined with SBFL, FONTE achieves an MRR of 0.481, an Acc@1 of 32.0%, and an Acc@5 of 70.4%, indicating its ability to rank the actual BIC highly within the candidates.

RQ1-3. Ablation Study

What is the impact of Rank-based Voting Power and Depth-based Decay on the performance of FONTE?

Evaluation Protocol To examine the influence of two key features of FONTE, Rank-based Voting Power and Depth-based Decay, on its overall performance, we conduct an ablation study. First, for evaluating the effect of Rank-based Voting Power, we evaluate a naive alternative strategy: using the FL scores directly as the voting power of each statement instead of considering the relative ranking among statements. In simpler terms, we replace Equation (4) with the following equation:

$$vote(e) = susp(e)$$
 (7)

Second, to gauge the impact of Depth-based Decay, we measure how the performance of FONTE changes when the value of λ is set to 0.0, while keeping all other settings unchanged. For the ablation study, we conducted the experiments based on the hyperparameter configuration that demonstrated the highest MRR for FONTE in RQ1-1 to simplify the analysis: (λ, α, τ) is set to (0.1, 0, dense) for FONTE with IRFL, (0.1, 0, max) for FONTE with SBFL.

Results Table VI presents the performance evaluation of FONTE with key features ablated. The absence of Rankingbased Voting Power leads to a 10.8% decrease in performance for FONTE-IRFL, and a 7.3% decrease for FONTE-SBFL, in terms of MRR. Similarly, removing Depth-based Decay causes a 6.8% performance drop with FONTE-IRFL and a 7.3% drop with FONTE-SBFL. Eliminating both features results in a reduction of MRR by 16.6% for FONTE-IRFL and 13.9% for FONTE-SBFL. Specifically, for FONTE combined with IRFL, the lack of Ranking-based Voting Power is particularly detrimental to performance, while the removal of Depth-based Decay, although less impactful, still results in a significant performance decline. This pattern is consistent when FONTE is combined with SBFL, especially in terms of Acc@5. Collectively, these findings highlight the crucial role that both Ranking-based Voting Power and Depth-based Decay play in the overall performance of FONTE, with Rank-based Voting Power playing a more critical role in enhancing performance. **Answer to RQ1-3**: The contribution of Rank-based Voting Power and Depth-based Decay to FONTE's efficacy is considerable: disabling both features results in up to a 16.6% decrease in MRR.

B. RQ2. Comparison with Other Techniques

Evaluation Protocol We compare the BIC ranking performance of FONTE against various commit scoring baselines. To guarantee a fair comparison focused solely on the scoring mechanisms of each method and FONTE, we apply the baseline techniques within the same reduced BIC search space, C_{BIC} . The baselines include a general FL score aggregation method and two state-of-the-art IR-based techniques:

• Max Aggregation of FL Scores: In Orca [9], the filelevel FL scores are converted into the commit level using max-aggregation, that is, the highest FL score among all files changed by the commit is assigned as the commit's score. This max-aggregation method is widely utilised in FL techniques to bridge differing granularities between initial FL scores and the targeted FL granularity [34], [35], such as from statements to methods or files to components. To illustrate and evaluate this concept, we adopt a scoring model where the score of a commit is determined by the maximum FL score among the code elements it alters:

$$commitScore(c) = \max_{e \in E_F^c} susp(e)$$
 (8)

- Bug2Commit [19]: Bug2Commit is a state-of-the-art IRbased BIC identification method for large-scale systems, leveraging various features of commits and bug reports. In our implementation of Bug2Commit, we opt for the Vector Space Model (VSM) because using a word-embedding model would necessitate an extra dataset comprising bug reports and commits for training. Following the approach detailed in the original study, we employ BM25 [36] for vectorisation. For the tokenisation process, the Ronin tokeniser is selected, recognised as the most sophisticated option available in Spiral [37]¹¹. We consider two features from each commit: the text of the commit message and the names of files that were altered. To represent bug reports, we evaluate two distinct configurations:
 - Bug2Commit_{report}: Utilizes (1) the title and (2) the content of the bug report, both crafted by humans.
 - Bug2Commit_{report+symptom}: Builds on the previous configuration by additionally incorporating (3) the observed failure symptoms, such as exception messages and stack traces from failed test cases.

TABLE VII Comparision of Fonte against commit scoring baselines. The methods marked with †utilise bug reports as input.

	MRR	Acc@1	Acc@5
Fonte with SBFL	0.481	32.0%	68.9%
Fonte with IRFL †	0.453	30.6%	62.6%
Bug2Commit _{report+symptom}	0.330	17.0%	57.3%
Bug2Commit _{report} †	0.318	17.5%	54.4%
Max Aggregation of SBFL Scores	0.288	12.1%	48.5%
Max Aggregation of IRFL Scores †	0.274	11.7%	46.6%
FBL-BERT †	0.246	14.1%	38.3%

• FBL-BERT [38]: FBL-BERT is a recently proposed changeset localisation technique based on a pre-trained BERT model called BERTOverflow [39]. Given a bug report, it retrieves the relevant changesets using their scores obtained by the BERT-based model. We fine-tune the model using the training dataset from the JDT project, which is the largest training dataset provided by their repository¹²: this is because no such training data is available for our target projects. We use the ARC changeset encoding strategy, which categorises the lines in the changeset into Added, Removed, and Context groups. This method has been demonstrated to perform the best for changeset-level retrieval in the original study [38]. As Defects4J contains the link to the original bug report for every bug, we use the contents of the original bug report as an input query.

Results Table VII presents the ranking performance of the commit scoring baselines, sorted in descending order of MRR, along with the performance of FONTE. Among the baselines, Bug2Commit performs the best when utilising both the human-written bug report and failure symptoms as input to find the relevant commit. However, the results show that FONTE outperforms all scoring baselines across every evaluation metric. Specifically, FONTE with SBFL and IRFL demonstrates at least 45.8% and 37.3% higher MRR, respectively, compared to the baselines. This superior performance of FONTE holds true for any hyperparameter configuration, as shown in Table V.

Furthermore, although three baselines (marked with †) use the same input data, i.e., the bug report, FONTE with IRFL achieves significantly superior performance. This highlights the effectiveness of FONTE's approach in converting codelevel FL scores to commit-level scores. This is particularly evident when comparing FONTE with the max aggregation scheme, as they differ only in how the initial IRFL scores (in this case, Blues) are converted to the commit level.

Answer to RQ2 The scoring approach of FONTE outperforms both the max-aggregation method for FL scores and the stateof-the-art IR-based techniques. Notably, when FONTE is paired with IRFL, which relies solely on the bug report for input, it achieves superior results compared to other methods that utilise the same input data.

 $^{^{12}}$ We confirm that the model fine-tuned with JDT performs better than that fine-tuned with ZXing, which has the smallest training dataset.



Fig. 7. The number of saved search iterations required until finding the BIC using the weighted bisection compared to the standard bisection on the **entire** commit history, C



Fig. 8. The number of saved search iterations required until finding the BIC using the weighted bisection compared to the standard bisection on the **reduced** commit history, C_{BIC}

C. RQ3. Standard Bisection vs. Weighted Bisection

Evaluation Protocol We simulate the standard and weighted bisection algorithms on all target bugs, assuming that the bug-revealing tests can perfectly reveal the existence of bugs. As commit scores, we use the best-performing configuration found in RQ1: FONTE with SBFL ($\alpha = 0, \tau = \max, \lambda = 0.1$). We report how many search iterations until finding the BIC can be saved by using the weighted bisection algorithm compared to the standard bisection.

Results Figure 7 presents a sorted bar chart that shows the number of saved search iterations for all subjects until finding the BIC using the weighted bisection algorithm with FONTE-generated scores, compared to the standard bisection search on the entire commit history. The weighted bisection can reduce the search cost for approximately 98% (202 out of 206) of the cases, saving up to 11 search iterations. On average, the number of iterations is reduced by 6.26, resulting in only 40% of the iterations required by the standard bisection approach. Notably, there is no case where the weighted bisection degrades the performance compared to the standard bisection.

For a more conservative comparison, the weighted bisection algorithm using FONTE-generated scores is compared against the standard bisection search when both are applied to the reduced search space, C_{BIC} . Figure 8 shows that the weighted bisection can reduce the number of required search iterations for 133 out of 206 subjects (64.6%), while the number of iterations is increased in only 17 out of 206 subjects (8.3%). In the remaining 27.2% of cases, the number of iterations is the same as the standard bisection. The results demonstrate that the commit score information can guide the search process more efficiently. To ensure that the median of the number of saved iterations is positive, indicating a performance improvement, a one-sided Wilcoxon signed-rank test [40] is performed. The null hypothesis is that the median is negative, implying performance degradation. The obtained p-value of 1.69×10^{-19} allows the rejection of the null hypothesis in favor of the alternative that the median of the number of saved iterations is



Fig. 9. Regression plot illustrating the relationship between the effectiveness of FONTE, measured by the normalized rank of the BIC, and the effectiveness of the weighted bisection technique, measured by the number of iterations saved compared to the standard bisection approach

greater than zero, supporting the performance improvement.

We conducted an additional analysis to understand why the weighted bisection technique degrades the search efficiency for 17 subjects (8.3%). In these cases, we found that the BIC was not ranked well by FONTE, either not being among the top 10 or even the top 50% candidates. Figure 9 illustrates that the number of saved search iterations by using the weighted bisection exhibits a negative correlation with the normalised BIC rank, with a Pearson correlation coefficient of -0.64. This finding collectively suggests that more accurate commit scores can benefit the search process of the weighted bisection.

Answer to RQ3 The combination of weighted bisection and FONTE-generated commit scores can reduce the BIC search cost for 98% of the studied bugs, compared to the standard bisection applied to the entire commit history. On average, it saves 6.3 iterations. When the bisection is performed solely on the reduced set of candidate commits, the weighted bisection technique saves the number of search iterations in 65% of cases, while increasing it in only 8% of cases where the commit scores are of low quality.

VII. APPLICATION TO INDUSTRY SOFTWARE

SAP HANA is a large-scale commercial software that consists of more than 10M lines of C++ and C. In the CI system of SAP HANA, multiple commits that have individually passed the pre-submit testing are merged into the delivery branch and tested together using a more extensive test suite on a daily basis. Considering the set of multiple commits as a single batch, this is a type of Batch Testing [41]. While batch testing reduces the overall test execution cost for SAP HANA, it also has some practical drawbacks: when a test fails, it is not immediately clear which change in the batch is responsible for the failure [7]. The current CI system of SAP HANA identifies the BIC in the batch using automatic bisection to aid the bug assignments [42]. However, each individual inspection during the bisection can take up to several hours due to the compilation, installation, and test execution cost, resulting in severe bottlenecks in the overall debugging process. The bottleneck can be particularly problematic if integration or system-level tests fail.



Fig. 10. Simplified batch testing scenario

TABLE VIII Evaluation of Fonte on the 23 batch testing failures of SAP HANA

	MRR	Accuracy				
		@1	@2	@3	@5	@10
Fonte	0.600	10 (43%)	14 (61%)	15 (65%)	20 (87%)	23 (100%)
Random	0.110	0	0	0	1	17

This motivates us to see whether FONTE and its weighted bisection can reduce the number of bisection iterations. To evaluate the effectiveness of applying FONTE, we collect 23 batch testing failures that occurred from July to August 2022 and their BICs identified by the bisection from the internal CI logs of SAP HANA. Using the data, we first check if FONTE can find the BIC inside the batch accurately (Figure 10). As the test coverage of SAP HANA is regularly and separately updated instead of being measured at each of the batch testings, we use the latest line-level coverage information to calculate the Ochiai scores. Note that we do not need to compute the Ochiai scores for all lines, but only the lines covered by the failing tests. When applying FONTE, depthbased voting decay is not used ($\lambda = 0$) because all candidate commits are submitted on the same day and have not yet been merged into the main codebase. For the other hyperparameters, we use $\alpha = 1$ and $\tau = \max$ which performed the best with $\lambda = 0$ in our experiment with Defects4J.

Table VIII shows the BIC ranking performance of FONTE in terms of MRR and Accuracy@n. While each batch contains 18.48 commits on average, FONTE can locate the actual BIC within the top 1 and 5 for 43% and 87% of the failures, respectively. Compared to the random baseline, it achieves 5.5-fold increase in MRR. Further, we also report that the weighted bisection can reduce the bisection iterations for 18 out of 23 cases (78%), while it increases the cost in only three cases (13%). Based on this result, we plan to incorporate weighted bisection into the CI process of SAP HANA, which is expected to save 32% of required iterations. Considering that each iteration can take up to several hours, we expect a significant reduction in the average BIC identification cost for SAP HANA in the long run.

VIII. THREATS TO VALIDITY

Threats to internal validity concern factors that can affect how confident we are about the causal relationship between the treated factors and the effects. FONTE relies on widelyadopted open-source tools to establish Cover and Evolve relations to ensure the chain of causality between the test failure and BIC identification. We compare the validity of these different code history mining tools, that are used to build the Evolve relation, and use the most reliable one, git log, for the later experiments. We also make the performance results with the other tools publicly available in our artifact for future scrutiny, Additionally, as the baseline techniques rely on multiple sources of information, such as bug reports, we choose Defects4J as our benchmark as it provides wellestablished links between real-world bug reports and the buggy version, not to mention human-written bug-revealing test cases that withheld scrutiny from the community.

Threats to external validity concern factors that may affect how well our findings can be generalised to unseen cases. Our key findings are primarily based on experiments with the open-source Java programs in Defects4J. Since they are not representative of the entire population of real-world programs, only further evaluations can strengthen our claim of generalisation. We tried to support our claim by evaluating FONTE with industry-scale software written in C and C++. We do note that FONTE does not generalise to bugs that are caused by non-executable files, such as configuration changes, as its base assumption is that the test failure is caused by a bug in the source code. We leave extension of FONTE to bugs caused by non-executable changes as our primary future work.

Threats to construct validity concern how well the used metrics measure the properties we aim to evaluate. We adopt two ranking-evaluation metrics, MRR and Accuracy@n, to evaluate FONTE: both have been widely used in the IR and SE literature. Since they are based on absolute ranks, we do note that the results can be overrated when the number of ranking candidates is small. To mitigate the threat, we also present the expected and worst values for the measures as baselines.

IX. RELATED WORK

Locus [2] is the first work that proposed to localise the bug at the software change level. It takes a bug report as an input query and locates the relevant change hunk based on the token similarities. IR-based techniques, such as Locus, and FONTE can complement each other depending on circumstances. When the failure cannot be reproduced from the bug report, IR-based techniques can be used instead of FONTE. However, if the coverage of the failing and passing tests are available, we can apply FONTE with SBFL to more precisely rank the commits without relying on IR. ChangeLocator [3] aims to find a BIC for crashes using the call stack information. It is a learning-based approach that requires data from fixed crashes. Unlike ChangeLocator, FONTE is not limited to crashes and can be applied to general failures. Orca [9] takes symptoms of bugs, such as an exception message or customer complaints, as an input query and outputs a ranked list of commits ordered by their relevance to the query. It uses the TF-IQF [43] to compute the relevance scores of files, and aggregate them to a commit level. Subsequently, it uses machine learning to predict the risk of candidate commits for breaking ties. Bug2Commit [19] uses multiple features extracted from bug reports and commits, and aggregates all features by taking the average of their vector representations. Although Bug2Commit uses an unsupervised

learning approach, it needs the historical data of projectspecific bug reports and commits to train the word embedding model. FBL-BERT [38] retrieves the relevant changeset for the input bug report using a fine-tuned BERT model that can capture the semantics in the text. It proposes fine-grained changeset encoding methods and accelerates the retrieval by offline indexing [44]. The major difference between FONTE and the techniques mentioned above is that FONTE does not require any training. Further, FONTE can be combined with any code-level FL technique, without being coupled to specific sources of information, as long as the coverage of failing executions is available.

The weighted bisection algorithm we propose is similar to FACF (Flaky Aware Culprit Finding) [45], which formulates the *flake-aware* bisection problem as a Bayesian inference, in that both guide the bisection process based on the probability of commits being a source of test failure. The difference between the two algorithms is that ours uses commit scores from FONTE to establish the initial probability distribution, while FACF updates the probability based on the test results during the search taking into account the potential for flakiness. The original work notes that FACF can take into account any prior information about the bug inducing change in the form of an initial probability distribution. Hence, we believe that the commit scores generated by FONTE can be used as an effective prior distribution for the FACF framework.

There exist studies that are highly relevant to FONTE despite not being specifically about the BIC identification domain. FaultLocator [46] is similar to FONTE as both use code-level FL scores to identify suspicious changes. FaultLocator combines spectrum information with the change impact analysis to precisely identify the failure-inducing *atomic* edits out of all edits between two versions, whereas FONTE aims to pinpoint BICs in the commit history. WhoseFault [47] is a method that utilises code-level FL scores and commit history to determine the developer responsible for a bug. While it provides insights into the assignment of bugs, it does not specifically target BIC identification. As a result, it cannot be directly compared with FONTE in our evaluation, nor can it be integrated with our bisection algorithm. Our belief is that accurately identifying the BIC can also be used to find the developer responsible for fixing the bug, based on the authorship of the changes, in addition to helping developers understand the context in which the failure occurred.

X. CONCLUSION

This paper proposes FONTE, a BIC identification technique that is available upon the observation of a failure. It prunes the BIC search space using failure coverage and the syntactic analysis of commits, and assigns scores to the remaining commits using the FL scores as well as change histories of code elements. Our experiments with 206 bugs in Defects4J show that FONTE can effectively identify BICs with an MRR of 0.481, which significantly outperforms the baselines including state-of-the-art BIC identification techniques. The findings indicate that FONTE is an effective algorithm to translate code-level suspiciousness scores into commit-level scores. Along with FONTE, we also propose the weighted bisection to accelerate the BIC search utilising the commit score information and show that it can save the search cost in 98% of the studied cases compared to the standard bisection. Finally, the application of FONTE to a large-scale industry software SAP HANA shows that FONTE can successfully reduce the cost of BIC identification in a batch-testing CI scenario.

REFERENCES

- J. Śliwerski, T. Zimmermann, and A. Zeller, "When do changes induce fixes?" ACM SIGSOFT Software Engineering Notes, vol. 30, no. 4, pp. 1–5, jul 2005. [Online]. Available: https://doi.org/10.1145%2F1082983. 1083147
- [2] M. Wen, R. Wu, and S.-C. Cheung, "Locus: locating bugs from software changes," in *Proceedings of the 31st IEEE/ACM International Conference on Automated Software Engineering*. ACM, aug 2016. [Online]. Available: https://doi.org/10.1145%2F2970276.2970359
- [3] R. Wu, M. Wen, S.-C. Cheung, and H. Zhang, "ChangeLocator: locate crash-inducing changes based on crash reports," *Empirical Software Engineering*, vol. 23, no. 5, pp. 2866–2900, nov 2017. [Online]. Available: https://doi.org/10.1007%2Fs10664-017-9567-4
- [4] M. Wen, Y. Liu, and S.-C. Cheung, "Boosting automated program repair with bug-inducing commits," in *Proceedings of the ACM/IEEE* 42nd International Conference on Software Engineering: New Ideas and Emerging Results. ACM, jun 2020. [Online]. Available: https://doi.org/10.1145%2F3377816.3381743
- [5] M. Wen, J. Chen, Y. Tian, R. Wu, D. Hao, S. Han, and S.-C. Cheung, "Historical spectrum based fault localization," *IEEE Transactions on Software Engineering*, vol. 47, no. 11, p. 2348–2368, Nov. 2021. [Online]. Available: http://dx.doi.org/10.1109/TSE.2019.2948158
- [6] M. Wen, R. Wu, Y. Liu, Y. Tian, X. Xie, S.-C. Cheung, and Z. Su, "Exploring and exploiting the correlations between bug-inducing and bug-fixing commits," in *Proceedings of the 27th ACM European* Software Engineering Conference and Symposium on the Foundations of Software Engineering. ACM, aug 2019. [Online]. Available: https://doi.org/10.1145%2F3338906.3338962
- [7] M. J. Beheshtian, A. H. Bavand, and P. C. Rigby, "Software batch testing to save build test resources and to reduce feedback time," *IEEE Transactions on Software Engineering*, vol. 48, no. 8, pp. 2784–2801, aug 2022. [Online]. Available: https://doi.org/10.1109% 2Ftse.2021.3070269
- [8] "Git-bisect-lk2009 documentation." [Online]. Available: https://git-scm. com/docs/git-bisect-lk2009.html
- [9] R. Bhagwan, R. Kumar, C. S. Maddila, and A. A. Philip, "Orca: Differential bug localization in large-scale services," in 13th USENIX Symposium on Operating Systems Design and Implementation (OSDI 18), 2018, pp. 493–509.
- [10] W. E. Wong, R. Gao, Y. Li, R. Abreu, and F. Wotawa, "A survey on software fault localization," *IEEE Transactions on Software Engineering*, vol. 42, no. 8, pp. 707–740, aug 2016. [Online]. Available: https://doi.org/10.1109%2Ftse.2016.2521368
- [11] R. Just, D. Jalali, and M. D. Ernst, "Defects4j: a database of existing faults to enable controlled testing studies for java programs," in *Proceedings of the 2014 International Symposium on Software Testing* and Analysis - ISSTA 2014. ACM Press, 2014. [Online]. Available: https://doi.org/10.1145%2F2610384.2628055
- [12] G. An, J. Hong, N. Kim, and S. Yoo, "Fonte: Finding bug inducing commits from failures," in 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE, May 2023. [Online]. Available: http://dx.doi.org/10.1109/ICSE48619.2023.00059
- [13] F. Grund, S. A. Chowdhury, N. C. Bradley, B. Hall, and R. Holmes, "CodeShovel: Constructing method-level source code histories," in 2021 IEEE/ACM 43rd International Conference on Software Engineering (ICSE). IEEE, may 2021. [Online]. Available: https://doi.org/10.1109%2Ficse43902.2021.00135
- [14] M. Jodavi and N. Tsantalis, "Accurate method and variable tracking in commit history," in *Proceedings of the 30th ACM Joint European Software Engineering Conference and Symposium on the Foundations* of Software Engineering. ACM, nov 2022. [Online]. Available: https://doi.org/10.1145%2F3540250.3549079

- [15] P. S. Kochhar, X. Xia, D. Lo, and S. Li, "Practitioners' expectations on automated fault localization," in *Proceedings of the 25th International Symposium on Software Testing and Analysis*, ser. ISSTA '16. ACM, Jul. 2016. [Online]. Available: http://dx.doi.org/10.1145/ 2931037.2931051
- [16] S. Artzi, S. Kim, and M. D. Ernst, "ReCrash: Making software failures reproducible by preserving object states," in *ECOOP 2008 – Object-Oriented Programming*. Springer Berlin Heidelberg, pp. 542–565. [Online]. Available: https://doi.org/10.1007%2F978-3-540-70592-5_23
- [17] W. Jin and A. Orso, "BugRedux: Reproducing field failures for in-house debugging," in 2012 34th International Conference on Software Engineering (ICSE). IEEE, jun 2012. [Online]. Available: https://doi.org/10.1109%2Ficse.2012.6227168
- [18] T. Zimmermann, R. Premraj, N. Bettenburg, S. Just, A. Schroter, and C. Weiss, "What makes a good bug report?" *IEEE Transactions on Software Engineering*, vol. 36, no. 5, pp. 618–643, sep 2010. [Online]. Available: https://doi.org/10.1109%2Ftse.2010.63
- [19] V. Murali, L. Gross, R. Qian, and S. Chandra, "Industry-scale IR-based bug localization: A perspective from facebook," in 2021 IEEE/ACM 43rd International Conference on Software Engineering: Software Engineering in Practice (ICSE-SEIP). IEEE, may 2021. [Online]. Available: https://doi.org/10.1109%2Ficse-seip52600.2021.00028
- [20] G. An and S. Yoo, "Reducing the search space of bug inducing commits using failure coverage," in *Proceedings of the 29th ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering*. ACM, aug 2021. [Online]. Available: https://doi.org/10.1145%2F3468264.3473129
- [21] S. Kim, T. Zimmermann, K. Pan, and E. J. J. Whitehead, "Automatic identification of bug-introducing changes," in 21st IEEE/ACM International Conference on Automated Software Engineering (ASE'06). IEEE, sep 2006. [Online]. Available: https://doi.org/10.1109%2Fase.2006.23
- [22] J. Falleri, F. Morandat, X. Blanc, M. Martinez, and M. Monperrus, "Fine-grained and accurate source code differencing," in ACM/IEEE International Conference on Automated Software Engineering, ASE '14, Vasteras, Sweden - September 15 - 19, 2014, 2014, pp. 313–324. [Online]. Available: http://doi.acm.org/10.1145/2642937.2642982
- [23] M. Fowler, Refactoring. Addison-Wesley Professional, 2018.
- [24] E. C. Neto, D. A. da Costa, and U. Kulesza, "The impact of refactoring changes on the SZZ algorithm: An empirical study," in 2018 IEEE 25th International Conference on Software Analysis, Evolution and Reengineering (SANER). IEEE, mar 2018. [Online]. Available: https://doi.org/10.1109%2Fsaner.2018.8330225
- [25] D. Silva, J. P. da Silva, G. Santos, R. Terra, and M. T. Valente, "RefDiff 2.0: A multi-language refactoring detection tool," *IEEE Transactions* on Software Engineering, vol. 47, no. 12, pp. 2786–2802, dec 2021. [Online]. Available: https://doi.org/10.1109%2Ftse.2020.2968072
- [26] J. Sohn and S. Yoo, "Why train-and-select when you can use them all?" in *Proceedings of the Genetic and Evolutionary Computation Conference*. ACM, jul 2019. [Online]. Available: https://doi.org/10. 1145%2F3321707.3321873
- [27] J. Sohn, G. An, J. Hong, D. Hwang, and S. Yoo, "Assisting bug report assignment using automated fault localisation: An industrial case study," in 2021 14th IEEE Conference on Software Testing, Verification and Validation (ICST). IEEE, apr 2021. [Online]. Available: https://doi.org/10.1109%2Ficst49551.2021.00041
- [28] S. Habchi, G. Haben, J. Sohn, A. Franci, M. Papadakis, M. Cordy, and Y. Le Traon, "What made this test flake? pinpointing classes responsible for test flakiness," *arXiv e-prints*, pp. arXiv–2207, 2022. [Online]. Available: https://doi.org/10.48550/arXiv.2207.10143
- [29] X. Zhang, S. Tallam, N. Gupta, and R. Gupta, "Towards locating execution omission errors," in *Proceedings of the 2007 ACM SIGPLAN* conference on Programming language design and implementation -*PLDI '07.* ACM Press, 2007. [Online]. Available: https://doi.org/10. 1145%2F1250734.1250782
- [30] R. Abreu, P. Zoeteweij, and A. V. Gemund, "An evaluation of similarity coefficients for software fault localization," in 2006 12th Pacific Rim International Symposium on Dependable Computing (PRDC'06). IEEE, 2006. [Online]. Available: https://doi.org/10.1109%2Fprdc.2006.18
- [31] M. Motwani and Y. Brun, "Better automatic program repair by using bug reports and tests together," in 2023 IEEE/ACM 45th International Conference on Software Engineering (ICSE). IEEE, May 2023. [Online]. Available: http://dx.doi.org/10.1109/ICSE48619.2023.00109
- [32] R. K. Saha, M. Lease, S. Khurshid, and D. E. Perry, "Improving bug localization using structured information retrieval," in 2013 28th IEEE/ACM International Conference on Automated Software

Engineering (ASE). IEEE, Nov. 2013. [Online]. Available: http://dx.doi.org/10.1109/ASE.2013.6693093

- [33] N. Craswell, "Mean reciprocal rank," in *Encyclopedia of Database Systems*. Springer US, 2009, pp. 1703–1703. [Online]. Available: https://doi.org/10.1007%2F978-0-387-39940-9_488
- [34] J. Sohn and S. Yoo, "FLUCCS: using code and change metrics to improve fault localization," in *Proceedings of the 26th ACM SIGSOFT International Symposium on Software Testing and Analysis*. ACM, jul 2017. [Online]. Available: https://doi.org/10.1145%2F3092703.3092717
- [35] Y. Lou, A. Ghanbari, X. Li, L. Zhang, H. Zhang, D. Hao, and L. Zhang, "Can automated program repair refine fault localization? a unified debugging approach," in *Proceedings of the 29th ACM SIGSOFT International Symposium on Software Testing and Analysis*. ACM, jul 2020. [Online]. Available: https://doi.org/10.1145%2F3395363.3397351
- [36] S. E. Robertson, S. Walker, S. Jones, M. M. Hancock-Beaulieu, M. Gatford *et al.*, "Okapi at TREC-3," *Nist Special Publication Sp*, vol. 109, p. 109, 1995.
- [37] M. Hucka, "Spiral: splitters for identifiers in source code files," *Journal of Open Source Software*, vol. 3, no. 24, p. 653, Apr. 2018. [Online]. Available: http://joss.theoj.org/papers/10.21105/joss.00653
- [38] A. Ciborowska and K. Damevski, "Fast changeset-based bug localization with BERT," in *Proceedings of the 44th International Conference* on Software Engineering. ACM, may 2022. [Online]. Available: https://doi.org/10.1145%2F3510003.3510042
- [39] J. Tabassum, M. Maddela, W. Xu, and A. Ritter, "Code and named entity recognition in StackOverflow," in *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, 2020, pp. 4913–4926. [Online]. Available: https://doi.org/10.18653/v1/ 2020.acl-main.443
- [40] F. Wilcoxon, "Individual comparisons by ranking methods," in *Springer Series in Statistics*. Springer New York, 1992, pp. 196–202. [Online]. Available: https://doi.org/10.1007%2F978-1-4612-4380-9_16
- [41] A. Najafi, P. C. Rigby, and W. Shang, "Bisecting commits and modeling commit risk during testing," in *Proceedings of the 2019 27th* ACM Joint Meeting on European Software Engineering Conference and Symposium on the Foundations of Software Engineering. ACM, aug 2019. [Online]. Available: https://doi.org/10.1145%2F3338906.3338944
- [42] T. Bach, A. Andrzejak, C. Seo, C. Bierstedt, C. Lemke, D. Ritter, D. W. Hwang, E. Sheshi, F. Schabernack, F. Renkes, G. Gaumnitz, J. Martens, L. Hoemke, M. Felderer, M. Rudolf, N. Jambigi, N. May, R. Joy, R. Scheja, S. Schwedes, S. Seibel, S. Seifert, S. Haas, S. Kraft, T. Kroll, T. Scheuer, and W. Lehner, "Testing very large database management systems: The case of SAP HANA," *Datenbank-Spektrum*, nov 2022. [Online]. Available: https://doi.org/10.1007%2Fs13222-022-00426-x
- [43] J.-M. Yang, R. Cai, F. Jing, S. Wang, L. Zhang, and W.-Y. Ma, "Searchbased query suggestion," in *Proceeding of the 17th ACM conference on Information and knowledge mining - CIKM '08.* ACM Press, 2008. [Online]. Available: https://doi.org/10.1145%2F1458082.1458321
- [44] J. Johnson, M. Douze, and H. Jégou, "Billion-scale similarity search with GPUs," *IEEE Transactions on Big Data*, vol. 7, no. 3, pp. 535–547, 2019. [Online]. Available: https://doi.org/10.1109/TBDATA. 2019.2921572
- [45] T. A. D. Henderson, B. Dorward, E. Nickell, C. Johnston, and A. Kondareddy, "Flake aware culprit finding," in 2023 IEEE Conference on Software Testing, Verification and Validation (ICST). IEEE, apr 2023. [Online]. Available: https://doi.org/10.1109%2Ficst57152.2023.00041
- [46] L. Zhang, M. Kim, and S. Khurshid, "Localizing failure-inducing program edits based on spectrum information," in 2011 27th IEEE International Conference on Software Maintenance (ICSM). IEEE, 2011, pp. 23–32. [Online]. Available: https://doi.org/10.1109/ICSM. 2011.6080769
- [47] F. Servant and J. A. Jones, "WhoseFault: Automatic developer-to-fault assignment through fault localization," in 2012 34th International Conference on Software Engineering (ICSE). IEEE, jun 2012. [Online]. Available: https://doi.org/10.1109%2Ficse.2012.6227208