WeedsGalore: A Multispectral and Multitemporal UAV-based Dataset for Crop and Weed Segmentation in Agricultural Maize Fields

Ekin Celikkan^{1,2} Timo Kunzmann¹ Yertay Yeskaliyev¹ Sibylle Itzerott¹ Nadja Klein³ Martin Herold¹ ¹GFZ German Research Centre for Geosciences ²Humboldt-Universität zu Berlin ³Scientific Computing Center, Karlsruhe Institute of Technology {ekin.celikkan, itzerott, herold}@gfz.de nadja.klein@kit.edu

Abstract

Weeds are one of the major reasons for crop yield loss but current weeding practices fail to manage weeds in an efficient and targeted manner. Effective weed management is especially important for crops with high worldwide production such as maize, to maximize crop yield for meeting increasing global demands. Advances in near-sensing and computer vision enable the development of new tools for weed management. Specifically, state-of-the-art segmentation models, coupled with novel sensing technologies, can facilitate timely and accurate weeding and monitoring systems. However, learning-based approaches require annotated data and show a lack of generalization to aerial imaging for different crops. We present a novel dataset for semantic and instance segmentation of crops and weeds in agricultural maize fields. The multispectral UAV-based dataset contains images with RGB, red-edge, and nearinfrared bands, a large number of plant instances, dense annotations for maize and four weed classes, and is multitemporal. We provide extensive baseline results for both tasks, including probabilistic methods to quantify prediction uncertainty, improve model calibration, and demonstrate the approach's applicability to out-of-distribution data. The results show the effectiveness of the two additional bands compared to RGB only, and better performance in our target domain than models trained on existing datasets. We hope our dataset advances research on methods and operational systems for fine-grained weed identification, enhancing the robustness and applicability of UAVbased weed management. The dataset and code are available at https://github.com/GFZ/weedsgalore.

1. Introduction

Weeds are a major reason for crop yield loss as they compete with desired crops for resources like nutrients, wa-



Figure 1. *WeedsGalore* dataset. We present a novel reference dataset for UAV-based weed monitoring for maize fields. The dataset a) contains images with 5-bands (RGB, near-infrared, red-edge) and b) is recorded at different growth stages, fully reflecting real-world agricultural practices. c) We provide detailed pixel-level annotations for semantic (multiple weed classes) and instance segmentation.

ter, and space [57]. The global demand for food is constantly rising, while climate change and economic considerations pose challenges to agricultural production [46, 62]. Hence, any factor threatening the yield should be managed and minimized, one such factor being weeds.

There are two common approaches to weeding: Chemical (i.e. spraying herbicides) and mechanical (i.e. physical removal) weeding. Both treatments have negative environmental impacts and financial costs. These are further amplified by excessive usage of chemicals, leading to herbicide-resistant weed populations [50]. In response to those challenges, site-specific weed management (SSWM) aims to target weeding to specific areas. To be able to realize SSWM effectively and at scale, as is the case in realworld agricultural fields, automated systems and data with high temporal and spatial precision are crucial.

Unmanned aerial vehicle (UAV) based systems are one of the most promising directions in agriculture. They do not suffer from the drawbacks associated with ground-based vehicles that have limited viewpoints and the inability to navigate complex terrains. This makes UAVs ideal candidates for weed monitoring. However, approaches relying on existing datasets fail to transfer to UAV systems for unseen crop types. Maize fields, having the highest worldwide production in the cereal category [22], are such a domain, for which such automated systems are crucial for future agricultural practices. There is very limited publicly available data for weed segmentation in general, especially when it comes to UAVs and more advanced sensors beyond RGB, which contain extra information useful for plant imaging [45, 65]. We introduce *WeedsGalore*, a dataset for pixel-level identification of maize and weeds. To the best of our knowledge, it is the first UAV-based dataset providing semantic and instance labels for crops and weeds in maize fields. We use a non-invasive UAV for data acquisition and provide labels for four weed classes, where the multitemporality is incorporated in terms of diversity in growth stages.

Segmentation models are useful beyond SSWM and there is an increasing interest in estimating the weed cover for plant science research, where computer vision-based weed localization can help in testing and comparing treatments (e.g. herbicides). A typical approach is to conduct different experiments regarding herbicide applications and calculate the weed control efficiency of the tested herbicide [39,49]. Traditionally, the weed cover during these experiments has been measured manually, which is naturally very cumbersome and error-prone [56, 61]. Hence, models that can accurately segment weeds are vital to support and accelerate agricultural research. To tackle the current lack of publicly available datasets for fine-grained weed segmentation in maize fields, our dataset WeedsGalore provides images with five bands (red, green, blue (RGB), red-edge (RE), near-infrared (NIR)) and contains four different weed classes, enabling monitoring of different weed populations.

Model selection plays an integral role in the realworld deployment of automated weed segmentation methods since real-world data is typically confronted with unseen objects and noisy measurements. As a result, models that are well-calibrated and quantify prediction uncertainty realistically are needed, to correctly detect overconfident predictions and areas of high uncertainties. Both properties can significantly contribute to risk management and generalizability in real-world agricultural fields. To meet the need for reliable methods, we propose to deploy a Bayesian model with uncertainty quantification on our dataset.

We evaluate *WeedsGalore* for the tasks of semantic and instance segmentation. The results show that our dataset

uniquely enables the application of aerial monitoring in maize fields, and through the use of probabilistic methods the model performance and calibration can be significantly improved, especially on out-of-distribution (OOD) data.

In summary, our contributions are:

- We present a novel reference dataset for crop and weed segmentation in maize fields, with dense annotations for multiple weed species covering multiple phenological stages. To the best of our knowledge, it is the first publicly available multispectral UAV dataset for weed monitoring in maize fields, offering two extra bands compared to conventional RGB datasets and with unprecedented weed density.
- We provide extensive quantitative evaluation for semantic and instance segmentation with several state-of-theart methods, including probabilistic methods for improved model calibration and uncertainty quantification.
- 3. We furthermore demonstrate the usefulness of our dataset by testing our method under real-world conditions and show that models trained on WeedsGalore can be successfully deployed in unseen maize fields, including large-scale orthomosaics.

2. Related Work

2.1. Weed Segmentation for Precision Agriculture and Plant Science Research

As in many domains, computer vision techniques have found interest in agricultural applications and research. One such task is weed monitoring, as there is growing interest in developing automated weeding systems that effectively localize and remove weeds from agricultural croplands [6, 14,66]. Existing approaches can be analyzed based on their choices for system components, such as imaging platform, sensor/image modality, target application (i.e. crop type), task formulation, and model selection.

Imaging platform. The majority of existing systems rely on unmanned ground vehicles (UGVs), although they have many limitations, for example, the inherent risk of damaging plants, the need for mechanical adjustment to different environments, and the deployment on crop fields with minimal inter- and intra-row distances (e.g. wheat, barley, etc. [4, 13]). A promising alternative is using images acquired by UAVs (i.e., drones), and localizing and classifying plants of interest. Our system and data are UAV-based, as UAVs stand out due to their agile and non-invasive nature, and commercial availability [35, 43].

Imaging sensor. The overwhelming majority of existing work on weed segmentation relies only on RGB data [15,25,58,64], which is surprising as more bands hold useful information for weed segmentation [45, 60]. We utilize multispectral imagery (MSI), which contains two extra bands compared to regular RGB sensors.

Dataset	V	C	DL ($\operatorname{GSD}\left[\frac{px}{mm}\right]$	Modality	Annotations		#	#Instances / Image		34.1.2	
	Year	Crop	Platform			Semantic	Instance	#weed classes	Crop	Weed	Multitemp.	Resolution
Carrot-Weed [31]	2015	Carrot	UGV	8.95	MSI	1	X	1	-	-	X	1296×966
WeedMap [54]	2018	Sugar beet	UAV	>8.3	MSI	1	X	1	_	-	1	-
CoFly-WeedDB [40]	2022	Cotton	UAV	-	RGB	1	X	3	-	-	×	1280×720
Sorghum-Weed [25]	2022	Sorghum	UAV	1.0	RGB	1	X	1	_	-	×	-
WE3DS [38]	2023	7*	UGV	0.4	RGB-D	1	X	10*	_	_	1	1600×1144
PhenoBench [64]	2023	Sugar beet	UAV	1.0	RGB	1	1	1	8.55	5.70	1	1024×1024
CropAndWeed (Fine24) [58]	2023	8*	hand-held	-	RGB	1	X	16*	-	-	1	1920×1088
WeedsGalore (Ours)	2024	Maize	UAV	2.5	MSI	1	1	4	13.91	64.30	1	600×600

Table 1. Comparison of publicly available real-world agricultural datasets that provide pixel-level annotations for weed and crop segmentation. GSD refers to ground sampling distance. *Multi-class datasets (i.e. multiple weed and crop classes).

Target crop. [53, 64], [40] and [26] use UAV-based images for weed segmentation, but they are for sugarbeet, cotton and sorghum fields respectively. [58, 68] segment weeds in maize fields, but from images acquired by hand-held cameras. In this work, we present a system specifically tailored for UAV-based weed segmentation in maize fields.

Task formulation. The task is often formulated as a semantic or instance segmentation problem [2,6,45,54]. Given an input image, the model outputs a prediction (or a full weed map if the whole field is given as input [54]) indicating perpixel semantic classes or instance masks. While the former is more fitting for targeted spraying (as it concerns larger patches, and the species information is useful to decide on the herbicide), and the latter is well-suited for mechanical weeding (where individual plants are removed); it is possibly the most effective when both are used in combination. We provide a reference dataset with both semantic and instance annotations, which can be used separately or in combination based on the target task.

Model selection. Early work on weed segmentation heavily relies on classical machine learning methods with multistage pipelines and manual feature extraction [28, 30, 44]. Essentially, all recent approaches utilize state-of-the-art deep-learning models for weed and crop segmentation. Milioto et al. [45] propose an encoder-decoder architecture for pixel-wise segmentation of sugarbeet crops and weeds. [68] use an improved Swin-Unet, and [51] the PSPNet [69] (Pyramid Scene Parsing Network) for semantic segmentation of maize and weed. [61] and [54] deploy several CNNbased architectures on large-scale orthomosaics for wheat and sugar beet respectively. Weyler et al. [64] benchmark various methods like Mask R-CNN [32] and Mask2Former [9] for panoptic segmentation of sugarbeet and weed. Recently there has been efforts for domain generalized methods for crop and weed segmentation to perform well under different field conditions, however, those methods focus on generalizing to different fields of the same crop and same acquisition mode [24,63]. Our dataset can be used complementary with other existing datasets for cross-domain validation or improved generalization.

2.2. Weed Segmentation Datasets

One of the driving forces behind progress in computer vision has been the availability of annotated data. Unfortunately, the amount and diversity of agricultural datasets are limited compared to more general datasets [12, 42] due to several factors, like the complexity of scenes (e.g. complex illumination conditions, occlusion, overlap of plant organs) and the need for expert knowledge for annotations.

A comparison of existing datasets is provided in Tab. 1. [31] is an early carrot dataset that suffers from low ground resolution. CoFly-WeedDB [40] contains RGB images captured on a single day at a cotton field in Greece. It provides semantic masks only for the weeds, but not the crops. PhenoBench [64] is a UAV dataset, with pixel-level annotations for semantic and instance segmentation of sugarbeets and uni-class weeds. The average number of plants per image is low, indicating a lack of challenging scenes and weed infestations. In contrast, our WeedsGalore contains around 64 weeds per image, compared to 5 of PhenoBench. WeedMap [54] provides large-scale multispectral orthomosaics with semantic annotations for a uni-weed class and sugarbeet crops, but does not provide raw drone images. Furthermore, the ground resolution is low, limiting the annotation detail and the applicability potential of the dataset.

While less common, there have been recent datasets that differentiate multiple weed classess. WE3DS [38] is an RGB-D dataset, collected with UGV. It contains multiple crop and weed species. However, the field (near Vienna, Austria) is a controlled research farm, and high-weed density areas are left out of the dataset, which does not fully reflect the real-life farming scenario. CropAndWeed Dataset [58] is a collection of RGB images from over a hundred locations in Austria. The images are collected manually with a hand-held camera, which is not a suitable acquisition mode for automated systems in large-scale fields. Tab. 1 highlights the need for a UAV-based crop-weed segmentation dataset targeting maize fields, with challenging realworld scenes, which is addressed by our dataset.

2.3. Probabilistic Deep Learning and Uncertainty Quantification for Semantic Segmentation

The majority of the existing state-of-the-art models are deterministic. As a result, during test time, the model outputs a point estimate only. However, accurate uncertainty quantification (UQ) via e.g., prediction intervals has recently shown to be useful if not necessary to deploy vision algorithms in real-world automated systems [3, 21, 34, 55].

One approach to quantify model confidence is to rely on softmax scores. However, this is not always a reliable metric as uncertain models can output high softmax scores [23, 52]. An alternative is a Bayesian approach, assuming probability distributions over the network weights. Commonly, variational inference (VI) with Monte Carlo (MC) dropout [23] and Bernoulli distribution as the variational density is used to provide approximations to the true posterior distribution. As a non-Bayesian alternative, deep ensembles [41] have gained popularity, where the same model is trained multiple times with different initializations, and the different samples during inference are used to calculate predictive uncertainty. However, existing work for precision agriculture or autonomous weeding systems typically does not include uncertainty scores in their systems [6]. Exceptions include [59], who consider epistemic uncertainty within the acquisition function in an active learning setting; and [5], who report predictive uncertainty scores for semantic segmentation of crops and weeds on the Sugarbeets2016 [7] dataset. In this paper, we deploy a probabilistic method, which not only improves segmentation performance but also reports reliable uncertainty scores. We believe this information is vital to deploy perception algorithms in real-world robotic weeding systems.

3. The WeedsGalore Dataset

We provide a high-resolution UAV dataset for weed segmentation in maize fields. In comparison to existing datasets, we provide extra input bands through multispectral sensing, dense semantic and instance annotations, and offer by far the largest number of weed instances per image.

3.1. Data Collection

Field Description. The field is located in Marquardt, Potsdam, Germany ($52^{\circ}27'50.6''N 12^{\circ}57'27.5''E$) and covers an area of approximately $1840m^2$. To represent realistic agricultural scenarios, the farmers carried out the usual practices without experimental interference, and weeds occurred naturally. The maize (*Zea mays L.*) was planted across the entire field, on May 9, 2023. The distance between rows was 70 cm with a 20 cm intra-row distance between crops. Due to dry conditions, irrigation was applied on June 6. Herbicide treatment was done on June 12. Weeds were abundant in quantity as well as species diversity, the most dominant being common amaranth (*Amaranthus retroflexus*). Another species with a strong presence was a grass-like weed barnyard grass (*Echinochloa crusgall*), with quickweed (*Galinsoga parviflora*) being the least common. Apart from those three types of weed, there was a variety of other species in substantially fewer quantities. **Data Acquisition.** The dataset contains images from different dates, hence at different growth stages, plant cover, and wasthen eardiview.

and weather conditions. We carried out four data recording campaigns at dates May 25, May 30, June 6, and June 15. The first campaign was when the first leaves of maize crops appeared (i.e., V1 stage [67]) where there were almost no weeds present, while the last campaign had almost full plant cover (both from weeds and crops).

The images were taken with the DJI Phantom P4 Multispectral, a UAV equipped with five monochromic sensors for multispectral imaging (Blue: 450±16 nm, Green: 560±16 nm, Red: 650±16 nm, Red-Edge: 730±16 nm, Near-Infrared: 840±26 nm) with effective pixel of 2.08 MP as well as an RGB sensor [17]. The flights were planned with DJI GS Pro [16]. The UAV flew with an overlap of 70% side and 60% front overlap, and images were captured in Hover&Capture mode to ensure the highest possible resolution. The flight height was 5 meters to be able to distinguish individual plant instances, which resulted in a GSD (ground sampling distance) of 2.5mm. As a result, approximately 1150 images were taken by the campaign.

Instead of creating the orthomosaic and annotating the orthophotos, our dataset contains raw images captured by the drone. This has multiple reasons. Firstly, similar to what was reported by previous work [64], we have observed the alignment causes artifacts, and this level of artifacts would lead to errors in our fine-grained segmentation masks. Secondly, a model that is trained on raw images can be easily deployed in the future by spraying robot drones that work in real-time on the captured images, rather than relying on a multi-step orthorectification process. Hence, we followed these steps: First, the five single-band images were aligned (which corresponds to a translation of few pixels [18]). Second, the central 600x600 pixels (a square format that is flexible for processing, e.g. data augmentation) were cropped, which were finally annotated. There is no overlap between annotated images. They are sampled from 48 separate locations as shown in Fig. 3. Yet, to have a clear overview of the field, and to structure the annotation process, we created the orthomosaic for each campaign using the software Agisoft Metashape [1].

3.2. Data Annotation

To ensure the representation of different locations within the field, we divided the whole field into 12 patches with equal areas, and randomly sampled 4 geo-referenced point locations from each patch, resulting in 48 locations (see Fig. 3). 36 of them were annotated for the first three recording dates (which are before the herbicide treatment, hence more relevant for the weed identification task as the growth stages of weeds on June 15 is too late for herbicide application). The remaining 12 were annotated for all four dates (marked with darker polygons in Fig. 3), to also provide data for late-stage weeds, which can be used for either mechanical weeding or weed cover analysis. The total annotated ground area corresponds to approximately 128 m² (per date). Example scenes from four different dates are shown in Fig. 2.



Figure 2. Change in plant cover over the acquisition timeline. Examples from four different dates and semantic masks (maize, amaranth, barnyard grass, quickweed, weed other). Best viewed on a colored screen, and zoomed in.

The images were annotated using the web-based tool Encord [20]. We used the AI-assisted tool with SAM [37] point prompt option, where the model made the initial mask prediction based on the click, which the annotators then refined. Hence, a total of 156 images were annotated by two annotators and mutually reviewed by three experts to ensure a high quality of the dataset, where the object boundary of each plant instance was marked with a polygon (i.e. instance mask) which was also assigned to one of the semantic classes from *maize*, *amaranth*, *barnyard grass*, *quickweed*, or *weed other* (in the case of rarely grown species or when it was not possible to distinguish the class due to similar phenological appearance, especially during early growth stages).

3.3. Dataset Statistics

We spatially split the data as 70:15:15 (i.e. 8/2/2 patches), such that images from the same location do not appear in more than one split, even if the data was recorded at a different date. Fig. 3 shows the splits and corresponding locations in the orthomosaic, and the resulting dataset statistics can be seen from Tab. 2. In addition to the annotated single images, we include 4 large orthomosaics in our dataset, providing a large amount of unlabeled data, which can be utilized for further research (*e.g.* unsupervised learning, active learning, plant analysis, etc.) [11, 19, 59].



Figure 3. Ortohomosaic of the full field and georeferenced locations of annotated images. Points show captured image locations, while their colors encode acquisition dates. The dataset splits are spatially separated by patches into train, validation, and test. Smaller polygons are drawn around the annotated samples: The *multitemporal* dataset contains samples from the same locations from all dates. Best viewed on screen and zoomed in.

Split	#crops	#weed	#amaranth	#grass	#quickweed	#weed_other	#images
Train	1,461	6,512	2,618	1,813	161	1,920	104
Validation	451	1,808	857	258	57	636	26
Test	257	1,711	634	466	31	580	26
Total	2,169	10,031	4,109	2,537	249	3,136	156

Table 2. **Dataset statistics.** The number of plant instances for each class within the defined splits are reported.

4. Experiments

We provide extensive evaluation and provide baselines for our new dataset. Sec. 4.1.1 and Sec. 4.1.2 contain results for semantic and instance segmentation for different input data modalities. Sec. 4.2 presents UQ results on our dataset. Sec. 4.3 presents results on the generalization capabilities of models trained on our dataset, compared to existing ones.

4.1. Benchmarks

4.1.1 Semantic Segmentation

Implementation Details and Evaluation Metrics. The goal of semantic segmentation is to assign pixel-level class labels. We evaluate two settings: 3-class (i.e., background, crop, weed) and 6-class (i.e., multiple weed species). For each task, we provide baselines using two different established architectures: DeepLabv3+ [8], and MaskFormer [10]. To study the influence of additional imaging bands, we test 3-channel (RGB) and 5-channel (MSI) inputs. We report intersection-over-union (IoU) scores for each class, as well as mean IoU (mIoU) amongst all classes.

For both architectures, we start with a pre-trained ResNet50 [33] backbone, only changing the first convolu-

Method	Input	$IoU_{bg} \\$	IoU _{crop}	IoU _{weed}	mIoU
DeepLabv3+ [8]	RGB	97.97	67.93	72.08	79.33
	MSI	98.45	72.93	77.31	82.90
MaskFormer [10]	RGB	97.73	70.18	69.85	79.26
	MSI	97.99	69.49	73.33	80.27

Table 3. Semantic segmentation scores (%) for the 3-class setting (uni-weed) on our test set.

Method	Input	IoU _{bg}	IoU _{crop}	IoU _{am}	IoUgr	$\mathrm{IoU}_{\mathrm{qw}}$	$\mathrm{IoU}_{\mathrm{wo}}$	mIoU
DeepLabv3+ [8]	RGB	97.94	71.46	74.32	45.95	6.26	8.92	50.81
	MSI	98.37	73.03	76.17	53.55	21.11	10.86	55.52
MaskFormer [10]	RGB	97.46	68.28	68.15	41.66	4.92	3.28	47.29
	MSI	97.90	68.04	73.11	45.34	8.66	10.86	50.65

Table 4. Semantic segmentation scores (%) for the 6-class setting on our test set. Crop, am, gr, qw and wo correspond to *maize*, *amaranth*, *barnyard grass*, *quickweed* and *weed other* respectively.

tional layer to 5 input channels with random initialization for the MSI input. The models are trained with Adam optimizer [36], batch size of 8, and standard data augmentation (i.e. rotation, flipping, random jitter) is applied. The learning rate is set to 0.001 and 0.00003 for DeepLabv3+ and MaskFormer respectively, and training is done on an Nvidia A100 GPU and an Intel Xeon Ice Lake CPU with 32GB memory, where the final parameters are chosen based on the validation set.

Results. The results for the 3-class and 6-class variants can be seen from Tab. 3 and Tab. 4 respectively. The results show that both architectures achieve similar mIoU, with DeepLabv3+ having slightly higher scores. While the additional NIR and RE bands consistently improve performance, the effects are more pronounced for the more challenging 6-class case. An important observation is that the improvements are most significant for *quickweed* and *weed other*, which are the underrepresented classes. Hence, the results show that MSI can provide additional information where data is scarce. The class-wise improvements also differ between the two chosen architectures. The MSI boost is the highest for *amaranth* (the class with most samples) for MaskFormer, while it's more prominent for *barnyard grass and quickweed* for DeepLabv3+.

Confusion matrices for both cases are shown in Fig. 4 The results for 3-class setting show that 8% of crops are missed (i.e. predicted as background) while 13% are misclassified as weeds. However, for weeds, almost the entire misclassification comes from false negatives (i.e., weed classified as background), which is especially the case for very small (early growth-stage) weeds as it can be seen from qualitative results in Fig. 5. In the 6-class case, the lowest prediction performance is for *quickweed* and *weed other*. The latter is expected, as several weed species are pooled together in one class, and they are sometimes classified as



Figure 4. Normalized confusion matrices for semantic segmentation. Scores reported for MSI input and DeepLabv3+ model, and uni-weed (left) and multi-weed class cases (right).

Input	mAP	mAP ₅₀	mAP ₇₅
RGB	32.17	33.66	32.01
MSI	32.53	34.70	33.34

Table 5. Instance segmentation scores (%).

one of the other known three categories. *Quickweed* is classified as *amaranth* by 28%, which is a very high ratio. This could be explained by the phenotypes (visual appearances) of the two plants, which are both broad-leaf species with very similar appearances.

4.1.2 Instance Segmentation

Implementation Details and Evaluation Metrics. We use MaskFormer to provide baseline results for instance segmentation for a 3-class case and both input modalities. We train the model with the same configuration as in Sec. 4.1.1 and report mAP (mean average precision) scores, which is calculated for IoU thresholds in the range [0.5, 0.95] with a step size of 0.05. Moreover, we report mAP₅₀ and mAP₇₅ at 50% and 75% IoU respectively.

Results. The quantitative scores are reported in Tab. 5. The two input modalities yield similar results, with MSI being slightly better. The baseline scores for instance-segmentation are overall lower than for other weed segmentation datasets [64], which can be explained by the relatively large number of plant instances in our dataset (on average more than 78 plants per image), which makes the task challenging, especially for small weeds.

4.2. Uncertainty Quantification

Variational Inference with MC Dropout. To model uncertainty, we employ VI with MC dropout. It is a widely used UQ method, and has been shown to effectively quantify prediction uncertainty for semantic segmentation of crops and weeds [5]. We use predictive entropy as the uncertainty metric.

Input	Method	IoU _{crop}	$\mathrm{IoU}_{\mathrm{weed}}$	mIoU	$\downarrow \text{ECE}$
RGB	DLv3+ [8]	67.93	72.08	79.33	0.0058
	Prob. DLv3+	69.29	72.19	79.81	0.0041
MSI	DLv3+ [8]	72.93	77.31	82.90	0.0048
	Prob. DLv3+	73.90	76.51	82.94	0.0018

Table 6. Comparison of deterministic and probabilistic variants. Scores for 3-class semantic segmentation on our test set.

Implementation Details and Evaluation Metrics. We implement a probabilistic version of DeepLabv3+, by adding dropout layers with $p_d = 0.5$ between each of the four convolutional blocks of the ResNet50 backbone. During inference, p_d is kept at 0.5, and number of forward passes K=5.

We report IoU scores to compare performance with its deterministic counterpart. Moreover, we report the expected calibration error (ECE) [29], which is defined as:

$$\text{ECE} = \sum_{m=1}^{M} \frac{|B_m|}{n} |\operatorname{acc}(B_m) - \operatorname{conf}(B_m)|,$$

where acc and conf represent accuracy and confidence respectively, n is the total number of MC samples and B_m contains predictions that fall into the *m*th bin. For the deterministic case, the softmax scores are taken as confidence, whereas for the MC dropout version, we take the average over the *K* forward passes during test time.

Results. Tab. 6 shows segmentation scores for the 3-class case, for both 3-channel (RGB) and 5-channel (MSI) inputs. For both input modalities, the probabilistic model is significantly better calibrated and has consistently higher IoU scores. The improvement in calibration is the most pronounced for the MSI input, where ECE drops to less than half. Qualitative results including the predictions, as well as error and predictive uncertainty are shown in Fig. 5.

Uncertainty, quantified by predictive entropy, is present at the object borders, a common case in many domains due to annotation artifacts and expected noise (captured by aleatoric uncertainty) at the edges [27, 47, 48]. Moreover, noisy and underrepresented areas, such as the small lumps of soil or stones in the bottom example, have high uncertainty, which can be attributed to both epistemic (not many examples in training data) and aleatoric uncertainty (noisy shadows and varying reflectance values due to changing weather conditions). Most importantly, the results show a high correlation between the error and high uncertainty regions. This implies that the model is the most uncertain about pixels that it misclassified, which is a must-have to safely deploy algorithms in real-world applications.

4.3. Application to Unseen Data

This section quantitatively demonstrates the need for a reference dataset, designed specifically for weed monitor-

Figure 5. Qualitative results for probabilistic crop and weed segmentation for MSI input. The uncertainty is high in regions that are misclassified, which is a desired and useful information.

ing in maize fields using UAVs, and showcases the generalization potentials of WeedsGalore to unseen data. To this end, we introduce an additional test field named *Maize2024*. This OOD data includes recordings from a different field, year, plant cover, and unseen (i.e. later) growth stages. These are the domain shifts that we expect in our application. Maize2024, an agricultural area in Marquardt, Potsdam, Germany, is an experimental field where half of the field (12 out of 24 patches) are assigned as *control* areas (ie. no herbicide treatment) whereas the other half are *test* (ie. sprayed with herbicides). The data is collected with the same drone after the treatment had its effect on the field, which means that weeds were mostly eliminated in the sprayed (*test*) patches whereas *control* areas had full plant cover (i.e. complete weed infestation).

The experimental setup enables informative qualitative evaluation. A well-performing model is expected to predict almost full weed cover in *control* patches, and little in the sprayed *test* areas. For the task of 3-class semantic segmentation, we train DeepLabv3+ separately on the following datasets: WeedsGalore (ours), PhenoBench [64] (same acquisition mode, different crop), CropAndWeed [58] (includes maize along others, different acquisition mode), and another variant of CropAndWeed, which we refer to as *MaizeOrWeed*, a subset of CropAndWeed (1753 images), including only scenes with maize. Fig. 6 shows qualitative predictions on the large-scale orthomosaic of Maize2024 for models trained on WeedsGalore and MaizeOrWeed. The former clearly captures the high weed cover in *control* areas, while the latter completely fails to segment any vegetation.

To get quantitative scores, from the Maize2024 orthomosaic Fig. 6(a) we annotate 6 cropped patches corresponding to 90 m² ground area, each of size $1000 \times 1100 px$. Tab. 7 shows the scores for 3-class semantic segmentation. The model trained on WeedsGalore (our dataset) achieves 52.55% mIoU on OOD Maize2024 data, 23.22% higher than the runner-up, confirming the qualitative results. The scores confirm that the acquisition mode or crop type alone isn't sufficient to handle domain shifts, and datasets targeting UAV-based weed-maize monitoring are needed.

Figure 6. Weed cover monitoring on OOD data. (a) Full orthomosaic of Maize2024 field, where control areas (i.e. not sprayed) have full plant cover because the weeds took over. Semantic segmentation results (weed vs. crop) for when (b) trained on WeedsGalore and (c) trained on MaizeOrWeed. A sample patch with its predictions is shown zoomed in. Best viewed on colored screen and zoomed in.

Figure 7. **Predictions on Maize2024.** Left side of the image from *control*, and right from *test* area. Predictions from both deterministic and probabilistic models are captioned with mIoU scores. The uncertainty map (i.e. entropy) produced by the probabilistic model highlights the challenging areas.

We deploy the probabilistic variant of the model on Maize2024 to show the significance and potentials of probabilistic approaches on unseen data. As it can be seen from Tab. 7, the probabilistic variant yields a 15% boost in crop IoU. This increased segmentation performance is accompanied by improved model calibration and informative uncertainty scores. Fig. 7, which includes sample segments from both *control* and *test* areas, gualitatively demonstrates that the deterministic model tends to misclassify soil and plant shadows, and parts of maize leaves as weeds, while probabilistic variant handles those challenging areas better. A common failure case is when there is full weed coverage (i.e. control areas), where many crops are missed by the model. In those areas, the uncertainty is very high, which could be useful in a real-world scenario (e.g. even though the area is segmented as weed, the weeding system may de-

Model	Source	UAV	Maize	IoU _{bg}	IoUcrop	IoUweed	↑ mIoU	\downarrow ECF
DLv3+	PhenoBench	✓	×	56.94	30.80	0.25	29.33	0.4519
DLv3+	CropAndWeed	×	✓	51.59	0.00	7.02	19.54	0.413
DLv3+	MaizeOrWeed	×	✓	50.25	0.00	0.21	16.82	0.5154
DLv3+	WeedsGalore (Ours)	\	\	67.10	35.70	54.84	52.55	0.129
Prob. DLv3+	WeedsGalore (Ours)	\	\	68.65	50.37	57.32	58.78	0.088

Table 7. **Results on Maize2024 data.** IoU for 3-class semantic segmentation of DeepLabv3+ trained on different datasets, including the probabilistic variant for WeedsGalore.

cide *not spray* to not to risk potential crops as the uncertainty is very high).

5. Conclusion

We introduce a novel UAV dataset for crop and weed segmentation in maize fields. The dataset includes multitemporal images from different growth stages and five spectral bands, along with high-quality instance and semantic annotations. This reference data can inspire further research in aerial weed identification and monitoring. We present baseline results for semantic and instance segmentation tasks, including probabilistic methods to quantify uncertainty, improve model calibration, and demonstrate the approach's applicability for weed cover monitoring on OOD data. We believe that the increased availability of more datasets targeting different species and using various sensing technologies will enhance model development, aiding automated weeding and monitoring systems.

6. Acknowledgements

The authors acknowledge the support of the Helmholtz Einstein International Berlin Research School in Data Science (HEIBRiDS) and the GFZ Potsdam. This work utilized high-performance computing resources made possible by funding from the Ministry of Science, Research and Culture of the State of Brandenburg (MWFK) and are operated by the IT Services and Operations unit of the Helmholtz Centre Potsdam.

References

- Agisoft. Agisoft Metashape: Agisoft Metashape agisoft.com. https://www.agisoft.com/. [Accessed 15-07-2024]. 4
- [2] Alireza Ahmadi, Michael Halstead, and Chris McCool. Bonnbot-i: A precise weed management and crop monitoring platform. In *Proceedings of the IEEE/RSJ International*

Conference on Intelligent Robots and Systems (IROS), pages 9202–9209, 2022. 3

- [3] Victor Besnier, David Picard, and Alexandre Briot. Learning uncertainty for safety-oriented semantic segmentation in autonomous driving. In *Proceedings of the IEEE International Conference on Image Processing (ICIP)*, pages 3353–3357, 2021. 4
- [4] Ullalena Boström, Lars Eric Anderson, and Ann-Charlotte Wallenhammar. Seed distance in relation to row distance: Effect on grain yield and weed biomass in organically grown winter wheat, spring wheat and spring oats. *Field Crops Research*, 134:144–152, 2012. 2
- [5] Ekin Celikkan, Mohammadmehdi Saberioon, Martin Herold, and Nadja Klein. Semantic segmentation of crops and weeds with probabilistic modeling and uncertainty quantification. In *Proceedings of the IEEE/CVF International Conference* on Computer Vision (ICCV) Workshops, 2023. 4, 6
- [6] Julien Champ, Adan Mora-Fallas, Hervé Goëau, Erick Mata-Montero, Pierre Bonnet, and Alexis Joly. Instance segmentation for the fine detection of crop and weed plants by precision agricultural robots. *Applications in Plant Sciences*, 8(7):e11373, 2020. 2, 3, 4
- [7] Nived Chebrolu, Philipp Lottes, Alexander Schaefer, Wera Winterhalter, Wolfram Burgard, and Cyrill Stachniss. Agricultural robot dataset for plant classification, localization and mapping on sugar beet fields. *The International Journal of Robotics Research*, 36(10):1045–1052, 2017. 4
- [8] Liang-Chieh Chen, Yukun Zhu, George Papandreou, Florian Schroff, and Hartwig Adam. Encoder-decoder with atrous separable convolution for semantic image segmentation. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pages 801–818, 2018. 5, 6, 7
- [9] Bowen Cheng, Ishan Misra, Alexander G. Schwing, Alexander Kirillov, and Rohit Girdhar. Masked-attention mask transformer for universal image segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1290–1299, 2022. 3
- [10] Bowen Cheng, Alex Schwing, and Alexander Kirillov. Perpixel classification is not all you need for semantic segmentation. Advances in Neural Information Processing Systems (NeurIPS), 34:17864–17875, 2021. 5, 6
- [11] Yue Linn Chong, Jan Weyler, Philipp Lottes, Jens Behley, and Cyrill Stachniss. Unsupervised generation of labeled training images for crop-weed segmentation in new fields and on different robotic platforms. *IEEE Robotics and Automation Letters (RA-L)*, 8(8):5259–5266, 2023. 5
- [12] Marius Cordts, Mohamed Omran, Sebastian Ramos, Timo Rehfeld, Markus Enzweiler, Rodrigo Benenson, Uwe Franke, Stefan Roth, and Bernt Schiele. The cityscapes dataset for semantic urban scene understanding. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 3213–3223, 2016. 3
- [13] Pasquale De Vita, Salvatore Antonio Colecchia, Ivano Pecorella, and Sergio Saia. Reduced inter-row distance improves yield and competition against weeds in a semidwarf durum wheat variety. *European Journal of Agronomy*, 85:69–77, 2017. 2

- [14] Boyang Deng, Yuzhen Lu, and Jiajun Xu. Weed database development: An updated survey of public weed datasets and cross-season weed detection adaptation. *Ecological Informatics*, 81:102546, 2024. 2
- [15] Jizhong Deng, Zhaoji Zhong, Huasheng Huang, Yubin Lan, Yuxing Han, and Yali Zhang. Lightweight semantic segmentation network for real-time weed mapping using unmanned aerial vehicles. *Applied Sciences*, 10(20), 2020. 2
- [16] DJI. DJI GS Pro. https://www.dji.com/uk/ ground-station-pro. [Accessed 15-07-2024]. 4
- [17] DJI. P4 Multispectral Specs. https://www.dji.com/ uk/p4-multispectral/specs. [Accessed 15-07-2024]. 4
- [18] DJI. P4 Multispectral Image Processing Guide, 2020. Version: 20200717. 4
- [19] Alessandro dos Santos Ferreira, Daniel Matte Freitas, Gercina Gonçalves da Silva, Hemerson Pistori, and Marcelo Theophilo Folhes. Unsupervised deep learning and semi-automatic data labeling in weed discrimination. *Computers and Electronics in Agriculture*, 165:104963, 2019. 5
- [20] Encord. The Complete Data Development Platform for AI
 — Encord. https://encord.com/. [Accessed 15-072024]. 5
- [21] Kuai Fang, Daniel Kifer, Kathryn Lawson, and Chaopeng Shen. Evaluating the potential and challenges of an uncertainty quantification method for long short-term memory models for soil moisture predictions. *Water Resources Research*, 56(12), Dec. 2020. 4
- [22] FAO. Agricultural production statistics 2000–2022. Technical Report 79, Food and Agriculture Organization of the United Nations, Rome, 2023. 2
- [23] Yarin Gal and Zoubin Ghahramani. Dropout as a bayesian approximation: Representing model uncertainty in deep learning. In *Proceedings of the International Conference on Machine Learning (ICML)*, pages 1050–1059. PMLR, 2016.
- [24] Junfeng Gao, Wenzhi Liao, David Nuyttens, Peter Lootens, Wenxin Xue, Erik Alexandersson, and Jan Pieters. Crossdomain transfer learning for weed segmentation and mapping in precision farming using ground and uav images. *Expert Systems with Applications*, 246:122980, 2024. 3
- [25] Nikita Genze, Raymond Ajekwe, Zeynep Güreli, Florian Haselbeck, Michael Grieb, and Dominik G. Grimm. Deep learning-based early weed segmentation using motion blurred uav images of sorghum fields. *Computers and Electronics in Agriculture*, 202:107388, 2022. 2, 3
- [26] Nikita Genze, Maximilian Wirth, Christian Schreiner, Raymond Ajekwe, Michael Grieb, and Dominik G. Grimm. Improved weed segmentation in uav imagery of sorghum fields with a combined deblurring segmentation model. *Plant Methods*, 19(1), Aug. 2023. 3
- [27] Ethan Goan and Clinton Fookes. Uncertainty in real-time semantic segmentation on embedded systems. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR) Workshops, pages 4491–4501, June 2023. 7

- [28] J.M. Guerrero, G. Pajares, M. Montalvo, J. Romeo, and M. Guijarro. Support vector machines for crop/weeds identification in maize fields. *Expert Systems with Applications*, 39(12):11149–11155, 2012. 3
- [29] Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. On calibration of modern neural networks. In *Proceedings of the International Conference on Machine Learning (ICML)*, pages 1321–1330. PMLR, 2017. 7
- [30] Sebastian Haug, Andreas Michaels, Peter Biber, and Jörn Ostermann. Plant classification system for crop /weed discrimination without segmentation. In Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision (WACV), pages 1142–1149, 2014. 3
- [31] Sebastian Haug and Jörn Ostermann. A crop/weed field image dataset for the evaluation of computer vision based precision agriculture tasks. In *Computer Vision - ECCV 2014 Workshops*, pages 105–116, 2015. 3
- [32] Kaiming He, Georgia Gkioxari, Piotr Dollár, and Ross Girshick. Mask r-cnn. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 2961–2969, 2017. 3
- [33] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 770–778, 2016. 5
- [34] S. Hernández and Juan L. López. Uncertainty quantification for plant disease detection using bayesian deep learning. *Applied Soft Computing*, 96:106597, 2020. 4
- [35] J. L. E. Honrado, D. B. Solpico, C. M. Favila, E. Tongson, G. L. Tangonan, and N. J. C. Libatique. Uav imaging with low-cost multispectral imaging system for precision agriculture applications. In 2017 IEEE Global Humanitarian Technology Conference (GHTC), pages 1–7, 2017. 2
- [36] Diederik Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In International Conference on Learning Representations (ICLR), 2015. 6
- [37] Alexander Kirillov, Eric Mintun, Nikhila Ravi, Hanzi Mao, Chloe Rolland, Laura Gustafson, Tete Xiao, Spencer Whitehead, Alexander C Berg, Wan-Yen Lo, et al. Segment anything. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 4015–4026, 2023. 5
- [38] Florian Kitzler, Norbert Barta, Reinhard W. Neugschwandtner, Andreas Gronauer, and Viktoria Motsch. We3ds: An rgb-d image dataset for semantic segmentation in agriculture. *Sensors*, 23(5), 2023. 3
- [39] Angeliki Kousta, Christos Katsis, Anastasia Tsekoura, and Dimosthenis Chachalis. Effectiveness and selectivity of preand post-emergence herbicides for weed control in grain legumes. *Plants*, 13(2), 2024. 2
- [40] Marios Krestenitis, Emmanuel K. Raptis, Athanasios Ch. Kapoutsis, Konstantinos Ioannidis, Elias B. Kosmatopoulos, Stefanos Vrochidis, and Ioannis Kompatsiaris. Coflyweeddb: A uav image dataset for weed detection and species identification. *Data in Brief*, 45:108575, 2022. 3
- [41] Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty esti-

mation using deep ensembles. In Advances in Neural Information Processing Systems (NeurIPS), volume 30, 2017. 4

- [42] Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár, and C Lawrence Zitnick. Microsoft coco: Common objects in context. In Proceedings of the European Conference on Computer Vision (ECCV), pages 740–755, 2014. 3
- [43] Xu Liu, Steven W. Chen, Guilherme V. Nardari, Chao Qu, Fernando Cladera, Camillo J. Taylor, and Vijay Kumar. Challenges and opportunities for autonomous micro-uavs in precision agriculture. *IEEE Micro*, 42(1):61–68, 2022. 2
- [44] Philipp Lottes, Raghav Khanna, Johannes Pfeifer, Roland Siegwart, and Cyrill Stachniss. Uav-based crop and weed classification for smart farming. In *Proceedings of the IEEE International Conference on Robotics and Automation* (*ICRA*), pages 3024–3031, 2017. 3
- [45] Andres Milioto, Philipp Lottes, and Cyrill Stachniss. Realtime semantic segmentation of crop and weed for precision agriculture robots leveraging background knowledge in cnns. In *Proceedings of the IEEE International Conference on Robotics and Automation (ICRA)*, pages 2229–2235, 2018.
 2, 3
- [46] António Monteiro and Sérgio Santos. Sustainable approach to weed management: The role of precision weed management. *Agronomy*, 12(1), 2022. 1
- [47] Jishnu Mukhoti and Yarin Gal. Evaluating bayesian deep learning methods for semantic segmentation. arXiv preprint arXiv:1811.12709, 2019. 7
- [48] Jishnu Mukhoti, Andreas Kirsch, Joost van Amersfoort, Philip H.S. Torr, and Yarin Gal. Deep deterministic uncertainty: A new simple baseline. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 24384–24394, June 2023. 7
- [49] Raghav Patel, A. K. Jha, Badal Verma, Muskan Porwal, Oscar Toppo, and Sourabh Raghuwanshi. Performance of pinoxaden herbicide against complex weed flora in wheat (triticum aestivum l.). *International Journal of Environment* and Climate Change, 13(7):339–345, May 2023. 2
- [50] Mark A Peterson, Alberto Collavo, Ramiro Ovejero, Vinod Shivrain, and Michael J Walsh. The challenge of herbicide resistance around the world: a current summary. *Pest Man*agement Science, 74(10):2246–2259, 2018. 1
- [51] Artzai Picon, Miguel G. San-Emeterio, Arantza Bereciartua-Perez, Christian Klukas, Till Eggers, and Ramon Navarra-Mestre. Deep learning-based segmentation of multiple species of weeds and corn crop using synthetic and real image datasets. *Computers and Electronics in Agriculture*, 194:106719, 2022. 3
- [52] Janis Postels, Mattia Segù, Tao Sun, Luca Daniel Sieber, Luc Van Gool, Fisher Yu, and Federico Tombari. On the practicality of deterministic epistemic uncertainty. In *Proceedings of the International Conference on Machine Learning* (*ICML*), pages 17870–17909, 2022. 4
- [53] Inkyu Sa, Zetao Chen, Marija Popovic, Raghav Khanna, Frank Liebisch, Juan Nieto, and Roland Siegwart. weednet: Dense semantic weed classification using multispectral images and mav for smart farming. *IEEE Robotics and Automation Letters*, 3(1):588–595, Jan. 2018. 3

- [54] Inkyu Sa, Marija Popović, Raghav Khanna, Zetao Chen, Philipp Lottes, Frank Liebisch, Juan Nieto, Cyrill Stachniss, Achim Walter, and Roland Siegwart. Weedmap: A largescale semantic weed mapping framework using aerial multispectral imaging and deep neural network for precision farming. *Remote Sensing*, 10(9), 2018. 3
- [55] Abhinav Sagar. Uncertainty quantification using variational inference for biomedical image segmentation. In Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision (WACV) Workshops, pages 44–51, 2022. 4
- [56] Gaini Sairam, AK Jha, Badal Verma, Muskan Porwal, MP Sahu, and RK Meshram. Effect of pre and post-emergence herbicides on weed flora of maize. *International Journal of Plant & Soil Science*, 35(11):68–76, 2023. 2
- [57] Aurelio Scavo and Giovanni Mauromicale. Integrated weed management in herbaceous field crops. *Agronomy*, 10(4), 2020. 1
- [58] Daniel Steininger, Andreas Trondl, Gerardus Croonen, Julia Simon, and Verena Widhalm. The cropandweed dataset: A multi-modal learning approach for efficient crop and weed manipulation. In *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, pages 3729–3738, 2023. 2, 3, 7
- [59] Bart M van Marrewijk, Charbel Dandjinou, Dan Jeric Arcega Rustia, Nicolas Franco Gonzalez, Boubacar Diallo, Jérôme Dias, Paul Melki, and Pieter M Blok. Active learning for efficient annotation in precision agriculture: a usecase on crop-weed semantic segmentation. arXiv preprint arXiv:2404.02580, 2024. 4, 5
- [60] Aichen Wang, Yifei Xu, Xinhua Wei, and Bingbo Cui. Semantic segmentation of crop and weed using an encoderdecoder network and image enhancement method under uncontrolled outdoor illumination. *IEEE Access*, 8:81724– 81734, 2020. 2
- [61] Yuemin Wang, Thuan Ha, Kathryn Aldridge, Hema Duddu, Steve Shirtliffe, and Ian Stavness. Weed mapping with convolutional neural networks on high resolution whole-field images. In Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV) Workshops, pages 505– 514, 2023. 2, 3
- [62] James H. Westwood, Raghavan Charudattan, Stephen O. Duke, Steven A. Fennimore, Pam Marrone, David C. Slaughter, Clarence Swanton, and Richard Zollinger. Weed management in 2050: Perspectives on the future of weed science. *Weed Science*, 66(3):275–285, 2018. 1
- [63] Jan Weyler, Thomas Läbe, Federico Magistri, Jens Behley, and C. Stachniss. Towards domain generalization in crop and weed segmentation for precision farming robots. *IEEE Robotics and Automation Letters*, 8:3310–3317, 2023. 3
- [64] Jan Weyler, Federico Magistri, Elias Marks, Yue Linn Chong, Matteo Sodano, Gianmarco Roggiolani, Nived Chebrolu, Cyrill Stachniss, and Jens Behley. PhenoBench: A Large Dataset and Benchmarks for Semantic Image Interpretation in the Agricultural Domain . *IEEE Transactions* on Pattern Analysis & Machine Intelligence, 46(12):9583– 9594, 2024. 2, 3, 4, 6, 7
- [65] Franziska Wolff, Tiina H. M. Kolari, Miguel Villoslada, Teemu Tahvanainen, Pasi Korpelainen, Pedro A. P. Zamboni,

and Timo Kumpula. Rgb vs. multispectral imagery: Mapping aapa mire plant communities with uavs. *Ecological Indicators*, 148:110140, 2023. 2

- [66] Xiaolong Wu, Stéphanie Aravecchia, Philipp Lottes, Cyrill Stachniss, and Cédric Pradalier. Robotic weed control using automated weed and crop classification. *Journal of Field Robotics*, 37(2):322–340, 2020. 2
- [67] Yang Yue, Jin-Hai Li, Li-Feng Fan, Li-Li Zhang, Peng-Fei Zhao, Qiao Zhou, Nan Wang, Zhong-Yi Wang, Lan Huang, and Xue-Hui Dong. Prediction of maize growth stages based on deep learning. *Computers and electronics in agriculture*, 172:105351, 2020. 4
- [68] Jiaheng Zhang, Jinliang Gong, Yanfei Zhang, Kazi Mostafa, and Guangyao Yuan. Weed identification in maize fields based on improved swin-unet. *Agronomy*, 13(7), 2023. 3
- [69] Hengshuang Zhao, Jianping Shi, Xiaojuan Qi, Xiaogang Wang, and Jiaya Jia. Pyramid scene parsing network. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), pages 2881–2890, 2017. 3