# TALKPLAY: Multimodal Music Recommendation with Large Language Models

Seungheon Doh<sup>\*12</sup> Keunwoo Choi<sup>\*2</sup> Juhan Nam<sup>1</sup>

# Abstract

We present TALKPLAY, a multimodal music recommendation system that reformulates the recommendation task as large language model token generation. TALKPLAY represents music through an expanded token vocabulary that encodes multiple modalities - audio, lyrics, metadata, semantic tags, and playlist co-occurrence. Using these rich representations, the model learns to generate recommendations through next-token prediction on music recommendation conversations, that requires learning the associations natural language query and response, as well as music items. In other words, the formulation transforms music recommendation into a natural language understanding task, where the model's ability to predict conversation tokens directly optimizes query-item relevance. Our approach eliminates traditional recommendationdialogue pipeline complexity, enabling end-toend learning of query-aware music recommendations. In the experiment, TALKPLAY is successfully trained and outperforms baseline methods in various aspects, demonstrating strong context understanding as a conversational music recommender. A demo of the recommendation system is available at: https://talkpl-ai. github.io/talkplay-demo

# 1. Introduction

Recent advances in recommendation systems have focused on leveraging rich multimodal data and complex user-item interactions (Liu et al., 2024a). While neural architectures have shown success in modeling these aspects (Salau et al., 2022), the emergence of Large Language Models (LLMs) presents new opportunities for recommendation. Current LLM-based approaches typically use these models either as dialogue managers for natural language interaction (Liu et al., 2023c) or as feature extractors for multimodal understanding (Tian et al., 2024). However, these methods often require complex pipelines to bridge the semantic understanding of LLMs with structured recommendation logic.

We present TALKPLAY, a multimodal music recommendation system that reformulates the recommendation task as next token prediction. Unlike existing approaches that maintain separate modules for dialogue, retrieval, and ranking, TALKPLAY unifies these components through a novel multimodal music tokenization and vocabulary expansion. By representing music items as sequences of tokens encoding audio features, lyrics, metadata, tags, and playlist co-occurrence, our system learns to recommend directly through next-token prediction on music discovery conversations. This formulation eliminates the need for separate recommendation logic while preserving the benefits of both content-based and collaborative filtering approaches.

The LLM and token prediction framework provides several fundamental advantages. First, it enables end-to-end learning of query-aware recommendations without requiring explicit dialogue management or retrieval mechanisms. Second, its causal nature naturally models sequential patterns in music discovery, similar to session-based approaches but with richer semantic context. Third, TALKPLAY inherits broad semantic understanding from pre-trained LLM weights, which likely contain rich knowledge about musical concepts like artist names, genres, and cultural contexts. Most significantly, the large capacity of the LLM architecture enables the model to effectively utilize this knowledge alongside all available signals - user preferences, contextual queries, and interaction patterns - for generating recommendations. This integration of multiple information sources through a text-based interface eliminates the need for modality-specific architectures while maintaining interpretability - a key advantage over traditional recommendation systems that require separate components for query understanding, preference modeling, and item retrieval.

# 2. Related Works in Recommendation Systems

Language Models : Recent progress in language models has led to significant interest in reformulating recommendation tasks as language modeling. Early approaches

<sup>\*</sup>Equal contribution <sup>1</sup>KAIST, South Korea <sup>2</sup>talkpl.ai, New York, USA. Correspondence to: SeungHeon Doh <seungheon-doh@kaist.ac.kr>, Juhan Nam <juhan.nam@kaist.ac.kr>.

Proceedings of the 41<sup>st</sup> International Conference on Machine Learning, Vancouver, Canada. PMLR 267, 2025. Copyright 2025 by the author(s).

such as BERT4Rec (Sun et al., 2019) and Transformers4Rec (de Souza Pereira Moreira et al., 2021) adapted transformer architectures for sequential recommendation, primarily focusing on modeling user behavior sequences through masked token prediction. These works demonstrated the potential of transformer-based architectures in capturing complex sequential patterns but were limited to behavioral data without leveraging rich semantic information.

More recent approaches have explored using foundation models for end-to-end recommendation. Text2Tracks (Palumbo et al., 2022) investigates generative track retrieval, directly generating music item IDs from natural language queries. This eliminates the need for explicit retrieval mechanisms but faces challenges in maintaining recommendation quality across large item catalogs. MMREC (Tian et al., 2024) extends this concept to multiple modalities, demonstrating how LLMs can jointly process different types of item features. However, these approaches still maintain separate modules for dialogue management and recommendation logic.

**Conversational Retrieval**: Traditional conversational recommendation systems employ separate modules for dialogue management and recommendation (Zhang et al., 2018; Chen et al., 2019), requiring complex pipelines to coordinate user interaction and item retrieval. Recent approaches such as UniCRS (Wang et al., 2022) and ReFICR (Yang & Chen, 2024) leverage LLMs towards unifying these components, but their systems still require separate training stages for different modules.

In the music domain, conversational recommendation is particularly effective due to the rapid feedback cycle of music consumption - users can instantly experience and provide feedback on recommended items, unlike domains such as movies or products that require longer engagement periods. While recent work has explored knowledgeenhanced architectures (Zhang et al., 2021) and multimodal approaches (Liu et al., 2023a), these systems still maintain separate modules for dialogue understanding and recommendation generation. Our work addresses these limitations by directly optimizing query-item relevance through next-token prediction, enabling seamless integration of user preferences, contextual queries, and domain knowledge.

**Multimodality in Music**: In the music domain, multimodality has been actively studied in the form of content-based music understanding (Gardner et al., 2023; Liu et al., 2023b) and generation tasks (Tal et al., 2024). For retrieval, multimodal approaches have primarily been used to address the cold-start problem (Van den Oord et al., 2013; Oramas et al., 2017). However, most works were limited to combining only a single modality such as audio or text. Multimodal recommendation systems have been actively studied in other domains. For example, CCF-LLM (Liu et al., 2024b) and CMBF (Chen et al., 2021) propose crossmodal fusion techniques to jointly learn from interaction patterns and content features, while fMRLRec (Lai et al., 2024) introduces hierarchical representations to capture information at different granularities. However, these methods still require careful design of modality-specific architectures and fusion mechanisms.

Rather than designing explicit fusion mechanisms, our work builds upon advances in both LLM-based and conversational approaches by representing different modalities through a unified token architecture. This approach allows the model to learn cross-modal relationships directly through self-attention, inheriting the semantic understanding capabilities of pre-trained LLM weights. By encoding audio features, lyrics, metadata, and playlist co-occurrences as token sequences, TALKPLAY eliminates the need for separate modality-specific architectures while maintaining interpretability - a key advantage over traditional multimodal fusion approaches.

# 3. Data

This section introduces the data generation process of TALK-PLAY. It is prohibitively difficult to perform research on recommendation without access to real-world data – information about items, users, and their interactions. Another challenge lies in the fact that the conversational recommendation system is in its early stage and so the publicly available dataset is scarce. The Conversational Playlist Curation Dataset (CPCD) is probably the most relevant one, but it comes with 917 conversations which are not sufficient to train a large model (Chaganty et al., 2023).

Inspired by recent works such as (Leszczynski et al., 2023; Doh et al., 2024), we generate the training data using a music playlist dataset and an LLM. In our primary reference (Doh et al., 2024), (1) each conversation is generated as a journey of machine-assisted music discovery; (2) each turn is generated as following: i) user's turn is stochastically chosen based on a user intention taxonomy, and ii) machine continues to react by choosing music items satisfying user's request. A notable difference is that in TALKPLAY, the base dataset is not simply a music dataset (e.g., (Bertin-Mahieux et al., 2011)) but a playlist dataset, in order to simulate more plausible and coherent conversation and recommendation.

#### 3.1. Base Dataset: Million Playlist Dataset

In the current era of music streaming, playlists are playing a crucial role in the music listening experience. They also provide unique and direct information about music items: which music items go along together well, according to the

Dataset	Training	Evaluation
Miliion Playlist Dataset		
# of Playlists	999,000	1,000
# of Average Tracklist	63.73	59.41
# of Warm Start Tracks	1,714,772	37,114
# of Cold Start Tracks	-	2,357
# of Vocab	24,129	713
Sparsity	0.99996	0.99850
TalkPlay Dataset		
# of Playlist	116,136	1,000
# of Dialogue	532,627	1,000
# of Tracks	406,768	11,022
# of Vocab	318,281	19,796
Avg. # of turns	7.03	13.31
Avg. query len.	17.62	15.35
Avg. reponse len.	17.91	14.92

Table 1. Statistics of the base dataset and TalkPlay dataset.

real listeners. They may suit well for the purpose of training TALKPLAY as well, as a base dataset, since conversation consisting of tracks in the same playlist would be more diverse, coherent, and hence realistic than other hypothetical strategies such as random sampling or any other heuristics.

Among the available playlist datasets, the Million Playlist Dataset (MPD) is chosen as our base dataset (Chen et al., 2018). Since being introduced in 2018, this dataset remains one of the largest playlist datasets available to the public by including one million Spotify playlists. The MPD provides track metadata and playlist co-occurrence and is extended with audio content, lyrics, and semantic annotations. The audio content are successfully crawled through the Spotify API for 1,717,148 items. The lyrics are extracted using WHISPER-LARGE-V3 (Radford et al., 2023), a well-known speech transcription model that performs decent lyrics transcription. For semantic annotations, we leverage a pretrained music captioning model, LP-MUSICCAPS (Doh et al., 2023), that incorporates information about genres, moods, instruments, and vocal styles.

### 3.2. TalkPlay Dataset

We use an LLM and the base dataset (MPD) to generate TalkPlay Dataset, a music conversation dataset with natural language and music recommendation.<sup>1</sup> These are the key design principles and choices to ensure the synthetic data can be used for the training of TALKPLAY.

**Coherence**: Given a user query or reaction, the system should respond with music recommendation and relevant dialogue.

Modality Coverage: Conversations span all target modal-

ities (audio, lyrics, metadata, and semantic tags) except playlist co-occurrence. We exclude the latter because: i) these implicit modality is difficult to verbalize, and ii) in our task setup, playlist co-occurrence would be inherently captured (Section 4.1).

**User Simulation**: Users may skip or reject recommended tracks, even if the track sequence is based on existing playlists. Our synthetic conversation reflects this by allowing users to request alternative recommendations.

**Text Format**: For the outcome of this generation (synthesized conversation), a structured format is preferred, in order to use the synthetic conversation for our training (i.e., music tokenization in Section 4.1). The JSON format is chosen and used as presented in Section A.2

Based on this, GEMINI-1.5-FLASH-002 (Team et al., 2024) is used to create music conversation given a prompt that includes i) our goal and the aforementioned conditions, ii) track identifiers and their metadata, semantic tags, lyrics. The prompt is included in Section A.1. Table 1 compares our dataset with the base dataset. Using 116k playlists with an average of 7 tracks each, our synthesis approach yields 552k multi-turn music recommendation dialogues. By leveraging rich textual annotations of music sequences, our LLM-based data synthesis technique significantly expands the text-music associations beyond just playlist titles, increasing the token count from 24k to 318k.

Each user-assistant interaction in our synthetic conversation dataset follows a triplet structure: {USER QUERY, REC-OMMENDED MUSIC, ASSISTANT RESPONSE}. The user query and assistant response are natural language expressions, while the recommended music is represented by a unique track identifier. During training, both the assistant response and the recommended music are used as labels. This structured format resembles the typical task or chat templates.

#### 3.3. Dataset Split

To reflect the real-world recommendation scenarios, we perform a chronological data split based on the playlist creation date. The test set is created by randomly sampling 1,000 playlists from the last creation date (2017-11-01), and training set include all the rest of the tracks. Through this split, around 2,357 tracks in the test split are cold-start items, tracks that only appear in the test set. Assuming a real-world scenario, these items represent newly released songs, which traditional collaborative filtering algorithms has no information to make recommendation from. In contrast, being multimodal, TALKPLAY is able to handle these items by understanding content such as audio, lyrics, metadata and semantic features.

<sup>&</sup>lt;sup>1</sup>We will release the dataset to the public after the review period.



Figure 1. Overview of TALKPLAY: (1) The multimodal music tokenizer converts source data into modality embeddings v and quantizes them into codebook indices c, which are mapped to music tokens i. (2) The LLM is fine-tuned on text and music token sequences. (3) The generated music tokens are mapped back to codebook indices and are used as queries to retrieve music items from the database.

# 4. TALKPLAY: The Proposed System

As illustrated in Figure 1, TALKPLAY consists of two parts – a music tokenizer and a model. The music tokenizer encodes multimodal music embeddings into tokens. A single music item is represented by multiple tokens, each of which represents a different modality. The model is a usual LLM that is presumably: i) capable of modeling music recommendation conversations (with text and music tokens), and ii) trained with a large amount of data including musical corpus for faster training and generalization.

#### 4.1. Music Tokenizer

The music tokenizer in TALKPLAY is designed under following goals and constraints. First, to retrieve and recommend items, the model needs to be connected to the database. Second, to easily utilize LLM as a recommendation engine, the items in the database need to be discretized as tokens. Third, the embeddings of those item tokens need to be trained well, requiring some minimum token occurrence in the training data. Given these conditions, we propose the following scheme for music tokenization in TALKPLAY. A music item  $x_i$  (*i* is an item index) may have rich information including (1) playlist co-occurrence, (2) semantic tag information, (3) metadata, (4) lyrics, and (5) audio.

Item Embeddings: For all the data modalities, pretrained models are used to extract item embedding  $v_i^m$ , where mstands for a modality index (1-5 for playlist co-occurrence, semantic tag, metadata, lyrics, and audio, respectively.) For playlist co-occurrence, a word2vec-style (Barkan & Koenigstein, 2016) item embedding model is trained using the training dataset ( $v_i^1 \in \mathbb{R}^{128}$ ). For semantic information, metadata, and lyrics, NV-Embed-v2 (Lee et al., 2024) is chosen as its state-of-the-art performance in various taxt embedding benchmarks (Muennighoff et al., 2022) ( $v_i^2, v_i^3, v_i^4 \in \mathbb{R}^{4096}$ ). For audio, the MusicFM (Won et al., 2024) model is chosen for its strong performance in many music informatics tasks  $(v_i^5 \in \mathbb{R}^{1024})$ .

**Quantization**: Due to the long-tail nature of music consumption and the limited size of available training data, all the item embeddings  $v_i^m$  are vector-quantized into Kclusters (per modality) using K-means clustering. Here,  $c_k^m$  represents a cluster centroid. In this paper, we chose K = 1024.

As a result, the overall music database is represented by  $K \times M$  indices, where the total number of modalities M is 5. However, this does not mean that all music items are reduced to  $1024 \times 5 = 5120$  unique clusters. A music item is represented by 5 modality tokens, where each modality embedding has 1024 clusters. Theoretically, the proposed music tokenization scheme is capable of representing  $1024^5$  = about 1,126 trillion unique music items.

Token Mapping: In this final step of tokenization step, the multimodal cluster indices of each music item is used in our token format: <|modality-index|>. For example, a music item whose embeddings are mapped to 29th audio cluster, 2nd metadata cluster, 98th lyrics cluster, 3th semantic cluster, and 59th user-item cluster is converted to <|playlist-59|><|semantic-361|> <|metadata-7|><|lyrics-98|><|audio-29|>.

This token mapping is simple and intuitive, but there is a caveat. Although powerful models are used to compute item embeddings, its rich semantic information is simplified by the cluster indices, i.e., every detailed information of the inter-cluster relationship is lost. This will be addressed in Section 5.1 with the introduction of a self-similarity loss.

#### 4.2. LLM: The Recommender

The LLM, our recommendation engine, is based on a pretrained open-source model. We opt for instruction finetuned model to utilize the conversationability as our goal is to build a conversational music recommender. To better understand the cultural background of various genres and languages, a multi-lingual model is preferred. At the same time, our task is highly specific compared to the scope of usual LLM training, leaving room for optimization. Altogether, Llama-3.2-1B-Instruct is chosen for our base model (Dubey et al., 2024).

To enhance the LLM's understanding of multimodal music information, we expand its vocabulary to include multimodal music tokens (Zhao et al., 2024). In detail, the vocabulary size of the base model is expanded by  $1024 \times 5 = 5120$ , to include the multimodal music tokens. Two more special tokens, <start\_of\_music> and <end\_of\_music>, are added as well, since they are used to wrap music tokens in the training data. This modification means 5122 new embeddings ( $e_k^m$  and two special token embeddings) to the model, each of which is 2048-dim in the Llama-3.2-1B model. Equivalently, it adds about 10.5M parameters to the model, increasing the model size by less than 1%. With this vocabulary expansion, the synthetic conversation (as in Section A.2), represented with the multimodal music tokens (as in Section A.3), is tokenized and fed to the model. This expansion allows the model to directly understand and generate multimodal music tokens along with regular text tokens during conversations.

#### 4.3. Training

The training of TALKPLAY is similar to the typical LLM supervised finetuning, using the cross-entropy loss  $\mathcal{L}_{conv}$  and the causal attention. The synthetic conversational data (Section 3.2) is fed into the model, after replacing the track identifies with the corresponding multimodal music tokens. The primary objective of this training process is to learn the newly introduced multimodal music token embeddings  $e_k^m$  by leveraging contextual information from preceding conversations and music token embeddings e are initialized with the mean and covariance of the existing embeddings (Hewitt, 2021). As a result, the model learns to make music recommendation by generating multimodal music tokens, as well as appropriate natural language responses.

In addition to the synthetic conversation dataset, we incorporate playlist continuation data as an next-token prediction task also trained on the cross-entropy loss,  $\mathcal{L}_{playlist}$ . This can be seen as a pretraining task on a music token corpus, providing supervision for learning both intra-track and intertrack relationships. The intra-track relationships are learned through the connections between the five multimodal music tokens representing each track, while the inter-track relationships are captured through playlist co-occurrence patterns. We split the given playlist dataset into two versions based on random select offsets, where the task is to predict the next track sequence given a track sequence.

The final cross-entropy loss  $\mathcal{L}_{CE}$  consists of two components: conversation loss  $\mathcal{L}_{conversation}$  and playlist continuation loss  $\mathcal{L}_{playlist}$ , which are jointly optimized as:

$$\mathcal{L}_{\rm CE} = \mathcal{L}_{\rm conversation} + \mathcal{L}_{\rm playlist} \tag{1}$$

where  $\mathcal{L}_{conversation}$  is computed from the synthetic conversation dataset and  $\mathcal{L}_{playlist}$  from the playlist continuation task. Both losses are standard cross-entropy losses for next-token prediction.

While the cross-entropy loss with vocabulary expansion successfully integrates multimodal tokens into the LLM, the newly added token embeddings lose the semantic relationships present in the original modality embeddings. This is because the added music token embedding e is randomly

initialized, although it is necessary since the semantic space of the base LLM embeddings are completely irrelevant to the semantics of c. To address it, a self-similarity loss is adopted as in Eq. (2). By measuring the self-similarity of the token embedding e and the cluster centroids c, during training, the token embedding is optimized for not only the music recommendation but also the information restoration.

$$\mathcal{L}_{\text{self-sim}} = \mathbb{E}_{i,j} |S(\hat{c}_i, \hat{c}_j) - S(\hat{e}_i, \hat{e}_j)|$$
(2)

where  $\hat{c}_i = \frac{c_i}{\|c_i\|_2}, \hat{c}_j = \frac{c_j}{\|c_j\|_2}$  are L2-normalized centroids,  $\hat{e}_i = \frac{e_i}{\|e_i\|_2}, \hat{e}_j = \frac{e_j}{\|e_j\|_2}$  are L2-normalized token embeddings, and  $S(x, y) = x^T y$  is dot product between normalized vectors. The total loss combines the cross-entropy loss for language modeling with the self-similarity loss,  $\mathcal{L}_{\text{total}} = \mathcal{L}_{\text{CE}} + \lambda \mathcal{L}_{\text{self-sim}}$ , where  $\lambda = 0.1$  to balance between the tasks.

#### 4.4. Inference: Recommendation by Generation

During inference, we use standard LLM generation parameters (temperature=1.0, top-p=0.9, repetition penalty=1.0) to generate multimodal music tokens. These tokens are generated before the assistant's response message to ensure recommendations are based solely on the query, avoiding potential popularity biases that could arise from conditioning on generated text (He et al., 2023).

The generated tokens must then be mapped back to music items through a reverse lookup of the tokenization process described in Section 4.1. As our clustering creates a many-to-one mapping, this process is stochastic, similar to approximate nearest neighbor searches used in industry recommenders (Bernhardsson & contributors, 2013–2025).

Given a sequence of five multimodal tokens representing a recommendation, we select items matching the token indices across modalities. However, due to the vast token space (1,126 trillion combinations) relative to our dataset size, exact matches are often unavailable. In such cases, we fall back to partial matching using weighted feature importance, with quadratically decreasing weights (25,16,9,4,1) assigned to playlist, tags, metadata, lyrics, and audio features respectively. The system iteratively searches for matches using token combinations prioritized by cumulative importance, ensuring recommendations preserve the most critical signals, particularly playlist co-occurrence patterns.

### 5. Experiment

In this section, we present the experiment results focusing on the training. Evaluation on the recommendation of TALKPLAY is discussed in Section 6. Using the synthetic conversation dataset (Section 3), TALKPLAY, a vocabularyexpanded Llama-3.2-1B model is trained with a 1024-token context length, a learning rate of 1e - 4, and the AdamW



*Figure 2.* Training curves showing cross-entropy loss (top) and similarity loss (bottom). The similarity loss is identical across splits because it is computed on the token embedding, independently from any conversation data.

optimizer (Loshchilov, 2017). The model reported in this paper is trained on 8 GPUs with a total batch size of 48 items (or 49,152 tokens). The model is trained over 2.3M steps, and the one with the lowest validation loss at step 2.1M is selected as the best checkpoint for evaluation.

#### 5.1. Training Stability and Self-Similarity Loss

Although the token count in a single batch (49,152) is smaller than typical LLM pretraining (E.g., 2 million tokens in Llama 3 (Dubey et al., 2024)), the training was stable. We hypothesize this due to two reasons: First, for the existing text tokens, the finetuning stages usually do not require a large batch size; Second, for the multimodal music tokens, the self-similarity loss works a regularizer and stablizes the training.

The regularization effect of the self-similarity loss is illustrated in Figure 2 (top). The model trained with selfsimilarity loss exhibits a consistent and small gap between validation and training cross-entropy losses, with both losses decreasing steadily over time. In contrast, without the selfsimilarity loss, the training loss rapidly decreases while the validation loss reaches its minimum within 25k steps, after which it keeps increasing, indicating overfitting.

The self-similarity loss curves in Figure 2 (bottom) provide additional evidence. In the model without self-similarity loss, this metric consistently increases as overfitting occurs. This demonstrates that not only does a low self-similarity loss lead to low cross-entropy loss, but the inverse relationship also holds, empirically showing their close connection.

### 5.2. Token Matching Analysis

The effectiveness of TALKPLAY's token representation can be evaluated through the analysis of token matching patterns

TalkPlay: Multimodal Music Recommendation with LLMs

Model	Retrieval Methods	$\mathrm{MRR}\uparrow$	Hit@1↑	Hit@10↑	Hit@100 ↑
BM25 (Robertson & Walker, 1999)	TF-IDF Scoring	0.005	0.001	0.009	0.037
CLAP (Wu et al., 2023)	Similarity-based	0.000	0.000	0.000	0.003
NV-Embeds (Lee et al., 2024)	Similarity-based	0.020	0.007	0.042	0.133
TALKPLAY (Ours)	Generative	0.023	0.014	0.036	0.142

Table 2. Comparison of conversational recommendation performance across different models. MRR indicates the mean reciprocal rank and Hit@K measures proportion of relevant items in top-K results. Higher is better for all metrics.

during inference. Given the vast combinatorial space of possible token sequences (1,126 trillion unique combinations) and a test set of only 39,471 tracks, random matching would yield practically zero matches. However, our analysis of 13,012 conversation turns reveals that 49.7% of generated token sequences successfully match to existing items, indicating that the model has learned meaningful associations between multimodal tokens.

This non-random matching behavior demonstrates that TALKPLAY has effectively captured the intrinsic relationships between different modalities of music items. More specifically, the model has learned valid combinations of collaborative filtering patterns, audio characteristics, metadata, lyrics, and content attributes that correspond to real music items.

Further analysis reveals interesting patterns in warm (seen during training) versus cold (unseen) items. While warm items constitute the majority of matches (93.6%), this is primarily due to the imbalanced distribution in the test set (37,114 warm vs 2,357 cold items). When normalized by their respective test set sizes, warm and cold items show comparable matching rates - 16.5% for warm items and 14.5% for cold items. This near-equal utilization suggests two important properties of our model: (1) it successfully learns meaningful multimodal patterns from the training data, and (2) this understanding generalizes to unseen items, indicating that the model has captured fundamental relationships between modalities rather than merely memorizing training examples.

The substantial proportion of zero-match cases (50.3%) can be attributed to the extreme sparsity of our test set relative to the possible token space. This suggests that expanding the size of the music catalog would likely improve the raw matching rate without compromising the model's demonstrated ability to generate valid multimodal token sequences.

# 6. Conversational Recommendation

### **6.1. Evaluation Metrics**

We evaluate our model's conversational recommendation capabilities along two key dimensions: (1) the ability to retrieve relevant music given multi-turn dialogue context, and (2) the ability to generate contextually appropriate responses. For the retrieval evaluation, we employ standard ranking metrics - Mean Reciprocal Rank (MRR) and Hit Rate at K (Hit@K) with  $K = \{1, 10, 100\}$ . MRR measures the average reciprocal of the rank at which the first relevant item appears, while Hit@K indicates whether a relevant item appears in the top-K retrieved results. We evaluate retrieval performance for each turn using 1,000 multi-turn conversations derived from 1,000 playlists in Table 1.

# 6.2. Baseline Models

We evaluate our model against three baseline approaches: BM25 (Robertson & Walker, 1999) for classical text-based sparse retrieval, NV-Embeds-V2 (Lee et al., 2024) for deep similarity retrieval with LLM embeddings, and CLAP (Wu et al., 2023) for multimodal audio-text retrieval. See Appendix A.4 for more details.

### 6.3. Multi-turn Music Retrieval Results

Table 2 presents the multi-turn music retrieval performance across different models. The LLM embedding-based NV-Embeds-V2 (Lee et al., 2024) significantly outperforms the traditional sparse retrieval approach BM25 (Robertson & Walker, 1999) while operating in the same text modality. Despite its strong performance on audio-text alignment tasks (Wu et al., 2023), CLAP exhibits near-zero performance in multi-turn retrieval scenarios, indicating limitations in processing user metadata such as track and artist names compared to its content-based training on genre and instrument information.

Our generative retrieval approach TALKPLAY demonstrates superior performance across almost all metrics compared to baseline methods. Most notably, it achieves nearly double the Hit@1 score compared to the embedding similaritybased NV-Embeds-V2 (Lee et al., 2024). This precisionseeking behavior is aligned with the training objective, as the next-token prediction with cross-entropy encourages the single true class while discouraging all the rest. The relatively low Hit@10 may be due to our inference strategy when there is no exact match. Dropping each modality, as we do in such a case, is an approximate nearest neighbor method, and using it at k=10 seems to be somewhat noisy in our test setup. The Hit@100 performance further validates

TalkPlay	Multimodal	Music	Recommendation	with	LLMs
----------	------------	-------	----------------	------	------

Turn	Types	Contents		
Chat History (Input Condition)				
1	Query	I am looking for a mix of songs for a road trip playlist folk, indie pop, and mellow tracks.		
1	Music	"Just A Game" by "Birdy" (Last.fm Tag: indie, folk, alternative, piano)		
1	Response	Let's start with a beautiful indie folk song with some haunting vocals		
2	Query	That was lovely and melancholic, now something a little more upbeat and folk-inspired, perhaps?		
Ground Truth				
2	Music	"Tomorrow Will Be Kinder" by "The Hunger Games Soundtrack" (Last.fm Tag: folk, soundtrack)		
2	Response	How about this folk-pop track with a brighter, more energetic feel?		
TALKPLAY Generataed Output				
2	Music	"Let Her Go" by "Passenger" (Last.fm Tag: folk, acoustic, 2021)		
2	Response	Here's a song with a more uplifting folk sound.		

Table 3. Example multi-turn music recommendation dialogue demonstrating the model's ability to adapt recommendations based on evolving user preferences, transitioning from initial folk, indie pop, and mellow criteria to subsequent upbeat and folk-inspired requests.



*Figure 3.* Performance comparison across conversation turns. The x-axis shows the turn number in the dialogue, and the y-axis shows Mean Reciprocal Rank (MRR).

that our approach not only excels at top-1 prediction but also learns meaningful relevance rankings across a broader recommendation set.

Figure 3 shows how retrieval performance varies across conversation turns. The MRR scores demonstrate that TALK-PLAY maintains relatively stable performance even as the conversation context grows longer, while baseline methods show rather degradation in later turns. This demonstrates the superior context understanding capabilities of the proposed LLM-based token prediction model. While similarity-based methods merely aggregate previous chat history for dot product, our generative retrieval approach leverages the model's internal attention mechanism during item decoding to naturally aggregate contextual information.

#### 6.4. Qualitative Results

Table 3 illustrates an example of multi-turn music recommendation. The first row shows the multi-turn queries that serve as conditions for the LLM, the second row presents the ground truth from our synthetic dataset, and the final row displays the LLM-generated output response and top-1 recommended music. Through this qualitative example, we can observe that our LLM demonstrates the ability to understand user queries at each turn and retrieve increasingly specific music recommendations that adapt to evolving user needs.

In the initial turn, the user specifies preferences for a "road trip" playlist with "folk, indie pop, and mellow" characteristics. The model's recommendation aligns with these criteria by suggesting a track with indie folk and mellow attributes. When the user subsequently requests a shift toward "more upbeat and folk-inspired" music, the model demonstrates contextual understanding by adapting its recommendation – maintaining the folk element while transitioning to a more energetic selection, evidenced by both the retrieved track and the generated descriptive response.

### 7. Conclusion

We presented TALKPLAY, demonstrating that music recommendation can be effectively reformulated as token generation within an LLM framework. Our key contributions multimodal tokenization, self-similarity loss, and unified conversational recommendation model - enable stable training and competitive performance while significantly reducing system complexity. The empirical results show that this approach maintains recommendation quality across different modalities while eliminating the need for separate dialogue management and retrieval modules. Future work could explore scaling to larger datasets, incorporating additional modalities, and leveraging unique LLM capabilities like chain-of-thought reasoning and zero-shot scenarios. As one of the first unified recommendation systems within the LLM framework, TALKPLAY demonstrates the potential for simpler yet more capable architectures.

# **Impact Statement**

TALKPLAY introduces a novel approach to conversational music recommendation that could impact both user experience and music discovery. By unifying dialogue and recommendation through language models, our work may democratize music discovery by enlarging the recommendation pool. However, the system's recommendations may be still influenced by biases present in the training data, potentially affecting artist exposure and representation. Additionally, while our token-based approach helps protect user privacy by avoiding direct embedding storage, practitioners implementing such systems should carefully consider data handling practices and user consent mechanisms. We believe our technical contributions advance the field of machine learning while encouraging thoughtful consideration of recommendation system design's impact on users, artists, and the broader music ecosystem.

### References

- Barkan, O. and Koenigstein, N. Item2vec: neural item embedding for collaborative filtering. In 2016 IEEE 26th International Workshop on Machine Learning for Signal Processing (MLSP). IEEE, 2016.
- Bernhardsson, E. and contributors. Annoy: Approximate nearest neighbors in c++/python. https://github.com/spotify/annoy, 2013-2025. Accessed: 2025-01-25.
- Bertin-Mahieux, T., Ellis, D. P., Whitman, B., and Lamere, P. The million song dataset. In *International Society for Music Information Retrieval (ISMIR)*, 2011.
- Chaganty, A. T., Leszczynski, M., Zhang, S., Ganti, R., Balog, K., and Radlinski, F. Beyond single items: Exploring user preferences in item sets with the conversational playlist curation dataset. In *Proceedings of the 46th International ACM SIGIR Conference on Research and Development in Information Retrieval*, 2023.
- Chen, C.-W., Lamere, P., Schedl, M., and Zamani, H. Recsys challenge 2018: Automatic music playlist continuation. In *Proceedings of the 12th ACM Conference on Recommender Systems*, pp. 527–528, 2018.
- Chen, Q., Lin, J., Zhang, Y., Ding, M., Cen, Y., Yang, H., and Tang, J. Towards knowledge-based recommender dialog system. arXiv preprint arXiv:1908.05391, 2019.
- Chen, X., Lu, Y., Wang, Y., and Yang, J. Cmbf: Crossmodal-based fusion recommendation algorithm. *Sensors*, 21(16):5275, 2021.
- de Souza Pereira Moreira, G., Rabhi, S., Lee, J. M., Ak, R., and Oldridge, E. Transformers4rec: Bridging the

gap between nlp and sequential/session-based recommendation. In *Proceedings of the 15th ACM conference on recommender systems*, pp. 143–153, 2021.

- Doh, S., Choi, K., Lee, J., and Nam, J. LP-musiccaps: LLMbased pseudo music captioning. *International Society for Music Information Retrieval (ISMIR)*, 2023.
- Doh, S., Choi, K., Kwon, D., Kim, T., and Nam, J. Music discovery dialogue generation using human intent analysis and large language models. In *International Society* for Music Information Retrieval (ISMIR), 2024.
- Dubey, A., Jauhri, A., Pandey, A., Kadian, A., Al-Dahle, A., Letman, A., Mathur, A., Schelten, A., Yang, A., Fan, A., et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.
- Gardner, J., Durand, S., Stoller, D., and Bittner, R. M. Llark: A multimodal foundation model for music. *arXiv preprint arXiv:2310.07160*, 2023.
- He, Z., Xie, Z., Jha, R., Steck, H., Liang, D., Feng, Y., Majumder, B. P., Kallus, N., and McAuley, J. Large language models as zero-shot conversational recommenders. In *Proceedings of the 32nd ACM international conference* on information and knowledge management, 2023.
- Hewitt, J. Initializing new word embeddings for pretrained language models. https:/nlp.stanford.edu/ johnhew/vocabexpansion.html, 2021.
- Lai, R., Chen, L., Chen, W., and Chen, R. Matryoshka representation learning for recommendation. arXiv preprint arXiv:2406.07432, 2024.
- Lee, C., Roy, R., Xu, M., Raiman, J., Shoeybi, M., Catanzaro, B., and Ping, W. Nv-embed: Improved techniques for training LLMs as generalist embedding models. *arXiv* preprint arXiv:2405.17428, 2024.
- Leszczynski, M., Zhang, S., Ganti, R., Balog, K., Radlinski, F., Pereira, F., and Chaganty, A. T. Talk the walk: Synthetic data generation for conversational music recommendation. arXiv preprint arXiv:2301.11489, 2023.
- Liu, C., Jin, R., Ren, Y., Yu, L., Dong, T., Peng, X., Zhang, S., Peng, J., Zhang, P., Lyu, Q., et al. M3ke: A massive multi-level multi-subject knowledge evaluation benchmark for chinese large language models. *arXiv preprint arXiv:2305.10263*, 2023a.
- Liu, Q., Hu, J., Xiao, Y., Zhao, X., Gao, J., Wang, W., Li, Q., and Tang, J. Multimodal recommender systems: A survey. ACM Computing Surveys, 57(2):1–17, 2024a.
- Liu, S., Hussain, A. S., Sun, C., and Shan, Y. M2ugen: Multi-modal music understanding and generation with

the power of large language models. *arXiv preprint arXiv:2311.11255*, 2023b.

- Liu, Y., Zhang, W., Chen, Y., Zhang, Y., Bai, H., Feng, F., Cui, H., Li, Y., and Che, W. Conversational recommender system and large language model are made for each other in E-commerce pre-sales dialogue. In Bouamor, H., Pino, J., and Bali, K. (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 9587–9605, Singapore, December 2023c. Association for Computational Linguistics. doi: 10.18653/v1/2023.findings-emnlp. 643. URL https://aclanthology.org/2023. findings-emnlp.643/.
- Liu, Z., Zhang, H., Dong, K., and Fang, Y. Collaborative cross-modal fusion with large language model for recommendation. In *Proceedings of the 33rd ACM International Conference on Information and Knowledge Management*, pp. 1565–1574, 2024b.
- Loshchilov, I. Decoupled weight decay regularization. International Conference on Learning Representations (ICLR 2019), 2017.
- Muennighoff, N., Tazi, N., Magne, L., and Reimers, N. Mteb: Massive text embedding benchmark. *arXiv preprint arXiv:2210.07316*, 2022.
- Oramas, S., Nieto, O., Sordo, M., and Serra, X. A deep multimodal approach for cold-start music recommendation. In *Proceedings of the 2nd workshop on deep learning for recommender systems*, pp. 32–37, 2017.
- Palumbo, E., Penha, G., Damianou, A., García, J. L. R., Heath, T. C., Wang, A., Bouchard, H., and Lalmas, M. Text2tracks: Generative track retrieval for prompt-based music recommendation. 2022.
- Radford, A., Kim, J. W., Xu, T., Brockman, G., McLeavey, C., and Sutskever, I. Robust speech recognition via largescale weak supervision. In *International Conference on Machine Learning (ICML)*, 2023.
- Robertson, S. E. and Walker, S. Okapi/keenbow at trec-8. In *TREC*, 1999.
- Salau, L., Hamada, M., Prasad, R., Hassan, M., Mahendran, A., and Watanobe, Y. State-of-the-art survey on deep learning-based recommender systems for e-learning. *Applied Sciences*, 12(23):11996, 2022.
- Sun, F., Liu, J., Wu, J., Pei, C., Lin, X., Ou, W., and Jiang, P. Bert4rec: Sequential recommendation with bidirectional encoder representations from transformer. In *Proceedings* of the 28th ACM international conference on information and knowledge management, pp. 1441–1450, 2019.

- Tal, O., Ziv, A., Gat, I., Kreuk, F., and Adi, Y. Joint audio and symbolic conditioning for temporally controlled textto-music generation. arXiv preprint arXiv:2406.10970, 2024.
- Team, G., Georgiev, P., Lei, V. I., Burnell, R., Bai, L., Gulati, A., Tanzer, G., Vincent, D., Pan, Z., Wang, S., et al. Gemini 1.5: Unlocking multimodal understanding across millions of tokens of context. arXiv preprint arXiv:2403.05530, 2024.
- Tian, J., Zhao, J., Wang, Z., and Ding, Z. Mmrec: LLM based multi-modal recommender system. *arXiv preprint arXiv:2408.04211*, 2024.
- Van den Oord, A., Dieleman, S., and Schrauwen, B. Deep content-based music recommendation. Advances in neural information processing systems, 26, 2013.
- Wang, X., Zhou, K., Wen, J.-R., and Zhao, W. X. Towards unified conversational recommender systems via knowledge-enhanced prompt learning. In *Proceedings* of the 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining, pp. 1929–1937, 2022.
- Won, M., Hung, Y.-N., and Le, D. A foundation model for music informatics. In ICASSP 2024-2024 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP), pp. 1226–1230. IEEE, 2024.
- Wu, Y., Chen, K., Zhang, T., Hui, Y., Berg-Kirkpatrick, T., and Dubnov, S. Large-scale contrastive language-audio pretraining with feature fusion and keyword-to-caption augmentation. In *ICASSP 2023-2023 IEEE International Conference on Acoustics, Speech and Signal Processing* (*ICASSP*). IEEE, 2023.
- Yang, T. and Chen, L. Unleashing the retrieval potential of large language models in conversational recommender systems. In *Proceedings of the 18th ACM Conference on Recommender Systems*, pp. 43–52, 2024.
- Zhang, T., Liu, Y., Zhong, P., Zhang, C., Wang, H., and Miao, C. Kecrs: Towards knowledge-enriched conversational recommendation system. arXiv preprint arXiv:2105.08261, 2021.
- Zhang, Y., Chen, X., Ai, Q., Yang, L., and Croft, W. B. Towards conversational search and recommendation: System ask, user respond. In *Proceedings of the 27th acm international conference on information and knowledge management*, pp. 177–186, 2018.
- Zhao, J., Zhang, Z., Gao, L., Zhang, Q., Gui, T., and Huang, X. Llama beyond english: An empirical study on language capability transfer. *arXiv preprint arXiv:2401.01055*, 2024.

# A. Synthetic Data

A.1. Prompt to Google Gemini to synthesize conversation

```
You are an AI assistant specializing in music. Generate an ANSWER to the QUESTION in
   valid LIST OF JSON:
- role: one of {"user", "assistant", "music"}
- content:
  - for "user": string of conversation text for music request
  - for "assistant": string of conversation text for answer to user's request.
  - for "music": string of unique track_id (i.e., "3pzjHKrQSvXGHQ98dx18HI", "7
   vFv0yFGMJW3qVXbAd9BK9")
1. Conversation Start:
- The conversation begins with a user query.
  - This query can be a specific music item request (i.e., "superstition by steve wonder")
 - This query can be a natural language request (i.e., "party anthem with energetic
   rhythm", "play some 90s rock music")
- The assistant should respond with two consecutive objects:
 - A text response (role: "assistant") providing a brief reason for the recommendation
  - A music recommendation (role: "music") containing the 'track_id'
2. Assistant Recommendations:
- The assistant should recommend just one song per single turn, one that shares common
   musical traits (i.e, genre, artist, mood, theme, tempo) with the query song.
- The goal is to syntehsize an engaging conversation and allow the user to explore music
   based on their request.
- The assistant's music recommendations prioritize music tracks and tags, and ignore non-
   musical words. If there are captions and lyrics, use them as optional information as
   needed.
3. User Satisfaction:
 - In each turn, the user may or may not be satisfied with the recommendations and simply
   listen.
- The user may express agreement with the recommendation (e.g., "This is great!").
4. User Direction Change:
 - In the real-world scenario, sometimes users are not happy with the recommendation. We
   need to include it in our synthetic conversation.
- In such a case, the user would express dissatisfaction with a recommendation.
- The user may specify a new direction or trend of the recommended songs. (e.g., "Play
   something different", "Play something more upbeat").
- Use the songs in the "NEGATIVE SET" to synthesize this recommendation that user does
   not like.
- This helps evaluate how the assistant responds to negative feedback and adapts its
   recommendations.
5. assistant Adaptation:
The assistant should provide the next music track based on the following factors:
- The previous conversation.
- The current music being played.
- The user's recent requests.
- The assistant should recommend at least half of the songs in the provided playlist.
7. JSON Format:
 - The conversation should be formatted as a list of JSON objects.
8. Example:
OUESTION :
Music Playlist:
{'5tkDCf3xKRZjT5RbCb3sZB': "Metadata:\n Title: Big Amount\n Artist: 2 Chainz, Drake\n
   Album: Pretty Girls Like Trap Music, Industry Kings 2\nTag: drake, Hip-Hop/Rap, rap\n
    Popularity: 55.0\nLyrics: Pat downs, [REST OF THE LYRICS ARE OMITTED]\nPseudo
   Caption: This music features a hip hop song that consists of a flat male vocal rapping
  over shimmering hi hats, claps, punchy kick, groovy bass, synth lead melody and tinny
```

```
hi hats. It sounds energetic, exciting and addictive - like something you would hear
   in clubs.\nTempo Estimate: 134.13\nKey Estimate: G# minor",
[REST OF THE TRACKS ARE OMITTED] }
Negative Set:
{'7bJ4mu7MHa3rHiNyKjOoSl': 'Metadata:\n Title: Ice Melts\n Artist: Young Thug, Drake\n
   Album: More Life\nTag: young thug, Hip-Hop/Rap\n Popularity: 60.0\nLyrics: You need
   to give it up to someone. [REST OF THE LYRICS ARE OMITTED]\nPseudo Caption: This music
    features a hip hop song that consists of a passionate male vocal, alongside
   harmonizing background vocals, singing over shimmering hi hats, punchy kick and claps.
    It sounds groovy and addictive - like something you would hear in clubs.\nTempo
   Estimate: 124.51\nKey Estimate: A major',
[REST OF THE TRACKS ARE OMITTED] }
ANSWER:
Γ
  {"role": "user","content": "Play something like 'Big Amount' by 2 Chainz and Drake"},
  {"role": "assistant", "content": "Here's a similar track with a similar vibe, featuring a
    catchy hook and hard-hitting flow." },
  {"role": "music", "content": "4ckuS4Nj4FZ7i3Def3Br8W"},
  {"role": "user", "content": "This is great! Can you play something more upbeat, but still
    in a hip hop style?"},
  {"role": "assistant","content": "Here's a track with a faster tempo and energetic rhythm
    , perfect for keeping the party going." },
  {"role": "music", "content": "0B8QzDH7YWih85V5SEMnyJ"},
  {"role": "user", "content": "I'm not feeling this one, play something different"},
  {"role": "assistant","content": "I understand. How about something with a bit more of a
   soulful feel, but still with a good groove?" },
  {"role": "music", "content": "0PXp9QxBfSKGGpWUNaws2X"},
  {"role": "user", "content": "Yeah, that's better, this is more my style"},
  {"role": "assistant","content": "Great choice! Let's keep it in this vein, with a focus
   on smooth vocals and melodic rhythms." },
  {"role": "music", "content": "OH8XeaJunhvpBdBFIYi6Sh"},
  {"role": "user", "content": "This is so good, this mood is perfect"},
  {"role": "assistant","content": "I'm glad you're enjoying it! Here's another track that
   leans into the same kind of soulful vibe." },
  {"role": "music", "content": "3LwYGYpsg5SQioMX5BwFAz"},
  {"role": "user", "content": "This is really good! One last request, something a little
   more intense with a little more aggression" },
  {"role": "assistant", "content": "You got it. Here's a track with a harder edge and more
   energetic production. Get ready to bump!" },
  {"role": "music", "content": "OutlOiJy2weVl9WTkcEWHy"}
1
```

After this prompt, the track identifiers and their metadata is provided in a similar form shown under "8. Example".

#### A.2. Synthetic Conversation Example

This is one of the synthetic conversation results.

```
[{"role": "user",
  "content": "I'm looking for some mellow acoustic tracks to relax to. Can you suggest
    something?"},
  {"role": "music",
   "content": "3kZC0ZmFWrEHdUCmUqlvgZ"},
  {"role": "assistant",
   "content": "I think I Will Follow You into the Dark by Death Cab for Cutie would suit
    your mood. It's known for its emotional depth and gentle acoustic sound."},
  {"role": "user",
   "content": "That was beautiful, but a little too somber. How about something with more
    energy, still in the alternative rock genre?"},
  {"role": "music",
   "content": "3mcG2NI5G5vhrQtRda1YnA"},
  {"role": "assistant",
```

"content": "Okay, let's try something more upbeat. The Middle by Jimmy Eat World is a
 popular alternative rock anthem that offers a good balance of energy and emotion."}]

#### A.3. After Music Tokenization

This is after applying the music tokenization process in Section 4.1. The music identifiers are converted to a sequence of multimodal music tokens. This is the text data fed to the LLM.

```
"<|begin_of_text|>
<|start_header_id|>system<|end_header_id|>\n\nCutting Knowledge Date: December 2023\nToday
    Date: 20 Jan 2025\n\nYou are a music expert. Your task is conversational retrieval:
   Predict the next music item based on the given chat history.<|eot_id|>
<|start header id|>user<|end header id|>\n\nI'm looking for some mellow acoustic tracks to
    relax to. Can you suggest something?<|eot_id|><|start_header_id|>assistant<|
   end_header_id|>\n\n<start_of_music><|playlist-53|><|semantic-559|><|metadata-895|><|
   lyrics-654|><|audio-268|><end_of_music>I think I Will Follow You into the Dark by
   Death Cab for Cutie would suit your mood. It's known for its emotional depth and
   gentle acoustic sound.<|eot_id|><|start_header_id|>user<|end_header_id|>\n\nThat was
   beautiful, but a little too somber. How about something with more energy, still in
   the alternative rock genre?<|eot_id|><|start_header_id|>assistant<|end_header_id|>\n\n
   <start_of_music><|playlist-86|><|semantic-165|><|metadata-767|><|lyrics-158|><|audio</pre>
   -743|><end_of_music>Okay, let's try something more upbeat. The Middle by Jimmy Eat
   World is a popular alternative rock anthem that offers a good balance of energy and
   emotion.<|eot_id|>'
```

#### A.4. Comparison Music Recommendation Models

We compare our approach against three representative baselines spanning different paradigms of music retrieval:

**BM25** (Robertson & Walker, 1999) represents a classical text-based sparse retrieval approach. It utilizes term frequencyinverse document frequency (TF-IDF) scoring to match user queries with music metadata and semantic tags. <sup>2</sup> While computationally efficient and interpretable, this method relies solely on lexical matching and cannot capture semantic relationships or cross-modal patterns.

**NV-Embeds-V2** (Lee et al., 2024) advances beyond sparse retrieval by implementing a text-based deep similarity retrieval framework. The model learns dense neural embeddings for both queries and music descriptions, enabling semantic matching that can capture latent relationships beyond exact word matches. This model represents a strong baseline as an LLM-based embedding extractor model that has demonstrated superior retrieval performance on the MTEB benchmark.

**CLAP** (Wu et al., 2023) extends the similarity-based paradigm to multiple modalities by jointly embedding audio and text. Through contrastive learning, it aligns the representations of music audio with corresponding textual descriptions, enabling cross-modal retrieval. This model represents the current state-of-the-art in audio-text music retrieval, providing a strong baseline for multimodal understanding.

Compare to other methods, TALKPLAY takes a fundamentally different approach by reformulating music retrieval as a generative task. Rather than learning separate embeddings, it unifies dialogue understanding and recommendation through token generation within a language model framework.

<sup>&</sup>lt;sup>2</sup>{Title} by {Artist} from {Album} {Semantic tags} {Year}