
Qwen2.5-VL Technical Report

Qwen Team, Alibaba Group

- \$\$ https://chat.qwenlm.ai
- 😕 https://huggingface.co/Qwen
- https://modelscope.cn/organization/qwen
- https://github.com/QwenLM/Qwen2.5-VL

Abstract

We introduce Qwen2.5-VL, the latest flagship model of Qwen vision-language series, which demonstrates significant advancements in both foundational capabilities and innovative functionalities. Qwen2.5-VL achieves a major leap forward in understanding and interacting with the world through enhanced visual recognition, precise object localization, robust document parsing, and long-video comprehension. A standout feature of Qwen2.5-VL is its ability to localize objects using bounding boxes or points accurately. It provides robust structured data extraction from invoices, forms, and tables, as well as detailed analysis of charts, diagrams, and layouts. To handle complex inputs, Qwen2.5-VL introduces dynamic resolution processing and absolute time encoding, enabling it to process images of varying sizes and videos of extended durations (up to hours) with second-level event localization. This allows the model to natively perceive spatial scales and temporal dynamics without relying on traditional normalization techniques. By training a native dynamic-resolution Vision Transformer (ViT) from scratch and incorporating Window Attention, we have significantly reduced computational overhead while maintaining native resolution. As a result, Qwen2.5-VL excels not only in static image and document understanding but also as an interactive visual agent capable of reasoning, tool usage, and task execution in real-world scenarios such as operating computers and mobile devices. The model achieves strong generalization across domains without requiring task-specific fine-tuning. Qwen2.5-VL is available in three sizes, addressing diverse use cases from edge AI to high-performance computing. The flagship Qwen2.5-VL-72B model matches state-of-the-art models like GPT-40 and Claude 3.5 Sonnet, particularly excelling in document and diagram understanding. The smaller Qwen2.5-VL-7B and Qwen2.5-VL-3B models outperform comparable competitors, offering strong capabilities even in resource-constrained environments. Additionally, Qwen2.5-VL maintains robust linguistic performance, preserving the core language competencies of the Qwen2.5 LLM.



1 Introduction

Large vision-language models (LVLMs) (OpenAI, 2024; Anthropic, 2024a; Team et al., 2023; Wang et al., 2024f) represent a pivotal breakthrough in artificial intelligence, signaling a transformative approach to multimodal understanding and interaction. By seamlessly integrating visual perception with natural language processing, these advanced models are fundamentally reshaping how machines interpret and analyze complex information across diverse domains. Despite significant advancements in multimodal large language models, the current capabilities of these models can be likened to the middle layer of a sandwich cookie—competent across various tasks but falling short of exceptional performance. Fine-grained visual tasks form the foundational layer of this analogy. In this iteration of Qwen2.5-VL, we are committed to exploring fine-grained perception capabilities, aiming to establish a robust foundation for LVLMs and create an agentic amplifier for real-world applications. The top layer of this framework is multi-modal QA data construction.

A spectrum of works have promoted the development of multimodal large models, characterized by architectural design, visual input processing, and data curation. One of the primary drivers of progress in LVLMs is the continuous innovation in architecture. The studies presented in (Alayrac et al., 2022; Li et al., 2022a; 2023b; Liu et al., 2023b; a) Wang et al., 2024i; Zhang et al., 2024b; Wang et al., 2023) have incrementally shaped the current paradigm, which typically consists of a visual encoder, a cross-modal projector, and LLM. Fine-grained perception models have emerged as another crucial area. Models like (Xiao et al., 2023; Liu et al., 2023c; Ren et al., 2024; Zhang et al., 2024a; Peng et al., 2023; Deitke et al., 2024) have pushed the boundaries of what is possible in terms of detailed visual understanding. The architectures of Omni (Li et al., 2024g; 2025b; Ye et al., 2024) and MoE (Riquelme et al., 2021; Lee et al., 2024; Li et al., 2024h; Chen et al., 2023; Liu et al., 2023; Liu et al., 2024b) also inspire the future evolution of LVLMs. Enhancements in visual encoders (Chen et al., 2023; Liu et al., 2024b; Liang et al., 2025) and resolution scaling (Li et al., 2023c; Ye et al., 2023; Li et al., 2023a) have played a pivotal role in improving the quality of practical visual understanding. Curating data with more diverse scenarios and higher-quality is an essential step in training advanced LVLMs. The efforts proposed in (Guo et al., 2024; Chen et al., 2024c; Liu et al., 2024a; Tong et al., 2024; Li et al., 2024a) are highly valuable contributions to this endeavor.

However, despite their remarkable progress, vision-language models currently face developmental bottlenecks, including computational complexity, limited contextual understanding, poor fine-grained visual perception, and inconsistent performance across varied sequence length.

In this report, we introduce the latest work Qwen2.5-VL, which continues the open-source philosophy of the Qwen series, achieving and even surpassing top-tier closed-source models on various benchmarks. Technically, our contributions are four-folds: (1) We implement window attention in the visual encoder to optimize inference efficiency; (2) We introduce dynamic FPS sampling, extending dynamic resolution to the temporal dimension and enabling comprehensive video understanding across varied sampling rates; (3) We upgrade MRoPE in the temporal domain by aligning to absolute time, thereby facilitating more sophisticated temporal sequence learning; (4) We make significant efforts in curating high-quality data for both pre-training and supervised fine-tuning, further scaling the pre-training corpus from 1.2 trillion tokens to 4.1 trillion tokens.

The sparkling characteristics of Qwen2.5-VL are as follows:

- **Powerful document parsing capabilities:** Qwen2.5-VL upgrades text recognition to omnidocument parsing, excelling in processing multi-scene, multilingual, and various built-in (handwriting, tables, charts, chemical formulas, and music sheets) documents.
- **Precise object grounding across formats:** Qwen2.5-VL unlocks improved accuracy in detecting, pointing, and counting objects, accommodating absolute coordinate and JSON formats for advanced spatial reasoning.
- Ultra-long video understanding and fine-grained video grounding: Our model extends native dynamic resolution to the temporal dimension, enhancing the ability to understand videos lasting hours while extracting event segments in seconds.
- Enhanced agent Functionality for computer and mobile devices: Leverage advanced grounding, reasoning, and decision-making abilities, boosting the model with superior agent functionality on smartphones and computers.




Figure 1: The Qwen2.5-VL framework demonstrates the integration of a vision encoder and a language model decoder to process multimodal inputs, including images and videos. The vision encoder is designed to handle inputs at their native resolution and supports dynamic FPS sampling. Images of varying sizes and video frames with different FPS rates are dynamically mapped to token sequences of varying lengths. Notably, MRoPE aligns time IDs with absolute time along the temporal dimension, enabling the model to better comprehend temporal dynamics, such as the pace of events and precise moment localization. The processed visual data is subsequently fed into the Qwen2.5 LM Decoder. We have re-engineered the vision transformer (ViT) architecture, incorporating advanced components such as FFN with SwiGLU activation, RMSNorm for normalization, and window-based attention mechanisms to enhance performance and efficiency.

2 Approach

In this section, we first outline the architectural updates of the Qwen2.5-VL series models and provide an overview of the data and training details.

2.1 Model Architecture

The overall model architecture of Qwen2.5-VL consists of three components:

Large Language Model: The Qwen2.5-VL series adopts large language models as its foundational component. The model is initialized with pre-trained weights from the Qwen2.5 LLM. To better meet the demands of multimodal understanding, we have modified the 1D RoPE (Rotary Position Embedding) to our Multimodal Rotary Position Embedding Aligned to Absolute Time.

Vision Encoder: The vision encoder of Qwen2.5-VL employs a redesigned Vision Transformer (ViT) architecture. Structurally, we incorporate 2D-RoPE and window attention to support native input resolutions while accelerating the computation of the entire visual encoder. During both training and inference, the height and width of the input images are resized to multiples of 28 before being fed into the ViT. The vision encoder processes images by splitting them into patches with a stride of 14, generating a set of image features. We provide a more detailed introduction to the vision encoder in Section 2.1.1.

MLP-based Vision-Language Merger: To address the efficiency challenges posed by long sequences of image features, we adopt a simple yet effective approach to compress the feature sequences before feeding them into the large language model (LLM). Specifically, instead of directly using the raw patch

features extracted by the Vision Transformer (ViT), we first group spatially adjacent sets of four patch features. These grouped features are then concatenated and passed through a two-layer multi-layer perceptron (MLP) to project them into a dimension that aligns with the text embeddings used in the LLM. This method not only reduces computational costs but also provides a flexible way to dynamically compress image feature sequences of varying lengths.

Configuration	Qwen2.5-VL-3B	Qwen2.5-VL-7B	Qwen2.5-VL-72B				
	Vision Transform	er (ViT)					
Hidden Size	1280	1280	1280				
# Layers	32	32	32				
# Num Heads	16	16	16				
Intermediate Size	3456	3456	3456				
Patch Size	14	14	14				
Window Size	112	112	112				
Full Attention Block Indexes	{7, 15, 23, 31}	{7, 15, 23, 31}	{7, 15, 23, 31}				
Vision-Language Merger							
In Channel	1280	1280	1280				
Out Channel	2048	3584	8192				
L	arge Language Mo	del (LLM)					
Hidden Size	2048	3,584	8192				
# Layers	36	28	80				
# KV Heads	2	4	8				
Head Size	128	128	128				
Intermediate Size	4864	18944	29568				
Embedding Tying	✓	×	×				
Vocabulary Size	151646	151646	151646				
# Trained Tokens	4.1T	4.1T	4.1T				

In Table 1, the architecture and configuration of Qwen2.5-VL are detailed.

Table 1: Configuration of Qwen2.5-VL.

2.1.1 Fast and Efficient Vision Encoder

The vision encoder plays a pivotal role in multimodal large language models (MLLMs). To address the challenges posed by computational load imbalances during training and inference due to native resolution inputs, we have redesigned the Vision Transformer (ViT) architecture. A key issue arises from the quadratic computational complexity associated with processing images of varying sizes. To mitigate this, we introduce windowed attention in most layers, which ensures that computational cost scales linearly with the number of patches rather than quadratically. In our architecture, only four layers employ full self-attention, while the remaining layers utilize windowed attention with a maximum window size of 112×112 (corresponding to 8×8 patches). Regions smaller than 112×112 are processed without padding, preserving their original resolution. This design allows the model to operate natively at the input resolution, avoiding unnecessary scaling or distortion.

For positional encoding, we adopt 2D Rotary Positional Embedding (RoPE) to effectively capture spatial relationships in 2D space. Furthermore, to better handle video inputs, we extend our approach to 3D patch partitioning. Specifically, we use 14×14 image patches as the basic unit, consistent with traditional ViTs for static images. For video data, two consecutive frames are grouped together, significantly reducing the number of tokens fed into the language model. This design not only maintains compatibility with existing architectures but also enhances efficiency when processing sequential video data.

To streamline the overall network structure, we align the ViT architecture more closely with the design principles of large language models (LLMs). Specifically, we adopt RMSNorm (Zhang &Sennrich, 2019) for normalization and SwiGLU (Dauphin et al., 2017) as the activation function. These choices enhance both computational efficiency and compatibility between the vision and language components of the model.

In terms of training, we train the redesigned ViT from scratch. The training process consists of several stages, including CLIP pre-training, vision-language alignment, and end-to-end fine-tuning. To ensure robustness across varying input resolutions, we employ dynamic sampling at native resolutions during

training. Images are randomly sampled according to their original aspect ratios, enabling the model to generalize effectively to inputs of diverse resolutions. This approach not only improves the model's adaptability but also ensures stable and efficient training across different sizes of visual data.

2.1.2 Native Dynamic Resolution and Frame Rate

Qwen2.5-VL introduces advancements in both spatial and temporal dimensions to handle diverse multimodal inputs effectively.

In the spatial domain, Qwen2.5-VL dynamically converts images of varying sizes into sequences of tokens with corresponding lengths. Unlike traditional approaches that normalize coordinates, our model directly uses the actual dimensions of the input image to represent bounding boxes, points, and other spatial features. This allows the model to learn scale information inherently, improving its ability to process images across different resolutions.

For video inputs, Qwen2.5-VL incorporates dynamic frame rate (FPS) training and absolute time encoding. By adapting to variable frame rates, the model can better capture the temporal dynamics of video content. Unlike other approaches that incorporate textual timestamps or utilize additional heads to enable temporal grounding, we introduce a novel and efficient strategy that aligns MRoPE IDs directly with the timestamps. This approach allows the model to understand the tempo of time through the intervals between temporal dimension IDs, without necessitating any additional computational overhead.

2.1.3 Multimodal Rotary Position Embedding Aligned to Absolute Time

Positional embeddings are crucial for modeling sequential data in both vision and language modalities. Building upon the Multimodal Rotary Position Embedding (MRoPE) introduced in Qwen2-VL, we extend its capabilities to better handle temporal information in videos.

The MRoPE in Qwen2-VL decomposes the position embedding into three distinct components: temporal, height, and width to effectively model multimodal inputs. For textual inputs, all three components use identical position IDs, making MRoPE functionally equivalent to traditional 1D RoPE (Su et al., 2024). For images, the temporal ID remains constant across visual tokens, while unique IDs are assigned to the height and width components based on each token's spatial position within the image. When processing videos, which are treated as sequences of frames, the temporal ID increments for each frame, while the height and width components follow the same assignment pattern as for static images.

However, in Qwen2-VL, the temporal position IDs in MRoPE were tied to the number of input frames, which did not account for the speed of content changes or the absolute timing of events within the video. To address this limitation, Qwen2.5-VL introduces a key improvement: aligning the temporal component of MRoPE with absolute time. As shown in Figure 1, by leveraging the intervals between temporal IDs, the model is able to learn consistent temporal alignment across videos with different FPS sampling rates.

2.2 Pre-Training

In this section, we first describe the construction of the pre-training dataset, followed by an overview of the overall training pipeline and configuration.

2.2.1 Pre-Training Data

Compared to Qwen2-VL, we have significantly expanded the volume of our pre-training data, increasing it from 1.2 trillion tokens to approximately 4 trillion tokens. Our pre-training dataset was constructed through a combination of methods, including cleaning raw web data, synthesizing data, etc. The dataset encompasses a wide variety of multimodal data, such as image captions, interleaved image-text data, optical character recognition (OCR) data, visual knowledge (e.g., celebrity, landmark, flora, and fauna identification), multi-modal academic questions, localization data, document parsing data, video descriptions, video localization, and agent-based interaction data. Throughout the training process, we carefully adjusted the composition and proportions of these data types at different stages to optimize learning outcomes.

Interleaved Image-Text Data Interleaved image-text data is essential for multimodal learning, offering three key benefits: (1) enabling in-context learning with simultaneous visual and textual cues (Alayrac et al., 2022), (2) maintaining strong text-only capabilities when images are missing (Lin et al., 2024), and (3) containing a wide range of general information. However, much of the available interleaved data

lacks meaningful text-image associations and is often noisy, limiting its usefulness for complex reasoning and creative generation.

To address these challenges, we developed a pipeline for scoring and cleaning data, ensuring only high-quality, relevant interleaved data is used. Our process involves two steps: standard data cleaning (Li et al., 2024e) followed by a four-stage scoring system using an internal evaluation model. The scoring criteria include: (1) text-only quality, (2) image-text relevance, (3) image-text complementarity, and (4) information density balance. This meticulous approach improves the model's ability to perform complex reasoning and generate coherent multimodal content.

The following is a description of these image-text scoring criteria:

Image-text Relevance: A higher score indicates a stronger connection between the image and text, where the image meaningfully supplements, explains or expands on the text rather than just decorating it.

Information Complementarity: A higher score reflects greater complementary information between the image and text. Each should provide unique details that together create a complete narrative.

Balance of Information Density: A higher score means a more balanced distribution of information between the image and text, avoiding excessive text or image information, and ensuring an appropriate balance between the two.

Grounding Data with Absolute Position Coordinates We adopt native resolution training with the aim of achieving a more accurate perception of the world. In contrast, relative coordinates fail to effectively represent the original size and position of objects within images. To address this limitation, Qwen2.5-VL uses coordinate values based on the actual dimensions of the input images during training to represent bounding boxes and points. This approach ensures that the model can better capture the real-world scale and spatial relationships of objects, leading to improved performance in tasks such as object detection and localization.

To improve the generalizability of grounding capabilities, we have developed a comprehensive dataset encompassing bounding boxes and points with referring expressions, leveraging both publicly available datasets and proprietary data. Our methodology involves synthesizing data into various formats, including XML, JSON, and custom formats, employing techniques such as copy-paste augmentation (Ghiasi et al., 2021) and synthesis with off-the-shelf models such as Grounding DINO (Liu et al., 2023c) and SAM (Kirillov et al., 2023). This approach facilitates a more robust evaluation and advancement of grounding abilities.

To enhance the model's performance on open-vocabulary detection, we expanded the training dataset to include over 10,000 object categories. Additionally, to improve the model's effectiveness in extreme object detection scenarios, we synthesized non-existent object categories within the queries and constructed image data containing multiple instances for each object.

To ensure superior point-based object grounding capabilities, we have constructed a comprehensive pointing dataset comprising both publicly available and synthetic data. Specifically, the data source includes public pointing and counting data from PixMo (Deitke et al., 2024), publicly accessible object grounding data (from both object detection and instance segmentation tasks), and data synthesized by an automated pipeline for generating precise pointing data towards certain image details.

Document Omni-Parsing Data To train Qwen2.5-VL, we synthesized a large corpus of document data. Traditional methods for parsing document content typically rely on separate models to handle layout analysis, text extraction, chart interpretation, and illustration processing. In contrast, Qwen2.5-VL is designed to empower a general-purpose model with comprehensive capabilities for parsing, understanding, and converting document formats. Specifically, we incorporated a diverse array of elements into the documents, such as tables, charts, equations, natural or synthetic images, music sheets, and chemical formulas. These elements were uniformly formatted in HTML, which integrates layout box information and descriptions of illustrations into HTML tag structures. We also enriched the document layouts according to typical reading sequences and included the coordinates corresponding to each module, such as paragraphs and charts, in the HTML-based ground truth. This innovative approach allows the complete information of any document, including its layout, text, charts, and illustrations, to be represented in a standardized and unified manner. As a result, Qwen2.5-VL achieves seamless integration of multimodal document elements, thereby facilitating more efficient and accurate document understanding and transformation.

Below is the QwenVL HTML format:

QwenVL HTML Format

<html><body> # paragraph content # table <style>table{id} style</style> table content # chart <div class="chart" data-bbox="x1 y1 x2 y2"> chart content </div> # formula <div class="formula" data-bbox="x1 y1 x2 y2"> <div> formula content </div></div> # image caption <div class="image caption" data-bbox="x1 y1 x2 y2"> image caption </div> # image ocr <div class="image ocr" data-bbox="x1 y1 x2 y2"> image ocr </div> # music sheet <div class="music sheet" format="abc notation" data-bbox="x1 y1 x2 y2"> <div> music sheet content </div></div> # chemical formula content <div class="chemical formula" format="smile" data-bbox="x1 y1 x2 y2"> <div> chemical formula content </div></div> </html></body>

This format ensures that all document elements are represented in a structured and accessible manner, enabling efficient processing and understanding by Qwen2.5-VL.

OCR Data Data from different sources are gathered and curated to enhance the OCR performance, including synthetic data, open-sourced data and in-house collected data. Synthetic data is generated through a visual text generation engine to produce high-quality text images in the wild. To support a wider range of languages and enhance multilingual capabilities, we have incorporated a large-scale multilingual OCR dataset. This dataset includes support for diverse languages such as French, German, Italian, Spanish, Portuguese, Arabic, Russian, Japanese, Korean, and Vietnamese. The dataset is carefully curated to ensure diversity and quality, utilizing both high-quality synthetic images and real-world natural scene images. This combination ensures robust performance across various linguistic contexts and improves the model's adaptability to different text appearances and environmental conditions. For chart-type data, we synthesized 1 million samples using visualization libraries including matplotlib, seaborn, and plotly, encompassing chart categories such as bar charts, relational diagrams, and heatmaps. Regarding tabular data, we processed 6 million real-world samples through an offline end-to-end table recognition model, subsequently filtering out low-confidence tables, overlapping tables, and tables with insufficient cell density.

Video Data To ensure enhanced robustness in understanding video data with varying frames per second (FPS), we dynamically sampled FPS during training to achieve a more evenly distributed representation of FPS within the training dataset. Additionally, for videos exceeding half an hour in length, we specifically constructed a set of long video captions by synthesizing multi-frame captions through a targeted synthesis pipeline. Regarding video grounding data, we formulated timestamps in both second-based formats and hour-minute-second-frame (hmsf) formats, ensuring that the model can accurately understand and output time in various formats.

Agent Data We enhance the perception and decision-making abilities to build the agent capabilities of Qwen2.5-VL. For perception, we collect screenshots on mobile, web, and desktop platforms. A synthetic data engine is used to generate screenshot captions and UI element grounding annotations. The caption task helps Qwen2.5-VL understand the graphic interface, while the grounding task helps it align the appearance and function of elements. For decision-making, we first unify the operations across mobile, web, and desktop platforms into a function call format with a shared action space. A set of annotated multi-step trajectories collected from open-source data and synthesized by agent framework (Wang et al., 2025; 2024b;c) on virtual environments are reformatted into a function format. We further generate a

reasoning process for each step through human and model annotators (Xu et al., 2024). Specifically, given a ground-truth operation, we highlight it on the screenshot. Then, we provide the global query, along with screenshots from before and after this operation, to the annotators and require them to write reasoning content to explain the intention behind this operation. A model-based filter is used to screen out low-quality reasoning content. Such reasoning content prevents Qwen2.5-VL from overfitting to the ground-truth operations and makes it more robust in real-world scenarios.

Stages	Visual Pre-Training	Multimodal Pre-Training	Long-Context Pre-Training
Data	Image Caption Knowledge OCR	+ Pure text Interleaved Data VQA, Video Grounding, Agent	+ Long Video Long Agent Long Document
Tokens	1.5T	2T	0.6T
Sequence length	8192	8192	32768
Training	ViT	ViT & LLM	ViT & LLM

Table 2: Training data volume and composition across different stages.

2.2.2 Training Recipe

We trained a Vision Transformer (ViT) from scratch using DataComp (Gadre et al., 2023) and some in-house datasets as the initialization for the vision encoder, while leveraging the pre-trained Qwen2.5 large language model (LLM) (Yang et al., 2024a) as the initialization for the LLM component. As shown in Table 2, the pre-training process is divided into three distinct phases, each employing different data configurations and training strategies to progressively enhance the model's capabilities.

In the first phase, only the Vision Transformer (ViT) is trained to improve its alignment with the language model, laying a solid foundation for multimodal understanding. The primary data sources during this phase include image captions, visual knowledge, and OCR data. These datasets are carefully selected to foster ViT's ability to extract meaningful visual representations that can be effectively integrated with textual information.

In the second phase, all model parameters are unfrozen, and the model is trained on a diverse set of multimodal image data to enhance its capacity to process complex visual information. This phase introduces more intricate and reasoning-intensive datasets, such as interleaved data, multi-task learning datasets, visual question answering (VQA), multimodal mathematics, agent-based tasks, video understanding, and pure-text datasets. These datasets strengthen the model's ability to establish deeper connections between visual and linguistic modalities, enabling it to handle increasingly sophisticated tasks.

In the third phase, to further enhance the model's reasoning capabilities over longer sequences, video, and agent-based data are incorporated, alongside an increase in sequence length. This allows the model to tackle more advanced and intricate multimodal tasks with greater precision. By extending the sequence length, the model gains the ability to process extended contexts, which is particularly beneficial for tasks requiring long-range dependencies and complex reasoning.

To address the challenges posed by varying image sizes and text lengths, which can lead to imbalanced computational loads during training, we adopted a strategy to optimize training efficiency. The primary computational costs arise from the LLM and the vision encoder. Given that the vision encoder has relatively fewer parameters and that we introduced window attention to further reduce its computational demands, we focused on balancing the computational load of the LLM across different GPUs. Specifically, we dynamically packed data samples based on their corresponding input sequence lengths to the LLM, ensuring consistent computational loads. In the first and second phases, data were uniformly packed to a sequence length of 8,192, while in the third phase, the sequence length was increased to 32,768 to accommodate the model's enhanced capacity for handling longer sequences.

2.3 Post-training

The post-training alignment framework of Qwen2.5-VL employs a dual-stage optimization paradigm comprising Supervised Fine-Tuning (SFT) and Direct Preference Optimization (DPO) (Rafailov et al., 2023). This hierarchical alignment strategy synergizes parameter-efficient domain adaptation with human preference distillation, addressing both representational grounding and behavioral refinement through distinct optimization objectives.

Supervised Fine-Tuning (SFT) aims to bridge the gap between pretrained representations and downstream task requirements through targeted instruction optimization. During this phase, we employ the ChatML format (Openai, 2024) to structure instruction-following data, deliberately diverging from the pretraining data schema while maintaining architectural consistency with Qwen2-VL (Wang et al., 2024e). This format transition enables three critical adaptations: 1) Explicit dialogue role tagging for multimodal turn-taking, 2) Structured injection of visual embeddings alongside textual instructions, and 3) Preservation of cross-modal positional relationships through format-aware packing. By exposing the model to curated multimodal instruction-response pairs under this enhanced schema, SFT enables efficient knowledge transfer while maintaining the integrity of pre-trained features.

2.3.1 Instruction Data

The Supervised Fine-Tuning (SFT) phase employs a meticulously curated dataset designed to enhance the model's instruction-following capabilities across diverse modalities. This dataset comprises approximately 2 million entries, evenly distributed between pure text data (50%) and multimodal data (50%), which includes image-text and video-text combinations. The inclusion of multimodal data enables the model to process complex inputs effectively. Notably, although pure text and multimodal entries are equally represented, multimodal entries consume significantly more tokens and computational resources during training due to the embedded visual and temporal information. The dataset is primarily composed of Chinese and English data, with supplementary multilingual entries to support broader linguistic diversity.

The dataset is structured to reflect varying levels of dialogue complexity, including both single-turn and multi-turn interactions. These interactions are further contextualized by scenarios ranging from single-image inputs to multi-image sequences, thereby simulating realistic conversational dynamics. The query sources are primarily drawn from open-source repositories, with additional contributions from curated purchased datasets and online query data. This combination ensures broad coverage and enhances the representativeness of the dataset.

To address a wide range of application scenarios, the dataset includes specialized subsets for General Visual Question Answering (VQA), image captioning, mathematical problem-solving, coding tasks, and security-related queries. Additionally, dedicated datasets for Document and Optical Character Recognition (Doc and OCR), Grounding, Video Analysis, and Agent Interactions are constructed to enhance domain-specific proficiency. Detailed information regarding the data can be found in the relevant sections of the paper. This structured and diverse composition ensures that the SFT phase effectively aligns pre-trained representations with the nuanced demands of downstream multimodal tasks, fostering robust and contextually aware model performance.

2.3.2 Data Filtering Pipeline

The quality of training data is a critical factor influencing the performance of vision-language models. Open-source and synthetic datasets typically exhibit significant variability, often containing noisy, redundant, or low-quality samples. Therefore, rigorous data cleaning and filtering processes are essential to address these issues. Low-quality data can lead to suboptimal alignment between pretrained representations and downstream task requirements, thereby diminishing the model's ability to effectively handle complex multimodal tasks. Consequently, ensuring high-quality data is paramount for achieving robust and reliable model performance.

To address these challenges, we implement a two-stage data filtering pipeline designed to systematically enhance the quality of the Supervised Fine-Tuning (SFT) dataset. This pipeline comprises the following stages:

Stage 1: Domain-Specific Categorization In the initial stage, we employ *Qwen2-VL-Instag*, a specialized classification model derived from Qwen2-VL-72B, to perform hierarchical categorization of question-answer (QA) pairs. This model organizes QA pairs into eight primary domains, such as *Coding* and *Planning*, which are further divided into 30 fine-grained subcategories. For example, the primary domain *Coding* is subdivided into subcategories including *Code_Debugging*, *Code_Generation*, *Code_Translation*, and *Code_Understanding*. This hierarchical structure facilitates domain-aware and subdomain-aware filtering strategies, enabling the pipeline to optimize data-cleaning processes tailored to each category's specific characteristics. Consequently, this enhances the quality and relevance of the supervised fine-tuning (SFT) dataset.

Stage 2: Domain-Tailored Filtering The second stage involves domain-tailored filtering, which integrates both rule-based and model-based approaches to comprehensively enhance data quality. Given

the diverse nature of domains such as Document Processing, Optical Character Recognition (OCR), and Visual Grounding, each may necessitate unique filtering strategies. Below, we provide an overview of the general filtering strategies applied across these domains.

Rule-Based Filtering employs predefined heuristics to eliminate low-quality or problematic entries. Specifically, for datasets related to Document Processing, OCR, and Visual Grounding tasks, repetitive patterns are identified and removed to prevent distortion of the model's learning process and ensure optimal performance. Additionally, entries containing incomplete, truncated, or improperly formatted responses—common in synthetic datasets and multimodal contexts—are excluded. To maintain relevance and uphold ethical standards, queries and answers that are unrelated or could potentially lead to harmful outputs are also discarded. This structured approach ensures that the dataset adheres to ethical guidelines and meets task-specific requirements.

Model-Based Filtering further refines the dataset by leveraging reward models trained on the Qwen2.5-VL series. These models evaluate multimodal QA pairs across multiple dimensions. Queries are assessed for complexity and relevance, retaining only those examples that are appropriately challenging and contextually pertinent. Answers are evaluated based on correctness, completeness, clarity, relevance to the query, and helpfulness. In visual-grounded tasks, particular attention is given to verifying the accurate interpretation and utilization of visual information. This multi-dimensional scoring ensures that only high-quality data progresses to the SFT phase.

2.3.3 Rejection Sampling for Enhanced Reasoning

To complement our structured data filtering pipeline, we employ rejection sampling as a strategy to refine the dataset and enhance the reasoning capabilities of the vision-language model (VLM). This approach is particularly critical for tasks requiring complex inference, such as mathematical problemsolving, code generation, and domain-specific visual question answering (VQA). Prior research has shown that incorporating Chain-of-Thought (CoT) Wei et al. (2022) reasoning significantly improves a model's inferential performance. (DeepSeek-AI et al., 2024) Our post-training experiments confirm this, underscoring the importance of structured reasoning processes for achieving high-quality outcomes.

The rejection sampling process begins with datasets enriched with ground truth annotations. These datasets are carefully curated to include tasks that demand multi-step reasoning, such as mathematical problem-solving, code generation, and domain-specific VQA. Using an intermediate version of the Qwen2.5-VL model, we evaluate the generated responses against the ground truth. Only samples where the model's output matches the expected answers are retained, ensuring the dataset consists solely of high-quality, accurate examples.

To further improve data quality, we apply additional constraints to filter out undesirable outputs. Specifically, we exclude responses that exhibit code-switching, excessive length, or repetitive patterns. These criteria ensure clarity and coherence in the CoT reasoning process, which is crucial for downstream applications.

A key challenge in applying CoT reasoning to vision-language models is their reliance on both textual and visual modalities. Intermediate reasoning steps may fail to adequately integrate visual information, either by ignoring relevant visual cues or misinterpreting them. To address this, we have developed rule-based and model-driven filtering strategies to validate the accuracy of intermediate reasoning steps. These mechanisms ensure that each step in the CoT process effectively integrates visual and textual modalities. Despite these efforts, achieving optimal modality alignment remains an ongoing challenge that requires further advancements.

The data generated through rejection sampling significantly enhances the model's reasoning proficiency. By iteratively refining the dataset and removing low-quality or erroneous samples, we enable the model to learn from high-fidelity examples that emphasize accurate and coherent reasoning. This methodology not only strengthens the model's ability to handle complex tasks but also lays the groundwork for future improvements in vision-language modeling.

2.3.4 Training Recipe

The post-training process for Qwen2.5-VL consists of two phases: Supervised Fine-Tuning (SFT) and Direct Preference Optimization (DPO), both with the Vision Transformer (ViT) parameters frozen. In the SFT phase, the model is fine-tuned on diverse multimodal data, including image-text pairs, video, and pure text, sourced from general VQA, Rejection Sampling, and specialized datasets such as Document and OCR, Grounding, Video, and Agent-related tasks. The DPO phase focuses exclusively on image-text and pure text data, utilizing preference data to align the model with human preferences, with each sample processed only once to ensure efficient optimization. This streamlined process enhances the model's

cross-modal reasoning and task-specific performance while maintaining alignment with user intent.

3 Experiments

In this section, we first introduce the overall model and compare it with the current state-of-the-art (SoTA) models. Then, we evaluate the model's performance across various sub-capabilities.

3.1 Comparison with the SOTA Models

Datasets	Previous Open-source SoTA	Claude-3.5 Sonnet-0620	GPT-40 0513	InternVL2.5 78B	Qwen2-VL 72B	Qwen2.5-VL 72B	Qwen2.5-VL 7B	Qwen2.5-VL 3B
		College-level	Problems					
MMMU _{val} (Yue et al., 2023) MMMU-Pro _{overall} (Yue et al., 2024)	70.1 Chen et al. (2024d) 48.6 Chen et al. (2024d)	68.3 51.5	69.1 51.9	70.1 48.6	64.5 46.2	70.2 51.1	58.6 38.3	53.1 31.56
		Mat	h					
MathVista _{mini} (Lu et al., 2024) MATH-Vision _{full} (Wang et al., 2024d) MathVerse _{mini} (Zhang et al., 2024c)	72.3 Chen et al. (2024d) 32.2 Chen et al. (2024d) 51.7 Chen et al. (2024d)	67.7 - -	63.8 30.4 50.2	72.3 32.2 51.7	70.5 25.9	74.8 38.1 57.6	68.2 25.1 49.2	62.3 21.2 47.6
	Gene	eral Visual Que	stion Ansa	wering				
$\begin{array}{l} \label{eq:metric} MegaBench (Chen et al., 2024b)\\ MMBench-CNtest (Liu et al., 2023d)\\ MMBench-CNtest (Liu et al., 2023d)\\ MMBench-V1.1-ENtest (Liu et al., 2023d)\\ MMStar (Chen et al., 2024c)\\ MME_{sum} (Fu et al., 2023)\\ MuirBench (Wang et al., 2024a)\\ BLINK_{val} (Fu et al., 2024c)\\ CRPE_{relation} (Wang et al., 2024h)\\ HallBenchavg (Guan et al., 2023)\\ MITVQA (Tang et al., 2024)\\ MRelaWorldQAvg (X.AI, 2024)\\ MME-RealWorlden (Zhang et al., 2024f)\\ MARE-RealWorlden (Zhang et$	69.5 Chen et al. (2024d) 2494 Chen et al. (2024d) 63.5 Chen et al. (2024d) 63.8 Chen et al. (2024d) 78.8 Chen et al. (2024d) 78.1 Wang et al. (2024d) 78.7 Chen et al. (2024d) 78.7 Chen et al. (2024d)	82.6 83.5 80.9 65.1 1920 - 55.5 25.7 60.1 51.6	54.2 83.4 82.1 83.1 64.7 2328 68.0 68.0 76.6 55.0 27.8 75.4 45.2	45.6 88.3 88.5 87.4 69.5 2494 63.5 63.8 78.8 57.4 31.9 78.7 62.9	46.8 86.9 86.7 86.1 68.3 2483 - - - 58.1 30.9 77.8	51.3 88.6 87.9 88.4 70.8 2448 70.7 64.4 79.2 55.2 31.7 75.7 63.2	36.8 83.5 83.4 82.6 63.9 2347 59.6 56.4 76.4 52.9 29.2 68.5 57.4	28.9 79.1 78.1 77.4 55.9 2157 47.6 73.6 46.3 24.8 65.4 53.1
MMVet _{turbo} (Yu et al., 2024) MM-MT-Bench (Agrawal et al., 2024)	74.0 Wang et al. (2024f) 7.4 Agrawal et al. (2024)	70.1 7.5	69.1 7.72	72.3	74.0 6.59	76.2 7.6	67.1 6.3	61.8 5.7

Table 3: Performance of Qwen2.5-VL and State-of-the-art.

The experimental section evaluates the performance of Qwen2.5-VL across a variety of datasets, comparing it with state-of-the-art models such as Claude-3.5-Sonnet-0620 (Anthropic, 2024a), GPT-4o-0513 (Ope-nAI, 2024), InternVL2.5 (Chen et al., 2024d), and different sizes of Qwen2-VL (Wang et al., 2024e). In college-level problems, Qwen2.5-VL-72B achieves a score of 70.2 on MMMU (Yue et al., 2023). For MMMU-Pro (Yue et al., 2024), Qwen2.5-VL-72B scores 51.1, surpassing the previous open-source state-of-the-art models and achieving performance comparable to GPT-4o.

In math-related tasks, Qwen2.5-VL-72B demonstrates strong capabilities. On MathVista (Lu et al., 2024), it achieves a score of 74.8, outperforming the previous open-source state-of-the-art score of 72.3. For MATH-Vision (Wang et al., 2024d), Qwen2.5-VL-72B scores 38.1, while MathVerse (Zhang et al., 2024c) achieves 57.6, both showing competitive results compared to other leading models.

For general visual question answering, Qwen2.5-VL-72B excels across multiple benchmarks. On MMbench-EN (Liu et al., 2023d), it achieves a score of 88.6, slightly surpassing the previous best score of 88.3. The model also performs well in MuirBench (Wang et al., 2024a) with a score of 70.7 and BLINK (Fu et al., 2024c) with 64.4. In the multilingual capability evaluation of MTVQA (Tang et al., 2024), Qwen2.5-VL-72B achieves a score of 31.7, showcasing its powerful multilingual text recognition abilities. In subjective evaluations such as MMVet (Yu et al., 2024) and MM-MT-Bench (Agrawal et al., 2024), Qwen2.5-VL-72B scores 76.2 and 7.6, respectively, demonstrating excellent natural conversational experience and user satisfaction.

3.2 Performance on Pure Text Tasks

To critically evaluate the performance of instruction-tuned models on pure text tasks, as illustrated in Table 4, we selected several representative benchmarks to assess the model's capabilities across a variety of domains, including general tasks (Wang et al., 2024; Gema et al., 2024; White et al., 2024), mathematics and science tasks (Rein et al., 2023; Hendrycks et al., 2021; Cobbe et al., 2021), coding tasks (Chen et al., 2021; Cassano et al., 2023), and alignment task (Zhou et al., 2023). We compared Qwen2.5-VL with several large language models (LLMs) of similar size. The results demonstrate that Qwen2.5-VL not only achieves state-of-the-art (SoTA) performance on multimodal tasks but also exhibits leading performance on pure text tasks, showcasing its versatility and robustness across diverse evaluation criteria.

Datasets	Llama-3.1-70B	Llama-3.1-405B	Qwen2-72B	Qwen2.5-72B	Qwen2.5-VL-72B
		General	Tasks		
MMLU-Pro	66.4	73.3	64.4	71.1	71.2
MMLU-redux	83.0	86.2	81.6	86.8	85.9
LiveBench-0831	46.6	53.2	41.5	52.3	57.0
		Mathematics &	Science Tasks		
GPQA	46.7	51.1	42.4	49.0	49.0
MATH	68.0	73.8	69.0	83.1	83.0
GSM8K	95.1	96.8	93.2	95.8	95.3
		Coding	Tasks		
HumanEval	80.5	89.0	86.0	86.6	87.8
MultiPL-E	68.2	73.5	69.2	75.1	79.5
		Alignmen	ıt Tasks		
IFEval	83.6	86.0	77.6	84.1	86.3

Table 4: Performance on pure text tasks of the 70B+ Instruct models and Qwen2.5-VL.

3.3 Quantitative Results

3.3.1 General Visual Question Answering

To comprehensively evaluate the model's capabilities in general visual question answering (VQA) and dialogue, we conducted extensive experiments across a diverse range of datasets. As illustrated in Table 3, Qwen2.5-VL demonstrates state-of-the-art performance in various VQA tasks, subjective evaluations, multilingual scenarios, and multi-image questions. Specifically, it excels on benchmark datasets such as MMBench series (Liu et al., 2023d), MMStar (Chen et al., 2024c), MME (Fu et al., 2023), MuirBench (Wang et al., 2024a), BLINK(Fu et al., 2024c), CRPE (Wang et al., 2024h), HallBench (Guan et al., 2023), MTVQA (Tang et al., 2024), MME-RealWorld (Zhang et al., 2024f), MMVet (Yu et al., 2024), and MM-MT-Bench (Agrawal et al., 2024).

In the domain of visual detail comprehension and reasoning, Qwen2.5-VL-72B achieves an accuracy of 88.4% on the MMBench-EN-V1.1 dataset, surpassing previous state-of-the-art models such as InternVL2.5 (78B) and Claude-3.5 Sonnet-0620. Similarly, on the MMStar dataset, Qwen2.5-VL attains a score of 70.8%, outperforming other leading models in this benchmark. These results underscore the model's robustness and adaptability across diverse linguistic contexts.

Furthermore, in high-resolution real-world scenarios, specifically on the MME-RealWorld benchmark, Qwen2.5-VL demonstrates state-of-the-art performance with a score of 63.2, showcasing its broad adaptability to realistic environments. Additionally, in multi-image understanding tasks evaluated on the MuirBench dataset, Qwen2.5-VL achieves a leading score of 70.7, further highlighting its superior generalization capabilities. Collectively, these results illustrate the strong versatility and effectiveness of Qwen2.5-VL in addressing general-purpose visual question answering (VQA) tasks across various scenarios.

Notably, even the smaller-scale versions of Qwen2.5-VL, specifically Qwen2.5-VL-7B and Qwen2.5-VL-3B, exhibit highly competitive performance. For instance, on the MMStar dataset, Qwen2.5-VL-7B achieves 63.9%, while Qwen2.5-VL-3B scores 55.9%. This demonstrates that Qwen2.5-VL's architecture is not only powerful but also scalable, maintaining strong performance even with fewer parameters.

3.3.2 Document Understanding and OCR

We evaluated our models across a diverse range of OCR, chart, and document understanding benchmarks. Table 5 demonstrates the performance comparison between Qwen2.5-VL models and toptier models on following OCR-related benchmarks: AI2D (Kembhavi et al., 2016), TextVQA (Singh et al., 2019), DocVQA (Mathew et al., 2021b), InfoVQA (Mathew et al., 2021a), ChartQA (Masry et al., 2022), CharXiv (Wang et al., 2024k), SEED-Bench-2-Plus (Li et al., 2024b), OCRBench (Liu et al., 2023e), OCRBench_v2 (Fu et al., 2024b), CC-OCR (Yang et al., 2024b), OmniDocBench (Ouyang et al., 2024), VCR (Zhang et al., 2024e).

For OCR-related parsing benchmarks on element parsing for multi-scene, multilingual, and various built-in (handwriting, tables, charts, chemical formulas, and mathematical expressions) documents,

as CC-OCR and OmniDocBench, Qwen2.5-VL-72B model sets the new state-of-the-art due to curated training data and excellent capability of LLM models.

For OCR-related understanding benchmarks for scene text, chart, diagram and document, Qwen2.5-VL models achieve impressive performance with good understanding abilities. Notably, on composite OCR-related understanding benchmarks as OCRBench, InfoVQA which focusing on infographics, and SEED-Bench-2-Plus covering text-rich scenarios including charts, maps, and webs, Qwen2.5-VL-72B achieves remarkable results, significantly outperforming strong competitors such as InternVL2.5-78B.

Furthermore, for OCR-related comprehensive benchmarks as OCRBench_v2 including a wide range of OCR-related parsing and understanding tasks, top performance is also achieved by Qwen2.5-VL models, largely exceeding best model Gemini 1.5-Pro by 9.6% and 20.6% for English and Chinese track respectively.

Datasets	Claude-3.5 Sonnet	Gemini 1.5 Pro	GPT 40	InternVL2.5 78B	Qwen2.5-VL 72B	Qwen2.5-VL 7B	Qwen2.5-VL 3B
		OC	R-related Pars	ing Tasks			
CC-OCR	62.5	73.0	66.9	64.7	79.8	77.8	74.5
$OmniDocBench_{editen/zh} {\downarrow}$	0.330/0.381	0.230/ 0.281	0.265/0.435	0.275/0.324	0.226 /0.324	0.308/0.398	0.409/0.543
		OCR-r	elated Underst	anding Tasks			
AI2D _{w. M.}	81.2	88.4	84.6	89.1	88.7	83.9	81.6
TextVQA _{val}	76.5	78.8	77.4	83.4	83.5	84.9	79.3
DocVQA _{test}	95.2	93.1	91.1	95.1	96.4	95.7	93.9
InfoVQA _{test}	74.3	81.0	80.7	84.1	87.3	82.6	77.1
ChartQA _{test Avg.}	90.8	87.2	86.7	88.3	89.5	87.3	84.0
CharXiv _{RO/DO}	60.2 /84.3	43.3/72.0	47.1/84.5	42.4/82.3	49.7/ 87.4	42.5/73.9	31.3/58.6
SEED-Bench-2-Plus	71.7	70.8	72.0	71.3	73.0	70.4	67.6
OCRBench	788	754	736	854	885	864	797
VCR _{En-Hard-EM}	41.7	28.1	73.2	-	79.8	80.5	37.5
		OCR-r	elated Comprei	hensive Tasks			
OCRBench_v2 _{en/zh}	45.2/39.6	51.9/43.1	46.5/32.2	49.8/52.1	61.5/63.7	56.3/57.2	54.3/52.1

Table 5: Performance of Qwen2.5-VL and other models on OCR, chart, and document understanding benchmarks.

3.3.3 Spatial Understanding

Understanding spatial relationships is crucial for developing AI models that can interpret and interact with the world as humans do. In Large Vision-Language Models, visual grounding allows for the precise localization and identification of specific objects, regions, or elements within an image based on natural language queries or descriptions. This capability transcends traditional object detection by establishing a semantic relationship between visual content and linguistic context, facilitating more nuanced and contextually aware visual reasoning. We evaluated Qwen2.5-VL's grounding capabilities on the referring expression comprehension benchmarks (Kazemzadeh et al., 2014; Mao et al., 2016), object detection in the wild (Li et al., 2022b), self-curated point grounding benchmark, and CountBench (Paiss et al., 2023).

We compare Qwen2.5-VL's visual grounding capabilities with other leading LVLMs including Gemini, Grounding-DINO (Liu et al., 2023c), Molmo (Deitke et al., 2024), and InternVL2.5.

Qwen2.5-VL achieves leading performance across different benchmarks from box-grounding, and pointgrounding to counting. By equipping Qwen2.5-VL with both box and point-grounding capability, it is able to understand, locate, and reason on the very details of certain parts of an image. For openvocabulary object detection, Qwen2.5-VL achieves a good performance of 43.1 mAP on ODinW-13, surpassing most LVLMs and quickly narrowing the gap between generalist models and specialist models. In addition, Qwen2.5-VL unlocks the point-based grounding ability so that it could precisely locate the very details of a certain object, which was difficult to represent by a bounding box in the past. Qwen2.5-VL's counting ability also makes great progress, achieving a leading accuracy of 93.6 on CountBench with Qwen2.5-VL-72B using a "detect then count"-style prompt.

3.3.4 Video Understanding and Grounding

We assessed our models across a diverse range of video understanding and grounding tasks, utilizing benchmarks that include videos ranging from a few seconds to several hours in length. Table 8 demonstrates the performance comparison between Qwen2.5-VL models and top-tier proprietary models on the following video benchmarks: Video-MME (Fu et al., 2024a), Video-MMMU (Hu et al., 2025), MMVU (Zhao

Datasets	Gemini 1.5 Pro	Grounding DINO	Molmo 72B	InternVL2.5 78B	Qwen2.5-VL 72B	Qwen2.5-VL 7B	Qwen2.5-VL 3B
Refcoco _{val}	73.2	90.6	-	93.7	92.7	90.0	89.1
Refcoco _{testA}	72.9	93.2	-	95.6	94.6	92.5	91.7
Refcoco _{testB}	74.6	88.2	-	92.5	89.7	85.4	84.0
Refcoco+ _{val}	62.5	88.2	-	90.4	88.9	84.2	82.4
Refcoco+ $_{testA}$	63.9	89.0	-	94.7	92.2	89.1	88.0
Refcoco+ $_{testB}$	65.0	75.9	-	86.9	83.7	76.9	74.1
Refcocog _{val}	75.2	86.1	-	92.7	89.9	87.2	85.2
Refcocog _{test}	76.2	87.0	-	92.2	90.3	87.2	85.7
ODinW	36.7	55.0	-	31.7	43.1	37.3	37.5
PointGrounding	-	-	69.2	-	67.5	67.3	58.3

Table 6: Performance of Qwen2.5-VL and other models on grounding.

Table 7: Performance of Qwen2.5-VL and other models on counting.

Datasets	Gemini 1.5-Pro	GPT-40	Claude-3.5 Sonnet	Molmo-72b	InternVL2.5-78B	Qwen2.5-VL-72B
CountBench	85.5	87.9	89.7	91.2	72.1	93.6

et al., 2025), MVBench (Li et al., 2024d), MMBench-Video (Fang et al., 2024), LongVideoBench (Wu et al., 2024a), EgoSchema (Mangalam et al., 2023), PerceptionTest (Patraucean et al., 2024), MLVU (Zhou et al., 2024), LVBench (Wang et al., 2024g), TempCompass (Liu et al., 2024c) and Charades-STA (Gao et al., 2017). Notably, on LVBench and MLVU, which evaluate long-form video understanding capabilities through question-answering tasks, Qwen2.5-VL-72B achieves remarkable results, significantly outperforming strong competitors such as GPT-4o.

By utilizing the proposed synchronized MRoPE, Qwen2.5-VL enhances its capabilities in time-sensitive video understanding, featuring improved timestamp referencing, temporal grounding, dense captioning, and additional functionalities. On the Charades-STA dataset, which assesses the capability to accurately localize events or activities with precise timestamps, Qwen2.5-VL-72B achieves an impressive mIoU score of 50.9, thereby surpassing the performance of GPT-40. For all evaluated benchmarks, we capped the maximum number of frames analyzed per video at 768, with the total number of video tokens not exceeding 24,576.

Datasets	Gemini 1.5-Pro	GPT-40	Qwen2.5-VL-72B	Qwen2.5-VL-7B	Qwen2.5-VL-3B
		Video Un	derstanding Tasks		
Video-MME _{w/o sub.}	75.0	71.9	73.3	65.1	61.5
Video-MME _{w sub.}	81.3	77.2	79.1	71.6	67.6
Video-MMMU	53.9	61.2	60.2	47.4	-
MMVU _{val}	65.4	67.4	62.9	50.1	-
MVBench	60.5	64.6	70.4	69.6	67.0
MMBench-Video	1.30	1.63	2.02	1.79	1.63
LongVideoBench _{val}	64.0	66.7	60.7	56.0	54.2
LVBench	33.1	30.8	47.3	45.3	43.3
EgoSchema _{test}	71.2	72.2	76.2	65.0	64.8
PerceptionTest _{test}	-	-	73.2	70.5	66.9
MLVU _{M-Avg}	-	64.6	74.6	70.2	68.2
TempCompass _{Avg}	67.1	73.8	74.8	71.7	64.4
		Video C	Frounding Tasks		
Charades-STA _{mIoU}	-	35.7	50.9	43.6	38.8

Table 8: Performance of Qwen2.5-VL and other models on video benchmarks.

3.3.5 Agent

Agent capabilities within multimodal models are crucial for enabling these models to effectively interact with real-world devices. We assess the agent capabilities of Qwen2.5-VL through various aspects. The UI

elements grounding is evaluated by ScreenSpot (Cheng et al., 2024) and ScreenSpot Pro (Li et al., 2025a). Offline evaluations are conducted on Android Control (Li et al., 2024f), while online evaluations are performed on platforms including AndroidWorld (Rawles et al., 2024), MobileMiniWob++ (Rawles et al., 2024), and OSWorld (Xie et al., 2025). We compare the performance of Qwen2.5-VL-72B againsts other prominent models, such as GPT-4o (OpenAI, 2024), Gemini 2.0 (Deepmind, 2024), Claude (Anthropic, 2024b), Aguvis-72B (Xu et al., 2024), and Qwen2-VL-72B (Wang et al., 2024e). The results are demonstrated in Table 9.

Benchmarks	GPT-40	Gemini 2.0	Claude	Aguvis-72B	Qwen2-VL-72B	Qwen2.5-VL-72B
ScreenSpot	18.1	84.0	83.0	89.2	-	87.1
ScreenSpot Pro	-	-	17.1	23.6	1.6	43.6
Android Control High _{EM}	20.8	28.5	12.5	66.4	59.1	67.36
Android Control Low _{EM}	19.4	60.2	19.4	84.4	59.2	93.7
AndroidWorld _{SR}	34.5% (SoM)	26% (SoM)	27.9%	26.1%	6% (SoM)	35%
MobileMiniWob++ _{SR}	61%	42% (SoM)	61% (SoM)	66%	50% (SoM)	68%
OSWorld	5.03	4.70	14.90	10.26	2.42	8.83

The performance of Qwen2.5-VL-72B demonstrates exceptional advancements across GUI grounding benchmarks. It achieves 87.1% accuracy on ScreenSpot, competing strongly with Gemini 2.0 (84.0%) and Claude (83.0%), while notably setting a new standard on ScreenSpot Pro with 43.6% accuracy - far surpassing both Aguvis-72B (23.6%) and its foundation Qwen2-VL-72B (1.6%). Leveraging these superior grounding capabilities, Qwen2.5-VL-72B significantly outperforms baselines across all offline evaluation benchmarks with a large gap. In online evaluation, some baselines have difficulty completing tasks due to limited grounding capabilities. Thus, we apply the Set-of-Mark (SoM) to the inputs of these models. The results show that Qwen2.5-VL-72B can outperform the baselines on AndroidWorld and MobileMiniWob++ and achieve comparable performance on OSWorld in online evaluation without auxiliary marks. This observation suggests that Qwen2.5-VL-72B is able to function as an agent in real and dynamic environments.

4 Conclusion

We present Qwen2.5-VL, a state-of-the-art vision-language model series that achieves significant advancements in multimodal understanding and interaction. With enhanced capabilities in visual recognition, object localization, document parsing, and long-video comprehension, Qwen2.5-VL excels in both static and dynamic tasks. Its native dynamic-resolution processing and absolute time encoding enable robust handling of diverse inputs, while Window Attention reduces computational overhead without sacrificing resolution fidelity. Qwen2.5-VL caters to a wide range of applications, from edge AI to high-performance computing. The flagship Qwen2.5-VL-72B matches or surpasses leading models like GPT-40, and Claude 3.5 Sonnet, particularly in document and diagram understanding, while maintaining strong performance on pure text tasks. The smaller Qwen2.5-VL-7B and Qwen2.5-VL-3B variants outperform similarly sized competitors, offering efficiency and versatility. Qwen2.5-VL sets a new benchmark for vision-language models, demonstrating exceptional generalization and task execution across domains. Its innovations pave the way for more intelligent and interactive systems, bridging perception and real-world application.

5 Authors

Core Contributors: Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, Humen Zhong, Yuanzhi Zhu, Mingkun Yang, Zhaohai Li, Jianqiang Wan, Pengfei Wang, Wei Ding, Zheren Fu, Yiheng Xu, Jiabo Ye, Xi Zhang, Tianbao Xie, Zesen Cheng, Hang Zhang, Zhibo Yang, Haiyang Xu, Junyang Lin

Contributors¹: An Yang, Binyuan Hui, Bowen Yu, Chen Cheng, Dayiheng Liu, Fan Hong, Fei Huang, Jiawei Liu, Jin Xu, Jianhong Tu, Jianyuan Zeng, Jie Zhang, Jinkai Wang, Jianwei Zhang, Jingren Zhou, Kexin Yang, Mei Li, Ming Yan, Na Ni, Rui Men, Songtao Jiang, Xiaodong Deng, Xiaoming Huang, Ximing Zhou, Xingzhang Ren, Yang Fan, Yichang Zhang, Yikai Zhu, Yuqiong Liu, Zhifang Guo

¹Alphabetical order.

References

- Pravesh Agrawal, Szymon Antoniak, Emma Bou Hanna, Baptiste Bout, Devendra Chaplot, Jessica Chudnovsky, Diogo Costa, Baudouin De Monicault, Saurabh Garg, Theophile Gervet, et al. Pixtral 12b. *arXiv preprint arXiv:*2410.07073, 2024.
- Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katherine Millican, Malcolm Reynolds, et al. Flamingo: a visual language model for few-shot learning. In *NeurIPS*, 2022.
- Anthropic. Claude 3.5 sonnet, 2024a. URL https://www.anthropic.com/news/claude-3-5-sonnet.
- Anthropic. Introducing computer use, a new claude 3.5 sonnet, and claude 3.5 haiku, 2024b. URL https://www.anthropic.com/news/3-5-models-and-computer-use.
- Federico Cassano, John Gouwar, Daniel Nguyen, Sydney Nguyen, Luna Phipps-Costin, Donald Pinckney, Ming-Ho Yee, Yangtian Zi, Carolyn Jane Anderson, Molly Q. Feldman, Arjun Guha, Michael Greenberg, and Abhinav Jangda. MultiPL-E: A scalable and polyglot approach to benchmarking neural code generation. *IEEE Trans. Software Eng.*, 49(7):3675–3691, 2023.
- Guiming Hardy Chen, Shunian Chen, Ruifei Zhang, Junying Chen, Xiangbo Wu, Zhiyi Zhang, Zhihong Chen, Jianquan Li, Xiang Wan, and Benyou Wang. Allava: Harnessing gpt4v-synthesized data for a lite vision-language model. *arXiv preprint arXiv:2402.11684*, 2024a.
- Jiacheng Chen, Tianhao Liang, Sherman Siu, Zhengqing Wang, Kai Wang, Yubo Wang, Yuansheng Ni, Wang Zhu, Ziyan Jiang, Bohan Lyu, et al. Mega-bench: Scaling multimodal evaluation to over 500 real-world tasks. *arXiv preprint arXiv:2410.10563*, 2024b.
- Lin Chen, Jinsong Li, Xiaoyi Dong, Pan Zhang, Yuhang Zang, Zehui Chen, Haodong Duan, Jiaqi Wang, Yu Qiao, Dahua Lin, et al. Are we on the right way for evaluating large vision-language models? *arXiv*:2403.20330, 2024c.
- Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Pondé de Oliveira Pinto, Jared Kaplan, Harrison Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, Alex Ray, Raul Puri, Gretchen Krueger, Michael Petrov, Heidy Khlaaf, Girish Sastry, Pamela Mishkin, Brooke Chan, Scott Gray, Nick Ryder, Mikhail Pavlov, Alethea Power, Lukasz Kaiser, Mohammad Bavarian, Clemens Winter, Philippe Tillet, Felipe Petroski Such, Dave Cummings, Matthias Plappert, Fotios Chantzis, Elizabeth Barnes, Ariel Herbert-Voss, William Hebgen Guss, Alex Nichol, Alex Paino, Nikolas Tezak, Jie Tang, Igor Babuschkin, Suchir Balaji, Shantanu Jain, William Saunders, Christopher Hesse, Andrew N. Carr, Jan Leike, Joshua Achiam, Vedant Misra, Evan Morikawa, Alec Radford, Matthew Knight, Miles Brundage, Mira Murati, Katie Mayer, Peter Welinder, Bob McGrew, Dario Amodei, Sam McCandlish, Ilya Sutskever, and Wojciech Zaremba. Evaluating large language models trained on code. *CoRR*, abs/2107.03374, 2021.
- Zhe Chen, Jiannan Wu, Wenhai Wang, Weijie Su, Guo Chen, Sen Xing, Muyan Zhong, Qinglong Zhang, Xizhou Zhu, Lewei Lu, Bin Li, Ping Luo, Tong Lu, Yu Qiao, and Jifeng Dai. Internvl: Scaling up vision foundation models and aligning for generic visual-linguistic tasks. *arXiv preprint arXiv:2312.14238*, 2023.
- Zhe Chen, Weiyun Wang, Yue Cao, Yangzhou Liu, Zhangwei Gao, Erfei Cui, Jinguo Zhu, Shenglong Ye, Hao Tian, Zhaoyang Liu, et al. Expanding performance boundaries of open-source multimodal models with model, data, and test-time scaling. *arXiv preprint arXiv:2412.05271*, 2024d.
- Kanzhi Cheng, Qiushi Sun, Yougang Chu, Fangzhi Xu, Yantao Li, Jianbing Zhang, and Zhiyong Wu. Seeclick: Harnessing gui grounding for advanced visual gui agents. *arXiv preprint arXiv:2401.10935*, 2024.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems. *CoRR*, abs/2110.14168, 2021.
- Yann N. Dauphin, Angela Fan, Michael Auli, and David Grangier. Language modeling with gated convolutional networks. In *ICML*, volume 70 of *Proceedings of Machine Learning Research*, pp. 933–941. PMLR, 2017.
- Google Deepmind. Introducing gemini 2.0: our new ai model for the agentic era, 2024. URL https://blog.google/technology/google-deepmind/google-gemini-ai-update-december-2024/.

- DeepSeek-AI, Aixin Liu, Bei Feng, Bing Xue, Bingxuan Wang, Bochao Wu, Chengda Lu, Chenggang Zhao, Chengqi Deng, Chenyu Zhang, Chong Ruan, Damai Dai, Daya Guo, Dejian Yang, Deli Chen, Dongjie Ji, Erhang Li, Fangyun Lin, Fucong Dai, Fuli Luo, Guangbo Hao, Guanting Chen, Guowei Li, H. Zhang, Han Bao, Hanwei Xu, Haocheng Wang, Haowei Zhang, Honghui Ding, Huajian Xin, Huazuo Gao, Hui Li, Hui Qu, J. L. Cai, Jian Liang, Jianzhong Guo, Jiaqi Ni, Jiashi Li, Jiawei Wang, Jin Chen, Jingchang Chen, Jingyang Yuan, Junjie Qiu, Junlong Li, Junxiao Song, Kai Dong, Kai Hu, Kaige Gao, Kang Guan, Kexin Huang, Kuai Yu, Lean Wang, Lecong Zhang, Lei Xu, Leyi Xia, Liang Zhao, Litong Wang, Liyue Zhang, Meng Li, Miaojun Wang, Mingchuan Zhang, Minghua Zhang, Minghui Tang, Mingming Li, Ning Tian, Panpan Huang, Peiyi Wang, Peng Zhang, Qiancheng Wang, Qihao Zhu, Qinyu Chen, Qiushi Du, R. J. Chen, R. L. Jin, Ruiqi Ge, Ruisong Zhang, Ruizhe Pan, Runji Wang, Runxin Xu, Ruoyu Zhang, Ruyi Chen, S. S. Li, Shanghao Lu, Shangyan Zhou, Shanhuang Chen, Shaoqing Wu, Shengfeng Ye, Shengfeng Ye, Shirong Ma, Shiyu Wang, Shuang Zhou, Shuiping Yu, Shunfeng Zhou, Shuting Pan, T. Wang, Tao Yun, Tian Pei, Tianyu Sun, W. L. Xiao, and Wangding Zeng. Deepseek-v3 technical report. *CoRR*, abs/2412.19437, 2024. doi: 10.48550/ARXIV.2412.19437.
- Matt Deitke, Christopher Clark, Sangho Lee, Rohun Tripathi, Yue Yang, Jae Sung Park, Mohammadreza Salehi, Niklas Muennighoff, Kyle Lo, Luca Soldaini, et al. Molmo and pixmo: Open weights and open data for state-of-the-art multimodal models. *arXiv preprint arXiv:2409.17146*, 2024.
- Xinyu Fang, Kangrui Mao, Haodong Duan, Xiangyu Zhao, Yining Li, Dahua Lin, and Kai Chen. Mmbench-video: A long-form multi-shot benchmark for holistic video understanding. *arXiv preprint arXiv*:2406.14515, 2024.
- Chaoyou Fu, Peixian Chen, Yunhang Shen, Yulei Qin, Mengdan Zhang, Xu Lin, Zhenyu Qiu, Wei Lin, Jinrui Yang, Xiawu Zheng, et al. Mme: A comprehensive evaluation benchmark for multimodal large language models. *arXiv:2306.13394*, 2023.
- Chaoyou Fu, Yuhan Dai, Yondong Luo, Lei Li, Shuhuai Ren, Renrui Zhang, Zihan Wang, Chenyu Zhou, Yunhang Shen, Mengdan Zhang, et al. Video-mme: The first-ever comprehensive evaluation benchmark of multi-modal llms in video analysis. *arXiv*:2405.21075, 2024a.
- Ling Fu, Biao Yang, Zhebin Kuang, Jiajun Song, Yuzhe Li, Linghao Zhu, Qidi Luo, Xinyu Wang, Hao Lu, Mingxin Huang, Zhang Li, Guozhi Tang, Bin Shan, Chunhui Lin, Qi Liu, Binghong Wu, Hao Feng, Hao Liu, Can Huang, Jingqun Tang, Wei Chen, Lianwen Jin, Yuliang Liu, and Xiang Bai. Ocrbench v2: An improved benchmark for evaluating large multimodal models on visual text localization and reasoning, 2024b. URL https://arxiv.org/abs/2501.00321.
- Xingyu Fu, Yushi Hu, Bangzheng Li, Yu Feng, Haoyu Wang, Xudong Lin, Dan Roth, Noah A Smith, Wei-Chiu Ma, and Ranjay Krishna. Blink: Multimodal large language models can see but not perceive. In *European Conference on Computer Vision*, pp. 148–166. Springer, 2024c.
- Samir Yitzhak Gadre, Gabriel Ilharco, Alex Fang, Jonathan Hayase, Georgios Smyrnis, Thao Nguyen, Ryan Marten, Mitchell Wortsman, Dhruba Ghosh, Jieyu Zhang, et al. Datacomp: In search of the next generation of multimodal datasets. *arXiv*:2304.14108, 2023.
- Jiyang Gao, Chen Sun, Zhenheng Yang, and Ram Nevatia. Tall: Temporal activity localization via language query. In *Proceedings of the IEEE international conference on computer vision*, pp. 5267–5275, 2017.
- Aryo Pradipta Gema, Joshua Ong Jun Leang, Giwon Hong, Alessio Devoto, Alberto Carlo Maria Mancino, Rohit Saxena, Xuanli He, Yu Zhao, Xiaotang Du, Mohammad Reza Ghasemi Madani, et al. Are we done with mmlu? *CoRR*, abs/2406.04127, 2024.
- Golnaz Ghiasi, Yin Cui, Aravind Srinivas, Rui Qian, Tsung-Yi Lin, Ekin D Cubuk, Quoc V Le, and Barret Zoph. Simple copy-paste is a strong data augmentation method for instance segmentation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 2918–2928, 2021.
- Tianrui Guan, Fuxiao Liu, Xiyang Wu, Ruiqi Xian, Zongxia Li, Xiaoyu Liu, Xijun Wang, Lichang Chen, Furong Huang, Yaser Yacoob, Dinesh Manocha, and Tianyi Zhou. Hallusionbench: An advanced diagnostic suite for entangled language hallucination & visual illusion in large vision-language models. *arXiv:2310.14566*, 2023.
- Jarvis Guo, Tuney Zheng, Yuelin Bai, Bo Li, Yubo Wang, King Zhu, Yizhi Li, Graham Neubig, Wenhu Chen, and Xiang Yue. Mammoth-vl: Eliciting multimodal reasoning with instruction tuning at scale. *arXiv preprint arXiv:*2412.05237, 2024.

- Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. Measuring mathematical problem solving with the MATH dataset. In *NeurIPS Datasets and Benchmarks*, 2021.
- Kairui Hu, Penghao Wu, Fanyi Pu, Wang Xiao, Yuanhan Zhang, Xiang Yue, Bo Li, and Ziwei Liu. Videommmu: Evaluating knowledge acquisition from multi-discipline professional videos. *arXiv preprint arXiv*:2501.13826, 2025.
- Sahar Kazemzadeh, Vicente Ordonez, Mark Matten, and Tamara Berg. Referitgame: Referring to objects in photographs of natural scenes. In *EMNLP*, 2014.
- Aniruddha Kembhavi, Mike Salvato, Eric Kolve, Minjoon Seo, Hannaneh Hajishirzi, and Ali Farhadi. A diagram is worth a dozen images. In *ECCV*, 2016.
- Alexander Kirillov, Eric Mintun, Nikhila Ravi, Hanzi Mao, Chloe Rolland, Laura Gustafson, Tete Xiao, Spencer Whitehead, Alexander C Berg, Wan-Yen Lo, et al. Segment anything. In *ICCV*, 2023.
- Byung-Kwan Lee, Beomchan Park, Chae Won Kim, and Yong Man Ro. Moai: Mixture of all intelligence for large language and vision models. In *European Conference on Computer Vision*, pp. 273–302. Springer, 2024.
- Bo Li, Peiyuan Zhang, Jingkang Yang, Yuanhan Zhang, Fanyi Pu, and Ziwei Liu. Otterhd: A high-resolution multi-modality model. *arXiv:2311.04219*, 2023a.
- Bo Li, Yuanhan Zhang, Dong Guo, Renrui Zhang, Feng Li, Hao Zhang, Kaichen Zhang, Peiyuan Zhang, Yanwei Li, Ziwei Liu, et al. Llava-onevision: Easy visual task transfer. *arXiv preprint arXiv*:2408.03326, 2024a.
- Bohao Li, Yuying Ge, Yi Chen, Yixiao Ge, Ruimao Zhang, and Ying Shan. Seed-bench-2-plus: Benchmarking multimodal large language models with text-rich visual comprehension. *arXiv preprint arXiv:*2404.16790, 2024b.
- Dongxu Li, Yudong Liu, Haoning Wu, Yue Wang, Zhiqi Shen, Bowen Qu, Xinyao Niu, Guoyin Wang, Bei Chen, and Junnan Li. Aria: An open multimodal native mixture-of-experts model. *arXiv preprint arXiv:2410.05993*, 2024c.
- Junnan Li, Dongxu Li, Caiming Xiong, and Steven C. H. Hoi. Blip: Bootstrapping language-image pre-training for unified vision-language understanding and generation. In *ICML*, 2022a.
- Junnan Li, Dongxu Li, Silvio Savarese, and Steven Hoi. Blip-2: Bootstrapping language-image pre-training with frozen image encoders and large language models. *arXiv:2301.12597*, 2023b.
- Kaixin Li, Ziyang Meng, Hongzhan Lin, Ziyang Luo, Yuchen Tian, Jing Ma, Zhiyong Huang, and Tat-Seng Chua. Screenspot-pro: Gui grounding for professional high-resolution computer use, 2025a. URL https://likaixin2000.github.io/papers/ScreenSpot_Pro.pdf. Preprint.
- Kunchang Li, Yali Wang, Yinan He, Yizhuo Li, Yi Wang, Yi Liu, Zun Wang, Jilan Xu, Guo Chen, Ping Luo, et al. Mvbench: A comprehensive multi-modal video understanding benchmark. In *CVPR*, 2024d.
- Liunian Harold Li, Pengchuan Zhang, Haotian Zhang, Jianwei Yang, Chunyuan Li, Yiwu Zhong, Lijuan Wang, Lu Yuan, Lei Zhang, Jenq-Neng Hwang, et al. Grounded language-image pre-training. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10965–10975, 2022b.
- Qingyun Li, Zhe Chen, Weiyun Wang, Wenhai Wang, Shenglong Ye, Zhenjiang Jin, Guanzhou Chen, Yinan He, Zhangwei Gao, Erfei Cui, et al. Omnicorpus: An unified multimodal corpus of 10 billion-level images interleaved with text. *arXiv preprint arXiv:2406.08418*, 2024e.
- Wei Li, William Bishop, Alice Li, Chris Rawles, Folawiyo Campbell-Ajala, Divya Tyamagundlu, and Oriana Riva. On the effects of data scale on computer control agents. *arXiv preprint arXiv:2406.03679*, 2024f.
- Yadong Li, Haoze Sun, Mingan Lin, Tianpeng Li, Guosheng Dong, Tao Zhang, Bowen Ding, Wei Song, Zhenglin Cheng, Yuqi Huo, et al. Baichuan-omni technical report. *arXiv preprint arXiv:2410.08565*, 3(7), 2024g.
- Yadong Li, Jun Liu, Tao Zhang, Song Chen, Tianpeng Li, Zehuan Li, Lijun Liu, Lingfeng Ming, Guosheng Dong, Da Pan, et al. Baichuan-omni-1.5 technical report. *arXiv preprint arXiv:2501.15368*, 2025b.

- Yunxin Li, Shenyuan Jiang, Baotian Hu, Longyue Wang, Wanqi Zhong, Wenhan Luo, Lin Ma, and Min Zhang. Uni-moe: Scaling unified multimodal llms with mixture of experts. *arXiv preprint arXiv*:2405.11273, 2024h.
- Zhang Li, Biao Yang, Qiang Liu, Zhiyin Ma, Shuo Zhang, Jingxu Yang, Yabo Sun, Yuliang Liu, and Xiang Bai. Monkey: Image resolution and text label are important things for large multi-modal models. *arXiv:2311.06607*, 2023c.
- Yuxuan Liang, Xu Li, Xiaolei Chen, Haotian Chen, Yi Zheng, Chenghang Lai, Bin Li, and Xiangyang Xue. Global semantic-guided sub-image feature weight allocation in high-resolution large vision-language models. *arXiv preprint arXiv:2501.14276*, 2025.
- Ji Lin, Hongxu Yin, Wei Ping, Pavlo Molchanov, Mohammad Shoeybi, and Song Han. Vila: On pretraining for visual language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 26689–26699, 2024.
- Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. Improved baselines with visual instruction tuning. *arXiv:2310.03744*, 2023a.
- Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. *arXiv*:2304.08485, 2023b.
- Shilong Liu, Zhaoyang Zeng, Tianhe Ren, Feng Li, Hao Zhang, Jie Yang, Chun yue Li, Jianwei Yang, Hang Su, Jun-Juan Zhu, and Lei Zhang. Grounding dino: Marrying dino with grounded pre-training for open-set object detection. *arXiv:2303.05499*, 2023c.
- Yangzhou Liu, Yue Cao, Zhangwei Gao, Weiyun Wang, Zhe Chen, Wenhai Wang, Hao Tian, Lewei Lu, Xizhou Zhu, Tong Lu, et al. Mminstruct: A high-quality multi-modal instruction tuning dataset with extensive diversity. *Science China Information Sciences*, 67(12):1–16, 2024a.
- Yuan Liu, Haodong Duan, Bo Li Yuanhan Zhang, Songyang Zhang, Wangbo Zhao, Yike Yuan, Jiaqi Wang, Conghui He, Ziwei Liu, Kai Chen, and Dahua Lin. Mmbench: Is your multi-modal model an all-around player? arXiv:2307.06281, 2023d.
- Yuan Liu, Zhongyin Zhao, Ziyuan Zhuang, Le Tian, Xiao Zhou, and Jie Zhou. Points: Improving your vision-language model with affordable strategies. *arXiv preprint arXiv:*2409.04828, 2024b.
- Yuanxin Liu, Shicheng Li, Yi Liu, Yuxiang Wang, Shuhuai Ren, Lei Li, Sishuo Chen, Xu Sun, and Lu Hou. Tempcompass: Do video llms really understand videos? *arXiv preprint arXiv:*2403.00476, 2024c.
- Yuliang Liu, Zhang Li, Mingxin Huang, Biao Yang, Wenwen Yu, Chunyuan Li, Xucheng Yin, Cheng lin Liu, Lianwen Jin, and Xiang Bai. Ocrbench: On the hidden mystery of ocr in large multimodal models. arXiv:2305.07895, 2023e.
- Pan Lu, Hritik Bansal, Tony Xia, Jiacheng Liu, Chunyuan Li, Hannaneh Hajishirzi, Hao Cheng, Kai-Wei Chang, Michel Galley, and Jianfeng Gao. Mathvista: Evaluating mathematical reasoning of foundation models in visual contexts. In *ICLR*, 2024.
- Karttikeya Mangalam, Raiymbek Akshulakov, and Jitendra Malik. Egoschema: A diagnostic benchmark for very long-form video language understanding. In *NeurIPS*, 2023.
- Junhua Mao, Jonathan Huang, Alexander Toshev, Oana Camburu, Alan L Yuille, and Kevin Murphy. Generation and comprehension of unambiguous object descriptions. In *CVPR*, 2016.
- Ahmed Masry, Do Xuan Long, Jia Qing Tan, Shafiq Joty, and Enamul Hoque. Chartqa: A benchmark for question answering about charts with visual and logical reasoning. *arXiv:2203.10244*, 2022.
- Minesh Mathew, Viraj Bagal, Rubèn Pérez Tito, Dimosthenis Karatzas, Ernest Valveny, and C.V. Jawahar. Infographicvqa. 2022 IEEE/CVF Winter Conference on Applications of Computer Vision (WACV), pp. 2582–2591, 2021a.
- Minesh Mathew, Dimosthenis Karatzas, and CV Jawahar. Docvqa: A dataset for vqa on document images. In *WACV*, 2021b.
- MiniMax, Aonian Li, Bangwei Gong, Bo Yang, Boji Shan, Chang Liu, Cheng Zhu, Chunhao Zhang, Congchao Guo, Da Chen, Dong Li, Enwei Jiao, Gengxin Li, Guojun Zhang, Haohai Sun, Houze Dong, Jiadai Zhu, Jiaqi Zhuang, Jiayuan Song, Jin Zhu, Jingtao Han, Jingyang Li, Junbin Xie, Junhao Xu, Junjie Yan, Kaishun Zhang, Kecheng Xiao, Kexi Kang, Le Han, Leyang Wang, Lianfei Yu, Liheng Feng, Lin Zheng, Linbo Chai, Long Xing, Meizhi Ju, Mingyuan Chi, Mozhi Zhang, Peikai Huang, Pengcheng

Niu, Pengfei Li, Pengyu Zhao, Qi Yang, Qidi Xu, Qiexiang Wang, Qin Wang, Qiuhui Li, Ruitao Leng, Shengmin Shi, Shuqi Yu, Sichen Li, Songquan Zhu, Tao Huang, Tianrun Liang, Weigao Sun, Weixuan Sun, Weiyu Cheng, Wenkai Li, Xiangjun Song, Xiao Su, Xiaodong Han, Xinjie Zhang, Xinzhu Hou, Xu Min, Xun Zou, Xuyang Shen, Yan Gong, Yingjie Zhu, Yipeng Zhou, Yiran Zhong, Yongyi Hu, Yuanxiang Fan, Yue Yu, Yufeng Yang, Yuhao Li, Yunan Huang, Yunji Li, Yunpeng Huang, Yunzhi Xu, Yuxin Mao, Zehan Li, Zekang Li, Zewei Tao, Zewen Ying, Zhaoyang Cong, Zhen Qin, Zhenhua Fan, Zhihang Yu, Zhuo Jiang, and Zijia Wu. Minimax-01: Scaling foundation models with lightning attention, 2025. URL https://arxiv.org/abs/2501.08313.

Openai. Chatml documents, 2024. URL https://github.com/openai/openai-python/blob/main/chatml. md.

OpenAI. Hello gpt-4o, 2024. URL https://openai.com/index/hello-gpt-4o.

- Linke Ouyang, Yuan Qu, Hongbin Zhou, Jiawei Zhu, Rui Zhang, Qunshu Lin, Bin Wang, Zhiyuan Zhao, Man Jiang, Xiaomeng Zhao, Jin Shi, Fan Wu, Pei Chu, Minghao Liu, Zhenxiang Li, Chao Xu, Bo Zhang, Botian Shi, Zhongying Tu, and Conghui He. Omnidocbench: Benchmarking diverse pdf document parsing with comprehensive annotations, 2024. URL https://arxiv.org/abs/2412.07626.
- Roni Paiss, Ariel Ephrat, Omer Tov, Shiran Zada, Inbar Mosseri, Michal Irani, and Tali Dekel. Teaching clip to count to ten. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 3170–3180, 2023.
- Viorica Patraucean, Lucas Smaira, Ankush Gupta, Adria Recasens, Larisa Markeeva, Dylan Banarse, Skanda Koppula, Mateusz Malinowski, Yi Yang, Carl Doersch, et al. Perception test: A diagnostic benchmark for multimodal video models. In *NeurIPS*, 2024.
- Zhiliang Peng, Wenhui Wang, Li Dong, Yaru Hao, Shaohan Huang, Shuming Ma, and Furu Wei. Kosmos-2: Grounding multimodal large language models to the world. *arXiv:2306.14824*, 2023.
- Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D. Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. In Alice Oh, Tristan Naumann, Amir Globerson, Kate Saenko, Moritz Hardt, and Sergey Levine (eds.), Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023, 2023. URL http://papers.nips.cc/ paper_files/paper/2023/hash/a85b405ed65c6477a4fe8302b5e06ce7-Abstract-Conference.html.
- Christopher Rawles, Sarah Clinckemaillie, Yifan Chang, Jonathan Waltz, Gabrielle Lau, Marybeth Fair, Alice Li, William Bishop, Wei Li, Folawiyo Campbell-Ajala, et al. Androidworld: A dynamic benchmarking environment for autonomous agents. *arXiv*:2405.14573, 2024.
- David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R. Bowman. GPQA: A graduate-level Google-proof Q&A benchmark. *CoRR*, abs/2311.12022, 2023.
- Tianhe Ren, Qing Jiang, Shilong Liu, Zhaoyang Zeng, Wenlong Liu, Han Gao, Hongjie Huang, Zhengyu Ma, Xiaoke Jiang, Yihao Chen, et al. Grounding dino 1.5: Advance the" edge" of open-set object detection. *arXiv preprint arXiv:2405.10300*, 2024.
- Carlos Riquelme, Joan Puigcerver, Basil Mustafa, Maxim Neumann, Rodolphe Jenatton, André Susano Pinto, Daniel Keysers, and Neil Houlsby. Scaling vision with sparse mixture of experts. *Advances in Neural Information Processing Systems*, 34:8583–8595, 2021.
- Amanpreet Singh, Vivek Natarajan, Meet Shah, Yu Jiang, Xinlei Chen, Dhruv Batra, Devi Parikh, and Marcus Rohrbach. Towards vqa models that can read. In *CVPR*, 2019.
- Jianlin Su, Murtadha H. M. Ahmed, Yu Lu, Shengfeng Pan, Wen Bo, and Yunfeng Liu. Roformer: Enhanced Transformer with rotary position embedding. *Neurocomputing*, 568:127063, 2024.
- Jingqun Tang, Qi Liu, Yongjie Ye, Jinghui Lu, Shu Wei, Chunhui Lin, Wanqing Li, Mohamad Fitri Faiz Bin Mahmood, Hao Feng, Zhen Zhao, Yanjie Wang, Yuliang Liu, Hao Liu, Xiang Bai, and Can Huang. Mtvqa: Benchmarking multilingual text-centric visual question answering. *arXiv*:2405.11985, 2024.
- Gemini Team, Rohan Anil, Sebastian Borgeaud, Yonghui Wu, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, et al. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*, 2023.

- Shengbang Tong, Ellis Brown, Penghao Wu, Sanghyun Woo, Manoj Middepogu, Sai Charitha Akula, Jihan Yang, Shusheng Yang, Adithya Iyer, Xichen Pan, et al. Cambrian-1: A fully open, vision-centric exploration of multimodal llms. *arXiv preprint arXiv:2406.16860*, 2024.
- Fei Wang, Xingyu Fu, James Y Huang, Zekun Li, Qin Liu, Xiaogeng Liu, Mingyu Derek Ma, Nan Xu, Wenxuan Zhou, Kai Zhang, et al. Muirbench: A comprehensive benchmark for robust multi-image understanding. *arXiv preprint arXiv:2406.09411*, 2024a.
- Junyang Wang, Haiyang Xu, Haitao Jia, Xi Zhang, Ming Yan, Weizhou Shen, Ji Zhang, Fei Huang, and Jitao Sang. Mobile-agent-v2: Mobile device operation assistant with effective navigation via multi-agent collaboration. *arXiv preprint arXiv:*2406.01014, 2024b.
- Junyang Wang, Haiyang Xu, Jiabo Ye, Ming Yan, Weizhou Shen, Ji Zhang, Fei Huang, and Jitao Sang. Mobile-agent: Autonomous multi-modal mobile device agent with visual perception. *arXiv preprint arXiv*:2401.16158, 2024c.
- Ke Wang, Junting Pan, Weikang Shi, Zimu Lu, Mingjie Zhan, and Hongsheng Li. Measuring multimodal mathematical reasoning with math-vision dataset. *arXiv:2402.14804*, 2024d.
- Peng Wang, Shuai Bai, Sinan Tan, Shijie Wang, Zhihao Fan, Jinze Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Yang Fan, Kai Dang, Mengfei Du, Xuancheng Ren, Rui Men, Dayiheng Liu, Chang Zhou, Jingren Zhou, and Junyang Lin. Qwen2-vl: Enhancing vision-language model's perception of the world at any resolution. *arXiv*:2409.12191, 2024e.
- Peng Wang, Shuai Bai, Sinan Tan, Shijie Wang, Zhihao Fan, Jinze Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, et al. Qwen2-vl: Enhancing vision-language model's perception of the world at any resolution. *arXiv preprint arXiv:2409.12191*, 2024f.
- Weihan Wang, Zehai He, Wenyi Hong, Yean Cheng, Xiaohan Zhang, Ji Qi, Xiaotao Gu, Shiyu Huang, Bin Xu, Yuxiao Dong, et al. Lvbench: An extreme long video understanding benchmark. *arXiv preprint arXiv:*2406.08035, 2024g.
- Weiyun Wang, Yiming Ren, Haowen Luo, Tiantong Li, Chenxiang Yan, Zhe Chen, Wenhai Wang, Qingyun Li, Lewei Lu, Xizhou Zhu, et al. The all-seeing project v2: Towards general relation comprehension of the open world. *arXiv preprint arXiv:2402.19474*, 2024h.
- Wenhai Wang, Jifeng Dai, Zhe Chen, Zhenhang Huang, Zhiqi Li, Xizhou Zhu, Xiaowei Hu, Tong Lu, Lewei Lu, Hongsheng Li, et al. Internimage: Exploring large-scale vision foundation models with deformable convolutions. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 14408–14419, 2023.
- Xinlong Wang, Xiaosong Zhang, Zhengxiong Luo, Quan Sun, Yufeng Cui, Jinsheng Wang, Fan Zhang, Yueze Wang, Zhen Li, Qiying Yu, et al. Emu3: Next-token prediction is all you need. *arXiv preprint arXiv:*2409.18869, 2024i.
- Yubo Wang, Xueguang Ma, Ge Zhang, Yuansheng Ni, Abhranil Chandra, Shiguang Guo, Weiming Ren, Aaran Arulraj, Xuan He, Ziyan Jiang, Tianle Li, Max Ku, Kai Wang, Alex Zhuang, Rongqi Fan, Xiang Yue, and Wenhu Chen. MMLU-Pro: A more robust and challenging multi-task language understanding benchmark. *CoRR*, abs/2406.01574, 2024j.
- Zhenhailong Wang, Haiyang Xu, Junyang Wang, Xi Zhang, Ming Yan, Ji Zhang, Fei Huang, and Heng Ji. Mobile-agent-e: Self-evolving mobile assistant for complex tasks. *arXiv preprint arXiv:*2501.11733, 2025.
- Zirui Wang, Mengzhou Xia, Luxi He, Howard Chen, Yitao Liu, Richard Zhu, Kaiqu Liang, Xindi Wu, Haotian Liu, Sadhika Malladi, Alexis Chevalier, Sanjeev Arora, and Danqi Chen. Charxiv: Charting gaps in realistic chart understanding in multimodal llms. *arXiv preprint arXiv:2406.18521*, 2024k.
- Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Ed H. Chi, Quoc Le, and Denny Zhou. Chain of thought prompting elicits reasoning in large language models. *CoRR*, abs/2201.11903, 2022. URL https://arxiv.org/abs/2201.11903.
- Colin White, Samuel Dooley, Manley Roberts, Arka Pal, Benjamin Feuer, Siddhartha Jain, Ravid Shwartz-Ziv, Neel Jain, Khalid Saifullah, Siddartha Naidu, Chinmay Hegde, Yann LeCun, Tom Goldstein, Willie Neiswanger, and Micah Goldblum. LiveBench: A challenging, contamination-free LLM benchmark. *CoRR*, abs/2406.19314, 2024.
- Haoning Wu, Dongxu Li, Bei Chen, and Junnan Li. Longvideobench: A benchmark for long-context interleaved video-language understanding, 2024a. URL https://arxiv.org/abs/2407.15754.

- Zhiyu Wu, Xiaokang Chen, Zizheng Pan, Xingchao Liu, Wen Liu, Damai Dai, Huazuo Gao, Yiyang Ma, Chengyue Wu, Bingxuan Wang, et al. Deepseek-vl2: Mixture-of-experts vision-language models for advanced multimodal understanding. *arXiv preprint arXiv:2412.10302*, 2024b.
- X.AI. Grok-1.5 vision preview. https://x.ai/blog/grok-1.5v, 2024.
- Bin Xiao, Haiping Wu, Weijian Xu, Xiyang Dai, Houdong Hu, Yumao Lu, Michael Zeng, Ce Liu, and Lu Yuan. Florence-2: Advancing a unified representation for a variety of vision tasks (2023). *URL https://arxiv.org/abs/2311.06242*, 2023.
- Tianbao Xie, Danyang Zhang, Jixuan Chen, Xiaochuan Li, Siheng Zhao, Ruisheng Cao, Jing Hua Toh, Zhoujun Cheng, Dongchan Shin, Fangyu Lei, et al. Osworld: Benchmarking multimodal agents for open-ended tasks in real computer environments. *Advances in Neural Information Processing Systems*, 37: 52040–52094, 2025.
- Yiheng Xu, Zekun Wang, Junli Wang, Dunjie Lu, Tianbao Xie, Amrita Saha, Doyen Sahoo, Tao Yu, and Caiming Xiong. Aguvis: Unified pure vision agents for autonomous gui interaction. *arXiv preprint arXiv:*2412.04454, 2024.
- An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, et al. Qwen2.5 technical report. *arXiv:2412.15115*, 2024a.
- Zhibo Yang, Jun Tang, Zhaohai Li, Pengfei Wang, Jianqiang Wan, Humen Zhong, Xuejing Liu, Mingkun Yang, Peng Wang, Shuai Bai, LianWen Jin, and Junyang Lin. Cc-ocr: A comprehensive and challenging ocr benchmark for evaluating large multimodal models in literacy, 2024b. URL https://arxiv.org/ abs/2412.02210.
- Hanrong Ye, De-An Huang, Yao Lu, Zhiding Yu, Wei Ping, Andrew Tao, Jan Kautz, Song Han, Dan Xu, Pavlo Molchanov, et al. X-vila: Cross-modality alignment for large language model. *arXiv preprint arXiv:*2405.19335, 2024.
- Qinghao Ye, Haiyang Xu, Jiabo Ye, Ming Yan, Haowei Liu, Qi Qian, Ji Zhang, Fei Huang, and Jingren Zhou. mplug-owl2: Revolutionizing multi-modal large language model with modality collaboration. *arXiv*:2311.04257, 2023.
- Weihao Yu, Zhengyuan Yang, Linjie Li, Jianfeng Wang, Kevin Lin, Zicheng Liu, Xinchao Wang, and Lijuan Wang. Mm-vet: Evaluating large multimodal models for integrated capabilities. In *ICML*, 2024.
- Xiang Yue, Yuansheng Ni, Kai Zhang, Tianyu Zheng, Ruoqi Liu, Ge Zhang, Samuel Stevens, Dongfu Jiang, Weiming Ren, Yuxuan Sun, et al. Mmmu: A massive multi-discipline multimodal understanding and reasoning benchmark for expert agi. *arXiv:2311.16502*, 2023.
- Xiang Yue, Tianyu Zheng, Yuansheng Ni, Yubo Wang, Kai Zhang, Shengbang Tong, Yuxuan Sun, Ming Yin, Botao Yu, Ge Zhang, et al. Mmmu-pro: A more robust multi-discipline multimodal understanding benchmark. *arXiv preprint arXiv:2409.02813*, 2024.
- Biao Zhang and Rico Sennrich. Root mean square layer normalization. In NeurIPS, 2019.
- Haotian Zhang, Haoxuan You, Philipp Dufter, Bowen Zhang, Chen Chen, Hong-You Chen, Tsu-Jui Fu, William Yang Wang, Shih-Fu Chang, Zhe Gan, and Yinfei Yang. Ferret-v2: An improved baseline for referring and grounding with large language models. *arXiv*:2404.07973, 2024a.
- Pan Zhang, Xiaoyi Dong, Yuhang Cao, Yuhang Zang, Rui Qian, Xilin Wei, Lin Chen, Yifei Li, Junbo Niu, Shuangrui Ding, et al. Internlm-xcomposer2. 5-omnilive: A comprehensive multimodal system for long-term streaming video and audio interactions. *arXiv preprint arXiv:2412.09596*, 2024b.
- Renrui Zhang, Dongzhi Jiang, Yichi Zhang, Haokun Lin, Ziyu Guo, Pengshuo Qiu, Aojun Zhou, Pan Lu, Kai-Wei Chang, Yu Qiao, et al. Mathverse: Does your multi-modal llm truly see the diagrams in visual math problems? In *European Conference on Computer Vision*, pp. 169–186. Springer, 2024c.
- Tao Zhang, Xiangtai Li, Hao Fei, Haobo Yuan, Shengqiong Wu, Shunping Ji, Chen Change Loy, and Shuicheng Yan. Omg-llava: Bridging image-level, object-level, pixel-level reasoning and understanding. *arXiv preprint arXiv:2406.19389*, 2024d.
- Tianyu Zhang, Suyuchen Wang, Lu Li, Ge Zhang, Perouz Taslakian, Sai Rajeswar, Jie Fu, Bang Liu, and Yoshua Bengio. Vcr: Visual caption restoration. *arXiv:2406.06462*, 2024e.

- Yi-Fan Zhang, Huanyu Zhang, Haochen Tian, Chaoyou Fu, Shuangqing Zhang, Junfei Wu, Feng Li, Kun Wang, Qingsong Wen, Zhang Zhang, et al. Mme-realworld: Could your multimodal llm challenge high-resolution real-world scenarios that are difficult for humans? *arXiv preprint arXiv:2408.13257*, 2024f.
- Yilun Zhao, Lujing Xie, Haowei Zhang, Guo Gan, Yitao Long, Zhiyuan Hu, Tongyan Hu, Weiyuan Chen, Chuhan Li, Junyang Song, Zhijian Xu, Chengye Wang, Weifeng Pan, Ziyao Shangguan, Xiangru Tang, Zhenwen Liang, Yixin Liu, Chen Zhao, and Arman Cohan. Mmvu: Measuring expert-level multi-discipline video understanding, 2025. URL https://arxiv.org/abs/2501.12380.
- Jeffrey Zhou, Tianjian Lu, Swaroop Mishra, Siddhartha Brahma, Sujoy Basu, Yi Luan, Denny Zhou, and Le Hou. Instruction-following evaluation for large language models. *CoRR*, abs/2311.07911, 2023.
- Junjie Zhou, Yan Shu, Bo Zhao, Boya Wu, Shitao Xiao, Xi Yang, Yongping Xiong, Bo Zhang, Tiejun Huang, and Zheng Liu. Mlvu: A comprehensive benchmark for multi-task long video understanding. *arXiv* preprint arXiv:2406.04264, 2024.