Position: There are no Champions in Long-Term Time Series Forecasting

Lorenzo Brigato^{*1} Rafael Morand^{*123} Knut Strømmen^{*12} Maria Panagiotou¹² Markus Schmidt³ Stavroula Mougiakakou¹

Abstract

Recent advances in long-term time series forecasting have introduced numerous complex prediction models that consistently outperform previously published architectures. However, this rapid progression raises concerns regarding inconsistent benchmarking and reporting practices, which may undermine the reliability of these comparisons. Our position emphasizes the need to shift focus away from pursuing ever-more complex models and towards enhancing benchmarking practices through rigorous and standardized evaluation methods. To support our claim, we first perform a broad, thorough, and reproducible evaluation of the top-performing models on the most popular benchmark by training 3,500+ networks over 14 datasets. Then, through a comprehensive analysis, we find that slight changes to experimental setups or current evaluation metrics drastically shift the common belief that newly published results are advancing the state of the art. Our findings suggest the need for rigorous and standardized evaluation methods that enable more substantiated claims, including reproducible hyperparameter setups and statistical testing.

1. Introduction

Long-term time series forecasting (LTSF) is critical across various domains, including energy management (Weron, 2014), financial planning (Sezer et al., 2020), and environmental modeling (Soni et al., 2024). Accurately predicting future values in time series data enables better decisionmaking and resource allocation. LTSF remains challenging due to the complex temporal dynamics, including trends,



Figure 1. **Performance comparison of recent models.** We summarize results in terms of relative MSE averaged over all forecast horizons for the leaderboard models of the TSLib benchmark.

seasonality, irregular fluctuations, and significant variability across datasets (Shao et al., 2024; Qiu et al., 2024).

Recent advancements in deep learning have improved LTSF capabilities, and the field is currently witnessing an exponential surge in publication rates (Kim et al., 2024). Transformer models have been adapted to time series forecasting with innovative modifications, such as univariate patching (Nie et al., 2023) and attention mechanisms tailored to exploit inter-variate dependencies (Liu et al., 2024a; Wang et al., 2024c). Additionally, models such as TimeMixer (Wang et al., 2024a), leveraging multiscale signal mixing, and TimesNet (Wu et al., 2023), using Fourier-based 2D decomposition, have expanded the field.

However, we claim that the field is facing significant fairbenchmarking challenges despite the introduction of extensive benchmarks such as TSLib (Wang et al., 2024b), BasicTS+ (Shao et al., 2024), and TFB (Qiu et al., 2024). Inconsistencies in test setups across different benchmarks, biased comparisons, and challenges with reproducibility are investigated as factors that hinder fair performance assessment in the field. Moreover, marginal performance gains in recent literature cast doubt on the practical value of increas-

^{*}Equal contribution ¹ARTORG Center, University of Bern ²Graduate School for Cellular and Biomedical Sciences, University of Bern ³Center for Experimental Neurology, Department of Neurology, Bern University Hospital. Correspondence to: Lorenzo Brigato <lorenzo.brigato@unibe.ch>, Rafael Morand <rafael.morand@unibe.ch>, Knut Strømmen <knut.stroemmen@unibe.ch>.

ingly complex model architectures (Zeng et al., 2022). To support our hypothesis, we conduct a comprehensive, rigorous, and reproducible evaluation of the top-performing models on the most widely used benchmark, training over 3,500 networks across 14 datasets. As shown in Figure 1, our findings reveal that no single model consistently outperforms all the baselines. This result directly challenges the prevailing narrative of new architectures consistently surpassing competing models across all domains (Nie et al., 2023; Wu et al., 2023; Liu et al., 2024a; Wang et al., 2024a;c). We provide insights into the potential reasons behind this phenomenon and offer recommendations to help the field progress. To facilitate ongoing research in LTSF, we will make our code publicly available upon acceptance. In summary, the contributions of our paper are as follows:

- We question the current narrative of consistently dominated LTSF benchmarks (Section 2) supported by results obtained over a comprehensive and reproducible experimental setup (Section 3).
- We provide possible reasons why this is happening (Section 4) and propose guidelines to reduce the likelihood of repeating such overstated claims (Section 5).
- We challenge previous claims that dataset characteristics may guide model selection, as our results show similar performance across networks, highlighting the need for further research in this direction (Section 6).

2. Field overview

We provide an overview of recent advancements in LTSF, focusing on current benchmarks (Section 2.1) and emerging champions (Section 2.2). Due to space limitations, additional related work on recent time series forecasting models and paradigms is included in Appendix A.

2.1. Benchmarks

TSLib (Wang et al., 2024b) compares 12 deep learning models across five tasks: classification, imputation, anomaly detection, and long-/short-term forecasting. For long-term forecasting, nine datasets from four domains are used. Results are presented for two settings: unified hyperparameters (HPs) and an HP search per model, but details on parameters, context length, forecast horizon, or the search process are missing. The evaluation metric is the mean squared error (MSE) averaged across datasets. The top models in the HP search setting are PatchTST (Zeng et al., 2022) (MSE 0.305), N-Beats (Oreshkin et al., 2020) (MSE 0.313), and iTransformer (Liu et al., 2024a) (MSE 0.317), and the top performing models for the unified HP setting are iTransformer (MSE 0.342), N-Beats (MSE 0.371), and PatchTST (MSE 0.373). The authors claim that their results clearly

show the superior forecasting capabilities of transformer models, particularly iTransformer and PatchTST, despite arguably marginal improvements. They stress the importance of continued exploration of methods that use temporal tokens in time series analysis.

TFB (Qiu et al., 2024) evaluates 22 statistical, classical machine learning, and deep learning methods using 25 multivariate and 8,068 univariate datasets. For multivariate forecasting, shorter datasets use forecast horizons of 24-60 and look-back windows of 36-104, while longer datasets use forecast horizons of 96-720 and look-back windows of 96-512. Univariate forecasting applies fixed forecasting horizons of 6-48 with a look-back window set to 1.25 times the forecasting horizon. The experiments adhere to each method's HPs specified in the original works. HP searches are performed across up to eight sets, and the best result is selected from these evaluations. Based on these results, the authors claim that linear models outperform deep learning methods in datasets with increased trends and distribution shifts. Conversely, transformers excel in datasets with marked patterns (e.g., seasonality). PatchTST and DLinear (Zeng et al., 2022) consistently perform well without notable weaknesses.

BasicTS+ (Shao et al., 2024) incorporates 28 forecasting models, including 17 short-term forecasting (STF) and 11 LTSF models, across 14 widely used datasets. STF models encompass prior-graph-based, latent-graph-based, and non-graph-based methods, while LTSF models consist of transformer-based and linear-layer-based architectures. In STF, both the context length and forecast horizon are fixed at 12. For LTSF, the forecast horizon is set to 336, while context length varies across 96, 192, 336, and 720, with the best performance across these lengths being reported. Models are implemented following publicly available architectures and HPs, with further tuning of parameters like learning rate and batch size via grid search to ensure performance is at least as good as reported in the original paper. Upon analyzing the results, the authors argue that dataset characteristics play a major role in determining model performance. They claim that Transformer models excel on datasets with clear, stable patterns, whereas simpler models like DLinear perform comparably on datasets without such patterns. The authors emphasize the need to address data distribution drift and unclear patterns instead of focusing solely on increasing model complexity. They suggest that this may indicate potential overfitting to commonly used datasets like ETT*, Electricity, Weather, and Exchange, which risks creating a misleading impression of progress. Consequently, they conclude that careful dataset selection and curation are essential for advancing MTS forecasting meaningfully.

2.2. Emergent LTSF champions

Recent models have made a leap in LTSF performance (Zeng et al., 2022; Nie et al., 2023; Wu et al., 2023; Wang et al., 2024a; Liu et al., 2024a; Wang et al., 2024c). One widely accepted benchmark for LTSF is TSLib (Wang et al., 2024b). Using this library, there has been a series of new models in 2024 that reportedly dominates the field. Sophisticated and elegant changes to established model architectures resulted in improved forecasting performance. The current leaderboard in TSlib includes five models, which we introduce in chronological order in Table 1.

(Zeng et al., 2022) introduced a collection of comparably simple multi-layer perceptron (MLP) baselines called LTFS-Linear. The authors challenged the utility of transformerbased models since, collectively, the linear baselines beat all previous transformers (Zhou et al., 2022a; Wu et al., 2021; Zhou et al., 2021; Liu et al., 2022b; Li et al., 2019). The DLinear model has since been used as a competitive baseline in LTSF benchmarks. PatchTST (Nie et al., 2023) is a transformer model that introduced univariate patching of time series for tokenization. PatchTST beat all previous transformer models but was occasionally beaten by DLinear. PatchTST has since been used as a competitive baseline in LTSF benchmarks. TimeMixer (Wang et al., 2024a) is an MLP mixer model that introduces past-decomposable mixing and future-predictor mixing. The authors used two experimental settings. In setting A), all models were trained and tested using unified HPs, and in B) with HP search. TimeMixer dominated in setting A where unified HPs were used. Although still the clear winner in setting B, TimeMixer took the position as runner-up in some datasets and forecast horizons, being on most occasions second to PatchTST. The iTransformer (Liu et al., 2024a) is a modification of the original transformer model with attention across variates instead of samples. This allows for capturing interactions between variates. It was the top model in 5/9 datasets. Since the remaining four datasets are similar (ETTh1, ETTh2, ETTm1, ETTm2), the authors also reported results for an average of these datasets. This improved the ranking of iTransformer, making it the top-performing model at the time. Finally, TimeXer (Wang et al., 2024c) is a transformer model that uses two attention stages, one for interactions between patches and one for interactions between variates. TimeXer won in 6/7 datasets, of which four are similar (ETT*). We summarize the striking winning percentages of these models in Table 1.

3. Who is the real champion?

As seen in the previous section, recent papers often suggest that newly proposed architectures outperform others across almost all tested datasets. However, the variability in results for the same algorithms and reliance on prior stud-

Table 1. Win percentages. Reported winners in LTSF for prediction lengths $T \in \{96, 192, 336, 720\}$. The percentage of reported wins is according to each prediction length without averaging. TimeMixer reported unified parameters (A) and HP search (B) results. (†avg. of all prediction horizons and avg. of ETT* datasets)

	8	F		8	
Win %	DLinear (2022)	PatchTST (2023)	TimeMixer (2024a)	iTransformer (2024a)	TimeXer (2024c)
MSE	50.0	87.5	A) 93.8 B) 81.2	33.3 †(71.4)	85.7
MAE	16.7	59.4	A) 100 B) 81.2	47.2 †(85.7)	60.7

ies with different HP optimizations raise questions about their consistent superiority. To investigate this, we selected the previously introduced five top-performing models from TSLib (Wang et al., 2024b) and performed a comprehensive HP search across 14 datasets from various domains.

3.1. Hyperparameter search

For HP tuning, we focused on optimizing parameters aligned with those described in TimeMixer (Wang et al., 2024a). Specifically, we searched for an input length between 96 and 512, model size d_m from 16 to 512, learning rate ranging from 10^{-5} to 0.1, and encoder layers between 1 and 5. We refer the reader to Table 7 for exact values. TimeMixer was limited to a maximum of 3 layers and a model size of 128 due to high memory demands. However, this is unlikely to affect performance, as the original HP search for all datasets in this study yielded results within these limits. We used the Optuna framework (Akiba et al., 2019) with a budget of 40 trials to optimize the HPs. We employed the default TPEsampler for HP sampling and applied the SuccessiveHalvingPruner, configured with a minimum of three epochs and a reduction factor of two to prune unpromising trials. The search was conducted with a batch size of 8, a maximum of 15 epochs, and early stopping with a patience of 3 epochs. All models were optimized with the Adam optimizer and an exponentially decaying scheduler following the default TSLib configuration. The optimal HPs, determined by the minimum validation loss in the trials, were used to train and evaluate the final model across three random seeds to ensure robust results.

We set the dimensions of the fully connected layers d_f equal to d_m . The patch length for transformer models using patching (i.e., PatchTST and TimeXer) was set to roughly match one period for each dataset, with the stride equal to the patch size (Table 6). Original works concluded that variations in patch length have minimal effects (Nie et al., 2023; Wang et al., 2024c). For the rest of the model HPs, we default to the configurations provided in TSLib.

Position: There are no Champions in Long-Term Time Series Forecasting

Model		DL	inear			Patel	nTST			iTrans	former			Time	eMixer			Time	Xer	
Metric	M	AE	М	SE	M	AE	М	SE	M	ΑE	М	SE	M	λE	MSI	E	M	AE	MS	E
Statistic	Mean	Min	Mean	Min	Mean	Min	Mean	Min	Mean	Min	Mean	Min	Mean	Min	Mean	Min	Mean	Min	Mean	Min
ETTh1	0.4772	0.4761	0.4741	0.4725	0.4319	0.4279	0.4143	0.4076	0.4428	0.4408	0.4244	0.4217	0.4429	0.4386	0.429	0.4245	0.44	0.4361	0.4252	0.4204
ETTm1	0.4218	0.4208	0.4031	0.4023	0.4314	0.4292	0.3936	0.3915	0.4373	0.4333	0.408	0.4029	0.4487	0.4385	0.4315	0.4157	0.4446	0.4398	0.4121	0.4054
ETTh2	0.4743	0.4736	0.4849	0.4841	0.4099	0.4062	0.3793	0.3736	0.4054	0.4028	0.3784	0.3742	0.4044	0.4011	0.3744	0.3684	0.4063	0.4038	0.377	0.3746
ETTm2	0.2611	0.261	0.1511	0.1511	0.2691	0.2676	0.1563	0.1552	0.2759	0.2749	0.1661	0.165	0.2704	0.2686	0.1618	0.1598	0.2767	0.2744	0.1682	0.1654
Electricity	0.2585	0.2583	0.1616	0.1615	0.2613	0.2608	0.164	0.1634	0.2622	0.2577	0.1655	0.162	0.2704	0.2686	0.1618	0.1598	0.2676	0.2635	0.1695	0.1645
Weather	0.2984	0.2984	0.2442	0.2441	0.2633	0.2623	0.2245	0.2235	0.2791	0.2779	0.2385	0.2367	0.2707	0.2639	0.2313	0.2248	0.2639	0.2616	0.2237	0.2217
Exchange	0.5905	0.5833	0.7754	0.7553	0.5746	0.5671	0.7379	0.7169	0.5572	0.5394	0.6995	0.6621	31.4575	0.7354	33705.21	1.3975	0.5616	0.5483	0.6973	0.6667
MotorImagery	1.1834	1.1821	4.5924	4.5831	1.006	1.0004	3.7749	3.7446	0.3835	0.3378	1.6916	1.4959	1.0113	0.9958	3.8691	3.8126	0.9155	0.8933	3.649	3.5762
TDBrain	0.8016	0.8014	1.1513	1.1505	0.7248	0.7223	0.9821	0.9757	0.7224	0.7206	0.9783	0.9742	0.7228	0.7199	0.9812	0.9742	0.7187	0.7168	0.97	0.9651
BeijingAir	0.4716	0.4708	0.5829	0.5823	0.5472	0.4584	0.8643	0.5758	0.4641	0.4612	0.5801	0.5719	0.4712	0.467	0.5917	0.5804	0.4618	0.4591	0.5818	0.5765
BenzeneConcentration	0.0196	0.0178	0.0082	0.0081	0.0419	0.0383	0.0111	0.0107	0.0529	0.0479	0.0117	0.0108	0.0225	0.0188	0.0082	0.008	0.1213	0.0383	0.0915	0.0119
AustraliaRainfall	0.7513	0.7507	0.8382	0.8376	0.7566	0.7556	0.8548	0.8524	0.7537	0.7531	0.8493	0.8482	0.7548	0.7539	0.853	0.8503	0.7528	0.7522	0.8468	0.8457
KDDCup2018	0.6302	0.6274	0.9967	0.9887	0.6474	0.6442	1.0856	1.0757	0.6485	0.6461	1.0882	1.0839	0.631	0.6273	1.0346	1.0302	0.6396	0.633	1.045	1.0297
PedestrianCounts	0.2892	0.2888	0.2983	0.2979	0.2929	0.2912	0.2915	<u>0.2885</u>	<u>0.2854</u>	<u>0.2827</u>	0.2947	0.2911	0.2845	0.2789	0.2923	0.2859	0.3066	0.2948	0.3112	0.2951
Average	0.4949	0.4936	0.7973	0.7942	0.4756	0.4665	0.7382	0.7111	0.4265	0.4197	0.5696	0.5501	2.6748	0.4757	2408.1878	0.7633	0.4698	0.4582	0.712	0.6942
Rank	3.07	3.29	3.21	3.43	3.14	3.07	2.93	2.71	2.86	3.07	2.93	2.93	2.93	2.64	3.00	2.93	3.00	2.93	2.93	3.00

Table 2. Main results. Mean and best (i.e., Min) values averaged over prediction lengths. Best and second-best are highlighted.



Figure 2. **Impact of datasets.** We evaluate the influence of removing a dataset from the evaluation, in particular *MotorImagery*. We observe that this experiment leads to a significantly different conclusion, as iTransformer remains the best model, albeit with only a modest net average improvement over the other baselines.

3.2. Datasets

We evaluate models on 14 datasets spanning five domains: Energy, Economy, Transport, Health, and Environment. The datasets vary significantly, containing between 7,588 and 72.58 million time points. They range from univariate to multivariate with up to 321 channels. Sampling frequencies differ from 1 Hz to hourly and daily intervals. Additionally, the datasets exhibit diversity in stationarity, complexity, trends, seasonality, and entropy (Appendix B). The dataset selection is designed to minimize bias, preventing undue advantages for any model while accounting for specific model strengths.

3.3. Results: There is no champion

We follow the benchmark TSlib and use MSE and mean absolute error (MAE) to evaluate model performance. Table 2 presents the MSE and MAE for each dataset, averaged over the most common forecast horizons (Wang et al., 2024c; Liu et al., 2024a; Nie et al., 2023; Wang et al., 2024c), revealing results that differ substantially from recent papers where proposed algorithms often dominate. Instead, our findings indicate no definitive best-performing model across all datasets and forecast horizons (Table 11). To assess reliability, we also compared our results with the best-reported outcomes from the original studies for three common datasets: *ETT**, *Electricity*, and *Weather*. As shown in Table 9, our HP search performed similar or better than the original papers' results. While this is not a one-to-one comparison due to differences in HP search procedures and context lengths, achieving comparable or better scores confirms the proper implementation and tuning of our baselines.

To present a comprehensive view that highlights both the optimal outcomes and the realistic performance variability, we report the minimum values (best MSE/MAE) and the averages. We observe that TimeMixer is the only model facing convergence challenges, specifically on *Exchange*, impacting its overall average performance. We further analyze run-to-run variability in Appendix E.

4. Why are they all champions?

This section provides strong empirical evidence on possible reasons for how each model can become a champion. We demonstrate how a few changes in the experimental setting, such as the exclusion/inclusion of an additional dataset, prediction horizon, or baseline model, plus HP tuning, may drastically change the final conclusions. Additionally, we illustrate how specific visualizations can influence the perceived performance differences between models. First, we interpret the results from our extensive experiments. Second, to support our hypothesis, we analyze cases in recent literature in which such scenarios occur.

4.1. Impact of datasets

From our results This experiment provides a practical sense of how much the addition/removal of a single dataset may affect conclusions. The most impactful case in our experimental setup corresponds to removing only the *MotorImagery* dataset from the full pool. As visible in Figure 2 (left), when all datasets are evaluated, iTransformer (red bar) seems to clearly be the best model in terms of MSE.

Position: There are no Champions in Long-Term Time Series Forecasting



Figure 3. **Impact of horizons.** We evaluate the influence of removing a forecast horizon from the evaluation. We observe that this experiment leads to three different benchmark champions underling the brittleness of conclusions regarding the best available models.

However, when we remove it (Figure 2, right), we get a much closer scenario where all models are basically equivalent. We report an additional view of this experiment in Appendix H (Figure 8), in which we show the MSE per dataset and that the sharp drop of difference is only due to the much better performance of iTransformer on *MotorImagery*, which biases the perception of the overall rankings.

From literature We observe that subsets of the full benchmark were used occasionally, which may be justified (e.g., too small datasets like ILI). (Liu et al., 2024a) averaged the performance over the four ETT datasets, which the authors justified by the similarity of the datasets. However, this increased the percentage of wins of their proposed method from 33.3% to 71.4%.

4.2. Impact of prediction horizons

From our results Similarly to the case of datasets, also prediction horizons may play a major role in biasing the perception of overall champions. In this small experiment, we select 6 datasets, more precisely ETT*, Weather, and *Exchange*, and remove one prediction horizon at a time. In such a manner, we simulate a slightly less broad evaluation yet reasonably acceptable considering that models are evaluated on 18 total scenarios (6 datasets and 3 prediction horizons). In Figure 3, we find that we can have three different champions in terms of MSE (red bars) out of four different cases. In particular, TimeXer wins the benchmark when prediction horizons 96 and 192 are removed, DLinear if the prediction is 336, and iTransformer if the forecast length is 720. Although the differences are less pronounced than in the dataset case, this serves as further empirical evidence of the fragility of such conclusions.

From literature (Shao et al., 2024) focuses solely on a forecast horizon of 336, whereas (Qiu et al., 2024) bases its analysis of the impact of different data characteristics on a horizon of 96 — despite reporting performance for all four forecast horizons. Our experiments demonstrate

Table 3. **Impact of HP tuning.** We report the MSE of DLinear for *Weather* at prediction length 96 when HP tuning is or is not performed both in our and previous papers, along with the relative improvement (when possible). "–" indicates a missing analysis.

1 \	1		/			U	5
MSE (DLinear)	2022	2023	2023	2024a	2024a	2024c	Ours
Unified HP	-	-	0.196	0.196	0.195	0.196	0.198
HP tuning	0.176	0.176	-	-	0.176	-	0.168
Rel. Improv.	-	-	-	-	+9.7%	-	+15.1%

that this reporting can lead to differing interpretations of model performance, underscoring the critical need for more consistent evaluation practices in LTSF.

4.3. Impact of evaluated models

From our results While less surprising, we stress that excluding the top model from a benchmark may automatically crown the second-best as a champion. For instance, from the full experimental setup evaluated in Figure 2 (left), removing iTransformer would automatically champion TimeXer as the best available model.

From literature We believe that the reports always include the best-performing complex models from the benchmarks (Appendix G). However, we notice the overall lack of inclusion of baseline models like N-Beats in the publications of the recent "champions", although it is a top-3 method in (Wang et al., 2024b). In addition, we identified cases where the best-performing model was excluded from discussions without clear justification. For example, (Shao et al., 2024; Qiu et al., 2024) claim recent transformers underperform compared to earlier methods, but their experiments show the most recent LTSF transformer at the time (PatchTST) outperformed competitors, contradicting this claim. In addition, (Shao et al., 2024) claims linear models are better for LTSF on datasets with unclear patterns or distribution shifts. However, the claim is based on results where PatchTST was excluded, although it performed similarly according to the full results, weakening their assertion.

Table 4. **iPatch as an unreliable champion.** Although iPatch scores the **best** average rank and the <u>second-best</u> MAE/MSE averaged over all datasets, it does not statistically differ from all the other baselines under a Friedman test (Section 5.3).

Avg.	DLinear	PatchTST	iTransformer	TimeMixer	TimeXer	iPatch
MSE	0.797	0.738	0.570	2408	0.712	<u>0.604</u>
MAE	0.494	0.476	0.426	2.675	0.470	<u>0.431</u>
Rank	3.71	3.50	3.71	3.57	3.43	3.07

4.4. Impact of HP tuning

From our results The impact of HP tuning on the absolute performance of machine learning models in benchmarks is becoming increasingly evident (Brigato et al., 2021; McEl-fresh et al., 2024). In Table 3, we investigate whether this may also be the case in LTSF via a proof-of-concept example. We report the evaluation in terms of MSE for DLinear on the *Weather* dataset at prediction horizon 96. HP tuning brings a relative performance boost of ~15% in our setup and an ~10% in (Wang et al., 2024b). Similarly, building on the HP search details in (Wang et al., 2024c), we found comparable performance between TimeMixer, iTransformer, and PatchTST, unlike the original work where TimeMixer consistently ranks first. This underscores how close the actual performance of models is, making outcomes and conclusions sensitive to slight variations in HP search.

From literature In TSLib, the models are usually based on the implementation of the original publications. However, in (Wu et al., 2023), for a fair comparison, they changed the input embeddings and the final projections to be the same for all models. Specifically, the sequence length was set to 96 for all models by default. This is critical since DLinear, after a broad ablation study, explicitly states that short input sequences (< 336) lead to underfitting (Zeng et al., 2022). We show the progression of the reported MSE of DLinear in Table 3 and underline the sharp improvement (+9.7%) if HP search, including context length, is performed. This concludes one example where efforts towards a fair comparison put baseline models at a known disadvantage, and therefore, we recommend a fair HP search for all baselines.

4.5. Impact of visualizations

From our results Visualizations are a strong tool to convey a message. In Figure 4, we investigate the impact of scales to visualize performance. We observe that using an absolute scale exaggerates differences between models that are not perceived in the relative scale with uniform axes. Conversely, it can obscure substantial differences as in the example of *MotorImagery* and *BenzeneConcentration* (Figure 4, right, b and e). Hence, for a fair comparison, we stress that researchers must carefully select appropriate styles and scales when visualizing results.



a) Exchange, b) MotorImagery, c) ETT, d) Electricity, e) BenzeneConcentration, f) AustraliaRainfall, g) KDDCup2018, h) Weather, i) BeijingAir, j) PedestrianCounts, k) TDBrain

Figure 4. **Bias in visualizations.** The radar plots show the same data represented at different scales (MSE for various datasets).

From literature Radar plots are commonly used in the literature. One example is (Liu et al., 2024a), which used a radar plot to visualize the relative performance between models, and (Qiu et al., 2024), which used a radar plot to show model performance across different dataset characteristics. In both cases, they used absolute scales. These choices can create a misleading impression of the models' actual performance and lead to false conclusions. This is just one example of how visualization choices can shape result interpretation. Other plots may also create biased impressions through axis scaling or selective metric representation.

5. How to make substantiated claims?

This section provides guidelines and a proof-of-concept example of how to make substantiated claims supported by robust statistical evidence regarding models' superiority in a broad experimental setup. First, we introduce recommended non-parametric statistical tests (Demšar, 2006). Second, we upgrade the existing iTransformer to emulate current modeldesign proposals and rigorously evaluate it in our setup (Section 3). While not an overall champion, the upgraded model statistically outperforms its predecessor, demonstrating the idea that reliable claims can be made.

5.1. Rigorous statistical testing

Following good practices for reliable evaluations in machine learning, we claim that statistical tests should be used to decrease the chances of making unreliable claims. (Demšar, 2006) studied various statistical tests for comparing classifiers from both theoretical and empirical perspectives. The study recommended a set of simple, reliable, and robust tests for such comparisons. In particular, the sign test (Salzberg, 1997) compares two classifiers over multiple datasets, and the Friedman test compares various classifiers over multiple datasets (see Appendix F for details).

The TSLib benchmark (Wang et al., 2024b) employs averaging for presenting aggregated results. However, averages are susceptible to outliers (Demšar, 2006). A classifier's strong performance on one dataset can mask weaknesses elsewhere, so we prioritize consistent performance across problems, making dataset averaging unsuitable for evaluation (Section 4). Both the BasicTS+ (Shao et al., 2024) and TFB (Qiu et al., 2024) benchmarks focus on the number of wins achieved by each model but do not incorporate any statistical testing, making conclusions less reliable and hard to communicate in a concise manner.

5.2. A proof-of-concept model for substantiated claims

The iPatch model is introduced as a hybrid architecture combining principles from iTransformer and PatchTST to better capture variate and temporal-specific dynamics in multivariate time-series data. By structuring the input into cycles and modeling both variate and cycle-level dependencies, iPatch provides a hierarchical approach to multivariate time-series forecasting.

Embedding To prepare the input for its two-stage attention mechanism, we modify the embedding layer by structuring the temporal information into cycles for temporal attention. Let the input be denoted as $\mathbf{x} \in \mathbb{R}^{B \times C \times L}$, where B is the batch size, C is the number of variates, and L is the lookback length. Following the iTransformer design, the input is tokenized into an embedding dimension d_m , resulting in $\mathbf{x} \in \mathbb{R}^{B \times C \times d_m}$. In iPatch, however, we first divide the sequence into N cycles of length P, such that $L = N \cdot P$. This restructuring reshapes the input from $\mathbb{R}^{B \times C \times L}$ to $\mathbb{R}^{B \times C \times (N \cdot P)}$, then further into $\mathbb{R}^{B \times (C \cdot N) \times P}$ for preparing attention over the temporal dimension as in PatchTST. Each cycle is subsequently embedded to d_m , resulting in $\mathbf{x} \in \mathbb{R}^{B \times (C \cdot N) \times d_m}$.

Transformer layer We enhance the attention module as a sequence of two attentions over variates and cycles. First, the input $\mathbf{x} \in \mathbb{R}^{B \times (C \cdot N) \times d_m}$ is reshaped to $\mathbb{R}^{(B \cdot N) \times C \times d_m}$ to isolate the *C* variates for each cycle. Attention is applied over the variates similarly to iTransformer. The result is reshaped back to $\mathbb{R}^{B \times (C \cdot N) \times d_m}$. Next, the output of the variate attention is reshaped to $\mathbb{R}^{(B \cdot C) \times N \times d_m}$ to isolate temporal cycles. We then apply the second attention mechanism over the *N* cycles for each variate. In the iTransformer, the MLP operates on univariate data, hypothesized to capture intrinsic time series properties like amplitude, periodicity, and frequency spectra (Liu et al., 2024a), for which we finally reshape the series from $\mathbb{R}^{(B \cdot C) \times N \times d_m}$ to $\mathbb{R}^{(B \cdot N) \times C \times d_m}$ before applying the MLP layers.

Table 5. iPatch outperforms iTransformer. We show pairwis
win comparisons among models and indicate significant p-value
following the sign test ($p < 0.05^*$). iPatch statistically outpe
forms iTransformer scoring 11 wins and a p-value of 0.05

#wins (\rightarrow)	DLinear	PatchTST	iTransformer	TimeMixer	TimeXer	iPatch
DLinear	-	6	6	6	7	7
PatchTST	8	_	8	7	6	6
iTransformer	8	6	-	7	8	3
TimeMixer	8	7	7	_	6	6
TimeXer	7	8	6	8	-	7
iPatch	7	8	11*	8	7	-

5.3. iPatch is not a champion although it may look so

First, we evaluate the performance of iPatch following either average MSE/MAE (Wang et al., 2024b) or average ranks. Table 4 shows that iPatch achieves the best average rank, the second-best MSE, and MAE. Complete results for iPatch are available in Table 12. In line with these outcomes and common practices in the field of LTSF, iPatch may "almost" seem the best-performing model. However, we then analyze more rigorously the results following the statistical analysis introduced in Section 5.1. In particular, we perform a Friedman test to compare the results of all the classifiers over all datasets from a statistical perspective. We obtain a Friedman statistic of 1.14 and a p-value of 0.95, demonstrating that there is actually no real champion from this analysis.

5.4. iPatch statistically outperforms iTransformer

Given the lack of a true champion, we proceed with pairwise comparisons among models by applying the sign test (Demšar, 2006). We first count the number of wins per dataset for each model and organize them in a 2D matrix, visible in Table 5. If the two algorithms compared are, as assumed under the null hypothesis, equivalent, each should win on approximately half of the datasets. We then compute the corresponding p-values for rejecting the null hypothesis, given that the number of wins follows a binomial distribution. There are no statistically significant differences among all pairwise comparisons except for iPatch and iTransformer, with the first model winning on 11/14 datasets and scoring a significant p-value of 0.05. This analysis provides two important takeaways: 1) The absence of statistical significance among pairwise comparisons re-iterates the lack of true champions among state-of-the-art models, and 2) with adhoc adjustments of existing architectures, it is still feasible to improve performance without claiming to be excellent overall. It is also essential to consider other factors that contribute to a model's superiority, such as the trade-offs introduced by architectural modifications between performance and efficiency (e.g., speed or memory consumption) or the actual net improvements that are practically relevant. However, these aspects fall beyond the scope of this paper.

6. Model selection based on dataset features

Identifying the appropriate model for a given dataset remains a challenging and nuanced task despite the availability of LTSF benchmarks. As anticipated in Section 2.1, BasicTS+ and TFB provide guidelines for this fundamental challenge (Shao et al., 2024; Qiu et al., 2024). In the following, we analyze whether our results align with previous observations. As we stated earlier, the tested models perform similarly across most datasets, regardless of architecture or characteristics, with MSE variations between datasets far exceeding those between models. For the following analyses, we make comparisons at a prediction length of 96 steps, as proposed in TFB.

6.1. Linear vs. transformer

BasicTS+ and TFB recommend using linear models when the data lacks clear patterns, has an increasing trend, or has a marked distribution shift. Conversely, transformers are recommended for datasets with clear patterns, strong internal similarities, or nonlinear structures. We revisit the example by (Shao et al., 2024) and assess the performance of a linear model (DLinear) versus transformer model (PatchTST) on data with clear and unclear patterns, respectively. We use the same dataset with an unclear pattern (Exchange) and replace their previously used PEMS with a clear pattern by PedestrianCounts (Figure 6). PatchTST outperforms DLinear on both occasions (Table 11), contradicting the previous claims by (Shao et al., 2024). We highlight that PatchTST, a transformer model, was excluded from their analysis for unknown reasons. However, both studies rely on limited datasets, urging caution before drawing broad conclusions.

6.2. Univariate vs. multivariate

Multivariate models should be preferred if – and only if – the dataset has strong inter-variate similarities (Shao et al., 2024; Qiu et al., 2024). To assess this guideline, we compare the performance of PatchTST (univariate) against iTransformer (multivariate) on all datasets. We use the explained variance from principal component analysis as a proxy for inter-variate similarity (Appendix B). Indeed, also for this comparison, we observe that neither model performs increasingly better depending on the inter-variate similarity as the ranks fluctuate across the full spectrum (Figure 5).

6.3. Future direction

From Figure 1, we only observe interesting and substantial differences in model performance in two datasets (*BenzeneConcentration* and *MotorImagery*). Hence, we recommend that the community prioritize identifying and analyzing datasets that differentiate performance across models, as such datasets are crucial for drawing meaningful conclu-



Figure 5. Univariate vs. multivariate PatchTST and iTransformer perform comparably as a function of explained variance.

sions. Extensive research is needed to establish clear model selection guidelines, addressing challenges like defining baselines, acquiring representative datasets, and analyzing experiments in a rapidly evolving architecture landscape.

7. Alternative view

Critics might argue that our results are suboptimal due to experimental limitations, that focusing on recent models excludes influential earlier architectures and introduces bias, or that testing selected models overlooks the field's diversity. Others may contend that some models consistently perform best on specific datasets, challenging our claim that no single model currently dominates in LTSF.

While these concerns are valid, our goal is not to establish exhaustive benchmarks or definitive rankings but to show that recent advancements often provide minimal improvement over earlier methods when experimental inconsistencies are addressed. The limitations in observed progress among the latest models underscore the need for the field to prioritize standardized and transparent testing practices over introducing increasingly complex architectures. Although our results may not be universally optimal, this further supports our position that small changes in experimental setups can significantly shift model rankings, making claims of superiority unreliable without standardized benchmarks and rigorous testing. By focusing on recent models, we intentionally highlight the current state of the field and its challenges in reliably evaluating and comparing new methods. Moreover, while some models may excel in narrow, context-specific scenarios, such isolated successes do not translate into universal applicability, further supporting our argument against the "champion" narrative.

8. Conclusions

In this work, we evaluated LTSF research, highlighting the need for rigorous and standardized benchmarking practices. Through an extensive and reproducible evaluation of 3,500+ models across 14 datasets, we demonstrated that claims of consistent performance improvements in newly published models often rely on specific experimental setups and evalu-

ation methods. Our findings question the idea of universal advancements, revealing that no single model consistently excels across our experiments. We identified issues in the LTSF domain, such as non-standardized evaluation frameworks, biased comparisons, and limited reproducibility that hinder fair assessment and delay real progress. To address these challenges, we recommend adopting standardized evaluation protocols, prioritizing benchmarking robustness over architectural complexity, and further investigating the link between dataset characteristics and model performance.

References

- Akiba, T., Sano, S., Yanase, T., Ohta, T., and Koyama, M. Optuna: A next-generation hyperparameter optimization framework. In *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 2019.
- Ansari, A. F., Stella, L., Turkmen, C., Zhang, X., Mercado, P., Shen, H., Shchur, O., Rangapuram, S. S., Arango, S. P., Kapoor, S., et al. Chronos: Learning the language of time series. arXiv preprint arXiv:2403.07815, 2024.
- Box, G. E. P. and Pierce, D. A. Distribution of residual autocorrelations in autoregressive-integrated moving average time series models. *Journal of the American Statistical Association*, 65(332):1509–1526, 1970.
- Breiman, L. Random forests. *Machine learning*, 45:5–32, 2001. doi: 10.1023/A:1010933404324.
- Brigato, L., Barz, B., Iocchi, L., and Denzler, J. Tune it or don't use it: Benchmarking data-efficient image classification. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV) Workshops*, pp. 1071–1080, October 2021.
- Cao, D., Jia, F., Arik, S. O., Pfister, T., Zheng, Y., Ye, W., and Liu, Y. Tempo: Prompt-based generative pre-trained transformer for time series forecasting. *arXiv preprint arXiv:2310.04948*, 2023.
- Challu, C., Olivares, K. G., Oreshkin, B. N., Ramirez, F. G., Canseco, M. M., and Dubrawski, A. Nhits: Neural hierarchical interpolation for time series forecasting. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pp. 6989–6997, 2023.
- Chang, C., Peng, W.-C., and Chen, T.-F. Llm4ts: Two-stage fine-tuning for time-series forecasting with pre-trained llms. *arXiv preprint arXiv:2308.08469*, 2023.
- Chen, T. and Guestrin, C. Xgboost: A scalable tree boosting system. In *Proceedings of the 22nd acm sigkdd international conference on knowledge discovery and data mining*, pp. 785–794, 2016.

- Das, A., Kong, W., Leach, A., Mathur, S., Sen, R., and Yu, R. Long-term Forecasting with TiDE: Time-series Dense Encoder, April 2024. URL http://arxiv. org/abs/2304.08424. arXiv:2304.08424 [stat].
- Demšar, J. Statistical comparisons of classifiers over multiple data sets. *The Journal of Machine learning research*, 7:1–30, 2006.
- Ekambaram, V., Jati, A., Nguyen, N. H., Dayama, P., Reddy, C., Gifford, W. M., and Kalagnanam, J. Ttms: Fast multi-level tiny time mixers for improved zero-shot and few-shot forecasting of multivariate time series. *arXiv* preprint arXiv:2401.03955, 2024.
- Friedman, J. H. Greedy function approximation: a gradient boosting machine. *Annals of statistics*, pp. 1189–1232, 2001.
- Friedman, M. The use of ranks to avoid the assumption of normality implicit in the analysis of variance. *Journal of the american statistical association*, 32(200):675–701, 1937.
- Friedman, M. A comparison of alternative tests of significance for the problem of m rankings. *The annals of mathematical statistics*, 11(1):86–92, 1940.
- Garza, A. and Mergenthaler-Canseco, M. Timegpt-1. arXiv preprint arXiv:2310.03589, 2023.
- Gruver, N., Finzi, M., Qiu, S., and Wilson, A. G. Large language models are zero-shot time series forecasters. *Advances in Neural Information Processing Systems*, 36, 2024.
- Hochreiter, S. and Schmidhuber, J. Long short-term memory. *Neural Computation*, 9(8):1735–1780, 1997. doi: 10. 1162/neco.1997.9.8.1735.
- Hyndman, R., Koehler, A. B., Ord, J. K., and Snyder, R. D. Forecasting with exponential smoothing: the state space approach. Springer Science & Business Media, 2008.
- Ke, G., Meng, Q., Finley, T., Wang, T., Chen, W., Ma, W., Ye, Q., and Liu, T.-Y. Lightgbm: A highly efficient gradient boosting decision tree. *Advances in neural information processing systems*, 30, 2017.
- Kim, J., Kim, H., Kim, H., Lee, D., and Yoon, S. A comprehensive survey of time series forecasting: Architectural diversity and open challenges. *arXiv preprint arXiv:2411.05793*, 2024.
- Koopmans, L. H. The spectral analysis of time series. Elsevier, 1995. doi: https://doi.org/10.1016/ B978-0-12-419251-5.X5000-5.

- Li, S., Jin, X., Xuan, Y., Zhou, X., Chen, W., Wang, Y.-X., and Yan, X. Enhancing the Locality and Breaking the Memory Bottleneck of Transformer on Time Series Forecasting. In Advances in Neural Information Processing Systems, volume 32. Curran Associates, Inc., 2019.
- Li, Z., Qi, S., Li, Y., and Xu, Z. Revisiting Long-term Time Series Forecasting: An Investigation on Linear Mapping, May 2023. URL http://arxiv.org/abs/2305. 10721. arXiv:2305.10721 [cs].
- Liu, M., Zeng, A., Chen, M., Xu, Z., LAI, Q., Ma, L., and Xu, Q. Scinet: Time series modeling and forecasting with sample convolution and interaction. In Koyejo, S., Mohamed, S., Agarwal, A., Belgrave, D., Cho, K., and Oh, A. (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 5816–5828. Curran Associates, Inc., 2022a.
- Liu, S., Yu, H., Liao, C., Li, J., Lin, W., Liu, A. X., and Dustdar, S. Pyraformer: Low-complexity pyramidal attention for long-range time series modeling and forecasting. In *International Conference on Learning Representations*, 2022b. URL https://openreview.net/forum? id=0EXmFzUn51.
- Liu, Y., Wu, H., Wang, J., and Long, M. Non-stationary transformers: Exploring the stationarity in time series forecasting. In Koyejo, S., Mohamed, S., Agarwal, A., Belgrave, D., Cho, K., and Oh, A. (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 9881–9893. Curran Associates, Inc., 2022c.
- Liu, Y., Hu, T., Zhang, H., Wu, H., Wang, S., Ma, L., and Long, M. iTransformer: Inverted Transformers Are Effective for Time Series Forecasting, March 2024a. URL http://arxiv.org/abs/2310.06625. Issue: arXiv:2310.06625 arXiv:2310.06625 [cs].
- Liu, Y., Zhang, H., Li, C., Huang, X., Wang, J., and Long, M. Timer: Generative pre-trained transformers are large time series models. In *Forty-first International Conference on Machine Learning*, 2024b. URL https: //openreview.net/forum?id=bYRYb7DMNo.
- McElfresh, D., Khandagale, S., Valverde, J., Prasad C, V., Ramakrishnan, G., Goldblum, M., and White, C. When do neural nets outperform boosted trees on tabular data? *Advances in Neural Information Processing Systems*, 36, 2024.
- Nie, Y., Nguyen, N. H., Sinthong, P., and Kalagnanam, J. A Time Series is Worth 64 Words: Long-term Forecasting with Transformers, March 2023. URL http://arxiv. org/abs/2211.14730. arXiv:2211.14730 [cs].

- Oreshkin, B. N., Carpov, D., Chapados, N., and Bengio, Y. N-beats: Neural basis expansion analysis for interpretable time series forecasting. In *International Conference on Learning Representations*, 2020. URL https: //openreview.net/forum?id=rlecqn4YwB.
- Qiu, X., Hu, J., Zhou, L., Wu, X., Du, J., Zhang, B., Guo, C., Zhou, A., Jensen, C. S., Sheng, Z., et al. Tfb: Towards comprehensive and fair benchmarking of time series forecasting methods. arXiv preprint arXiv:2403.20150, 2024.
- Rasul, K., Ashok, A., Williams, A. R., Khorasani, A., Adamopoulos, G., Bhagwatkar, R., Biloš, M., Ghonia, H., Hassen, N. V., Schneider, A., et al. Lag-llama: Towards foundation models for time series forecasting. arXiv preprint arXiv:2310.08278, 2023.
- Salzberg, S. L. On comparing classifiers: Pitfalls to avoid and a recommended approach. *Data mining and knowl*edge discovery, 1:317–328, 1997.
- Sezer, O. B., Gudelek, M. U., and Ozbayoglu, A. M. Financial time series forecasting with deep learning : A systematic literature review: 2005–2019. Applied Soft Computing, 90:106181, 2020. ISSN 1568-4946. doi: https://doi.org/10.1016/j.asoc.2020.106181. URL https://www.sciencedirect.com/ science/article/pii/S1568494620301216.
- Shao, Z., Wang, F., Xu, Y., Wei, W., Yu, C., Zhang, Z., Yao, D., Sun, T., Jin, G., Cao, X., et al. Exploring progress in multivariate time series forecasting: Comprehensive benchmarking and heterogeneity analysis. *IEEE Transactions on Knowledge and Data Engineering*, 2024.
- Soni, R., Nathani, M., and Mishra, R. Comprehensive evaluation of deep ltsf models for forecasting of air quality index. In 2024 IEEE International Conference on Big Data (BigData), pp. 4410–4419, 2024. doi: 10.1109/BigData62323.2024.10825393.
- Sun, C., Li, Y., Li, H., and Hong, S. Test: Text prototype aligned embedding to activate llm's ability for time series. *arXiv preprint arXiv:2308.08241*, 2023.
- Toda, H. Y. and Phillips, P. C. B. Vector autoregressions and causality. *Econometrica*, 61(6):1367–1393, 1993. doi: 10.2307/2951647.
- Wang, S., Wu, H., Shi, X., Hu, T., Luo, H., Ma, L., Zhang, J. Y., and Zhou, J. TimeMixer: Decomposable Multiscale Mixing for Time Series Forecasting, May 2024a. URL http://arxiv.org/abs/2405. 14616. arXiv:2405.14616 [cs].
- Wang, Y., Wu, H., Dong, J., Liu, Y., Long, M., and Wang, J. Deep Time Series Models: A Comprehensive Survey and Benchmark, July 2024b. URL http://arxiv.org/ abs/2407.13278. arXiv:2407.13278 [cs].

- Wang, Y., Wu, H., Dong, J., Qin, G., Zhang, H., Liu, Y., Qiu, Y., Wang, J., and Long, M. TimeXer: Empowering Transformers for Time Series Forecasting with Exogenous Variables, November 2024c. URL http:// arxiv.org/abs/2402.19072. arXiv:2402.19072 [cs].
- Weron, R. Electricity price forecasting: A review of the state-of-the-art with a look into the future. International Journal of Forecasting, 30 (4):1030-1081, 2014. ISSN 0169-2070. doi: https://doi.org/10.1016/j.ijforecast.2014.08.008. URL https://www.sciencedirect.com/ science/article/pii/S0169207014001083.
- Woo, G., Liu, C., Kumar, A., Xiong, C., Savarese, S., and Sahoo, D. Unified training of universal time series forecasting transformers. arXiv preprint arXiv:2402.02592, 2024.
- Wu, H., Xu, J., Wang, J., and Long, M. Autoformer: Decomposition transformers with auto-correlation for long-term series forecasting. *Advances in neural information processing systems*, 34:22419–22430, 2021.
- Wu, H., Hu, T., Liu, Y., Zhou, H., Wang, J., and Long, M. TimesNet: Temporal 2D-Variation Modeling for General Time Series Analysis, April 2023. URL http:// arxiv.org/abs/2210.02186. arXiv:2210.02186 [cs].
- Xue, H. and Salim, F. D. Promptcast: A new promptbased learning paradigm for time series forecasting. *IEEE Transactions on Knowledge and Data Engineering*, 2023.
- Zeng, A., Chen, M., Zhang, L., and Xu, Q. Are Transformers Effective for Time Series Forecasting?, August 2022. URL http://arxiv.org/abs/2205. 13504. arXiv:2205.13504 [cs].
- Zhang, Y. and Yan, J. Crossformer: Transformer utilizing cross-dimension dependency for multivariate time series forecasting. In *The eleventh international conference on learning representations*, 2023.
- Zhou, H., Zhang, S., Peng, J., Zhang, S., Li, J., Xiong, H., and Zhang, W. Informer: Beyond efficient transformer for long sequence time-series forecasting. In *Proceedings of the AAAI conference on artificial intelligence*, volume 35, pp. 11106–11115, 2021.
- Zhou, T., Ma, Z., Wen, Q., Wang, X., Sun, L., and Jin, R. FEDformer: Frequency enhanced decomposed transformer for long-term series forecasting. In Chaudhuri, K., Jegelka, S., Song, L., Szepesvari, C., Niu, G., and Sabato, S. (eds.), *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings*

of Machine Learning Research, pp. 27268–27286. PMLR, 17–23 Jul 2022a. URL https://proceedings. mlr.press/v162/zhou22g.html.

Zhou, T., Ma, Z., Wen, Q., Wang, X., Sun, L., and Jin, R. Fedformer: Frequency enhanced decomposed transformer for long-term series forecasting. In *International conference on machine learning*, pp. 27268–27286. PMLR, 2022b.

A. Related work

A.1. Classical approaches

Traditional statistical methods, such as AutoRegressive Integrated Moving Average (Box & Pierce, 1970), Vector Autoregression (Toda & Phillips, 1993), Exponential Smoothing (Hyndman et al., 2008), and Spectral Analysis (Koopmans, 1995) were widely used in TS forecasting. Progressively, machine learning models such as XGBoost (Chen & Guestrin, 2016), Random Forest (Breiman, 2001), Gradient Boosting Regression Trees (Friedman, 2001), and LightGBM (Ke et al., 2017) have shown improvements in the forecast due to their ability to handle non-linear patterns.

A.2. Deep learning models

Deep learning models have advanced TS forecasting, starting with Recurrent Neural Networks (RNNs), specifically designed to model sequential data. In particular, advanced variants such as RNNs with Long Short-Term Memory units, widely adopted within the TS community, have seen significantly increased usage (Hochreiter & Schmidhuber, 1997). Additionally, MLP-based models, such as DLinear (Zeng et al., 2022), N-BEATS (Oreshkin et al., 2020), and N-Hits (Challu et al., 2023) use MLP to learn the coefficients that produce both backcast and forecast outputs from their structure.

Originally from NLP, the Transformer architecture is increasingly adapted for time series forecasting, often with modified attention layers to capture temporal dependencies, as seen in Section 2 and other prior works, which we describe in the following. Informer (Zhou et al., 2021) and Pyaformer (Liu et al., 2022b) are transformer-based models that modify the attention mechanism. Informer designs a ProbSparse self-attention mechanism to replace the standard self-attention. Pyaformer, on the other hand, presents a pyramidal attention module, where the inter-scale tree structure captures features at different resolutions, and the intra-scale neighboring connections model the temporal dependencies across different ranges. Wu et al. (Wu et al., 2021) introduced the Autoformer with an Auto-Correlation mechanism to capture the series-wise temporal dependencies based on the learned periods. Following, FEDformer (Zhou et al., 2022b) utilizes a mixture-of-expert framework to improve seasonal-trend decomposition and integrates Fourier and Wavelet-enhanced blocks to capture key structures in the TS. (Zhang & Yan, 2023) presented Crossformer, a transformer-based model utilizing cross-dimension dependency for multivariate TS forecasting. Another recent approach is TimesNet (Wu et al., 2023), which is a univariate 2D CNN that segments 1D time series according to Fourier decomposition. The segments are then stacked to build a 2D series. This enables the convolutions to simultaneously look at the local structure of the signal at t_i and t_{i-T} simultaneously, where T denotes a dominant signal period.

A.3. Large Language Models

The success of Large Language Models (LLMs) like BERT and GPT in natural language processing has inspired researchers to apply these models to TS tasks. One significant approach involves transforming numerical TS data into natural language prompts to leverage pre-trained language models without modifications. PromptCast (Xue & Salim, 2023) and (Gruver et al., 2024) present this method, demonstrating effective generalization in zero-shot settings and often outperforming traditional numerical models. Moving to few-shot training strategies, TEST (Sun et al., 2023) adapts TS data for pre-trained LLMs by tokenizing the data and aligning the embedding space, particularly in few-shot and generalization scenarios. Several frameworks focus on enhancing TS forecasting through specialized fine-tuning strategies such as LLM4TS (Chang et al., 2023) and TEMPO (Cao et al., 2023).

A.4. Foundation Models

There is a growing interest in foundation models designed explicitly for TS tasks. Tiny Time Mixers (Ekambaram et al., 2024) introduce a compact model for multivariate TS forecasting. Timer-XL is a foundation model for unified time series forecasting, supporting univariate and multivariate data by extending next-token prediction for causal generation (Liu et al., 2024b). The model introduced a universal TimeAttention mechanism to capture fine-grained intra- and inter-series dependencies. MOIRAI (Woo et al., 2024) addresses challenges like cross-frequency learning and varied distributional properties in large-scale data, achieving competitive zero-shot forecasting performance. TimeGPT-1 (Garza & Mergenthaler-Canseco, 2023) and Lag-LLama (Rasul et al., 2024), utilizing decoder-only transformer architectures and achieving strong zero-shot generalization. Chronos (Ansari et al., 2024) trains transformer-based models on discrete tokens processed from TS data, demonstrating superior performance on diverse datasets.

B. Datasets

We include a commonly used set of small datasets (*ETT**, *Electricity*, *Weather*, *Exchange*) and a set of larger datasets (*MotorImagery*, *TDBrain*, *BeijingAir*, *BenzeneConcentration*, *AustraliaRainfall*, *KDDCup2018*, *PedestrianCounts*) which represents a subset of the Unified Time Series Dataset (UTSD) (Liu et al., 2024b).

This section provides a summary of descriptive statistics about the used datasets, an example of two contrastive datasets with clear and unclear patterns, respectively, and dataset-specific preprocessing steps.

B.1. Dataset statistics

				Tabl	le 6. Dataset	statistics.				
Domain	Dataset	# Timesteps	# Channels	Shannon Entropy	Spectral Entropy	Sample Entropy	Stationarity	Complexity	Explained Variance (PC1)	Source
Energy	ETTh1	17420	7	0.775	0.669	0.769	-5.909	0.497	0.344	(Wang et al., 2024b)
Energy	ETTm1	69680	7	0.789	0.548	0.430	-14.985	0.485	0.346	(Wang et al., 2024b)
Energy	ETTh2	17420	7	0.813	0.639	0.526	-4.136	0.397	0.431	(Wang et al., 2024b)
Energy	ETTm2	69680	7	0.817	0.527	0.319	-5.664	0.425	0.431	(Wang et al., 2024b)
Energy	Electricity	26304	321	0.516	0.497	0.714	-8.445	0.673	0.547	(Wang et al., 2024b)
Environment	Weather	52696	21	0.453	0.57	0.110	-26.681	0.632	0.424	(Wang et al., 2024b)
Economic	Exchange	7588	8	0.805	0.347	0.066	-1.902	0.529	0.618	(Wang et al., 2024b)
Health	MotorImagery	1134000	64	0.719	0.519	0.326	-3.133	0.763	0.305	(Liu et al., 2024b)
Health	TDBrain	2221212	33	0.823	0.749	0.987	-3.167	0.404	0.475	(Liu et al., 2024b)
Environment	BeijingAir	407184	9	0.493	0.686	0.951	-13.253	0.165	0.383	(Liu et al., 2024b)
Environment	BenzeneConcentration	2042880	8	0.799	0.701	1.938	-3.114	-0.049	0.534	(Liu et al., 2024b)
Environment	AustraliaRainfall	3846408	3	0.838	0.604	2.215	-31.734	-0.013	0.996	(Liu et al., 2024b)
Environment	KDDCup2018	2942364	1	0.569	0.665	0.410	-9.379	0.530	1.000	(Liu et al., 2024b)
Transport	PedestrianCounts	3132346	1	0.687	0.522	0.412	-4.590	0.630	1.000	(Liu et al., 2024b)

In Table 6, we provide a comprehensive description of the datasets employed in this work and their corresponding statistics. In the following, we describe in detail the various analyses employed to derive such dataset features.

Time steps and channels We counted the *number of time steps* and *number of channels* as the size of the respective dimension.

Shannon entropy and spectral entropy Shannon entropy quantifies the average level of uncertainty or information content associated with the outcomes in a discrete variable X. Spectral entropy, a related concept, applies this measure to the frequency domain, using the normalized power spectral density as the probability distribution. Entropy is calculated as

$$H(X) = -\sum_{x \in \chi} p(x) \log p(x)$$

where χ is the set of all possible outcomes, and p(x) is the probability of outcome x.

Sample Entropy Sample entropy is a statistical measure used to quantify the complexity or regularity of a time series. Unlike Shannon entropy, which evaluates uncertainty in discrete probability distributions, sample entropy assesses the likelihood that similar patterns in the time series remain similar at the next time step. It is defined as the negative natural logarithm of the conditional probability that two sequences of length m that match within a tolerance r will still match when extended to m + 1. A lower sample entropy indicates more regularity or predictability in the time series, while a higher value suggests greater randomness or complexity. Sample entropy is calculated as

$$\mathsf{SampEn}(m,r,N) = -\ln\frac{A}{B}$$

where m is the embedding dimension, r is the tolerance, N is the total length of the time series, A is the number of matching pairs of length m + 1, and B is the number of matching pairs of length m.

Stationarity In LTSF, stationarity is an important characteristic of time series, where the statistical characteristics, such as mean and variance, remain constant over time. We used the Augmented Dickey-Fuller (ADF) test to assess stationarity. This test evaluates the null hypothesis that a unit root is present and confirms stationarity if $\gamma < 0$ and the result is statistically significant. We report γ since it scales with stationarity.

Complexity In time series analysis, complexity refers to the irregularity or unpredictability in the data. We quantify complexity by using Higuchi's fractal dimension. A higher fractal dimension indicates greater complexity, while a lower value suggests more regularity or predictability in the data. Higuchi's fractal dimension is calculated as

$$D = \lim_{k \to 0} \frac{\log\left(\sum_{i=1}^{n} \left(\frac{|x_{i+k} - x_i|}{k}\right)\right)}{\log k}$$

where x_i represents the data points, k is the time scale, and the sum is taken over different segments of the time series.

Inter-variate similarity As a proxy for inter-variate similarity, we provide the explained variance of the first principal component (PC1) obtained through principal component analysis (PCA). PC1 represents the direction of maximum variance in the data, capturing the dominant shared variation among the variables. The explained variance of PC1 quantifies the proportion of the total variance that is accounted for by this component. A higher explained variance indicates stronger similarity and shared dynamics among the variables, while a lower value suggests more independent behavior.

B.2. Clear vs. unclear patterns

In Section 6, we assessed the performance of a linear model versus a transformer model on datasets with clear and unclear patterns, respectively. We use the same dataset as BasicTS+ (Shao et al., 2024) with an unclear pattern (*Exchange*) and replace their previously used PEMS with a clear pattern by *PedestrianCounts* (Fig. 4). The plots of the time series highlight contrasting characteristics: *Exchange* displays seemingly random trends, whereas *PedestrianCounts* exhibits evident cyclic behavior. To further emphasize this distinction, we provide butterfly plots, which reveal pronounced periodic patterns in *PedestrianCounts* and irregular, stochastic-like trends in *Exchange*. Additionally, the power spectrum analysis underscores this contrast, showing a dominant peak for *PedestrianCounts* and an absence of such peaks for *Exchange*.



Figure 6. Distinct temporal patterns in two datasets.

B.3. Preprocessing

We followed the preprocessing steps from TSlib (Wang et al., 2024b). Furthermore, we added functionality to import data from UTSD as curated by (Liu et al., 2024b). Since the UTSD datasets are magnitudes larger, we modified the respective dataloader to return sequences at a stride length S = 100 to accelerate the training.

C. Exact hyperparameters

To ensure a fair comparison, we performed an extensive hyperparameter search for all models on all the datasets. We searched for input length, learning rate, number of layers, and model dimension. The specific ranges are presented inTable 7. Note that the range was the same for all models except for TimeMixer. In that case, we limited the range for the number of layers and model dimensions due to increasingly high memory demands (> 49GB of VRAM on an RTX A6000 GPU if $d_m > 128$ and L = 720). However, this is unlikely to affect performance, as the original HP search for all datasets in TimeMixer yielded results within these limits.

Tabl	e 7. Exact values of hyperpara	neters searched.
Hyperparameter	TimeMixer	Other Models
Input Length	{96, 192, 336, 720}	{96, 192, 336, 720}
Learning Rate	$\{10^{-5}, 10^{-4}, 10^{-3}, 10^{-2}\}$	$\{10^{-5}, 10^{-4}, 10^{-3}, 10^{-2}\}$
#Layers	{1, 2, 3}	{1, 2, 3, 4}
d_m	{16, 32, 64, 128}	{16, 32, 64, 128, 256, 512}

The patch length, a parameter used in PatchTST and TimeXer (and by extension also iPatch), was set based on the characteristics of the datasets (Table 8). As visualized in Figure 6, there are datasets with dominant periodic behavior. We set the patch length $P \approx \operatorname{argmax}(\operatorname{FFT}(X))$ wherever we observed such a natural pattern. Unsurprisingly, the patch length resulted in a span of one day in all datasets with a pattern. In the remaining cases, we set the patch length manually (*Exchange, MotorImagery, TDBrain*). We aligned with the idea of TimesNet, which introduced series segmentation based on dominant frequencies to enhance performance (Wu et al., 2023). Moreover, the original works concluded that variations in patch length have minimal effects (Nie et al., 2023; Wang et al., 2024c).

Table 8. Patch lengths. Details of the employed patch lengths for PatchTST, TimeXer, and iPatch models.

Dataset	ETTh*	ETTm*	Electricity	Weather	Exchange	MotorImagery	otorImagery TDBrain Beijir		BenzeneConcentration	AustraliaRainfall	KDDCup2018	PedestrianCounts
Patch Length	24	96	24	24	96	96	48	24	24	24	24	24

D. Results reliability

Table 9. **Results reliability.** To assess the reliability of our results, we compare our implementation (best and average MSE) against the original works on popular datasets. Despite not being directly comparable for slight differences in setups, we align with previous values.

Dataset	DLinear				PatchTST	,		iTransform	er		TimeMixe	r		TimeXer	
Implementation	Original	Ours Min	Ours Mean	Original	Ours Min	Ours Mean	Original	Ours Min	Ours Mean	Original	Ours Min	Ours Mean	Original	Ours Min	Ours Mean
ETT*	0.37	0.378	0.378	0.338	0.332	0.336	0.383	0.342	0.344	0.333	0.342	0.349	0.363	0.341	0.346
Electricity	0.166	0.162	0.162	0.159	0.163	0.164	0.178	0.162	0.166	0.156	0.154	0.156	0.171	0.165	0.170
Weather	0.246	0.244	0.244	0.225	0.224	0.225	0.258	0.237	0.239	0.241	0.225	0.231	0.241	0.222	0.224

E. Stability of HP search

In this section, we perform a small proof-of-concept experiment to show the reliability of our HP search. For a subset of datasets and models, we performed two independent HP runs and consequent training of three models with the found optimal HPs to analyze the stability of the performed HP search. We focused on prediction horizon 96. In Figure 7, we plot the MSE of the two searches over two opposing axes, meaning that points on the diagonal indicate a very stable search that leads to the same final result. To provide an even more comprehensive analysis, we show the average of the three final models (left) and also the best model out of the final three (right). The averages show a few cases with slight variability, namely PatchTST on *BejingAir* and TimeXer on *BenzeneConcentration*, but overall, the experiment proves a reliable and stable HP search across independent runs. In the case of best results (Figure 7, right), the variability is even less noticeable.



Figure 7. HP search variability. Comparison among two independent HP search results in terms of MSE for forecast horizon 96. The average of the final three models shows minimal variability except for a few cases (left), while the best model is even more stable (right).

F. Statistical tests

F.1. Friedman test

The Friedman test (Friedman, 1937; 1940) is a non-parametric statistical method designed as an alternative to repeatedmeasures ANOVA. It enables the comparison of multiple algorithms across multiple datasets when the assumptions of parametric tests may not hold. The test works by ranking the algorithms on each dataset separately, with the best-performing algorithm assigned a rank of 1, the second-best a rank of 2, and so forth. In cases of tied performance, average ranks are assigned across the tied algorithms.

Let r_i^j denote the rank of the *j*-th algorithm out of *k* algorithms on the *i*-th dataset out of *N* datasets. The Friedman test evaluates the average ranks of the algorithms, calculated as $R^j = \frac{1}{N} \sum_{i=1}^{N} r_i^j$. Under the null hypothesis, which assumes that all algorithms are equivalent in performance and thus their ranks R^j should be approximately equal, the Friedman statistic is given by:

$$\chi_F^2 = \frac{12N}{k(k+1)} \left[\sum_{j=1}^k (R^j)^2 - \frac{k(k+1)^2}{4} \right]$$

For sufficiently large values of N and k, as a rule of thumb N > 10 and k > 5 (Demšar, 2006), this statistic follows a χ^2 distribution with k - 1 degrees of freedom. Note our experimental setup aligns with these conditions.

The Friedman test, though less powerful than parametric repeated-measures ANOVA when its assumptions are met, is more robust in handling violations of these assumptions, with (Friedman, 1940) observing largely consistent results between the two tests across 56 independent problems.

F.2. Sign test

The sign test (Salzberg, 1997) is a non-parametric statistical method commonly used to compare the performance of two algorithms across multiple datasets. It operates by evaluating the number of datasets on which each algorithm outperforms the other, assuming that the outcomes are independent and identically distributed. Contrary to popular belief, counting only significant wins and losses actually makes the tests less reliable, as it imposes an arbitrary threshold of p < 0.05 to



Figure 8. **Impact of datasets.** We provide an alternative view of Figure 2 and clearly visualize that the difference in average scores solely depends on the *MotorImagery* dataset All baselines score similar results over the rest of the datasets.

determine meaningfulness (Demšar, 2006).

Under the null hypothesis, it is assumed that the two algorithms are equivalent in their performance, and thus, each algorithm has an equal probability (0.5) of outperforming the other on a given dataset. This leads to the number of wins for either algorithm following a binomial distribution with parameters N (the total number of datasets) and p = 0.5. The null hypothesis is rejected if the observed number of wins for one algorithm is significantly different from $\frac{N}{2}$, indicating that one algorithm systematically outperforms the other.

For small sample sizes, as in our case, with a total number of datasets being equal to 14, critical values can be determined directly from the cumulative distribution function of the binomial distribution. For larger sample sizes, the central limit theorem allows for an approximation using the normal distribution. Specifically, the number of wins under the null hypothesis can be approximated by a normal distribution with mean $\mu = N/2$ and standard deviation $\sigma = \sqrt{N}/2$. In cases where there are ties in performance, these ties are treated as supporting evidence for the null hypothesis. To account for this, ties are split evenly between the two algorithms. If the number of tied datasets is odd, one tie is disregarded to ensure that only whole numbers are assigned to each algorithm.

G. Baseline comparisons

We provide an overview of included baselines for the top-performing LTSF models (Table 10). We observe that previous models were replaced by recent ones as the field progressed. We highlight that TimeMixer was not included as a baseline in TimeXer, although it was available at the time.

H. Full results

Table 11 shows the full results from our extensive experiments. We present the MSE and MAE for all forecast horizons $T \in \{96, 192, 336, 720\}$ and their average, respectively. To provide a comprehensive view, we show the best and the average values over three random seeds. Table 12 presents the corresponding full results for iPatch.

Table 10. Included baseline models from top-performing models in long-term forecasting. x: included; o: introduced

Model	DLinear (2022)	PatchTST (2022)	TimeMixer (2024a)	iTransformer (2024a)	TimeXer (2024c)	FEDformer (2022b)	Autoformer (2021)	Informer (2021)	Pyraformer (2022b)	LogTrans (2019)	Stationary (2022c)	Crossformer (2023)	TimesNet (2023)	SCINet (2022a)	Rlinear (2023)	TiDE (2024)	others
DLinear (2022)	0					x	х	х	х	х							
PatchTST (2023)	x	0				x	х	х	х	х							
TimeMixer (2024a)	x	х	0			x	х	х			х	х	х				х
iTransformer (2024a)	x	х		0		x	х				х	х	х	х	х	х	
TimeXer (2024c)	x	х		х	0		х		х		х	х	х	х	х	х	

	Model		DLi	inear		<u>`</u>	Patc	hTST			iTrans	former	0	1	Tin	neMixer			Time	Xer	
Detecat	Metric	I м	AE	м	ISE	М	AF	м	SE	I м	AF	м	SE	м	AE	MS	E	м	AE	MS	SE.
Dataset	Statistia	Maan	Min	Maan	Min	Moon	Min	Maan	Min	Meen	Min	Mean	Min	Maan	Min	Mean	Min	Maan	Min	Maan	Min
	Statistic	wiean	. 2022	wican	NIII	Nicali	0.402.4	a azao	0.0770		0.4002	a acor	0.2707	wiean	Willi	a area	NIIII	Nicali	0.0076	0.0750	0.0710
	96	0.3938	0.3932	0.3703	0.3698	0.4044	0.4034	0.3798	0.3779	0.4031	0.4002	0.3806	0.3787	0.3967	0.4261	0.3702	0.3682	0.4001	0.3976	0.3758	0.3/12
ETT51	336	0.5320	0.532	0.5427	0.5426	0.4329	0.4306	0.4221	0.4170	0.4423	0.4413	0.4351	0.4327	0.4416	0.4381	0.438	0.4343	0.4345	0.4308	0.4247	0.4217
LIIII	720	0.5464	0.5428	0.5608	0.5551	0.4626	0.4543	0.4378	0.4231	0.4876	0.4847	<u>0.4684</u>	<u>0.4646</u>	0.4985	0.4944	0.4968	0.4909	0.4957	0.4934	0.4831	0.4812
	Average	0.4772	0.4761	0.4741	0.4725	0.4319	0.4279	0.4143	0.4076	0.4428	0.4408	0.4244	0.4217	0.4429	0.4386	0.429	0.4245	0.4400	0.4361	0.4252	0.4204
	96	0.3736	0.3736	0.3415	0.3415	0.3737	0.3705	0.3263	0.3236	0.387	0.3801	0.3374	0.3294	0.3869	0.3777	0.3410	0.3292	0.3961	0.3902	0.3482	0.3393
	192	0.4070	0.4070	0.4015	0.4015	0.4120	<u>0.4097</u>	0.3618	0.3613	0.4254	0.4243	0.4028	0.4008	0.4272	0.4126	0.3972	0.3692	0.4279	0.422	0.4010	0.3934
ETTm1	336	0.4349	0.4325	<u>0.4116</u>	<u>0.4093</u>	<u>0.4445</u>	<u>0.4431</u>	0.4062	0.4019	0.4519	0.4469	0.4232	0.4157	0.4808	0.4733	0.4976	0.487	0.4612	0.4575	0.4277	0.4246
	720	0.4716	0.4701	0.4578	0.4567	0.4955	0.4937	0.4799	0.4792	0.4850	0.482	0.4687	0.4657	0.4997	0.4905	0.4904	0.4773	0.4931	0.4894	0.4715	0.4645
	Average	0.4218	0.4208	<u>0.4031</u>	<u>0.4023</u>	<u>0.4314</u>	<u>0.4292</u>	0.3936	0.3915	0.4373	0.4333	0.408	0.4029	0.4487	0.4385	0.4315	0.4157	0.4446	0.4398	0.4121	0.4054
	96	0.3677	0.3655	0.3042	0.3014	0.3414	0.3389	0.2833	0.2807	0.3515	0.348	0.3026	0.2964	<u>0.3439</u>	<u>0.3413</u>	0.287	<u>0.2836</u>	0.3489	0.3460	0.2965	0.2948
	192	0.4429	0.4428	0.4232	0.4231	0.3919	0.3902	0.3602	0.3563	0.4016	0.3972	0.3837	0.379	0.4055	0.4041	0.3876	0.3843	0.3971	0.3954	0.3658	0.3624
ETTh2	720	0.5990	0.5988	0.6997	0.6991	0.48	0.4245	0.4677	0.4548	0.4436	0.4220	0.4245	0.4237	0.4288	0.4201	0.4144	0.4081	0.4200	0.4515	0.4441	0.4435
	Average	0 4743	0.4736	0 4849	0 4841	0.4099	0.4062	0 3793	0.3736	0 4054	0.4028	0 3784	0 3742	0 4044	0.4011	0 3744	0 3684	0.4063	0.4038	0 3770	0 3746
	06	0.2215	0.2215	0.1015	0.1091	0.2243	0.2234	0.1003	0.1080	0.2225	0.2222	0.1170	0.1176	0.2253	0.224	0.1102	0.1080	0.2275	0.2273	0.1136	0.1121
	192	0.2471	0.2215	0.134	0.1339	0.2561	0.2547	0.1396	0.1384	0.2525	0.2608	0.1483	0.1473	0.2532	0.2527	0.1399	0.1395	0.2689	0.2636	0.1562	0.1505
ETTm2	336	0.2713	0.2712	0.1616	0.1616	0.2811	0.279	0.1675	0.1658	0.2899	0.2891	0.1826	0.1816	0.2848	0.2826	0.1792	0.1746	0.287	0.2853	0.1785	0.1771
	720	0.3044	0.3044	0.2008	0.2008	<u>0.3148</u>	<u>0.3133</u>	<u>0.2089</u>	<u>0.2079</u>	0.3195	0.3175	0.2157	0.2135	0.3183	0.315	0.2179	0.2161	0.3235	0.3213	0.2246	0.2211
	Average	0.2611	0.261	0.1511	0.1511	0.2691	0.2676	0.1563	0.1552	0.2759	0.2749	0.1661	0.1650	0.2704	0.2686	0.1618	0.1598	0.2767	0.2744	0.1682	0.1654
	96	0.2298	0.2298	0.1330	0.1330	0.2274	0.227	0.1301	<u>0.1300</u>	0.2300	0.2290	0.1350	0.134	0.2280	0.2270	0.1311	0.1299	0.2398	0.2393	0.1375	0.1372
	192	0.275	0.2749	0.2156	0.2156	<u>0.2465</u>	0.2458	<u>0.1972</u>	0.1962	0.2582	0.2579	0.2076	0.2071	0.2545	<u>0.2437</u>	0.2044	<u>0.1938</u>	0.2415	0.2392	0.192	0.1892
Electricity	336	0.2621	0.2612	0.1633	0.1627	0.2718	0.2713	0.1725	0.1710	0.2686	0.2602	0.1696	0.1629	0.2645	0.2618	0.1653	0.1628	0.2611	0.2575	0.1626	0.1599
	120	0.2991	0.2991	0.2031	0.2031	0.3045	0.3038	0.207	0.2062	0.2975	0.2957	0.2046	0.2024	0.2811	0.2785	0.1820	0.1785	0.321	0.3106	0.2293	0.2135
	Average	0.2585	0.2583	0.1616	0.1615	0.2613	0.2608	0.164	0.1634	0.2622	0.2577	0.1655	0.162	0.2704	0.2686	0.1618	0.1598	0.2676	0.2635	0.1695	0.1645
	96	0.2262	0.226	0.1678	0.1678	0.1952	0.1947	0.1455	0.1451	0.2158	0.2141	0.164	0.1616	0.2114	0.2012	0.1567	0.1487	0.1991	0.1975	0.1472	0.1459
1 17	336	0.2750	0.2749	0.2625	0.2136	0.2403	0.2438	0.2431	0.1902	0.2382	0.2379	0.2601	0.258	0.2343	0.2849	0.2044	0.2496	0.2413	0.2392	0.192	0.2426
Weather	720	0.3767	0.3767	0.3307	0.3307	0.3298	0.3279	0.3123	0.3111	0.3427	0.3408	0.322	0.3202	0.3284	0.3259	0.3108	0.3069	0.3291	0.3278	0.3103	0.309
	Average	0.2984	0.2984	0.2442	0.2441	0.2633	0.2623	0.2245	0.2235	0.2791	0.2779	0.2385	0.2367	0.2707	0.2639	0.2313	0.2248	0.2639	0.2616	0.2237	0.2217
	96	0.2166	0.2166	0.0963	0.0963	0.2153	0.2112	0.0953	0.0913	0.2134	0.2131	0.0929	0.0922	0.2363	0.2116	0.1074	0.0920	0.2158	0.2148	0.0954	0.0947
	192	0.3385	0.337	0.2271	0.2249	0.308	0.3031	0.1888	0.183	0.3023	0.3017	0.1804	0.18	0.3334	0.3138	0.2173	0.192	0.3043	0.3033	0.184	0.1828
Exchange	336	1.2155	1.204	2.2101	2.1704	0.8419	0.8405	1.1522	1.1326	0.7177	0.6595	0.8852	0.7692	123.74	1.0005	134815	1.5782	<u>0.7949</u>	0.7489	1.0473	0.9525
	720	0.5913	0.5756	0.5681	0.5296	0.9331	0.9137	1.5152	1.4605	0.9954	0.9834	1.6394	1.607	1.5125	1.4158	5.0646	3.7279	0.9313	0.9261	1.4625	1.437
	Average	0.5905	0.5833	0.7754	0.7553	0.5746	0.5671	0.7379	0.7169	0.5572	0.5394	0.6995	0.6621	31.457	0.7354	33705	1.3975	<u>0.5616</u>	0.5483	0.6973	0.6667
	96	0.9128	0.9106	2.7345	2.7281	0.7809	0.779	2.0489	2.0277	0.1654	0.159	0.4718	0.438	0.754	0.7213	2.0469	1.9562	0.3444	0.3064	1.2702	1.1502
	192	1.1518	1.1498	4.5688	4.5506	0.9406	0.9345	3.3327	3.289	0.2719	0.2382	0.8407	0.7093	0.9481	0.9367	3.5042	3.4629	0.8772	0.8567	<u>3.1613</u> 5.1760	<u>3.1102</u> 5.0606
MotorImagery	720	1.3270	1.3410	5.1007	5.0979	1.2071	1.2005	4.9048	4.8849	0.4500	0.5693	3.0805	2.7657	1.2243	1.2203	4.9304	4.9205	1.2676	1.2643	4.9876	4.9838
	Average	1.1834	1.1821	4.5924	4.5831	1.006	1.0004	3.7749	3.7446	0.3835	0.3378	1.6916	1.4959	1.0113	0.9958	3.8691	3.8126	0.9155	0.8933	3.6490	3.5762
	96	0.6500	0.6499	0.7693	0.7692	0 5958	0 5951	0.6641	0.662	0 5979	0 5966	0.6726	0.6704	0 5959	0 5916	0.673	0.6636	0.5911	0.5906	0.6574	0.6566
	192	0.7463	0.7463	1.0022	1.0021	0.6695	0.6689	0.8348	0.8335	0.6671	0.6653	0.8314	0.8277	0.6688	0.6657	0.8374	0.8296	0.6633	0.6626	0.824	0.8224
TDBrain	336	0.8460	0.8460	1.2863	1.2862	0.7543	0.7467	1.066	1.0467	0.7488	0.7451	1.0531	1.0438	0.7498	0.7469	1.0568	1.0493	0.7482	0.743	1.0505	1.0373
	720	0.9643	0.9633	1.5473	1.5443	0.8798	0.8786	1.3633	1.3606	<u>0.8757</u>	<u>0.8753</u>	1.3561	1.3551	0.8767	0.8755	1.3575	1.3545	0.8722	0.871	1.3479	1.3441
	Average	0.8016	0.8014	1.1513	1.1505	0.7248	0.7223	0.9821	0.9757	<u>0.7224</u>	0.7206	<u>0.9783</u>	<u>0.9742</u>	0.7228	<u>0.7199</u>	0.9812	<u>0.9742</u>	0.7187	0.7168	0.97	0.9651
	96	<u>0.4409</u>	0.4399	<u>0.5290</u>	0.5279	0.7806	0.428	1.6671	<u>0.5181</u>	0.4415	0.4326	0.5399	0.5145	0.4516	0.4411	0.5515	0.5275	0.4321	<u>0.4300</u>	0.5261	0.5219
	192	0.4635	0.4634	0.5690	0.5687	0.4543	0.4539	0.5723	0.5716	0.4584	0.4578	0.5710	0.5677	0.4717	0.4674	0.5955	0.5763	0.4538	0.4483	0.5737	0.5627
BeijingAir	720	0.5088	0.5068	0.6426	0.6415	0.4879	0.4858	0.5908	0.5905	0.4682	0.4675	0.5948	0.5955	0.4948	0.4004	0.6309	0.6292	0.4961	0.4944	0.6393	0.6354
	Average	0.4716	0.4708	0.5829	0.5823	0.5472	0.4584	0.8643	0.5758	0.4641	0.4612	0 5801	0 5719	0.4712	0.467	0.5917	0.5804	0.4618	0.4591	0.5818	0.5765
	06	0.4710	0.0144	0.0067	0.0065	0.0407	0.0202	0.0005	0.0003	0.0582	0.0482	0.0105	0.0088	0.4712	0.0132	0.0050	0.0059	0.3792	0.0625	0.3288	0.0122
	192	0.0102	0.0134	0.0066	0.0065	0.0407	0.0393	0.0095	0.0095	0.0367	0.0432	0.0077	0.0076	0.0185	0.0152	0.0063	0.0062	0.03782	0.0329	0.0103	0.0122
BenzeneConcentration	336	0.0192	0.0173	0.0082	0.008	0.0415	0.0396	0.0094	0.0093	0.0586	0.0551	0.0133	0.0126	0.0285	0.0196	0.0079	0.0075	0.0321	0.03	0.0114	0.0113
	720	<u>0.0282</u>	0.026	0.0115	0.0114	0.0583	0.0504	0.0157	0.0147	0.0581	0.0529	0.0153	0.0143	0.0266	0.0258	0.0126	<u>0.0125</u>	0.0376	0.0279	0.0156	0.0141
	Average	0.0196	0.0178	0.0082	0.0081	0.0419	0.0383	0.0111	0.0107	0.0529	0.0479	0.0117	0.0108	0.0225	0.0188	0.0082	0.008	0.1213	0.0383	0.0915	0.0119
	96	0.7298	0.7288	0.8063	0.805	0.7317	0.7309	0.8154	0.8139	0.7271	0.7265	0.809	0.8084	0.7286	0.7276	0.8135	0.8105	<u>0.7277</u>	0.7263	0.8075	0.8061
	192	0.7508	0.7505	0.8388	0.8387	0.7583	0.7562	0.8623	0.8554	0.7548	0.7536	0.8507	0.8489	0.7555	0.7543	0.8546	0.8516	<u>0.7527</u>	0.7524	0.8475	0.8469
AustraliaRainfall	336	0.7600	0.7592	0.8502	0.8495	0.7641	0.7635	0.8644	0.8635	0.7631	0.7622	0.8633	0.8616	0.7647	0.7639	0.8678	0.8653	0.762	0.7614	0.8614	0.8593
	120	0.7512	0.7507	0.0070	0.0075	0.7566	0.7556	0.0775	0.0707	0.7527	0.7521	0.0745	0.0755	0.7549	0.7520	0.0701	0.8502	0.7528	0.7522	0.0707	0.0707
	Average	0.7515	0.7507	0.0302	0.8370	0.7300	0.7550	0.8348	0.8324	0.7557	0.7551	0.8495	0.6462	0.7348	0.7359	0.855	0.8505	0.7328	0.7322	0.8408	0.8437
	96	0.6273	0.6265	1.0863	1.0816	0.6524	0.6472	1.1694	1.1398	0.6547	0.6537	1.1861	1.1833	0.6301	<u>0.627</u> 0.6361	1.1202 1.0484	1.1126	0.6558	0.645	1.1455	1.1106
KDDCur2018	336	0.6482	0.6409	1.0208	1.0060	0.6576	0.6538	1.0924	1.0900	0.6533	0.6495	1.0649	1.0587	0.6344	0.6286	1.0404	1.0081	0.6377	0.6303	1.0101	0.9986
KDDCup2018	720	0.6185	0.6159	0.9014	0.8894	0.6342	0.6308	0.9905	0.9885	0.6350	0.6348	1.0076	1.0067	0.6188	0.6174	0.9589	0.9563	0.6359	0.6286	0.9901	0.9754
	Average	0.6302	0.6274	0.9967	0.9887	0.6474	0.6442	1.0856	1.0757	0.6485	0.6461	1.0882	1.0839	0.631	0.6273	1.0346	1.0302	0.6396	0.6330	1.0450	1.0297
	96	0.2578	0.2572	0.2388	0.2383	0.2541	0.2519	0.2203	<u>0.2</u> 182	0.2463	<u>0.2</u> 415	0.2258	0.2199	0.2482	0.2391	0.2246	0.2188	0.2449	0.2415	0.219	0.2157
	192	0.2720	0.2715	0.2659	0.2654	0.2742	0.2731	0.2565	0.2555	0.2553	0.2545	0.255	0.2529	<u>0.2673</u>	0.2656	0.2586	0.2547	0.3674	0.3308	0.3771	0.3223
PedestrianCounts	336	0.2950	0.2945	0.3072	0.3068	0.3026	0.3008	0.3046	0.3026	0.3057	0.3023	0.3122	0.3086	0.2844	0.2827	0.2973	0.2945	0.2871	0.2825	0.2886	0.2839
	/20	0.3322	0.3318	0.3815	0.3812	0.3407	0.5388	0.3844	0.5778	0.3341	0.3324	0.3859	0.383	0.3381	0.328	0.5888	0.3755	0.3271	0.3245	0.3601	0.3585
	Average	0.2892	0.2888	0.2983	0.2979	0.2929	0.2912	0.2915	<u>0.2885</u>	0.2854	0.2827	0.2947	0.2911	0.2845	0.2789	<u>0.2923</u>	0.2859	0.3066	0.2948	0.3112	0.2951
Average	Average	0.4949	0.4936	0.7973	0.7942	0.4756	0.4665	0.7382	0.7111	0.4265	0.4197	0.5696	0.5501	2.6748	0.4757	2408.1878	0.7633	<u>0.4698</u>	0.4582	0.712	0.6942
Rank	Average	3.07	3.29	3.21	3.43	3.14	3.07	2.93	2.71	2.86	3.07	2.93	2.93	<u>2.93</u>	2.64	3.00	2.93	3.00	2.93	2.93	3.00

Table 11. Full results. Mean and best (i.e., Min) values for all prediction lengths. Best and second-best are highlighted.

Dataset	Model	iPatch					Model	iPatch			
	Metric	MAE		MSE		Dataset	Metric	MAE		MSE	
	Statistic	Mean	Min	Mean	Min		Statistic	Mean	Min	Mean	Min
ETTh1	96 192 336 720	0.4074 0.4241 0.4301 0.4635	0.3995 0.4221 0.4284 0.4599	0.3877 0.415 0.4241 0.45	0.379 0.413 0.4198 0.4451	MotorImagery	96 192 336 720	0.1433 0.2633 0.3999 1.1959	0.1287 0.2079 0.3458 1.1879	0.4238 1.0616 2.183 4.8701	0.3541 0.7352 1.8659 4.8506
	Average	0.4313	0.4275	0.4192	0.4142		Average	0.5006	0.4676	2.1346	1.9515
ETTm1	96 192 336 720 Average	0.383 0.418 0.4478 0.4963 0.4363	0.3726 0.4171 0.446 0.4919 0.4319	0.3229 0.3749 0.4289 0.4937 0.4051	0.3115 0.3719 0.4259 0.4862 0.3989	TDBrain	96 192 336 720 Average	0.5985 0.6704 0.7483 0.871 0.722	0.5909 0.665 0.7423 0.8704 0.7171	0.6747 0.8383 1.0502 1.3459 0.9773	0.6592 0.824 1.036 1.3451 0.9661
ETTh2	96 192 336 720 Average	0.3445 0.3953 0.4337 0.4443 0.4045	0.3423 0.3931 0.4323 0.4419 0.4024	0.2935 0.3759 0.4226 0.4197 0.3779	0.2902 0.3711 0.4205 0.4172 0.3747	BeijingAir	96 192 336 720 Average	0.4345 0.4559 0.4665 0.4721 0.4573	0.4302 0.455 0.4658 0.4685 0.4549	0.5334 0.569 0.5962 0.5909 0.5724	0.5231 0.5643 0.5941 0.5843 0.5665
ETTm2	96 192 336 720	0.2282 0.2595 0.2865 0.3181	0.2281 0.2593 0.285 0.3148 0.2718	0.1145 0.146 0.18 0.214 0.1636	0.1134 0.1457 0.1786 0.2099	BenzeneConcentration	96 192 336 720	0.0197 0.0247 0.0188 0.0315	0.0192 0.0244 0.0166 0.0302 0.0226	0.0059 0.0112 0.0077 0.0152	0.0059 0.0111 0.0076 0.0149 0.0098
Electricity	96 192 336 720 Average	0.2315 0.2471 0.2808 0.3196 0.2698	0.2304 0.2456 0.2782 0.3159 0.2675	0.1333 0.1511 0.1798 0.2295 0.1734	0.133 0.15 0.1769 0.2268 0.1717	AustraliaRainfall	96 192 336 720 Average	0.7284 0.7533 0.7623 0.7691 0.7533	0.7274 0.7524 0.7608 0.7683 0.7522	0.8115 0.85 0.8624 0.8719 0.8489	0.8093 0.8484 0.8583 0.8702 0.8466
Weather	96 192 336 720 Average	0.204 0.2501 0.2879 0.3348 0.2692	0.2031 0.2494 0.2878 0.3337 0.2685	0.1532 0.2032 0.2516 0.3202 0.232	0.1525 0.2016 0.2511 0.3192 0.2311	KDDCup2018	96 192 336 720 Average	0.6556 0.6455 0.6397 0.6504 0.6478	0.6539 0.6454 0.6366 0.6478 0.6459	1.1853 1.0951 1.0313 1.0057 1.0793	1.1828 1.0948 1.0267 0.9874 1.0729
Exchange	96 192 336 720 Average	0.2075 0.3101 0.7651 1.0439 0.5817	0.2041 0.3014 0.7414 1.0229 0.5674	0.0877 0.1891 1.0303 1.8326 0.7849	0.0849 0.1805 0.9813 1.7492 0.749	PedestrianCounts	96 192 336 720 Average	0.2316 0.2628 0.2797 0.3196 0.2734	0.2309 0.2498 0.274 0.318 0.2682	0.2139 0.2564 0.2939 0.3726 0.2842	0.213 0.2475 0.2894 0.372 0.2805

Table 12. Full results iPatch. We present TSLib (left) and UTSD datasets (right). See Table 4 for average MSE, MAE, and Rank.