# A Statistical Case Against Empirical Human–AI Alignment

Julian Rodemann<sup>1</sup> Esteban Garcés Arias<sup>12</sup> Christoph Luther<sup>34</sup> Christoph Jansen<sup>5</sup> Thomas Augustin<sup>1</sup>

# Abstract

Empirical human–AI alignment aims to make AI systems act in line with observed human behavior. While noble in its goals, we argue that empirical alignment can inadvertently introduce statistical biases that warrant caution. This position paper thus advocates against naive empirical alignment, offering *prescriptive* alignment and *a posteriori* empirical alignment as alternatives. We substantiate our principled argument by tangible examples like humancentric decoding of language models.

# 1. Introduction

"If we use, to achieve our purposes, a mechanical agency with whose operation we cannot interfere effectively, [...] we had better be quite sure that the purpose put into the machine is the purpose which we really desire and not merely a colorful imitation of it."

– Wiener (1960), In: Science, 131(3410), page 1355.

Aligning artificial intelligence (AI) with human goals has shifted from abstract ethics to urgent policy agendas. Regulators see safety and harm prevention as prerequisites for AI's widespread deployment, not optional virtues, see e.g., Chatila & Havens (2019). Against this background, it comes as no surprise that

Preprint. Copyright by the authors. 2025.



*Figure 1.* Number of arxiv paper uploads per year with alignment-related keywords (2019-2024).

the challenges of human–AI alignment have sparked a lot of interest in the machine learning (ML) research community. In 2024 alone, more than 1500 papers with alignment-related keywords were uploaded to arxiv, see Fig. 1. Analyses of github and Hugging Face uploads show similar trends. An alignment benchmark study (Kirk et al., 2024) won a best paper award at NeurIPS.

The position paper track at last year's ICML alone saw at least four papers (Sorensen et al., 2024; Lindauer et al., 2024; Conitzer et al., 2024; Yang et al., 2024) explicitly calling for more, better, or more nuanced human–AI alignment. Lindauer et al. (2024) advocate for a more human-centered approach to automating ML pipelines. Both Sorensen et al. (2024); Conitzer et al. (2024) emphasize the need to align AI systems with diverse and potentially conflicting human interests. Yang et al. (2024) move beyond a mere human-centered perspective: They recognize the need to adapt AI to environments and self-constraints in *addition* to human intentions. For instance, agents have to be aligned with environmental dynamics in order to understand whether the next actions could violate human preferences learned in the first place. Exclusively aligning with human intentions seems too strong of a restriction even for adhering to the very same intentions in the real world.

Partly inspired by Yang et al. (2024), this interdisciplinary position paper at hand argues that empir-

<sup>&</sup>lt;sup>1</sup>Department of Statistics, LMU Munich, Germany <sup>2</sup>Munich Center for Machine Learning (MCML), Germany <sup>3</sup>Research Group Neuroinformatics, Faculty of Computer Science, University of Vienna, Vienna, Austria <sup>4</sup>Doctoral School Computer Science, Faculty of Computer Science, University of Vienna, Vienna, Austria <sup>5</sup>School of Computing & Communications, Lancaster University Leipzig, Germany. Correspondence to: Julian Rodemann <mail@julianrodemann.de>.

ical alignment's nobility of purpose can disguise statistical flaws. We are convinced that the pursuit of aligning AI with human preferences through observing the latter may inadvertently introduce biases and limitations into these systems. Unlike Yang et al. (2024), we specifically focus on *forward* (a priori) alignment of ML systems in an *empirical* way. That is, we make the case against aligning AI through *observing* human preferences *before* deployment, see definitions 2.1 through 2.3 and Section 3. Constructively, we offer three alternatives: Empirical backward (rather than forward) alignment (Section 5) as well as prescriptive (rather than empirical) alignment, both forward (Section 4) and backward (Section 6), see Table 1.

Our stance relies on a statistical perspective, as empirical alignment hinges on a myriad of (implicit and often ignored) statistical assumptions like representative samples, absence of confounders and welldefined populations. We identify several statistical biases as empirical alignment's Achilles heel, see Section 3.3. Effectively, they skew the alignment goals away from the "purpose which we really desire" to a "colorful imitation of it" (Wiener (1960), page 1355, see above).

Unlike backward empirical alignment, which aligns AI *after* deployment, forward empirical alignment directly leads to these alignment-caused biases being encoded in the AI models. This makes it hard to disentangle them from the originally trained model. Thus, we contend that AI should be – wherever possible – explained and altered *a posteriori* rather than empirically aligned *a priori*. Section 5 compares the merits of backward empirical alignment to the perils of forward empirical alignment in greater detail.

Empirical-alignment-induced biases are not only counterproductive for solving novel tasks in nonhuman-centered environments (Yang et al., 2024). More dramatically, these biases restrict an AI systems' potential for scientific discovery by confining them to human-centric perspectives. They hinder the understanding of broader and potentially more important phenomena that lie beyond human interests and perception. Such anthropocentric biases are not unique to AI alignment. In Section 3.1, we draw parallels to the rich literature on anthropocentrism, eventually relating alignment-induced biases to the *observation selection effect* in physics, see Section 3.2. We learn that AI systems will miss crucial parts of the universe *Table 1.* Fourfold distinction of forward vs. backward and empirical vs. prescriptive human–AI alignment and our positions.

	Empirical Alignment	Prescriptive Alignment		
Forward	Contra (Section 3)	Pro (Section 4)		
Backward	Pro (Section 5)	Pro (Section 6)		

if empirically aligned with those that are perceived as useful for humans or, more generally, that are perceivable by humans at all. This implies that such biases are unresolvable within an observational, i.e., purely empirical framework. In this way, we expose empirical alignment as susceptible to the positivist "myth of that which is the case" (Horkheimer & Adorno, 2002, page vii), credulously relying on observations to accurately represent alignment goals.<sup>1</sup> Indeed, following Popper (2002/1959, page 93-94),"[t]he empirical basis" does not provide "a solid bedrock," rather, "[...] science rises [...] above a swamp."

These insights motivate our call for prescriptive alignment, which aligns AI systems with transparent axioms rather than human observations. Roughly speaking, our perspective hinges on the insight that **humans are reasonably good at defining rational axioms, but rather bad at acting according to them**, see Tversky & Kahneman (1974); Birnbaum et al. (2016) and Section 4. Recent work by Kirk et al. (2024) serves as a motivating example: They find that preferences of humans exposed in conversations with large language models (LLMs) depart from preferences prestated in a survey. In Section 6, we showcase the advantages of prescriptive over empirical alignment in a case study on decoding of large language models.

In summary, this position paper cautions against biases arising from forward empirical human–AI alignment. We advocate for *prescriptive* instead of empirical alignment and contend that, where possible, AI should be *a posteriori* explained and modified rather than *a priori* aligned.

<sup>&</sup>lt;sup>1</sup>Beyond alignment, such mindless adherence to observations without questioning their origin and relation to the world has led to non-replicability in ML, see the position paper of Herrmann et al. (2024).

### 2. Human–AI Alignment

We do not argue against human–AI alignment *per se*, but rather focus on what we perceive as a popular (see Fig. 1) yet often unquestioned approach to alignment in the ML community: *forward* and *empirical* human–AI alignment. We approach this notion by first defining alignment generally.

**Definition 2.1** (Human–AI Alignment). Consider any ML model identified with parameters  $\theta \in \Theta$ . Denote by  $\omega \in \Omega$  an alignment target. Define human– AI alignment as any process involving changes of  $\theta$  that considers a function of the form  $\Theta \times \Omega \rightarrow \mathcal{A}$ ;  $(\theta, \omega) \mapsto ||f(\theta) - g(\omega)||$ , where  $f : \Theta \rightarrow \mathcal{A}$  and  $g : \Omega \rightarrow \mathcal{A}$  map to some alignment space  $\mathcal{A}$  equipped with some notion of distance  $|| \cdot ||$ . For instance, this process can be  $\min_{\theta \in \Theta} ||f(\theta) - g(\omega)||^2$ .

In line with Ji et al. (2023), we distinguish between *forward* and *backward* human–AI alignment. Forward alignment refers to harmonizing AI systems with human values already during the training phase and *before* deployment. In other words,  $\theta$  is altered informed by  $(\theta, \omega) \mapsto ||f(\theta)-g(\omega)||$  *before* the test phase. The approach is more proactive, embedding alignment into learning itself.

Backward human–AI alignment, in contrast, changes the parameters  $\theta$  of a *trained* model *during or after* deployment. It includes safety evaluations, governance frameworks, and interpretability methods, see Section 5. This approach is rather reactive, focusing on monitoring, adjusting, and managing AI behavior as new risks or misalignments emerge during deployment. In addition to the *forward-backward* distinction by Ji et al. (2023), we define *prescriptive* human–AI alignment and *empirical* alignment as follows, giving rise to our fourfold distinction in Table 1.

**Definition 2.2** (Prescriptive Human–AI Alignment). If  $\omega \in \Omega$  result from *pre-defined axioms*, the process in definition 2.1 shall be called *prescriptive* human–AI alignment.

**Definition 2.3** (Empirical Human–AI Alignment). If  $\omega \in \Omega$  are *observed human behaviors*, the process in definition 2.1 shall be called *empirical* human–AI alignment.

We emphasize the abstract nature of this fourfold dis-

tinction. In practice, the stylized separation by Ji et al. (2023) between forward and backward alignment is often less strict. Consider, e.g., continual learning (Shin et al., 2017; Kirkpatrick et al., 2017; Parisi et al., 2019; Lopez-Paz & Ranzato, 2017). Here, dynamic environments require sequential training and hence also sequential alignment.

The bulk of recent human–AI alignment research revolves around empirical alignment, see right chart in Fig. 1. Examples of **forward empirical** comprise reinforcement learning from human feedback (RLHF) (Christiano et al., 2023; Stiennon et al., 2020; Nakano et al., 2021; Ouyang et al., 2022a; Bai et al., 2022a; Glaese et al., 2022) or direct preference optimization (DPO) (Rafailov et al., 2023; Richardson et al., 2024; Tang & Xu, 2024; Afzali & Khodabandeh, 2024; Wang et al., 2024a; Gupta et al., 2024; Yin & Leong, 2024; Li et al., 2024).

In **backward empirical** alignment, post-deployment fine-tuning, interpretability methods, and safety checks allow the system to be continually refined based on new data (Sun et al., 2019; Kairouz et al., 2021).

**Forward prescriptive** alignment has its origins in rule-based AI and expert systems (Giarratano & Riley, 1998). It goes beyond mere training on human preferences and instead introduces explicit principles, guidelines, or "constitutions" that prescribe what the AI model should or should not do. Note that these pre-defined axioms can harness observational information, too. They can be functions of potential observations. For instance, rule-based rewards by Mu et al. (2024) increase sample efficiency of RLHF through rule-based alignment.

Albeit its origins laying in the last century, prescriptive approaches to AI alignment are still popular in state-of-the art models like DeepSeek-R1 (Guo et al., 2025), which was trained on rule-based rewards for reasoning. Bai et al. (2022b;a) propose codifying guidelines for harmlessness and helpfulness via "Constitutional AI", while Glaese et al. (2022) integrate targeted human feedback to produce safer dialogue agents. Normative frameworks like Delphi and Social Chemistry 101 collect large knowledge bases of social and moral rules (Jiang et al., 2021; Forbes et al., 2020). Meanwhile, Hendrycks et al. (2020) underscore the importance of embedding shared human values into model alignment protocols.

<sup>&</sup>lt;sup>2</sup>Observe this definition's similarity to model misspecification in statistics (White, 1982), serving as additional motivation for examining alignment through a statistical prism, see Section 3.3.

Lastly, **backward prescriptive** alignment involves enforcing explicit rule sets once the AI system is already deployed, for instance, via real-time policy-based governance (Ge, 2024; Bayne & Paul, 2005; Wang et al., 2021; Miao et al., 2021) or via decoding of language models, see Section 6.

# 3. Contra Forward Empirical Alignment

As this paper cautions against anthropocentric biases arising from **forward empirical** alignment, we turn to this kind of alignment in more detail. We first emphasize the philosophical underpinnings of our argument in Section 3.1, and then – motivated by the anthropic principle in physics (Section 3.2) – discuss concrete statistical biases in Section 3.3.

### 3.1. The Anthropocentric Bias

Anthropocentric thinking, which places humans at the center of the universe, has deep roots in Western thought. In the Judaeo–Christian tradition, the anthropocentric perspective originates from the creation narrative, where humans are depicted as the pinnacle of creation (Genesis 1:27). Historically, this has heavily influenced science.

However, the anthropocentric interpretation of Genesis 1:27 faced staunch opposition already from within the Jewish tradition itself. One notable critic was Moses Maimonides, a preeminent Torah scholar of the twelfth century AD (Lamm, 1965; Shapiro, 2003). In his seminal work, The Guide for the Perplexed, Maimonides emphasized the vastness and complexity of the universe, which, in his view, diminished the centrality of humans. He famously referred to humans as "just a drop in the bucket," evoking Isaiah (40:15), see Dan (1989). Notably, Maimonides' opposition to anthropocentrism was a theological one. He believed that attributing undue importance to humanity was arrogant and a misinterpretation of divine intent. For Maimonides, recognizing the humility of human existence was essential for a proper understanding of God and the natural order.

It was more than three centuries later when Nicolaus Copernicus, Galileo Galilei, and Isaac Newton established a new *helio*centric model of the universe, literally shifting the center of the universe away from humans. This paradigm shift (Kuhn, 1997) paved the way for the scientific revolution in the 16th and 17th centuries. Yet, anthropocentric biases still per-



Figure 2. Limits of the human-observable universe: The Hubble eXtreme Deep Field, showing roughly 5500 galaxies. Source: https://esahubble.org/images/heicl214a/ (acc. 01/15/25)

sist in science to this day. The argument is plain and simple: By focusing on explaining phenomena that are useful for humans, we inadvertently miss structures that are not perceived as useful according to current societal values, which are strongly limited in time and generality. In the words of Peters (2012), "Nature has much more structure than what is useful for humans." Strong positions within evolutionary epistemology even argue we cannot perceive anything that is *not* useful, since our cognitive apparatus is a product of evolution, thus overfitted to useful elements of nature (Lorenz, 1977; Wuketits, 1990).

The example of Maimonides shows that even within an overarching anthropocentric dogma, there is room for critical reflection and nuanced positions. This motivates our stance on AI alignment. We are well aware of the pressing need to align AI with human safety constraints in the wake of ever more powerful models and in anticipation of AGI, see also Section 7. However, we assert that empirical alignment is the wrong path towards that goal. Just like the Torah scholar Maimonides, who firmly believed in the dogma of his times, we do not oppose the paradigm of alignment generally. Quite the contrary, for alignment to work sustainably, we argue, it has to be freed from anthropocentric biases originating from forward empirical alignment.

#### 3.2. The Anthropic Principle in Physics

Modern-day physics is aware of such anthropocentric biases and – going even further – the more general anthropic principle, also referred to as "observation selection effect" (Bostrom, 2000; 2002; Carter, 1983). It states that all possible observations of the universe are limited by the fact that they can only be made in a universe capable of developing intelligent life, and is commonly attributed to Robert Dicke (Dicke, 1961; 1957), building on work by Paul Dirac. For example, constants of nature like the electron charge appear fine-tuned for life because, if they were not, we would not be around to observe them.

Accepting this natural restriction to human reasoning, Bostrom (2002) postulates the self-sampling assumption, which we can directly relate to empirical alignment. It states: "One should reason as if one were a random sample from the set of all observers in one's reference class" (Bostrom (2000), page 57). The self-sampling assumption reveals an unresolvable dilemma of empirical alignment. If we define the reference class broad enough to capture all environments relevant to AI deployment, empirical alignment will violate the self-sampling assumption, since the sample is biased towards humans. On the other hand, if the reference class is narrowly restricted to human-related objects, the model can hardly generalize beyond these objectives, see e.g., Yang et al. (2024).

Indeed, it was recognized by Schmidhuber (2000; 2002) that the anthropic principle provides little insight when the thought experiment is restricted to only one universe. A meaningful theory requires informative priors or alternative universes, see approaches by Schmidhuber (2000; 2002); Bostrom (2002). These are all pre-defined axioms, corresponding to a *prescriptive* approach.

Transferred to empirical human-AI alignment, this insight implies that we have to at least enrich empirical alignment by axiomatic assumptions on the alignment procedure. In Popper's image of empirical science rising "above a swamp", see Section 1, these assumptions are the "piles [...] driven down from above into the swamp" (Popper, 2002/1959, page 93-94). Blindly relying on a sample without additional assumptions on the population where it is drawn from will always lead to biased conclusions abound non-human entities. The heart of the matter is that making no population-related assumptions at all implicitly corresponds to making the strongest as**sumption of all** – the sample being fully sufficient for the alignment goal. The anthropic literature even teaches us that we have to explicitly take sample selection probabilities into account, requiring a *statistical* perspective. We thus need to consult the statistical literature on causal and selective inference as well as sampling theory. The following Section does the job.

#### 3.3. The Statistical Perspective

Indeed, the limits of empirical alignment can be best understood from a statistical perspective: Empirical alignment intends to harmonize AI with the intentions of some population of (potential) human agents, constituting  $\Omega$  in Definition 2.1. This is commonly done by means of a self-selected, thus – as we learned from the anthropic principle in physics – distorted sample thereof. This distortion can become manifest in a myriad of statistical biases, which particularly have been discussed in the social and survey statistics literature.

A sole focus on empirical evidence denies the problem of adequation (Menges, 1982; Grohmann, 2000), which is concerned with the – eo ipso insufficient – fit between what is, in principle, observable, describable, and analyzable within the framework of our formalization process, and the "world-in-itself". Groves & Lyberg (2010) concretise some major biases arising from this discrepancy by their **TSE-(Total Survey** Error) concept. They distinguish between what we call population representation biases and structural representation biases. The first one comprises, e.g., biases in the selection frame. That is, the population from which the sample is taken differs from the population of interest.<sup>3</sup> Other instances of the population representation biases are the classical sampling error arising from a random selection of the sample from the underlying population and the unitnonresponses arising when certain units refuse, or are incapable of, participating in the survey. The latter can distort conclusions because non-respondents' characteristics often differ systematically from those who participate.

The structural representation biases refer to the content-related part of the analysis and the resulting incomplete reflection of the complex relationships between the true concepts and the set of variables available for analysis. This includes **biases of opera-tionalizing** complex latent constructs and the **item**-

<sup>&</sup>lt;sup>3</sup>One can distinguish issues of over-coverage (units may be sampled that are not an element of the target population) and under-coverage (some units of the target population are not in the frame from which the sample is taken).

nonresponse bias, arising when individuals ready to participate in principle refuse to answer certain sensitive questions. Response biases refer to biased data obtained from those that *do* respond, comprising acquiescence bias (a tendency to agree) or primacy and recency effects (a preference for selecting the first or last item in a sequence), see Kaufmann et al. (2023). A further source of structural representation bias, not explicitly elaborated in the TSE framework, is the **omitted variable bias**. It refers to situations when decisive influence factors (such as hidden personal characteristics or genetic dispositions) are not accessible to the researcher, for example, for reasons of privacy preservation. This can spuriously enlarge the effect of global variables like sex or age in the merely empirical data-based analysis. Note that all the biases / errors listed here are *big data biases* in the sense that they do not vanish with increasing sample size. They are present to their full extent, also in big data sets. The only exception is the usual statistical uncertainty induced by the sample error.

Beyond the TSE, there is a bulk of statistical literature on what Benjamini (2020) calls "the silent killer of replicability": Selective inference. It occurs when hypotheses, models, or features are selected based on the observed data. Such post-selection inference biases arise in numerous scenarios, like variable selection in regression models, multiple hypothesis testing, and adaptive stopping rules in ML (Benjamini & Hochberg, 1995; Wasserman, 2009; Fithian et al., 2014; Tibshirani & Taylor, 2016; Lee et al., 2016). Empirical alignment is prone to suffer from selective inference, if the alignment targets  $\omega$  are functions of the same observations being used for finding  $\theta \in \Theta$  through empirical risk minimization, see definition 2.1, as is often the case. If data is sampled anew from a different population for alignment, such trouble can be avoided. In that case, however, the procedure becomes very data hungry. This can pose practical challenges, as human samples are typically burdensome and expensive to acquire (Shinn et al., 2024). For an illustrative example of selective inference that arises when empirically aligning language models, we refer the interested reader to experimental results in Appendix C.

**Reflexivity** constitutes an even more fundamental problem in empirical alignment. In addition to the observation selection effect – which persists in any empirical science, see Section 3.2 –, empirical *human*-AI alignment suffers from a fundamental problem

in the *social* sciences: The observant entity (human) coincides with the observing entity (also human). Unlike for atoms (natural sciences), we can expect humans (social sciences) to react to conclusions (in our case, AI alignment) being drawn from observing them, thereby compromising the validity of those conclusions. This "reflexivity problem" (Soros, 2015) dates back to early work of Morgenstern (1928) and has recently seen some revival in the ML community, recognizing the fact that today's predictions can change tomorrow's population (Perdomo et al., 2020; Hardt & Mendler-Dünner, 2023; Mendler-Dünner et al., 2020; Miller et al., 2021). In empirical alignment, consider the popular example of fine-tuning LLMs by RLHF, which implicitly relies on the "unrealistic" (Carroll et al., 2024) assumption that human preferences regarding LLM answer quality is static. To say the least, it is certainly plausible that previous LLM answers affect our judgments through, e.g., anchor effects (Lieder et al., 2018). Very recently, Carroll et al. (2024) took steps to address such feedback loops by drafting AI alignment as a dynamic Markov Decision Process (MDP), taking into account that our preferences can change by interacting with changing AI systems. Mitelut et al. (2023) go further and argue entirely against alignment to human intent, since AI systems can reshape the latter, see also Gabriel (2020).

**Causal misrepresentation** refers to misleading associations that do not reflect causal connection between variables. Such correlations occur in observational data, on which empirical alignment mostly still hinges on – with the notable exception of experimental methods in the assurance literature, see Ji et al. (2023, §4.3).

Statistical science offers sound remedies for many of the above mentioned biases. They typically involve additional assumptions about the population like "absence of unobserved confounders." Essentially, these assumptions are *prescriptive* elements, which we advocate for. Even if they are self-evident as in the case of confounders, we strongly encourage making them explicit.

This increases transparency not only for humans but also for AI, thus addressing potential unintended misalignments due to miscommunication. If AI systems fail to understand that the actual goal is populationalignment rather than sample-alignment, consequences can be dire, see Bostrom (2014, pages 122125) and Harari (2024, Chapter 8). For instance, spurious correlation between race and occupation status in alignment samples might lead to discrimination through aligned AI Systems.

While these statistical remedies address known epistemic uncertainties (Hüllermeier & Waegeman, 2021) ("known unknowns") about the population, there are potentially many more unaddressed sources of uncertainty ("unknown unknowns"), see e.g., Rodemann & Augustin (2021; 2022; 2024). This especially holds for statistical representation of *preference* data, essential to measuring human intentions, as we detail in the next Section.

# 4. Pro Forward Prescriptive Alignment

The theory of preference(s) (relations) originates in modeling rational agents within the foundations of decision theory. It finds ever broader areas of application in modern ML (e.g., Fürnkranz & Hüllermeier (2003); Jansen et al. (2023a;c); Bengs et al. (2021); Jansen et al. (2024); Rodemann et al. (2023a;b; 2025); Dietrich et al. (2024); Kim & Oh (2024)). In particular, the subfields of *preference elicitation* (e.g., Ha & Haddaway (1999); Baarslag & Gerding (2015); Mukherjee et al. (2012); Mersmann et al. (2015); Jansen et al. (2018); Zhang & Hardt (2024)) play decisive roles here. In what follows, we support our case *pro* forward prescriptive alignment by findings from these two subfields.

The term *preference elicitation* refers to the systematic retrieval of initially unknown (human) preferences, often achieved by successively (and adaptively) presenting queries to the agent under consideration. It is an excellent illustration of the superiority of a prescriptive understanding of alignment (using pre*defined axioms* as alignment targets  $\omega \in \Omega$ , see Definition 2.2) over a purely empirical understanding of alignment (Definition 2.3): It is easy to find pre*defined axioms* on the nature of preference structures modeling rational behavior that meet broad social consensus. - and it is precisely these supposedly rational axioms that are often violated in empirical studies. These violations, however, are often due to lacking oversight rather than being conscious and intended choices of the agent. At the same time, integrating rationality axioms in elicitation strategies is an instance of forward prescriptive alignment: The axioms are agreed upon *before* the model is deployed.

Probably the most prominent example of a rationality axiom in the context of preference elicitation is that of *transitivity*: If an agent prefers x over y and y over *z*, then the preference of *x* over *z* should follow. While there is strong theoretical support of transitivity via money-pump arguments (e.g., Aldred (2003)), numerous studies (e.g., Birnbaum et al. (1999; 2016); Birnbaum & Schmidt (2008); Bikhchandani & Segal (2021); Guadalupe-Lanas et al. (2020)) show that agents often behave intransitively or even cyclic, although they fully agree with transitivity as a rationality axiom. This happens in particular when the choice situation is dynamic and a large number of different options for action are available. The intransitivity of the agent's behavior in such cases is rather an expression of their limited comprehension than an ideal of action to be elevated to a principle. Consequently, the naive demand for a purely empirical alignment here would translate to an AI that only imitates the agent's lack of oversight instead of pursuing and supporting their actual interests.

A simple *prescriptive* alignment strategy that prevents the occurrence of intransitive preference patterns by construction was proposed by Jansen et al. (2022): Instead of asking the agent about all possible pairwise comparisons step by step, the *transitive hull* of the elicited preferences is formed after each query. The next pair to be presented is then selected from the remaining pairs, *excluding* those pairs that would follow anyway due to transitivity, ensuring the final result to be transitive.

Beyond elicitation procedures, another problem of purely relying on empirical alignment arises in the context of *preference aggregation*. This term refers to the problem of defining procedures that aggregate arbitrary *profiles* (fixed-size tuples) of preference relations to one collective preference, in a way that is conceived fair. For instance, preference aggregation plays a crucial role in benchmarking problems under multiple evaluations (e.g., Eugster et al. (2012); Mersmann et al. (2015); Rodemann & Blocher (2024); Zhang & Hardt (2024)), where one aims to aggregate several rankings of ML algorithms, e.g., obtained by domain experts.

Infamously, the attempt to define (full-domain) aggregation procedures for preference profiles is generally doomed to failure already under very weak axiomatic conditions. This follows from Arrow's impossibility theorem (Arrow, 1950), which was discussed in Conitzer et al. (2024) as a major challenge in aligning AI with diverse human feedback.

A common way to get around this impossibility is to retreat to the Pareto front of the aggregation problem, i.e. to base analyses on the (undominated elements of the) *partial* preference order arising as the intersection of the preference orders in the respective profile. However, this strategy, too, has serious disadvantages: Retreating to the Pareto front – given some of the preference orders in the profiles originate from some (latent) real-valued score – results in significant information loss and thus inefficiency, see. e.g., Jansen et al. (2023b); Farrow & Goldstein (2009).

Both challenges just sketched – aggregation and Pareto-analysis – essentially originate from an implicit assumption of purely empirical forward alignment. Accordingly, both challenges can potentially be avoided by a prescriptive approach: In the context of aggregation, this would imply that the aggregate does not have to correspond directly to a function of the preference orders of the individual agents. Instead, external factors could also be taken into account in the aggregation, allowing the rigid framework of the impossibility theorem to be left behind. In the light of the second problem, the inefficiency of the Pareto front can also be remedied: As demonstrated in e.g., Kreuter (2013); Jansen et al. (2022), in the process of eliciting preferences, paradata about preference intensity (i.e., latent cardinal information) can be implicitly collected, allowing the full available information to be included. Under a prescriptive alignment paradigm, this data – not directly related to targeted human behavior – could be used to obtain significantly more information-efficient improvements on the Pareto front.

# 5. Pro Backward Empirical Alignment

Another argument versus forward empirical alignment stems from the pursuit of transparency. While most ML models are powerful predictors their decision making process typically is not human intelligible – with the exception of intrinsically interpretable models. Transparency, however, is desired to understand model decisions especially in high-stakes environments – let alone legal requirements like the EU AI Act.

We argue that forward empirical alignment adds to the opacity of models. In RLHF, for example, the reward function is typically approximated by a deep neural network trained on observed human behavior (Christiano et al., 2023), and hence the (often nontransparent) policy is optimized using feedback from a nontransparent reward model. More importantly, though, any forward empirical alignment encodes biases into the model that cannot be disentangled from dependencies in the training data as discussed in Section 3.3, which further impedes model understanding. Thus, we argue for more transparent alignment. Prescriptive alignment techniques check this box by explicitly stating the axioms a model shall be aligned to. If the latter is impractical, however, we offer changes of an ML model's parameters  $\theta \in \Theta$  informed by interpretable ML (IML) as potential strategy. In line with Ji et al. (2023), we call this *backward* alignment. Modifications to the model architecture, by contrast, are another valid option but per definition not part of the alignment process of the original model.

There is a vast literature on IML methods for classical ML (e.g., Molnar (2022); Ribeiro et al. (2016); Lundberg & Lee (2017); Greenwell et al. (2018); Covert et al. (2020)) as well as those dedicated to explain decision making in RL (e.g., Puiutta & Veith (2020); Milani et al. (2022); Madumal et al. (2019); Topin & Veloso (2019); Olson et al. (2021); Huang et al. (2018)).

Such methods typically provide explanations of ML models during or after deployment that are subsequently inspected by human observers. Upon inspection, model explanations can *a posteriori assure* that the model works as intended. On the contrary, the observer can infer that the model behaves against their intentions and imply changes on the parameters  $\theta \in \Theta$  without ever explicitly stating their preferences and while never providing universally applicable axioms. Thus, we merely observe human preferences implicitly and call the latter scenario empirical backward alignment. Note that – while inherently prescriptive – the choice of the (I)ML method is not yet part of the alignment process. As we argue for transparent alignment, we contend that such a posteriori informed backward alignment achieves this due to the more explicit nature of the performed changes unlike forward empirical alignment. Moreover, the strategy comprises a rather static choice situation which can mitigate the issue of irrational behavior in empirical alignment raised in Section 4.

*Table 2.* Empirical vs. prescriptive alignment of language models: Decoding strategies Contrastive Search (CS) and DoubleExp are compared across three datasets using two alignment metrics: QText (*prescriptive*) and MAUVE (*empirical*) for **Automatic Evaluation**. **Human Evaluation** results indicate the percentage of evaluators favoring each strategy based on perceived semantic coherence and fluency. Human selections align with QText (*prescriptive*), see Garcés et al. (2024b). All results are reported as percentages.

	Automatic Evaluation				Human Evaluation				
	QText ( <i>prescriptive</i> ) ↑		MAUVE ( <i>empirical</i> ) $\uparrow$		Semantic coherence ↑		Fluency ↑		
Dataset	CS DoubleExp		CS	DoubleExp	CS DoubleExp		CS	DoubleExp	
Wikinews	91.95	82.79	84.14	90.65	73.00	27.00	61.00	39.00	
Wikitext	87.64	81.50	77.97	84.07	57.00	43.00	60.50	39.50	
BookCorpus	88.71	82.12	84.74	85.66	64.50	35.50	61.00	39.00	
All	89.68	82.22	82.82	87.16	66.00	34.00	59.00	41.00	

### 6. Pro Backward Prescriptive Alignment

An illustrative example of backward alignment in language models emerges in the choice of decoding strategies for autoregressive text generation. These strategies specify how each subsequent token is selected from the model's probability distribution over tokens at every inference step, thereby exerting a critical influence on the quality of the generated text.

Various automatic metrics have been introduced to evaluate text generated by different decoding strategies. Among them are several prescriptive ones like coherence, diversity or QText (harmonic mean of these latter), and *empirical* ones such as MAUVE (Pillutla et al., 2021). For a detailed overview and technical description, we refer to Appendix A.1 and A.2. While coherence assesses how likely the generated text is given the prompt, diversity measures lexical repetition rates (Su & Xu, 2022). In contrast, MAUVE measures how closely machine-generated text aligns with empirical samples of human-written text by comparing their distributional "fingerprints" in a latent representation space. Technically, it calculates the Kullback-Leibler divergence between the two distributions. Higher MAUVE scores correspond to lower divergence, indicating greater similarity to humanproduced text.

Choosing a decoding strategy to align the model output with human-generated text is an obvious example of *backward* alignment: Decoding strategies are chosen *after* the language model has been trained, allowing for fine-tuning towards human preferences. Relying exclusively on MAUVE to select or evaluate decoding strategies constitutes *backward empirical* 

*alignment*: the quality of a strategy is evaluated based on how well its text generations align with observed human-written text samples. This methodology has notable limitations, as our illustrative case study reveals: Based on experimental results in Garcés et al. (2024b; 2025), we compare the quality (assessed by human evaluators) of text generated by the same model (GPT2-XL (Radford et al., 2019)) using two different decoding strategies, namely CS (contrastive search, Su & Xu (2022); Su & Collier (2023)) and DoubleExp (Garcés et al., 2024b). In one scenario, the decoding strategy is empirically aligned via MAUVE. In the other scenario, we use QText, a prescriptive metric, to choose the decoding method.

Table 2 highlights discrepancies between high MAUVE scores and human judgments of final text quality. In other words, if we choose a decoding strategy *empirically* through MAUVE, the output is judged to be of lower quality than the one generated by a *prescriptively* chosen decoding strategy. While DoubleExp consistently achieves higher MAUVE scores than CS, it is rejected by human evaluators, which prefer CS for its perceived semantic coherence and fluency.

In a nutshell, these findings suggest that humans favor text from a model that was not aligned to empirically observed human-generated text but to a prescriptive metric. For further results, we refer to Tables 3 and 4 in Appendix B. Conclusively, we emphasize that these findings are not limited to specific decoding methods like CS, see comprehensive studies in Su & Xu (2022); Garcés et al. (2024b;a; 2025); Ding et al. (2025).

### 7. Alternative Views

In this Section, we present two alternative views – *pro* forward empirical alignment and *contra* alignment altogether.

#### 7.1. Pro Forward Empirical Alignment

While statistical caution is appropriate, there might be other – potentially superior – reasons to do align AI with human preferences in a forward empirical way. Often, ML's main and only goal is good prediction. Strong cases for empirical alignment are especially concerned with such "performance" goals (see Ibarz et al. (2018)). A prime example is *Instruct*-GPT (Ouyang et al., 2022b), an LLM trained with a "technique [that] can align to a specific human reference group for a specific application" (p. 18). The authors name improved performance and costeffectiveness over larger models as key benefits of their approach. Stiennon et al. (2020) report similar benefits of smaller, empirically forward aligned models for the clearly defined task of text summarization. Potentially reduced model size while maintaining predictive performance is further desirable for the widespread deployment of ML models on less powerful hardware. We refer to Appendix D for a similar argument in defense of forward empirical alignment from a benchmarking perspective.

### 7.2. A Case Against Alignment Altogether

With the very same principled arguments from Section 3, one might as well arrive at the reasonable position of giving up alignment entirely. Our offered alternatives (backward and/or prescriptive alignment) increase transparency and decrease negative effects of statistical biases. Yet, they cannot resolve the fundamental dilemma of the observation selection effect: As detailed in Section 3.1, any alignment to humans will necessarily bias the AI away from other entities in nature. Fundamentally opposing alignment might thus be particularly justified if the AI's goal is scientific inference, e.g., by means of IML. While we considered explicit changes to a model informed by IML as *backward alignment*, the use of IML can end at the stage of model explanation as a tool for scientific inference (Freiesleben et al., 2024; Ewald et al., 2024; Molnar et al., 2023; König et al., 2024) – typically about the data generating distribution. From a statistician's perspective, we deem such inference as valuable in itself and further argue that principled

explanations aid in understanding model decisions. Covert et al. (2020) introduce SAGE values for so called *global feature importance* that – under certain conditions – represent mutual information between inputs and output or conditional output variance, König et al. (2024) extend similar insights to feature dependencies and Freiesleben et al. (2024) define a general framework to design and use IML methods for scientific inference grounded in statistical learning theory.

We contend that a bias from any form of alignment encoded in the ML model can confound the relations between the model variables and as a result diminish the potential for scientific discovery. This argument is further underlined by findings from RL. Silver et al. (2017) show that the famous AlphaGo model trained from observations of human play is inferior to AlphaGo Zero trained without human knowledge. Moreover, Schut et al. (2023) use concept-based explanations to extract sequences of actions in chess from an AI trained without human oversight that go beyond human skill level. It can be argued that not only forward empirical, but any kind of alignment – in the language of Schut et al. (2023) – biases the machine representational space towards the human representational space. It introduces or exacerbates an anthropocentric bias that can substantially reduce AI's ability to learn concepts beyond human knowledge.

# 8. Conclusion

AI alignment is a double-edged sword. Done well, it makes AI safer. Done poorly, it biases models and limits their potential for discovery. This paper developed a nuanced statistical perspective on this tradeoff. It cautioned against forward empirical alignment unless strictly necessary.

We emphasized the statistical caveats of common empirical alignment practices (Section 3) and scrutinized (in)consistencies of observed human preferences (Section 4). We showed that *forward* empirical alignment is especially prone to "locking in" statistical biases during training. What is more, we constructively discussed alternatives like *prescriptive* (Section 4 and 6) and *backward* (Section 5 and 6) alignment. We further provided practical guidance by concrete examples like decoding of language models (Section 6). Along the way, we discovered a fourfold distinction – forward vs. backward, empirical vs. prescriptive (Table 1) – of alignment methods that might be of independent interest. Our hope is that this taxonomy and the accompanying arguments guide the ML community towards (more) statistically informed alignment. We wish to stimulate a constructive debate on the trade-offs between these different approaches to alignment, see also the contrasting opinions in Section 7.

# 9. Impact Statement

This paper warns against the uncritical and naive use of forward empirical alignment, arguing that such alignment introduces statistical biases and anthropocentric constraints. We propose alternatives: prescriptive alignment and backward adjustments. These latter ensure transparency and prevent AI from merely imitating (potentially irrational and inconsistent) human behavior at the cost of better reasoning. This misalignment can lead to significant societal risks, as touched upon in Section 3.3.

Future AI policy should thus consider the biases discussed in this position paper. Regulation should not blindly enforce empirical alignment, but instead, demand transparency in how models are aligned. This means documenting alignment assumptions, ensuring explainability, and regularly auditing statistical biases in training data.

The ethical stakes are high. If AI is aligned to flawed human preferences, it may amplify societal biases rather than correct them.

At worst, it could reinforce harmful power structures, see the example of racial biases in Section 3.3. Conversely, dismissing empirical alignment entirely might create models that fail to serve human needs. We advocate a middle ground: rigorous, principlebased alignment that minimizes bias while allowing AI to generalize beyond human-imposed limits.

Particularly, by pushing for a middle ground, we object to the misinterpretation of this paper's arguments as a call against alignment altogether. We discussed this as an alternative view in Section 7. Abandoning alignment entirely poses the severe and existential risk of loosing human control over AI systems, potentially giving rise to several "doom" scenarios, see also Section 3.1.

To invoke Norbert Wiener, whose famous quote on the alignment problem (see Section 1) motivated this whole paper, once again:

"Moreover, if we move in the direction of making machines which learn and whose behavior is modified by experience, we must face the fact that every degree of independence we give the machine is a degree of possible defiance of our wishes."

– Norbert Wiener, 1949, Markoff (2013, acc. 01/15/25)

As AI grows more autonomous, "who aligns whom?" will become a central ethical question. Our position is clear: Alignment should be governed by principles, not just by unreflected mirroring of observations.

### A. Metrics for Evaluating Decoding of Language Models

In what follows, we discuss the prescriptive and empirical metrics used for language model alignment via decoding strategy selection in Section 6.

#### **A.1. Prescriptive Metrics**

**Coherence.** Proposed by Su & Xu (2022), the coherence metric is defined as the averaged log-likelihood of the generated text conditioned on the prefix text as

$$\text{Coherence}(\hat{\boldsymbol{x}}, \boldsymbol{x}) = \frac{1}{|\hat{\boldsymbol{x}}|} \sum_{i=1}^{|\hat{\boldsymbol{x}}|} \log p_{\mathcal{M}} \left( \hat{\boldsymbol{x}}_i \mid [\boldsymbol{x} : \hat{\boldsymbol{x}}_{< i}] \right)$$

where x and  $\hat{x}$  are the prefix text and the generated text, respectively; [:] is the concatenation operation and  $\mathcal{M}$  is an external language model, namely OPT (2.7B) (Zhang et al., 2022).

Diversity. Proposed by Su & Xu (2022), the diversity metric aggregates n-gram repetition rates:

$$\text{DIV} = \prod_{n=2}^{4} \frac{|\text{ unique n-grams } (\mathbf{x}_{\text{cont}}) |}{|\text{ total n-grams } (\mathbf{x}_{\text{cont}}) |}$$

A low diversity score suggests the model suffers from repetition, and a high diversity score means the modelgenerated text is lexically diverse.

QText. QText (Garcés et al., 2025) is given by the harmonic mean of rescaled coherence and diversity:

$$QText = \frac{2}{\frac{1}{COH} + \frac{1}{DIV}} * 100,$$

where

$$COH = \frac{Coherence - min(Coherence) + 1}{max(Coherence) - min(Coherence) + 1}.$$

QText values close to 100 indicate high-quality text generation, while values approaching zero reflect low-quality outcomes.

#### **A.2. Empirical Metrics**

**MAUVE.** MAUVE (Pillutla et al., 2021) is a metric designed to quantify how closely a model distribution Q matches a target distribution P of human texts. Two main types of error contribute to any discrepancy between Q and P:

- **Type I Error:** *Q* assigns high probability to text that is unlikely under *P*.
- **Type II Error:** *Q* fails to generate text that is plausible under *P*.

These errors can be formalized using the Kullback–Leibler (KL) divergences  $KL(Q \parallel P)$  and  $KL(P \parallel Q)$ . If *P* and *Q* do not share the same support, at least one of these KL divergences will be infinite. To address this issue, Pillutla et al. (2021) propose measuring errors through a mixture distribution

$$R_{\lambda} = \lambda P + (1 - \lambda) Q \quad \text{with } \lambda \in (0, 1).$$

*Table 3.* Automatic evaluation results: Comparison of Contrastive Search (CS) and DoubleExp across Wikinews, Wikitext, and BookCorpus using two automatic metrics: QText and MAUVE. DoubleExp outperforms CS in terms of MAUVE, while CS outperforms DoubleExp in terms of QText across all three datasets.

-					
Datasat	QText	(prescriptive) ↑	MAUVE ( <i>empirical</i> ) ↑		
Dataset	CS	DoubleExp	CS	DoubleExp	
Wikinews	91.95	82.79	84.14	90.65	
Wikitext	87.64	81.50	77.97	84.07	
BookCorpus	88.71	82.12	84.74	85.66	
All	89.68	82.22	82.82	87.16	

*Table 4.* Human evaluation results: Human ratings of Contrastive Search (CS) and DoubleExp across Wikinews, Wikitext, and BookCorpus, focusing on perceived semantic coherence and fluency of the generated text. DoubleExp is consistently rejected by human evaluators.

Datasat		Semantic coherence		Fluency			
Dataset	CS is better	CS and DoubleExp are similar	DoubleExp is better	CS is better	CS and DoubleExp are similar	DoubleExp is better	
Wikinews	56%	34%	10%	32%	58%	10%	
Wikitext	34%	46%	20%	29%	63%	8%	
BookCorpus	49%	31%	20%	32%	58%	10%	
All	48%	36%	16%	28%	62%	10%	

This leads to redefined Type I and Type II errors given by

$$\operatorname{KL}(Q \| R_{\lambda})$$
 and  $\operatorname{KL}(P \| R_{\lambda})$ ,

respectively.

By varying  $\lambda$  and computing these two errors, one obtains a *divergence curve* 

$$\mathcal{C}(P,Q) = \left\{ \left( \exp\left(-c \operatorname{KL}(Q \| R_{\lambda})\right), \, \exp\left(-c \operatorname{KL}(P \| R_{\lambda})\right) \right) \, : \, R_{\lambda} = \lambda P + (1-\lambda)Q, \, \lambda \in (0,1) \right\},$$

where c > 0 is a hyperparameter that controls the scaling.

Finally, MAUVE(P, Q) is defined as the area under the divergence curve C(P, Q). Its value lies between 0 and 100, with higher values indicating that Q is more similar to P.

# B. Further Results on Decoding Alignment of Language Models

We provide additional details on the experimental results presented in Section 6, see also Garcés et al. (2024b; 2025). Tables 3 and 4 provide a more granular breakdown of the empirical versus prescriptive alignment methods evaluated in Table 2 in the main paper. Table 3 presents quantitative comparisons across various datasets and evaluation metrics, highlighting the alignment discrepancies when relying on empirical metrics like MAUVE versus prescriptive metrics such as QText. Table 4 provides a more detailed breakdown of the human evaluation results reported in Table 2 in the main paper. The latter summarized the human preferences by reporting the share of text generations that was preferred, while Table 4 additionally shows indifference votes. The results reinforce the finding that empirical alignment methods may not necessarily correspond to human-perceived text quality. This further substantiates our argument for a more principle-driven approach to AI alignment. To reflect the share of human raters favoring each decoding strategy, as depicted in Table 2 in the main paper, we apply the following scoring approach:

$$Score_{CS} = \frac{\#(CS \text{ is better }) + 0.5 \times \#(\text{ tie })}{\#(CS \text{ is better }) + \#(\text{ tie }) + \#(\text{ DoubleExp is better })}$$

Score  $_{\text{DoubleExp}} = 100 - \text{Score}_{\text{CS}}$ .

Dataset	Truncation	# Examples		MAUVE(%)↑			Preferred
	length	CS	ACS	CS	ACS	Δ	Method
Wikinews	64	1939	2000	87.42	85.79	-1.63	CS
	96	1920	2000	81.11	88.13	7.02	ACS
	128	1859	1977	84.14	85.39	1.25	ACS
	160	1684	1824	84.86	85.78	0.92	ACS
	192	1447	1617	85.23	87.10	1.87	ACS
Wikitext	64	1296	1314	82.78	86.83	4.05	ACS
	96	1280	1314	81.46	85.67	4.21	ACS
	128	1250	1301	77.97	79.82	1.85	ACS
	160	845	889	69.66	80.53	10.87	ACS
	192	529	564	81.50	75.45	-6.05	CS
BookCorpus	64	1907	1947	84.22	87.04	2.82	ACS
	96	1873	1947	87.82	83.66	-4.16	CS
	128	1657	1749	84.74	85.49	0.75	ACS
	160	863	922	83.59	83.68	0.09	ACS
	192	476	518	79.43	83.38	3.95	ACS

C. Selective Inference in Decoding Alignment of Language Models

*Table 5.* Illustration of selective inference in aligning decoding strategies for language models. MAUVE scores are computed on both machine- and human-written text. In order to compute the KL-divergence, see Appendix A.2, MAUVE typically considers samples based on the minimal token lengths observed in human-reference texts (already seen during model training). Texts exceeding this length are truncated, while texts that do not achieve this length are excluded from the sample. Results are reported across three different datasets. This can be seen in the varying numbers of examples (column 3). Positive  $\Delta$ -values indicate that the decoding method ACS (Garcés et al., 2024b) outperforms the baseline CS (Su & Collier, 2023). All computations were performed using the gpt2-xl model (Radford et al., 2019). For CS (Su & Collier, 2023), hyperparameters k = 5 and  $\alpha = 0.6$  were selected.

In this section, we discuss a tangible and concrete example of selective inference (Section 3.3) arising in empirical alignment of decoding methods in language models.

When empirically aligning decoding methods via MAUVE, see also section 6, only machine-generated samples that match the distributional length constraints of human-written texts are considered. Any generated text that exceeds these bounds is often truncated or outright discarded (Pillutla et al., 2021; Garcés et al., 2024b). This leads to a biased evaluation where only text that "fits" pre-existing norms is measured, disregarding potentially superior but unconventional outputs. More precisely, MAUVE is typically computed over samples based on the minimal token lengths observed in human-reference texts (already seen during model training), in order to compute the Kullback-Leibler-divergence between their respective distributions, see Appendix A.2. Texts exceeding this length are truncated, while texts that do not achieve this length are excluded from the sample.

Through a statistical lens, any inference from a so-aligned model is doomed to suffer from post-selection bias – as discussed in Section 3.3. Only considering samples of a certain length corresponds to reducing the domain of the sample, i.e, setting some parameters  $\theta$  to zero, thus shrinking the model's *effective* parameter space  $\Theta$ . All subsequent probabilistic inference guarantees are then hampered, because they fail to condition on the events (that is, sample realizations) that led to the changes of  $\Theta$ . Correction methods (e.g., Berk et al. (2013); Benjamini & Hochberg (1995); Wasserman (2009); Fithian et al. (2014); Tibshirani & Taylor (2016); Lee et al. (2016)) can render post-selection inference valid again. These prescriptive elements, however, are not considered in many empirical alignment use cases like decoding alignment through MAUVE (Pillutla et al., 2021).

This highlights a general pattern: Forward empirical alignment, if driven by selective inference, may optimize for artifacts of the training data rather than the intended alignment objective. A naïve adherence to empirical alignment thus risks codifying and amplifying these biases in AI behavior rather than mitigating them. By

recognizing selective inference as a fundamental issue in empirical AI alignment, we advocate for more prescriptive and transparent approaches that explicitly account for sample selection biases and ensure alignment is guided by rationally defined objectives rather than self-reinforcing observational artifacts.

# D. Additional Alternative View: Empirical Alignment as a Necessary Benchmarking Tool

We have argued against forward empirical alignment as a primary strategy. An alternative perspective holds that empirical methods are not just unavoidable but necessary *for benchmarking and validation*. According to this view, even if prescriptive alignment is theoretically preferable, it ultimately requires empirical validation to ensure it functions as intended in real-world settings. Without empirical feedback, alignment objectives risk becoming too abstract or detached from practical deployment concerns (Gao et al., 2022; Ding & Zou, 2021).

However, this argument presumes that empirical validation provides a neutral or reliable ground truth for alignment, rather than a reflection of existing biases. In practice, empirical benchmarks often reinforce anthropocentric limitations, locking models into human-like behaviors that may not generalize to more robust or scalable alignment strategies, see section 3.3 and also Gabriel (2020); Perdomo et al. (2020); Wang et al. (2024b). Instead of treating empirical evaluation as a fundamental necessity, an alternative approach would prioritize validation through formal guarantees, logical consistency, and predictive stability, reducing dependence on imperfect human-labeled data. This perspective suggests to walk a tightrope, balancing empirical and prescriptive benchmarking: Rather than outright rejecting empirical methods, alignment research should redefine their role. One can treat them as a secondary check on prescriptive models rather than as the primary mechanism for defining alignment itself.

In this framing, the burden of proof is reversed: Instead of requiring prescriptive methods to justify themselves empirically, empirical methods should justify their necessity in cases where prescriptive approaches provide clear, rule-based guarantees. This would allow empirical tools to serve as a complement rather than a crutch, making sure alignment strategies are both rigorous and adaptable.

### References

- Afzali, A. and Khodabandeh, B. Aligning visual contrastive learning models via preference optimization. *arXiv* preprint arXiv:2411.08923, 2024. URL https://arxiv.org/pdf/2411.08923.
- Aldred, J. The money pump revisited. *Risk, Decision and Policy*, 8(1):59–76, 2003.
- Arrow, K. A difficulty in the concept of social welfare. Journal of Political Economy, 58:328–346, 1950.
- Baarslag, T. and Gerding, E. H. Optimal incremental preference elicitation during negotiation. In Proceedings of the 24th International Conference on Artificial Intelligence, IJCAI'15, pp. 3–9. AAAI Press, 2015.
- Bai, Y., Jones, A., Ndousse, K., Askell, A., Chen, A., Muratore, P., Perry, J., Lin, Q., Sorensen, A., Knight, M., Conerly, T., et al. Training a helpful and harmless assistant with reinforcement learning from human feedback. *arXiv preprint arXiv:*2204.05862, 2022a. URL https://arxiv.org/abs/2204.05862.
- Bai, Y., Kadavath, S., Kundu, S., Askell, A., Kernion, J., Jones, A., Chen, A., Goldie, A., Mirhoseini, A., McKinnon, C., et al. Constitutional ai: Harmlessness from ai feedback. arXiv preprint arXiv:2212.08073, 2022b.
- Bayne, J. and Paul, R. Policy-based command and control. In 10th International Command and Control Research Technology Symposium, 2005. URL http://dodccrp.org/events/10th\_ICCRTS/CD/papers/360.pdf.
- Bengs, V., Busa-Fekete, R., Mesaoudi-Paul, A. E., and Hüllermeier, E. Preference-based online learning with dueling bandits: A survey. *Journal of Machine Learning Research*, 22(7):1–108, 2021. URL http://jmlr.org/papers/v22/18-546.html.
- Benjamini, Y. Selective Inference: The Silent Killer of Replicability. *Harvard Data Science Review*, 2(4), dec 16 2020. https://hdsr.mitpress.mit.edu/pub/l39rpgyc.
- Benjamini, Y. and Hochberg, Y. Controlling the false discovery rate: a practical and powerful approach to multiple testing. *Journal of the Royal Statistical Society: Series B (Methodological)*, 57(1):289–300, 1995.
- Berk, R., Brown, L., Buja, A., Zhang, K., and Zhao, L. Valid post-selection inference. *The Annals of Statistics*, pp. 802–837, 2013.
- Bikhchandani, S. and Segal, U. Intransitivity in the small and in the large. *Journal of Risk and Uncertainty*, 63(3): 257–273, 2021.
- Birnbaum, M. H. and Schmidt, U. An experimental investigation of violations of transitivity in choice under uncertainty. *Journal of Risk and Uncertainty*, 37:77–91, 2008.
- Birnbaum, M. H., Patton, J. N., and Lott, M. K. Evidence against rank-dependent utility theories: Tests of cumulative independence, interval independence, stochastic dominance, and transitivity. *Organizational Behavior and human decision Processes*, 77(1):44–83, 1999.
- Birnbaum, M. H., Navarro-Martinez, D., Ungemach, C., Stewart, N., and Quispe-Torreblanca, E. G. Risky decision making: Testing for violations of transitivity predicted by an editing mechanism. *Judgment and Decision Making*, 11(1):75–91, 2016.
- Bostrom, N. *Observational Selection Effects in Science and Philosophy*. PhD thesis, London School of Economics, 2000.
- Bostrom, N. Anthropic Bias: Observation Selection Effects in Science and Philosophy. Routledge, New York, USA, 2002.
- Bostrom, N. Superintelligence: Paths, strategies, dangers. Oxford University Press, Oxford, UK, 2014.
- Carroll, M., Foote, D., Siththaranjan, A., Russell, S., and Dragan, A. Ai alignment with changing and influenceable reward functions. *arXiv preprint arXiv:*2405.17713, 2024.

- Carter, B. The anthropic principle and its implications for biological evolution. *Philosophical Transactions of the Royal Society of London. Series A, Mathematical and Physical Sciences*, 310(1512):347–363, 1983.
- Chatila, R. and Havens, J. C. The IEEE global initiative on ethics of autonomous and intelligent systems. *Robotics and well-being*, pp. 11–16, 2019.
- Christiano, P., Leike, J., Brown, T. B., Martic, M., Legg, S., and Amodei, D. Deep reinforcement learning from human preferences, 2023. URL https://arxiv.org/abs/1706.03741.
- Conitzer, V., Freedman, R., Heitzig, J., Holliday, W. H., Jacobs, B. M., Lambert, N., Mossé, M., Pacuit, E., Russell, S., Schoelkopf, H., et al. Position: Social choice should guide ai alignment in dealing with diverse human feedback. In *Forty-first International Conference on Machine Learning*, 2024.
- Covert, I., Lundberg, S. M., and Lee, S.-I. Understanding global feature contributions with additive importance measures. In Larochelle, H., Ranzato, M., Hadsell, R., Balcan, M., and Lin, H. (eds.), Advances in Neural Information Processing Systems, volume 33, pp. 17212–17223. Curran Associates, Inc., 2020.
- Dan, Y. Studies in Jewish thought. Praeger, 1989.
- Dicke, R. H. Gravitation without a principle of equivalence. *Reviews of Modern Physics*, 29(3):363, 1957.
- Dicke, R. H. Dirac's cosmology and mach's principle. *Nature*, 192(4801):440–441, 1961.
- Dietrich, S., Rodemann, J., and Jansen, C. Semi-supervised learning guided by the generalized bayes rule under soft revision. In *International Conference on Soft Methods in Probability and Statistics*, pp. 110–117. Springer, 2024.
- Ding, X. and Zou, J. On the biases of standard machine learning evaluation metrics. In *NeurIPS 2021*, 2021.
- Ding, Y., Arias, E. G., Li, M., Rodemann, J., Aßenmacher, M., Chen, D., Fan, G., Heumann, C., and Zhang, C. Guard: Glocal uncertainty-aware robust decoding for efficient hyperparameter-free text generation. *arXiv*, 2025.
- Eugster, M., Hothorn, T., and Leisch, F. Domain-based benchmark experiments: Exploratory and inferential analysis. *Austrian Journal of Statistics*, 41(1):5–26, 2012.
- Ewald, F. K., Bothmann, L., Wright, M. N., Bischl, B., Casalicchio, G., and König, G. A guide to feature importance methods for scientific inference. In Longo, L., Lapuschkin, S., and Seifert, C. (eds.), *Explainable Artificial Intelligence*, pp. 440–464, Cham, 2024. Springer Nature Switzerland.
- Farrow, M. and Goldstein, M. Almost-pareto decision sets in imprecise utility hierarchies. *Journal of Statistical Theory and Practice*, 3:137–155, 2009.
- Fithian, W., Sun, D., and Taylor, J. Optimal inference after model selection. arXiv preprint arXiv:1410.2597, 2014.
- Forbes, M., Sap, M., Seering, J., Kim, S., Choi, Y., et al. Social chemistry 101: Learning to reason about social and moral norms. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 653–670, 2020. URL https://arxiv.org/abs/2010.00672.
- Freiesleben, T., König, G., Molnar, C., and Tejero-Cantero, A. Scientific inference with interpretable machine learning: Analyzing models to learn about real-world phenomena. *Minds and Machines*, 34(3), July 2024. URL http://dx.doi.org/10.1007/s11023-024-09691-z.
- Fürnkranz, J. and Hüllermeier, E. Pairwise preference learning and ranking. In Lavrač, N., Gamberger, D., Blockeel, H., and Todorovski, L. (eds.), *Machine Learning: ECML 2003*, pp. 145–156. Springer, 2003.
- Gabriel, I. Artificial intelligence, values, and alignment. Minds and machines, 30(3):411-437, 2020.

- Gao, J. P., Durmus, E., Cho, K., and Mielke, S. J. Aligning language models to follow instructions. *arXiv preprint arXiv:*2210.01264, 2022.
- Garcés, E. A., Blocher, H., Rodemann, J., Li, M., Heumann, C., and Aßenmacher, M. Towards better open-ended text generation: A multicriteria evaluation framework. *arXiv preprint arXiv*:2410.18653, 2024a.
- Garcés, E. A., Rodemann, J., Li, M., Heumann, C., and Aßenmacher, M. Adaptive contrastive search: Uncertaintyguided decoding for open-ended text generation. In Al-Onaizan, Y., Bansal, M., and Chen, Y.-N. (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 15060–15080, Miami, Florida, USA, November 2024b. Association for Computational Linguistics. URL https://aclanthology.org/2024. findings-emnlp.885/.
- Garcés, E. A., Li, M., Heumann, C., and Assenmacher, M. Decoding decoded: Understanding hyperparameter effects in open-ended text generation. In Rambow, O., Wanner, L., Apidianaki, M., Al-Khalifa, H., Eugenio, B. D., and Schockaert, S. (eds.), *Proceedings of the 31st International Conference on Computational Linguistics*, pp. 9992–10020, Abu Dhabi, UAE, January 2025. Association for Computational Linguistics. URL https://aclanthology.org/2025.coling-main.668/.
- Ge, Y. The symbiosis of trust and ai: Scientific foundations for strategic network security, autonomous resilience, and prescriptive governance, 2024. URL https://search.proquest.com/openview/7ff78946fb5901d4f6064a861fd598ff/1.
- Giarratano, J. C. and Riley, G. Expert systems. PWS Publishing Co., 1998.
- Glaese, A., McAleese, N., Laroche, J., Irving, G., Humphreys, O., Leike, J., Rauh, M., Bohg, J., Hooker, S., Christiano, P. F., Amodei, D., Legassick, A., Downey, C., Simonyan, K., Suleyman, M., and Hassabis, D. Improving alignment of dialogue agents via targeted human judgements. *arXiv preprint arXiv:2209.14375*, 2022. URL https://arxiv.org/abs/2209.14375.
- Greenwell, B. M., Boehmke, B. C., and McCarthy, A. J. A simple and effective model-based variable importance measure, 2018. URL https://arxiv.org/abs/1805.04755.
- Grohmann, H. Statistik als Instrument der empirischen Wirtschafts- und Sozialforschung: Eine methodologische Betrachtung aus der Sicht der Frankfurter Schule der sozialwissenschaftlichen Statistik [Statistics as an instrument of empirical research in economy and society: A methodological reflection in the view of the Frankfurt School of Statistics]. *Jahrbücher für Nationalökonomie und Statistik*, 220:669–688, 2000.
- Groves, R. M. and Lyberg, L. Total survey error past, presence and future. *Public Opinion Quarterly*, 7:849–879, 2010.
- Guadalupe-Lanas, J., Cruz-Cárdenas, J., Artola-Jarrín, V., and Palacio-Fierro, A. Empirical evidence for intransitivity in consumer preferences. *Heliyon*, 6:1–8, 2020.
- Guo, D., Yang, D., Zhang, H., Song, J., Zhang, R., Xu, R., Zhu, Q., Ma, S., Wang, P., Bi, X., et al. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*, 2025.
- Gupta, T., Shandilya, S., and Ghosh, S. Unveiling context-aware criteria in self-assessing llms. *arXiv preprint arXiv:*2410.21545, 2024. URL https://arxiv.org/pdf/2410.21545.
- Ha, V. and Haddaway, P. A hybrid approach to reasoning with partially elicited preference models. In Laskey, K. and Prade, H. (eds.), *Proceedings of the Fifteenth Conference on Uncertainty in Artificial Intelligence*. 1999.
- Harari, Y. N. Nexus: A brief history of information networks from the Stone Age to AI. Signal, 2024.
- Hardt, M. and Mendler-Dünner, C. Performative prediction: Past and future. *arXiv preprint arXiv:2310.16608*, 2023.

- Hendrycks, D., Mazeika, M., Burns, C., Basart, S., Critch, A., Song, D., and Steinhardt, J. Aligning ai with shared human values. *arXiv preprint arXiv:2008.02275*, 2020. URL https://arxiv.org/abs/2008.02275.
- Herrmann, M., Lange, F. J. D., Eggensperger, K., Casalicchio, G., Wever, M., Feurer, M., Rügamer, D., Hüllermeier, E., Boulesteix, A.-L., and Bischl, B. Position paper: Rethinking empirical research in machine learning: Addressing epistemic and methodological challenges of experimentation. *International Conference on Machine Learning*, 2024.
- Horkheimer, M. and Adorno, T. W. *Dialectic of Enlightenment: Philosophical Fragments*. Stanford University Press, Standford, 2002.
- Huang, S. H., Bhatia, K., Abbeel, P., and Dragan, A. D. Establishing appropriate trust via critical states. *CoRR*, abs/1810.08174, 2018. URL http://arxiv.org/abs/1810.08174.
- Hüllermeier, E. and Waegeman, W. Aleatoric and epistemic uncertainty in machine learning: An introduction to concepts and methods. *Machine learning*, 110(3):457–506, 2021.
- Ibarz, B., Leike, J., Pohlen, T., Irving, G., Legg, S., and Amodei, D. Reward learning from human preferences and demonstrations in atari. In Bengio, S., Wallach, H., Larochelle, H., Grauman, K., Cesa-Bianchi, N., and Garnett, R. (eds.), Advances in Neural Information Processing Systems, volume 31. Curran Associates, Inc., 2018.
- Jansen, C., Schollmeyer, G., and Augustin, T. A probabilistic evaluation framework for preference aggregation reflecting group homogeneity. *Mathematical Social Sciences*, 96:49–62, 2018. URL https://www. sciencedirect.com/science/article/pii/S0165489618300660.
- Jansen, C., Blocher, H., Augustin, T., and Schollmeyer, G. Information efficient learning of complexly structured preferences: Elicitation procedures and their application to decision making under uncertainty. *International Journal of Approximate Reasoning*, 144:69–91, 2022.
- Jansen, C., Nalenz, M., Schollmeyer, G., and Augustin, T. Statistical comparisons of classifiers by generalized stochastic dominance. *Journal of Machine Learning Research*, 24(231):1–37, 2023a. URL http://jmlr.org/papers/v24/22-0902.html.
- Jansen, C., Schollmeyer, G., and Augustin, T. Multi-target decision making under conditions of severe uncertainty. In Torra, V. and Narukawa, Y. (eds.), *Modeling Decisions for Artificial Intelligence*, pp. 45–57, Cham, 2023b. Springer Nature Switzerland.
- Jansen, C., Schollmeyer, G., Blocher, H., Rodemann, J., and Augustin, T. Robust statistical comparison of random variables with locally varying scale of measurement. In Evans, R. J. and Shpitser, I. (eds.), *Proceedings of the Thirty-Ninth Conference on Uncertainty in Artificial Intelligence*, volume 216 of *Proceedings of Machine Learning Research*, pp. 941–952. PMLR, 2023c.
- Jansen, C., Schollmeyer, G., Rodemann, J., Blocher, H., and Augustin, T. Statistical multicriteria benchmarking via the GSD-front. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL https://openreview.net/forum?id=jXxvSkb9HD.
- Ji, J., Qiu, T., Chen, B., Zhang, B., Lou, H., Wang, K., Duan, Y., He, Z., Zhou, J., Zhang, Z., et al. Ai alignment: A comprehensive survey. *arXiv preprint arXiv:2310.19852*, 2023.
- Jiang, L. A. H., Sap, M., Choi, Y., et al. Delphi: Towards machine ethics and norms via language models. https://delphi.allenai.org/, 2021.
- Kairouz, P., McMahan, H. B., et al. Advances and open problems in federated learning. Foundations and Trends in Machine Learning, 14(1–2):1–210, 2021.

- Kaufmann, T., Ball, S., Beck, J., Hüllermeier, E., and Kreuter, F. On the challenges and practices of reinforcement learning from real human feedback. In *Joint European Conference on Machine Learning and Knowledge Discovery in Databases*, pp. 276–294. Springer, 2023.
- Kim, J. and Oh, M. Queueing matching bandits with preference feedback. In *The Thirty-eighth Annual Conference* on Neural Information Processing Systems, 2024. URL https://openreview.net/forum?id=0TUMAAb3of.
- Kirk, H. R., Whitefield, A., Röttger, P., Bean, A., Margatina, K., Ciro, J., Mosquera, R., Bartolo, M., Williams, A., He, H., et al. The prism alignment project: What participatory, representative and individualised human feedback reveals about the subjective and multicultural alignment of large language models. *arXiv preprint arXiv*:2404.16019, 2024.
- Kirkpatrick, J., Pascanu, R., Rabinowitz, N., Veness, J., Desjardins, G., Rusu, A. A., Milan, K., Quan, J., Ramalho, T., Grabska-Barwinska, A., et al. Overcoming catastrophic forgetting in neural networks. *Proceedings of the National Academy of Sciences*, 114(13):3521–3526, 2017.
- Kreuter, F. (ed.). Improving surveys with paradata: Analytic uses of process information. John Wiley & Sons, 2013.
- Kuhn, T. S. The structure of scientific revolutions, volume 962. University of Chicago press Chicago, 1997.
- König, G., Günther, E., and von Luxburg, U. Disentangling interactions and dependencies in feature attribution, 2024. URL https://arxiv.org/abs/2410.23772.
- Lamm, N. Man's position in the universe. a comparative study of the views of saadia gaon and maimonides. *The Jewish Quarterly Review*, 55(3):208–234, 1965.
- Lee, J. D., Sun, D. L., Sun, Y., and Taylor, J. E. Exact post-selection inference with the lasso. *The Annals of Statistics*, 44(3):907–927, 2016.
- Li, X., Yu, Z., and Xiong, C. Montessori-instruct: Generate influential training data tailored for student learning. *arXiv preprint arXiv:*2410.14208, 2024. URL https://arxiv.org/pdf/2410.14208.
- Lieder, F., Griffiths, T. L., M. Huys, Q. J., and Goodman, N. D. The anchoring bias reflects rational use of cognitive resources. *Psychonomic bulletin & review*, 25:322–349, 2018.
- Lindauer, M., Karl, F., Klier, A., Moosbauer, J., Tornede, A., Mueller, A. C., Hutter, F., Feurer, M., and Bischl, B. Position: A call to action for a human-centered automl paradigm. In *Forty-first International Conference on Machine Learning*, 2024.
- Lopez-Paz, D. and Ranzato, M. Gradient episodic memory for continual learning. In Advances in Neural Information Processing Systems, volume 30, 2017.
- Lorenz, K. Behind the Mirror. Methuen, London, 1977.
- Lundberg, S. M. and Lee, S. A unified approach to interpreting model predictions. *CoRR*, abs/1705.07874, 2017. URL http://arxiv.org/abs/1705.07874.
- Madumal, P., Miller, T., Sonenberg, L., and Vetere, F. Explainable reinforcement learning through a causal lens. *CoRR*, abs/1905.10958, 2019. URL http://arxiv.org/abs/1905.10958.
- Markoff, J. In 1949, he imagined an age of robots. New York Times, 2013. URL https://shorturl.at/Zhyss.
- Mendler-Dünner, C., Perdomo, J., Zrnic, T., and Hardt, M. Stochastic optimization for performative prediction. *Advances in Neural Information Processing Systems*, 33:4929–4939, 2020.
- Menges, G. Die statistische Adäquation [The Statistical Adequation]. Jahrbücher für Nationalökonomie und Statistik, 197(4):289–308, 1982. URL http://www.degruyter.com/document/doi/10.1515/ jbnst-1982-0402/html.

- Mersmann, O., Preuss, M., Trautmann, H., Bischl, B., and Weihs, C. Analyzing the BBOB results by means of benchmarking concepts. *Evolutionary Computation*, 23:161–185, 2015.
- Miao, F., Holmes, W., Huang, R., Zhang, H., et al. *AI and education: A guidance for policymakers*. Unesco Publishing, 2021.
- Milani, S., Topin, N., Veloso, M., and Fang, F. A survey of explainable reinforcement learning, 2022. URL https://arxiv.org/abs/2202.08434.
- Miller, J. P., Perdomo, J. C., and Zrnic, T. Outside the echo chamber: Optimizing the performative risk. In *International Conference on Machine Learning*, pp. 7710–7720. PMLR, 2021.
- Mitelut, C., Smith, B., and Vamplew, P. Intent-aligned ai systems deplete human agency: the need for agency foundations research in ai safety. *arXiv preprint arXiv:2305.19223*, 2023.
- Molnar, C. Interpretable Machine Learning. 2 edition, 2022. URL https://christophm.github.io/ interpretable-ml-book.
- Molnar, C., Freiesleben, T., König, G., Herbinger, J., Reisinger, T., Casalicchio, G., Wright, M. N., and Bischl, B. Relating the partial dependence plot and permutation feature importance to the data generating process. In Longo, L. (ed.), *Explainable Artificial Intelligence*, pp. 456–479, Cham, 2023. Springer Nature Switzerland.
- Morgenstern, O. Wirtschaftsprognose: Eine untersuchung ihrer voraussetzungen und möglichkeiten [Economic forecast: An examination of its assumptions and possibilities]. *Wissenschaftstheorie in Ökonomie und Wirtschaftsinformatik, Deutscher Universitäts-Verlag, Wiesbaden,* pp. 171–190, 1928.
- Mu, T., Helyar, A., Heidecke, J., and Achiam, J. Rule-based rewards for fine-grained llm safety. In *ICML*. OpenReview, 2024.
- Mukherjee, S., Lalitha, A., Kalantari, K., Deshmukh, A. A., Liu, G., Ma, Y., and Kveton, B. Optimal design for human preference elicitation. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL https://openreview.net/forum?id=cCGWj61Ael.
- Nakano, R., Hilton, J., Balaji, S., Wu, J., Ouyang, L., Kim, C., Hashemi, M., Jiang, L., Chen, A., Haas, J., Shi, J., Iyer, S., Goodfellow, I., Butchireddygari, S., and Sucholutsky, I. WebGPT: Browser-assisted question-answering with human feedback. *arXiv preprint arXiv:2112.09332*, 2021. URL https://arxiv.org/abs/2112.09332.
- Olson, M. L., Khanna, R., Neal, L., Li, F., and Wong, W.-K. Counterfactual state explanations for reinforcement learning agents via generative deep learning. *Artificial Intelligence*, 295:103455, June 2021. URL http://dx. doi.org/10.1016/j.artint.2021.103455.
- Ouyang, L., Wu, J., Jiang, X., Almeida, D., Wainwright, C., Mishkin, P., Zhang, C., Agarwal, S., Slama, K., Ray, A., et al. Training language models to follow instructions with human feedback. *Advances in neural information* processing systems, 35:27730–27744, 2022a.
- Ouyang, L., Wu, J., Jiang, X., Almeida, D., Wainwright, C. L., Mishkin, P., Zhang, C., Agarwal, S., Slama, K., Ray, A., Schulman, J., Hilton, J., Kelton, F., Miller, L., Simens, M., Askell, A., Welinder, P., Christiano, P., Leike, J., and Lowe, R. Training language models to follow instructions with human feedback, 2022b. URL https://arxiv.org/abs/2203.02155.
- Parisi, G. I., Kemker, R., Part, J. L., Kanan, C., and Wermter, S. Continual lifelong learning with neural networks: A review. *Neural Networks*, 113:54–71, 2019.
- Perdomo, J., Zrnic, T., Mendler-Dünner, C., and Hardt, M. Performative prediction. In International Conference on Machine Learning, pp. 7599–7609. PMLR, 2020.
- Peters, O. Time for a change: Introducing irreversible time in economics. In Talk at Gresham College, 2012.

- Pillutla, K., Swayamdipta, S., Zellers, R., Thickstun, J., Welleck, S., Choi, Y., and Harchaoui, Z. Mauve: Measuring the gap between neural text and human text using divergence frontiers, 2021. URL https://arxiv.org/ abs/2102.01454.
- Popper, K. R. The Logic of Scientific Discovery. Routledge Classics, 2002/1959.
- Puiutta, E. and Veith, E. M. S. P. Explainable reinforcement learning: A survey. *CoRR*, abs/2005.06247, 2020. URL https://arxiv.org/abs/2005.06247.
- Radford, A., Wu, J., Child, R., Luan, D., Amodei, D., and Sutskever, I. Language models are unsupervised multitask learners. https://cdn.openai.com/better-language-models/language\_models\_are\_ unsupervised\_multitask\_learners.pdf, 2019. Accessed: 2025-01-27.
- Rafailov, R., Sharma, A., and Mitchell, E. Direct preference optimization: Your language model is secretly a reward model. In *Advances in Neural Information Processing Systems*, 2023.
- Ribeiro, M. T., Singh, S., and Guestrin, C. "why should i trust you?": Explaining the predictions of any classifier, 2016. URL https://arxiv.org/abs/1602.04938.
- Richardson, K., Srikumar, V., and Sabharwal, A. Understanding the logic of direct preference alignment. *arXiv* preprint arXiv:2412.17696, 2024.
- Rodemann, J. and Augustin, T. Accounting for imprecision of model specification in bayesian optimization. In *Poster presented at International Symposium on Imprecise Probabilities (ISIPTA)*, 2021.
- Rodemann, J. and Augustin, T. Accounting for gaussian process imprecision in bayesian optimization. In *International Symposium on Integrated Uncertainty in Knowledge Modelling and Decision Making*, pp. 92–104. Springer, 2022.
- Rodemann, J. and Augustin, T. Imprecise bayesian optimization. *Knowledge-Based Systems*, 300:112186, 2024.
- Rodemann, J. and Blocher, H. Partial rankings of optimizers. In The Second Tiny Papers Track at ICLR 2024, 2024.
- Rodemann, J., Goschenhofer, J., Dorigatti, E., Nagler, T., and Augustin, T. Approximately bayes-optimal pseudolabel selection. In *Uncertainty in Artificial Intelligence*, pp. 1762–1773. PMLR, 2023a.
- Rodemann, J., Jansen, C., Schollmeyer, G., and Augustin, T. In all likelihoods: Robust selection of pseudo-labeled data. In *International Symposium on Imprecise Probability: Theories and Applications*, pp. 412–425. PMLR, 2023b.
- Rodemann, J., Jansen, C., and Schollmeyer, G. Reciprocal learning. *Advances in Neural Information Processing* Systems, 37:1686–1724, 2025.
- Schmidhuber, J. Algorithmic theories of everything. arXiv preprint quant-ph/0011122, 2000.
- Schmidhuber, J. The speed prior: a new simplicity measure yielding near-optimal computable predictions. In *International conference on computational learning theory*, pp. 216–228. Springer, 2002.
- Schut, L., Tomasev, N., McGrath, T., Hassabis, D., Paquet, U., and Kim, B. Bridging the human-ai knowledge gap: Concept discovery and transfer in alphazero, 2023. URL https://arxiv.org/abs/2310.16410.
- Shapiro, M. B. *The Limits of Orthodox Theology: Maimonides' Thirteen Principles Reappraised*. Liverpool University Press, 2003.
- Shin, H., Lee, J. K., Kim, J., and Kim, J. Continual learning with deep generative replay. In *Advances in Neural Information Processing Systems*, volume 30, 2017.
- Shinn, N., Cassano, F., Gopinath, A., Narasimhan, K., and Yao, S. Reflexion: Language agents with verbal reinforcement learning. *Advances in Neural Information Processing Systems*, 36, 2024.

- Silver, D., Schrittwieser, J., Simonyan, K., Antonoglou, I., Huang, A., Guez, A., Hubert, T., Baker, L., Lai, M., Bolton, A., Chen, Y., Lillicrap, T., Hui, F., Sifre, L., van den Driessche, G., Graepel, T., and Hassabis, D. Mastering the game of go without human knowledge. *Nature*, 550(7676):354–359, Oct 2017. URL https://doi.org/10.1038/nature24270.
- Sorensen, T., Moore, J., Fisher, J., Gordon, M. L., Mireshghallah, N., Rytting, C. M., Ye, A., Jiang, L., Lu, X., Dziri, N., et al. Position: A roadmap to pluralistic alignment. In *Forty-first International Conference on Machine Learning*, 2024.
- Soros, G. The alchemy of finance. John Wiley & Sons, 2015.
- Stiennon, N., Ouyang, L., Wu, J., Ziegler, D. M., Lowe, R. J., Voss, C., Radford, A., Amodei, D., and Christiano, P. F. Learning to summarize with human feedback. In *Advances in Neural Information Processing Systems* (*NeurIPS*), volume 33, pp. 3008–3021, 2020. URL https://arxiv.org/abs/2009.01325.
- Su, Y. and Collier, N. Contrastive search is what you need for neural text generation, 2023. URL https: //arxiv.org/abs/2210.14140.
- Su, Y. and Xu, J. An empirical study on contrastive search and contrastive decoding for open-ended text generation, 2022. URL https://arxiv.org/abs/2211.10797.
- Sun, C., Qiu, X., Xu, Y., and Huang, X. How to fine-tune bert for text classification? In Lecture Notes in Computer Science, pp. 153–163. Springer, 2019.
- Tang, W. and Xu, R. A stochastic analysis approach to conditional diffusion guidance. *Columbia University Preprint*, 2024. URL http://www.columbia.edu/~wt2319/CDG.pdf.
- Tibshirani, R. J. and Taylor, J. Exact post-selection inference for sequential regression procedures. *Journal of the American Statistical Association*, 111(514):600–620, 2016.
- Topin, N. and Veloso, M. Generation of policy-level explanations for reinforcement learning. *CoRR*, abs/1905.12044, 2019. URL http://arxiv.org/abs/1905.12044.
- Tversky, A. and Kahneman, D. Judgment under uncertainty: Heuristics and biases: Biases in judgments reveal some heuristics of thinking under uncertainty. *Science*, 185(4157):1124–1131, 1974.
- Wang, S., Qureshi, M. A., and Miralles-Pechuan, L. Applications of explainable ai for 6g: Technical aspects, use cases, and research challenges. *arXiv preprint*, 2021. URL https://arxiv.org/pdf/2112.04698.
- Wang, S., Zhang, S., Zhang, J., Hu, R., and Zhang, T. Reinforcement learning enhanced llms: A survey. *arXiv* preprint arXiv:2412.10400, 2024a. URL https://arxiv.org/pdf/2412.10400.
- Wang, X., Chen, Q., and Singh, S. Towards verifiable ai alignment: The case for formal guarantees. *arXiv preprint arXiv*:2401.09172, 2024b.
- Wasserman, L. All of statistics: a concise course in statistical inference. Springer Science & Business Media, 2009.
- White, H. Maximum likelihood estimation of misspecified models. *Econometrica: Journal of the econometric society*, pp. 1–25, 1982.
- Wiener, N. Some moral and technical consequences of automation: As machines learn they may develop unforeseen strategies at rates that baffle their programmers. *Science*, 131(3410):1355–1358, May 1960.
- Wuketits, F. *Evolutionary Epistemology and Its Implications for Humankind*. State University of New York Press, Albany, 1990.

- Yang, Z., Liu, A., Liu, Z., Liu, K., Xiong, F., Wang, Y., Yang, Z., Hu, Q., Chen, X., Zhang, Z., et al. Position: Towards unified alignment between agents, humans, and environment. In *Forty-first International Conference on Machine Learning*, 2024.
- Yin, Q. and Leong, C. Direct preference optimization using sparse feature-level constraints. *arXiv preprint arXiv:2411.07618, 2024.* URL https://arxiv.org/pdf/2411.07618.
- Zhang, G. and Hardt, M. Inherent trade-offs between diversity and stability in multi-task benchmarks. In Salakhutdinov, R., Kolter, Z., Heller, K., Weller, A., Oliver, N., Scarlett, J., and Berkenkamp, F. (eds.), *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pp. 58984–59002. PMLR, 2024.
- Zhang, S., Roller, S., Goyal, N., Artetxe, M., Chen, M., Chen, S., Dewan, C., Diab, M., Li, X., Lin, X. V., Mihaylov, T., Ott, M., Shleifer, S., Shuster, K., Simig, D., Koura, P. S., Sridhar, A., Wang, T., and Zettlemoyer, L. Opt: Open pre-trained transformer language models, 2022. URL https://arxiv.org/abs/2205.01068.