UAR-NVC: A Unified AutoRegressive Framework for Memory-Efficient Neural Video Compression

Jia Wang, Xinfeng Zhang Senior Member, IEEE, Gai Zhang Student Member, IEEE, Jun Zhu Student Member, IEEE, Lv Tang Student Member, IEEE and Li Zhang Senior Member, IEEE

Abstract-Implicit Neural Representations (INRs) have demonstrated significant potential in video compression by representing videos as neural networks. However, as the number of frames increases, the memory consumption for training and inference increases substantially, posing challenges in resource-constrained scenarios. Inspired by the success of traditional video compression frameworks, which process video frame by frame and can efficiently compress long videos, we adopt this modeling strategy for INRs to decrease memory consumption, while aiming to unify the frameworks from the perspective of timeline-based autoregressive modeling. In this work, we present a novel understanding of INR models from an autoregressive (AR) perspective and introduce a Unified AutoRegressive Framework for memory-efficient Neural Video Compression (UAR-NVC). UAR-NVC integrates timelinebased and INR-based neural video compression under a unified autoregressive paradigm. It partitions videos into several clips and processes each clip using a different INR model instance, leveraging the advantages of both compression frameworks while allowing seamless adaptation to either in form. To further reduce temporal redundancy between clips, we treat the corresponding model parameters as proxies for these clips, and design two modules to optimize the initialization, training, and compression of these model parameters. In special, the Residual Quantization and Entropy Constraint (RQEC) module dynamically balances the reconstruction quality of the current clip and the newly introduced bitrate cost using the previously optimized parameters as conditioning. In addition, the Interpolation-based Initialization (II) module flexibly adjusts the degree of reference used during the initialization of neighboring video clips, based on their correlation. UAR-NVC supports adjustable latencies by varying the clip length. Extensive experimental results demonstrate that UAR-NVC, with its flexible video clip setting, can adapt to resource-constrained environments and significantly improve performance compared to different baseline models.

Index Terms—Video compression framework, implicit neural representation, autoregressive model, practical video compression.

I. INTRODUCTION

W ITH the advancement of media technologies, video data has become a widely used medium for connecting people to the world. However, this widespread use has also introduced significant challenges related to storage and transmission. To address these challenges, various video compression standards, such as H.264/AVC [2], H.265/HEVC [3], and H.266/VVC [4], have been developed in recent decades. These



Fig. 1. Different AutoRegressive (AR) methods: (a) Pixel-level AR, which utilizes the PixelCNN [1] model to model pixel probabilities. (b) Framelevel AR, which employs techniques such as optical flow estimation to model relationships between frames. (c) Implicit domain (INR-based) AR, which first converts video information into a neural network and then performs AR between the layers of the feature map, considering coordinates, intermediate feature maps, and output values as variables, treating each network layer as a conditional probability model. (d) Our UAR-NVC, which integrates INR-based AR and timeline-based AR by using INR models to represent each video clip and applying AR between INR models to capture inter-clip relationships.

standards generally treat video as an extension of images along the timeline and separately reduce the redundancies within and between frames.

Deep neural networks (DNNs) have recently achieved significant advancements across a wide range of fields. Consequently, neural video compression (NVC) [5]–[13] has evolved from replacing certain components [5]–[7] of traditional compression frameworks to designing an end-to-end compression framework, such as DVC [12] in an autoencoder framework. This shift has significantly enhanced NVC's potential,

Jia Wang, Xinfeng Zhang (corresponding author), Gai Zhang, Jun Zhu and Lv Tang are with School of Computer Science and Technology, University of Chinese Academy of Sciences, Beijing, China. Li Zhang is with Bytedance Inc., San Diego, USA. (Email: wangjia242@mails.ucas.ac.cn, xfzhang@ucas.ac.cn, zhanggai16@mails.ucas.ac.cn, zhujun23@mails.ucas.ac.cn, luckybird1994@gmail.com and lizhang.idm@bytedance.com)

achieving superior rate-distortion performance through joint optimization. Building on this, numerous studies have explored various advancements in individual modules, rapidly improving the Rate-Distortion (RD) performance of NVC. Although the most recent NVC codecs [14] have surpassed VVC in RD performance, they still face challenges, including limited generalization capacity and suboptimal performance on unseen datasets [15]. Moreover, the autoencoder-style video compression frameworks encounter bottlenecks in decoding speed [16], highlighting an urgent need for alternative approaches that simplify the pipeline and alleviate computational burdens.

In recent years, implicit neural representation (INR) has emerged as a powerful signal representation method, which has been used in image compression [17]-[21] and video compression, such as NeRV [16]. NeRV utilizes the timestamp as its sole input, enabling the decoding of an entire frame in a single forward pass, thereby significantly accelerating the decoding speed. Numerous follow-up works based on NeRV [22]-[29] have further improved the performance of INR codecs. Among these, HiNeRV [25] demonstrated notable improvements in RD performance for videos with obvious dynamic content, while MVC [29] even outperformed H.266/VVC by 20% in BD-Rate [30] saving when tested on conference and surveillance video datasets. Despite these advancements, INR-based approaches face significant challenges due to the reliance on a single model to encode all video frames, which places a heavy burden on GPU memory during both training and inference. This issue renders them impractical for many applications. How to decrease the training burden or processing longer video becomes a significant problem. An intuitive solution is to divide the video into clips, and use multiple smaller INR networks. However, this strategy will also introduce redundancy among models for different clips, potentially degrading the rate-distortion performance of INRbased video compression systems.

To address this issue, we review the representative traditional framework H.264/AVC [2], which compresses videos frame by frame using concepts like I-frames and P-frames. This enables efficient processing of long videos with limited memory resources. This raises a key question: can a similar concept be applied when using INRs to model videos? The traditional I-frame and P-frame modeling approach can be interpreted as an autoregressive process over time, where information from previous frames helps model subsequent ones. In this process, each frame serves as a fundamental unit. More specifically, video coding consists of intra-frame and inter-frame encoding, with the latter conceptualized as a form of timeline autoregression. Extending this idea, we propose expanding timeline autoregression from the frame level to the clip level.

Building on this concept, we divide a video into multiple clips, where each clip is modeled using a dedicated instance of an INR model, trained in an autoregressive manner. The clip length can be configured by users based on their available computational resources. To leverage the correlation between clips, we propose the Interpolation-based Initialization (II) module, which improves model initialization efficiency by utilizing information from INR models trained on previous clips. To avoid introducing redundant information between neighboring INR models, we design the Residual Quantization and Entropy Constraint (RQEC) module, which dynamically balances restoration quality and newly introduced information. In addition, to support random access, we introduce the concept of the Group of Models (GOM), similar to the Group of Pictures (GOP) in traditional video coding. However, unlike GOP, GOM treats clips, rather than frames, as the fundamental units in timeline autoregression. Building on these modules, we propose a novel Neural Video Compression (NVC) framework that combines the powerful modeling capabilities of INRs with the flexibility of traditional video coding frameworks to exploit the correlation of longer time domains, termed the Unified AutoRegressive-based Neural Video Compression framework (UAR-NVC).

The contributions of our work are summarized as follows:

- Unified Framework: We propose UAR-NVC, a novel framework that unifies timeline-based and INR-based NVC frameworks. Most existing INR model can be seamlessly integrated into our framework, demonstrating its flexibility and generality.
- Enhancements in Autoregressive Modeling: We design two modules to enhance autoregressive modeling for videos under the proposed UAR-NVC framework. The RQEC module dynamically balances the newly introduced information and the distortion of the current clip, based on the INR model parameters of the previous clip. The II module adaptively controls the reference strength for INR model initialization, allowing it to handle diverse video data effectively.
- Comprehensive Experiments: We conduct extensive experiments to verify the efficiency of the proposed UAR-NVC framework. The results demonstrate its superior performance in rate-distortion optimization and highlight its advantages for practical applications.

II. RELATED WORK

A. Traditional Video Compression Standards

As early as 1969, video coding was proposed as an academic problem at the Image Coding Workshop in Boston. Subsequently, under the impetus of the Telecommunication Standardization Organization of the International Telecommunication Union (ITU [31]), it rapidly developed into the H.261 standard [32]. As the earliest video coding standard, H.261 prescribed all components of video coding, including motion compensation, DCT transform, quantization, and entropy coding. Following this, H.262 [33], H.263 [34], and H.264/AVC [2] standards were proposed successively. With the introduction of multi-frame reference, intra-frame prediction, and multi-scale coding block technology, H.264 became the most widely adopted coding standard, marking the maturity of the hybrid coding framework. To further improve performance, H.265/HEVC [3] was proposed, achieving the same visual quality with nearly half the bitrate compared to H.264. More recently, the H.266/VVC [4] standard has emerged, offering even better performance.



Fig. 2. The proposed UAR-NVC, a practical INR framework for video compression. The video frames are grouped into several GOPs (video clips), where we train one model for one GOP. To balance correlation capture and random access, GOPs are grouped into GOMs. And time dependency exists only between GOPs within a GOM. The right part shows the training and compression pipeline of one GOM in UAR-NVC.

Besides the H.26x series, the AVS series developed by the Audio and Video Coding Standard Workgroup of China [35] has also gained significant attention. Although the first version, AVS1, was much later than H.261, the latest version, AVS3, achieves performance comparable to H.266 in 2021. Meanwhile, the video coding standards VP8 [36], VP9 [37], and AV1 [38], led by Google, continue to evolve. Despite these advancements, nearly all of these standards follow the pipeline established by H.264, which underscores the robustness of the hybrid video coding framework. This highlights the stability and practicality of this framework, which served as an inspiration for our work.

B. Neural Video Compression

With the popularity of deep learning, many works [5]–[7], [39] have focused on designing neural modules to replace certain components in traditional video coding frameworks. [5] proposes a fully connected network for intra prediction. [6] proposes training multiple networks as different prediction modes. [7] further incorporates RNNs and CNNs into the design of intra prediction networks, respectively. [40] and [41] optimize motion compensation using an improved subpixel interpolation algorithm. Meanwhile, [8] introduces a multiframe reference and bidirectional motion estimation mechanism, effectively improving the accuracy and compression efficiency of inter-frame prediction. In the aspect of entropy models, researchers have used CNNs or MLPs to predict the probability distribution of different data parts [8], [42], [43].

In another aspect, several researchers have proposed new video coding schemes [9], [10], [12], [44]–[47]. For instance, [9] trains two autoencoders using deep neural networks to compress intra-frame blocks and the inter prediction residuals for I-frames or P-frames, respectively. [10] employs the image coding scheme introduced in [11] to compress I-frames, while utilizing image interpolation to compress motion information from known frames for the remaining frames. [12] proposes

the first end-to-end neural video compression framework by replacing all modules in the traditional framework and enabling joint optimization across the entire system. Leveraging the powerful learning ability of neural networks, DCVC [13] uses a conditional method to capture the correlation between the current frame and the reference frame instead of simply using residuals. The subsequent work, DCVC-FM [46], further enhances Neural Video Compression (NVC) by introducing feature modulation techniques and support a wide quality range, and can effectively handle long prediction chains. Despite these advancements, these methods face generalization challenges and cannot get the optimal latent, as their model parameters are amortized over a fixed training dataset. To address this limitation, a new learning approach that can optimize model parameters specifically for each individual video is needed.

C. INR for Image Compression

Recently, Implicit Neural Representation (INR) has gained significant attention and has been successfully applied in the representation of objects [48], voxel [49] and scenes [50]. COIN [17] introduces INR into image compression. In this framework, the target image is represented as a set of pixels, where each pixel is defined by its coordinates and color values: (x, y, R, G, B). By learning the mapping function $f_{\theta} : (x, y) \rightarrow (R, G, B)$ parameterized by the network parameters θ , the information of the image is encoded into the network parameters. Afterward, COIN applies quantization and entropy coding to these parameters and stores them in a binary file, completing the encoding process. The decoding process involves multiple forward passes of the network for all the pixels, following entropy decoding and dequantization of the parameters.

Subsequently, several works have focused on reducing the encoding time through meta-learning [18] and improved rate-distortion (RD) performance via better network architectures [51] or more precise quantization techniques [20], [52]. Other works have further enhanced the RD performance through model pruning [53] or by combining autoencoders [21]. COOL-CHIC [54] innovatively combines INR with feature embedding, proposing a low-complexity image codec. Building on COOL-CHIC, the subsequent work C3 [55] demonstrated RD performance close to VTM on the UVG video benchmark with less than 5k MACs/pixel for decoding. This highlights the promising advantages of implicit neural representation methods, particularly in resource-constrained environments.

D. INR for Video Compression

Different from coordinate-based INR models like SIREN [56] and COIN, NeRV [16] uses the time stamp tas the input of the INR network, allowing it to reconstruct a entire video frame in one forward pass. This approach can achieve faster decoding speeds even than the practical traditional codec H.264. Following that, E-NeRV [22] combines spatial coordinates with time stamps and replaces the convolution kernel with two consecutive convolution kernels with smaller channels. PS-NeRV [57] reconstructs patches of the image instead of the whole image and uses Adaptive Instance Normalization (AdaIN) to modulate the features of the later convolution layers according to a time-coordinate condition. FF-NeRV [23] uses learnable multi-scale resolution feature grids to replace time or spatial coordinates, incorporates flow information into frame-wise representations to exploit the temporal redundancy across frames, and introduces quantization-aware training to shrink the quantization gap between training and model compression. HNeRV [24] trains an encoder to generate content-adaptive embeddings and proposes evenly distributed parameters for HNeRV, providing more capacity to store high-resolution content and video details. HiNeRV [25] uses the learnable feature grid not only at the network input but also in the subsequent upsampling module. By further improving the pruning and quantization parts of the model compression pipeline, HiNeRV achieves a 43.4% overall bit rate saving over DCVC on the UVG dataset, measured in PSNR. Boost-NeRV [26] proposes three universal techniques for NeRV-style models in module conditioning, activation layers, and entropy constraints, respectively.

Besides these excellent works that progressively improve the rate-distortion performance of Video INR, some works focus on the application of Video INR. To handle videos with frequent scene switching, D-NeRV [28] represents a large and diverse set of videos as a single neural network by using a multi-tiered structure together with a Visual Content Encoder and Motion-aware Decoder. Additionally, MVC [29] employs several spatial context enhancement and temporal correlation capturing techniques to further improve the representation capability of Video INR, achieving up to a 20% bitrate reduction compared to the latest video coding standard H.266 in conference and surveillance videos. To process long and different resolution videos, NIRVANA [27] proposes fitting every continuous three frames using different independent patch-wise model instances and employs an autoregressive approach in model initialization and compression. However, NIRVANA is limited by its specific model structure, we unify the timeline-based framework and INR-based NVC framework from an autoregressive perspective. Our UAR-NVC framework allows users to choose different GOP sizes based on available resources, supports various INR base models, and includes two modules that significantly leverage the correlation between clips, thereby greatly improving rate-distortion (RD) performance for video compression.

III. PROPOSED METHOD

Algorithm 1 Pipeline of UAR-NVC
procedure Video $Process(\mathbf{V}, T, p, m)$
$GOM_nums \leftarrow T/(p \cdot m)$
for $i_{gom} = 0$ to $GOM_nums - 1$ do
$(i_s, i_e) = (i_{aom}, i_{aom} + 1) \cdot p \cdot m$
$GOPs := \mathbf{V}[i_s:i_e]$
$INR_TASK(GOM, p, m)$
end for
// Training process within a COM
meandure INP TASK (COM n m)
for $h = 0$ to $m = 1$ do
$ \begin{array}{l} \text{for } \kappa = 0 \text{ to } m - 1 \text{ to} \\ \text{if } h = 0 \text{ there} \end{array} $
$\mathbf{I} k \equiv = 0 \text{inen}$
$\theta_k \leftarrow Normal(0, 1)$
$oldsymbol{ heta}_k \leftarrow oldsymbol{ heta}_k$
else $a' = (a + a^*)$
$\boldsymbol{\theta}_{k} \leftarrow f_{i} \left(\boldsymbol{\theta}_{k-1}, \boldsymbol{\theta}_{k-1} \right)$
$GOP := GOPs \left[k \cdot p : k \cdot (p+1) \right]$
for $e = 0$ to epochs do
for $i_{frame} = 0$ to $p-1$ do
$\mathbf{v}_{frame} := GOP\left[i_{frame}\right]$
$\hat{\mathbf{v}}_{frame} \leftarrow \text{NeRV}.forward\left(t; \boldsymbol{\theta}_{k}^{*}\right)$
$loss_d \leftarrow MSE(v_{frame}, \hat{v}_{frame})$
$loss_{r} \leftarrow I\left(f_{c}\left(oldsymbol{ heta}_{k}^{*},oldsymbol{ heta}_{k}^{*} ight) ight)$
$(loss_r + \lambda \cdot loss_d)$.backward ()
end for
end for
$bitstream \leftarrow f_c\left(oldsymbol{ heta}_k^{*},oldsymbol{ heta}_k^{*} ight)$
end for

To enhance the practicality of INR models for video compression tasks while ensuring compatibility with existing models, we propose the UAR-NVC framework from an autoregressive perspective, as illustrated in Fig. 2. In Sec. III-A, we review the advancements in autoregressive (AR) modeling for timeline-based video compression and provide a novel interpretation of INR models. In Sec. III-B, we introduce our UAR-NVC framework, followed by a detailed explanation of its three key components. Sec. III-C discusses the detailed methodology for segmenting an input video. In Sec. III-D, we present the Residual Quantization and Entropy Constrain (RQEC) module. Finally, in Sec. III-E, we describe the model initialization process within UAR-NVC.

A. Information Autoregressive

In the context where x represents a pixel, PixelCNN [1] can be employed to model spatial relationships through the probability distribution $p(x_i|x_{i-1}x_{i-2}...)$, which utilizes preceding pixels to model the probability distribution of the current pixel. This approach is referred to as pixel-level AR. If x denotes a frame, temporal relationships can be modeled using $p(x_i|x_{i-1})$ by leveraging motion estimation between neighboring frames [13]. This method captures temporal correlations within a video and is referred to as frame-level AR. Unlike generation tasks, compression tasks require recording both the signal distribution and the sampling position, as accurate signal recovery is necessary. Therefore, we consider the AR process in compression as an alternating process: initially obtaining the probability distribution, subsequently introducing new information decoded from the bitstream, and finally determining the value of the intermediate variable, which gradually converges to the original signal.

For an INR model, training is conducted over multiple epochs to encode information from images or videos into the network parameters. The reconstructed image or video is then obtained through a forward pass. Considering the network's input (coordinates), the output image or video, and the intermediate features as variables, the forward process can be interpreted as estimating a probability distribution. This process introduces new information from the bitstream into the network parameters, computes the next layer's feature values, and progressively refines the reconstructed frame, akin to the autoregressive (AR) modeling approach previously discussed. The two primary differences between timeline-based and INRbased compression models are as follows: (1) Timeline-based models store information transformation exclusively in the latent space, whereas INR-based models encode it within the network parameters. (2) During video decoding, conventional timeline-based models introduce information from the bitstream and perform the transformation in a single pass, whereas INR-based models repeat this process multiple times.

Since the transformation within a single convolutional or multilayer perceptron (MLP) layer is relatively simple, deeper network architectures are often necessary for mapping coordinates to images or videos. However, increasing network depth substantially raises GPU memory consumption. To address this issue, we partition the video into clips and model each clip using a separate INR model instance, thereby reducing memory usage. In addition, we apply timeline-based autoregressive (AR) modeling by treating each clip as a symbol and modeling them sequentially to further minimize temporal redundancy. We refer to this approach as Unified AR.

B. The Proposed UAR-NVC Framework

We begin by introducing the foundational concepts of our framework. A video with T frames can be represented as $\mathbf{V} = \{\mathbf{v}_t\}_{t=1}^T \in \mathbb{R}^{T \times H \times W \times 3}$. The INR model can be regarded as a mapping function $f_{\boldsymbol{\theta}} : \mathbb{R} \to \mathbb{R}^{H \times W \times 3}$ parameterized by $\boldsymbol{\theta}$. Given a time stamp t, the reconstructed frame $\hat{\mathbf{v}}_t$ is obtained, forming the complete reconstructed video

 $\hat{\mathbf{V}} = {\{\hat{\mathbf{v}}_t\}}_{t=1}^T \in \mathbb{R}^{T \times H \times W \times 3}$. We define p and m as userdefined hyperparameters representing the size of GOP (Group of Pictures) and GOM (Group of Models), respectively. The video is partitioned based on these parameters. Each GOP instance is denoted as $\text{GOP}\#k, k \in \mathbb{R}$, and each GOM instance as $\text{GOM}\#k, k \in \mathbb{R}$, where k represents the index of the respective GOP or GOM. The first model in a GOM is referred to as the I-model, meaning it does not depend on any preceding model. The remaining models in a GOM are termed P-models, as they reference the previous model for initialization and compression.

As illustrated in Fig. 2, we begin by grouping video frames into GOPs based on the parameter p. Each GOP contains the same number of frames and follows an identical model structure, but distinct model instances are assigned to each GOP. We employ an INR model, such as HNeRV [24], to fit the video frames within each GOP. Subsequently, GOPs are further grouped into GOMs according to the parameter m. All GOMs follow a consistent processing pipeline, where INR models are sequentially trained using their corresponding GOPs as training data.

Within a GOM, we employ an autoregressive approach for training and compressing each model. For Model#0, initialized with randomly parameters θ_0 , the frames in GOP#0 serve as the training data. After training, the parameters are optimized from θ_0 to θ_0^* , denoted as: $\theta_0 \xrightarrow{train} \theta_0^*$. The corresponding bitrate is defined as:

$$Rate_0 = I\left(\boldsymbol{\theta}_0^*\right),\tag{1}$$

where $I(\cdot)$ calculates the total bitrate required to encode the given parameters.

Since the randomly initialized parameters θ_0 can be reconstructed using the initialization seed, and θ_0^* can be read back from the bit stream, both (primarily θ_0^*) serve as reference information for processing Model#1. The relationship between adjacent GOPs is captured through model parameters. Specifically, instead of using randomly initialized parameters θ_1 , we derive specially initialized parameters θ_1' for Model#1 by combining θ_0 and θ_0^* , defined as:

$$\boldsymbol{\theta}_1' = f_i\left(\boldsymbol{\theta}_0, \boldsymbol{\theta}_0^*\right). \tag{2}$$

This initialization strategy accelerates the training of Model#1, with experimental analyses provided in Sec. IV. Furthermore, since the final parameters θ_1^* are obtained through training (or fine-tuning) from the primary parameters θ_1' , denoted as: $\theta_1' \xrightarrow{train} \theta_1^*$, we store the difference between θ_1' and θ_1^* instead of directly recording θ_1^* . The bitrate of Model#1 is given by:

$$Rate_1 = I\left(f_c\left(\boldsymbol{\theta}_1', \boldsymbol{\theta}_1^*\right)\right),\tag{3}$$

where the definition of $f_c()$ will be given in Sec. III-D. The remaining P-models follow the same reference process, differing only in the reference target. The complete processing pipelines is detailed in Alg. 1.

C. Group of Models

Traditional video compression standards, such as H.264, categorize video frames into three types: intra-coded (I)



Fig. 3. (a): GOP level video partition with I-frames and P-frames. (b): GOM level video partition with I-models(#1/4) and P-models(#2/3/5/6).

frames, predictive-coded (P) frames, and bidirectionally predicted (B) frames. One purpose of this classification is to regulate the reference direction of each frame. The Group of Pictures (GOP) structure segments a video sequence into multiple groups, where frames within a GOP can reference each other while ensuring a one-way reference direction between any two frames. Across different GOPs, compression and decompression occur independently, enabling resynchronization during decoding in practical applications such as video jump playback.

Inspired by this setting, we define the set of frames which are modeled together a GOP, equivalent to a clip in our framework. Consequently, each GOP is assigned a separate INR model instance, as described in Sec. III-B. Building on this concept, we extend the traditional GOP definition from the frame level to the model level, introducing the Group of Models (GOM). Analogous to GOPs, we designate the first model in a GOM as an I-model, while subsequent models are classified as P-models. The I-model is initialized and compressed independently, whereas P-models rely on the parameters of the preceding model for initialization and compression. Under this framework, a given video sequence is first divided into multiple GOPs through frame grouping, followed by further partitioning into GOMs through model grouping. We use equal-length and continuous sub-items (frames/models) in this process, though it can be extended to uneven or dynamic partitioning based on sequence variability or user-defined requirements. The partitioning and reference process is illustrated in Fig. 3.

D. Residual Quantization and Entropy Constrain

COIN [17] and NeRV [16] reformulate video compression as a model compression problem by fitting videos using neural networks. Many subsequent works adopt the model compression pipeline introduced by NeRV, which consists of model pruning, model quantization, and parameter encoding. Among these, the latest INR model, HiNeRV [25], introduces several advancements. It applies a higher pruning ratio to convolutional layers with wider channels, based on the assumption that they contain more redundancy. In addition, it leverages Quantization-Aware Training (QAT) to mitigate the quantiza-



Fig. 4. Residual quantization-based entropy estimation on P-model. θ'_k denotes the parameters initialized from the model trained previously and θ^*_k denotes the parameters used for the forward process of network. Since the model from the same GOM is accessible at the initialization of the current model, we can dynamically capture the relationship between these two models by estimating the entropy of $\Delta \theta$ during training. Notice that $\Delta \theta$ is the residual of θ^*_k and θ'_k in our deployment, though alternative formats can also be employed.

tion gap between training and inference. Furthermore, HiNeRV replaces the Huffman encoder with a more advanced arithmetic encoder, significantly improving rate-distortion performance.

In our view, certain works [26], [27], [58] can further improve compression performance by dynamically balancing reconstruction quality and bitrate cost. This can be achieved by estimating the entropy of network parameters and incorporating it into the training loss. Therefore, we adopt the entropy-constrained method from Boost-NeRV [26], in which a symmetric scalar quantization scheme with a trainable scale parameter ς is used for model parameters:

$$Q(\boldsymbol{\theta}) = \left\lfloor \frac{\boldsymbol{\theta}}{\varsigma} \right\rceil, \quad P(\boldsymbol{\theta}) = \boldsymbol{\theta} \times \varsigma, \tag{4}$$

where $Q(\cdot)$ represents scale and quant, while $P(\cdot)$ represents scale back. Furthermore, we model the probability distribution of the quantized parameters $\hat{\theta}$ using a Gaussian distribution:

$$p\left(\hat{\boldsymbol{\theta}}\right) = \prod_{i} \left(\mathcal{N}\left(\mu_{\boldsymbol{\theta}}, \sigma_{\boldsymbol{\theta}}^{2}\right) * \mathcal{U}\left(-\frac{1}{2}, \frac{1}{2}\right) \right) \left(\hat{\boldsymbol{\theta}}_{i}\right), \quad (5)$$

where μ_{θ} and σ_{θ}^2 are the mean and variance of the parameters θ for each layer, and *i* represents layer index. Here, * denotes convolution. As previously mentioned, this approach captures global relationships among all parameter elements. Notably, we observed that parameters in wider convolutional layers are allocated fewer bits, effectively replicating the functionality of uneven pruning in HiNeRV [25].

We incorporate this entropy estimation method in the training of the I-model and further extend it to the training of the P-model. As shown in Fig. 4, for the k-th model (k%m > 0), θ'_k and θ^*_k refer to the parameters initialized from the previous model by the function f_i and the optimized parameters via training process, respectively. We define the reference function as:

$$f_c\left(\boldsymbol{\theta}_k^{\prime}, \boldsymbol{\theta}_k^{*}\right) = \boldsymbol{\theta}_k^{*} - \boldsymbol{\theta}_k^{\prime},$$
 (6)



Fig. 5. Variation of RD performance with different random percent. The anchor for PNSR and bpp variations is $\varepsilon = 0$. The legend for the right axis and the legend for the left axis share the same linetypes.

While computing the reconstructed frame \hat{v} , we use θ_k^* , but for entropy estimation of the network parameters, we use the difference $\theta_k^* - \theta_k'$. The loss function is:

$$\begin{cases}
Loss_d = MSE(\mathbf{v}, f(t; \boldsymbol{\theta}_k^*)), \\
Loss_r = I(\boldsymbol{\theta}_k^* - \boldsymbol{\theta}_k'), \\
Loss = Loss_r + \lambda \cdot Loss_d,
\end{cases}$$
(7)

where f denotes the forward process of an INR model parameterized by θ_k^* . This approach allows information from the previous model instance to improve convergence speed while simultaneously reducing redundancy.

E. Interpolation-based Model Initialization

Since adjacent frames in a video exhibit strong correlations, autoregressively initialized models that leverage parameters from neighboring model perform well when p is small. However, as p increases, these correlations weaken or even disappear. Consequently, the direct initialization (D-init) method may perform poorly, potentially even worse than random initialization (R-init). This phenomenon may arise from the large space of network parameters. The optimal parameters for GOP#a may be significantly different from those for GOP#b, both of which are also distant from the randomly initialized parameters. In extreme cases, where the optimal parameters of two models lie in opposite directions, D-init can increase optimization difficulty rather than providing a useful starting point.

Based on this assumption, we propose an interpolationbased model initialization method, which dynamically controls the usage percentage of the trained parameters from the previous model. Specifically, we fuse preliminary parameters with a percentage factor ε to regularize the trained parameters from the previous model. Our model initialization function is:

$$\boldsymbol{\theta}_{k}^{\prime} = f_{i}\left(\boldsymbol{\theta}_{k-1}, \boldsymbol{\theta}_{k-1}^{*}\right) = \varepsilon \cdot \boldsymbol{\theta}_{k-1} + (1-\varepsilon) \cdot \boldsymbol{\theta}_{k-1}^{*}, \quad (8)$$



Fig. 6. Relationship between the gap of corresponding frames (measured using MSE) and the best random initialization percent ε .

where $\varepsilon \in [0,1]$, k%m > 0. This indicates that the interpolation initialization (II) module is not applied to the first model in a Group of Models (GOM). We only store a seed to reconstruct θ_0 on the decoding side, which serve as the initialization parameters of the first model in a GOM.

To determine the optimal ε , we analyze the rate-distortion (RD) performance across different values of ε and p. Our findings indicate that the best ε varies depending on p. Specifically, as p increases, the gap between adjacent GOPs widens, necessitating a larger ε to achieve the best RD performance. This trend likely arises because a larger p results in greater differences between corresponding frames in successive GOPs. To quantify the gap between two GOPs, we measure the Mean Squared Error (MSE) of corresponding frames [27]. To establish a numerical relationship between MSE and ε , we conduct a statistical analysis of the optimal ε and MSE values across different p settings using three sequences from the MCL-JCV [59] dataset, which are non-repetitive with the test datasets we use in Sec. IV. We assume this function follows a variant of an exponential function:

$$\varepsilon = -ae^{(-b \times MSE + c)} + 1, \tag{9}$$

where a > 0, b > 0. As illustrated in Fig. 6, we use the collected data to determine the hyperparameters a, b, and c, obtaining precise values. In all subsequent experiments on other datasets, we adopt the initialization function defined in Eqn. (9).

IV. EXPERIMENTS

In the following, we first present the experimental settings, followed by the overall rate-distortion performance of our framework. Next, we highlight the advantages of our framework under different p settings from three perspectives. Finally, we conduct ablation studies to validate the effectiveness of our two modules.



Fig. 7. Rate Distortion performance on UVG dataset with different p (GOP).

A. Experiment Setting

1) Test Sequences and Base Models: We select HNeRV [24] and HiNeRV [25] as the base models for our framework and evaluate them on the UVG dataset and VVC Class B dataset. For the UVG dataset, we use six sequences ("HoneyBee", "Bosphorus", "Beauty", "YachtRide", "Jockey", "ReadySetGo"), each containing 600 frames. We set m = 5and evaluate p with values of (6, 30, 120) for the UVG dataset and (5, 25, 100) for the VVC Class B dataset to evaluate small, medium, and large p scenarios. We provide two versions of the base models. The "base" version employs the QAT [25] and D init. The "ours" version incorporates our RQEC and II modules.

2) Implementation Details: To achieve different bitrate points, we follow previous work to adjust the model size [16], [24], [25]. For small p, the model sizes are (0.3, 0.45, 0.6, 0.9) MB. For medium p, the model sizes are (0.6, 0.9, 1.8, 2.7) MB. For large p, the model sizes are (3.0, 4.5, 6.0, 9.0) MB. In addition, we set the rate-distortion trade-off parameter λ to 5.0 for HiNeRV and 0.5 for HNeRV, as they have very different network architectures. We obtained these values using a fitting method similar to ε described in Sec. III-E. The small, medium and large p settings correspond to different learning rates and training epochs for HiNeRV: 5e-3/2e-3/2e-3 and 3k/1.5k/1.5k for I-model, and 2k/2k/1k for P-model. For HNeRV, the learning rates are adjusted to 2e-3/2e-3/1e-3. The papramter selection follows the setting in their original

paper [24], [25]. Besides, we train for more epochs when p is smaller, as fewer data points per epoch require longer training.

During training, we set the batch size to 1 and use the Adam optimizer. We also apply cosine learning rate decay with a 10% warm-up, following previous NeRV-based approaches [16], [24], [26]. Most experiments are conducted on a single NVIDIA GTX 3090 GPU, except for some HiNeRV experiments, which require more memory and are trained on an NVIDIA A6000 GPU.

For traditional codecs, we compare our framework's performance with dominant video coding standards, including H.264 [2] and H.265 [3]. We also use the same value of pas GOP for these traditional codecs for fair testing, which is (5/6, 25/30, 100/120). We use x264 and x265 in FFmpeg with the veryslow profile as follows:

- i) ffmpeg -pix_fmt yuv420p -s:v W×H -i input.yuv -vframes N_e -c:v libx264 -preset veryslow -qp QP -g GOP output.mkv
- ii) ffmpeg -pix_fmt yuv420p -s:v W×H -i Video.yuv -vframes Ne -c:v libx265 -preset veryslow -x265-params "qp=QP :keyint=GOP" output.mkv

3) Evaluation Metrics: We use Peak Signal-to-Noise Ratio (PSNR) and Multi-Scale Structural Similarity (MS-SSIM) to evaluate the quality of the reconstructed frames compared to the original frames. Bits per pixel (bpp) measures the average number of bits required to encode each pixel. In addition, we use the Bjøntegaard Delta Rate (BD-Rate) [30] to compare the



Fig. 8. Rate Distortion performance on VVC ClassB dataset with different p (GOP).

 TABLE I

 BD-rate (%) for PSNR/MS-SSIM. The anchor for each methods is x265 (veryslow).

Dataset	UVG				VVC ClassB							
Metirc		PSNR		MS-SSIM			PSNR			MS-SSIM		
GOP	GOP6	GOP30	GOP120	GOP6	GOP30	GOP120	GOP5	GOP25	GOP100	GOP5	GOP25	GOP100
HNeRV (base)	358.00	225.81	157.71	254.53	140.22	108.40	397.38	413.73	343.36	332.77	389.09	279.90
HNeRV (ours)	189.30	113.17	113.04	234.61	135.19	76.12	291.54	250.67	193.87	251.86	238.46	169.31
HiNeRV (base)	217.16	102.15	65.89	37.28	4.56	-1.50	285.36	193.53	100.12	112.90	68.05	21.58
HiNeRV (ours)	20.43	-17.60	-34.29	-30.86	-51.29	-53.79	85.55	36.34	-18.79	3.01	-4.82	-50.57

compression performance of different schemes, where negative values indicate bitrate savings, and positive values indicate increased bitrate consumption.

B. Rate-Distortion Performance

To evaluate the performance of our framework under different settings, we first conduct experiments on the UVG dataset. As shown in Fig. 7, both HiNeRV and HNeRV exhibit significant improvements when integrated with our proposed modules. Specifically, when using HNeRV (base) and HiNeRV (base) as anchors, and comparing the RD curve positions of HNeRV (ours) and HiNeRV (ours), we observe that the primary gain in HNeRV stems from bitrate savings, while the primary gain in HiNeRV arises from improved image quality. This improvement is attributed to HiNeRV's more complex grid design, which enables it to capture finer details and fully leverage the potential of a more advanced entropy model with flexible bit allocation. Conversely, HNeRV's architecture is optimized for efficiency, featuring a compact structure that reduces memory consumption and accelerates inference speed. This streamlined design also imposes a limit on its maximum reconstruction quality, even as it achieves substantial bitrate reductions with our two modules. When evaluated using the MS-SSIM metric, both models exhibit a trend similar to the analysis in PSNR. However, compared to x265 (veryslow) as the anchor, INR-based methods achieve significantly better in MS-SSIM relative to PSNR. This discrepancy arises because INR models encode video data in a more holistic manner, leading to superior structural fidelity. In contrast, traditional block-based encoders struggle to effectively capture the structural relationships between blocks.

Examining the performance gap across different p settings, we observe that in smaller p settings, the RD performance of INR-based model is inferior to that in larger p settings. This is primarily because models with larger p settings are more effective at reducing temporal redundancy. Consequently, choosing



Fig. 9. Subjective quality comparison between HiNeRV (base) and HiNeRV (ours). HiNeRV (ours) achieves lower distortion at a similar bitrate.

an appropriate p value involves a trade-off dictated by resource constraints. In addition, we note that when p = 6, HiNeRV (ours) performs less effectively than x265 (veryslow) at low bitrates but surpasses it at higher bitrates. This occurs because, when fitted with a smaller model, the HiNeRV structure has limited capacity to capture fine details, reducing its fitting ability. However, higher bitrate models alleviate this limitation, leading to improved overall performance. As p increases, the performance of our method improves steadily and eventually surpasses that of x265 (veryslow), demonstrating the robust modeling capabilities of implicit representation models. Notably, p = 30 represents a highly practical configuration, with encoding delays that remain acceptable in many realworld scenarios. In this setup, our RD performance exceeds that of x265 (veryslow), further validating the effectiveness of our framework. When p = 120, HiNeRV (ours) significantly outperforms x265 (veryslow). This result demonstrates that our framework is not only suitable for lower-resource environments but is also capable of maximizing RD performance across a broad spectrum of resource configurations.

Fig. 8 presents the experimental results on the VVC Class B dataset. Most of the analyses observed on the UVG dataset, as discussed earlier, also apply here. However, due to the inherent characteristics of current INRs, which are more suitable for videos with fewer dynamic scenes, the overall gain relative to x265 (veryslow) on this dataset is lower than that observed on the UVG dataset. Nevertheless, at larger p settings, the RD performance of HiNeRV (ours) still surpasses that of x265 (veryslow). In addition, we present the BD-Rate results for both PSNR and MS-SSIM metrics in Table I to show the performance of HiNeRV (ours) over four bitrate points. Among all INR-based methods, HiNeRV (ours) achieves the best performance. For the PSNR metric, it outperforms x265 (veryslow) in half of the experimental setups. In terms of MS-SSIM, HiNeRV (ours) exceeds x265 (veryslow) in most setups, achieving up to a 50% bitrate reduction with maintaining equivalent MS-SSIM when p = 120. To further illustrate the effectiveness of our method, Fig. 9 presents visualized comparisons between HiNeRV (base) and HiNeRV (ours). The results clearly show that HiNeRV (ours) restores finer details while requiring a lower bitrate. Furthermore, HiNeRV (base) is more prone to amplifying certain details, causing them to become more prominent and interfering with the background. In contrast, HiNeRV (ours) models these details more effectively, preventing them from disrupting background consistency.

C. Advantage of Different GOP Settings

To achieve the same reconstruction quality for a given video dataset and model architecture, a smaller p generally corresponds to a smaller model size, as fewer frames need to be fitted. Next, we analyze the impact of variations in model size.

Memory Usage and Computational Complexity are critical considerations for practical deployment. Memory usage and computational complexity are critical considerations for practical deployment. Table II presents the memory consumption of HNeRV under different batch sizes and model sizes. We observe that as the batch size (bs) and model size increase, memory usage also rises. For a 10 MB HiNeRV model, a batch size of 4 approaches the limit on a consumer-grade GPU with 24 GB of VRAM. While HNeRV is already a memoryefficient INR model due to its balanced parameter distribution, other INR models tend to consume even more memory. In our experiments, we also tested HiNeRV, which exhibits significantly higher memory usage, necessitating the use of GPUs with larger memory capacities for certain experiments.

Given the diverse range of encoding tasks across various scenarios, the compression model must operate on devices with different hardware configurations. In our framework, small GOP settings only require fitting smaller models, providing users with the flexibility to adjust hyperparameters

TABLE IIGPU MEMORY COST (MB), MACS AND TRAINING TIME COST PERIMAGE(ONCE FORWARD+BACKWARD) WITH DIFFERENT p (GOP)SETTING. THE "-" STANDS CUDA OUT OF MEMORY.

ModelSize	0.3MB	1.0MB	3.0MB	5.0MB	10.0MB
Mem(bs1)	2500	2832	4014	4244	6062
Mem(bs2)	4326	4966	6852	8534	15770
Mem(bs4)	8264	10258	13194	15386	24187
Mem(bs8)	16248	20114	-	-	-
Macs	11.13G	43.16G	134.53G	217.32G	419.85G
Train time Per iteration	37.78ms	53.33ms	86.67ms	116.67ms	242.22ms

TABLE III Ablation study of UAR-NVC. Values in the table mean bpp/PSNR (dB).

GOP	6	30	120
HiNeRV (ours) (V0) II init + ref	0.279/39.219	0.158/38.905	0.143/39.053
(V1) R init + w/o ref	0.327/38.758	0.174/38.503	0.145/38.927
(V2) D init	0.401/37.786	0.226/37.289	0.185/37.785
(V3) w/o ref	0.344/38.995	0.181/38.605	0.144/39.054

according to their needs. More generally, our framework captures temporal correlations across multiple GOPs through autoregression, allowing each GOP to be loaded separately onto the GPU for training while maintaining an efficient compression ratio.

Fitting Speed influence not only deployment by also training efficiency. Apart from low GPU memory consumption, another advantage of a small model is the reduction in forward-pass computation time, which impacts both training and inference speeds. Table II presents the time required for a single training iteration of one frame (one forward and backward pass), showing that smaller model sizes result in faster processing speeds. Consequently, smaller p settings ebables faster training. Early in training (not converged), the PSNR is higher for small p with the same training time. In addition, the reduced computational cost during inference allows for operation on more lightweight devices, also making the approach suitable for Single-Encoding Multiple-Decoding (SEMD) scenario.

D. Ablation Study

To evaluate the effectiveness of each proposed module, we conducted ablation experiments. We tested two components of UAR-NVC: the II module and the QEC module. For the II module, we compared it against random initialization (Rinit), which does not utilize any information from the trained parameters of previous models, and direct initialization (Dinit), which directly transfers the trained parameters of the previous model as the initialization for the current model. For the RQEC module, we assessed performance in the absence of reference-based compression (w/o ref).

For p = 6/30, we compare V0 and V3, as shown in Table III, and found that the reference compression design in the QEC module reduces bitrate by 12.7%/18.9% while improving the PSNR metric by 0.3 dB/0.224 dB. This improvement occurs because the reference compression setting



Fig. 10. The convergence process under the three initialization strategies.

captures the correlation between adjacent GOPs, further enhancing reconstruction quality through the RD optimization mechanism of the QEC module. Comparing V1 and V3, our II-init module provides only a marginal improvement. This is because, after approaching convergence, II-init and R-init have minimal impact on the final RD performance without reference.

Fig. 10 illustrates the convergence process of the three initialization strategies. The results show that utilizing the similarity between GOPs can improve the reconstruction quality at the beginning of training. As analyzed in Sec. III-E, D-init leads to parameter overfitting to previous GOP data, trapping the optimization in local minima and restricting subsequent performance improvements. In contrast, our II-init approach not only exploits the correlation between adjacent GOPs to accelerate training but also mitigates the overfitting issue observed in D-init.

For p = 120, the performances of V0, V1, and V3 are nearly identical. This is because the performance gains derived from neighboring models primarily stem from the correlation between adjacent GOPs. However, at larger p settings, this correlation diminishes, limiting the potential performance improvement. Nevertheless, we observe that the two adverse effects caused by D-init persist, whereas our R-init effectively mitigates these issues.

V. CONCLUSION AND FUTURE WORK

In this work, we propose UAR-NVC, a neural video framework that unifies timeline-based and INR-based Neural Video Compression (NVC) from an autoregressive perspective, enabling current INR models to be adaptively utilized in different resource-constrained scenarios. Furthermore, to enhance ratedistortion (RD) performance, we introduce two key modules: The RQEC module, designed for network optimization and model compression; the II module, designed for efficient model initialization.

Although the framework has been introduced, several aspects require further improvement. Since the complexity of fitting videos varies significantly based on scene dynamics, future work should explore dynamic clip partitioning in the *frame grouping* process to better adapt to different motion

patterns. In addition, our framework currently relies on existing INR models for clip processing, and the RD performance of UAR-NVC with small GOPs is not yet optimal. A more carefully designed and optimized INR model architecture could further enhance performance. Furthermore, our current approach to model reference compression and reference initialization is relatively simplistic. Future work could focus on refining these two modules to further improve efficiency and rate-distortion performance.

REFERENCES

- A. Van Den Oord, N. Kalchbrenner, and K. Kavukcuoglu, "Pixel recurrent neural networks," in *International conference on machine learning*. PMLR, 2016, pp. 1747–1756.
- [2] H. Schwarz, D. Marpe, and T. Wiegand, "Overview of the scalable video coding extension of the h. 264/avc standard," *IEEE Transactions on circuits and systems for video technology*, vol. 17, no. 9, pp. 1103–1120, 2007.
- [3] G. J. Sullivan, J.-R. Ohm, W.-J. Han, and T. Wiegand, "Overview of the high efficiency video coding (hevc) standard," *IEEE Transactions* on circuits and systems for video technology, vol. 22, no. 12, pp. 1649– 1668, 2012.
- [4] B. Bross, Y.-K. Wang, Y. Ye, S. Liu, J. Chen, G. J. Sullivan, and J.-R. Ohm, "Overview of the versatile video coding (vvc) standard and its applications," *IEEE Transactions on Circuits and Systems for Video Technology*, vol. 31, no. 10, pp. 3736–3764, 2021.
- [5] J. Li, B. Li, J. Xu, R. Xiong, and W. Gao, "Fully connected networkbased intra prediction for image coding," *IEEE Transactions on Image Processing*, vol. 27, no. 7, pp. 3236–3247, 2018.
- [6] J. Pfaff, P. Helle, D. Maniry, S. Kaltenstadler, W. Samek, H. Schwarz, D. Marpe, and T. Wiegand, "Neural network based intra prediction for video coding," in *Applications of Digital Image Processing XLI*, vol. 10752. SPIE, 2018, pp. 359–365.
- [7] Y. Hu, W. Yang, M. Li, and J. Liu, "Progressive spatial recurrent neural network for intra prediction," *IEEE Transactions on Multimedia*, vol. 21, no. 12, pp. 3024–3037, 2019.
- [8] J. Lin, D. Liu, H. Li, and F. Wu, "M-lvc: Multiple frames prediction for learned video compression," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2020, pp. 3546–3554.
- [9] T. Chen, H. Liu, Q. Shen, T. Yue, X. Cao, and Z. Ma, "Deepcoder: A deep neural network based video compression," in 2017 IEEE Visual Communications and Image Processing (VCIP). IEEE, 2017, pp. 1–4.
- [10] C.-Y. Wu, N. Singhal, and P. Krahenbuhl, "Video compression through image interpolation," in *Proceedings of the European conference on computer vision (ECCV)*, 2018, pp. 416–431.
- [11] G. Toderici, D. Vincent, N. Johnston, S. Jin Hwang, D. Minnen, J. Shor, and M. Covell, "Full resolution image compression with recurrent neural networks," in *Proceedings of the IEEE conference on Computer Vision* and Pattern Recognition, 2017, pp. 5306–5314.
- [12] G. Lu, W. Ouyang, D. Xu, X. Zhang, C. Cai, and Z. Gao, "Dvc: An end-to-end deep video compression framework," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2019, pp. 11006–11015.
- [13] J. Li, B. Li, and Y. Lu, "Deep contextual video compression," Advances in Neural Information Processing Systems, vol. 34, pp. 18114–18125, 2021.
- [14] —, "Neural video compression with diverse contexts," in *IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2023, Vancouver, Canada, June 18-22, 2023, 2023.*
- [15] L. Tang, J. Zhu, X. Zhang, L. Zhang, S. Ma, and Q. Huang, "Canerv: Content adaptive neural representation for video compression," *arXiv* preprint arXiv:2502.06181, 2025.
- [16] H. Chen, B. He, H. Wang, Y. Ren, S. N. Lim, and A. Shrivastava, "Nerv: Neural representations for videos," *Advances in Neural Information Processing Systems*, vol. 34, pp. 21557–21568, 2021.
- [17] E. Dupont, A. Goliński, M. Alizadeh, Y. W. Teh, and A. Doucet, "Coin: Compression with implicit neural representations," *arXiv preprint* arXiv:2103.03123, 2021.
- [18] E. Dupont, H. Loya, M. Alizadeh, A. Goliński, Y. W. Teh, and A. Doucet, "Coin++: Neural compression across modalities," *arXiv* preprint arXiv:2201.12904, 2022.

- [19] Y. Strümpler, J. Postels, R. Yang, L. V. Gool, and F. Tombari, "Implicit neural representations for image compression," in *European Conference* on Computer Vision. Springer, 2022, pp. 74–91.
- [20] B. B. Damodaran, M. Balcilar, F. Galpin, and P. Hellier, "Rqat-inr: Improved implicit neural image compression," in 2023 Data Compression Conference (DCC). IEEE, 2023, pp. 208–217.
- [21] T. Pham, Y. Yang, and S. Mandt, "Autoencoding implicit neural representations for image compression," in *ICML 2023 Workshop Neural Compression: From Information Theory to Applications*, 2023.
- [22] Z. Li, M. Wang, H. Pi, K. Xu, J. Mei, and Y. Liu, "E-nerv: Expedite neural video representation with disentangled spatial-temporal context," in *European Conference on Computer Vision*. Springer, 2022, pp. 267– 284.
- [23] J. C. Lee, D. Rho, J. H. Ko, and E. Park, "Ffnerv: Flow-guided framewise neural representations for videos," in *Proceedings of the 31st ACM International Conference on Multimedia*, 2023, pp. 7859–7870.
- [24] H. Chen, M. Gwilliam, S.-N. Lim, and A. Shrivastava, "Hnerv: A hybrid neural representation for videos," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2023, pp. 10270–10279.
- [25] H. M. Kwan, G. Gao, F. Zhang, A. Gower, and D. Bull, "Hinerv: Video compression with hierarchical encoding based neural representation," *arXiv preprint arXiv:2306.09818*, 2023.
- [26] X. Zhang, R. Yang, D. He, X. Ge, T. Xu, Y. Wang, H. Qin, and J. Zhang, "Boosting neural representations for videos with a conditional decoder," arXiv preprint arXiv:2402.18152, 2024.
- [27] S. R. Maiya, S. Girish, M. Ehrlich, H. Wang, K. S. Lee, P. Poirson, P. Wu, C. Wang, and A. Shrivastava, "Nirvana: Neural implicit representations of videos with adaptive networks and autoregressive patch-wise modeling," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2023, pp. 14378–14387.
- [28] B. He, X. Yang, H. Wang, Z. Wu, H. Chen, S. Huang, Y. Ren, S.-N. Lim, and A. Shrivastava, "Towards scalable neural representation for diverse videos," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2023, pp. 6132–6142.
- [29] L. Tang, X. Zhang, G. Zhang, and X. Ma, "Scene matters: Model-based deep video compression," in *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2023, pp. 12481–12491.
- [30] G. Bjontegaard, "Calculation of average psnr differences between rdcurves," *ITU SG16 Doc. VCEG-M33*, 2001.
- [31] International Telecommunication Union, "Itu." [Online]. Available: http://www.itu.int/
- [32] M. Liou, "Overview of the p× 64 kbit/s video coding standard," Communications of the ACM, vol. 34, no. 4, pp. 59–63, 1991.
- [33] International Telecommunication Union, "Generic coding of moving pictures and associated audio information-part 2: video," Tech. Rep., 1995. [Online]. Available: https://www.itu.int/rec/T-REC-H.262
- [34] J. Ribas-Corbera and S. Lei, "Rate control in dct video coding for lowdelay communications," *IEEE Transactions on circuits and systems for* video technology, vol. 9, no. 1, pp. 172–185, 1999.
- [35] Audio Video Coding Standard Workgroup of China, "Avs workgroup," 2023. [Online]. Available: http://www.avs.org.cn/
- [36] J. Bankoski, P. Wilkins, and Y. Xu, "Technical overview of vp8, an open source video codec for the web," in 2011 IEEE International Conference on Multimedia and Expo. IEEE, 2011, pp. 1–6.
- [37] D. Mukherjee, J. Han, J. Bankoski, R. Bultje, A. Grange, J. Koleszar, P. Wilkins, and Y. Xu, "A technical overview of vp9-the latest opensource video codec," in *SMPTE 2013 Annual Technical Conference & Exhibition*. SMPTE, 2013, pp. 1–17.
- [38] J. Han, B. Li, D. Mukherjee, C.-H. Chiang, A. Grange, C. Chen, H. Su, S. Parker, S. Deng, U. Joshi *et al.*, "A technical overview of av1," *arXiv* preprint arXiv:2008.06091, 2020.
- [39] Y. Zhang, Z. Pan, N. Li, X. Wang, G. Jiang, and S. Kwong, "Effective data driven coding unit size decision approaches for hevc intra coding," *IEEE Transactions on Circuits and Systems for Video Technology*, vol. 28, no. 11, pp. 3208–3222, 2017.
- [40] N. Yan, D. Liu, H. Li, and F. Wu, "A convolutional neural network approach for half-pel interpolation in video coding," in 2017 IEEE international symposium on circuits and systems (ISCAS). IEEE, 2017, pp. 1–4.
- [41] N. Yan, D. Liu, H. Li, B. Li, L. Li, and F. Wu, "Convolutional neural network-based fractional-pixel motion compensation," *IEEE Transactions on Circuits and Systems for Video Technology*, vol. 29, no. 3, pp. 840–853, 2018.
- [42] R. Song, D. Liu, H. Li, and F. Wu, "Neural network-based arithmetic coding of intra prediction modes in hevc," in 2017 IEEE Visual Communications and Image Processing (VCIP). IEEE, 2017, pp. 1–4.

- [43] C. Ma, D. Liu, X. Peng, and F. Wu, "Convolutional neural networkbased arithmetic coding of dc coefficients for hevc intra coding," in 2018 25th IEEE International Conference on Image Processing (ICIP). IEEE, 2018, pp. 1772–1776.
- [44] S. Wang, Y. Zhao, H. Gao, M. Ye, and S. Li, "End-to-end video compression for surveillance and conference videos," *Multimedia Tools* and Applications, vol. 81, no. 29, pp. 42713–42730, 2022.
- [45] J. Chen, M. Wang, P. Zhang, S. Wang, and S. Wang, "Sparse-to-dense: High efficiency rate control for end-to-end scale-adaptive video coding," *IEEE Transactions on Circuits and Systems for Video Technology*, vol. 34, no. 5, pp. 4027–4039, 2023.
- [46] J. Li, B. Li, and Y. Lu, "Neural video compression with feature modulation," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2024, pp. 26099–26108.
- [47] W. Liu, W. Gao, G. Li, S. Ma, T. Zhao, and H. Yuan, "Enlarged motionaware and frequency-aware network for compressed video artifact reduction," *IEEE Transactions on Circuits and Systems for Video Technology*, 2024.
- [48] J. J. Park, P. Florence, J. Straub, R. Newcombe, and S. Lovegrove, "Deepsdf: Learning continuous signed distance functions for shape representation," in *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, 2019, pp. 165–174.
- [49] Z. Song, W. Duan, Y. Zhang, S. Wang, S. Ma, and W. Gao, "Spc-nerf: spatial predictive compression for voxel based radiance field," *arXiv* preprint arXiv:2402.16366, 2024.
- [50] V. Sitzmann, M. Zollhöfer, and G. Wetzstein, "Scene representation networks: Continuous 3d-structure-aware neural scene representations," *Advances in Neural Information Processing Systems*, vol. 32, 2019.
- [51] L. Catania and D. Allegra, "Nif: A fast implicit image compression with bottleneck layers and modulated sinusoidal activations," in *Proceedings* of the 31st ACM International Conference on Multimedia, 2023, pp. 9022–9031.
- [52] C. Gordon, S.-F. Chng, L. MacDonald, and S. Lucey, "On quantizing implicit neural representations," in *Proceedings of the IEEE/CVF Winter Conference on Applications of Computer Vision*, 2023, pp. 341–350.
- [53] J. R. Schwarz, J. Tack, Y. W. Teh, J. Lee, and J. Shin, "Modalityagnostic variational compression of implicit neural representations," arXiv preprint arXiv:2301.09479, 2023.
- [54] T. Ladune, P. Philippe, F. Henry, G. Clare, and T. Leguay, "Coolchic: Coordinate-based low complexity hierarchical image codec," in *Proceedings of the IEEE/CVF International Conference on Computer Vision*, 2023, pp. 13 515–13 522.
- [55] H. Kim, M. Bauer, L. Theis, J. R. Schwarz, and E. Dupont, "C3: High-performance and low-complexity neural compression from a single image or video," *arXiv preprint arXiv:2312.02753*, 2023.
- [56] V. Sitzmann, J. Martel, A. Bergman, D. Lindell, and G. Wetzstein, "Implicit neural representations with periodic activation functions," *Advances in neural information processing systems*, vol. 33, pp. 7462– 7473, 2020.
- [57] Y. Bai, C. Dong, C. Wang, and C. Yuan, "Ps-nerv: Patch-wise stylized neural representations for videos," in 2023 IEEE International Conference on Image Processing (ICIP). IEEE, 2023, pp. 41–45.
- [58] C. Gomes, R. Azevedo, and C. Schroers, "Video compression with entropy-constrained neural representations," in *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, 2023, pp. 18497–18506.
- [59] H. Wang, W. Gan, S. Hu, J. Y. Lin, L. Jin, L. Song, P. Wang, I. Katsavounidis, A. Aaron, and C.-C. J. Kuo, "Mcl-jcv: a jnd-based h. 264/avc video quality assessment dataset," in 2016 IEEE international conference on image processing (ICIP). IEEE, 2016, pp. 1509–1513.