

# WELL-POSEDNESS AND STABILITY OF INFINITE-DIMENSIONAL SYSTEMS UNDER MONOTONE FEEDBACK

ANTHONY HASTIR AND LASSI PAUNONEN

ABSTRACT. We study the well-posedness and stability of an impedance passive infinite-dimensional linear system under nonlinear feedback of the form  $u(t) = \phi(v(t) - y(t))$ , where  $\phi$  is a monotone function. Our first main result introduces conditions guaranteeing the existence of classical and generalised solutions in a situation where the original linear system is well-posed. In the absence of the external input  $v$  we establish the existence of strong and generalised solutions under strictly weaker conditions. Finally, we introduce conditions guaranteeing that the origin is a globally asymptotically stable equilibrium point of the closed-loop system. Motivated by the analysis of partial differential equations with nonlinear boundary conditions, we use our results to investigate the well-posedness and stability of abstract boundary control systems, port-Hamiltonian systems, a Timoshenko beam model, and a two-dimensional boundary controlled heat equation.

## 1. INTRODUCTION

In this article we study the well-posedness and stability of abstract infinite-dimensional linear systems under nonlinear output feedback. These topics have been investigated actively in the literature both in the framework of abstract systems [40, 20, 5, 39], as well as in the case of controlled partial differential equations [47, 18]. The situation where the original system is linear and the feedback is nonlinear leads to the class of infinite-dimensional *Lur'e systems* [22, 11, 12]. The existing literature especially demonstrates that several classes of linear models with *passivity* properties lead to well-behaving closed-loop systems under feedback with suitable directional properties. We focus on exactly this case.

More precisely, we consider the existence of solutions and stability of impedance passive well-posed linear systems under monotone output feedback. As our main results we introduce mild conditions under which the closed-loop system has well-defined generalised and classical solutions. Moreover, we introduce conditions for the global asymptotic stability of the equilibrium point at the origin for the closed-loop system. Our results especially generalise the well-posedness results in [11, 14, 3] and the stability results in [40, 5, 8].

To introduce our main results, let  $\Sigma = (\mathbb{T}, \Phi, \Psi, \mathbb{F})$  be a *well-posed linear system* [41, 46] on a Hilbert space  $X$ . The system  $\Sigma$  is called *impedance passive* if its

---

2020 *Mathematics Subject Classification*. 34G20, 47H20, 93B52, 93D20 (47H06, 35B35, 35K05).

*Key words and phrases*. Well-posed system, nonlinear feedback, impedance passive, global asymptotic stability, Lur'e system, nonlinear contraction semigroup, boundary control system, port-Hamiltonian system, heat equation.

input and output spaces are equal, i.e.,  $Y = U$ , and if for every initial state  $x_0$  and input  $u$  its state trajectory  $x$  and output  $y$  satisfy (see Section 2 for details)

$$\|x(t)\|_X^2 - \|x_0\|_X^2 \leq 2\operatorname{Re} \int_0^t \langle u(s), y(s) \rangle_U ds, \quad t \geq 0.$$

For an impedance passive well-posed linear system  $\Sigma$  we consider output feedback of the form  $u(t) = \phi(v(t) - y(t))$ , see Figure 1. Here the function  $\phi$  describes the nonlinearity of the feedback and  $v$  is the new input of the system. Applying this output feedback leads formally to the system of equations

$$(1a) \quad x(t) = \mathbb{T}_t x_0 + \Phi_t \mathbf{P}_t \phi(v - y), \quad t \geq 0,$$

$$(1b) \quad y = \Psi_\infty x_0 + \mathbb{F}_\infty \phi(v - y).$$

However, the existence of the closed-loop state trajectory  $x$  and output  $y$  satisfying (1) depends on the properties of the system  $\Sigma$  and the function  $\phi$ .




FIGURE 1. The closed-loop system resulting from the nonlinear feedback  $u(t) = \phi(v(t) - y(t))$ .

In the case of impedance passive systems the most natural class of feedback nonlinearities  $\phi$  consists of functions which are *monotone* in the sense that  $\operatorname{Re} \langle \phi(u_2) - \phi(u_1), u_2 - u_1 \rangle \geq 0$  for  $u_1, u_2 \in U$ . Our first result utilises the strictly stronger condition (2) to guarantee the existence of solutions to (1). The estimate for the differences of solutions in the claim shows that if  $\kappa = 1$ , then the closed-loop system equipped with the output  $\phi(v - y)$  is *incrementally scattering passive* in the sense of [38]. Moreover, in the absence of the external input the closed-loop system is contractive.

**Theorem 1.1.** *Suppose that  $\Sigma = (\mathbb{T}, \Phi, \Psi, \mathbb{F})$  is an impedance passive well-posed linear system whose transfer function  $P$  satisfies  $P(\lambda) + P(\lambda)^* \geq c_\lambda I$  for some  $\lambda, c_\lambda > 0$ . Moreover, assume that*

$$(2) \quad \operatorname{Re} \langle \phi(u_2) - \phi(u_1), u_2 - u_1 \rangle_U \geq \kappa \|\phi(u_2) - \phi(u_1)\|_U^2, \quad u_1, u_2 \in U$$

for some constant  $\kappa > 0$ . Then for any  $x_0 \in X$  and  $u \in L_{loc}^2(0, \infty; U)$  the equations (1) have a unique solution  $x \in C([0, \infty); X)$  and  $y \in L_{loc}^2(0, \infty; U)$ . Moreover, if  $(x_1, y_1)$  and  $(x_2, y_2)$  are two pairs of solutions of (1) corresponding to the initial states  $x_{01} \in X$  and  $x_{02} \in X$  and the inputs  $v_1 \in L_{loc}^2(0, \infty; U)$  and  $v_2 \in L_{loc}^2(0, \infty; U)$ , respectively, then for all  $t \geq 0$

$$\begin{aligned} & \|x_2(t) - x_1(t)\|_X^2 + \kappa \int_0^t \|\phi(v_2(s) - y_2(s)) - \phi(v_1(s) - y_1(s))\|_U^2 ds \\ & \leq \|x_2(0) - x_1(0)\|_X^2 + \frac{1}{\kappa} \int_0^t \|v_2(s) - v_1(s)\|_U^2 ds. \end{aligned}$$

It should be noted that condition (2) implies that the function  $\phi : U \rightarrow U$  is globally Lipschitz continuous. The full version of the result is presented in Theorem 3.3. Theorem 3.3 also shows that for initial conditions  $x_0 \in X$  and inputs

$v \in H_{\text{loc}}^1(0, \infty; U)$  satisfying a natural compatibility condition the state trajectory  $x$  and output  $y$  of the equation (1) have additional smoothness properties and can be interpreted as classical state trajectory and output of the closed-loop system.

Theorem 1.1 can also be applied in the case  $v \equiv 0$  to guarantee the existence of solutions of the closed-loop system without an external input. However, in this case the existence of solutions can also be obtained under strictly weaker conditions. As our second main result in Theorem 3.9 we will show that the closed-loop system arising from feedback  $u(t) = \phi(-y(t))$  has well-defined strong and generalised solutions provided that  $\phi : U \rightarrow U$  is a continuous monotone function satisfying  $\text{Re} \langle \phi(u_2) - \phi(u_1), u_2 - u_1 \rangle > 0$  whenever  $\phi(u_1) \neq \phi(u_2)$ . This result generalises the well-posedness results in [11, 44, 3]. Our result in Theorem 3.9 is also applicable in the case of systems which are impedance passive but not necessarily well-posed. This situation is especially encountered in the study of multi-dimensional wave equations with collocated boundary inputs and outputs.

In the second main part of the article we introduce conditions guaranteeing the stability of an impedance passive system under the feedback  $u(t) = \phi(-y(t))$ . The state trajectories and outputs of a well-posed linear system  $\Sigma$  can alternatively be described using the associated *system node* [46, Sec. 4]. In this setting our feedback leads formally to a system of equations

$$(3) \quad \begin{bmatrix} \dot{x}(t) \\ y(t) \end{bmatrix} = \begin{bmatrix} A \& B \\ C \& D \end{bmatrix} \begin{bmatrix} x(t) \\ \phi(-y(t)) \end{bmatrix}, \quad t \geq 0.$$

Our third main result below introduces conditions under which the origin is a globally asymptotically stable equilibrium point of (3). The main requirement for the stability of this system is that  $\Sigma$  becomes asymptotically stable under *linear* negative feedback  $u(t) = -y(t)$  and that there exist  $\alpha, \gamma, \delta > 0$  such that

$$(4) \quad \begin{cases} \text{Re} \langle \phi(u), u \rangle \geq \alpha \|u\|^2 & \text{when } \|u\| < \delta, \text{ and} \\ \text{Re} \langle \phi(u), u \rangle \geq \gamma & \text{when } \|u\| \geq \delta. \end{cases}$$

The result also guarantees that for all initial states  $x(0) = x_0 \in X$  the system (3) has a well-defined *generalised solution* in the sense defined in Section 3.2.

**Theorem 1.2.** *Suppose that  $\Sigma$  is an impedance passive well-posed linear system such that  $\text{Ker}(C)$  is dense in  $X$  and  $P(\lambda) + P(\lambda)^* \geq c_\lambda I$  for some  $c_\lambda, \lambda > 0$ . Let  $\phi : U \rightarrow U$  be a locally Lipschitz continuous monotone function such that  $\phi(0) = 0$ ,  $\text{Re} \langle \phi(u_2) - \phi(u_1), u_2 - u_1 \rangle > 0$  whenever  $\phi(u_1) \neq \phi(u_2)$ , and there exist  $\alpha, \gamma, \delta > 0$  such that (4) hold. Assume further that the well-posed linear system  $\Sigma^K = (\mathbb{T}^K, \Phi^K, \Psi^K, \mathbb{F}^K)$  obtained from  $\Sigma$  by negative feedback  $u = -y + v$  is such that the semigroup  $\mathbb{T}^K$  is strongly stable. Then the origin is a globally asymptotically stable equilibrium point of (3), i.e., for every initial state  $x_0 \in X$  the system (3) has a well-defined generalised solution  $x \in C([0, \infty); X)$  and  $\|x(t)\| \rightarrow 0$  as  $t \rightarrow \infty$ .*

This result is presented in Theorem 4.4. In Theorem 4.3 we also introduce a result which can be used to study the convergence of individual orbits of the closed-loop system. Theorem 4.3 can also be combined with well-posedness results from the literature, e.g. [46, Thm. 7.2], to study stability under feedback  $u(t) = \phi(-y(t))$ , where  $\phi$  is not a monotone function.

In the final two sections we study partial differential equations with nonlinear boundary conditions. We first present versions of our main results for the class of abstract boundary control systems [33, 23] in Section 5. Subsequently, in Section 6

we employ our results in establishing the well-posedness and stability of the class of infinite-dimensional port-Hamiltonian systems [17], a Timoshenko beam model, and a two-dimensional heat equation with nonlinear boundary feedback.

Both the well-posedness and stability of infinite-dimensional systems with nonlinearities have been studied actively in the literature, and these two aspects are often considered together. Earlier studies have introduced results for abstract classes of systems and for concrete partial differential equations, often focusing either on monotone feedback for systems with collocated inputs, or on nonlinear dampings. The well-posedness and stability under nonlinear feedback of abstract linear systems with collocated inputs and outputs have been studied especially in [40, 1, 2, 8, 24, 25, 16, 19, 6] in the case of bounded input operators, and in [36, 20, 5, 3, 12, 35] for systems with unbounded input operators. Some studies also focus on well-posedness and stability of infinite-dimensional Lur'e systems with either monotone or non-monotone nonlinear feedbacks [22, 10, 11]. In addition, the stability of wave equations with nonlinear boundary dampings has been studied separately, for instance, in [13, 47, 18, 48]. The well-posedness of infinite-dimensional linear and nonlinear systems under nonlinear feedback have been studied especially in [46, 28, 14, 38]. In particular, in [38, 37, 39] the authors introduced the class of *well-posed nonlinear systems* and studied passivity properties in this framework.

The closest existing results related to our stability results have in our view been presented in [20, 5, 8]. In particular, [20] study a large class of abstract systems with nonlinear boundary damping and introduce conditions for stability based on a comparison with the stability properties of a linear semigroup. In [5] the authors present conditions for the well-posedness and asymptotic stability of abstract systems with possibly unbounded collocated input and output operators and a large class of monotone nonlinear feedbacks. In our stability results the class of systems is allowed to be slightly larger than in [5]. Our Theorem 4.4 directly generalises the stability results in [5, Cor. 3.11] and [8, Thm. 2.2] which were stated for systems with collocated input and output operators and semigroup generators with compact resolvent. Our results on well-posedness differ from many of the existing results due to the fact that Theorem 1.1 focuses on the situation where the external input acts *through* the nonlinearity. Very recently during the preparation of this manuscript, the well-posedness of well-posed *nonlinear* systems under this same kind of feedback was investigated in [26]. This reference establishes the existence of generalised solutions of the closed-loop system under the same condition (2) as in Theorem 1.1. In addition, the approaches taken in this article and the reference [26] are both based on the analysis of an associated Lax–Phillips semigroup.

The paper is organized as follows. In Section 2 we review the definitions of well-posed linear systems and system nodes. In Section 3 we present our results on well-posedness under nonlinear feedback. Our results on strong stabilization by nonlinear output feedback are presented in Section 4. In Section 5 we present versions of our results for the class of abstract boundary control systems. In Section 6 we employ our results in analysing the well-posedness and stability of partial differential equations with nonlinear boundary conditions, namely, infinite-dimensional port-Hamiltonian systems, a Timoshenko beam model, and a two-dimensional heat equation.

**Acknowledgments.** This research was supported by the Research Council of Finland grant 349002 and the German Research Foundation (DFG) grant HA 10262/2-1. The authors would like to thank Nicolas Vanspranghe for his helpful advice on nonlinear semigroups. They also thank Hilla Paunonen for her help on the proof of Lemma 3.12.

**Notation.** If  $X$  and  $Y$  are Banach spaces and  $A : D(A) \subset X \rightarrow Y$  is a linear operator we denote by  $D(A)$ ,  $\text{Ker}(A)$  and  $\text{Ran}(A)$  the domain, kernel, and range of  $A$ , respectively. The space of bounded linear operators from  $X$  to  $Y$  is denoted by  $\mathcal{L}(X, Y)$  and we write  $\mathcal{L}(X)$  for  $\mathcal{L}(X, X)$ . If  $A : X \rightarrow X$ , then  $\sigma(A)$  and  $\rho(A)$  denote the spectrum and the resolvent set of  $A$ , respectively. The inner product on a Hilbert space is denoted by  $\langle \cdot, \cdot \rangle$  and all our Hilbert spaces are assumed to be complex. For  $T \in \mathcal{L}(X)$  on a Hilbert space  $X$  we define  $\text{Re} T = \frac{1}{2}(T + T^*)$ . For  $\tau > 0$  and  $u : [0, \infty) \rightarrow U$  we define  $\mathbf{P}_\tau u : [0, \tau] \rightarrow U$  as the truncation of the function  $u$  to the interval  $[0, \tau]$ . We denote  $\mathbb{C}_+ = \{\lambda \in \mathbb{C} \mid \text{Re } \lambda > 0\}$ .

## 2. PRELIMINARIES

Let  $U, X$  and  $Y$  be (complex) Hilbert spaces. Throughout the paper we consider a well-posed linear system  $\Sigma = (\Sigma_t)_{t \geq 0} = (\mathbb{T}_t, \Phi_t, \Psi_t, \mathbb{F}_t)_{t \geq 0}$  defined in the sense of [46, Def. 3.1] with input space  $U$ , state space  $X$ , and output space  $Y$ . We define the *mild state trajectory*  $x \in C([0, \infty); X)$  and *mild output*  $y \in L^2_{\text{loc}}(0, \infty; Y)$  corresponding to the initial state  $x_0 \in X$  and the input  $u \in L^2_{\text{loc}}(0, \infty; U)$  so that

$$(5a) \quad x(t) = \mathbb{T}_t x_0 + \Phi_t \mathbf{P}_t u,$$

$$(5b) \quad \mathbf{P}_t y = \Psi_t x_0 + \mathbb{F}_t \mathbf{P}_t u,$$

for all  $t \geq 0$ . We denote the *extended output map* and *extended input-output map* [46, Sec. 3] of  $\Sigma$  by  $\Psi_\infty : X \rightarrow L^2_{\text{loc}}(0, \infty; Y)$  and  $\mathbb{F}_\infty : L^2_{\text{loc}}(0, \infty; U) \rightarrow L^2_{\text{loc}}(0, \infty; Y)$ , respectively. Using these operators the output  $y$  corresponding to the initial state  $x_0$  and input  $u$  can be equivalently expressed as  $y = \Psi_\infty x_0 + \mathbb{F}_\infty u$ . We especially study *impedance passive* well-posed linear systems which are defined in the following way.

**Definition 2.1.** A well-posed system  $\Sigma$  is called *impedance passive* if  $Y = U$  and if every mild state trajectory  $x$  and mild output  $y$  corresponding to an initial state  $x_0 \in X$  and an input  $u \in L^2_{\text{loc}}(0, \infty; U)$  satisfy

$$\|x(t)\|_X^2 - \|x_0\|_X^2 \leq 2\text{Re} \int_0^t \langle u(s), y(s) \rangle_U ds, \quad t \geq 0.$$

The following theorem shows that if  $\Sigma$  is an impedance passive well-posed linear system we can apply *negative output feedback* of the form  $u(t) = -y(t) + v(t)$ , and the resulting system with input  $v$ , state  $x$ , and output  $y$  is again an impedance passive well-posed linear system.

**Theorem 2.2.** *Let  $\Sigma = (\mathbb{T}, \Phi, \Psi, \mathbb{F})$  be an impedance passive well-posed linear system. There exists a unique well-posed linear system  $\Sigma^K = (\mathbb{T}^K, \Phi^K, \Psi^K, \mathbb{F}^K)$  which satisfies*

$$\begin{bmatrix} \mathbb{T}_t^K & \Phi_t^K \\ \Psi_t^K & \mathbb{F}_t^K \end{bmatrix} - \begin{bmatrix} \mathbb{T}_t & \Phi_t \\ \Psi_t & \mathbb{F}_t \end{bmatrix} = \begin{bmatrix} \mathbb{T}_t & \Phi_t \\ \Psi_t & \mathbb{F}_t \end{bmatrix} \begin{bmatrix} 0 & 0 \\ 0 & -I \end{bmatrix} \begin{bmatrix} \mathbb{T}_t^K & \Phi_t^K \\ \Psi_t^K & \mathbb{F}_t^K \end{bmatrix}, \quad t \geq 0.$$

The system  $\Sigma^K$  is impedance passive and the norms

$$\left\| \begin{bmatrix} \mathbb{T}_t^K & \Phi_t^K \\ \Psi_t^K & \mathbb{F}_t^K \end{bmatrix} \right\|_{\mathcal{L}(X \times L^2(0,t;U), X \times L^2(0,t;Y))}$$

are uniformly bounded with respect to  $t \geq 0$ . In particular,  $\Psi_\infty x_0 \in L^2(0, \infty; Y)$  and  $\mathbb{F}_\infty u \in L^2(0, \infty; Y)$  for all  $x_0 \in X$  and  $u \in L^2(0, \infty; U)$ .

*Proof.* See [43, Cor. 6.1] and [46, Prop. 5.15].  $\square$

Recall that a strongly continuous semigroup  $\mathbb{T}$  on  $X$  is called *strongly stable* if  $\|\mathbb{T}_t x_0\| \rightarrow 0$  as  $t \rightarrow \infty$  for all  $x_0 \in X$ . In our stability analysis in Section 4 we will utilise the following result concerning well-posed systems with strongly stable semigroups from [41, Lem. 8.1.2(iii)] (see also [29, Lem. 12]).

**Lemma 2.3** ([41, Lem. 8.1.2(iii)]). *Let  $\Sigma = (\mathbb{T}, \Phi, \Psi, \mathbb{F})$  be a well-posed linear system on the Hilbert spaces  $(U, X, Y)$ . Assume that the semigroup  $\mathbb{T}$  is strongly stable and that there exists  $M > 0$  such that  $\|\Phi_t\| \leq M$  for all  $t \geq 0$ . Then for every  $u \in L^2(0, \infty; U)$  we have  $\|\Phi_t \mathbf{P}_t u\|_X \rightarrow 0$  as  $t \rightarrow \infty$ .*

In the following we recall the concept of a *system node* which is closely related to well-posed linear systems. For a generator  $A$  of a strongly continuous semigroup we denote by  $X_{-1}$  the completion of the space  $(X, \|(\lambda_0 - A)^{-1} \cdot\|_X)$  where  $\lambda_0 \in \rho(A)$  is fixed. It is well-known that  $A : D(A) \subset X \rightarrow X$  extends to an operator in  $\mathcal{L}(X, X_{-1})$  [41, Sec. 3.6], and we will also denote this extension by  $A$ .

**Definition 2.4** ([41, Def. 4.7.2]). Let  $X, U,$  and  $Y$  be Hilbert spaces. A closed operator

$$S := \begin{bmatrix} A \& B \\ C \& D \end{bmatrix} : D(S) \subset X \times U \rightarrow X \times Y$$

is called a *system node* on the spaces  $(U, X, Y)$  if it has the following properties.

- The operator  $A : D(A) \subset X \rightarrow X$  defined by  $Ax = A \& B \begin{bmatrix} x \\ 0 \end{bmatrix}$  for  $x \in D(A) = \{x \in X \mid (x, 0)^\top \in D(S)\}$  generates a strongly continuous semigroup on  $X$ .
- The operator  $A \& B$  (with domain  $D(S)$ ) can be extended to an operator  $[A, B] \in \mathcal{L}(X \times U, X_{-1})$ .
- $D(S) = \{(x, u)^\top \in X \times U \mid Ax + Bu \in X\}$ .

Every well-posed linear system  $\Sigma = (\mathbb{T}, \Phi, \Psi, \mathbb{F})$  is associated with a unique system node  $S$  [46, Sec. 4]. In particular, if  $x_0 \in X$  and  $u \in H_{\text{loc}}^1(0, \infty; U)$  are such that  $(x_0, u(0))^\top \in D(S)$ , then the mild state trajectory  $x$  and output  $y$  of  $\Sigma$  defined by (5) satisfy  $x \in C^1([0, \infty); X)$ ,  $x(0) = x_0$  and  $y \in H_{\text{loc}}^1(0, \infty; Y)$  and

$$(6) \quad \begin{bmatrix} \dot{x}(t) \\ y(t) \end{bmatrix} = S \begin{bmatrix} x(t) \\ u(t) \end{bmatrix}, \quad t \geq 0.$$

Motivated by this, a system node  $S$  is called *well-posed* if it is the system node of some well-posed linear system  $\Sigma$ .

We note that the conditions in Definition 2.4 imply that  $C \& D \in \mathcal{L}(D(S), Y)$ . The *transfer function*  $P : \rho(A) \rightarrow \mathcal{L}(U, Y)$  of a system node  $S$  on  $(U, X, Y)$  is defined by

$$P(\lambda)u = C \& D \begin{bmatrix} (\lambda - A)^{-1} B u \\ u \end{bmatrix}, \quad u \in U, \lambda \in \rho(A).$$

In addition, the *output operator*  $C \in \mathcal{L}(D(A), Y)$  of  $S$  is defined by  $Cx = C\&D \begin{bmatrix} x \\ 0 \end{bmatrix}$  for all  $x \in D(A)$ . Finally, we define the *impedance passivity* of a system node. In the literature, it is more customary to use a definition based on the solutions of the equation (6), but the definitions are equivalent by [43, Thm. 4.2]. Due to this same result, a well-posed system node  $S$  is impedance passive if and only if its associated well-posed linear system  $\Sigma$  is impedance passive.

**Definition 2.5.** A system node  $S$  on  $(U, X, Y)$  is *impedance passive* if  $Y = U$  and

$$\operatorname{Re} \left\langle A\&B \begin{bmatrix} x_0 \\ u_0 \end{bmatrix}, x_0 \right\rangle_X \leq \operatorname{Re} \left\langle C\&D \begin{bmatrix} x_0 \\ u_0 \end{bmatrix}, u_0 \right\rangle_U$$

for all  $(x_0, u_0)^\top \in D(S)$ .

It follows from Definition 2.5 that the transfer function of an impedance passive system node satisfies  $\operatorname{Re} P(\lambda) \geq 0$  for all  $\lambda \in \mathbb{C}_+$ . In addition, the transfer function of an impedance passive well-posed system node  $S$  coincides with the transfer function of the associated well-posed linear system  $\Sigma$  on  $\mathbb{C}_+$ .

### 3. WELL-POSEDNESS UNDER NONLINEAR FEEDBACK

In this section we study the existence of state trajectories and outputs of an impedance passive linear system under a nonlinear feedback. We separately consider situations where the closed-loop system has an input and an output (in Section 3.1), and where the input of the closed-loop system is set to zero (in Section 3.2). In the latter case we prove the existence of solutions under weaker conditions.

**3.1. Well-Posedness With External Inputs.** In this section we study the existence of solutions of the closed-loop system

$$(7) \quad \begin{bmatrix} \dot{x}(t) \\ y(t) \end{bmatrix} = \begin{bmatrix} A\&B \\ C\&D \end{bmatrix} \begin{bmatrix} x(t) \\ \phi(u(t) - y(t)) \end{bmatrix}, \quad t \geq 0,$$

where  $\phi : U \rightarrow U$  is a globally Lipschitz continuous function and

$$(8) \quad S = \begin{bmatrix} A\&B \\ C\&D \end{bmatrix}, \quad D(S) = \{(x, u)^\top \in X \times U \mid Ax + Bu \in X\}$$

is an impedance passive system node on the Hilbert spaces  $(U, X, U)$ . Before stating our main result we define the concepts of classical and generalised solutions of the system (7), cf. [46, Def. 4.2], [39, Def. 5.1].

**Definition 3.1.** Let  $S$  be the system node (8) on  $(U, X, U)$ . A triple  $(x, u, y)$  is called a *classical solution* of (7) on  $[0, \infty)$  if

- $x \in C^1([0, \infty); X)$ ,  $u \in C([0, \infty); U)$ , and  $y \in C([0, \infty); U)$ ;
- $\begin{bmatrix} x(t) \\ \phi(u(t) - y(t)) \end{bmatrix} \in D(S)$  for all  $t \geq 0$ ;
- (7) holds for every  $t \geq 0$ .

A triple  $(x, u, y)$  is called a *generalised solution* of (7) on  $[0, \infty)$  if

- $x \in C([0, \infty); X)$ ,  $u \in L^2_{\text{loc}}(0, \infty; U)$ , and  $y \in L^2_{\text{loc}}(0, \infty; U)$ ;
- there exists a sequence  $(x^k, u^k, y^k)$  of classical solutions of (7) on  $[0, \infty)$  such that for every  $\tau > 0$  we have  $(\mathbf{P}_\tau x^k, \mathbf{P}_\tau u^k, \mathbf{P}_\tau y^k)^\top \rightarrow (\mathbf{P}_\tau x, \mathbf{P}_\tau u, \mathbf{P}_\tau y)^\top$  as  $k \rightarrow \infty$  in  $C([0, \tau]; X) \times L^2(0, \tau; U) \times L^2(0, \tau; U)$ .

We make the following assumption on the nonlinearity  $\phi$ . The condition in particular implies that  $\phi$  is monotone and globally Lipschitz continuous with Lipschitz constant  $1/\kappa$ . Examples of functions satisfying Assumption 3.2 are provided in Example 3.7.

**Assumption 3.2.** *The function  $\phi : U \rightarrow U$  on the Hilbert space  $U$  satisfies*

$$\operatorname{Re} \langle \phi(u_2) - \phi(u_1), u_2 - u_1 \rangle_U \geq \kappa \|\phi(u_2) - \phi(u_1)\|_U^2, \quad u_1, u_2 \in U$$

for some  $\kappa > 0$ .

The following theorem is the main result of this section. It shows that under Assumption 3.2 the closed-loop system (7) resulting from nonlinear feedback has well-defined classical and generalised solutions. The estimate (10) shows that if  $\kappa = 1$ , then the closed-loop system considered with the input  $u$  and the output  $\phi(u - y)$  is *incrementally scattering passive* in the sense of [38]. Moreover, in the absence of an external input the closed-loop system is contractive. In order to study the classical solutions of (7) we define a subset  $D_{\text{comp}}$  of  $X \times U$  by

$$D_{\text{comp}} = \left\{ (x, u)^\top \in X \times U \mid \exists v \in U \text{ s.t. } Ax + B\phi(u - v) \in X, v = C\&D[\phi(u - v)] \right\}.$$

**Theorem 3.3.** *Suppose that  $S$  is an impedance passive well-posed system node on the Hilbert spaces  $(U, X, U)$  and let  $\Sigma = (\mathbb{T}, \Phi, \Psi, \mathbb{F})$  be the associated well-posed linear system. Moreover, suppose that the transfer function  $P$  of  $\Sigma$  satisfies  $\operatorname{Re} P(\lambda) \geq c_\lambda I$  for some  $\lambda, c_\lambda > 0$ , and that  $\phi : U \rightarrow U$  satisfies Assumption 3.2 for some  $\kappa > 0$ . If  $x_0 \in X$  and  $u \in L_{loc}^2(0, \infty; U)$ , then the system (7) has a generalised solution  $(x, u, y)$  satisfying  $x(0) = x_0$ . This solution satisfies  $t \mapsto \phi(u(t) - y(t)) \in L_{loc}^2(0, \infty; U)$  and*

$$(9a) \quad x(t) = \mathbb{T}_t x_0 + \Phi_t \mathbf{P}_t \phi(u - y), \quad t \geq 0,$$

$$(9b) \quad y = \Psi_\infty x_0 + \mathbb{F}_\infty \phi(u - y).$$

If  $x_0 \in X$  and  $u \in H_{loc}^1(0, \infty; U)$  are such that  $(x_0, u(0))^\top \in D_{\text{comp}}$ , then this  $(x, u, y)$  is a classical solution of (7) on  $[0, \infty)$ .

If  $(x_1, u_1, y_1)$  and  $(x_2, u_2, y_2)$  are two generalised solutions of (7), then for all  $t \geq 0$  we have

$$(10a) \quad \|x_2(t) - x_1(t)\|_X^2 + \kappa \int_0^t \|\phi(u_2(s) - y_2(s)) - \phi(u_1(s) - y_1(s))\|_U^2 ds$$

$$(10b) \quad \leq \|x_2(0) - x_1(0)\|_X^2 + \frac{1}{\kappa} \int_0^t \|u_2(s) - u_1(s)\|_U^2 ds.$$

The proof of Theorem 3.3 is presented in Section 3.3.

**Remark 3.4.** Combining the estimate (10) with the formula (9b) shows that for every  $t > 0$  there exists  $M_t > 0$  such that if  $(x_1, u_1, y_1)$  and  $(x_2, u_2, y_2)$  are two generalised solutions of (7), then

$$\begin{aligned} & \|x_2(t) - x_1(t)\|_X^2 + \int_0^t \|y_2(s) - y_1(s)\|_U^2 ds \\ & \leq M_t \|x_2(0) - x_1(0)\|_X^2 + M_t \int_0^t \|u_2(s) - u_1(s)\|_U^2 ds. \end{aligned}$$

This estimate in particular implies that if  $x_1(0) = x_2(0)$  and  $u_1 = u_2$ , then necessarily  $y_1 = y_2$  and  $x_1(t) = x_2(t)$  for  $t \geq 0$ . This means that the generalised “state trajectory”  $x$  and “output”  $y$  of (7) are uniquely determined by  $x(0)$  and  $u$ .

**Remark 3.5.** By [21, Thm. 4.4] the condition that  $\operatorname{Re} P(\lambda) \geq c_\lambda I$  for some  $c_\lambda > 0$  in Theorem 3.3 is satisfied for one  $\lambda > 0$  if and only if it is satisfied for all  $\lambda > 0$  (here  $c_\lambda > 0$  is allowed to depend on  $\lambda > 0$ ). The proofs of Lemma 3.12, Proposition 3.14, and Theorem 3.3 below will demonstrate that this condition in Theorem 3.3 can be replaced with any other assumption which guarantees that for any  $v \in U$  the equation  $z + P(\lambda)\phi(z) = v$  has a unique solution which is determined by  $z = h(v)$ , where  $h : U \rightarrow U$  is a globally Lipschitz continuous function.

**Remark 3.6.** We note that many of the arguments in the proof of Theorem 3.3 remain valid even without the assumption that the system node  $S$  is well-posed. Indeed, the well-posedness of the system node will be used in deducing that if  $(x_0, u(0))^\top \in D_{\text{comp}}$ , then  $x \in C^1([0, \infty); X)$  and that (17c) holds for all  $t \geq 0$ , and in deducing that the system has a well-defined generalised output. In the situation where the system node  $S$  is impedance passive but not necessarily well-posed the arguments in the proof show that for all  $x_0 \in X$  and  $u \in H_{\text{loc}}^1(0, \infty; U)$  satisfying  $(x_0, u(0))^\top \in D_{\text{comp}}$  the system (7) has a *strong solution* in the sense that

- $x \in W_{\text{loc}}^{1, \infty}(0, \infty; X)$ ,  $u \in C([0, \infty); U)$ , and  $y \in C([0, \infty); U)$ ;
- $\begin{bmatrix} x(t) \\ \phi(u(t) - y(t)) \end{bmatrix} \in D(S)$  for all  $t \geq 0$ ;
- (7) holds for almost every  $t \geq 0$ .

The arguments in the proof will also show that any two such strong solutions satisfy the estimate (10). Moreover, if  $x_0 \in X$  and  $u \in L_{\text{loc}}^2(0, \infty; U)$ , then (7) still has a “generalised state trajectory”  $x \in C([0, \infty); X)$  in the sense that there exists a sequence  $(x^k, u^k, y^k)$  of strong solutions of (7) such that for every  $\tau > 0$  we have  $(\mathbf{P}_\tau x^k, \mathbf{P}_\tau u^k)^\top \rightarrow (\mathbf{P}_\tau x, \mathbf{P}_\tau u)^\top$  as  $k \rightarrow \infty$  in  $C([0, \tau]; X) \times L^2(0, \tau; U)$ . Without well-posedness of the system node, the arguments in the proof of Theorem 3.3 do not guarantee the existence of a generalised output, but they show that there exists  $\psi \in L_{\text{loc}}^2(0, \infty; U)$  such that the sequence  $(x^k, u^k, y^k)$  of strong solutions above satisfies  $\mathbf{P}_\tau \phi(u^k - y^k) \rightarrow \mathbf{P}_\tau \psi$  as  $k \rightarrow \infty$  for all  $\tau > 0$ .

**Example 3.7.** Let  $\psi : [0, \infty) \rightarrow [0, \infty)$  be a non-decreasing function which is globally Lipschitz continuous with Lipschitz constant  $L_\psi$  and satisfies  $\psi(0) = 0$ . Then  $\phi : U \rightarrow U$  defined by  $\phi(0) = 0$  and  $\phi(u) = \psi(\|u\|)\|u\|^{-1}u$  for  $u \neq 0$  satisfies Assumption 3.2 with  $\kappa = 1/L_\psi$ . In particular, the *saturation function*  $\phi : \mathbb{C} \rightarrow \mathbb{C}$  defined so that  $\phi(u) = u$  whenever  $|u| < 1$  and  $\phi(u) = u/|u|$  whenever  $|u| \geq 1$  satisfies Assumption 3.2 with  $\kappa = 1$ . Moreover, if  $\phi_1 : U_1 \rightarrow U_1$  and  $\phi_2 : U_2 \rightarrow U_2$  satisfy Assumption 3.2 for some  $\kappa$ , then also  $\phi : U \rightarrow U$  defined by  $\phi(u) = (\phi_1(u_1), \phi_2(u_2))^\top$  for  $u = (u_1, u_2)^\top \in U := U_1 \times U_2$  satisfies Assumption 3.2 with the same  $\kappa$ .

**3.2. Well-Posedness Without External Inputs.** In this section we consider the system

$$(11) \quad \begin{bmatrix} \dot{x}(t) \\ y(t) \end{bmatrix} = S \begin{bmatrix} x(t) \\ \phi(-y(t)) \end{bmatrix}, \quad t \geq 0,$$

where  $S$  is an impedance passive system node. We note that Theorem 3.3 with  $u(t) \equiv 0$  already provides conditions for the existence of generalised and classical

solutions of this system. In this section we show the existence of solutions without well-posedness of  $S$  and under considerably weaker assumptions on  $\phi : U \rightarrow U$ . The system (11) can be formulated as a nonlinear abstract Cauchy problem

$$(12) \quad \dot{x}(t) = A_\phi(x(t)), \quad t \geq 0$$

when we define the operator  $A_\phi : D(A_\phi) \subset X \rightarrow X$  so that

$$D(A_\phi) = \left\{ x \in X \mid \exists v \in U \text{ s.t. } Ax + B\phi(-v) \in X, v = C\&D[\phi(-v)] \right\}$$

$$A_\phi x = Ax + B\phi(-v(x)), \quad x \in D(A_\phi),$$

where  $v(x)$  is the element  $v$  in the definition of  $D(A_\phi)$ .

**Definition 3.8.** Let  $S$  be a system node on the spaces  $(U, X, U)$ .

- The function  $x \in H_{\text{loc}}^1(0, \infty; X)$  is called a *strong solution* of (12) if  $x(t) \in D(A_\phi)$  for all  $t \geq 0$  and if the identity in (12) holds for almost every  $t \geq 0$ .
- The function  $x \in C([0, \infty); X)$  is called a *generalised solution* of (12) on  $[0, \infty)$  if there exists a sequence  $(x^k)_{k \in \mathbb{N}}$  of strong solutions of (12) on  $[0, \infty)$  such that  $\|\mathbf{P}_\tau x^k - \mathbf{P}_\tau x\|_{C([0, \tau]; X)} \rightarrow 0$  as  $k \rightarrow \infty$  for all  $\tau > 0$ .

It follows from the definition that if  $x$  is a strong solution of (12), we can define a corresponding *output* so that  $y(t) = v(x(t))$  (the element ‘ $v$ ’ corresponding to  $x(t) \in D(A_\phi)$ ) for  $t \geq 0$ . Then  $x$  and  $y$  are such that the identity in (11) holds for almost every  $t \geq 0$  (and the second line holds for all  $t \geq 0$ ).

The following result introduces conditions for the existence of strong and generalised solutions of (11). In particular, the proof shows that under the given assumptions  $A_\phi$  is a single-valued  $m$ -dissipative operator. The theorem is related to the well-posedness results in [11, 44, 3].

**Theorem 3.9.** *Let  $S$  be an impedance passive system node whose transfer function satisfies  $\text{Re } P(\lambda) \geq c_\lambda I$  for some  $\lambda, c_\lambda > 0$ , and let  $\phi : U \rightarrow U$  be a continuous monotone function satisfying  $\text{Re} \langle \phi(u_2) - \phi(u_1), u_2 - u_1 \rangle > 0$  whenever  $\phi(u_1) \neq \phi(u_2)$ . If  $x_1$  and  $x_2$  are two generalised solutions of (12), then*

$$(13) \quad \|x_2(t) - x_1(t)\|_X \leq \|x_2(0) - x_1(0)\|_X, \quad t \geq 0.$$

*For every  $x_0 \in \overline{D(A_\phi)}$  the equation (12) has a unique generalised solution  $x$  satisfying  $x(0) = x_0$ . If  $x_0 \in D(A_\phi)$ , then this  $x$  is a strong solution of (12) and its corresponding output  $y$  defined by  $y(t) = v(x(t))$ ,  $t \geq 0$ , is a right-continuous function such that  $y \in L^\infty(0, \infty; U)$  and  $\phi(-y) \in L^\infty(0, \infty; U)$ .*

*If  $S$  is well-posed and its associated well-posed system is  $\Sigma = (\mathbb{T}, \Phi, \Psi, \mathbb{F})$ , then for every  $x_0 \in D(A_\phi)$  the strong solution  $x$  and the corresponding output  $y$  satisfy*

$$(14a) \quad x(t) = \mathbb{T}_t x_0 + \Phi_t \mathbf{P}_t \phi(-y), \quad t \geq 0,$$

$$(14b) \quad y = \Psi_\infty x_0 + \mathbb{F}_\infty \phi(-y).$$

The following lemma lists selected sufficient conditions for  $D(A_\phi)$  to be dense in  $X$ . The proofs of Theorem 3.9 and Lemma 3.10 will be presented in Section 3.3.

**Lemma 3.10.** *Suppose that  $S$  is an impedance passive system node whose transfer function satisfies  $\text{Re } P(\lambda) \geq c_\lambda I$  for some  $\lambda, c_\lambda > 0$  and that  $\phi : U \rightarrow U$  is a continuous monotone function. The set  $D(A_\phi)$  is dense in  $X$  whenever one of the following conditions holds.*

- (a) *The kernel  $\text{Ker}(C)$  is dense in  $X$ .*

- (b)  $\|(\lambda - A)^{-1}B\| \rightarrow 0$  as  $\lambda \rightarrow \infty$  and  $\phi$  is bounded, i.e.,  $\sup_{u \in U} \|\phi(u)\| < \infty$ .
- (c)  $P(\lambda) \rightarrow 0$  as  $\lambda \rightarrow \infty$  and  $\phi$  is globally Lipschitz continuous.
- (d)  $B \in \mathcal{L}(U, X)$ ,  $C$  extends to an operator  $C \in \mathcal{L}(X, U)$ , and  $C \& D = [C, 0]$ .
- (e)  $S$  is well-posed and  $\phi$  satisfies Assumption 3.2 for some  $\kappa > 0$ .
- (f)  $S$  is well-posed with associated well-posed linear system  $\Sigma = (\mathbb{T}, \Phi, \Psi, \mathbb{F})$ ,  $A_\phi$  is single-valued, and for every  $x_0 \in X$  there exist  $x \in C([0, \infty); X)$  and  $y \in L_{loc}^2(0, \infty; U)$  which satisfy (14).

**Remark 3.11.** The proof of Theorem 3.9 will show that the assumption that  $\operatorname{Re} \langle \phi(u_2) - \phi(u_1), u_2 - u_1 \rangle > 0$  whenever  $\phi(u_1) \neq \phi(u_2)$  can be replaced with the assumption that  $A_\phi$  is single-valued or, equivalently, that the element  $v$  in the definition of  $D(A_\phi)$  is unique. This is in particular true if the input operator  $B$  of the system node is *completely unbounded* in the sense that  $\operatorname{Ran}(B) \cap X = \{0\}$ . Indeed, if  $x \in D(A_\phi)$  and if  $v_1, v_2 \in U$  are two elements satisfying the conditions of “ $v$ ” in  $D(A_\phi)$ , then  $X \ni Ax + B\phi(-v_2) - (Ax + B\phi(-v_1)) = B(\phi(-v_2) - \phi(-v_1))$ . This implies that  $\phi(-v_1) = \phi(-v_2)$ , and further that  $v_1 = v_2$ , finally showing that  $A_\phi$  is single-valued.

**3.3. Proofs of the Well-Posedness Results.** In the beginning of the proof of Theorem 3.3 we will show that if  $\phi : U \rightarrow U$  satisfies Assumption 3.2 for some  $\kappa > 0$ , we can reduce our analysis to the case where  $\kappa = 1$  with suitable rescaling. More precisely, if  $\phi$  satisfies Assumption 3.2 for some  $\kappa > 0$ , then the scaled function  $\phi_\kappa := \sqrt{\kappa}\phi(\sqrt{\kappa}\cdot)$  satisfies it with  $\kappa = 1$ . Because of this, in Lemma 3.12 and Proposition 3.14 we may also restrict our attention to this case. More general versions of these two results can be obtained by applying them to the function  $\phi_\kappa$  and the impedance passive system node  $S_\kappa = \begin{bmatrix} 1 & 0 \\ 0 & 1/\sqrt{\kappa} \end{bmatrix} S \begin{bmatrix} 1 & 0 \\ 0 & 1/\sqrt{\kappa} \end{bmatrix}$ .

**Lemma 3.12.** *Let  $U$  be a Hilbert space and  $\phi : U \rightarrow U$ . Then the following hold.*

- (a) *Suppose that  $\phi$  is continuous and monotone and that  $Q \in \mathcal{L}(U)$  satisfies  $\operatorname{Re} Q \geq cI$  for some  $c > 0$ . For all  $u, r \in U$  the equation  $y = r + Q\phi(u - y)$  has a unique solution which is determined by  $y = g(u, r)$ , where  $g : U \times U \rightarrow U$  is a globally Lipschitz continuous function.*
- (b) *The function  $\phi$  satisfies Assumption 3.2 with  $\kappa = 1$  if and only if*

$$2\operatorname{Re} \langle \phi(v_2 - y_2) - \phi(v_1 - y_1), y_2 - y_1 \rangle \leq \|v_2 - v_1\|^2 - \|\phi(v_2 - y_2) - \phi(v_1 - y_1)\|^2$$

for all  $v_1, v_2, y_1, y_2 \in U$ .

*Proof.* To prove part (a), assume that  $\operatorname{Re} Q \geq cI$  for some  $c > 0$ . Defining  $z = u - y$  and  $v = u - r$  the equation  $y = r + Q\phi(u - y)$  becomes  $z + Q\phi(z) = v$ . We have from [30, Lem. A.1(a)] that  $Q$  is invertible and  $\operatorname{Re} Q^{-1} \geq c\|Q\|^{-2}I$ . We can therefore write  $Q^{-1} = S + J$ , where  $S$  is self-adjoint and  $S \geq c\|Q\|^{-2}I$  and  $J^* = -J$ . Then

$$z + Q\phi(z) = v \quad \Leftrightarrow \quad Sz + Jz + \phi(z) = Q^{-1}v.$$

If we denote  $\varphi(z) = Jz + \phi(z)$ , then the monotonicity of  $\phi$  and  $J^* = -J$  imply that  $\varphi$  is monotone as well. As the next step we can note that

$$\begin{aligned} z + Q\phi(z) = v &\quad \Leftrightarrow \quad S^{1/2}z + S^{-1/2}\varphi(S^{-1/2}S^{1/2}z) = S^{-1/2}Q^{-1}v \\ &\quad \Leftrightarrow \quad \tilde{z} + \psi(\tilde{z}) = S^{-1/2}Q^{-1}v, \end{aligned}$$

where we have denoted  $\tilde{z} = S^{1/2}z$  and  $\psi(\tilde{z}) = S^{-1/2}\varphi(S^{-1/2}\tilde{z})$ . Since  $S^{-1/2}$  is self-adjoint, we have  $\operatorname{Re} \langle \psi(z_2) - \psi(z_1), z_2 - z_1 \rangle \geq 0$  for  $z_1, z_2 \in U$ . Thus the continuous function  $-\psi : U \rightarrow U$  defines a (single-valued) maximally dissipative operator and since  $U$  is a Hilbert space, this operator is  $m$ -dissipative by [27, Cor. 2.27]. Because of this,  $\operatorname{Ran}(I + \psi) = U$  and by [27, Cor. 2.10] the equation  $\tilde{z} + \psi(\tilde{z}) = S^{-1/2}Q^{-1}v$  has a unique solution for every  $v \in U$ . Thus  $y = u - z = u - S^{-1/2}(I + \psi)^{-1}(S^{-1/2}Q^{-1}(u - r))$ . We have from [27, Cor. 2.10] that  $(I + \psi)^{-1}$  is a contraction, and thus in particular globally Lipschitz continuous. This further implies that the mapping  $(u, r) \mapsto y$  is globally Lipschitz continuous.

It remains to prove part (b). If we denote  $w = v_2 - v_1$ ,  $u_1 = v_1 - y_1$  and  $u_2 = v_2 - y_2$ , then  $y_2 - y_1 = v_2 - u_2 + u_1 - v_1 = w - u_2 + u_1$ , and we can see that the estimate in (b) is equivalent to the property that

$$\|w\|^2 - 2\operatorname{Re} \langle \phi(u_2) - \phi(u_1), w - u_2 + u_1 \rangle - \|\phi(u_2) - \phi(u_1)\|^2 \geq 0$$

for all  $w, u_1, u_2 \in U$ . Denoting  $\delta = u_2 - u_1$  and  $\Delta = \phi(u_2) - \phi(u_1)$  for brevity, the expression on the left-hand side of the above inequality can be rewritten as

$$\begin{aligned} & \|w\|^2 - 2\operatorname{Re} \langle \phi(u_2) - \phi(u_1), w - u_2 + u_1 \rangle - \|\phi(u_2) - \phi(u_1)\|^2 \\ &= \|w\|^2 - 2\operatorname{Re} \langle \Delta, w \rangle + 2\operatorname{Re} \langle \Delta, \delta \rangle - \|\Delta\|^2 \\ &= \|w - \Delta\|^2 + 2[\operatorname{Re} \langle \Delta, \delta \rangle - \|\Delta\|^2]. \end{aligned}$$

This expression is non-negative for all  $w, u_1, u_2 \in U$  if and only if  $\operatorname{Re} \langle \Delta, \delta \rangle \geq \|\Delta\|^2$  for all  $u_1, u_2 \in U$ , which is exactly the condition in Assumption 3.2.  $\square$

We recall that a possibly nonlinear single-valued operator  $A : D(A) \subset X \rightarrow X$  on a Hilbert space  $X$  is called *dissipative* if  $\operatorname{Re} \langle A(x_2) - A(x_1), x_2 - x_1 \rangle \leq 0$  for all  $x_1, x_2 \in D(A)$  [27, Def. 2.4]. Such a dissipative operator  $A$  is *maximally dissipative* if  $A$  does not have a proper (possibly multi-valued) dissipative extensions [27, Def. 2.5]. Since  $X$  is a Hilbert space, a dissipative operator  $A$  is maximally dissipative if and only if it is  $m$ -dissipative, i.e.,  $\operatorname{Ran}(\lambda - A) = X$  for one/all  $\lambda > 0$  [27, Lem. 2.12–2.13 & Cor. 2.27]. We will now define the generator of a so-called *Lax–Phillips semigroup* associated to our system (7). It is worthwhile to note that in this construction we consider (7) to be equipped with the output  $\phi(u(t) - y(t))$ .

**Definition 3.13.** Let  $S$  be an impedance passive system node on the Hilbert spaces  $(U, X, U)$  and let  $\phi : U \rightarrow U$ . Define  $X_{LP} := L^2(-\infty, 0; U) \times X \times L^2(0, \infty; U)$  and define the operator  $\mathcal{A} : D(\mathcal{A}) \subset X_{LP} \rightarrow X_{LP}$  by

$$\begin{aligned} D(\mathcal{A}) &= \left\{ (y, x, u)^\top \in H^1(-\infty, 0; U) \times X \times H^1(0, \infty; U) \mid \exists v \in U \text{ s.t.} \right. \\ &\quad \left. Ax + B\phi(u(0) - v) \in X, v = C\&D[\phi(u(0) - v)], \text{ and } y(0) = \phi(u(0) - v) \right\} \\ \mathcal{A} \left( \begin{bmatrix} y \\ x \\ u \end{bmatrix} \right) &= \begin{bmatrix} y' \\ Ax + B\phi(u(0) - v(u(0), x)) \\ u' \end{bmatrix}, \quad (y, x, u)^\top \in D(\mathcal{A}), \end{aligned}$$

where  $v(u(0), x)$  is the element  $v$  in the definition of  $D(\mathcal{A})$ .

**Proposition 3.14.** Suppose that  $S$  is an impedance passive system node  $S$  on  $(U, X, U)$  whose transfer function satisfies  $\operatorname{Re} P(\lambda) \geq c_\lambda I$  for some  $\lambda, c_\lambda > 0$  and that the function  $\phi : U \rightarrow U$  satisfies Assumption 3.2 with  $\kappa = 1$ . Then  $\mathcal{A}$  in

*Definition 3.13* is a single-valued, densely defined and  $m$ -dissipative (nonlinear) operator.

*Proof.* We first note that the property  $Ax + B\phi(u(0) - v) \in X$  in the definition of  $D(\mathcal{A})$  implies that  $(x, \phi(u(0) - v))^\top \in D(S) = D(C\&D)$ . We begin by showing that  $D(\mathcal{A})$  is dense in  $X_{LP}$ . To this end, let  $\lambda > 0$  and denote  $R_\lambda = (\lambda - A)^{-1}$ . If we let  $x_0 \in D(A)$  and define  $x = x_0 + R_\lambda B\phi(0)$  and  $v = Cx_0 + P(\lambda)\phi(0)$ , then  $Ax + B\phi(0) = Ax_0 + \lambda R_\lambda B\phi(0) \in X$  and the properties of the system node  $S$  imply that  $C\&D\left[\begin{smallmatrix} x \\ \phi(0) \end{smallmatrix}\right] = Cx_0 + P(\lambda)\phi(0) = v$ . This means that if we define  $D_0 := \{x_0 + R_\lambda B\phi(0) \mid x_0 \in D(A)\}$  and  $D_{LP} := \{(y, x, u)^\top \in H^1(-\infty, 0; U) \times D_0 \times H^1(0, \infty; U) \mid u(0) = C\&D\left[\begin{smallmatrix} x \\ \phi(0) \end{smallmatrix}\right], y(0) = \phi(0)\}$ , then we have  $D_{LP} \subset D(\mathcal{A}) \subset X_{LP}$ . But since  $D_0$  is dense in  $X$ , it is easy to see that  $D_{LP}$  is dense in  $X_{LP}$ . This further implies that  $D(\mathcal{A})$  is dense in  $X_{LP}$ .

We will now show that  $\mathcal{A}$  is a single-valued operator. This is clearly true if the element  $v$  in the definition of  $D(\mathcal{A})$  is unique<sup>1</sup>. Let  $(y, x, u)^\top \in D(\mathcal{A})$  and let  $v_1 \in U$  and  $v_2 \in U$  be two elements such that

$$Ax + B\phi(u(0) - v_k) \in X \text{ and } v_k = C\&D\left[\begin{smallmatrix} x \\ \phi(u(0) - v_k) \end{smallmatrix}\right], \quad k = 1, 2.$$

If we denote  $\phi_1 := \phi(u(0) - v_1)$  and  $\phi_2 := \phi(u(0) - v_2)$  for brevity, then the first equations imply  $X \ni Ax + B\phi_2 - (Ax + B\phi_1) = A0 + B(\phi_2 - \phi_1)$ , and thus  $(0, \phi_2 - \phi_1)^\top \in D(S)$ . Moreover,  $C\&D\left[\begin{smallmatrix} 0 \\ \phi_2 - \phi_1 \end{smallmatrix}\right] = C\&D\left[\begin{smallmatrix} x \\ \phi_2 \end{smallmatrix}\right] - \left[\begin{smallmatrix} x \\ \phi_1 \end{smallmatrix}\right] = v_2 - v_1$ . The impedance passivity of  $S$  and Assumption 3.2 imply that

$$\begin{aligned} 0 &= \operatorname{Re} \langle A\&B\left[\begin{smallmatrix} 0 \\ \phi_2 - \phi_1 \end{smallmatrix}\right], 0 \rangle_X \geq \operatorname{Re} \langle C\&D\left[\begin{smallmatrix} 0 \\ \phi_2 - \phi_1 \end{smallmatrix}\right], \phi_1 - \phi_2 \rangle_U \\ &= \operatorname{Re} \langle v_2 - v_1, \phi_1 - \phi_2 \rangle_U \\ &= \operatorname{Re} \langle u(0) - v_1 - (u(0) - v_2), \phi(u(0) - v_1) - \phi(u(0) - v_2) \rangle_U \\ &\geq \|\phi(u(0) - v_1) - \phi(u(0) - v_2)\|^2. \end{aligned}$$

Thus  $\phi_2 = \phi_1$ , which implies  $v_2 = C\&D\left[\begin{smallmatrix} x \\ \phi_2 \end{smallmatrix}\right] = C\&D\left[\begin{smallmatrix} x \\ \phi_1 \end{smallmatrix}\right] = v_1$ . Thus the element  $v$  in the definition of  $D(\mathcal{A})$  is unique and  $\mathcal{A}$  is single-valued.

To show that  $\mathcal{A}$  is dissipative, let  $(y_1, x_1, u_1)^\top, (y_2, x_2, u_2)^\top \in D(\mathcal{A})$ . Denote  $v_1 := v(u_1(0), x_1)$ ,  $v_2 := v(u_2(0), x_2)$ ,  $\phi_1 := \phi(u_1(0) - v(u_1(0), x_1))$ , and  $\phi_2 := \phi(u_2(0) - v(u_2(0), x_2))$  for brevity. Using the impedance passivity of the system

<sup>1</sup>Lemma 3.12(b) can be used to show that also the converse holds.

node  $S$ , [9, Thm. 5], and Lemma 3.12(b) we can estimate

$$\begin{aligned}
& \operatorname{Re} \left\langle \mathcal{A} \left( \begin{bmatrix} y_2 \\ x_2 \\ u_2 \end{bmatrix} \right) - \mathcal{A} \left( \begin{bmatrix} y_1 \\ x_1 \\ u_1 \end{bmatrix} \right), \begin{bmatrix} y_2 \\ x_2 \\ u_2 \end{bmatrix} - \begin{bmatrix} y_1 \\ x_1 \\ u_1 \end{bmatrix} \right\rangle \\
&= \operatorname{Re} \langle y_2' - y_1', y_2 - y_1 \rangle_{L^2(-\infty, 0; U)} + \operatorname{Re} \langle Ax_2 + B\phi_2 - Ax_1 - B\phi_1, x_2 - x_1 \rangle_X \\
&\quad + \operatorname{Re} \langle u_2' - u_1', u_2 - u_1 \rangle_{L^2(0, \infty; U)} \\
&= \frac{1}{2} \int_{-\infty}^0 \frac{d}{dt} \|y_2(t) - y_1(t)\|_U^2 dt + \operatorname{Re} \langle A(x_2 - x_1) + B(\phi_2 - \phi_1), x_2 - x_1 \rangle_X \\
&\quad + \frac{1}{2} \int_0^{\infty} \frac{d}{dt} \|u_2(t) - u_1(t)\|_U^2 dt \\
&\leq \frac{1}{2} \|y_2(0) - y_1(0)\|^2 + \operatorname{Re} \langle C\&D \begin{bmatrix} x_2 - x_1 \\ \phi_2 - \phi_1 \end{bmatrix}, \phi_2 - \phi_1 \rangle_X - \frac{1}{2} \|u_2(0) - u_1(0)\|_U^2 \\
&= \frac{1}{2} \|\phi(u_2(0) - v_2) - \phi(u_1(0) - v_1)\|_U^2 - \frac{1}{2} \|u_2(0) - u_1(0)\|_U^2 \\
&\quad + \operatorname{Re} \langle v_2 - v_1, \phi(u_2(0) - v_2) - \phi(u_1(0) - v_1) \rangle_U \leq 0.
\end{aligned}$$

This completes the proof that  $\mathcal{A}$  is dissipative.

In the last part of the proof, we will show that  $\mathcal{A}$  is  $m$ -dissipative. By [27, Lem. 2.13] it suffices to show that  $\operatorname{Ran}(\lambda - \mathcal{A}) = X_{LP}$  for some  $\lambda > 0$ . To this end, let  $(y_1, x_1, u_1)^\top \in X_{LP}$  be arbitrary and let  $\lambda > 0$  be such that  $\operatorname{Re} P(\lambda) \geq c_\lambda I$  for some  $c_\lambda > 0$ . If we define  $u : [0, \infty) \rightarrow U$  by  $u(t) = \int_t^\infty e^{\lambda(t-s)} u_1(s) ds$ , then similarly as in [42, Prop. 6.4] we have  $u \in H^1(0, \infty; U)$  and  $\lambda u - u' = u_1$ . In particular, we have  $u(0) = \hat{u}_1(\lambda) \in U$ . The definition of  $\mathcal{A}$  shows that we have  $(y, x, u)^\top \in D(\mathcal{A})$  and  $(\lambda - \mathcal{A}) \begin{bmatrix} y \\ x \\ u \end{bmatrix} = \begin{bmatrix} y_1 \\ x_1 \\ u_1 \end{bmatrix}$  if  $y \in H^1(-\infty, 0; U)$ ,  $x \in X$  and  $v \in U$  are such that

$$(15) \quad \begin{cases} \lambda y - y' = y_1, & \text{on } (-\infty, 0) \\ y(0) = \phi(\hat{u}_1(\lambda) - v) \\ (\lambda - A)x - B\phi(\hat{u}_1(\lambda) - v) = x_1 \\ v = C\&D \begin{bmatrix} x \\ \phi(\hat{u}_1(\lambda) - v) \end{bmatrix}. \end{cases}$$

To solve equations (15) we denote  $R_\lambda := (\lambda - A)^{-1}$  for brevity and note that by Lemma 3.12(a) we can define  $v$  as the (unique) element of  $U$  such that

$$v = CR_\lambda x_1 + P(\lambda)\phi(\hat{u}_1(\lambda) - v).$$

If we define  $x = R_\lambda x_1 + R_\lambda B\phi(\hat{u}_1(\lambda) - v)$ , then  $(\lambda - A)x - B\phi(\hat{u}_1(\lambda) - v) = x_1$  in (15), and a direct computation using the properties of system nodes shows that

$$\begin{aligned}
C\&D \begin{bmatrix} x \\ \phi(\hat{u}_1(\lambda) - v) \end{bmatrix} &= C\&D \begin{bmatrix} R_\lambda x_1 + R_\lambda B\phi(\hat{u}_1(\lambda) - v) \\ \phi(\hat{u}_1(\lambda) - v) \end{bmatrix} \\
&= CR_\lambda x_1 + P(\lambda)\phi(\hat{u}_1(\lambda) - v) = v.
\end{aligned}$$

Finally, we define  $y$  as the solution of the boundary value problem

$$\begin{aligned}
\lambda y(t) - y'(t) &= y_1(t), & t \in (-\infty, 0) \\
y(0) &= \phi(\hat{u}_1(\lambda) - v).
\end{aligned}$$

Since  $y_1 \in L^2(-\infty, 0; U)$ , we have  $y(t) = e^{\lambda t} \phi(\hat{u}_1(\lambda) - v) + \int_t^0 e^{\lambda(t-s)} y_1(s) ds$  for  $t \leq 0$ , and  $y \in H^1(-\infty, 0; U)$  and  $y(0) = \phi(\hat{u}_1(\lambda) - v)$ , as required. Since  $(y_1, x_1, u_1)^\top \in X_{LP}$  was arbitrary, we have shown that  $\operatorname{Ran}(\lambda - \mathcal{A}) = X_{LP}$ , and thus  $\mathcal{A}$  is  $m$ -dissipative.  $\square$

**Remark 3.15.** The proof of Proposition 3.14 shows that the condition for  $\phi$  in Assumption 3.2 is in a certain sense *minimal* for the dissipativity of  $\mathcal{A}$  and, consequently, also for the estimate (10) in Theorem 3.3. Indeed, if  $S$  is *impedance energy preserving*, then  $\operatorname{Re} \langle Ax + Bu, x \rangle = \operatorname{Re} \langle C\&D \begin{bmatrix} x \\ u \end{bmatrix}, u \rangle_U$  for all  $(x, u)^\top \in D(S)$  and Lemma 3.12 and the estimates in the proof of Proposition 3.14(b) imply that  $\mathcal{A}$  is dissipative if and only if  $\phi$  satisfies Assumption 3.2.

We are now in a position to prove Theorem 3.3.

*Proof of Theorem 3.3.* We begin by noting that if we define  $\tilde{u} = \kappa^{-1/2}u$  and  $\tilde{y} = \kappa^{-1/2}y$ , then (7) can be rewritten as

$$\begin{bmatrix} \dot{x}(t) \\ \tilde{y}(t) \end{bmatrix} = S_\kappa \begin{bmatrix} x(t) \\ \phi_\kappa(\tilde{u}(t) - \tilde{y}(t)) \end{bmatrix}, \quad t \geq 0,$$

where  $\phi_\kappa := \sqrt{\kappa}\phi(\sqrt{\kappa}\cdot) : U \rightarrow U$  and where

$$S_\kappa = \begin{bmatrix} 1 & 0 \\ 0 & \kappa^{-1/2} \end{bmatrix} \begin{bmatrix} A\&B \\ C\&D \end{bmatrix} \begin{bmatrix} 1 & 0 \\ 0 & \kappa^{-1/2} \end{bmatrix},$$

$$D(S_\kappa) = \left\{ (x, u)^\top \in X \times U \mid Ax + \kappa^{-1/2}Bu \in X \right\}$$

is an impedance passive system node on the spaces  $(U, X, U)$ . The function  $\phi_\kappa$  satisfies Assumption 3.2 with “ $\kappa = 1$ ”. It is straightforward to check that the claims of the theorem for the system node  $S_\kappa$ , the associated well-posed linear system  $\Sigma_\kappa$ , and  $\phi_\kappa$  with  $\kappa = 1$  immediately imply the original claims for  $S$ ,  $\Sigma$ , and  $\phi$ . Because of this, we can without loss of generality assume that  $\kappa = 1$ .

We next note that it suffices to prove the claim in the situation where  $u \in L^2(0, \infty; U)$  or  $u \in H^1(0, \infty; U)$  instead of  $u \in L^2_{\text{loc}}(0, \infty; U)$  or  $u \in H^1_{\text{loc}}(0, \infty; U)$ , respectively. Indeed, if  $u \in L^2_{\text{loc}}(0, \infty; U)$  (resp.  $u \in H^1_{\text{loc}}(0, \infty; U)$ ), for an arbitrary  $T > 0$  we can define  $u_T \in L^2(0, \infty; U)$  (resp.  $u_T \in H^1(0, \infty; U)$ ) so that  $u$  and  $u_T$  coincide on  $[0, T]$  and  $u_T$  vanishes on  $[T + 1, \infty)$ . Once we prove the claims of Theorem 3.3 for such truncated input functions, we establish the existence of classical or generalised solutions  $(x_T, u_T, y_T)$  satisfying  $x_T(0) = x_0$ . Moreover, by Remark 3.4 the state trajectory  $x_T$  and output  $y_T$  on  $[0, T]$  are uniquely determined by  $x_0$  and  $u_T$  on  $[0, T]$ . Because of this we can define  $x \in C([0, \infty); X)$  and  $y \in L^2_{\text{loc}}(0, \infty; U)$  such that  $x$  coincides with  $x_T$  and  $y$  coincides with  $y_T$  on  $[0, T]$  for every  $T > 0$ . It is straightforward to deduce from Definition 3.1 and the properties of the solutions  $(x_T, u_T, y_T)$  for  $T > 0$  that  $(x, u, y)$  is a generalised solution of (7) whenever  $x_0 \in X$  and  $u \in L^2_{\text{loc}}(0, \infty; U)$  and that it is a classical solution of (7) whenever  $u \in H^1_{\text{loc}}(0, \infty; U)$  and  $(x_0, u(0))^\top \in D_{\text{comp}}$ . Finally, the formulas (9) and the estimate (10) for two solutions follow directly from the corresponding properties of the solutions  $(x_T, u_T, y_T)$  for  $T > 0$ .

Proposition 3.14 shows that  $\mathcal{A}$  is single-valued, densely defined, and  $m$ -dissipative (equivalently, maximally dissipative). We begin by showing the existence of classical solutions of (7). To this end, let  $x_0 \in X$  and  $u \in H^1(0, \infty; U)$  be such that  $(x_0, u(0))^\top \in D_{\text{comp}}$ . We can then choose  $y_0 \in H^1(-\infty, 0; U)$  so that  $(y_0, x_0, u)^\top \in D(\mathcal{A})$ . We have from [27, Thm. 4.20] that  $\mathcal{A}$  is the generator of a nonlinear contraction semigroup  $\mathcal{T}$  on  $X_{LP} = L^2(-\infty, 0; U) \times X \times L^2(0, \infty; U)$ . We define  $x_{e0} = (y_0, x_0, u)^\top$  and  $x_e(t) = \mathcal{T}_t(x_{e0})$  for  $t \geq 0$ . We then have from [27, Thm. 4.10, Cor. 3.7] that  $x_e : [0, \infty) \rightarrow X_{LP}$  is a Lipschitz continuous, right-differentiable, and

almost everywhere differentiable function such that  $x_e(0) = (y_0, x_0, u)^\top$ ,  $x_e(t) \in D(\mathcal{A})$  for all  $t \geq 0$ ,  $t \mapsto \mathcal{A}(x_e(t))$  is right-continuous, and

$$(16) \quad \dot{x}_e(t) = \mathcal{A}(x_e(t)) \quad \text{for a.e. } t \geq 0.$$

Together these properties also imply that  $x_e \in W_{\text{loc}}^{1,\infty}(0, \infty; X_{LP})$ . For every  $t \geq 0$  we can decompose  $x_e(t)$  into parts as  $x_e(t) = (\tilde{y}(t, \cdot), x(t), \tilde{u}(t, \cdot))^\top$ , and we denote by  $y(t) := v(\tilde{u}(t, 0), x(t))$  the element ‘ $v$ ’ in the definition of  $D(\mathcal{A})$  corresponding to  $(\tilde{y}(t, \cdot), x(t), \tilde{u}(t, \cdot))^\top \in D(\mathcal{A})$ . With this notation equation (16) is equivalent to the equations

$$(17a) \quad \frac{\partial \tilde{y}}{\partial t}(t, s) = \frac{\partial \tilde{y}}{\partial s}(t, s)$$

$$(17b) \quad \tilde{y}(t, 0) = \phi(\tilde{u}(t, 0) - y(t))$$

$$(17c) \quad \dot{x}(t) = Ax(t) + B\phi(\tilde{u}(t, 0) - y(t))$$

$$(17d) \quad \frac{\partial \tilde{u}}{\partial t}(t, r) = \frac{\partial \tilde{u}}{\partial r}(t, r)$$

$$(17e) \quad y(t) = C\&D \left[ \begin{array}{c} x(t) \\ \phi(\tilde{u}(t, 0) - y(t)) \end{array} \right]$$

for a.e.  $t \geq 0$ , a.e.  $s \in (-\infty, 0]$ , and a.e.  $r \in [0, \infty)$ . Moreover, equations (17b) and (17e) hold for every  $t \geq 0$ , and we have  $\tilde{u}(t, \cdot) \in H^1(0, \infty; U)$  and  $\tilde{y}(t, \cdot) \in H^1(-\infty, 0; U)$  for all  $t \geq 0$ . The property  $\tilde{u}(0, \cdot) = u \in H^1(0, \infty; U)$  together with the equation (17d) imply, as in [45, Ex. 2.3.7], that  $\tilde{u}(t, r) = u(t+r)$  for all  $t \geq 0$  and  $r \in [0, \infty)$ . In particular, we have  $\tilde{u}(t, 0) = u(t)$  for all  $t \geq 0$ . The properties of  $x_e$  imply that  $x \in W_{\text{loc}}^{1,\infty}(0, \infty; X)$ .

We will now show that  $t \mapsto \phi(u(t) - y(t)) \in H_{\text{loc}}^1(0, \infty; U)$ . We begin by showing that  $t \mapsto \phi(u(t) - y(t))$  is locally square integrable. To this end, let  $\lambda > 0$  be such that  $\text{Re } P(\lambda) \geq c_\lambda I$  for some  $c_\lambda > 0$ . Equation (17c) implies that for a.e.  $t \geq 0$  we have  $\lambda x(t) - \dot{x}(t) = (\lambda - A)x(t) - B\phi(t)$ , and further  $x(t) = R_\lambda(\lambda x(t) - \dot{x}(t)) + R_\lambda B\phi(t)$ , where we have denoted  $R_\lambda := (\lambda - A)^{-1}$  and  $\phi(t) := \phi(u(t) - y(t))$ . Substituting this into (17e) and using  $R_\lambda(\lambda x(t) - \dot{x}(t)) \in D(A)$  we get, for a.e.  $t \geq 0$ ,

$$\begin{aligned} y(t) &= C\&D \left[ \begin{array}{c} x(t) \\ \phi(t) \end{array} \right] = CR_\lambda(\lambda x(t) - \dot{x}(t)) + C\&D \left[ \begin{array}{c} R_\lambda B\phi(t) \\ \phi(t) \end{array} \right] \\ &= CR_\lambda(\lambda x(t) - \dot{x}(t)) + P(\lambda)\phi(u(t) - y(t)). \end{aligned}$$

We have from Lemma 3.12(a) that there exists a globally Lipschitz continuous function  $g : U \times U \rightarrow U$  such that  $y(t) = g(u(t), CR_\lambda(\lambda x(t) - \dot{x}(t)))$  for a.e.  $t \geq 0$ . But since  $u \in H_{\text{loc}}^1(0, \infty; U)$  and  $t \mapsto CR_\lambda(\lambda x(t) - \dot{x}(t)) \in L_{\text{loc}}^\infty(0, \infty; U)$ , we deduce that  $y \in L_{\text{loc}}^2(0, \infty; U)$ , and the global Lipschitz continuity of  $\phi$  also implies  $t \mapsto \phi(u(t) - y(t)) \in L_{\text{loc}}^2(0, \infty; U)$ . Since  $t \mapsto \phi(u(t) - y(t)) \in L_{\text{loc}}^2(0, \infty; U)$ , we have from [45, Ex. 4.2.7] that the unique solution of (17a) for a.e.  $t \geq 0$  and a.e.  $s \leq 0$  satisfies  $\tilde{y}(t, s) = \tilde{y}(t+s, 0)$  for all  $s \in [-t, 0]$ . Equation (17b) for all  $t \geq 0$  therefore implies that for every fixed  $\tau > 0$  we have

$$\phi(u(t) - y(t)) = \phi(\tilde{u}(t, 0) - y(t)) = \tilde{y}(\tau, t - \tau), \quad t \in [0, \tau].$$

But since  $\tilde{y}(\tau, \cdot) \in H^1(-\infty, 0; U)$  and since this identity holds for every  $\tau > 0$ , we can deduce that  $t \mapsto \phi(u(t) - y(t)) \in H_{\text{loc}}^1(0, \infty; U)$ . Combining this property, our knowledge that  $\dot{x} \in L^\infty(0, \infty; X)$ , and the fact that (17c) holds for a.e.  $t \geq 0$  with the results [46, Prop. 4.6 & 4.7] shows that  $x \in C^1([0, \infty); X)$ ,  $y \in H^1(0, \infty; U)$ ,

that (17c) and (17e) in fact hold for all  $t \geq 0$ , and that  $x$  and  $y$  satisfy (9). We therefore have from Definition 3.1 that  $(x, u, y)$  is a classical solution of (7).

We will now show that classical and generalised solutions of (7) satisfy the incremental estimate (10). Let  $(x_1, u_1, y_1)$  and  $(x_2, u_2, y_2)$  be two classical solutions of (7) and denote  $\phi_k(s) = \phi(u_k(s) - y_k(s))$  for  $k = 1, 2$  for brevity. Using the fact that (7) holds for almost every  $t \geq 0$ , the impedance passivity of the system node  $S$ , and Lemma 3.12(b) we have that

$$\begin{aligned} \frac{d}{ds} \|x_2(s) - x_1(s)\|^2 &= 2\operatorname{Re} \left\langle A\&B \begin{bmatrix} x_2(s) - x_1(s) \\ \phi_2(s) - \phi_1(s) \end{bmatrix}, x_2(s) - x_1(s) \right\rangle_X \\ &\leq 2\operatorname{Re} \left\langle C\&D \begin{bmatrix} x_2(s) - x_1(s) \\ \phi_2(s) - \phi_1(s) \end{bmatrix}, \phi_2(s) - \phi_1(s) \right\rangle_U \\ &= 2\operatorname{Re} \langle y_2(s) - y_1(s), \phi_2(s) - \phi_1(s) \rangle_U \\ &\leq \|u_2(s) - u_1(s)\|^2 - \|\phi(u_2(s) - y_2(s)) - \phi(u_1(s) - y_1(s))\|^2 \end{aligned}$$

for almost every  $s \geq 0$ . Rearranging the terms and integrating the above estimate with respect to  $s$  from 0 to  $t$  shows that the classical solutions satisfy the estimate (10). Moreover, it is easy to see that this property together with Definition 3.1 and the global Lipschitz continuity of  $\phi$  imply that also all generalised solutions (as limits of classical solutions) satisfy (10).

Now let  $x_0 \in X$  and  $u \in L^2(0, \infty; U)$ . We will show that (7) has a generalised solution  $(x, u, y)$  satisfying  $x(0) = x_0$ . Let  $\tau > 0$  be arbitrary and define  $y_0 = 0 \in L^2(-\infty, 0; U)$  and  $x_{e0} = (y_0, x_0, u)^\top \in X_{LP}$ . We define  $x_e(t) = \mathcal{T}_t(x_{e0})$ ,  $t \geq 0$ , where  $\mathcal{T}$  is again the nonlinear contraction semigroup generated by  $\mathcal{A}$ . Then  $x_e \in C([0, \infty); X_{LP})$ ,  $x_e(0) = x_{e0}$  and  $x_e(t)$  has the structure  $x_e(t) = (\tilde{y}(t, \cdot), x(t), \tilde{u}(t, \cdot))^\top \in X_{LP}$  for all  $t \geq 0$ . Since  $D(\mathcal{A})$  is dense in  $X_{LP}$  by Proposition 3.14, there exists a sequence  $(x_{e0}^k)_{k \in \mathbb{N}} \subset D(\mathcal{A})$  such that  $\|x_{e0}^k - x_{e0}\| \rightarrow 0$  as  $k \rightarrow \infty$ . If we define  $x_e^k(t) = \mathcal{T}_t(x_{e0}^k)$  for  $t \geq 0$ , then the contractivity of  $\mathcal{T}$  implies

$$(18) \quad \sup_{t \in [0, \tau]} \|x_e(t) - x_e^k(t)\|_{X_{LP}} \leq \|x_{e0} - x_{e0}^k\|_{X_{LP}} \rightarrow 0, \quad k \rightarrow \infty.$$

Similarly as above, for every  $k \in \mathbb{N}$  the element  $x_e^k = (\tilde{y}^k, x^k, \tilde{u}^k)^\top$  defines a classical solution  $(x^k, u^k, y^k)$  of (7). Moreover, these classical solutions satisfy the estimate (10). The property that  $x_e^k(0) \rightarrow x_e(0)$  in  $X_{LP}$  implies that  $\tilde{u}^k(0, \cdot) \rightarrow u$  in  $L^2(0, \infty; U)$ . As above, we have  $\tilde{u}^k(t, r) = u^k(t+r)$  for all  $t \geq 0$  and  $r \geq 0$ , and thus we can deduce that  $\mathbf{P}_\tau u^k \rightarrow \mathbf{P}_\tau u$  in  $L^2(0, \tau; U)$  as  $k \rightarrow \infty$ . The continuity of  $x_e$  implies  $x \in C([0, \infty); X)$  and (18) implies  $\|\mathbf{P}_\tau x^k - \mathbf{P}_\tau x\|_{C([0, \tau]; X)} \rightarrow 0$  as  $k \rightarrow \infty$ .

In the final step of the proof we will show that there exists  $y \in L^2_{\text{loc}}(0, \infty; U)$  such that  $\mathbf{P}_\tau y^k \rightarrow \mathbf{P}_\tau y$  in  $L^2(0, \tau; U)$  as  $k \rightarrow \infty$ . This will establish that  $(x, u, y)$  is a generalised solution of (7). Similarly as above, we can see that  $(x^k, u^k, y^k)$  satisfy

$$(19a) \quad x^k(t) = \mathbb{T}_t x^k(0) + \Phi_t \mathbf{P}_t \phi(u^k - y^k)$$

$$(19b) \quad \mathbf{P}_t y^k = \Psi_t x^k(0) + \mathbb{F}_t \mathbf{P}_t \phi(u^k - y^k).$$

for all  $k \in \mathbb{N}$  and  $t \geq 0$ . Moreover, the estimate (10) implies that for every  $t > 0$

$$\|\mathbf{P}_t \phi(u^k - y^k) - \mathbf{P}_t \phi(u^n - y^n)\|_{L^2(0, t)}^2 \leq \|x^k(0) - x^n(0)\|^2 + \|\mathbf{P}_t u^k - \mathbf{P}_t u^n\|_{L^2(0, t)}^2$$

for all  $k, n \in \mathbb{N}$ . For every  $t > 0$  the sequences  $(x^k(0))_k \subset X$  and  $(\mathbf{P}_t u^k)_k \subset L^2(0, t; U)$  are convergent, and the above estimate implies that  $(\mathbf{P}_t \phi(u^k - y^k))_k \subset$

$L^2(0, t; U)$  is a Cauchy sequence, and therefore has a limit  $\psi_t \in L^2(0, t; U)$ . The above estimate also implies that if  $t_2 > t_1 > 0$  then  $\mathbf{P}_{t_1}\psi_{t_2} = \psi_{t_1}$ . We can therefore define  $\psi \in L^2_{\text{loc}}(0, \infty; U)$  such that  $\mathbf{P}_t\psi = \psi_t$  for every  $t > 0$ , and define  $y \in L^2_{\text{loc}}(0, \infty; U)$  by  $y = \Psi_\infty x_0 + \mathbb{F}_\infty \psi$ . Since  $\Sigma$  is a well-posed system and since  $\mathbf{P}_\tau\phi(u^k - y^k) \rightarrow \psi_\tau$  in  $L^2(0, \tau; U)$  as  $k \rightarrow \infty$ , the identity (19b) with  $t = \tau$  and the definition of  $y$  imply that  $\mathbf{P}_\tau y^k \rightarrow \mathbf{P}_\tau y$  in  $L^2(0, \tau; U)$  as  $k \rightarrow \infty$ . Since  $\tau > 0$  was arbitrary, we have that  $(x, u, y)$  is a generalised solution of (7). Since  $\phi$  is globally Lipschitz, we also have that  $\phi(u - y) \in L^2_{\text{loc}}(0, \infty; U)$  and  $\mathbf{P}_\tau\phi(u^k - y^k) \rightarrow \mathbf{P}_\tau\phi(u - y)$  as  $k \rightarrow \infty$ . The fact that we also have  $\mathbf{P}_\tau\phi(u^k - y^k) \rightarrow \mathbf{P}_\tau\psi_\tau$  and the uniqueness of limits imply that  $\mathbf{P}_\tau\psi_\tau = \mathbf{P}_\tau\phi(u - y)$ . Thus the definition of  $y$  implies that (9b) holds. Finally, the well-posedness of  $\Sigma$  implies that the right-hand side of (19a) converges to  $\mathbb{T}_t x(0) + \Phi_t \mathbf{P}_t \phi(u - y)$  for every  $t > 0$  as  $k \rightarrow \infty$ . Since we also have  $x^k(t) \rightarrow x(t)$  as  $k \rightarrow \infty$  for all  $t > 0$ , the uniqueness of limits implies that (9a) holds.  $\square$

*Proof of Theorem 3.9.* We will first show that  $A_\phi$  is a single-valued  $m$ -dissipative operator. The operator  $A_\phi$  is single-valued if the element ‘ $v$ ’ in the definition of  $D(A_\phi)$  is unique (and these two properties are, in fact, equivalent). For proving the uniqueness of  $v$  we will use our assumption that  $\text{Re} \langle \phi(u_2) - \phi(u_1), u_2 - u_1 \rangle > 0$  whenever  $\phi(u_1) \neq \phi(u_2)$ . Let  $x \in D(A_\phi)$  and let  $v_1 \in U$  and  $v_2 \in U$  be two elements satisfying

$$Ax + B\phi(-v_k) \in X \text{ and } v_k = C\&D \begin{bmatrix} x \\ \phi(-v_k) \end{bmatrix}, \quad k = 1, 2.$$

If we denote  $\phi_1 := \phi(-v_1)$  and  $\phi_2 := \phi(-v_2)$  for brevity, then  $X \ni Ax + B\phi_2 - (Ax + B\phi_1) = A0 + B(\phi_2 - \phi_1)$ , and thus  $(0, \phi_2 - \phi_1)^\top \in D(S)$ . Moreover,  $C\&D \begin{bmatrix} 0 \\ \phi_2 - \phi_1 \end{bmatrix} = C\&D \left( \begin{bmatrix} x \\ \phi_2 \end{bmatrix} - \begin{bmatrix} x \\ \phi_1 \end{bmatrix} \right) = v_2 - v_1$ . The impedance passivity of  $S$  implies that

$$\begin{aligned} 0 &= \text{Re} \langle A\&B \begin{bmatrix} 0 \\ \phi_2 - \phi_1 \end{bmatrix}, 0 \rangle_X \geq \text{Re} \langle C\&D \begin{bmatrix} 0 \\ \phi_2 - \phi_1 \end{bmatrix}, \phi_1 - \phi_2 \rangle_U \\ &= \text{Re} \langle v_2 - v_1, \phi_1 - \phi_2 \rangle_U \geq 0. \end{aligned}$$

Thus  $\text{Re} \langle v_2 - v_1, \phi_1 - \phi_2 \rangle_U = 0$ , which based on our assumption implies that  $\phi(-v_1) = \phi(-v_2)$ , and further that  $v_2 - v_1 = C\&D \begin{bmatrix} 0 \\ \phi_2 - \phi_1 \end{bmatrix} = 0$ . Thus the element  $v$  in the definition of  $D(A_\phi)$  is unique and  $A_\phi$  is single-valued.

To show that  $A_\phi$  is dissipative, let  $x_1, x_2 \in D(A_\phi)$  and let  $v_1, v_2 \in U$  denote the corresponding elements in the definition of  $D(A_\phi)$ . Then the impedance passivity of  $S$  and the monotonicity of  $\phi$  imply that

$$\begin{aligned} \text{Re} \langle A_\phi(x_2) - A_\phi(x_1), x_2 - x_1 \rangle &= \text{Re} \langle Ax_2 + B\phi(-v_2) - (Ax_1 + B\phi(-v_1)), x_2 - x_1 \rangle \\ &= \text{Re} \left\langle A\&B \begin{bmatrix} x_2 - x_1 \\ \phi(-v_2) - \phi(-v_1) \end{bmatrix}, x_2 - x_1 \right\rangle \\ &\leq \text{Re} \left\langle C\&D \begin{bmatrix} x_2 - x_1 \\ \phi(-v_2) - \phi(-v_1) \end{bmatrix}, \phi(-v_2) - \phi(-v_1) \right\rangle \\ &= \text{Re} \langle v_2 - v_1, \phi(-v_2) - \phi(-v_1) \rangle \leq 0. \end{aligned}$$

Thus  $A_\phi$  is dissipative.

We will now show that  $A_\phi$  is  $m$ -dissipative. By [27, Lem. 2.13] it suffices to show that  $\text{Ran}(\lambda - A_\phi) = X$  for some  $\lambda > 0$ . To this end, let  $x_1 \in X$  be arbitrary and let  $\lambda > 0$  be such that  $\text{Re} P(\lambda) \geq c_\lambda I$  for some  $c_\lambda > 0$ . By Lemma 3.12(a) we can

define  $v$  as the (unique) element in  $U$  such that

$$v = CR_\lambda x_1 + P(\lambda)\phi(-v).$$

If we define  $x = R_\lambda x_1 + R_\lambda B\phi(-v)$ , then  $(\lambda - A)x - B\phi(-v) = x_1$ , and a direct computation shows that

$$C\&D \begin{bmatrix} x \\ \phi(-v) \end{bmatrix} = C\&D \begin{bmatrix} R_\lambda x_1 + R_\lambda B\phi(-v) \\ \phi(-v) \end{bmatrix} = CR_\lambda x_1 + P(\lambda)\phi(-v) = v.$$

Thus  $x \in D(A_\phi)$  and  $(\lambda - A_\phi)(x) = x_1$ . Since  $x_1 \in X$  was arbitrary, we conclude that  $A_\phi$  is  $m$ -dissipative.

To verify the estimate (13), let  $x_1, x_2 \in C([0, \infty); U)$  be two strong solutions of (12) on  $[0, \infty)$  with corresponding outputs  $y_1$  and  $y_2$ . If we denote  $\phi_k(t) = \phi(-y_k(t))$ ,  $k = 1, 2$ , for brevity, then the impedance passivity of  $S$  and the monotonicity of  $\phi$  imply that for a.e.  $t \geq 0$

$$\begin{aligned} \frac{1}{2} \frac{d}{dt} \|x_2(t) - x_1(t)\|^2 &= \operatorname{Re} \left\langle A\&B \begin{bmatrix} x_2(t) - x_1(t) \\ \phi_2(t) - \phi_1(t) \end{bmatrix}, x_2(t) - x_1(t) \right\rangle_X \\ &\leq \operatorname{Re} \left\langle C\&D \begin{bmatrix} x_2(t) - x_1(t) \\ \phi_2(t) - \phi_1(t) \end{bmatrix}, \phi_2(t) - \phi_1(t) \right\rangle_U \\ &= \operatorname{Re} \langle y_2(t) - y_1(t), \phi_2(t) - \phi_1(t) \rangle_U \leq 0. \end{aligned}$$

Because of this,  $\|x_2(t) - x_1(t)\| \leq \|x_2(0) - x_1(0)\|$  for all  $t \geq 0$ . It is straightforward to verify that also the generalised solutions of (12) (as limits of strong solutions) satisfy the same estimate. In particular, strong and generalised solutions of (12) are uniquely determined by  $x(0)$ .

We will now study the existence of strong solutions of (12). To this end, let  $x_0 \in D(A_\phi)$ . Since  $A_\phi$  is a single-valued and  $m$ -dissipative (equivalently, maximally dissipative) operator we have from [27, Thm. 4.20] that  $A_\phi$  is the generator of a nonlinear contraction semigroup  $\mathbb{T}^\phi$  on  $\overline{D(A_\phi)}$ , which is a closed and convex subset of  $X$ . We define  $x(t) = \mathbb{T}_t^\phi(x_0)$  for  $t \geq 0$ . We then have from [27, Thm. 4.10, Cor. 3.7] that  $x : [0, \infty) \rightarrow X$  is a locally Lipschitz continuous, right-differentiable, and almost everywhere differentiable function such that  $x(0) = x_0$ ,  $x(t) \in D(A_\phi)$  for all  $t \geq 0$ ,  $t \mapsto A_\phi(x(t))$  is right-continuous, and

$$(20) \quad \dot{x}(t) = A_\phi(x(t)) \quad \text{for a.e. } t \geq 0.$$

Moreover, by contractivity of  $\mathbb{T}^\phi$  and by [27, Cor. 3.7] both  $x$  and  $\dot{x}$  are essentially bounded. Together these properties imply that  $x \in W^{1,\infty}(0, \infty; X)$ , and thus  $x$  is a strong solution of (12). For  $t \geq 0$  we denote by  $y(t) := v(x(t))$  the element ‘ $v$ ’ in the definition of  $D(A_\phi)$  corresponding to the element  $x(t)$ . Equation (20) and the structure of  $A_\phi$  imply that

$$(21a) \quad \dot{x}(t) = Ax(t) + B\phi(-y(t))$$

$$(21b) \quad y(t) = C\&D \begin{bmatrix} x(t) \\ \phi(-y(t)) \end{bmatrix}$$

for a.e.  $t \geq 0$ . Moreover, the second equation also holds for every  $t \geq 0$ .

We will now show that  $y$  is right-continuous and that  $y, \phi(-y) \in L^\infty(0, \infty; U)$ . To this end, let  $\lambda > 0$  be such that  $\operatorname{Re} P(\lambda) \geq c_\lambda I$  for some  $c_\lambda > 0$ . By [27, Cor. 3.7] the function  $x : [0, \infty) \rightarrow X$  is right-differentiable, its right-derivative  $z := D^+x$  is right-continuous and non-increasing on  $[0, \infty)$ , and  $z(t) = Ax(t) + B\phi(-y(t))$  for  $t \geq 0$ . In particular,  $z \in L^\infty(0, \infty; X)$ . For  $t \geq 0$  we therefore have  $\lambda x(t) - z(t) =$

$(\lambda - A)x(t) - B\phi(-y(t))$ , and further  $x(t) = R_\lambda(\lambda x(t) - z(t)) - R_\lambda B\phi(-y(t))$ , where we have denoted  $R_\lambda := (\lambda - A)^{-1}$ . Substituting this into (21b) and using  $R_\lambda(\lambda x(t) - z(t)) \in D(A)$  we get for  $t \geq 0$

$$y(t) = C\&D \begin{bmatrix} x(t) \\ \phi(-y(t)) \end{bmatrix} = CR_\lambda(\lambda x(t) - z(t)) + P(\lambda)\phi(-y(t)).$$

We have from Lemma 3.12(a) that there exists a globally Lipschitz continuous function  $g : U \times U \rightarrow U$  such that  $y(t) = g(0, CR_\lambda(\lambda x(t) - z(t)))$  for  $t \geq 0$ . But since  $t \mapsto CR_\lambda(\lambda x(t) - z(t))$  is right-continuous and essentially bounded, we deduce that also  $y$  is right-continuous and  $y \in L^\infty(0, \infty; U)$ . Finally, since  $\operatorname{Re} P(\lambda) \geq c_\lambda I$ , we have that  $P(\lambda)$  is invertible and  $\phi(-y(t)) = P(\lambda)^{-1}(y(t) - CR_\lambda(\lambda x(t) - z(t)))$  for  $t \geq 0$ . Thus also  $t \mapsto \phi(-y(t))$  is right-continuous and  $t \mapsto \phi(-y(t)) \in L^\infty(0, \infty; U)$ .

Assume for the moment that  $S$  is well-posed and denote the associated well-posed system by  $\Sigma = (\mathbb{T}, \Phi, \Psi, \mathbb{F})$ . We will show that  $x$  and  $y$  satisfy (14). The property  $\phi(-y(\cdot)) \in L^2_{\text{loc}}(0, \infty; U)$ , our knowledge that  $\dot{x} \in L^\infty(0, \infty; X)$ , the fact that (21a) holds for a.e.  $t \geq 0$  together with [46, Prop. 4.7] imply that  $x(t) = \mathbb{T}_t x_0 + \Phi_t \mathbf{P}_t \phi(-y)$  for all  $t \geq 0$ . We will now show that  $y$  satisfies (14b). Denote  $\psi = \phi(-y(\cdot))$ . We saw above that  $y, \psi \in L^\infty(0, \infty; U)$ , and since  $\|Ax(\cdot) + B\psi\| = \|\dot{x}\| \in L^\infty(0, \infty)$ , we have  $(x, \phi(-y))^\top \in L^\infty(0, \infty; D(S))$ . Since  $C\&D \in \mathcal{L}(D(S), U)$ , taking Laplace transforms on both sides of (21a) and (21b) shows that for  $\lambda \in \mathbb{C}_+$  we have  $\hat{x}(\lambda) = (\lambda - A)^{-1}x_0 + (\lambda - A)^{-1}B\hat{\psi}(\lambda)$  and

$$\hat{y}(\lambda) = C\&D \begin{bmatrix} \hat{x}(\lambda) \\ \hat{\psi}(\lambda) \end{bmatrix} = C(\lambda - A)^{-1}x_0 + P(\lambda)\hat{\psi}(\lambda).$$

Together with [46, Prop. 4.7] this implies that the Laplace transform of  $y$  coincides with the Laplace transform of  $\Psi_\infty x_0 + \mathbb{F}_\infty \phi(-y)$  on some open right half plane of  $\mathbb{C}$ . The uniqueness of Laplace transforms implies that  $y = \Psi_\infty x_0 + \mathbb{F}_\infty \phi(-y)$ . This completes the proof that if  $S$  is well-posed, then  $x$  and  $y$  satisfy (14).

To prove the existence of a generalised solution, assume that  $x_0 \in \overline{D(A_\phi)}$ . Then there exists a sequence  $(x_0^k)_{k \in \mathbb{N}} \subset D(A_\phi)$  such that  $\|x_0^k - x_0\| \rightarrow 0$  as  $k \rightarrow \infty$ . If we define  $x(t) = \mathbb{T}_t^\phi(x_0)$  and  $x^k(t) = \mathbb{T}_t^\phi(x_0^k)$  for  $t \geq 0$  and for  $k \in \mathbb{N}$ , then the contractivity of the semigroup  $\mathbb{T}^\phi$  implies that

$$\sup_{t \geq 0} \|x^k(t) - x(t)\| \leq \|x_0^k - x_0\| \rightarrow 0$$

as  $k \rightarrow \infty$ . This implies that  $x$  is a generalised solution of (12).  $\square$

*Proof of Lemma 3.10.* We first note that by [21, Thm. 4.4] we have  $\operatorname{Re} P(\lambda) \geq c_\lambda I$  for some  $c_\lambda > 0$  for one  $\lambda > 0$  if and only if such a  $c_\lambda > 0$  exists for all  $\lambda > 0$ . Because of this, Lemma 3.12(a) implies that for every  $\lambda > 0$  and  $r \in U$  the equation  $v = r + P(\lambda)\phi(-v)$  has a unique solution  $v \in U$  which is determined by  $v = g_\lambda(r)$ , where  $g_\lambda : U \rightarrow U$  is a globally Lipschitz continuous function. Using the properties of  $S$  and similar computations as in the proof of Theorem 3.9 it is straightforward to verify that for any  $\lambda > 0$

$$D(A_\phi) = \{x_0 + (\lambda - A)^{-1}B\phi(-v) \mid x_0 \in D(A), v = g_\lambda(Cx_0)\}.$$

For brevity, we denote  $R_\lambda = (\lambda - A)^{-1}$  for  $\lambda > 0$  throughout the proof.

To prove part (a) it suffices to note that if we let  $\lambda > 0$  and define  $v_0 = g_\lambda(0) \in U$ , then  $v_0 = P(\lambda)\phi(-v_0)$  and the above characterisation of  $D(A_\phi)$  implies that

$\{x_0 + R_\lambda B\phi(-v_0) \mid x_0 \in \text{Ker}(C)\} \subset D(A_\phi) \subset X$ . But since  $\text{Ker}(C)$  is dense in  $X$  and  $R_\lambda B\phi(-v_0) \in X$ , the set  $D(A_\phi)$  must be dense in  $X$ .

In part (b), let  $M > 0$  be such that  $\|\phi(u)\| \leq M$  for all  $u \in U$ . Let  $x \in X$  and  $\varepsilon > 0$  be arbitrary. Since  $\|R_\lambda B\| \rightarrow 0$  as  $\lambda \rightarrow \infty$  by assumption, we can choose  $\lambda > 0$  such that  $\|R_\lambda B\| < \varepsilon/(2M)$ . If we choose  $x_0 \in D(A)$  such that  $\|x_0 - x\| < \varepsilon/2$  and  $v = g_\lambda(Cx_0) \in U$ , then  $x_0 + R_\lambda B\phi(-v) \in D(A_\phi)$  and

$$\|x - x_0 - R_\lambda B\phi(-v)\| < \frac{\varepsilon}{2} + \|R_\lambda B\| \|\phi(-v)\| < \varepsilon.$$

Since  $x \in X$  and  $\varepsilon > 0$  were arbitrary, we have that  $D(A_\phi)$  is dense in  $X$ .

To prove part (c), assume that  $P(\lambda) \rightarrow 0$  as  $\lambda \rightarrow \infty$  and that  $\phi$  is globally Lipschitz continuous with Lipschitz constant  $L_\phi > 0$ . For any  $u \in U$  and  $\lambda > 0$  we have that  $(R_\lambda B u, u)^\top \in D(S)$  and the impedance passivity of  $S$  implies

$$\text{Re} \langle P(\lambda)u, u \rangle = \text{Re} \left\langle C \&D \begin{bmatrix} R_\lambda B u \\ u \end{bmatrix}, u \right\rangle \geq \text{Re} \langle A R_\lambda B u + B u, R_\lambda B u \rangle = \lambda \|R_\lambda B u\|^2.$$

This implies that  $\|R_\lambda B\|^2 \leq \lambda^{-1} \|P(\lambda)\| \rightarrow 0$  as  $\lambda \rightarrow \infty$ . Let  $x \in X$  and  $\varepsilon > 0$  be arbitrary and let  $(\lambda_n)_{n \in \mathbb{N}} \subset (0, \infty)$  be such that  $\lambda_n \rightarrow \infty$  as  $n \rightarrow \infty$ . Choose  $x_0 \in D(A)$  such that  $\|x - x_0\| < \varepsilon/2$  and define  $v_n = g_{\lambda_n}(Cx_0)$  for  $n \in \mathbb{N}$ . Then  $v_n = Cx_0 + P(\lambda_n)\phi(-v_n)$ ,  $n \in \mathbb{N}$ . Since  $P(\lambda_n) \rightarrow 0$  as  $n \rightarrow \infty$ , there exists  $n_0 \in \mathbb{N}$  such that  $\|P(\lambda_n)\| < 1/(2L_\phi)$  for all  $n \geq n_0$ . For all  $n \geq n_0$  we therefore have

$$\|v_n\| \leq \|Cx_0\| + \|P(\lambda_n)\| \|\phi(-v_n)\| \leq \|Cx_0\| + \frac{1}{2L_\phi} L_\phi \|v_n\|,$$

which implies that  $\|v_n\| \leq 2\|Cx_0\|$ , and further that  $\|\phi(-v_n)\| \leq 2L_\phi \|Cx_0\|$ , for all  $n \geq n_0$ . Since  $R_{\lambda_n} B \rightarrow 0$  as  $n \rightarrow \infty$  we can choose  $m \geq n_0$  such that  $\|R_{\lambda_m} B\| < \varepsilon/(4L_\phi \|Cx_0\|)$ . Then  $x_0 + R_{\lambda_m} B\phi(-v_m) \in D(A_\phi)$  and

$$\|x - x_0 - R_{\lambda_m} B\phi(-v_m)\| < \frac{\varepsilon}{2} + \|R_{\lambda_m} B\| \|\phi(-v_m)\| < \frac{\varepsilon}{2} + \frac{\varepsilon}{2} = \varepsilon.$$

Since  $x \in X$  and  $\varepsilon > 0$  were arbitrary, we have that  $D(A_\phi)$  is dense in  $X$ .

To prove part (d), assume that  $B \in \mathcal{L}(U, X)$  and  $C \&D = [C, 0]$  with  $C \in \mathcal{L}(X, U)$ . If  $x \in D(A)$  and if we choose  $v = Cx$ , then  $Ax + B\phi(-v) \in X$  and  $v = C \&D \begin{bmatrix} x \\ \phi(-v) \end{bmatrix} = Cx$ . Thus  $x \in D(A_\phi)$ . Since  $x \in D(A)$  was arbitrary, we have  $D(A) \subset D(A_\phi) \subset X$ , and this implies that  $D(A_\phi)$  is dense in  $X$ .

To prove part (f), we will first show that the maps  $x_0 \mapsto x(t)$ ,  $t \geq 0$ , define a (nonlinear) semigroup  $\mathbb{T}^0$  of contractions so that  $\mathbb{T}_t^0(x_0) = x(t)$ ,  $t \geq 0$ . Let  $x_1, x_2 \in C([0, \infty); X)$  and  $y_1, y_2 \in L_{\text{loc}}^2(0, \infty; U)$  be solutions of (14) corresponding to two initial conditions  $x_{10} \in X$  and  $x_{20} \in X$ . Then

$$\begin{aligned} x_2(t) - x_1(t) &= \mathbb{T}_t(x_{10} - x_{20}) + \Phi_t \mathbf{P}_t(\phi(-y_2) - \phi(-y_1)), \quad t \geq 0, \\ y_2 - y_1 &= \Psi_\infty(x_{20} - x_{10}) + \mathbb{F}_\infty(\phi(-y_2) - \phi(-y_1)). \end{aligned}$$

Denoting  $\phi_k = \phi(-y_k(\cdot))$ ,  $k = 1, 2$ , the impedance passivity of  $\Sigma$  and the monotonicity of  $\phi$  imply that for all  $t \geq 0$

$$\|x_2(t) - x_1(t)\|^2 - \|x_{20} - x_{10}\|^2 \leq 2\text{Re} \int_0^t \langle \phi_2(s) - \phi_1(s), y_2(s) - y_1(s) \rangle ds \leq 0.$$

Thus  $\|x_2(t) - x_1(t)\|^2 \leq \|x_{20} - x_{10}\|^2$  for all  $t \geq 0$ . The properties of  $\Sigma$  therefore imply that the maps  $x_0 \mapsto x(t)$ ,  $t \geq 0$ , indeed define a semigroup  $\mathbb{T}^0$  of contractions on  $X$  in the sense of [27, Def. 3.1]. We have from the proof of Theorem 3.9 and Remark 3.11 that  $A_\phi$  is the infinitesimal generator [27, Def. 3.2] of a semigroup  $\mathbb{T}^\phi$  of

contractions on  $\overline{D(A_\phi)}$ , and that  $\mathbb{T}_t^0(x_0) = \mathbb{T}_t^\phi(x_0)$  for all  $t \geq 0$  and  $x_0 \in D(A_\phi)$ . This further implies that the infinitesimal generator  $A_0$  of  $\mathbb{T}^0$  is a dissipative extension of  $A_\phi$ . But since  $X$  is a Hilbert space,  $A_\phi$  is a maximal dissipative operator [27, Def. 2.5], and thus necessarily  $A_\phi = A_0$ . Finally, we have from [27, Thm. 4.20] that  $D(A_\phi) = D(A_0)$  is dense in  $X$ .

Finally, to prove part (e) we note that Assumption 3.2 in particular implies that  $\operatorname{Re} \langle \phi(u_2) - \phi(u_1), u_2 - u_1 \rangle > 0$  whenever  $\phi(u_1) \neq \phi(u_2)$ . Therefore the argument in the proof of Theorem 3.9 shows that  $A_\phi$  is single-valued and our claim follows from part (f) and Theorem 3.3.  $\square$

#### 4. GLOBAL ASYMPTOTIC STABILITY UNDER NONLINEAR FEEDBACK

In this section we study the global asymptotic stability of the origin of the nonlinear system obtained from an impedance passive well-posed linear system under nonlinear feedback of the form  $u(t) = \phi(-y(t))$ . In this situation the function  $\phi : U \rightarrow U$  is assumed to satisfy the following conditions.

**Assumption 4.1.** *The function  $\phi : U \rightarrow U$  is locally Lipschitz continuous,  $\phi(0) = 0$  and there exists constants  $\alpha, \gamma, \delta > 0$  such that*

- $\operatorname{Re} \langle \phi(u), u \rangle \geq \alpha \|u\|^2$  when  $\|u\| < \delta$ ;
- $\operatorname{Re} \langle \phi(u), u \rangle \geq \gamma$  when  $\|u\| \geq \delta$ .

**Example 4.2.** If  $\psi : [0, \infty) \rightarrow [0, \infty)$  satisfies Assumption 4.1 with  $U = [0, \infty)$  then it is easy to check that also the function  $\phi : U \rightarrow U$  defined by  $\phi(0) = 0$  and  $\phi(u) = \psi(\|u\|)\|u\|^{-1}u$  for  $u \neq 0$  satisfies Assumption 4.1. In particular, the saturation function  $\phi : \mathbb{C} \rightarrow \mathbb{C}$  defined so that  $\phi(u) = u$  whenever  $|u| < 1$  and  $\phi(u) = u/|u|$  whenever  $|u| \geq 1$  satisfies Assumption 4.1. Moreover, if  $\phi_1 : U_1 \rightarrow U_1$  and  $\phi_2 : U_2 \rightarrow U_2$  satisfy Assumption 4.1, then the same is true for  $\phi : U \rightarrow U$  defined by  $\phi(u) = (\phi_1(u_1), \phi_2(u_2))$  for  $u = (u_1, u_2)^\top \in U := U_1 \times U_2$ .

Our first main result establishes the convergence of individual solutions of the nonlinear closed-loop system under the assumption that *linear* feedback of the form  $u = -y + v$  achieves strong stability of the closed-loop semigroup.

**Theorem 4.3.** *Suppose that  $\Sigma = (\mathbb{T}, \Phi, \Psi, \mathbb{F})$  is an impedance passive well-posed linear system and that  $\phi : U \rightarrow U$  satisfies Assumption 4.1. Moreover, assume that the well-posed linear system  $\Sigma^K = (\mathbb{T}^K, \Phi^K, \Psi^K, \mathbb{F}^K)$  obtained from  $\Sigma$  by negative feedback  $u = -y + v$  is such that the semigroup  $\mathbb{T}^K$  is strongly stable. Let  $x_0 \in X$  be such that there exist  $x \in C([0, \infty); X)$  and  $y \in L_{loc}^2(0, \infty; U)$  such that  $\phi(-y) \in L_{loc}^2(0, \infty; U)$  and*

$$(22a) \quad x(t) = \mathbb{T}_t x_0 + \Phi_t \mathbf{P}_t \phi(-y), \quad t \geq 0,$$

$$(22b) \quad y = \Psi_\infty x_0 + \mathbb{F}_\infty \phi(-y).$$

*Then  $\|x(t)\| \rightarrow 0$  as  $t \rightarrow \infty$ , and  $y \in L^2(0, \infty; U)$  and  $\phi(-y) \in L^2(0, \infty; U)$ .*

*In particular, if  $x$  and  $y$  with the above properties exist for every  $x_0 \in X$ , then  $\|x(t)\| \rightarrow 0$  as  $t \rightarrow \infty$  and  $y, \phi(-y) \in L^2(0, \infty; U)$  for every  $x_0 \in X$ .*

*Proof.* Let  $x_0 \in X$  and  $y \in L_{loc}^2(0, \infty; U)$  be such that  $\phi(-y) \in L_{loc}^2(0, \infty; U)$  and assume that (22) hold for all  $t \geq 0$ . We begin by showing that  $y \in L^2(0, \infty; U)$  and  $\phi(-y) \in L^2(0, \infty; U)$ . Since  $\Sigma$  is impedance passive, Definition 2.1 implies that

$$(23) \quad 2\operatorname{Re} \int_0^t \langle \phi(-y(s)), -y(s) \rangle ds \leq \|x_0\|^2 - \|x(t)\|^2 \leq \|x_0\|^2, \quad t \geq 0.$$

Let  $\alpha, \gamma, \delta > 0$  be as in Assumption 4.1. For a fixed representative of the equivalence class  $y \in L^2_{\text{loc}}(0, \infty; U)$ , define  $g = \|y(\cdot)\|$  and define  $\Omega_2 = g^{-1}([0, \delta))$  and  $\Omega_1 = [0, \infty) \setminus \Omega_2$ . Then  $\Omega_1$  and  $\Omega_2$  are measurable and disjoint subsets of  $[0, \infty)$  and

$$\begin{cases} \|y(t)\| \geq \delta, & \text{for a.e. } t \in \Omega_1 \\ \|y(t)\| < \delta, & \text{for a.e. } t \in \Omega_2. \end{cases}$$

Assumption 4.1 and (23) imply that

$$\gamma\mu(\Omega_1) \leq \text{Re} \int_{\Omega_1} \langle \phi(-y(s)), -y(s) \rangle ds \leq \frac{1}{2}\|x_0\|^2.$$

Thus  $\mu(\Omega_1) \leq \frac{1}{2\gamma}\|x_0\|^2$  and in particular  $\Omega_1$  has finite measure. On the other hand, Assumption 4.1 and (23) imply that

$$(24) \quad \alpha \int_{\Omega_2} \|y(s)\|^2 ds \leq \text{Re} \int_{\Omega_2} \langle \phi(-y(s)), -y(s) \rangle ds \leq \frac{1}{2}\|x_0\|^2 < \infty.$$

Since  $y \in L^2_{\text{loc}}(0, \infty; U)$  by assumption, we have  $\|y\|_{L^2(\Omega_1; U)} < \infty$ . Combined with (24) this implies  $y \in L^2(0, \infty; U)$  as claimed. Since  $\phi(-y) \in L^2_{\text{loc}}(0, \infty; U)$  by assumption and  $\mu(\Omega_1) < \infty$ , we have  $\|\phi(-y)\|_{L^2(\Omega_1; U)} < \infty$ . On the other hand, since  $\phi$  is locally Lipschitz continuous and  $\|y(t)\| < \delta$  for a.e.  $t \in \Omega_2$ , there exists  $L_\delta > 0$  such that  $\|\phi(-y(t))\| \leq L_\delta\|y(t)\|$  for a.e.  $t \in \Omega_2$ . Hence

$$\int_{\Omega_2} \|\phi(-y(s))\|^2 ds \leq L_\delta^2 \int_{\Omega_2} \|y(s)\|^2 ds < \infty.$$

Combining the above properties shows that  $\phi(-y) \in L^2(0, \infty; U)$  as claimed.

We have from Theorem 2.2 and [46, Prop. 5.15] that for all  $t \geq 0$

$$\begin{bmatrix} x(t) \\ \mathbf{P}_t y \end{bmatrix} = \begin{bmatrix} \mathbb{T}_t & \Phi_t \\ \Psi_t & \mathbb{F}_t \end{bmatrix} \begin{bmatrix} x_0 \\ \mathbf{P}_t \phi(-y) \end{bmatrix} = \begin{bmatrix} \mathbb{T}_t^K & \Phi_t^K \\ \Psi_t^K & \mathbb{F}_t^K \end{bmatrix} \left( \begin{bmatrix} x_0 \\ \mathbf{P}_t \phi(-y) \end{bmatrix} + \begin{bmatrix} 0 \\ \mathbf{P}_t y \end{bmatrix} \right),$$

which implies  $x(t) = \mathbb{T}_t^K x_0 + \Phi_t^K \mathbf{P}_t(y + \phi(-y))$  for  $t \geq 0$ . The semigroup  $\mathbb{T}^K$  is strongly stable by assumption and thus  $\mathbb{T}_t^K x_0 \rightarrow 0$  as  $t \rightarrow \infty$ . Theorem 2.2 implies that there exists  $M > 0$  such that  $\|\Phi_t^K\| \leq M$  for all  $t \geq 0$ . In the first part of the proof we showed that  $y, \phi(-y) \in L^2(0, \infty; U)$ , and thus we also have  $y + \phi(-y) \in L^2(0, \infty; U)$ . Lemma 2.3 therefore implies that  $\Phi_t^K \mathbf{P}_t(y + \phi(-y)) \rightarrow 0$  as  $t \rightarrow \infty$ . Because of this, we have  $\|x(t)\| \rightarrow 0$  as  $t \rightarrow \infty$ .  $\square$

As the main result of this section we introduce conditions guaranteeing that the origin is a globally asymptotically stable equilibrium point of the system under nonlinear feedback  $u(t) = \phi(-y(t))$ . Here the operator  $A_\phi$  is defined as in Section 3.2. We recall that sufficient conditions for  $D(A_\phi)$  being dense in  $X$  are listed in Lemma 3.10.

**Theorem 4.4.** *Suppose that  $S$  is an impedance passive well-posed system node with associated well-posed system  $\Sigma$ , and assume that its transfer function satisfies  $\text{Re } P(\lambda) \geq c_\lambda I$  for some  $c_\lambda, \lambda > 0$ . Assume further that  $\phi : U \rightarrow U$  satisfies Assumption 4.1, that  $D(A_\phi)$  is dense in  $X$ , and that  $\text{Re} \langle \phi(u_2) - \phi(u_1), u_2 - u_1 \rangle > 0$  whenever  $\phi(u_1) \neq \phi(u_2)$ . Finally, assume that the well-posed linear system  $\Sigma^K = (\mathbb{T}^K, \Phi^K, \Psi^K, \mathbb{F}^K)$  obtained from  $\Sigma$  by negative feedback  $u = -y + v$  is such that*

the semigroup  $\mathbb{T}^K$  is strongly stable. Then the origin is a globally asymptotically stable equilibrium point of the system

$$(25) \quad \dot{x}(t) = A_\phi(x(t)), \quad t \geq 0,$$

that is, for every initial state  $x_0 \in X$  the equation (25) has a generalised solution  $x$  such that  $x(0) = x_0$  and this solution satisfies  $\|x(t)\| \rightarrow 0$  as  $t \rightarrow \infty$ .

*Proof.* Let  $x_0 \in X$ . Since  $D(A_\phi)$  is dense in  $X$ , Theorem 3.9 implies that (25) has a unique generalised solution  $x$  on  $[0, \infty)$  satisfying  $x(0) = x_0$ . To show that  $\|x(t)\| \rightarrow 0$  as  $t \rightarrow \infty$ , let  $\varepsilon > 0$ . We can choose  $z_0 \in D(A_\phi)$  such that  $\|x_0 - z_0\| < \varepsilon/2$ . By Theorem 3.9 there exists a strong solution  $x_\varepsilon$  of (25) on  $[0, \infty)$  and a corresponding output  $y_\varepsilon \in L^2_{\text{loc}}(0, \infty; U)$  such that  $x_\varepsilon(0) = z_0$ ,  $\phi(-y_\varepsilon) \in L^2_{\text{loc}}(0, \infty; U)$ , and

$$\begin{aligned} x_\varepsilon(t) &= \mathbb{T}_t z_0 + \Phi_t \mathbf{P}_t \phi(-y_\varepsilon), & t \geq 0, \\ y_\varepsilon &= \Psi_\infty z_0 + \mathbb{F}_\infty \phi(-y_\varepsilon). \end{aligned}$$

We thus have from Theorem 4.3 that  $\|x_\varepsilon(t)\| \rightarrow 0$  as  $t \rightarrow \infty$ . Because of this, we can choose  $t_0 > 0$  so that  $\|x_\varepsilon(t)\| < \varepsilon/2$  for all  $t \geq t_0$ . We have from Theorem 3.9 that  $x$  and  $x_\varepsilon$  satisfy the estimate (13), and thus for all  $t \geq t_0$  we have

$$\|x(t)\| \leq \|x(t) - x_\varepsilon(t)\| + \|x_\varepsilon(t)\| \leq \|x_0 - z_0\| + \|x_\varepsilon(t)\| < \frac{\varepsilon}{2} + \frac{\varepsilon}{2} = \varepsilon.$$

Since  $\varepsilon > 0$  was arbitrary, we have that  $\|x(t)\| \rightarrow 0$  as  $t \rightarrow \infty$ .  $\square$

## 5. BOUNDARY CONTROL SYSTEMS WITH NONLINEAR FEEDBACK

In this section we investigate abstract boundary control systems [33, 23, 17] of the form

$$(26a) \quad \dot{x}(t) = Lx(t)$$

$$(26b) \quad Gx(t) = u(t)$$

$$(26c) \quad y(t) = Kx(t)$$

for  $t \geq 0$ . If  $X$ ,  $U$ , and  $Y$  are Hilbert spaces, then the triple  $(G, L, K)$  is called a *boundary node* on the spaces  $(U, X, Y)$  if  $L : D(L) \subset X \rightarrow X$ ,  $G \in \mathcal{L}(D(L), U)$ ,  $K \in \mathcal{L}(D(L), Y)$  and the following hold.

- The restriction  $A := L|_{\text{Ker}(G)}$  with domain  $D(A) = \text{Ker}(G)$  generates a strongly continuous semigroup  $\mathbb{T}$  on  $X$ .
- The operator  $G \in \mathcal{L}(D(L), U)$  has a bounded right inverse, i.e., there exists  $G^r \in \mathcal{L}(U, D(L))$  such that  $GG^r = I$ .

This boundary node is *impedance passive* if  $Y = U$  and if

$$\text{Re} \langle Lx, x \rangle_X \leq \text{Re} \langle Gx, Kx \rangle_U, \quad x \in D(L).$$

Moreover, the *transfer function*  $P : \rho(A) \rightarrow \mathcal{L}(U, Y)$  of  $(G, L, K)$  is defined so that  $P(\lambda)u = Kx$ , where  $x \in D(L)$  is the unique solution of the equations  $(\lambda - L)x = 0$  and  $Gx = u$ .

It has been shown in [23] that every boundary node  $(G, L, K)$  gives rise to a system node  $S$  on  $(U, X, Y)$ . More precisely, [23, Thm. 2.3] shows that the operator

$$S = \begin{bmatrix} L \\ K \end{bmatrix} \begin{bmatrix} I \\ G \end{bmatrix}^{-1}, \quad D(S) = \text{Ran} \left( \begin{bmatrix} I \\ G \end{bmatrix} \right)$$

is a system node on  $(U, X, Y)$ . We note that the definition of  $S$  in particular implies that  $(x, u)^\top \in D(S)$  if and only if  $x \in D(L)$  and  $u = Gx$ . If  $(G, L, K)$  is impedance passive, then the associated system node  $S$  is impedance passive as well, since for  $(x, u)^\top \in D(S)$  we then have

$$\operatorname{Re} \left\langle L \begin{bmatrix} I \\ G \end{bmatrix}^{-1} \begin{bmatrix} x \\ u \end{bmatrix}, x \right\rangle = \operatorname{Re} \langle Lx, x \rangle \leq \operatorname{Re} \langle Kx, Gx \rangle = \operatorname{Re} \left\langle K \begin{bmatrix} I \\ G \end{bmatrix}^{-1} \begin{bmatrix} x \\ u \end{bmatrix}, u \right\rangle.$$

In addition, the transfer function of  $(G, L, K)$  coincides with the transfer function of the associated system node.

Because of this connection with system nodes, we can call a boundary node  $(G, L, K)$  (*externally*) *well-posed* if its associated system node  $S$  is well-posed, that is, if  $S$  is a system node of a well-posed linear system  $\Sigma$ . In this case we can also say  $\Sigma$  is the well-posed system associated with  $(G, L, K)$ . If  $x_0 \in D(L)$  and  $u \in C^2([0, \infty); U)$  are such that  $Gx_0 = u(0)$ , then by [23, Lem. 2.6] there exists  $x \in C^1([0, \infty); X) \cap C([0, \infty); D(L))$  and  $y \in C([0, \infty); Y)$  such that  $x(0) = x_0$  and such that (26) hold for all  $t \geq 0$ . The well-posedness of  $(G, L, K)$  is equivalent to the property that there exists  $\tau, M_\tau > 0$  such that all such solutions of (26) satisfy [17, Ch. 13]

$$\|x(\tau)\|_X^2 + \int_0^\tau \|y(t)\|_Y^2 dt \leq M_\tau \left( \|x_0\|_X^2 + \int_0^\tau \|u(t)\|_U^2 dt \right).$$

**Lemma 5.1.** *Let  $(G, L, K)$  be an impedance passive boundary node on the spaces  $(U, X, U)$  with  $U \neq \{0\}$  and let  $P$  be the transfer function of  $(G, L, K)$ . For every  $\lambda \in \mathbb{C}_+$  there exists  $c_\lambda > 0$  such that  $\operatorname{Re} P(\lambda) \geq c_\lambda I$ .*

*Proof.* Let  $\lambda > 0$  and  $u \in U$ . Then  $P(\lambda)u = Kx$ , where  $x \in D(L)$  satisfies  $Lx = \lambda x$  and  $Gx = u$ . The identity  $x = \lambda^{-1}Lx$  implies that  $2\langle Lx, x \rangle = \lambda\|x\|^2 + \lambda^{-1}\|Lx\|^2 \geq \min\{\lambda, \lambda^{-1}\}\|x\|_{D(L)}^2$ . Since  $U \neq \{0\}$  and since  $G$  is surjective, we have  $G \neq 0$  and  $\|u\|^2 = \|Gx\|^2 \leq \|G\|_{\mathcal{L}(D(L), U)}\|x\|_{D(L)}^2$ . Combining these estimates and using the impedance passivity of  $(G, L, K)$  shows that

$$\operatorname{Re} \langle P(\lambda)u, u \rangle = \operatorname{Re} \langle Kx, Gx \rangle \geq \operatorname{Re} \langle Lx, x \rangle \geq \frac{\min\{\lambda, \lambda^{-1}\}}{2\|G\|_{\mathcal{L}(D(L), U)}} \|u\|^2.$$

Since  $u \in U$  was arbitrary, there exists  $c_\lambda > 0$  such that  $\operatorname{Re} P(\lambda) \geq c_\lambda I$ . Since  $P$  is a positive real function [21, Thm. 4.4] implies the claim for all  $\lambda \in \mathbb{C}_+$ .  $\square$

We are interested in the well-posedness and stability of the equation

$$(27a) \quad \dot{x}(t) = Lx(t)$$

$$(27b) \quad Gx(t) = \phi(u(t) - y(t))$$

$$(27c) \quad y(t) = Kx(t)$$

for  $t \geq 0$ , where  $(G, L, K)$  is an impedance passive and well-posed boundary node on  $(U, X, U)$  and  $\phi : U \rightarrow U$ . The following definition of classical and generalised solutions of (27) agree with the concepts of classical and generalised solutions of the equation (7) when the system node in (8) is associated with  $(G, L, K)$ .

**Definition 5.2.** Let  $(G, L, K)$  be a well-posed boundary node on  $(U, X, U)$ . A triple  $(x, u, y)$  is called a *classical solution* of (27) on  $[0, \infty)$  if

- $x \in C^1([0, \infty); X)$ ,  $u \in C([0, \infty); U)$ , and  $y \in C([0, \infty); U)$ ;
- $x(t) \in D(L)$  for all  $t \geq 0$  and (27) hold for every  $t \geq 0$ .

A triple  $(x, u, y)$  is called a *generalised solution* of (27) on  $[0, \infty)$  if

- $x \in C([0, \infty); X)$ ,  $u \in L^2_{loc}(0, \infty; U)$ , and  $y \in L^2_{loc}(0, \infty; U)$ ;
- there exists a sequence  $(x^k, u^k, y^k)$  of classical solutions of (27) on  $[0, \infty)$  such that for every  $\tau > 0$  we have  $(\mathbf{P}_\tau x^k, \mathbf{P}_\tau u^k, \mathbf{P}_\tau y^k)^\top \rightarrow (\mathbf{P}_\tau x, \mathbf{P}_\tau u, \mathbf{P}_\tau y)^\top$  as  $k \rightarrow \infty$  in  $C([0, \tau]; X) \times L^2(0, \tau; U) \times L^2(0, \tau; U)$ .

The following result introduces conditions for the existence of classical and generalised solutions of (27).

**Theorem 5.3.** *Suppose that  $(G, L, K)$  is an impedance passive and well-posed boundary node on  $(U, X, U)$  with  $U \neq \{0\}$  and suppose that  $\phi : U \rightarrow U$  satisfies Assumption 3.2 for some  $\kappa > 0$ . If  $x_0 \in X$  and  $u \in L^2_{loc}(0, \infty; U)$ , then (27) has a generalised solution  $(x, u, y)$  on  $[0, \infty)$  satisfying  $x(0) = x_0$ . This solution satisfies*

$$\begin{aligned} x(t) &= \mathbb{T}_t x_0 + \Phi_t \mathbf{P}_t \phi(u - y), & t \geq 0, \\ y &= \Psi_\infty x_0 + \mathbb{F}_\infty \phi(u - y), \end{aligned}$$

where  $\Sigma = (\mathbb{T}, \Phi, \Psi, \mathbb{F})$  is the well-posed system associated to  $(G, L, K)$ . If  $x_0 \in D(L)$  and  $u \in H^1_{loc}(0, \infty; U)$  are such that  $Gx_0 = \phi(u(0) - Kx_0)$ , then this  $(x, u, y)$  is a classical solution of (27) on  $[0, \infty)$ .

If  $(x_1, u_1, y_1)$  and  $(x_2, u_2, y_2)$  are two generalised solutions of (27), then for all  $t \geq 0$  we have

$$(28a) \quad \|x_2(t) - x_1(t)\|_X^2 + \kappa \int_0^t \|\phi(u_2(s) - y_2(s)) - \phi(u_1(s) - y_1(s))\|_U^2 ds$$

$$(28b) \quad \leq \|x_2(0) - x_1(0)\|_X^2 + \frac{1}{\kappa} \int_0^t \|u_2(s) - u_1(s)\|_U^2 ds.$$

*Proof.* Let  $S = \begin{bmatrix} A & B \\ C & D \end{bmatrix}$  be the system node associated with the boundary node  $(G, L, K)$ . Definitions 3.1 and 5.2 and the relationship between  $(G, L, K)$  and  $S$  imply that the classical and generalised solutions of (7) coincide with the classical and generalised solutions, respectively, of (27). Our assumptions and Lemma 5.1 imply that  $S$  is impedance passive and well-posed, and its transfer function  $P$  satisfies  $\operatorname{Re} P(\lambda) \geq c_\lambda I$  for some  $\lambda, c_\lambda > 0$ . Because of this, Theorem 3.3 implies that (7) — and consequently also (27) — has classical and generalised solutions with the properties stated in the claim. In particular,  $(x, u)^\top \in X \times U$  satisfies  $(x, u)^\top \in D(S)$  (or equivalently  $Ax + Bu \in X$ ) if and only if  $x \in D(L)$  and  $Gx = u$  and we have from [23, Thm. 2.3(iv)] that  $C \& D = [K, 0]_{D(S)}$ . These properties imply that the condition  $(x_0, u(0))^\top \in D_{\text{comp}}$  in Theorem 3.3 holds if and only if  $x_0 \in D(L)$  and  $Gx_0 = \phi(u(0) - Kx_0)$ . Finally, the estimate for the difference of two generalised solutions of (27) follows directly from the corresponding estimate for the pairs of solutions of (7).  $\square$

In the absence of the external input  $u(t)$ , the system (27) becomes

$$(29a) \quad \dot{x}(t) = Lx(t)$$

$$(29b) \quad Gx(t) = \phi(-y(t))$$

$$(29c) \quad y(t) = Kx(t)$$

for  $t \geq 0$ , where  $(G, L, K)$  is an impedance passive (but not necessarily well-posed) boundary node on the spaces  $(U, X, U)$ . We can use Theorems 3.9 and 4.4 to analyse

the well-posedness and stability of this system. We begin by defining the strong and generalised solutions of (29).

**Definition 5.4.** Let  $(G, L, K)$  be a boundary node on the spaces  $(U, X, U)$ .

- The function  $x \in \mathbf{H}_{\text{loc}}^1(0, \infty; X)$  is called a *strong solution* of (29) if  $x(t) \in D(L)$  and (29b) hold for all  $t \geq 0$ , and if (29a) holds for almost every  $t \geq 0$ . The corresponding *output*  $y : [0, \infty) \rightarrow U$  is defined by (29c) for all  $t \geq 0$ .
- The function  $x \in C([0, \infty); X)$  is called a *generalised solution* of (29) on  $[0, \infty)$  if there exists a sequence  $(x^k)_{k \in \mathbb{N}}$  of strong solutions of (29) on  $[0, \infty)$  such that  $\|\mathbf{P}_\tau x^k - \mathbf{P}_\tau x\|_{C([0, \tau]; X)} \rightarrow 0$  as  $k \rightarrow \infty$  for all  $\tau > 0$ .

**Theorem 5.5.** *Suppose that  $(G, L, K)$  is an impedance passive boundary node on  $(U, X, U)$  with  $U \neq \{0\}$ , that  $\text{Ker}(G) \cap \text{Ker}(K)$  is dense in  $X$  and that  $\phi : U \rightarrow U$  is a continuous monotone function. Then for every initial state  $x_0 \in X$  the system (29) has a well-defined generalised solution  $x$  on  $[0, \infty)$  satisfying  $x(0) = x_0$ . If  $x_0 \in D(L)$  and  $Gx_0 = \phi(-Kx_0)$ , then this  $x$  is a strong solution of (29) on  $[0, \infty)$ . The corresponding output  $y$  is right-continuous and  $y, \phi(-y) \in L^\infty(0, \infty; U)$ . If  $x_1$  and  $x_2$  are two generalised solutions of (29) on  $[0, \infty)$ , then*

$$\|x_2(t) - x_1(t)\|_X \leq \|x_2(0) - x_1(0)\|_X, \quad t \geq 0.$$

*If  $(G, L, K)$  is well-posed and its associated well-posed system is  $\Sigma = (\mathbb{T}, \Phi, \Psi, \mathbb{F})$ , then for every  $x_0 \in D(L)$  satisfying  $Gx_0 = \phi(-Kx_0)$  the strong solution  $x$  and the corresponding output  $y$  satisfy*

$$\begin{aligned} x(t) &= \mathbb{T}_t x_0 + \Phi_t \mathbf{P}_t \phi(-y), & t \geq 0, \\ y &= \Psi_\infty x_0 + \mathbb{F}_\infty \phi(-y). \end{aligned}$$

*Proof.* Let  $S = \begin{bmatrix} A & B \\ C & D \end{bmatrix}$  be the system node associated with the boundary node  $(G, L, K)$ . Definitions 3.8 and 5.4 and the relationship between  $(G, L, K)$  and  $S$  imply that the strong and generalised solutions of (11) coincide with the strong and generalised solutions, respectively, of (29). Our assumptions and Lemma 5.1 imply that  $S$  is impedance passive and that its transfer function  $P$  satisfies  $\text{Re } P(\lambda) \geq c_\lambda I$  for some  $\lambda, c_\lambda > 0$ . The relationship between  $(G, L, K)$  and  $S$  implies that  $(x, u)^\top \in X \times U$  satisfies  $(x, u)^\top \in D(S)$  (or equivalently  $Ax + Bu \in X$ ) if and only if  $x \in D(L)$  and  $Gx = u$ , and we have  $C\&D = [K, 0]_{D(S)}$  by [23, Thm. 2.3(iv)]. These properties imply that the operator  $A_\phi$  in Theorem 3.9 has the form

$$A_\phi x = Lx, \quad x \in D(A_\phi) = \{x \in D(L) \mid Gx = \phi(-Kx)\},$$

and  $A_\phi$  is in particular single-valued. The output operator of  $S$  satisfies  $\text{Ker}(C) = \text{Ker}(G) \cap \text{Ker}(K)$ , and therefore Lemma 3.10(a) and our assumption imply that  $D(A_\phi)$  is dense in  $X$ . Because of this, Theorem 3.9 and Remark 3.11 imply that (11) — and therefore also (29) — has strong and generalised solutions with exact the properties stated in the claim, and a generalised solution on  $[0, \infty)$  exists for every  $x_0 \in X$ . Moreover, the estimate for the pairs of generalised solutions follows directly from the corresponding estimate for the solutions of (11) in Theorem 3.9.  $\square$

Finally, the following theorem introduces conditions for the global asymptotic stability of the origin for the system (29).

**Theorem 5.6.** *Suppose that  $(G, L, K)$  is an impedance passive well-posed boundary node on  $(U, X, U)$  with  $U \neq 0$ , that  $\text{Ker}(G) \cap \text{Ker}(K)$  is dense in  $X$ , and that the operator  $L|_{\text{Ker}(G+K)}$  generates a strongly stable semigroup. Finally, assume that*

$\phi : U \rightarrow U$  is a locally Lipschitz continuous monotone function,  $\phi(0) = 0$ , and there exist  $\alpha, \gamma, \delta > 0$  such that

- $\operatorname{Re} \langle \phi(u), u \rangle \geq \alpha \|u\|^2$  when  $\|u\| < \delta$ ;
- $\operatorname{Re} \langle \phi(u), u \rangle \geq \gamma$  when  $\|u\| \geq \delta$ .

Then the origin is a globally asymptotically stable equilibrium point of (29), i.e., the generalised solutions on  $[0, \infty)$  corresponding to all initial states  $x(0) = x_0 \in X$  exist and satisfy  $\|x(t)\| \rightarrow 0$  as  $t \rightarrow \infty$ .

*Proof.* The existence of generalised solutions corresponding to all initial states  $x_0 \in X$  follows from Theorem 5.5. If we denote by  $\Sigma$  the well-posed linear system associated with  $(G, L, K)$  and by  $\Sigma^K = (\mathbb{T}^K, \Phi^K, \Psi^K, \mathbb{F}^K)$  the well-posed system obtained from  $\Sigma$  by negative feedback  $u = -y + \nu$ , then it is straightforward to use [41, Thm. 7.4.1] to verify that the generator of  $\mathbb{T}^K$  is exactly  $L|_{\operatorname{Ker}(G+K)}$ . As shown in the proof of Theorem 5.5, the operator  $A_\phi$  in Theorems 3.9 and 4.4 is such that  $D(A_\phi)$  is dense in  $X$ , and the generalised solutions of (29) coincide with those of (11). Therefore Theorem 4.4 shows that generalised solutions corresponding to all initial states  $x_0 \in X$  satisfy  $\|x(t)\| \rightarrow 0$  as  $t \rightarrow \infty$ .  $\square$

## 6. PARTIAL DIFFERENTIAL EQUATION SYSTEMS WITH NONLINEAR FEEDBACK

**6.1. Port-Hamiltonian Systems.** In this section we apply our results in the study of *infinite-dimensional port-Hamiltonian systems* [17, 15, 3]. This class consists of partial differential equations of the form

$$(30a) \quad \frac{\partial x}{\partial t}(\zeta, t) = P_1 \frac{\partial}{\partial \zeta} (\mathcal{H}(\zeta)x(\zeta, t)) + P_0 (\mathcal{H}(\zeta)x(\zeta, t))$$

$$(30b) \quad \begin{bmatrix} \tilde{W}_{B,1} \\ \tilde{W}_{B,2} \end{bmatrix} \begin{bmatrix} \mathcal{H}(b)x(b, t) \\ \mathcal{H}(a)x(a, t) \end{bmatrix} = \begin{bmatrix} I \\ 0 \end{bmatrix} u(t)$$

$$(30c) \quad y(t) = \tilde{W}_C \begin{bmatrix} \mathcal{H}(b)x(b, t) \\ \mathcal{H}(a)x(a, t) \end{bmatrix}$$

for  $t \geq 0$  and  $\zeta \in [a, b]$ , where  $x(\zeta, t) \in \mathbb{C}^n$ . Here  $P_1 \in \mathbb{C}^{n \times n}$  is a Hermitian matrix, i.e.,  $P_1^* = P_1$ , and  $P_0 \in \mathbb{C}^{n \times n}$  satisfies  $\operatorname{Re} P_0 \leq 0$ . The function  $\mathcal{H}(\cdot) \in L^\infty(a, b; \mathbb{C}^{n \times n})$  is assumed to satisfy  $\mathcal{H}(\zeta)^* = \mathcal{H}(\zeta)$  and  $\mathcal{H}(\zeta) \geq cI$  for some  $c > 0$  and for a.e.  $\zeta \in [a, b]$ . The matrices  $\tilde{W}_{B,1}$ ,  $\tilde{W}_{B,2}$ , and  $\tilde{W}_C$  determine the boundary input  $u(t) \in \mathbb{C}^p$ , homogeneous boundary conditions, and boundary output  $y(t) \in \mathbb{C}^p$  based on the values of  $\mathcal{H}(\cdot)x(\cdot, t)$  at the endpoints of the spatial interval  $[a, b]$ . As shown in [17], the class of port-Hamiltonian systems (30) especially contains mathematical models of mechanical systems described by, for instance, the one-dimensional wave equation and the Timoshenko beam equation. We make the following assumptions on the parameters  $\mathcal{H}$ ,  $\tilde{W}_{B,1}$ ,  $\tilde{W}_{B,2}$ , and  $\tilde{W}_C$ .

**Assumption 6.1.** *Denote*

$$R_0 = \frac{1}{\sqrt{2}} \begin{bmatrix} P_1 & -P_1 \\ I & I \end{bmatrix}, \quad \Xi = \begin{bmatrix} 0 & I \\ I & 0 \end{bmatrix}, \quad W_B = \begin{bmatrix} \tilde{W}_{B,1} \\ \tilde{W}_{B,2} \end{bmatrix} R_0^{-1},$$

$W_{B,1} = \tilde{W}_{B,1} R_0^{-1}$ ,  $W_{B,2} = \tilde{W}_{B,2} R_0^{-1}$ , and  $W_C = \tilde{W}_C R_0^{-1}$ . Suppose that the following hold.

- (a) We have  $W_B \Xi W_B^* \geq 0$  and  $\operatorname{rank} \left( \begin{bmatrix} W_B \\ W_C \end{bmatrix} \right) = n + \operatorname{rank}(W_C)$ .
- (b)  $2\operatorname{Re} \langle W_{B,1}g, W_Cg \rangle \geq \langle \Xi g, g \rangle$  for all  $g \in \operatorname{Ker}(W_{B,2})$ .

- (c)  $P_1 \mathcal{H}(\zeta) = S(\zeta)^{-1} \Delta(\zeta) S(\zeta)$ ,  $\zeta \in [a, b]$ , where  $S, \Delta \in C^1([a, b]; \mathbb{C}^{n \times n})$  are such that  $\Delta(\zeta)$  is a diagonal matrix and  $S(\zeta)$  is nonsingular for all  $\zeta \in [a, b]$ .

As shown in [17, Ch. 11–13], the system (30) can be recast as a boundary control system on the Hilbert space  $X = L^2(a, b; \mathbb{C}^n)$  equipped with the inner product  $\langle f, g \rangle_X := \langle f, \mathcal{H}g \rangle_{L^2(a, b; \mathbb{C}^n)}$  (see also [49, 32]). The boundary node  $(G, L, K)$  on  $(\mathbb{C}^p, X, \mathbb{C}^p)$  associated to the system (30) is defined by

$$(31a) \quad Lx = P_1 \frac{d}{d\zeta} (\mathcal{H}x) + P_0 (\mathcal{H}x),$$

$$(31b) \quad D(L) = \{x \in X \mid \mathcal{H}x \in H^1(a, b; \mathbb{C}^n), \tilde{W}_{B,2} \begin{bmatrix} (\mathcal{H}x)(b) \\ (\mathcal{H}x)(a) \end{bmatrix} = 0\},$$

$$(31c) \quad Gx = \tilde{W}_{B,1} \begin{bmatrix} (\mathcal{H}x)(b) \\ (\mathcal{H}x)(a) \end{bmatrix}, \quad Kx = \tilde{W}_C \begin{bmatrix} (\mathcal{H}x)(b) \\ (\mathcal{H}x)(a) \end{bmatrix}.$$

Assumption 6.1(a) implies that  $(G, L, K)$  is a boundary node on  $(\mathbb{C}^p, X, \mathbb{C}^p)$  [17, Thm. 11.3.2 & Rem. 11.3.3]. We can check that Assumption 6.1(b) implies that  $(G, L, K)$  is impedance passive (cf. [31, Lem. V.3]). Indeed, if  $x \in D(L)$ , then  $\mathcal{H}x \in H^1(a, b; \mathbb{C}^n)$ . If we define  $g = R_0 \begin{bmatrix} (\mathcal{H}x)(b) \\ (\mathcal{H}x)(a) \end{bmatrix}$ , then  $W_{B,2}g = 0$ ,  $Gx = W_{B,1}g$ , and  $Kx = W_Cg$ . We therefore have from [17, Lem. 7.2.1 & (7.26)] and Assumption 6.1(b) that

$$\operatorname{Re} \langle Lx, x \rangle_X \leq \frac{1}{2} \langle \Xi g, g \rangle_{\mathbb{C}^p} \leq \operatorname{Re} \langle W_{B,1}g, W_Cg \rangle_{\mathbb{C}^p} = \operatorname{Re} \langle Gx, Kx \rangle_{\mathbb{C}^p}.$$

Thus  $(G, L, K)$  is impedance passive. Finally, if conditions (a) and (c) in Assumption 6.1 hold, then [17, Thm. 13.2.2] implies  $(G, L, K)$  is well-posed, and in addition that the associated well-posed system  $\Sigma$  is uniformly regular in the sense that the limit  $\lim_{\lambda \rightarrow \infty, \lambda > 0} P(\lambda)$  exists.

We can now investigate the well-posedness and stability of the nonlinear partial differential equation

$$(32a) \quad \frac{\partial x}{\partial t}(\zeta, t) = P_1 \frac{\partial}{\partial \zeta} (\mathcal{H}(\zeta)x(\zeta, t)) + P_0 (\mathcal{H}(\zeta)x(\zeta, t)),$$

$$(32b) \quad \begin{bmatrix} \tilde{W}_{B,1} \\ \tilde{W}_{B,2} \end{bmatrix} \begin{bmatrix} \mathcal{H}(b)x(b, t) \\ \mathcal{H}(a)x(a, t) \end{bmatrix} = \begin{bmatrix} I \\ 0 \end{bmatrix} \phi \left( u(t) - \tilde{W}_C \begin{bmatrix} \mathcal{H}(b)x(b, t) \\ \mathcal{H}(a)x(a, t) \end{bmatrix} \right)$$

$$(32c) \quad y(t) = \tilde{W}_C \begin{bmatrix} \mathcal{H}(b)x(b, t) \\ \mathcal{H}(a)x(a, t) \end{bmatrix}.$$

The following result is a direct consequence of Theorem 5.3.

**Proposition 6.2.** *Suppose that Assumption 6.1 holds and that  $\phi : \mathbb{C}^p \rightarrow \mathbb{C}^p$  satisfies Assumption 3.2 for some  $\kappa > 0$ , and let  $(G, L, K)$  be as in (31). If  $x_0 \in D(L)$  and  $u \in H_{loc}^1(0, \infty; \mathbb{C}^p)$  are such that*

$$(33) \quad \begin{bmatrix} \tilde{W}_{B,1} \\ \tilde{W}_{B,2} \end{bmatrix} \begin{bmatrix} \mathcal{H}(b)x_0(b) \\ \mathcal{H}(a)x_0(a) \end{bmatrix} = \begin{bmatrix} I \\ 0 \end{bmatrix} \phi \left( u(0) - \tilde{W}_C \begin{bmatrix} \mathcal{H}(b)x_0(b) \\ \mathcal{H}(a)x_0(a) \end{bmatrix} \right),$$

then (32) has a classical solution  $(x, u, y)$  satisfying  $x(\cdot, 0) = x_0$  in the sense that  $x : [a, b] \times [0, \infty) \rightarrow \mathbb{C}^n$  and  $y \in C([0, \infty); \mathbb{C}^p)$  are such that  $t \mapsto x(\cdot, t) \in C^1([0, \infty); X)$ ,  $x(\cdot, t) \in D(L)$  for all  $t \geq 0$ , and (32) hold for every  $t \geq 0$  and for almost every  $\zeta \in [a, b]$ .

If  $x_0 \in X$  and  $u \in L_{loc}^2(0, \infty; \mathbb{C}^p)$ , then (32) has a generalised solution  $(x, u, y)$  satisfying  $x(\cdot, 0) = x_0$  in the sense that  $t \mapsto x(\cdot, t) \in C([0, \infty); X)$  and  $y \in$

$L^2_{loc}(0, \infty; U)$  and there exists a sequence  $(x^k, u^k, y^k)$  of classical solutions such that for every  $\tau > 0$  we have  $\sup_{t \in [0, \tau]} \|x^k(\cdot, t) - x(\cdot, t)\|_X \rightarrow 0$ ,  $\|\mathbf{P}_\tau u^k - \mathbf{P}_\tau u\|_{L^2(0, \tau)} \rightarrow 0$ , and  $\|\mathbf{P}_\tau y^k - \mathbf{P}_\tau y\|_{L^2(0, \tau)} \rightarrow 0$  as  $k \rightarrow \infty$ . Each pair  $(x_1, u_1, y_1)$  and  $(x_2, u_2, y_2)$  of generalised solutions satisfy the estimate

$$\begin{aligned} & \|x_2(\cdot, t) - x_1(\cdot, t)\|_{L^2(a, b)}^2 + \kappa \int_0^t \|\phi(u_2(s) - y_2(s)) - \phi(u_1(s) - y_1(s))\|_{\mathbb{C}^p}^2 ds \\ & \leq \|x_2(\cdot, 0) - x_1(\cdot, 0)\|_{L^2(a, b)}^2 + \frac{1}{\kappa} \int_0^t \|u_2(s) - u_1(s)\|_{\mathbb{C}^p}^2 ds, \quad t \geq 0. \end{aligned}$$

*Proof.* As explained above, Assumption 6.1 implies that  $(G, L, K)$  defined in (31) is well-posed and impedance passive. The claims follow from the application of Theorem 5.3 to  $(G, L, K)$  in (31).  $\square$

In the case where  $u \equiv 0$  we can use Theorems 5.5 and 5.6 to introduce conditions for the existence and stability of solutions of (32). The part on the existence of solutions does not require condition (c) in Assumption 6.1, and it is related to the earlier result on port-Hamiltonian systems with nonlinear feedback in [3, Thm. 4.2] and [44, Sec. 5.1]. Sufficient conditions for the stability of the differential equation (32) with the linear boundary condition (34) have been presented, for instance, in [49, 4, 34].

**Proposition 6.3.** *Suppose that Assumption 6.1(a–b) hold and that  $\phi : \mathbb{C}^p \rightarrow \mathbb{C}^p$  is a continuous monotone function, and let  $(G, L, K)$  be as in (31). If  $x_0 \in D(L)$  is such that*

$$\begin{bmatrix} \tilde{W}_{B,1} \\ \tilde{W}_{B,2} \end{bmatrix} \begin{bmatrix} \mathcal{H}(b)x_0(b) \\ \mathcal{H}(a)x_0(a) \end{bmatrix} = \begin{bmatrix} I \\ 0 \end{bmatrix} \phi \left( -\tilde{W}_C \begin{bmatrix} \mathcal{H}(b)x_0(b) \\ \mathcal{H}(a)x_0(a) \end{bmatrix} \right),$$

then (32) with  $u \equiv 0$  has a strong solution  $x$  satisfying  $x(\cdot, 0) = x_0$  in the sense that  $t \mapsto x(\cdot, t) \in H^1_{loc}(0, \infty; X)$ ,  $x(t) \in D(L)$  for all  $t \geq 0$ , (32b) holds for all  $t \geq 0$ , and (32a) holds for almost every  $t \geq 0$  and almost every  $\zeta \in [a, b]$ . The corresponding output  $y : [0, \infty) \rightarrow \mathbb{C}^p$  defined by (32c) for  $t \geq 0$  is right-continuous and  $y, \phi(-y) \in L^\infty(0, \infty; \mathbb{C}^p)$ . If  $x_0 \in X$  and  $u \in L^2_{loc}(0, \infty; \mathbb{C}^p)$ , then (32) has a generalised solution  $x$  satisfying  $x(\cdot, 0) = x_0$  in the sense that there exists a sequence  $(x^k)_{k \in \mathbb{N}}$  of strong solutions of (32) such that  $\sup_{t \in [0, \tau]} \|x^k(\cdot, t) - x(\cdot, t)\|_X \rightarrow 0$  for all  $\tau > 0$ . Every pair  $x_1$  and  $x_2$  of generalised solutions of (32) satisfy

$$\|x_2(\cdot, t) - x_1(\cdot, t)\|_{L^2(a, b)} \leq \|x_2(\cdot, 0) - x_1(\cdot, 0)\|_{L^2(a, b)}, \quad t \geq 0.$$

Assume further that Assumption 6.1(c) holds, that  $\phi$  satisfies Assumption 4.1, and that the linear partial differential equation (32a) together with the boundary condition

$$(34) \quad \begin{bmatrix} \tilde{W}_{B,1} + \tilde{W}_C \\ \tilde{W}_{B,2} \end{bmatrix} \begin{bmatrix} \mathcal{H}(b)x_0(b) \\ \mathcal{H}(a)x_0(a) \end{bmatrix} = 0$$

is strongly stable in the sense that all its classical solutions  $x$  satisfy  $\|x(\cdot, t)\|_X \rightarrow 0$  as  $t \rightarrow \infty$ . Then the origin is a globally asymptotically stable equilibrium point of (29), i.e., the generalised solutions corresponding to all initial states  $x_0 \in X$  exist and satisfy  $\|x(\cdot, t)\|_X \rightarrow 0$  as  $t \rightarrow \infty$ .

*Proof.* Assumption 6.1(a)–(b) imply that  $(G, L, K)$  defined in (31) is an impedance passive boundary node on  $(\mathbb{C}^p, X, \mathbb{C}^p)$ . Since  $\text{Ker}(G) \cap \text{Ker}(K)$  in particular contains all functions  $x \in L^2(a, b; \mathbb{C}^n)$  for which  $\mathcal{H}x$  is a smooth function satisfying

$(\mathcal{H}x)(a) = (\mathcal{H}x)(b) = 0$ , and since  $\mathcal{H}(\zeta) \geq cI$  for some  $c > 0$  and for a.e.  $\zeta \in [a, b]$ , it is easy to verify that  $\text{Ker}(G) \cap \text{Ker}(K)$  is dense in  $X$ . The classical solutions of (32a) with the boundary condition (34) coincide with the classical orbits of the contraction semigroup generated by  $L|_{\text{Ker}(G+K)}$ , and our assumption therefore implies that this semigroup is strongly stable. Because of this, the claims follow directly from Theorems 5.5 and 5.6.  $\square$

**6.2. A Timoshenko beam with saturated boundary damping.** We consider the well-posedness and stability of a one-dimensional Timoshenko beam model

$$(35a) \quad \rho(\zeta)w_{tt}(\zeta, t) = (K(\zeta)(w_\zeta(\zeta, t) - \varphi(\zeta, t)))_\zeta$$

$$(35b) \quad I_\rho(\zeta)\varphi_{tt}(\zeta, t) = (EI(\zeta)\varphi_\zeta(\zeta, t))_\zeta + K(\zeta)(w_\zeta(\zeta, t) - \varphi(\zeta, t))$$

$$(35c) \quad w_t(a, t) = 0, \quad \varphi_t(a, t) = 0$$

$$(35d) \quad EI(b)\varphi_\zeta(b, t) = \phi_{\text{sat}}(u_1(t) - \varphi_t(b, t))$$

$$(35e) \quad K(b)(w_\zeta(b, t) - \varphi(b, t)) = \phi_{\text{sat}}(u_2(t) - w_t(b, t))$$

for  $\zeta \in (a, b)$  and  $t \geq 0$ , where  $w(\zeta, t)$  is the transverse displacement of the beam and  $\varphi(\zeta, t)$  is the rotation angle of a filament of the beam. The physical parameters  $\rho, I_\rho, EI$  and  $K$  are the mass per unit length, the rotary moment of inertia of a cross section of the beam, the product of Young's modulus of elasticity and the moment of inertia of the cross section and the shear modulus, respectively. We assume that these physical parameters are positive and continuously differentiable with respect to  $\zeta \in [a, b]$ . The external input of the system is  $u(t) = (u_1(t), u_2(t))^T \in \mathbb{C}^2$ ,  $t \geq 0$ . In (35d)–(35e),  $\phi_{\text{sat}} : \mathbb{C} \rightarrow \mathbb{C}$  is the scalar saturation function defined by  $\phi_{\text{sat}}(u) = u$  when  $|u| < 1$  and  $\phi_{\text{sat}}(u) = u/|u|$  when  $|u| \geq 1$ . The boundary conditions describe the situation where the beam is clamped at  $\zeta = a$  and is subject to saturated damping and input at  $\zeta = b$ . We define the distance between the two states  $(w^1, \varphi^1)$  and  $(w^2, \varphi^2)$  of (35) at time  $t \geq 0$  as

$$\begin{aligned} D_{(w^2, \varphi^2), (w^1, \varphi^1)}(t) := & \int_0^1 \left[ K(\zeta) |w_\zeta^2(\zeta, t) - w_\zeta^1(\zeta, t) - \varphi^2(\zeta, t) + \varphi^1(\zeta, t)|^2 \right. \\ & + \rho(\zeta) |w_t^2(\zeta, t) - w_t^1(\zeta, t)|^2 + EI(\zeta) |\varphi_\zeta^2(\zeta, t) - \varphi_\zeta^1(\zeta, t)|^2 \\ & \left. + I_\rho(\zeta) |\varphi_t^2(\zeta, t) - \varphi_t^1(\zeta, t)|^2 \right] d\zeta. \end{aligned}$$

We define the *energy* of the state  $(w, \varphi)$  of (35) at time  $t \geq 0$  by  $E_{w, \varphi}(t) := \frac{1}{2}D_{(w, \varphi), (0, 0)}(t)$ . The concepts of classical and generalised solutions of (35) are given in the following definition.

**Definition 6.4.** The triple  $(w, \varphi, u)$  is called a *classical solution* of (35) on  $[0, \infty)$  if  $u \in C([0, \infty); \mathbb{C}^2)$ ,  $\varphi_t(b, \cdot), w_t(b, \cdot) \in C([0, \infty))$ ,  $t \mapsto w_\zeta(\cdot, t) - \varphi(\cdot, t)$ ,  $t \mapsto w_t(\cdot, t)$ ,  $t \mapsto \varphi_\zeta(\cdot, t)$ ,  $t \mapsto \varphi_t(\cdot, t) \in C^1([0, \infty); L^2(a, b))$ , and  $w_\zeta(\cdot, t) - \varphi(\cdot, t)$ ,  $w_t(\cdot, t)$ ,  $\varphi_\zeta(\cdot, t)$ ,  $\varphi_t(\cdot, t) \in H^1(a, b)$ ,  $t \geq 0$ , and if (35) hold for all  $t \geq 0$  and for a.e.  $\zeta \in [a, b]$ .

The triple  $(w, \varphi, u)$  is called a *generalized solution* of (35) on  $[0, \infty)$  if  $u \in L^2_{\text{loc}}(0, \infty; \mathbb{C}^2)$ ,  $t \mapsto w_\zeta(\cdot, t) - \varphi(\cdot, t)$ ,  $t \mapsto w_t(\cdot, t)$ ,  $t \mapsto \varphi_\zeta(\cdot, t)$ ,  $t \mapsto \varphi_t(\cdot, t) \in C([0, \infty); L^2(a, b))$ , and  $\varphi_t(b, \cdot), w_t(b, \cdot) \in L^2_{\text{loc}}(0, \infty)$  are such that there exists a

sequence  $(w^k, \varphi^k, u^k)$  of classical solutions such that for every  $\tau > 0$  we have

$$\begin{aligned} \sup_{t \in [0, \tau]} D_{(w^k, \varphi^k), (w, \varphi)}(t) &\rightarrow 0, & \|\mathbf{P}_\tau u^k - \mathbf{P}_\tau u\|_{L^2(0, \tau; \mathbb{C}^2)} &\rightarrow 0, \\ \|\mathbf{P}_\tau(\varphi_t^k(b, \cdot), w_t^k(b, \cdot))^\top - \mathbf{P}_\tau(\varphi_t(b, \cdot), w_t(b, \cdot))^\top\|_{L^2(0, \tau; \mathbb{C}^2)} &\rightarrow 0 \end{aligned}$$

as  $k \rightarrow \infty$ .

The following result establishes the existence of classical and generalised solutions of the nonlinear model (35) and shows that the origin is a globally asymptotically stable equilibrium point of the system.

**Proposition 6.5.** *If  $w_0, w_1, \varphi_0$ , and  $\varphi_1$  and  $u = (u_1, u_2)^\top \in L^2_{loc}(0, \infty; \mathbb{C}^2)$  are such that  $w'_0 - \varphi_0, w_1, \varphi'_0, \varphi_1 \in L^2(a, b)$ , then (35) has a generalised solution  $(w, \varphi, u)$  on  $[0, \infty)$  satisfying  $w(\cdot, 0) = w_0, w_t(\cdot, 0) = w_1, \varphi(\cdot, 0) = \varphi_0$  and  $\varphi_t(\cdot, 0) = \varphi_1$ . If  $u \in H^1_{loc}(0, \infty; \mathbb{C}^2)$ ,  $w'_0 - \varphi_0, w_1, \varphi'_0, \varphi_1 \in H^1(a, b)$  and*

$$(36a) \quad w_1(a) = 0, \quad \varphi_1(a) = 0,$$

$$(36b) \quad EI(b)\varphi'_0(b) = \phi_{\text{sat}}(u_1(0) - \varphi_1(b)),$$

$$(36c) \quad K(b)(w'_0(b) - \varphi_0(b)) = \phi_{\text{sat}}(u_2(0) - w_1(b)),$$

then this  $(w, \varphi, u)$  is a classical solution of (35). Every pair  $(w^1, \varphi^1, u^1)$  and  $(w^2, \varphi^2, u^2)$  of generalised solutions satisfies

$$\begin{aligned} D_{(w^2, \varphi^2), (w^1, \varphi^1)}(t) + \int_0^t \left\| \phi \left( u^2(s) - \begin{bmatrix} \varphi_t^2(b, s) \\ w_t^2(b, s) \end{bmatrix} \right) - \phi \left( u^1(s) - \begin{bmatrix} \varphi_t^1(b, s) \\ w_t^1(b, s) \end{bmatrix} \right) \right\|_{\mathbb{C}^2}^2 ds \\ \leq D_{(w^2, \varphi^2), (w^1, \varphi^1)}(0) + \int_0^t \|u^2(s) - u^1(s)\|_{\mathbb{C}^2}^2 ds, \quad t \geq 0. \end{aligned}$$

Moreover, if  $u \equiv 0$ , then the origin of (35) is a globally asymptotically stable equilibrium point, i.e., the generalised solutions described above satisfy  $E_{w, \varphi}(t) \rightarrow 0$  as  $t \rightarrow \infty$ .

*Proof.* We start by showing that (35) can be formulated as an infinite-dimensional port-Hamiltonian system of the form (32) which satisfies Assumption 6.1. To this end we define

$$\begin{aligned} x_1(\zeta, t) &= w_\zeta(\zeta, t) - \varphi(\zeta, t), \quad x_2(\zeta, t) = \rho(\zeta)w_t(\zeta, t), \\ x_3(\zeta, t) &= \varphi_\zeta(\zeta, t), \quad x_4(\zeta, t) = I_\rho(\zeta)\varphi_t(\zeta, t) \end{aligned}$$

and  $x = (x_1, x_2, x_3, x_4)^\top$ . Then (35a)–(35b) has the form (30a) on  $X = L^2(a, b; \mathbb{C}^4)$ , where

$$P_1 = \begin{bmatrix} 0 & 1 & 0 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 0 \end{bmatrix}, \quad P_0 = \begin{bmatrix} 0 & 0 & 0 & -1 \\ 0 & 0 & 0 & 0 \\ 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 \end{bmatrix}, \quad \mathcal{H}(\zeta) = \text{diag}(K(\zeta), \rho(\zeta)^{-1}, EI(\zeta), I_\rho(\zeta)^{-1})^\top.$$

We have  $P_1 = P_1^*$  and  $\text{Re } P_0 \leq 0$ . If we define  $\phi : \mathbb{C}^2 \rightarrow \mathbb{C}^2$  such that  $\phi(u) = (\phi_{\text{sat}}(u_1), \phi_{\text{sat}}(u_2))^\top$  for  $u = (u_1, u_2)^\top$  and define  $u(t) = (u_1(t), u_2(t))^\top$ ,  $y(t) = (\varphi_t(b, t), w_t(b, t))^\top$ , and

$$\begin{aligned} \tilde{W}_{B,1} &= \begin{bmatrix} 0 & 0 & 1 & 0 & 0 & 0 & 0 & 0 \\ 1 & 0 & 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix}, & \tilde{W}_{B,2} &= \begin{bmatrix} 0 & 0 & 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 0 & 0 & 0 & 1 \end{bmatrix}, \\ \tilde{W}_C &= \begin{bmatrix} 0 & 0 & 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 & 0 & 0 & 0 \end{bmatrix}, \end{aligned}$$

then (35c)–(35e) are exactly of the form (32b)–(32c).

We will now show that Assumption 6.1 is satisfied. A direct computation shows that

$$W_{B,1} = \frac{1}{\sqrt{2}} \begin{bmatrix} 0 & 0 & 0 & 1 & 0 & 0 & 1 & 0 \\ 0 & 1 & 0 & 0 & 1 & 0 & 0 & 0 \end{bmatrix}, \quad W_{B,2} = \frac{1}{\sqrt{2}} \begin{bmatrix} -1 & 0 & 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & -1 & 0 & 0 & 0 & 0 & 1 \end{bmatrix},$$

$$W_C = \frac{1}{\sqrt{2}} \begin{bmatrix} 0 & 0 & 1 & 0 & 0 & 0 & 0 & 1 \\ 1 & 0 & 0 & 0 & 0 & 1 & 0 & 0 \end{bmatrix}.$$

These matrices satisfy  $W_B \Xi W_B^* = 0_{4 \times 4}$  and  $\text{rank} \left( \begin{bmatrix} W_B \\ W_C \end{bmatrix} \right) = 6$  where  $n = 4$  and  $\text{rank}(W_C) = 2$ . Thus Assumption 6.1(a) is satisfied. Now observe that

$$\text{Ker}(W_{B,2}) = \{(g_1, g_2, g_3, g_4, g_5, g_6, g_7, g_8)^\top \in \mathbb{C}^8 \mid g_1 = g_6, g_3 = g_8\}.$$

Moreover, we have  $\langle \Xi g, g \rangle = 2\text{Re}(\overline{g_1}g_5 + \overline{g_2}g_6 + \overline{g_3}g_7 + \overline{g_4}g_8)$  and it is easy to check that if  $g \in \text{Ker}(W_{B,2})$ , then

$$\begin{aligned} 2\text{Re} \langle W_{B,1}g, W_Cg \rangle &= \text{Re}(\overline{g_1}(g_2 + g_5) + \overline{g_3}(g_4 + g_7) + \overline{g_6}(g_2 + g_5) + \overline{g_8}(g_4 + g_7)) \\ &= \langle \Xi g, g \rangle. \end{aligned}$$

Thus Assumption 6.1(b) is satisfied. Finally, it is straightforward to check that  $P_1 \mathcal{H}(\zeta) = S(\zeta)^{-1} \Delta(\zeta) S(\zeta)$  for  $\zeta \in [0, 1]$  with  $S \in C^1([0, 1]; \mathbb{C}^4)$  and with  $\Delta = \text{diag}(\sqrt{EI/I_\rho}, -\sqrt{EI/I_\rho}, \sqrt{K/\rho}, -\sqrt{K/\rho})$ . Thus Assumption 6.1(c) is satisfied.

The properties in Examples 3.7 and 4.2 imply that  $\phi$  satisfies Assumptions 3.2 with  $\kappa = 1$  and Assumption 4.1 with some  $\alpha, \gamma, \delta > 0$ . Let  $w_0, w_1, \varphi_0$ , and  $\varphi_1$  and  $u = (u_1, u_2)^\top \in L_{\text{loc}}^2(0, \infty; \mathbb{C}^2)$  be such that  $w'_0 - \varphi_0, w_1, \varphi'_0, \varphi_1 \in L^2(a, b)$ , and define  $x_0 = (w'_0 - \varphi_0, \rho(\cdot)w_1, \varphi'_0, I_\rho(\cdot)\varphi_1)^\top$ . Then  $x_0 \in X$  and Proposition 6.2 implies that (32) has a generalised solution on  $[0, \infty)$  satisfying  $x(\cdot, 0) = x_0$ . It is straightforward to check that there exist  $w : [a, b] \times [0, \infty) \rightarrow \mathbb{C}$  and  $\varphi : [a, b] \times [0, \infty) \rightarrow \mathbb{C}$  such that  $t \mapsto w(\cdot, t) \in C([0, \infty); H^1(a, b))$ ,  $t \mapsto w_t(\cdot, t) \in C([0, \infty); L^2(a, b))$ ,  $t \mapsto \varphi(\cdot, t) \in C([0, \infty); H^1(a, b))$ ,  $t \mapsto \varphi_t(\cdot, t) \in C([0, \infty); L^2(a, b))$ , and  $x(\zeta, t) = (w_\zeta(\zeta, t) - \varphi(\zeta, t), \rho(\zeta)w_t(\zeta, t), \varphi_\zeta(\zeta, t), I_\rho(\zeta)\varphi_t(\zeta, t))^\top$  for all  $t \geq 0$  and for a.e.  $\zeta \in [a, b]$ . The assumptions that  $K, \rho, EI, I_\rho \in C^1([a, b])$  and  $K^{-1}, \rho^{-1}, EI^{-1}, I_\rho^{-1} \in L^\infty(a, b)$  imply that  $(w, \varphi, u)$  is a generalised solution of (35) in the sense of Definition 6.4. In addition, the estimate for the pairs of generalised solutions of (32) implies the estimate for the pairs of generalised solutions of (35) in the claim. Moreover, if  $u \in H_{\text{loc}}^1(0, \infty; \mathbb{C}^2)$ ,  $w'_0 - \varphi_0, w_1, \varphi'_0, \varphi_1 \in H^1(a, b)$  and (36) hold, then  $x_0$  satisfies  $\mathcal{H}x_0 \in H^1(a, b)$ ,  $\tilde{W}_{B,2}x_0 = 0$ , and (33) holds. Thus Proposition 6.2 shows that  $x$  is a classical solution of (32), and consequently  $(w, \varphi, u)$  is a classical solution of (35) in the sense of Definition 6.4.

We have from [50, Ex. 5.22] that the semigroup  $\mathbb{T}^K$  associated with the partial differential equation (35a)–(35b) with the boundary condition of the form (34) is strongly stable. Therefore the claim regarding the convergence of generalised solutions directly from Proposition 6.3. The claim about stability follows from Proposition 6.3.  $\square$

**6.3. A two-dimensional heat equation.** We consider a heat equation on a two-dimensional spatial domain  $\Omega \subset \mathbb{R}^2$ . We assume that  $\Omega$  is open, connected, and bounded subset of  $\mathbb{R}^2$  and that its boundary  $\partial\Omega$  is piecewise  $C^2$ -smooth (see [7, Sec. 2] for the precise definition). Our heat equation with a scalar-valued nonlinear

boundary input  $u(t) \in \mathbb{C}$  and a boundary output  $y(t) \in \mathbb{C}$  on  $\Omega$  has the form

$$(37a) \quad \frac{\partial x}{\partial t}(\zeta, t) = \Delta x(\zeta, t), \quad \zeta \in \Omega, \quad t > 0,$$

$$(37b) \quad \frac{\partial x}{\partial n}(\zeta, t) = b(\zeta)\phi(u(t) - y(t)), \quad \zeta \in \partial\Omega, \quad t > 0$$

$$(37c) \quad y(t) = \int_{\partial\Omega} b(\zeta)x(\zeta, t)d\zeta, \quad t > 0$$

for  $t > 0$ , where  $\frac{\partial x}{\partial n}(\zeta, t)$  is the outward normal derivative of  $x(\cdot, t)$  at  $\zeta \in \partial\Omega$ , where  $b \in L^2(\partial\Omega; \mathbb{R})$  is the profile function associated with the Neumann boundary input and the boundary output  $y(t)$ . We assume that  $\int_{\partial\Omega} b(\zeta)d\zeta \neq 0$ . The following result based on Theorems 3.3 and 4.4 establishes the existence of classical and generalised solutions as well as the global asymptotic stability of (37) in the case where  $\phi : \mathbb{C} \rightarrow \mathbb{C}$  is a saturation function.

**Proposition 6.6.** *Suppose that  $b \in L^2(\partial\Omega; \mathbb{R})$  satisfies  $\int_{\partial\Omega} b(\zeta)d\zeta \neq 0$  and let  $\phi : \mathbb{C} \rightarrow \mathbb{C}$  be the saturation function defined by  $\phi(u) = u$  if  $|u| \leq 1$  and  $\phi(u) = u/|u|$  if  $|u| > 1$ . Let  $x_0 \in H^2(\Omega)$  and  $u \in H^1_{loc}(0, \infty)$  be such that*

$$(38) \quad \frac{\partial x_0}{\partial n} = b(\cdot)\phi\left(u(0) - \int_{\partial\Omega} b(\zeta)x_0(\zeta)d\zeta\right) \quad \text{on } \partial\Omega.$$

Then (37) has a classical state trajectory  $x : \Omega \times [0, \infty) \rightarrow \mathbb{C}$  satisfying  $x(\cdot, 0) = x_0$  and classical output  $y \in C([0, \infty))$  in the sense that  $t \mapsto x(\cdot, t) \in C^1([0, \infty); L^2(\Omega))$ ,  $x(\cdot, t) \in H^2(\Omega)$  for all  $t \geq 0$ , (37a) holds for all  $t > 0$  and for a.e.  $\zeta \in \Omega$ , (37b) holds for  $t \geq 0$  and for a.e.  $\zeta \in \partial\Omega$ , and (37c) holds for all  $t \geq 0$ .

If  $x_0 \in L^2(\Omega)$  and  $u \in L^2_{loc}(0, \infty)$ , then (37) has a generalised state trajectory  $x \in C([0, \infty); L^2(\Omega))$  satisfying  $x(\cdot, 0) = x_0$  and a generalised output  $y \in C([0, \infty))$  in the sense that there exist sequences  $(u^k)_{k \in \mathbb{N}}$ ,  $(x^k)_{k \in \mathbb{N}}$  and  $(y^k)_{k \in \mathbb{N}}$  with the following properties.

- For each  $k \in \mathbb{N}$ ,  $x^k$  and  $y^k$  are the classical state trajectory and output, respectively, of (37) corresponding to the initial state  $x^k(0)$  and input  $u^k \in C([0, \infty))$
- For all  $\tau > 0$  we have  $(\mathbf{P}_\tau x^k, \mathbf{P}_\tau u^k, \mathbf{P}_\tau y^k)^\top \rightarrow (\mathbf{P}_\tau x, \mathbf{P}_\tau u, \mathbf{P}_\tau y)^\top$  as  $t \rightarrow \infty$  in  $C([0, \tau]; L^2(\Omega)) \times L^2(0, \tau) \times L^2(0, \tau)$ .

If  $x_1, x_2 \in C([0, \infty); L^2(\Omega))$  and  $y_1, y_2 \in C([0, \infty))$  are two generalised state trajectories and outputs of (37) corresponding to initial states  $x_{01}, x_{02} \in L^2(\Omega)$  and inputs  $u_1, u_2 \in L^2_{loc}(0, \infty)$ , then they satisfy the estimate (10) with  $X = L^2(\Omega)$  and  $\kappa = 1$  for all  $t \geq 0$ .

Finally, if  $u \equiv 0$ , then for every  $x_0 \in L^2(\Omega)$  the generalised state trajectory  $x$  and the generalised output  $y$  satisfy  $\|x(\cdot, t)\|_{L^2(\Omega)} \rightarrow 0$  as  $t \rightarrow \infty$  and  $y \in L^2(0, \infty)$ .

*Proof.* The heat equation (37) can be represented as a system of the form (7) on the spaces  $X = L^2(\Omega)$  and  $U = \mathbb{C}$  if we define  $S$  as the system node associated with the linear heat equation (37a) on  $\Omega$  with the linear Neumann boundary input

$$(39) \quad \frac{\partial x}{\partial n}(\zeta, t) = b(\zeta)u(t), \quad \zeta \in \partial\Omega, \quad t > 0$$

and with the boundary output (37c). We have from [7, Sec. 7] that this  $S$  is defined by

$$D(S) = \left\{ (x, u)^\top \in \mathbb{H}^2(\Omega) \times \mathbb{C} \mid \frac{\partial x}{\partial n} = b(\cdot)u \text{ on } \partial\Omega \right\}$$

$$S \begin{bmatrix} x \\ u \end{bmatrix} = \begin{bmatrix} A\&B \\ C\&D \end{bmatrix} \begin{bmatrix} x \\ u \end{bmatrix} = \begin{bmatrix} \Delta x \\ \int_{\partial\Omega} b(\zeta)x(\zeta)d\zeta \end{bmatrix}, \quad \begin{bmatrix} x \\ u \end{bmatrix} \in D(S).$$

It is shown in [7, Cor. 1 & Sec. 7] that  $S$  is a well-posed system node on  $(\mathbb{C}, X, \mathbb{C})$  and by [7, Cor. 2] the associated well-posed system  $\Sigma = (\mathbb{T}, \Phi, \Psi, \mathbb{F})$  is uniformly regular in the sense that its transfer function satisfies  $P(\lambda) \rightarrow 0$  as  $\lambda \rightarrow \infty$  with  $\lambda > 0$ . To check that  $S$  is impedance passive, let  $(x, u)^\top \in D(S)$ . Integration by parts and the assumption that  $b$  is real-valued imply that

$$\begin{aligned} \operatorname{Re} \langle A\&B \begin{bmatrix} x \\ u \end{bmatrix}, x \rangle_X &= \operatorname{Re} \langle \Delta x, x \rangle_{L^2(\Omega)} = \operatorname{Re} \int_{\partial\Omega} b(\zeta)u \overline{x(\zeta)} d\zeta - \|\nabla x\|_{L^2(\Omega)}^2 \\ &\leq \operatorname{Re} \langle C\&D \begin{bmatrix} x \\ u \end{bmatrix}, u \rangle. \end{aligned}$$

Thus  $S$  is impedance passive. Since  $b \neq 0$ , it is easy to see that  $P(\lambda) \in \mathbb{R}$  for  $\lambda > 0$  and  $P(\lambda) \neq 0$  for some  $\lambda > 0$ , and thus (since  $S$  is impedance passive) we have  $\operatorname{Re} P(\lambda) \geq c_\lambda$  for some  $\lambda, c_\lambda > 0$ . Finally, we note that the saturation function  $\phi$  satisfies Assumptions 3.2 and 4.1 (see Examples 3.7 and 4.2). Since  $(x_0, u(0))^\top \in D_{\text{comp}}$  if and only if  $x_0 \in \mathbb{H}^2(\Omega)$  and (38) holds, the existence of classical and generalised state trajectories and outputs and the estimate (10) follow directly from Theorem 3.3.

To prove the claims regarding the convergence of solutions as  $t \rightarrow \infty$ , let  $\Sigma = (\mathbb{T}, \Phi, \Psi, \mathbb{F})$  be the well-posed linear system associated with  $S$ . We will now show that the semigroup  $\mathbb{T}^K$  of the well-posed system  $\Sigma^K = (\mathbb{T}^K, \Phi^K, \Psi^K, \mathbb{F}^K)$  obtained from  $\Sigma$  with linear negative output feedback is exponentially stable. The generator  $A^K$  of  $\mathbb{T}^K$  in Theorem 4.4 is given by

$$A^K x = \Delta x, \quad x \in D(A^K) = \left\{ x \in \mathbb{H}^2(\Omega) \mid \frac{\partial x}{\partial n} = -b(\cdot) \int_{\partial\Omega} b(\zeta)x(\zeta)d\zeta \text{ on } \partial\Omega \right\}.$$

We first note that  $A^K$  has compact resolvent. Integration by parts shows that for  $x \in D(A^K)$  we have

$$(40) \quad \langle A^K x, x \rangle_X = - \left| \int_{\partial\Omega} b(\zeta)x(\zeta)d\zeta \right|^2 - \|\nabla x\|_{L^2(\Omega)}^2 \leq 0,$$

and thus  $A^K$  is self-adjoint and  $A^K \leq 0$ . If  $A^K x = 0$ , then (40) shows that  $\|\nabla x\|_{L^2(\Omega)} = 0$ , which implies that  $x$  is constant with respect to  $\zeta \in \Omega$ . But since  $\int_{\partial\Omega} b(\zeta)d\zeta \neq 0$  by assumption and since (40) implies  $\int_{\partial\Omega} b(\zeta)x(\zeta)d\zeta = 0$ , we necessarily have  $x = 0$ . Thus 0 is not an eigenvalue of  $A^K$  and, since  $A^K$  has compact resolvent, we have  $0 \in \rho(A)$ . This implies that the semigroup  $\mathbb{T}^K$  generated by  $A^K$  is exponentially stable. Moreover, since  $\phi$  satisfies Assumption 3.2, we have  $\operatorname{Re} \langle \phi(u_2) - \phi(u_1), u_2 - u_1 \rangle > 0$  whenever  $\phi(u_1) \neq \phi(u_2)$  and the domain  $D(A_\phi)$  of  $A_\phi$  in (25) is dense in  $X$  by Lemma 3.10. Because of this, Theorem 4.4 implies that for any  $x_0 \in L^2(\Omega)$  and for  $u \equiv 0$  the corresponding generalised state trajectory  $x$  and generalised output  $y$  satisfy  $\|x(\cdot, t)\|_{L^2(\Omega)} \rightarrow 0$  as  $t \rightarrow \infty$  and  $y \in L^2(0, \infty)$ .  $\square$

The following result shows that the generalised state trajectory  $x$  in Proposition 6.6 also has an interpretation as a *weak solution* of the heat equation (37).

**Proposition 6.7.** *For every  $x_0 \in L^2(\Omega)$  and  $u \in L^2_{loc}(0, \infty)$  the generalised state trajectory and output in Proposition 6.6 satisfy  $t \mapsto x(\cdot, t) \in L^2_{loc}(0, \infty; H^1(\Omega))$  and*

$$\begin{aligned} \langle x(\cdot, t) - x_0, z \rangle_{L^2(\Omega)} &= \int_0^t \left[ \phi(u(s) - y(s)) \int_{\partial\Omega} b(\zeta) \overline{z(\zeta)} d\zeta - \langle \nabla x(\cdot, s), \nabla z \rangle_{L^2(\Omega; \mathbb{C}^2)} \right] ds \\ y(t) &= \int_{\partial\Omega} b(\zeta) x(\zeta, t) d\zeta \end{aligned}$$

for all  $z \in H^1(\Omega)$ , where the first identity holds for all  $t \geq 0$  and the second one holds for a.e.  $t \geq 0$ .

*Proof.* Let  $X = L^2(\Omega)$  and let  $S$  be as in the proof of Proposition 6.6 and let  $x$  and  $y$  be the generalised state trajectory and output of (37) in Proposition 6.6. We have from the proof of Proposition 6.6 and Theorem 3.3 that  $x$  and  $y$  satisfy (9a). Therefore [45, Rem. 4.2.6] implies that

$$(41) \quad \langle x(\cdot, t) - x_0, z \rangle_X = \int_0^t \left[ \langle x(\cdot, s), \Delta z \rangle_X + \phi(u(s) - y(s)) \int_{\partial\Omega} b(\zeta) \overline{z(\zeta)} d\zeta \right] ds$$

for all  $z \in D(A) = \{x \in H^2(\Omega) \mid \frac{\partial x}{\partial n} = 0 \text{ on } \partial\Omega\}$  and  $t \geq 0$ . Let  $(x^k)_{k \in \mathbb{N}}$ ,  $(u^k)_{k \in \mathbb{N}}$  and  $(y^k)_{k \in \mathbb{N}}$  be sequences with the properties described in Proposition 6.6. Denote  $x^k(t) := x^k(\cdot, t)$  and  $x(t) := x(\cdot, t)$  for  $t \geq 0$  and  $k \in \mathbb{N}$  for brevity. Integration by parts shows that for  $k, n \in \mathbb{N}$  the classical state trajectories  $x^k$  and  $x^n$  of (37) satisfy

$$\begin{aligned} \frac{d}{ds} \|x^k(s) - x^n(s)\|_X^2 &= 2\operatorname{Re} \langle \Delta(x^k(s) - x^n(s)), x^k(s) - x^n(s) \rangle_X \\ &= 2\operatorname{Re} \langle \phi(u^k(s) - y^k(s)) - \phi(u^n(s) - y^n(s)), y^k(s) - y^n(s) \rangle_{\mathbb{C}} \\ &\quad - 2\|\nabla(x^k(s) - x^n(s))\|_X^2. \end{aligned}$$

Integrating with respect to  $s$  from 0 to  $t$  and using Assumption 3.2 and Lemma 3.12(b) implies that

$$2 \int_0^t \|\nabla x^k(s) - \nabla x^n(s)\|_X^2 ds \leq \|x^k(0) - x^n(0)\|_X^2 + \|\mathbf{P}_t u^k - \mathbf{P}_t u^n\|_{L^2(0, t)} \rightarrow 0$$

as  $k, n \rightarrow \infty$ . Since we also have  $\|\mathbf{P}_t x^k(\cdot) - \mathbf{P}_t x^n(\cdot)\|_{L^2(0, t; X)} \rightarrow 0$  as  $k, n \rightarrow \infty$ , we conclude that  $(\mathbf{P}_t x^k(\cdot))_{k \in \mathbb{N}}$  is a Cauchy sequence in  $L^2(0, t; H^1(\Omega))$ . Since we have  $\sup_{s \in [0, t]} \|x^k(s) - x(s)\| \rightarrow 0$  as  $k \rightarrow \infty$ , we can deduce that  $\mathbf{P}_t x \in L^2(0, t; H^1(\Omega))$ . Since  $t > 0$  was arbitrary, we have  $x \in L^2_{loc}(0, \infty; H^1(\Omega))$  as claimed. Since  $y^k(t) = \int_{\partial\Omega} b(\zeta) x^k(\zeta, t) d\zeta$  for all  $t \geq 0$  and since  $\mathbf{P}_t x^k(\cdot) \rightarrow \mathbf{P}_t x(\cdot)$  in  $L^2(0, t; H^1(\Omega))$  as  $k \rightarrow \infty$ , it is easy to show that  $y(t) = \int_{\partial\Omega} b(\zeta) x(\zeta, t) d\zeta$  for a.e.  $t \geq 0$ .

Finally, for  $z \in D(A)$  and for a.e.  $s \geq 0$  we have  $\langle x(\cdot, s), \Delta z \rangle_X = -\langle \nabla x(\cdot, s), \nabla z \rangle_X$  by integration by parts. Since  $D(A)$  is dense in  $H^1(\Omega)$ , the first identity in the claim follows from (41).  $\square$

## REFERENCES

- [1] F. Alabau-Boussouira and K. Ammari. Sharp energy estimates for nonlinearly locally damped PDEs via observability for the associated undamped system. *J. Funct. Anal.*, 260(8):2424–2450, 2011.
- [2] F. Alabau-Boussouira, Y. Privat, and E. Trélat. Nonlinear damped partial differential equations and their uniform discretizations. *J. Funct. Anal.*, 273(1):352–403, 2017.

- [3] B. Augner. Well-posedness and stability of infinite-dimensional linear port-Hamiltonian systems with nonlinear boundary feedback. *SIAM J. Control Optim.*, 57(3):1818–1844, 2019.
- [4] B. Augner and B. Jacob. Stability and stabilization of infinite-dimensional linear port-Hamiltonian systems. *Evol. Equ. Control The.*, 3(2):207–229, 2014.
- [5] L. Berrahmoune. Stabilization of unbounded linear control systems in Hilbert space with monotone feedback. *Asymptotic Anal.*, 80(1-2):93–131, 2012.
- [6] A. Binid, A. M. Taboye, and M. Laabissi. Cone-bounded feedback laws for linear second order systems. *Evol. Equ. Control The.*, 12(4):1174–1192, 2023.
- [7] C.I. Byrnes, D.S. Gilliam, V.I. Shubov, and G. Weiss. Regular Linear Systems Governed by a Boundary Controlled Heat Equation. *J. Dyn. Control Syst.*, 8(3):341–370, 2002.
- [8] R. Curtain and H. Zwart. Stabilization of collocated systems by nonlinear boundary control. *Syst. Control Lett.*, 96:11–14, 2016.
- [9] B. Farkas and S.-A. Wegner. Variations on Barbálat’s lemma. *Am. Math. Mon.*, 123(8):825–830, 2016.
- [10] P. Grabowski and F. M. Callier. On the circle criterion for boundary control systems in factor form: Lyapunov stability and Lur’e equations. *ESAIM Control Optim. Calc. Var.*, 12(1):169–197, 2006.
- [11] P. Grabowski and F. M. Callier. Lur’e feedback systems with both unbounded control and observation: well-posedness and stability using nonlinear semigroups. *Nonlinear Anal.*, 74(10):3065–3085, 2011.
- [12] C. Guiver, H. Logemann, and M. R. Opmeer. Infinite-Dimensional Lur’e Systems: Input-To-State Stability and Convergence Properties. *SIAM J. Control Optim.*, 57(1):334–365, 2019.
- [13] A. Haraux. Stabilization of trajectories for some weakly damped hyperbolic equations. *J. Differ. Equations*, 59(2):145–154, 1985.
- [14] A. Hastir, F. Califano, and H. Zwart. Well-posedness of infinite-dimensional linear systems with nonlinear feedback. *Syst. Control Lett.*, 128:19–25, 2019.
- [15] B. Jacob, K. Morris, and H.J. Zwart.  $C_0$ -semigroups for hyperbolic partial differential equations on a one-dimensional spatial domain. *J. Evol. Equ.*, 15:493–502, 2015.
- [16] B. Jacob, F. L. Schwenninger, and L. A. Vorberg. Remarks on input-to-state stability of collocated systems with saturated feedback. *Math. Control Signal.*, 32(3):293–307, 2020.
- [17] B. Jacob and H.J. Zwart. *Linear Port-Hamiltonian Systems on Infinite-dimensional Spaces*. Number 223 in Operator Theory: Advances and Applications. Springer, 2012.
- [18] R. Joly and C. Laurent. Decay of semilinear damped wave equations: cases without geometric control condition. *Ann. H. Lebesgue*, 3:1241–1289, 2020.
- [19] M. Laabissi and A. M. Taboye. Strong stabilization of non-dissipative operators in Hilbert spaces with input saturation. *Math. Control Signal*, 33(3):553–568, 2021.
- [20] I. Lasiecka and T. I. Seidman. Strong stability of elastic control systems with dissipative saturating feedback. *Syst. Control Lett.*, 48(3):243–252, March 2003.
- [21] H. Logemann. Some spectral properties of operator-valued positive-real functions. *Syst. Control Lett.*, 145:104786, 9, 2020.
- [22] H. Logemann and E. P. Ryan. Time-varying and adaptive integral control of infinite-dimensional regular linear systems with input nonlinearities. *SIAM J. Control Optim.*, 38(4):1120–1144, 2000.
- [23] J. Malinen and O. J. Staffans. Conservative boundary control systems. *J. Differ. Equations*, 231(1):290–312, 2006.
- [24] S. Marx, V. Andrieu, and C. Prieur. Cone-bounded feedback laws for  $m$ -dissipative operators on Hilbert spaces. *Math. Control Signal*, 29(4):Art. 18, 32, 2017.
- [25] S. Marx, Y. Chitour, and C. Prieur. Stability analysis of dissipative systems subject to nonlinear damping via Lyapunov techniques. *IEEE T. Automat. Cont.*, 65(5):2139–2146, 2020.
- [26] S. Marx and G. Weiss. The well-posedness of an impedance passive nonlinear system with a static monotone feedback operator. In *Proceedings of the 5th IFAC Workshop on Control of Systems Governed by Partial Differential Equations*, submitted, 2025.
- [27] I. Miyadera. *Nonlinear semigroups*, volume 109. American Mathematical Soc., 1992.
- [28] V. Natarajan and J. Bentsman. Approximate local output regulation for nonlinear distributed parameter systems. *Math. Control Signal*, 28(3):Art. 24, 44, 2016.
- [29] J. C. Oostveen and R. F. Curtain. Riccati equations for strongly stabilizable bounded linear systems. *Automatica*, 34(8):953–967, 1998.

- [30] L. Paunonen. Stability and robust regulation of passive linear systems. *SIAM J. Control Optim.*, 57(6):3827–3856, 2019.
- [31] L. Paunonen, Y. Le Gorrec, and H. Ramirez. A Lyapunov approach to robust regulation of distributed port-Hamiltonian systems. *IEEE T. Automat. Cont.*, 66(12):6041–6048, 2021.
- [32] F. Philipp, T. Reis, and M. Schaller. Infinite-dimensional port-Hamiltonian systems – a system node approach. *arXiv e-prints*, page arXiv:2302.05168, February 2023.
- [33] D. Salamon. Infinite-dimensional linear systems with unbounded control and observation: A functional analytic approach. *Trans. Amer. Math. Soc.*, 300(2):383–431, 1987.
- [34] J. Schmid. Stabilization of port-Hamiltonian systems with discontinuous energy densities. *Evol. Equ. Control The.*, 11(5):1775–1795, 2022.
- [35] J. Schmid and H. Zwart. Stabilization of port-Hamiltonian systems by nonlinear boundary control in the presence of disturbances. *ESAIM Control Optim. Calc. Var.*, 27:Paper No. 53, 37, 2021.
- [36] T. I. Seidman and H. Li. A note on stabilization with saturating feedback. *Discrete Cont. Dyn. S.*, 7(2):319–328, 2001.
- [37] S. Singh. *Incrementally scattering passive infinite dimensional systems on Hilbert spaces*. PhD thesis, Tel Aviv University, 2023.
- [38] S. Singh and G. Weiss. Nonlinear perturbation of a class of conservative linear system. In *2022 IEEE 61st Conference on Decision and Control (CDC)*, pages 396–402, 2022.
- [39] S. Singh and G. Weiss. Second Order Systems on Hilbert Spaces with Nonlinear Damping. *SIAM J. Control Optim.*, 61(4):2630–2654, 2023.
- [40] M. Slemrod. Feedback stabilization of a linear control system in Hilbert space with an a priori bounded control. *Math. Control Signals Systems*, 2(3):265–285, 1989.
- [41] O. Staffans. *Well-Posed Linear Systems*. Cambridge University Press, 2005.
- [42] O. Staffans and G. Weiss. Transfer functions of regular linear systems. II. The system operator and the Lax-Phillips semigroup. *T. Am. Math. Soc.*, 354(8):3229–3262, 2002.
- [43] O. J. Staffans. Passive and conservative continuous-time impedance and scattering systems. Part I: Well-posed systems. *Math. Control Signal*, 15(4):291–315, 2002.
- [44] S. Trostorff. A characterization of boundary conditions yielding maximal monotone operators. *J. Funct. Anal.*, 267(8):2787–2822, 2014.
- [45] M. Tucsnak and G. Weiss. *Observation and Control for Operator Semigroups*. Birkhäuser Basel, 2009.
- [46] M. Tucsnak and G. Weiss. Well-posed systems—The LTI case and beyond. *Automatica*, 50(7):1757–1779, 2014.
- [47] J. Vancostenoble. Weak asymptotic stability of second-order evolution equations by nonlinear and nonmonotone feedbacks. *SIAM J. Math. Anal.*, 30(1):140–154, 1999.
- [48] N. Vanspranghe, F. Ferrante, and C. Prieur. Control of a wave equation with a dynamic boundary condition. In *59th IEEE Conference on Decision and Control (CDC)*, pages 652–657, Jeju Island, Republic of Korea, 14–18 December 2020.
- [49] J. A. Villegas, H. Zwart, Y. Le Gorrec, B. Maschke, and A. J. van der Schaft. Stability and stabilization of a class of boundary control systems. In *Proceedings of the 44th IEEE Conference on Decision and Control*, pages 3850–3855, Dec 2005.
- [50] J.A. Villegas. *A Port-Hamiltonian Approach to Distributed Parameter Systems*. PhD thesis, University of Twente, The Netherlands, May 2007.

(A. Hastir) SCHOOL OF MATHEMATICS AND NATURAL SCIENCES, UNIVERSITY OF WUPPERTAL, 42119, WUPPERTAL, GERMANY

*Email address:* hastir@uni-wuppertal.de

(L. Paunonen) MATHEMATICS RESEARCH CENTRE, TAMPERE UNIVERSITY, P.O. BOX 692, 33101 TAMPERE, FINLAND

*Email address:* lassi.paunonen@tuni.fi