# Multi-Object Sketch Animation by Scene Decomposition and Motion Planning

Jingyu Liu, Zijie Xin, Yuhan Fu, Ruixiang Zhao, Bangxiang Lan, Xirong Li<sup>†</sup>

## Renmin University of China



Figure 1. **Comparison of different methods for multi-object sketch animation**. The SOTA sketch animation methods FlipSketch [1] and Live-Sketch [6] struggle to animate multi-object sketches. FlipSketch fails to preserve visual appearance, while Live-Sketch struggles with modeling complex motion, leading to random shaky or nearly static animations and violating plausibility (the liquid in the bottle increases during pouring). In contrast, our proposed MoSketch, overcomes these issues and achieves excellent performance.

## Abstract

Sketch animation, which brings static sketches to life by generating dynamic video sequences, has found widespread applications in GIF design, cartoon production, and daily entertainment. While current sketch animation methods perform well in single-object sketch animation, they struggle in multi-object scenarios. By analyzing their failures, we summarize two challenges of transitioning from singleobject to multi-object sketch animation: object-aware motion modeling and complex motion optimization. For multiobject sketch animation, we propose MoSketch based on iterative optimization through Score Distillation Sampling (SDS), without any other data for training. We propose four modules: LLM-based scene decomposition, LLM-based motion planning, motion refinement network and compositional SDS, to tackle the two challenges in a divide-andconquer strategy. Extensive qualitative and quantitative experiments demonstrate the superiority of our method over existing sketch animation approaches. MoSketch takes a pioneering step towards multi-object sketch animation, opening new avenues for future research and applications. The code will be released.

## 1. Introduction

Sketch animation brings sketches composed of strokes to life by generating dynamic video sequences, making it widely used in GIF design, cartoon production, and daily entertainment [8, 27, 36]. In this work, we aim to animate a multi-object sketch *w.r.t.* a specific textual instruction.

In the field of sketch animation, early methods required manual intervention [3, 24, 42, 44], and it is only recently that approaches such as Live-Sketch [6] and FlipS-ketch [1], which rely solely on text input as guidance, have

<sup>&</sup>lt;sup>†</sup>Corresponding author

Method	Sketch Representation	Object-aware Motion Modeling	Training Data	Optimization Method
FlipSketch	Raster	No	Yes	Fine-Tune
Live-Sketch	Vector	No	No	SDS
MoSketch	Vector	Yes	No	Compositional SDS

 
 Table 1. A brief comparison of FlipSketch, Live-Sketch and our proposed MoSketch in multi-object sketch animation.

emerged. Live-Sketch is a method based on iterative optimization without any other data for training. With a vector representation of sketches, Live-Sketch ultilizes a set of MLPs as the generation network, modeling sketch animation from both holistic and local perspectives. The animation result is iteratively optimized through Score Distillation Sampling (SDS) [19] to leverage a pre-trained textto-video (T2V) diffusion model [34]. FlipSketch is a finetuning-based method that requires additional data for training. It utilizes rasterized sketches and applies DDIM inversion [26] to the input sketch to extract a noise pattern that captures the sketch's visual appearance. This noise pattern is then fed into a T2V diffusion model [34] fine-tuned on a dataset synthesized by Live-Sketch to generate sketch animations. Both Live-Sketch and FlipSketch demonstrate excellent performance in single-object sketch animation.

Compared to single-object sketch animation, multiobject sketch animation is complex and more challenging, as it not only requires ensuring smooth motion and preserving the visual appearance of each object, but also necessitates considering plausible relationships, interactions and physical constraints among multiple objects. Both Live-Sketch and FlipSketch struggle when transitioning to multiobject scenarios, as shown in Fig. 1. Live-Sketch does not incorporate object-aware motion modeling, leaving objects' relationships and interactions untouched. The iterative optimization of Live-Sketch process suffers from T2V diffusion models' limitation in handling complex motions among objects, a challenge that has been extensively studied in recent works [5, 15, 29, 32]. As for FlipSketch, in addition to lacking object-aware motion modeling, the noise patterns extracted through DDIM inversion are insufficient to fully capture the appearance of multi-object sketches. More importantly, since its fine-tuning data is synthezed from Live-Sketch, which rarely includes multi-object scenarios or exhibits poor quality for such cases, significantly significantly the multi-object animation.

By analyzing their failures, we summarize that transitioning from single-object to multi-object sketch animation presents two challenges: (1) **Object-aware motion modeling**: Relative motions, interactions, and physical constraints among objects should be fully considered during motion modeling. (2) **complex motion optimization**: complex motions of multiple objects should be effectively guided during the optimization process. An effective multi-object sketch animation method should fully address these two challenges.

Since there are no multi-object sketch animation datasets for training, we propose MoSketch for multi-object sketch animation based on iterative optimization through SDS. Following Live-Sketch, we use a vector representation of sketches. We propose four modules: LLM-based scene decomposition, LLM-based motion planning, motion refinement network and compositional SDS, to tackle the two challenges in a divide-and-conquer strategy. The LLMbased scene decomposition is employed to identify objects, obtain their locations, and decompose complex motions into simpler ones, which serve as the foundation for the other three modules. (2) We employ LLM-based motion planning to generate a motion plan in advance, which defines a coarse-grained object-level motion, ultilizing LLM's motion priors about relative motions, interactions and physical constraints. (3) Based on Live-Sketch, we propose a motion refinement network to refine the coarse object motion. (4) During iterative optimization through SDS, we additionally use a compositional SDS to guide the simpler motions modeling sequentially, which can be effectively featured by T2V diffusion models. We briefly compare MoSketch with Live-Sketch and FlipSketch in Tab. 1. Our key contribution can be summarized as follows:

- We propose MoSketch for multi-object sketch animation based on iterative optimization through SDS.
- We propose four modules to tackle with the two challenges in multi-object sketch animation in a divide-andconquer strategy.
- Extensive qualitative and quantitative experiments demonstrate the superiority of our method over existing sketch animation approaches.

## 2. Related Works

#### 2.1. Sketch Animation

Sketch animation aims to convert a static sketch into a dynamic one, which has been extensively studied within the field of computer graphics [3, 6, 42]. Early sketch animation works focus on developing tools for human-driven creation [13, 25, 43] or incorporating additional inputs such as videos [23, 30, 44] and skeletons [4, 24] as references to guide the animation process. These methods cannot avoid the need for manual intervention.

Gal *et al.* [6] proposes a text-based sketch animation method Live-Sketch, which does not require any other training data. Instead, it utilizes Score Distillation Sampling (SDS) [19] to iteratively optimize the animation process by leveraging a pre-defined T2V diffusion model. Some works [22, 40] have further optimized the animation quality by building upon this paradigm, while Bandyopadhyay *et al.* [1] performs DDIM inversion to the given sketches and generate sketch animation by a fine-tuned T2V diffusion model. Although performing excellently in single-object sketch animation, these methods fail in multi-object one due to the lack of object-aware motion modeling and complex motion optimization.

Due to no data for training, we follow Live-Sketch, using SDS to leverage a pre-defined T2V diffusion model to guide the animation process.

### 2.2. Text-guided Image-to-Video Generation

A close research area to sketch animation is text-guided image-to-video (I2V) generation [9, 31, 35, 41], aiming to synthesize a video with contents and motions guided from a image and a text description. Videocrafter [2] is the first open-source foundational model capable of I2V while maintaining content preservation constraints. I2VGen-XL [46] proposes a cascaded framework that first generates low-resolution content consistent video and then performs high-resolution detail refinement. Cogvideox [41] is based on DiT [18], jointly learning text and visual tokens to perform I2V. DynamiCrafter [37] leverages pre-trained T2V priors with the proposed dual-stream image injection mechanism and the dedicated training paradigm to achieve I2V.

Although these methods perform well on pixel-domain I2V tasks, they struggle in sketch animation due to the domain gap between sketches and normal images.

#### 2.3. LLM-assisted Compositional Generation

Compositional generation requires modeling the relative relationships and interactions between multiple objects, which generative models often struggle to learn effectively [10, 14, 39]. In contrast, LLMs possess extensive prior knowledge, serving as a valuable complement to address these limitations.

LLMs exhibit strong planning capabilities. In text-toimage [20, 21] and text-to-3D [7, 47] compositional generation, LLMs are employed for static layout generation of objects, while in T2V [14, 32] and text-to-4D [38, 45] tasks, they are used for dynamic trajectory planning. Furthermore, LLMs have demonstrated scene decomposition capabilities, decomposing complex multi-object task into multiple single- or few-object ones [7, 15]. This decomposition enables generative models to tackle the problem in a divide-and-conquer manner.

Inspired by these works, we employ LLM for scene decomposition and motion planning in our method, playing a crucial role in the task of multi-object sketch animation.

### 3. Method

Following Live-Sketch, our method uses a vector representation of sketches and achieves multi-object sketch animation based on iterative optimization through SDS. We first introduce the preliminaries of vector sketch representation, followed by a brief description of Live-Sketch.

### 3.1. Preliminaries

Vector Sketch Representation. A vector sketch is composed of strokes, where each stroke is a cubic Bézier curve controled by four points. A vector sketch can be parameterized by all control points' 2D coordinates. Given a vector sketch  $P \in \mathbb{R}^{n \times 2}$  parameterized by n 2D control points and a text instruction Y describing the desired motion, vector sketch animation requires a model to generate a short video consisted of a sequence of vector sketches, formulated by movements of all control points  $\Delta Z \in \mathbb{R}^{n \times f \times 2}$ , where fis the number of steps, equivalent to the number of frames. This process can be formulated at a high-level as follows:

$$\Delta Z \leftarrow \text{Model}(P, Y) \tag{1}$$

**Live-Sketch in a Nutshell.** Live-Sketch designs a simple generative model, separating the sketch animation target  $\Delta Z$  into sketch-level and point-level motion  $\Delta Z_s$  and  $\Delta Z_p$ . The sketch-level motion  $\Delta Z_s$  is the result of holistic transformations (translation, scaling, shearing, and rotation) of the whole sketch, while the point-level motion  $\Delta Z_p$  is the translation of control points, focusing on the internal motion of the sketch.

Specially, the vector sketch  $P \in \mathbb{R}^{n \times 2}$  is fed into a MLP and get a hidden representation, which is then separated into a sketch embedding  $\hat{B} \in \mathbb{R}^{1 \times d}$  and a point embedding  $\hat{P} \in \mathbb{R}^{n \times d}$ , where d denotes the hidden dimension. The sketch embedding  $\hat{B} \in \mathbb{R}^{1 \times d}$  is passed to a MLP to predict parameters  $\tilde{B} \in \mathbb{R}^{f \times 7}$  of holistic transformations in all frames (seven parameters in a frame: two for translation, two for scaling, two for shearing and one for rotation). The holistic transformations are applied to all control points P, yielding a sketch-level motion  $\Delta Z_s \in \mathbb{R}^{n \times f \times 2}$ . The point embedding directly predicts all control points' translations  $\Delta Z_p \in \mathbb{R}^{n \times f \times 2}$  through a MLP. The sketch-level motion  $\Delta Z_s$  and point-level motion  $\Delta Z_p$  are gathered to get the sketch animation  $\Delta Z$ . This process is formulated as:

$$\begin{cases} \hat{B}, \hat{P} \leftarrow \text{MLP}(P), \\ \tilde{B} \leftarrow \text{MLP}(\hat{B}), \\ \Delta Z_s \leftarrow \text{transformation}(\tilde{B}, P), \\ \Delta Z_p \leftarrow \text{MLP}(\hat{P}), \\ \Delta Z \leftarrow \Delta Z_s + \Delta Z_p. \end{cases}$$
(2)

Live-Sketch utilizes Score Distillation Sampling (SDS) [19] to leverage a pre-trained T2V diffusion model [34] to guide the animation process. SDS is a method that using pre-trained pixel-aware diffusion models to guide other non-pixel generation process in an iterative optimization-based manner, without any other data for training. We denote the SDS loss in Live-Sketch as:

$$\mathcal{L}_{SDS} \leftarrow \text{SDS}(\Delta Z, Y) \tag{3}$$



Figure 2. Diagram of our proposed MoSketch for multi-object sketch animation. Four modules: LLM-based scene decomposition, LLM-based motion planning, motion refinement network and compositional SDS, are proposed to tackle the two challenges of multi-object sketch animation in a divide-and-conquer strategy. There are m = 3 objects and r = 2 decomposed instructions in this example.

By iteratively minimizing  $\mathcal{L}_{SDS}$ , the animation result  $\Delta Z$  will progressively align with the text instruction Y.

### 3.2. Multi-object Sketch Animation

Based on Live-Sketch, we propose MoSketch for multiobject sketch animation, as shown in Fig. 2. We propose four modules: LLM-based scene decomposition, LLMbased motion planning, fine-grained motion network and compositional SDS, to tackle the two challenges described in Introduction in a divide-and-conquer strategy. The LLMbased scene decomposition is the foundation of other three modules, which is employed to identify objects, obtain their locations, and decompose complex motions into simpler components. The LLM-based motion planning and the motion refinement network achieves the object-aware motion modeling considering of relative motions, interactions and physical constraints among objects. The compositional SDS ensures that the complex motions of multiple objects are effectively guided during the iterative optimization. We will describe these four modules as follows.

#### 3.2.1 LLM-based Scene Decomposition

The scene decomposition is employed to identify objects, obtain their locations, and decompose complex motions into simpler components, which serve as the foundation for the other three modules. We employ GPT-4 for scene decomposition, which is successfully applied in compositional generation works [15, 28, 38], as shown in Fig. 3. Given a sketch P and a text instruction Y, we first ask GPT-4 to identify the objects requiring motion planning and decompose the complex motion described in Y, resulting in m

identified objects and r simple motions. The m identified objects should be independent of each other, with no hierarchical or synonymous relationships. The decomposed r simpler motions is described in r short text instructions  $\{Y_k\}_{k=1}^r$ , and each should involve one or few identified objects [15, 38]. In our method, both m and r are not fixed, but m should be less than 7 and r should be less than 5. We employ a powerful open-world object detection model Grounding DINO [16] to get objects' bounding boxes  $B_0 \in \mathbb{R}^{m \times 4}$ . Note that sketch P is parameterized by the n control points, we assign each point to an object based on the distance between the center point of the stroke it controls and the bounding boxes of all objects. The point is assigned to the object whose bounding box is closest to the stroke's center. The assignment result is denoted as  $\{P_k\}_{k=1}^m$ , where  $P_k$  are control points belonging to k-the object. The LLM-based scene decomposition can be formulate briefly as:

$$\begin{cases} \text{objects, } \{Y_k\}_{k=1}^r & \leftarrow \quad \text{GPT4}(P, Y), \\ B_0 & \leftarrow \quad \text{grounding}(P, \text{objects}), \\ \{P_k\}_{k=1}^m & \leftarrow \quad \text{assign}(B_0, P) \end{cases}$$
(4)

#### 3.2.2 LLM-based Motion Planning

Object-aware motion modeling should consider of relative motions, interactions, and particularly physical constraints among objects, which are important yet difficult to model with conventional networks like Live-Sketch. Recent works [17, 48] reveal that GPT-4 possesses prior knowledge of multi-object motions in the real world and can roughly plan the external motion of objects. Thus we employ GPT-



Figure 3. **Illustration of the LLM-based scene decomposition.** The LLM-based scene decomposition is the foundation of our method, used to identify objects, obtain their locations, and decompose complex motions into simpler components.



Figure 4. **Illustration of the LLM-based motion planning.** The LLM-based motion plan defines a coarse-grained object external motion for a multi-object sketch.

4 for motion planning, defining a coarse object-level motion for object-aware motion modeling, as shown in Fig. 4. Given the sketch P, text instruction Y, objects' initial location  $B_0$ , GPT-4 generates a coarse motion plan which is the bounding boxes of objects in f frames, denoted as  $B \in \mathbb{R}^{m \times f \times 4}$ . To ensure that GPT-4 fully considers object interactions, relative motions and physical constraints such as inertia and gravity during motion planning, we follow [14] by incorporating a reasoning step before GPT-4 generates its response. With the motion plan B and point assignment  $\{P_k\}_{k=1}^m$ , we gather a coarse-grained object motion  $\Delta Z_c \in \mathbb{R}^{n \times f \times 2}$ . This process is formulate as:

$$\begin{cases} B &\leftarrow \text{GPT4}(P,Y,B_0), \\ \Delta Z_c &\leftarrow \text{gather}(\{P_k\}_{k=1}^m,B), \end{cases}$$
(5)

### 3.2.3 Motion Refinement Network

While GPT-4 provides a motion plan for objects, a generative networks is still required to refine the external motion and model the internal motion of objects. Based on Live-Sketch, we propose a motion refinement network, as shown in Fig. 5. By reviewing the generative process of Live-Sketch, it is evident that the generative model is not object-aware. Thus we replace sketch-level motion  $\Delta Z_s$  in Live-Sketch to object-level motion  $\Delta Z_o$ , and turn the pointlevel motion  $\Delta Z_p$  in Live-Sketch to the object-aware one.



Figure 5. Illustration of the motion refinement network. The motion refinement network generates a fine-grained object motion and point motion, for external motion refinement and internal motion modeling of objects respectively.  $n_1, n_2, n_3$  are the number of control points in the three objects.

We regard  $\Delta Z_o$  and  $\Delta Z_p$  to the refinement of external motion and the modeling of internal motion for all objects, respectively.

Specially, besides P as the input of all points, we add the motion plan  $B \in \mathbb{R}^{m \times (f \times 4)}$  as the input of m objects. Each passes through a MLP to get a hidden representation and fed into Transformers for featuring relationships and interactions between objects, yielding object embedding  $\hat{B} \in \mathbb{R}^{m \times d}$  and point embedding  $\hat{P} \in \mathbb{R}^{n \times d}$ :

$$B, P \leftarrow \text{Transformers}(\text{MLP}(B), \text{MLP}(P)).$$
 (6)

Similar to sketch embedding for holistic transformations for the whole sketch in Live-Sketch, object embeddings  $\hat{B}$ are used for holistic transformations of objects. Each object embedding  $\hat{B}_k$  is passed through a dedicated MLP to predict the seven transformation parameters  $\tilde{B}_k \in \mathbb{R}^{f \times 7}$ and the transformations are applied to relative control points  $P_k$ . We gather all transformation results as the fine-grained object motion  $\Delta Z_o \in \mathbb{R}^{n \times f \times 2}$ . Like Live-Sketch, point embedding  $\hat{P}$  directly predicts points in different objects. Finally, the coarse-grained object motion  $\Delta Z_c$ , fine-grained object motion  $\Delta Z_o$  and point motion  $\Delta Z_p$  are gathered to generate sketch animation  $\Delta Z$ . This process is denoted as:

$$\begin{cases} \{B_k\}_{k=1}^m, \{\hat{P}_k\}_{k=1}^m \leftarrow \hat{B}, \hat{P}, \\ \{\tilde{B}_k\}_{k=1}^m \leftarrow \{\text{MLP}_k(\hat{B}_k)\}_{k=1}^m, \\ \Delta Z_o \leftarrow \{\text{transformation}(\tilde{B}_k, P_k)\}_{k=1}^m, \\ \Delta Z_p \leftarrow \{\text{MLP}_k(\hat{P}_k)\}_{k=1}^m. \\ \Delta Z \leftarrow \Delta Z_c + \Delta Z_o + \Delta Z_p. \end{cases}$$
(7)

#### 3.2.4 Compositional SDS

Following Live-Sketch, we use SDS to leverage a pretrained T2V diffusion model [17] to iteratively guide the



Figure 6. Qualitative results. We exhibit the multi-object sketch animation results  $\Delta Z$  and coarse-grained object motion  $\Delta Z_c$  predefined by LLM-based motion planning. See the supplementary for the full videos and additional results.

animation, without any other data for training. To ensuring that the complex motions of multiple objects are effectively guided, inspired by compositional generation works [7, 38, 47], we use compositional SDS in addition to the original one in Live-Sketch during the T2V diffusion model guidance. Specially, for each decomposed simple motion described by  $Y_k$ , we obtain a sub-video  $\Delta Z_k$  decomposed from  $\Delta Z$ , which is the animation result of involved objects in  $Y_k$  from  $\Delta Z$ . A SDS loss  $\mathcal{L}_{SDS-k}$  is calculated upon  $\Delta Z_k$  and  $Y_k$ , guiding the simpler motion in  $Y_k$ , which can be effectively featured by the T2V diffusion model. All SDS loss of simple motions  $\{Y_k\}_{k=1}^r$  are added with the original SDS loss  $\mathcal{L}_{SDS}$  of complex motion. The guidance process is formulated as:

$$\begin{cases} \{\Delta Z_k\}_{k=1}^r &\leftarrow \{\operatorname{decompose}(\Delta Z, Y_k)\}_{k=1}^r, \\ \{\mathcal{L}_{SDS-k}\}_{k=1}^r &\leftarrow \{\operatorname{SDS}(\Delta Z_k, Y_k)\}_{k=1}^r, \\ \mathcal{L}_{SDS} &\leftarrow \operatorname{SDS}(\Delta Z, Y), \\ \mathcal{L}_{CSDS} &\leftarrow \mathcal{L}_{SDS} + \sum_{k=1}^r \mathcal{L}_{SDS-k}. \end{cases}$$
(8)

## 4. Evaluation

### 4.1. Experimental Setup

**Testing Data Creation**. We create 60 multi-object sketches to test multi-object sketch animation. First, we random select pixel-based images with at least two objects from three categories: human, animal and object following [6]. Then we use CLIPasso [33] to convert these images to vector

sketches. Finally, for each multi-object sketch, we employ GPT-4 to generate a text description which implicitly suggests possible motions. These 60 multi-object sketches encompass various real-life scenarios such as sports, dining, transportation and work. All sketches are provided in the supplementary.

**Baselines**. We compare our method with two textguided sketch animation methods:

• Live-Sketch, CVPR24 [6], which uses a vector representation and sketches and employ SDS to leverage a pre-trained T2V diffusion model for animation without any other data for fine-tuning.

• FlipSketch, CVPR25 [1], which applies DDIM inversion to the given raster sketch and perform sketch animation by a fine-tuned T2V diffusion model.

Viewing text-guided sketch animation as a special case of text-guided image-to-video (I2V) generation, we further compare with two I2V methods:

• Cogvideox, arxiv24 [41], a DIT-based method that jointly learning text and visual tokens.

• Dynamicrafter, ECCV24 [37], leveraging pre-trained T2V priors with a dual-stream image injection mechanism and dedicated training paradigm to achieve I2V generation.

**Details of Implementation**. The parameters in the finegrained motion network are optimized under the guidance of SDS. The hidden dimension d of both object and point



Figure 7. Different animation results according to different text instructions.



Figure 8. Single-object sketch animation results of MoSketch.

embedding is set to 128. The number of frames f is fixed at 16. The Transformer network consists of 2 layers. For optimization, we use the Adam optimizer with an initial learning rate of 5e-3 and a weight decay of 1e-2. The network is iterated for 500 steps, requiring approximately one hour on a single RTX 3090 Ti GPU.

**Evaluation Criteria**. We follow Live-Sketch [6] and FlipSketch [1], evaluating the model's ability to generate videos that align with the text description (text-to-video alignment), as well as the ability to preserve structural characteristics (sketch-to-video alignment). Considering that our sketches contain multiple objects, we employ "Overall Consistency" and "I2V Subject" introduced in a comprehensive video generation benchmark VBench [11, 12] as the metric for "text-to-video alignment" and "sketch-to-video alignment" respectively. Additionally, we use "Motion Smoothness" and "Dynamic Degree" from VBench to evaluate the quality of generated videos.

#### 4.2. Results

**Qualitative Results**. Fig. 6 shows the multi-object sketch animation results of MoSketch. With the LLM-based motion planning and the fine-grained motion network, MoSketch achieves vivid and realistic animations of complex scenarios, including rock climbing, basketball playing, and tank target shooting. The LLM-based motion plans are highly plausible, while the fine-grained motion network further refines the animation (the basketball finally enters the net, and the shell explodes when it collides with the target). We observe that even when the object localization or point assignment during LLM-based scene description contains



Figure 9. Qualitative comparisons for multi-object sketch animation. See the supplementary for more examples.

Method	Text-to-Video Alignment	Sketch-to-Video Alignment	Motion Smoothing	Dynamic Degree
Cogvideox	0.141	0.610	0.747	-
Dynamicrafter	0.184	0.771	0.868	-
FlipSketch	0.199	0.704	0.839	-
Live-Sketch	0.207	0.897	0.956	0.266
MoSketch	0.218	0.914	0.977	0.283

Table 2. Quantitative comparisons for multi-object sketch animation. Due to the failure to preserve visual appearance in CogVideo, Dynamicrafter, and FlipSketch, the "Dynamic Degree" metric in these methods lacks meaningful interpretation.

minor inaccuracies (the "smoke" is not grounded and the shell's point assignment is inaccurate), the final results remain robust and visually compelling. Fig. 7 demonstrates that, given a scene sketch, MoSketch generates diverse animation results by considering different object interactions or relative relationships based on varying text instructions. This capability greatly improves the diversity and flexibility of our approach. Fig. 8 shows the animation results of MoSketch in single-object situations. Thanks to the LLMbased motion plan module, MoSketch achieves large-range displacements in single-object animations.

The result of qualitative comparison is shown in Fig. 9. Due to the domain gap between natural images and sketches, and the lack of specialized training on sketch data, the results generated by the I2V methods Cogvideox and Dynamicrafter fail to preserve visual appearance of the input sketch, leading to chaos. The sketch animation method FlipSketch generates animation results in the sketch domain due to fine-tuning on sketch data, but fail to preserve visual appearance due to the raster representation of sketches. Live-Sketch preserves visual appearance due to the vector representation of sketches but struggles to model complex motion in multi-object animation. Our proposed method MoSketch proposed three effective modules to handle complex motion modeling, leading to vivid and realistic multiobject sketch animation.

**Quantitative Comparison**. Tab. 2 shows the quantitative comparisons of MoSketch and baselines. In "Textto-Video Alignment" and "Sketch-to-Video Alignment", MoSketch achieves superior performance. Due to inabil-



Figure 10. Qualitative ablation of MoSketch. Best view digitly.

#	setup	Text-to-Video Alignment	Sketch-to-Video Alignment	Motion Smoothing	Dynamic Degree
0	Full	0.218	0.914	0.977	0.283
1	w/o $\Delta Z_c$	0.212	0.955	0.959	0.083
2	w/o $\Delta Z_o$	0.212	0.909	0.964	0.266
3	w/o $\Delta Z_p$	0.203	0.971	0.971	0.200
4	w/o Object-aware	0.205	0.932	0.968	0.266
5	w/o CSDS	0.207	0.911	0.966	0.267

Table 3. **Quantitative ablation of MoSketch**. Note that Setup#1, Setup#3 and Setup#4 get high scores in "Sketch-to-Video Alignment" due to the lack of changes in objects' appearance (the shell does not explode).

ity to follow the complex instructions and preserve visual appearance, Cogvideox, Dynamicrafter and FlipSketch get low scores in "Text-to-Video Alignment" and "Sketch-to-Video Alignment". Live-Sketch preserves visual appearance because of the vector representation of sketches, but gets lower "Text-to-Video Alignment" score than MoSketch due to the inability to generate complex motions required in text instructions. For the evaluation of video quality, MoSketch achieves the smoothest motion. Compared to Live-Sketch, MoSketch's animations are of larger motions.

#### 4.3. Ablation Study of MoSketch

We analyze the effectiveness of LLM-based motion plan, motion refinement network and compositional SDS with several ablation studies. The qualitative and quantitative ablation study results are shown in Fig. 10 and Tab. 3.

The Need of Motion Planning. We eliminate the coarse-grained object motion  $\Delta Z_c$  defined by the generated motion plan (Setup#1), leading to nearly static external movements (the shell cannot be launched).

The Necessity of the two fine-grained motions. We separately remove the fine-grained object motion  $\Delta Z_o$  (Setup#2) and the fine-grained point motion  $\Delta Z_p$  (Setup#3). Without  $\Delta Z_o$ , the object external motion is not refined (the shell is not scaled up enough to explode). The



Figure 11. Limitations of MoSketch.

absence of  $\Delta Z_p$  directly results in the complete lack of internal motion within objects.

The Necessity of Object-aware Network. We replace our object-aware motion refinement network with the not object-aware one in Live-Sketch (Setup#4). Although the animation result aligns with the descriptions (the shell is launched), the lack of object-aware motion modeling in generative network results in insufficiently refined motion (the shell does not explode).

The Need of Compositional Optimization. We remove the SDS loss  $\{\mathcal{L}_{SDS-k}\}_{k=1}^{r}$  in Eq. (8) (Setup#5), only using  $\mathcal{L}_{SDS}$  to guide the complex motion modeling. Guided by the T2V diffusion model that struggles with modeling complex motions of multiple objects, the generated animations also lack details.

**Limitations**. Fig. 11 shows several limitations of our method: (1) While Fig. 6 illustrates that MoSketch can tolerate minor point assignment inaccuracies without significantly degrading the final results, a large number of errors can severely impact the output quality (Godzilla's tail is incorrectly attributed to "city"). (2) Coarse object motion derived from a highly incorrect motion plan (the goalkeeper should move towards the football) cannot be effectively corrected by the motion refinement network. (3) Since our animations are guided by a T2V model [34], which may be unaware of special motion such as "fight", the relative sketch animation result may not be generated successfully.

## 5. Conclusion

We propose MoSketch for multi-object sketch animation based on iterative optimization through SDS, without any other data for training. To tackle the two challenges: objectaware motion modeling and complex motion optimization, we propose four modules: LLM-based scene decomposition, LLM-based motion planning, motion refinement network and compositional SDS. Extensive experiments reveal that our proposed MoSketch achieves the superior performance than the SOTA methods in multi-object sketch animation. The ablation studies demonstrate the effectiveness and necessity of the proposed modules. Other experiments show the flexibility of MoSketch. MoSketch takes a pioneering step towards multi-object sketch animation, opening new avenues for future research and applications.

## References

- Hmrishav Bandyopadhyay and Yi-Zhe Song. Flipsketch: Flipping static drawings to text-guided sketch animations. In *CVPR*, 2025. 1, 2, 6, 7
- [2] Haoxin Chen, Menghan Xia, Yingqing He, Yong Zhang, Xiaodong Cun, Shaoshu Yang, Jinbo Xing, Yaofang Liu, Qifeng Chen, Xintao Wang, et al. Videocrafter1: Open diffusion models for high-quality video generation. arXiv preprint arXiv:2310.19512, 2023. 3
- [3] Richard C Davis, Brien Colwell, and James A Landay. Ksketch: a'kinetic'sketch pad for novice animators. In *CHI*, pages 413–422, 2008. 1, 2
- [4] Marek Dvorožnák, Wilmot Li, Vladimir G Kim, and Daniel Sýkora. Toonsynth: example-based synthesis of handcolored cartoon animations. ACM Transactions on Graphics, 37(4):1–11, 2018. 2
- [5] Hao Fei, Shengqiong Wu, Wei Ji, Hanwang Zhang, and Tat-Seng Chua. Dysen-vdm: Empowering dynamics-aware textto-video diffusion with llms. In *CVPR*, pages 7641–7653, 2024. 2
- [6] Rinon Gal, Yael Vinker, Yuval Alaluf, Amit Bermano, Daniel Cohen-Or, Ariel Shamir, and Gal Chechik. Breathing life into sketches using text-to-video priors. In *CVPR*, pages 4325–4336, 2024. 1, 2, 6, 7
- [7] Gege Gao, Weiyang Liu, Anpei Chen, Andreas Geiger, and Bernhard Schölkopf. Graphdreamer: Compositional 3d scene synthesis from scene graphs. In *CVPR*, pages 21295– 21304, 2024. 3, 6
- [8] David Ha and Douglas Eck. A neural representation of sketch drawings. In *ICLR*, 2018. 1
- [9] Li Hu. Animate anyone: Consistent and controllable imageto-video synthesis for character animation. In *CVPR*, pages 8153–8163, 2024. 3
- [10] Kaiyi Huang, Kaiyue Sun, Enze Xie, Zhenguo Li, and Xihui Liu. T2i-compbench: A comprehensive benchmark for open-world compositional text-to-image generation. Advances in Neural Information Processing Systems, 36:78723–78747, 2023. 3
- [11] Ziqi Huang, Yinan He, Jiashuo Yu, Fan Zhang, Chenyang Si, Yuming Jiang, Yuanhan Zhang, Tianxing Wu, Qingyang Jin, Nattapol Chanpaisit, et al. Vbench: Comprehensive benchmark suite for video generative models. In *CVPR*, pages 21807–21818, 2024. 7
- [12] Ziqi Huang, Fan Zhang, Xiaojie Xu, Yinan He, Jiashuo Yu, Ziyue Dong, Qianli Ma, Nattapol Chanpaisit, Chenyang Si, Yuming Jiang, et al. Vbench++: Comprehensive and versatile benchmark suite for video generative models. arXiv preprint arXiv:2411.13503, 2024. 7

- [13] Rubaiat Habib Kazi, Fanny Chevalier, Tovi Grossman, Shengdong Zhao, and George Fitzmaurice. Draco: bringing life to illustrations with kinetic textures. In *CHI*, pages 351–360, 2014. 2
- [14] Long Lian, Baifeng Shi, Adam Yala, Trevor Darrell, and Boyi Li. Llm-grounded video diffusion models. In *ICLR*, 2024. 3, 5
- [15] Han Lin, Abhay Zala, Jaemin Cho, and Mohit Bansal. Videodirectorgpt: Consistent multi-scene video generation via llm-guided planning. *arXiv preprint arXiv:2309.15091*, 2023. 2, 3, 4
- [16] Shilong Liu, Zhaoyang Zeng, Tianhe Ren, Feng Li, Hao Zhang, Jie Yang, Qing Jiang, Chunyuan Li, Jianwei Yang, Hang Su, et al. Grounding dino: Marrying dino with grounded pre-training for open-set object detection. In *ECCV*, pages 38–55. Springer, 2024. 4
- [17] Jiaxi Lv, Yi Huang, Mingfu Yan, Jiancheng Huang, Jianzhuang Liu, Yifan Liu, Yafei Wen, Xiaoxin Chen, and Shifeng Chen. Gpt4motion: Scripting physical motions in text-to-video generation via blender-oriented gpt planning. In *CVPR*, pages 1430–1440, 2024. 4, 5
- [18] William Peebles and Saining Xie. Scalable diffusion models with transformers. In *ICCV*, pages 4195–4205, 2023. 3
- [19] Ben Poole, Ajay Jain, Jonathan T Barron, and Ben Mildenhall. Dreamfusion: Text-to-3d using 2d diffusion. arXiv preprint arXiv:2209.14988, 2022. 2, 3
- [20] Jie Qin, Jie Wu, Weifeng Chen, Yuxi Ren, Huixia Li, Hefeng Wu, Xuefeng Xiao, Rui Wang, and Shilei Wen. Diffusiongpt: Llm-driven text-to-image generation system. arXiv preprint arXiv:2401.10061, 2024. 3
- [21] Leigang Qu, Shengqiong Wu, Hao Fei, Liqiang Nie, and Tat-Seng Chua. Layoutllm-t2i: Eliciting layout guidance from llm for text-to-image generation. In ACM MM, pages 643– 654, 2023. 3
- [22] Gaurav Rai and Ojaswa Sharma. Enhancing sketch animation: Text-to-video diffusion models with temporal consistency and rigidity constraints. arXiv preprint arXiv:2411.19381, 2024. 2
- [23] Gaurav Rai, Shreyas Gupta, and Ojaswa Sharma. Sketchanim: Real-time sketch animation transfer from videos. *Computer Graphics Forum*, 43(8):e15176, 2024. 2
- [24] Harrison Jesse Smith, Qingyuan Zheng, Yifei Li, Somya Jain, and Jessica K Hodgins. A method for animating children's drawings of the human figure. ACM Transactions on Graphics, 42(3):1–15, 2023. 1, 2
- [25] Eisung Sohn and Yoon-Chul Choy. Sketch-n-stretch: sketching animations using cutouts. *IEEE computer graphics and applications*, 32(3):59–69, 2010. 2
- [26] Jiaming Song, Chenlin Meng, and Stefano Ermon. Denoising diffusion implicit models. In *ICLR*, 2021. 2
- [27] Qingkun Su, Xue Bai, Hongbo Fu, Chiew-Lan Tai, and Jue Wang. Live sketch: Video-driven dynamic deformation of static drawings. In *CHI*, pages 1–12, 2018. 1
- [28] Sitong Su, Litao Guo, Lianli Gao, Hengtao Shen, and Jingkuan Song. Motionzero: Exploiting motion priors for zero-shot text-to-video generation. arXiv preprint arXiv:2311.16635, 2023. 4

- [29] Kaiyue Sun, Kaiyi Huang, Xian Liu, Yue Wu, Zihan Xu, Zhenguo Li, and Xihui Liu. T2v-compbench: A comprehensive benchmark for compositional text-to-video generation. *arXiv preprint arXiv:2407.14505*, 2024. 2
- [30] Ryo Suzuki, Rubaiat Habib Kazi, Li-Yi Wei, Stephen Di-Verdi, Wilmot Li, and Daniel Leithinger. Realitysketch: Embedding responsive graphics and visualizations in ar through dynamic sketching. In UIST, pages 166–181, 2020. 2
- [31] Zineng Tang, Ziyi Yang, Chenguang Zhu, Michael Zeng, and Mohit Bansal. Any-to-any generation via composable diffusion. Advances in Neural Information Processing Systems, 36, 2024. 3
- [32] Ye Tian, Ling Yang, Haotian Yang, Yuan Gao, Yufan Deng, Jingmin Chen, Xintao Wang, Zhaochen Yu, Xin Tao, Pengfei Wan, et al. Videotetris: Towards compositional text-to-video generation. arXiv preprint arXiv:2406.04277, 2024. 2, 3
- [33] Yael Vinker, Ehsan Pajouheshgar, Jessica Y Bo, Roman Christian Bachmann, Amit Haim Bermano, Daniel Cohen-Or, Amir Zamir, and Ariel Shamir. Clipasso: Semantically-aware object sketching. ACM Transactions on Graphics, 41(4):1–11, 2022. 6
- [34] Jiuniu Wang, Hangjie Yuan, Dayou Chen, Yingya Zhang, Xiang Wang, and Shiwei Zhang. Modelscope text-to-video technical report. *arXiv preprint arXiv:2308.06571*, 2023. 2, 3, 8
- [35] Xiang Wang, Hangjie Yuan, Shiwei Zhang, Dayou Chen, Jiuniu Wang, Yingya Zhang, Yujun Shen, Deli Zhao, and Jingren Zhou. Videocomposer: Compositional video synthesis with motion controllability. Advances in Neural Information Processing Systems, 36, 2024. 3
- [36] Yifan Wei, Wenkang Shan, Qi Zhang, Liuxin Zhang, Jian Zhang, and Siwei Ma. Real-time interaction with animated human figures in chinese ancient paintings. In *ICMEW*, pages 1–6. IEEE, 2024. 1
- [37] Jinbo Xing, Menghan Xia, Yong Zhang, Haoxin Chen, Wangbo Yu, Hanyuan Liu, Gongye Liu, Xintao Wang, Ying Shan, and Tien-Tsin Wong. Dynamicrafter: Animating open-domain images with video diffusion priors. In ECCV, pages 399–417. Springer, 2024. 3, 6
- [38] Dejia Xu, Hanwen Liang, Neel P Bhatt, Hezhen Hu, Hanxue Liang, Konstantinos N Plataniotis, and Zhangyang Wang. Comp4d: Llm-guided compositional 4d scene generation. arXiv preprint arXiv:2403.16993, 2024. 3, 4, 6
- [39] Zizheng Yan, Jiapeng Zhou, Fanpeng Meng, Yushuang Wu, Lingteng Qiu, Zisheng Ye, Shuguang Cui, Guanying Chen, and Xiaoguang Han. Dreamdissector: Learning disentangled text-to-3d generation from 2d diffusion priors. In ECCV, pages 124–141. Springer, 2024. 3
- [40] Ruolin Yang, Da Li, Honggang Zhang, and Yi-Zhe Song. Sketchanimator: Animate sketch via motion customization of text-to-video diffusion models. In VCIP, pages 1–5. IEEE, 2024. 2
- [41] Zhuoyi Yang, Jiayan Teng, Wendi Zheng, Ming Ding, Shiyu Huang, Jiazheng Xu, Yuanming Yang, Wenyi Hong, Xiaohan Zhang, Guanyu Feng, et al. Cogvideox: Text-to-video diffusion models with an expert transformer. *arXiv preprint arXiv:2408.06072*, 2024. 3, 6

- [42] Tingting Yin, Danli Wang, Kun Yu, and Hao Wang. Sketch animation techniques and applications based on mobile devices. In *APWCS*, pages 78–81. IEEE, 2010. 1, 2
- [43] Enting Ying, Tianyang Xiong, Gaoxiang Zhu, Ming Qiu, Yipeng Qin, and Shihui Guo. Wristsketcher: Creating 2d dynamic sketches in ar with a sensing wristband. *International Journal of Human–Computer Interaction*, pages 1–17, 2024.
- [44] Emilie Yu, Kevin Blackburn-Matzen, Cuong Nguyen, Oliver Wang, Rubaiat Habib Kazi, and Adrien Bousseau. Videodoodles: Hand-drawn animations on videos with scene-aware canvases. ACM Transactions on Graphics, 42 (4):1–12, 2023. 1, 2
- [45] Bohan Zeng, Ling Yang, Siyu Li, Jiaming Liu, Zixiang Zhang, Juanxi Tian, Kaixin Zhu, Yongzhen Guo, Fu-Yun Wang, Minkai Xu, et al. Trans4d: Realistic geometry-aware transition for compositional text-to-4d synthesis. arXiv preprint arXiv:2410.07155, 2024. 3
- [46] Shiwei Zhang, Jiayu Wang, Yingya Zhang, Kang Zhao, Hangjie Yuan, Zhiwu Qin, Xiang Wang, Deli Zhao, and Jingren Zhou. I2vgen-xl: High-quality image-to-video synthesis via cascaded diffusion models. arXiv preprint arXiv:2311.04145, 2023. 3
- [47] Xiaoyu Zhou, Xingjian Ran, Yajiao Xiong, Jinlin He, Zhiwei Lin, Yongtao Wang, Deqing Sun, and Ming-Hsuan Yang. Gala3d: Towards text-to-3d complex scene generation via layout-guided generative gaussian splatting. In *ICML*, 2024. 3, 6
- [48] Hanxin Zhu, Tianyu He, Anni Tang, Junliang Guo, Zhibo Chen, and Jiang Bian. Compositional 3d-aware video generation with llm director. In *NeurIPS*, 2024. 4



A jet take off one by one from the aircraft carrier, while another jet ascend into formation in the sky above.



Viewed from the front, an airplane lifts off from the runway, its wheels leaving the ground as it ascends into the sky.



A shell bursts from the cannon, leaving a trail of smoke as it hurtles through the air.



Viewed from the top, the car in the back is going to overtake the car in front on the open road.



Viewed from the back, a car navigates a curving road at the base of majestic mountains.



The road curves ahead as a jeep viewed from the back, travels in one direction while a motorcycle approaches from the opposite side.



A lone car maneuvers with steep cliffs and dense vegetation enclosing the winding road.



Two cyclists maneuver a curvy road, one leading while the other follows closely, capturing the thrill of the ride.



The motorcycle will jump over the oncoming car.



A person holding a spoonful of food close to their lips, ready to take a bite.



An excavator digging and scooping soil, forming a pile nearby.



A large crane lowers a container onto a heavily loaded cargo ship.



Two people rappel down a rope from a hovering helicopter.



Ice cubes splash into a glass of liquid, sending droplets and energy into the air, capturing a lively and refreshing moment.



A bottle is gracefully pouring liquid into a glass, the steady stream creating ripples in the drink.



Rollercoaster cart at the peak of a rollercoaster drops, bracing for the adrenaline-fueled descent.



The satellite shifts position as the Earth rotates, adjusting its pose to gather information from different angles.



The space shuttle begins its ascent, tilting slightly as it gains altitude, leaving a trail of flames near the launch pad.



A tank is firing shells towards a distant rectangular target, with a burst of energy smoke.



A vintage steam locomotive with an attached carriage is traveling along the tracks, exuding a sense of historic charm and industrial innovation.

A. .

A stealthy cat crouches low, its eyes locked on a tiny mouse, ready to spring forward with calculated precision. The mouse is going to escape.



Two playful cats stand on their hind legs, batting at a ball suspended between them in mid-air, engaged in a lively and fun interaction.



A curious cat jumps up to a table, reaching toward a bowl of food on the table with curiosity.



The person throws a frisbee through the air, and the dog sits poised, ready to sprint forward and catch it with its mouth in a swift motion.



The dog prepares to enjoy a delightful meal near the table, using its paws to carefully handle the chopsticks.



The dog reaches up to the table, anticipating a chance to grab the food within its reach.



The dog races up the stairs in pursuit of the cat, eager to catch up to its swift companion.

Ø



The seal on a stage prepares to leap toward the ball. The ball is throw to the seal.



The seal seats on a stage, juggling the ball skillfully on its nose, preparing to toss it into the air for an impressive trick.

The dolphin is mid-leap, heading toward the ball, preparing to nudge it forward with its snout, creating a playful splash.



The dolphin is jumping through the hoop from the water.



The eagle is in pursuit of the smaller bird, its wings stretched wide as it closes the distance in an intense aerial chase.



The larger fish opens its mouth wide as it chases the smaller fish, preparing to close the gap and capture its prey in an instant.



The giraffe is approaching the tree, preparing to eat from its high branches.



A goat grazes peacefully on the grass, its head lowered as it feeds on the vegetation.



Godzilla and the other monster face off, the rubble of the city forming a chaotic battlefield between them.



A horse-drawn carriage moves steadily forward, the driver urging the horses onward as the wheels turn across the terrain.



A person leads the horse gently by the reins, while the rider sits calmly, observing the surroundings as they move forward.



The horse gracefully soars over the obstacle, with the rider maintaining perfect balance and focus in mid-air on the horse.



The tiger leaps through the air, claws extended, as the fox darts away swiftly, trying to escape the predator's pursuit.

× A A

The drummer pounds the cymbals, bringing the song to a crashing halt. The guitarist strums a final chord, while the keyboardist focused on the melody.



The player soars through the air with a basketball, arm extended for an electrifying slam dunk to the hoop.



A climber dangles mid-air, navigating the rugged face of a towering mountain.



A climber ascends a rock wall, dynamically reaching for the next hold with determination.



A woman and a man sitting at a dining table, clinking glasses in a celebratory toast, enjoying their moment together.



A man gently feeds a woman across a dining table, offering her a spoonful of food with a caring expression.

A tot

A man pulls himself up on a horizontal bar, while a sporter lifts a barbell overhead in a deep squat position, showcasing strength and stability.



The scene depicts two individuals engaging in exercises: a man is performing dips on parallel bars, and a woamn is holding a plank position on the floor, demonstrating core strength.



The boxer throws a powerful punch at the heavy sandbag. The sandbags hoisted with brackets is swing.

ĸ

A woman throws a frisbee with force while a man dives to catch it mid-air.



No.

A soccer player executes an acrobatic bicycle kick, sending the ball flying towards the goal.

A soccer player skillfully dribbles the ball toward the goal as the goalkeeper prepares to defend.



Three athletes in action during a hurdle race: one running towards the hurdle, another mid-air clearing a hurdle, and the third already sprinting ahead, showcasing their athleticism and agility.



Three children enjoying a jump rope activity: two on either end turning the rope, while one jumps enthusiastically in the middle.



A worker climbing an inclined ladder, wearing protective gear and holding onto the ladder rungs securely, moving steadily upwards.



A bride and groom stand facing each other, holding hands. The bride's flowing gown and veil trail elegantly behind her, while the groom leans slightly forward, creating an intimate and heartfelt moment.



A person carefully stacking boxes, aligning them into a neat pile with focused attention.



A person sits alone, holding a fork poised over their food, savoring a moment of quiet dining.



Superman flies swiftly through the air, arm extended, racing to catch the falling man just moments before he hits the ground.



The workers in unison: one shovels debris, another operates a power tool, and a third transports materials with a wheelbarrow.