Dimitrios Stamatios Bouras dimitris.bouras@outlook.com Peking University Beijing, China Yihan Dai 2113826@mail.nankai.edu.cn Nankai University Tianjin, China

Yingfei Xiong xiongyf@pku.edu.cn Peking University Beijing, China Tairan Wang tairan.wang.22@ucl.ac.uk University College London London, United Kingdom

Abstract

While software requirements are often expressed in natural language, verifying the correctness of a program against such requirements is a hard and underexplored problem. Large language models (LLMs) are promising candidates for addressing this challenge, however our experience shows that they are ineffective in this task, often failing to detect even straightforward bugs. To address this gap, we introduce HoarePrompt, a novel approach that adapts fundamental ideas from program verification to natural language artifacts. Drawing inspiration from the strongest postcondition calculus, Hoare-Prompt employs a systematic, step-by-step process in which an LLM generates natural language descriptions of reachable program states at various code points. To manage loops, we propose fewshot-driven k-induction, an adaptation of the k-induction method widely used in model checking. Once program states are described, HoarePrompt leverages the LLM to assess whether the program, annotated with these state descriptions, conforms to the natural language requirements. For evaluating the quality of classifiers of program correctness with respect to natural language requirements, we constructed CoCoClaNeL, a challenging dataset of solutions to programming competition problems. Our experiments show that HoarePrompt improves the MCC by 62% compared to directly using Zero-shot-CoT prompts for correctness classification. Furthermore, HoarePrompt outperforms a classifier that assesses correctness via LLM-based test generation by increasing the MCC by 93%. The inductive reasoning mechanism contributes a 28% boost to MCC, underscoring its effectiveness in managing loops.

1 Introduction

A key objective of software quality assurance is assessing whether a program meets its intended requirements. In practice, these requirements are often written in natural language, geared towards human-to-human communication or designed as prompts for large language models (LLMs). Verifying the correctness of a program against natural language requirements is an inherently difficult and largely unexplored challenge.

This problem can be approached from multiple angles. One approach is to generate tests based on requirements using an LLM, and use these tests to check program correctness [5]. In a more general form, natural language requirements can be translated in formal

Sergey Mechtaev* mechtaev@pku.edu.cn Peking University Beijing, China

ones, and then used in conjunction with verification tools [16]. Despite the promise of these approaches, our experiments demonstrate that LLMs tend to generate incorrect or incomplete assertions when handling complex requirements, which reduces their accuracy. Another option is to directly employ LLMs to assess the program's conformance to requirements, relying on the fact that LLMs can reason about both natural language and code [33]. Our experiments show that the state-of-the-art LLMs struggle with this task, often failing to identify even simple bugs when assessing program correctness. We attribute this limitation to the models' inability to reason precisely about the intricacies of program semantics.

To address this gap, we introduce HoarePrompt, a program analysis approach for reasoning about program correctness w.r.t. natural language requirements that synergizes LLM reasoning techniques with fundamental ideas from program analysis and verification. In the core of this approach is the *natural Hoare triple*, a variant of the traditional Hoare triple [21] with pre- and postconditions expressed in natural language, for example,

{x is a full name} x = x.split()[0] {x is a first name}.

Inspired by the strongest postcondition calculus [14], HoarePrompt employs a step-by-step process to generate natural language descriptions of reachable program states at various points in the code. This is achieved by sampling *natural strongest postconditions (NSP)* from SP, our LLM-based natural Hoare triple completion model defining the conditional probability distribution:

SP(Post | Pre, C),

where Pre, Post are natural pre- and postconditions, *C* is a program fragment. Inspired by methods to enhance LLM reasoning about program execution [37], HoarePrompt uses these state descriptions to annotate a program, and then prompts an LLM to access if the annotated program aligns with the given requirements.

HoarePrompt's key novelty in comparison with traditional program analysis and verification is in using natural language as the medium of reasoning about program semantics, as opposite to, e.g., first-order logic [17] or monotonic functions over lattices [10]. This enables a direct application of HoarePrompt to assessing program correctness w.r.t. natural language requirements without hard and time-consuming formal modeling. Effectively, HoarePrompt bridging the gap between formal semantics and informal requirements. In comparison to previous techniques for reasoning about code with LLMs [28, 33, 37], HoarePrompt reasons about all reachable

^{*}Sergey Mechtaev is the corresponding author.

Dimitrios Stamatios Bouras, Yihan Dai, Tairan Wang, Yingfei Xiong, and Sergey Mechtaev



Figure 1: Annotating code with natural language descriptions of reachable program states, which are automatically inferred by HoarePrompt, enables an LLM to find a bug that is missed by the straightforward Vanilla prompt.

Table 1: Success rates for detecting the bug in Figure 1 via prompts with and without state annotations, using three LLMs, across 60 responses for each, with the temperature 0.5.

Model	Not Annotated	Annotated
Qwen2.5-7B	0%	11.7%
Qwen2.5-Coder-32B	15%	85%
Qwen2.5-72B	35%	85%

states simultaneously instead of individual concrete states. This enables HoarePrompt to operate statically, without executing the program and without reliance on provided failing tests.

Loops pose a fundamental challenge in program analysis and verification because they give rise to infinite execution paths [46]. Our experiments demonstrate that LLMs also struggle to summarize the semantics of complex loops, producing incorrect natural postconditions. To address this problem, we introduce a novel method, *few-shot-driven k-induction*, synergizing few-shot learning [4] with the idea of k-induction [15] widely used in model checking. This method starts with iteratively unwinding a loop k times to compute natural postconditions after each iterations. After that, it performs an induction inference step by prompting an LLM to compute the postcondition for the entire loop, using the computed natural Hoare triples for individual iterations as few-shot examples.

To evaluate HoarePrompt, we created CoCoClaNeL, a dataset of program and natural language requirement pairs, where some programs meet the requirements and others do not. All programs and requirements were published since January 2024, after the training cut-off date of many SOTA LLMs to prevent data leakage. The dataset consists of human-introduced bugs and challenging requirements to test the reasoning limits of SOTA LLMs. We formulated correctness assessment as a binary classification problem with two classes: correct and incorrect. Our experiments show that HoarePrompt, at the expense of a higher token use, improves the MCC by 62% compared to directly using Zero-shot-CoT prompts for correctness classification. Furthermore, HoarePrompt outperforms a classifier that assesses correctness via LLM-based test generation by increasing the MCC by 93%. The few-shot-driven *k*-induction mechanism contributes a 28% boost to MCC.

In summary, the paper makes the following contributions:

- HoarePrompt, the first program analysis approach using natural language as the medium for reasoning about program semantics.
- Few-shot-driven *k*-induction, the first approach that enhances LLM's ability to summarize loops.
- CoCoClaNeL, a challenging benchmark for program correctness classification.
- An empirical study of classifying program correctness w.r.t. natural language requirements that demonstrates effectiveness of HoarePrompt.

All code, scripts, and data necessary to reproduce this work are available at https://github.com/msv-lab/HoarePrompt.

2 Motivating Examples

To motivate our approach, we first show that annotating a program with natural language descriptions of reachable program states enhances LLM's reasoning about program correctness, and then show how our approach precisely summarizes loops.



Figure 2: Few-shot-driven *k*-induction unrolls the loop three times, computes the natural strongest postconditions (NSP) for each iteration sequentially, and uses the resulting natural Hoare triples as few-shot examples for inductively inferring the postcondition for the entire loop, which enhances precision compared to non-inductive inference, or only a single unrolling.

2.1 State Descriptions Enhance LLM Reasoning

Consider the following problem: "given an integer list, the task is to find the maximum product of any sublist." Figure 1 (left) presents a flawed implementation of Kadane's algorithm to solve this problem. The issue lies in incorrect indentation, which results in best_so_far being updated only once — after the loop ends instead of being updated during each iteration.

Despite the bug's simplicity, SOTA LLMs struggle to identify it consistently, therefore wrongly classifying the program as correct. Providing evidence that an LLM fails to solve a task is inherently challenging due to the model's non-deterministic behavior [40] and its sensitivity to prompt design [43]. To address these challenges, we made every effort to present objective evidence by crafting six distinct prompts: a straightforward (Vanilla) prompt, a Zero-shot-CoT prompt [30], an open-ended prompt [1], and combinations of these strategies, each containing containing the problem description and the code snippet. For each prompt, we generated 10 responses from three different LLMs, employing various temperature settings. More details about the experimental setup and results for this example can be found in the supplementary materials (Appendix A.1).

The results in Table 1 demonstrate that LLMs, using the above six prompts, labelled collectively as "Not Annotated", detect the bug with only a small probability. An example of an incorrect response for the Vanilla prompt in presented in Figure 1 on the left. HoarePrompt address this problem as follows. It first extracts the program's natural precondition by prompting an LLM to summarize the set of valid input values based on the problem description. In this case, the inferred precondition is {xs is a list of integers}. Then, it iteratively queries its natural strongest postcondition (NSP) model to propagate reachable state descriptions along the program's control flow graph (CFG). For example, computing the NSP of the first if statement based on the program's precondition will result in the following natural Hoare triple:

```
{xs is a list of integers}
if (not xs):
    return float('-inf')
{xs is a list of integers, and xs is not empty}
```

capturing that fact that if an execution reaches the program point after the if statement, the list is guaranteed to be non-empty.

HoarePrompt continues to propagate the states until it reaches the end of the program. Loops, which present a particular challenge, are handled via inductive reasoning as illustrated in Section 2.2.

Finally, HoarePrompt annotates the program with the reachable states at key program points (return statements, after top-level if statements and loops) as presented in Figure 1 on the right. Adding such annotations to the six prompts significantly increases LLM's success rate of correctness classification as shown in Table 1.



Figure 3: HoarePrompt succinctly describes program behaviour in human-centric terms, which helps to align formal semantics with informal requirements.

2.2 Inductively Reasoning About Loops

Reasoning about loops is challenging, because they induce infinite behaviours [46], and our experience shows that LLMs also struggle to summarize them. To alleviate this problem, we take inspiration for the k-induction technique [15] widely used in model checking, which first checks that the property holds for all states in the first k steps of the program's execution, and then proves that if a property holds for any k consecutive steps, then it holds for the next step.

To illustrate our adaptation of k-induction, which we refer to as *few-shot-driven* k-induction, consider the program with a loop in Figure 2, labelled as "Program". Assume that its precondition is given in "Precondition". Inferring its natural strongest postcondition (NSP) using the straightforward "Non-Inductive NSP Prompt" with Qwen2.5-72B results in an incorrect natural postcondition mistakenly stating the min_diff is the smallest absolute difference between any two consecutive elements in the list.

HoarePrompt unrolls the loop k times, with the semantics of each iteration represented by code snippets in "Iteration 1", …, "Iteration k". Then, it sequentially computes natural strongest postconditions for each iteration, using the postcondition of the previous iteration as the precondition of the next one (the first iteration uses the precondition of the entire loop). The resulting triples

{Precondition} Iteration 1 {Postcondition 1},

{Postcondition k-1} Iteration k {Postcondition k}

are used as few-shot examples to infer the postcondition of the entire loop in "Inductive NSP Prompt (k=3)". The intuition of this step is that LLMs generalize from few relevant examples [4], and the examples above are relevant by construction. As shown in the corresponding LLM response, the enhanced prompt enabled the LLM to correctly infer that min_diff is the smallest absolute difference between any element in the list and the first element.

Interestingly, unrolling the loop only once ("Inductive NSP Prompt (k=1)") did not help to correct the mistake, as the model failed to generalize from a single example. Based on our pilot study, we choose k = 3 as a trade-off between precision and cost.

2.3 Expressive Power of Natural Language

LLMs exhibit limitations in symbolic reasoning due to their reliance on natural language [48, 56]. Consequently, HoarePrompt avoids formal logical inference, opting instead for natural language as the reasoning medium. While this approach does not provide formal correctness guarantees, it generates structured informal proofs, which, as demonstrated in Section 5, help LLMs effectively align program semantics with informal requirements.

We hypothesize that the efficacy of this method stems from natural language's expressive power. An example in Figure 3 shows that Qwen2.5-72B computes a natural strongest postcondition for a code fragment, succinctly summarizing the variable sat using human-centric terms rather than formal execution semantics, leveraging its extensive training data. This expressivity is hard to achieve in symbolic logic due to its inherently limited vocabulary. More examples are given in the supplementary materials (Appendix A.3).

3 Background

Hoare logic [21] is a formalism for reasoning about program correctness, at the core of which are specifications called *Hoare triples*

$$\{\operatorname{Pre}\} C \{\operatorname{Post}\},\$$

meaning that the postcondition Post holds in any state reachable by executing the code *C* from an initial state in which the precondition Pre holds, provided that the code terminates. Pre- and postconditions are predicates over program states (mappings of variables to values) that are typically expressed in first-order logic [17].

Strongest postcondition calculus [14] automates verification using Hoare logic. The strongest postcondition (SP) of a program Cwith respect to a precondition Pre, denoted as sp(Pre, C), is the most precise logical formula describing all possible states reachable after executing C from a state satisfying Pre. Formally,

$$\models$$
 {Pre} C {Post} iff sp(Pre, C) \implies Post

The following algorithm for computing SP is defined compositionally for WHILE [39], a simple programming language that has only assignments (x := e), sequences (S_1 ; S_2), if statements, one loop instruction (while) and a single type (integer):

$$sp(\operatorname{Pre}, x := e) = \operatorname{Pre}[x \mapsto e]$$

$$sp(\operatorname{Pre}, S_1; S_2) = sp(S_1, sp(\operatorname{Pre}, S_2))$$

$$sp(\operatorname{Pre}, \text{if } b \text{ then } S_1 \text{ else } S_2) =$$

$$(sp(\operatorname{Pre}, S_1) \land b) \lor (sp(\operatorname{Pre}, S_2) \land \neg b)$$

$$sp(\operatorname{Pre}, \text{while } b \text{ do } S) =$$

$$(\operatorname{Pre} \land \neg b) \lor sp(sp(\operatorname{Pre} \land b, S), \text{while } b \text{ do } S)$$

The last rule, which handles loops, is recursively defined, which makes it hard to compute.

The k-induction method [15] applies the principle of mathematical induction for practical loop analysis. Let $P(s_i)$ denote the target property at loop state s_i after *i* iterations. The method consists of two phases. The base case verification checks that the target property $P(s_i)$ holds for the first *k* iterations:

$$\bigwedge_{i=0}^{k-1} P(s_i).$$

The inductive step proves that if the property holds for any k consecutive iterations, then it also holds for the next iteration:

$$\forall n \ge 0. \left(\bigwedge_{i=0}^{k-1} P(s_{n+i}) \right) \to P(s_{n+k})$$



Figure 4: HoarePrompt's correctness classification workflow.

4 HoarePrompt

We introduce the *natural Hoare triple*, a Hoare triple where preand postconditions are expressed in natural language (NL). To differentiate natural Hoare triples from traditional Hoare triples, we highlight sentences from NL with blue:

$\{\operatorname{Pre}\} C \{\operatorname{Post}\}.$

In analogy with the strongest postcondition calculus, we introduce the *natural strongest postcondition (NSP)*. The traditional algorithm sp(Pre, *C*) cannot be applied in the context of NL. Instead, we create SP, an LLM-based natural Hoare triple completion model defining a conditional probability distribution

SP(Post | Pre, Stmt).

Let $\llbracket \cdot \rrbracket : \mathbb{NL} \to 2^S$ capture the human interpretation of NL state descriptions as a mapping from sentences to sets of program states *S*. Then, the goal to achieve by SP to ensure plausible reasoning can be measured using the following objective function:

Definition 4.1 (NSP Objective Function). The objective function for SP is the cross-entropy loss between predicted postconditions and the traditional strongest postconditions computed over the interpretations of natural language preconditions:

$$\mathcal{L} = -\sum_{\text{Post}\in\text{NL}} \mathbb{I}(\llbracket\text{Post}\rrbracket \equiv \text{sp}(\llbracket\text{Pre}\rrbracket, C))\log \mathcal{SP}(\text{Post} \mid \text{Pre}, C),$$

where where $\mathbb{I}(\cdot)$ is the indicator function.

HoarePrompt applies SP to classify program correctness w.r.t. natural language requirements using the workflow depicted in Figure 4. First, it prompts an LLM to extract a precondition (a description of valid program inputs) from the requirements. Second, it traverses the program's control-flow graph (CFG), while sampling natural strongest postconditions from SP, starting from the precondition, for each code segments. Finally, it annotates key program points with the inferred reachable state descriptions, and prompts an LLM to check whether the code meets the requirements.

4.1 Precondition Extraction

HoarePrompt prompts an LLM to extract a precondition from the given requirements to identify the set of all valid inputs to the program. For example, for the problem description

"given N, write a function that finds the Nth Fibonacci number",



Figure 5: Computing NSP for an if-else statement.

and the function signature

def func(num),

an LLM will produce the precondition

{num is a non-negative integer}.

We implemented precondition extraction using few-shot learning (see details in supplementary materials Appendices B.6 and B.7).

4.2 NSP Computation

In principle, SP can be realized by fine-tuning an LLM to optimize the NSP objective function (Definition 4.1). Due to budget constraints, we opted instead to adapt an LLM through prompt engineering and in-context learning. Specifically, we curated a pilot dataset, distinct from our evaluation set, and carefully designed prompts and few-shot examples for Python programs by eyeballing the LLM's output on this dataset.

Simple Statements. Atomic operations such as assignments are processed by directly prompting an LLM to compute the postcondition. We use a dedicated prompt with few-shot examples, presented in supplementary materials Appendix B.8, that tasks the model to infer the updated state based on variable modifications while preserving relevant information from the precondition. Apart from that, we use dedicated prompts (in supplementary materials Appendices B.10 and B.11) to capture effects of return and print commands, since program correctness often depends on them.

Compound Statements. Similar to the traditional sp, SP is defined compositionally, which enables it to precisely reason about complex programs by breaking them down into simpler fragments. For example, given a sequence of statements S_1 ; S_2 , SP is computed by first completing natural Hoare triple {Pre} S_1 {Post}, and then its postcondition Post serves as the precondition for S_2 . To reduce the

number of LLM queries, we group a configurable number of atomic statements together using a dedicated prompt (in supplementary materials Appendix B.9).

If Statements. Figure 5 shows how if-else statements are processed by HoarePrompt. Given a precondition $\{Pre\}$ and a statement if $b: S_1$ else: S_2 , it first samples preconditions for the if and else branches:

 $\operatorname{Pre_{if}} \sim \mathcal{SP}(\,\cdot \mid \operatorname{Pre, assert} b), \ \operatorname{Pre_{else}} \sim \mathcal{SP}(\,\cdot \mid \operatorname{Pre, assert} \neg b)$

Then, it samples NSPs for each branch:

$$\text{Post}_{if} \sim S\mathcal{P}(\cdot | \text{Pre}_{if}, S_1), \text{Post}_{else} \sim S\mathcal{P}(\cdot | \text{Pre}_{else}, S_2)$$

Finally, it uses a dedicated prompt to merge $Post_{if}$ and $Post_{else}$ into a single postcondition Post, which will hold after the loop. Prompts used for these operations are given in supplementary materials Appendices B.14 to B.16.

Loop Statements. HoarePrompt reasons about loops using our few-shot-driven *k*-induction method. For a while statement while *b* : *S* and a precondition Pre, it first samples a precondition for the loop body, and a postcondition for the first iterations:

$$\operatorname{Pre_{while}} \sim SP(\cdot | \operatorname{Pre,assert} b), \operatorname{Post}_1 \sim SP(\cdot | \operatorname{Pre_{while}}, S).$$

Then, it continues to unwind the loop k - 1 times, sequentially computing the following natural pre- and postconditions for each iteration:

$$\operatorname{Pre}_{i} \sim S\mathcal{P}(\cdot | \operatorname{Post}_{i-1}, \operatorname{assert} b), \operatorname{Post}_{i} \sim S\mathcal{P}(\cdot | \operatorname{Pre}_{i}, S),$$

where $i \in [2, 3, ..., k]$.

Finally, the NSP for the whole while statement is computed using our inductive prompt that includes the natural Hoare triples

$$\left\{\left\{\operatorname{Pre}_{i}\right\} S\left\{\operatorname{Post}_{i}\right\}\right\}_{i\in[1,2,\ldots,k]}$$

as few-shot examples. This process is illustrated in Figure 2 for a for statement, which is handled accordingly.

Many programming languages allow iterations over a collection, e.g., the for loop in Python. The challenge of handling such iteration constructs is that they are implemented using implicit iterators, which store internal states updated at each iteration. Since iterators are not explicit variables, LLM tends to not include them when producing NSPs. Therefore, when dealing with for loops and iterators, in addition to the states of other variables, we explicitly model the state of the iterator.

Our modeling of Python's iterators involves maintaining the index of the next element of the iterator, which increments by 1 with each call to next(). Our natural language descriptions of program states refer to elements from the iterator as "the {index}th elements of the iterator", where "{index}" represents our modeled index, and the description of the iterator itself is always accompanied with the description of the current index representing its state. If an iterator is used across loops, its index also need to be summarized via k-induction together with other parts of the state.

For a loop for item in I, to accurately reflect the additional changes of both the iterator and the index for at the start of each iteration, the precondition for the i-th iteration is sampled as:

$$\operatorname{Pre}_i \sim S\mathcal{P}(\cdot | \operatorname{Post}_i, \operatorname{stmt}_{\operatorname{iter}}),$$



Figure 6: Computing NSP for the call of input() for stdin.

where
$$i \in [1, 2, ..., k]$$
, Post₀ = Pre, stmt_{iter} is

where I_iter is an iterator obtained from I and index is initialized to 0. For commonly used loops over lists or ranges of elements suuch as range(0,n), we directly refer to the index of list without modeling the semantics of next() for simplicity.

The supplementary materials include our prompts for computing preconditions of the loop body (Appendices B.17 and B.19), for handling while and for loops transitions (Appendices B.18 and B.20), and for inductive inference (Appendices B.21 and B.23).

Exceptions Handling. Given a precondition Pre, and a try-except statement

try: α except $E_1: \beta_1$ except $E_2: \beta_2, \ldots$ except $E_m: \beta_m$,

we first sample the NSP for the try-block:

Post_{try} ~
$$S\mathcal{P}(\cdot | \operatorname{Pre}, \alpha)$$
,

and then the NSPs for different exception handling blocks:

Post_i ~ $SP(\cdot \mid \text{``variables may take arbitrary values''}, \beta_i)$.

Finally, we merge $Post_{try}$, $Post_1$, $Post_2$, ..., $Post_m$ using a prompt provided in the supplementary materials (Appendix B.12). Note that, due to the complexity of handling nonlinear control flow, the NSP computation for exception handling blocks does not inherit any preconditions here, assuming that the state may be arbitrary.

Input Stream. Figure 6 shows how data from the standard input (stdin) is processed by HoarePrompt. When programs read from stdin, the precondition extraction explicitly describes the expected structure and content of the stdin based on the given problem description. So, the precondition would clearly indicate that stdin contains these inputs in that specific order. Every time a postcondition for a statement reading stdin is sampled as

Post ~
$$SP(\cdot | Pre, x = input())$$
,

the description of the stream state in Post will be updated accordingly. After all data is read, the state of the stream is described as "stdin is empty". Note that this modeling applies only to noninteractive programs, where stdin is predetermined and does not depend on the execution of the program.

4.3 Correctness Classification

Let *R* be the natural language requirement, *P* be the program to be evaluated, $D = \{(R_1, P_1, y_1), (R_2, P_2, y_2), \dots, (R_n, P_n, y_n)\}$ be a labeled dataset, where $y_i \in \{\text{Correct, Incorrect}\}$ represents whether program P_i satisfies requirement R_i . The problem of classifying correctness w.r.t. natural language requirements can be formalized as the task of learning a function $f : (R, P) \rightarrow \{\text{Correct, Incorrect}\}$.

In this work, we investigate several classification functions based on NSP, as well as alternative ideas.

HoarePrompt: Given R and P, HoarePrompt first annotates key program points with descriptions of reachable states computed using SP. Specifically, it adds annotations as comments after toplevel if and loop statements. Apart from that, it adds descriptions of returned and printed values after return and print statements, as these values are often used to assess correctness. An example of an annotation program is given in Figure 1. The annotated program is passed alongside R to an LLM via our classification prompt. The supplementary materials contain the classification prompts for single- and multi-function programs (Appendices B.4 and B.5).

HoarePrompt (No Unroll): We also implemented a variant of HoarePrompt that employs a non-compositional approach to computing the NSP for loops by prompting an LLM to infer the postcondition of the entire loop directly within a single LLM query. The prompts applied in this approach are given in the supplementary materials (Appendices B.22 and B.24).

Vanilla: Given *R* and *P*, it directly asks an LLM to classify program correctness using a simple prompts given in the supplementary materials (Appendix B.2).

Zero-shot-CoT: Our Zero-shot-CoT [30] prompt extends the Vanilla by triggering chain-of-thought reasoning [52] by adding the "think step-by-step" instruction. The prompt is given in the supplementary materials (Appendix B.1).

Tester: As an alternative to static reasoning, we also employed testing for classifying program correctness. Specifically, this method first generates tests based on R with an LLM using the testing prompt adapted from AgentCoder [23], executes P on the generated tests, and classifies it as correct iff it passes the tests.

5 Evaluation

Our experiments address these research questions:

- **RQ1:** How does the classification performance of HoarePrompt compare to other techniques?
- **RQ2:** How does few-shot-driven *k*-induction impact HoarePrompt's effectiveness?
- **RQ3:** How does the LLM token use of HoarePrompt compare to other techniques?

We evaluated five correctness classifiers defined in Section 4.3. For that, we selected three representative open-weight LLMs from Qwen [18] family: Qwen2.5-7B, a popular smaller model, Qwen2.5-Coder-32B, a model specialized for coding tasks, and Qwen2.5-72B, demonstrating performance comparable to GPT-4o-mini [47].

All experiments were conducted in a virtual machine with a AMD EPYC 7543 64-bit CPU, two cores and 16GB of RAM.

5.1 CoCoClaNeL Dataset

Although there exist numerous datasets of natural language requirements [2, 20], some including incorrect implementations [49], we could not use most of them due to potential data leakage, since memorization of correct solutions will significantly impact LLM reasoning [13, 53]. Apart from that, we required not-trivial requirements and subtle bugs to thoroughly evaluate the ability of LLMs to reason about program correctness.

We constructed a benchmark CoCoClaNeL (<u>Code Correctness</u> <u>Classification w.r.t. Natural Language</u> requirements). It consists of 645 problem-solution pairs from Codeforces programming contests that took place in the first half of 2024, with solutions labelled as correct or incorrect by the Codeforces' internal testing system. Totally, 322 of the solutions (49.9%) are incorrect. This benchmark meets the criteria above, with all problems and solutions being released since January 2024, after the cut-off data of many SOTA LLMs, and the problems are challenging, have unambiguous descriptions, and solutions to these problems are rigorously tested to find subtle bugs [24].

To construct such a benchmark, we crawled the Codeforces database, using the submission with the verdict "Accepted" as correct, and those with the verdict of "Wrong Answer" as incorrect. These verdicts were assigned by the Codeforces' internal testing system. To capture subtle and challenging coding errors, we specifically included incorrect submissions that immediately preceded correct ones, hypothesizing that these would likely contain nuanced mistakes. Problems with no correct submissions were excluded to ensure that a reference solution is always available. Additionally, for each problem, when available, we included one submission with a test pass rate near 50% and one with only a single failing test case. Additional details, including the distribution of the difficulty levels of the selected problems, are provided in the supplementary materials (Appendix A.4).

5.2 Controlling Variance in LLM Responses

We repeated experiments multiples time to ensure statistical reliability in the presence of LLM non-determinism [40]. Our method for determining the rerun count accounts for both the LLM's confidence and its consistency across queries. To estimate the LLM's confidence, we followed the approach outlined by Xiong et al. [54]. Given a binary response (Correct or Incorrect), the LLM assigns a log-probability log P(Y), which is converted into a confidence score $\exp(\log P(Y))$. We aggregate confidence across multiple reruns using the Avg-Conf method [54]:

$$C_{\text{avg-conf}} = \frac{\sum_{i=1}^{M} \mathbb{I}(Y_i = Y) \cdot C_i}{\sum_{i=1}^{M} C_i}$$

where Y_i is the *i*-th response, C_i its confidence score, and $\mathbb{I}(Y_i = Y)$ an indicator for majority agreement.

Table 2: Performance of classifiers of program correctness w.r.t. natural language requirements and their token use across three
LLMs evaluated on CoCoClaNeL. HoarePrompt significantly improves the MCC in comparison with baselines at the expense of
a higher token use. HoarePrompt without loop unrolling represents a trade-off between classification quality and token cost.

Model	Classifier	Correctness Classification Quality Metrics					Tokens (Millions)			
Model		MCC	∆MCC	BA	TPR	FNR	FPR	IT	OT	TT
Qwen2.5-7B	Vanilla	0.055		0.521	0.193	0.807	0.151	1.8	0.8	2.6
	Zero-shot-CoT	0.085	+54.5%	0.543	0.563	0.437	0.478	2.1	1.3	3.4
	Tester	0.109	+98.18%	0.519	0.051	0.949	0.012	1.7	3.8	5.5
	HoarePrompt	0.159	+189.1%	0.577	0.700	0.300	0.546	205.1 (93.9)	31.9	237.1 (125.9)
	HoarePrompt no unroll	0.119	+98.18%	0.558	0.666	0.334	0.550	19.9 (12.3)	3.4	23.4 (15.7)
	Vanilla	0.137		0.553	0.233	0.767	0.128	1.9	0.9	2.8
0	Zero-shot-CoT	0.123	-10.22%	0.560	0.438	0.562	0.318	2.4	1.5	3.9
Qwen2.5- Coder-32B	Tester	0.096	-29.93%	0.518	0.055	0.945	0.019	1.9	3.3	5.2
	HoarePrompt	0.231	+68.61%	0.616	0.593	0.407	0.362	186.5 (88.2)	42.6	229.1 (130.8)
	HoarePrompt no unroll	0.158	+15.04%	0.579	0.571	0.429	0.412	19.2 (11.6)	4.4	23.6 (15.9)
	Vanilla	0.169		0.578	0.382	0.618	0.226	1.7	0.9	2.6
	Zero-shot-CoT	0.193	+14.20%	0.593	0.714	0.286	0.527	2.0	1.3	3.2
Qwen2.5-72B	Tester	0.131	-22.49%	0.522	0.052	0.948	0.007	1.9	3.8	5.6
	HoarePrompt	0.259	+53.25%	0.629	0.667	0.333	0.409	163.5 (78.7)	32.5	196.0 (111.2)
	HoarePrompt no unroll	0.231	+36.69%	0.615	0.618	0.382	0.387	19.3 (11.8)	3.8	23.1 (15.6)

Abbreviations: MCC = Matthews Correlation Coefficient, \triangle MCC: Relative MCC Improvement over Vanilla, BA = Balanced Accuracy, TPR = True Positive Rate, FNR = False Negative Rate, FPR = False Positive Rate, IT = Input Tokens, OT = Output Tokens, TT = Total Tokens. Parentheses in IT and TT for HoarePrompt classifiers indicate token counts excluding few-shot learning examples, which can be eliminated via fine-tuning.

Let *P* denote the consistency of the LLM's response, representing the probability that a response for a given program remains the same across different runs. If the dataset consists of *X* programs, performing *R* reruns results in an effective dataset size of $N = R \cdot X$. To achieve a confidence level *C* with a margin of error ϵ , we model the consistency rate as a binomial distribution with mean *P* and variance P(1 - P)/N. The margin of error is given by:

$$\epsilon = Z \sqrt{\frac{P(1-P)}{N}}, \quad N = \frac{Z^2 P(1-P)}{\epsilon^2}, \quad R = \frac{N}{X}$$

where *Z* is the critical value for *C* (e.g., Z = 2.33 for 98%). For our dataset, with 645 problem solution pairs, 0.963 average measure response confidence, 0.98 desired confidence level and 1% margin of error, the calculations yielded R = 3, meaning each experiment has to be repeated three times.

5.3 RQ1: Classification Performance

In the first research question, we examine whether structural reasoning with descriptions of reachable states helps HoarePrompt improve LLMs' ability to evaluate program correctness compared to other techniques. By systematically tracking program states through HoarePrompt, we hypothesize that structured reasoning will enhance correctness classification.

To measure classification quality, we adopted the Matthews Correlation Coefficient (MCC) as it considers all four components of the confusion matrix, and produces more reliable statistical results than F1 score [9]. Besides MCC, we also report other standard classification metrics such as Balanced Accuracy, True Positive Rate (TPR), False Negative Rate (FNR), and False Positive Rate (FPR). We say that a classification result is a true positive if a correct program is classified as correct.

Table 2 shows the results for each model. In comparison with LLM-based baselines, Vanilla and Zero-shot-CoT, HoarePrompt consistently demonstrated higher classification quality. On average, HoarePrompt improves the MCC by 62% over Zero-shot-COT and 80% over Vanilla. *HoarePrompt's* impact is most pronounced in smaller models. The most significant improvement of MCC is in Qwen2.5-7B, being 87% over Zero-shot-COT and 189% over Vanilla. For Qwen2.5-72B, MCC improves by 34% and 53% over the Zero-shot-CoT and Vanilla respectively.

Similar improvement is observed across other classification metrics. HoarePrompt's TPR is 14.4% higher than Zero-shot-COT and 142.8% higher than Vanilla. HoarePrompt also reduces the FNR compared to Zero-shot-COT and Vanilla, however it comes with an increase in FPR to 0.439, slightly lower than Zero-shot-COT (0.441) but higher than Vanilla (0.168).

HoarePrompt also outperformed the Tester classifier. On average, its MCC is 93% higher than that of Tester. Moreover, Tester exhibits an extremely low True Positive Rate of only 0.052, meaning it correctly identifies just 5.2% of correct programs. This suggests that the expected output oracles inferred from the requirements are incorrect, leading to misclassifications of correct programs as incorrect. This phenomenon is illustrated in an example given in the supplementary materials (Appendix A.2).

RQ1: *HoarePrompt* consistently outperforms the baselines in terms of classification quality across all LLMs, achieving an average improvement of **62**% in MCC over Zero-shot-COT, **80**% over Vanilla and **93**% over Tester.

These results confirm that incorporating structured reasoning into program correctness assessment substantially enhances an LLM's ability to assess correctness, particularly benefiting smaller models with weaker inherent reasoning capabilities.

5.4 RQ2: Impact of Inductive Reasoning

Loops introduce complexity for reasoning about programs. Hoare-Prompt mitigates this complexity by inductively reasoning about loops using our novel few-shot-driven k-induction technique. This technique involves unrolling loops k times, with k = 3 in our experiments, before generalizing the final state.

This question investigates whether loop unrolling enhances correctness classification quality. To measure the impact of our fewshot-driven k-induction algorithm, we compare HoarePrompt's classification performance with that of HoarePrompt (no unroll) that summarizes loops within a single step.

As shown in Table 2, the few-shot-driven *k*-induction technique provides a significant additional performance gains, improving the MCC by an average of 27.9% over the non-inductive version (*HoarePrompt* no unroll) on average. Specifically, it improves MCC by 33.6% in Qwen2.5-7B, 45.3% in Qwen2.5-Coder-32B, and 12.1% in Qwen2.5-32B. Even without unrolling, HoarePrompt demonstrates the second best result among the studied classifiers.

RQ2: Few-shot-driven k-induction enhances classification performance across all models, improving the MCC by an average of **27.9%** over the non-inductive version of HoarePrompt.

These results suggest that reasoning about loops is indeed a challenge for LLMs, and few-driven k-induction effectively alleviates this challenge by inferring more precise loop postconditions.

5.5 RQ3: Token Usage

Since HoarePrompt involves multiple LLM queries, it consumes more tokens than direct LLM prompts [34]. The goal of this question is quantify this increase and investigate the trade-off between token use and classification quality.

Table 2 provides the total token usage across classifiers and models for the 645 problem-solution pairs of the CoCoClaNeL. For each classifier, we measured the input tokens (IT), the output tokens (OT), and total tokens (TT). As explained in Section 4.2, we chose to implement our natural strongest postcondition computation using prompt engineering with few-shot learning examples due to budget constraints. Tokens representing these hard-coded examples are repeatedly sent to an LLM during the algorithm iterations; in principle, they can be eliminated via fine-tuning. Because of that, for the HoarePrompt variants, we also report the number of "essential" input and total token, in parentheses, that excludes hard-coded few-shot example tokens.

On average, HoarePrompt consumes 81.6 times more tokens than Vanilla (45 times when excluding non-essential tokens), 61.9 times more tokens than Zero-shot-CoT (33.9 times more when excluding non-essential tokens), and 39.7 times more tokens than Tester (21.6 time more, when excluding non-essential tokens).

A key reason for the increased token usage is our inductive reasoning algorithm (few-shot-driven *k*-induction) that performs loop unrolling. On average, it requires 8.4 times extra tokens (6.8 times extra when excluding non-essential tokens) the tokens than the non-inductive variant. Thus, the few-shot k-induction is more suitable for situations when classification accuracy is prioritized over cost. The non-inductive version, HoarePrompt no unroll, represents a practical trade-off by retaining a substantial performance boost (27% better than the top performing approach, Zero-shot-COT) while consuming 87% fewer tokens than full unrolling, which is only 5.7 times more (3.5 times more, when excluding non-essential tokens) than Zero-shot-COT.

RQ3: HoarePrompt's significant performance boost comes at the expense of an average token usage increase by 62 times (34 times when excluding non-essential tokens that can be eliminated via fine-tuning) compared to the most accurate baseline, Zero-shot-COT. The version of HoarePrompt without unrolling represents a practical trade-off between classification quality and cost, demonstrating the second best performance, while consuming 87% less tokens than the main variant.

6 Discussion

HoarePrompt introduces a new paradigm of structurally reasoning about programs in natural language. Although it does not guarantee correctness, it demonstrates a significant increase in the correctness classification accuracy w.r.t. natural language requirements by bridging the gap between formal semantics and informal requirements. Incorporating techniques like symbolic CoT [56] may help further enhance reasoning and provide formal guarantees.

Previous research showed that formal proofs can be effectively constructed by following steps of informal proofs [26]. Thus, Hoare-Prompt can serve as the first step in the process of automating formal software verification. Similarly, state description computed by HoarePrompt may enhance testing by increasing test coverage and producing more precise oracles.

Shi et al. [44] proposed generating natural language outlines as a new method for interacting between AI assistants and human developers. Employing HoarePrompt will help to produce outlines that more precisely reflect program semantics, and therefore enhance human-AI interaction.

A limitation of HoarePrompt, especially when employing the fewshot-driven *k*-induction, is a high token consumption. Although a comparable balance between cost and performance is shared by many agentic systems [34], and we show that the token use can be significantly reduced via potential fine-tuning, or by disabling unrolling, we believe more research is required to reduce the cost. Applying prompt compression [27] or grouping several statements during compositional reasoning are promising directions.

Our implementation has limitations in handling program semantics, include handling variable scope, side effects, complex data structures, and multi-function analyses. Enhancements in state tracking for mutations and data flow, as well as using function postconditions as preconditions in interdependent function analyses, represent directions for future improvement.

7 Threats of Validity

LLMs are inherently nondeterministic [40], leading to varied responses. To address this, we employed multiple reruns per sample with confidence-based sampling to ensure robust performance estimates. Although further reruns could slightly refine our results, the current methodology provides high-confidence evaluations.

Main threats to external validity are that the selected dataset may not generalize to other programs, or that performance enhancements will not generalize to other LLMs. To avoid data leakage, we constructed a new dataset from recent Codeforces competition problems, ensuring challenging, human-authored, and varied submissions. Despite efforts to minimize biases, future studies on alternative datasets could further validate generalizability and performance trends. Apart from that, real-world requirements contain ambiguities, which are typically not present in programming competition problems. Techniques like ClarifyGPT [35] that detects ambiguities in informal requirements may address this concern.

We evaluated HoarePrompt across models of diverse sizes (7B to 72B), including Qwen-32B-Coder, a model specialized for coding tasks. This broad spectrum enhances generalizability; however, different LLM architectures may yield varying results. Nevertheless, observed trends suggest broad applicability, especially relevant given industry shifts toward proprietary small and mid-sized models [7]. Evaluating HoarePrompt on larger and more powerful models beyond the Qwen family may help assess its scalability and effectiveness in leveraging more advanced reasoning capabilities.

8 Related Work

HoarePrompt's contributions are relevant to works on reasoning about code with LLMs, LLM-assisted testing and verification.

Reasoning About Code with LLMs. Many generic approaches have been introduced to realize effective chain-of-though (CoT) reasoning [52]. We employed Zero-shot-CoT [30], a popular automation of CoT, as a baseline in our experiments. CJ-Eval [60] uses LLMs as judges of program correctness applying an approach equivalent to our baseline Vanilla prompt (Section 4.3). Since CJ-Eval is based on a widely-used Apps dataset [20], which is subject to data leakage, we constructed a new dataset CoCoClaNeL. A large body of work focused on reasoning about concrete execution states. Zhang et al. [59] fine-tuned LLMs with concrete execution states to improve their ability to track execution faithfully. Similarly, NExT [37] enhances debugging using programs annotated with concrete execution traces. CodeMind [33] includes a "specification reasoning" task that we measure how including test data in the specification helps the model generate the correct code. REval [6] evaluates runtime behaviour reasoning capabilities, specifically consistency in intermediate state prediction by analyzing variable states at specific execution points. The key difference of HoarePrompt is that it reasons about not individual executions but potentially infinitely many executions, without relying of specific inputs.

LLM-Assisted Formal Verification. Recent works on LLM-assisted verification focus on translating natural language specifications into formal verification conditions, relying on external theorem provers or SMT solvers [16]. Marmaragan [11] synthesizes formal Ada/SPARK contracts directly from natural language. Similarly, SynVer [36] biases LLM-generated C code towards verifiability by producing assertions and invariants, subsequently verified by tools like Coq or the Verified Software Toolchain (VST). LLMLIFT [3] integrates LLMs into verified compilation, generating proof sketches alongside code translation, with formal verification performed via SMT solvers. Stanford et al. [29] introduce Proof-Carrying Code Completions (PC3), prompting LLMs to produce Dafny [31] programs accompanied by machine-checkable correctness proofs, automating verification through Dafny. While these approaches embed formal verification into LLM-driven code generation pipelines, they fundamentally rely on external verification systems such as Dafny, Coq [51], or Z3 [12]. Despite the promise of these methods, they have shown limited scalability, with Marmaragan achieving only 50.7% correctness in its generated Ada/SPARK contracts [11] and Endres et al. [16] reporting that even with optimized prompting, only 77% of LLM-generated postconditions were verifiable. Hoare-Prompt employs an alternative approach of constructing structured informal proofs in natural language, leveraging its expressive power and flexibility, for classifying program correctness. Following previous work [26] such informal proofs might be translated into formal once to automate formal verification.

LLM-Based Automated Test Generation. Recent works [8, 32, 42, 58] have employed LLMs for automated test generation. Apart from that, the analysis of LLM-generated test outcomes has been used to facilitate program synthesis tasks [55], exemplified by CODET [5], AgentCoder [23], CodeCoT [22], and CoCoST [19]. While Hoare-Prompt is designed to solve a different task – classifying program correctness w.r.t. natural language requirements. Section 5 shows that directly using LLM-generated tests for correctness classification, embodied in our *Tester* baseline adopting AgentCoder's approach [23], suffers from high false negative rate, because LLM fail to infer precise assertions for complex requirements. We believe ideas of HoarePrompt can be synergized with testing to enhance accuracy and reduce cost.

Competition-Level Benchmarks. Recent studies reveal significant data leakage in widely used LLM benchmarks, inflating model performance due to test-training overlaps [13, 38]. Several new benchmarks, such as LiveCodeBench [25], CodeElo [41], ProBench [57], and USACO-based evaluations [45], mitigate leakage by incorporating recent programming competition problems. However, these benchmarks primarily assess code generation capabilities and do not provide solution submissions with explicit correctness labels. In contrast, CoCoClaNeL specifically targets correctness classification by offering labeled problem-solution pairs sourced from Codeforces 2024 contests, enabling evaluation of LLMs on their execution-state reasoning capabilities rather than memorization or test-based validation alone.

9 Conclusion

In this work, we introduced HoarePrompt, a novel approach leveraging LLMs to assess program correctness against natural language requirements. Unlike traditional verification and testing techniques that depend on external formal tools or concrete test executions, HoarePrompt systematically applies natural language-based structural reasoning. By adapting strongest postcondition calculus into

natural language and introducing few-shot driven k-induction, HoarePrompt computes natural strongest postconditions at key program points. Our evaluation demonstrates significant performance improvements in classification quality, with HoarePrompt increasing the MCC by 62% over Zero-shot-CoT, 80% over Vanilla prompting, and 93% over an LLM testing-based classifier. Our novel k-induction further enhances performance, yielding an average MCC improvement of 28% compared to a non-inductive approach. Although these improvements entail higher token consumption, the no-unroll variant provides a practical trade-off, achieving a 27% MCC improvement over Zero-shot-CoT while using substantially fewer tokens than the standard HoarePrompt version.

References

- [1] Simran Arora, Avanika Narayan, Mayee F Chen, Laurel Orr, Neel Guha, Kush Bhatia, Ines Chami, Frederic Sala, and Christopher Ré. 2022. Ask me anything: A simple strategy for prompting language models. arXiv preprint arXiv:2210.02441 (2022).
- [2] Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, and Charles Sutton. 2021. Program Synthesis with Large Language Models. arXiv preprint arXiv:2108.07732 (2021).
- [3] Sahil Bhatia, Jie Qiu, Niranjan Hasabnis, Sanjit A. Seshia, and Alvin Cheung. 2024. Verified Code Transpilation with LLMs. arXiv:2406.03003 [cs.PL] https: //arxiv.org/abs/2406.03003
- [4] Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. Advances in neural information processing systems 33 (2020), 1877–1901.
- [5] Bei Chen, Fengji Zhang, Anh Nguyen, Daoguang Zan, Zeqi Lin, Jian-Guang Lou, and Weizhu Chen. 2022. Codet: Code generation with generated tests. arXiv preprint arXiv:2207.10397 (2022).
- [6] Junkai Chen, Zhiyuan Pan, Xing Hu, Zhenhao Li, Ge Li, and Xin Xia. 2024. Reasoning Runtime Behavior of a Program with LLM: How Far Are We? arXiv:2403.16437 [cs.SE] https://arxiv.org/abs/2403.16437
- [7] Lihu Chen and Gaël Varoquaux. 2024. What is the role of small models in the llm era: A survey. arXiv preprint arXiv:2409.06857 (2024).
- [8] Yinghao Chen, Zehao Hu, Chen Zhi, Junxiao Han, Shuiguang Deng, and Jianwei Yin. 2024. Chatunitest: A framework for llm-based test generation. In Companion Proceedings of the 32nd ACM International Conference on the Foundations of Software Engineering. 572–576.
- [9] Davide Chicco and Giuseppe Jurman. 2020. The advantages of the Matthews correlation coefficient (MCC) over F1 score and accuracy in binary classification evaluation. *BMC genomics* 21 (2020), 1–13.
- [10] Patrick Cousot and Radhia Cousot. 1977. Abstract interpretation: a unified lattice model for static analysis of programs by construction or approximation of fixpoints. In Proceedings of the 4th ACM SIGACT-SIGPLAN symposium on Principles of programming languages. 238–252.
- [11] Marcos Cramer and Lucian McIntyre. 2025. Verifying LLM-Generated Code in the Context of Software Verification with Ada/SPARK. arXiv:2502.07728 [cs.SE] https://arxiv.org/abs/2502.07728
- [12] Leonardo de Moura and Nikolaj Bjørner. 2008. Z3: An Efficient SMT Solver. In Proceedings of the 14th International Conference on Tools and Algorithms for the Construction and Analysis of Systems (TACAS). Springer, 337–340. https: //doi.org/10.1007/978-3-540-78800-3_24
- [13] Chunyuan Deng, Yilun Zhao, Yuzhao Heng, Yitong Li, Jiannan Cao, Xiangru Tang, and Arman Cohan. 2024. Unveiling the Spectrum of Data Contamination in Language Model: A Survey from Detection to Remediation. In Findings of the Association for Computational Linguistics: ACL 2024. Association for Computational Linguistics, Bangkok, Thailand, 16078–16092. https: //doi.org/10.18653/v1/2024.findings-acl.951
- [14] Edsger Wybe Dijkstra, Edsger Wybe Dijkstra, Edsger Wybe Dijkstra, Etats-Unis Informaticien, and Edsger Wybe Dijkstra. 1976. A discipline of programming. Vol. 613924118. prentice-hall Englewood Cliffs.
- [15] Alastair F Donaldson, Leopold Haller, Daniel Kroening, and Philipp Rümmer. 2011. Software verification using k-induction. In Static Analysis: 18th International Symposium, SAS 2011, Venice, Italy, September 14-16, 2011. Proceedings 18. Springer, 351–368.
- [16] Madeline Endres, Sarah Fakhoury, Saikat Chakraborty, and Shuvendu K Lahiri. 2024. Can large language models transform natural language intent into formal method postconditions? *Proceedings of the ACM on Software Engineering* 1, FSE (2024), 1889–1912.

- [17] Jean-Christophe Filliåtre and Andrei Paskevich. 2013. Why3-where programs meet provers. In Programming Languages and Systems: 22nd European Symposium on Programming, ESOP 2013, Held as Part of the European Joint Conferences on Theory and Practice of Software, ETAPS 2013, Rome, Italy, March 16-24, 2013. Proceedings 22. Springer, 125–128.
- [18] Alibaba Group. 2024. Qwen2.5: Advancing Open-Source Large Language Models. https://qwenlm.github.io/blog/qwen2.5-llm/?utm_source=chatgpt.com
- [19] Xinyi He, Jiaru Zou, Yun Lin, Mengyu Zhou, Shi Han, Zejian Yuan, and Dongmei Zhang. 2024. CoCoST: Automatic Complex Code Generation with Online Searching and Correctness Testing. arXiv preprint arXiv:2403.13583 (2024).
- [20] Dan Hendrycks, Steven Basart, Saurav Kadavath, Mantas Mazeika, Akul Arora, Ethan Guo, Collin Burns, Samir Puranik, Horace He, Dawn Song, and Jacob Steinhardt. 2021. Measuring Coding Challenge Competence with APPS. In Advances in Neural Information Processing Systems (NeurIPS) Datasets and Benchmarks Track.
- [21] Charles Antony Richard Hoare. 1969. An axiomatic basis for computer programming. Commun. ACM 12, 10 (1969), 576–580.
- [22] Dong Huang, Qingwen Bu, Yuhao Qing, and Heming Cui. 2023. Codecot: Tackling code syntax errors in cot reasoning for code generation. arXiv preprint arXiv:2308.08784 (2023).
- [23] Dong Huang, Jie M Zhang, Michael Luck, Qingwen Bu, Yuhao Qing, and Heming Cui. 2023. Agentcoder: Multi-agent-based code generation with iterative testing and optimisation. arXiv preprint arXiv:2312.13010 (2023).
- [24] Yiming Huang, Zhenghao Lin, Xiao Liu, Yeyun Gong, Shuai Lu, Fangyu Lei, Yaobo Liang, Yelong Shen, Chen Lin, Nan Duan, and Weizhu Chen. 2024. Competition-Level Problems are Effective LLM Evaluators. In Findings of the Association for Computational Linguistics: ACL 2024. Association for Computational Linguistics, Bangkok, Thailand, 13526–13544. https://doi.org/10.18653/v1/2024.findingsacl.803
- [25] Naman Jain, King Han, Alex Gu, Wen-Ding Li, Fanjia Yan, Tianjun Zhang, Sida Wang, Armando Solar-Lezama, Koushik Sen, and Ion Stoica. 2024. Live-CodeBench: Holistic and Contamination Free Evaluation of Large Language Models for Code. arXiv:2403.07974 [cs.SE] https://arxiv.org/abs/2403.07974
- [26] Albert Q Jiang, Sean Welleck, Jin Peng Zhou, Wenda Li, Jiacheng Liu, Mateja Jamnik, Timothée Lacroix, Yuhuai Wu, and Guillaume Lample. 2022. Draft, sketch, and prove: Guiding formal theorem provers with informal proofs. arXiv preprint arXiv:2210.12283 (2022).
- [27] Huiqiang Jiang, Qianhui Wu, Xufang Luo, Dongsheng Li, Chin-Yew Lin, Yuqing Yang, and Lili Qiu. 2023. Longllmlingua: Accelerating and enhancing llms in long context scenarios via prompt compression. arXiv preprint arXiv:2310.06839 (2023).
- [28] Nan Jiang, Xiaopeng Li, Shiqi Wang, Qiang Zhou, Soneya Hossain, Baishakhi Ray, Varun Kumar, Xiaofei Ma, and Anoop Deoras. 2024. LeDex: Training LLMs to Better Self-Debug and Explain Code. Advances in Neural Information Processing Systems 37 (2024), 35517–35543.
- [29] Parnian Kamran, Premkumar Devanbu, and Caleb Stanford. 2024. Vision Paper: Proof-Carrying Code Completions. In Proceedings of the 39th IEEE/ACM International Conference on Automated Software Engineering Workshops (Sacramento, CA, USA) (ASEW '24). Association for Computing Machinery, New York, NY, USA, 35–42. https://doi.org/10.1145/3691621.3694932
- [30] Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. 2022. Large language models are zero-shot reasoners. Advances in neural information processing systems 35 (2022), 22199–22213.
- [31] K. Rustan M. Leino. 2010. Dafny: An Automatic Program Verifier for Functional Correctness. In *Logic for Programming, Artificial Intelligence, and Reasoning,* Edmund M. Clarke and Andrei Voronkov (Eds.). Springer Berlin Heidelberg, Berlin, Heidelberg, 348–370.
- [32] Kefan Li and Yuan Yuan. 2024. Large language models as test case generators: Performance evaluation and enhancement. arXiv preprint arXiv:2404.13340 (2024).
- [33] Changshu Liu, Shizhuo Dylan Zhang, Ali Reza Ibrahimzada, and Reyhaneh Jabbarvand. 2024. Codemind: A framework to challenge large language models for code reasoning. arXiv preprint arXiv:2402.09664 (2024).
- [34] Tongxuan Liu, Xingyu Wang, Weizhe Huang, Wenjiang Xu, Yuting Zeng, Lei Jiang, Hailong Yang, and Jing Li. 2024. Groupdebate: Enhancing the efficiency of multi-agent debate using group discussion. arXiv preprint arXiv:2409.14051 (2024).
- [35] Fangwen Mu, Lin Shi, Song Wang, Zhuohao Yu, Binquan Zhang, Chenxue Wang, Shichao Liu, and Qing Wang. 2023. Clarifygpt: Empowering llm-based code generation with intention clarification. arXiv preprint arXiv:2310.10996 (2023).
- [36] Prasita Mukherjee and Benjamin Delaware. 2024. Towards Automated Verification of LLM-Synthesized C Programs. arXiv:2410.14835 [cs.PL] https: //arxiv.org/abs/2410.14835
- [37] Ansong Ni, Miltiadis Allamanis, Arman Cohan, Yinlin Deng, Kensen Shi, Charles Sutton, and Pengcheng Yin. 2024. Next: Teaching large language models to reason about code execution. arXiv preprint arXiv:2404.14662 (2024).
- [38] Shiwen Ni, Xiangtao Kong, Chengming Li, Xiping Hu, Ruifeng Xu, Jia Zhu, and Min Yang. 2025. Training on the Benchmark Is Not All You Need.

arXiv:2409.01790 [cs.CL] https://arxiv.org/abs/2409.01790

- [39] Flemming Nielson, Hanne R Nielson, and Chris Hankin. 2015. Principles of program analysis. springer.
- [40] Shuyin Ouyang, Jie M Zhang, Mark Harman, and Meng Wang. 2025. An empirical study of the non-determinism of chatgpt in code generation. ACM Transactions on Software Engineering and Methodology 34, 2 (2025), 1–28.
- [41] Shanghaoran Quan, Jiaxi Yang, Bowen Yu, Bo Zheng, Dayiheng Liu, An Yang, Xuancheng Ren, Bofei Gao, Yibo Miao, Yunlong Feng, Zekun Wang, Jian Yang, Zeyu Cui, Yang Fan, Yichang Zhang, Binyuan Hui, and Junyang Lin. 2025. CodeElo: Benchmarking Competition-level Code Generation of LLMs with Human-comparable Elo Ratings. arXiv:2501.01257 [cs.CL] https://arxiv.org/abs/ 2501.01257
- [42] Max Schäfer, Sarah Nadi, Aryaz Eghbali, and Frank Tip. 2023. An empirical evaluation of using large language models for automated unit test generation. *IEEE Transactions on Software Engineering* 50, 1 (2023), 85–105.
- [43] Melanie Sclar, Yejin Choi, Yulia Tsvetkov, and Alane Suhr. 2023. Quantifying Language Models' Sensitivity to Spurious Features in Prompt Design or: How I learned to start worrying about prompt formatting. arXiv preprint arXiv:2310.11324 (2023).
- [44] Kensen Shi, Deniz Altınbüken, Saswat Anand, Mihai Christodorescu, Katja Grünwedel, Alexa Koenings, Sai Naidu, Anurag Pathak, Marc Rasi, Fredde Ribeiro, et al. 2024. Natural language outlines for code: Literate programming in the llm era. arXiv preprint arXiv:2408.04820 (2024).
- [45] Quan Shi, Michael Tang, Karthik Narasimhan, and Shunyu Yao. 2024. Can Language Models Solve Olympiad Programming? arXiv:2404.10952 [cs.CL]
- [46] Xujie Si, Hanjun Dai, Mukund Raghothaman, Mayur Naik, and Le Song. 2018. Learning loop invariants for program verification. Advances in Neural Information Processing Systems 31 (2018).
- [47] LLM Stats. 2024. GPT-4o-mini 2024-07-18 vs Qwen2 72B Instruct. https://llmstats.com/models/compare/gpt-4o-mini-2024-07-18-vs-qwen2-72b-instruct Accessed: 2025-03-14.
- [48] Rob Sullivan and Nelly Elsayed. 2024. Can Large Language Models Act as Symbolic Reasoners? arXiv:2410.21490 [cs.CL] https://arxiv.org/abs/2410.21490
- [49] Shin Hwei Tan, Jooyong Yi, Sergey Mechtaev, Abhik Roychoudhury, et al. 2017. Codeflaws: a programming competition benchmark for evaluating automated program repair tools. In 2017 IEEE/ACM 39th International Conference on Software Engineering Companion (ICSE-C). IEEE, 180–182.
- [50] Codeforces Team. 2019. Codeforces: Problem Difficulties. https://codeforces.com/ blog/entry/62865
- [51] The Coq Development Team. 2024. The Coq Reference Manual Release 8.19.0. https://coq.inria.fr/doc/V8.19.0/refman.
- [52] Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. 2022. Chain-of-thought prompting elicits reasoning in large language models. Advances in Neural Information Processing Systems 35 (2022), 24824–24837.
- [53] Chulin Xie, Yangsibo Huang, Chiyuan Zhang, Da Yu, Xinyun Chen, Bill Yuchen Lin, Bo Li, Badih Ghazi, and Ravi Kumar. 2024. On memorization of large language models in logical reasoning. arXiv preprint arXiv:2410.23123 (2024).
- [54] Miao Xiong, Zhiyuan Hu, Xinyang Lu, Yifei Li, Jie Fu, Junxian He, and Bryan Hooi. 2024. Can LLMs Express Their Uncertainty? An Empirical Evaluation of Confidence Elicitation in LLMs. arXiv:2306.13063 [cs.CL] https://arxiv.org/abs/ 2306.13063
- [55] Weimin Xiong, Yiwen Guo, and Hao Chen. 2023. The program testing ability of large language models for code. arXiv preprint arXiv:2310.05727 (2023).
- [56] Jundong Xu, Hao Fei, Liangming Pan, Qian Liu, Mong-Li Lee, and Wynne Hsu. 2024. Faithful logical reasoning via symbolic chain-of-thought. arXiv preprint arXiv:2405.18357 (2024).
- [57] Lei Yang, Renren Jin, Ling Shi, Jianxiang Peng, Yue Chen, and Deyi Xiong. 2025. ProBench: Benchmarking Large Language Models in Competitive Programming. arXiv:2502.20868 [cs.CL] https://arxiv.org/abs/2502.20868
- [58] Zhiqiang Yuan, Yiling Lou, Mingwei Liu, Shiji Ding, Kaixin Wang, Yixuan Chen, and Xin Peng. 2023. No more manual tests? evaluating and improving chatgpt for unit test generation. arXiv preprint arXiv:2305.04207 (2023).
- [59] David W. Zhang, Michaël Defferrard, Corrado Rainone, and Roland Memisevic. 2025. Grounding code understanding in step-by-step execution. https:// openreview.net/forum?id=MUr7Fl93QS
- [60] Yuwei Zhao, Ziyang Luo, Yuchen Tian, Hongzhan Lin, Weixiang Yan, Annan Li, and Jing Ma. 2024. CodeJudge-Eval: Can Large Language Models be Good Judges in Code Understanding? arXiv preprint arXiv:2408.10718 (2024).

A Supplementary Materials

All code, documentation, results and complimentary material for this work is available in our repository: https://github.com/msvlab/HoarePrompt.

A.1 Details of Motivating Example

For evaluating the motivating example presented in Section 2.1, we ran a series of experiments using three different qwen2.5 models (7b-instruct, coder-32b-instruct, 72b-instruct) at three temperatures (0.5, 1.0, 1.5). For each temperature, we tested:

- Not Annotated: 6 different prompts with no reachable state annotations.
- Annotated: 6 different prompts that included reachable state descriptions.

Each model/prompt combination was run 10 times, for a total of 1080 calls across all setups. Table 3 shows the success rates (the percentage of calls that correctly identified the code as buggy).

Table 3: Success rates (%) for detecting the indentation bug under different prompts ("Not Annotated" vs. "Annotated"), temperatures, and models. Each cell shows *successful runs / total runs* (percentage).

Temperature = 0.5				
Model	Not Annotated	Annotated		
7b-instruct	0/60 (0%)	7/60 (11.7%)		
coder-32b-instruct	9/60 (15%)	51/60 (85%)		
72b-instruct	21/60 (35%)	51/60 (85%)		
Temperature = 1.0				
Model	Not Annotated	Annotated		
7b-instruct	0/60 (0%)	2/60 (3.3%)		
coder-32b-instruct	9/60 (15%)	50/60 (83.3%)		
72b-instruct	29/60 (48.3%)	49/60 (81.7%)		
Temperature = 1.5				
Model	Not Annotated	Annotated		
7b-instruct	4/60 (6.7%)	5/60 (8.3%)		
coder-32b-instruct	7/60 (11.7%)	51/60 (85%)		
72b-instruct	31/60 (51.7%)	42/60 (70%)		

A.2 Motivational Example for Tester Classifier

This section provides a detailed example highlighting the limitations of LLM-generated test cases in program correctness assessment. It demonstrates that LLM-based testing struggles with generating effective test cases and computing expected outputs accurately for complex requirements.

In this example, the program contains a division-by-zero error that only occurs when a specific computed condition holds. However, the LLM-generated test cases fail to provide such inputs, preventing the bug from manifesting. Furthermore, even when valid inputs are provided, the LLM incorrectly predicts the expected output, leading to incorrect classification.

A.3 Natural Language and LLMs for State Tracking

We explore the effectiveness of Qwen2.5-72B-Instruct in inferring the final state (postcondition) of a program segment by leveraging semantic context and real-world knowledge. Unlike formal verification methods that rely on explicit rules and symbolic execution, Qwen2.5-72B-Instruct can generate intuitive and human-readable explanations of code behavior. This approach enhances analysis precision by utilizing variable names and structure to improve reasoning. While it does not provide formal correctness guarantees, it acts as a practical fuzzy correctness classifier, making it useful for tasks like bug detection and code generation.

In Figures8,9 we present two more examples to complement that in Section 2.3. These examples illustrate how an LLM can concisely infer express program states by leveraging natural language. We believe this ability of LLM to succinctly capture program behavior using user-centric terms helps HoarePrompt to accurately classify program correctness by bridging the gap between program semantics and informal requirements.

A.4 Dataset Details

To better illustrate the difficulty of problems in CoCoClaNeL, we use the *rating* tags for problems provided by Codeforces as an indicator. Initially, rating was solely an indicator of user rankings on programming competition platforms. Subsequently, to better assist users in selecting appropriate problems for practice, Codeforces began assigning each problem a rating to represent its difficulty, which is determined by the solving statistics of participants for this problem [50]. Formally, a problem's rating x quantifies that participants with a rating of x have a 50% probability of solving it on their first encounter.

Rating for problems ranges from 800 to 3500 and serves as a difficulty coefficient indicator, where a higher rating indicates greater problem difficulty. During the problem collection process, we also gathered the ratings of each problem and present the rating distribution of our dataset. As shown in Figure 10, our dataset has an average rating of 1206. According to the statistics and evaluations from CodeElo[41], a problem with a rating of 1206 indicates that approximately 60% of all participants on Codeforces find it challenging (with less than a 50% probability of solving it on their first encounter), and only 2 of the 33 tested LLMs achieved a higher rating than 1206, which is difficult for LLMs to simply retrieve.

Additionally, as can be seen from the figure, the data presents a skewed distribution of "higher on the left and lower on the right". The frequency in low rating intervals (such as 800–1000) is significantly higher, and as the rating increases, the frequency generally shows a downward trend. The main reason is that as the difficulty of the problem increases (the rise in rating), the number of people who solve this problem (or even the number of people who attempt to solve it) decreases. Therefore, there are fewer submission records available for sampling, and even fewer submission records that meet our sampling strategy.

The scraped problems were originally in raw HTML format. We parsed out all the useful content w.r.t. the problem and converted it into Markdown format (to be consistent with our prompt), which may include the problem description, input format, output format, Dimitrios Stamatios Bouras, Yihan Dai, Tairan Wang, Yingfei Xiong, and Sergey Mechtaev







Figure 8: Example 2 - Unique Email Domains



Figure 9: Example 3 - First name extraction

examples, notes, and so on, to ensure the sufficiency of the problem information and details.

For a problem, we filtered out all its Python submissions. The specific strategy for selecting submissions is as follows:

• Include three consecutive incorrect/correct code pairs (each pair comes from the same user). If there are less than three, include all that are available. If the problem has not been solved by anyone, skip it.



Figure 10: The Frequency Histogram of Rating for CoCo-ClaNeL with x-axis representing the rating intervals of the problems and y-axis representing the number of problemcode pairs within each rating interval in the dataset.

• If available, include one code with a test passed rate of 50% (or close to 50% due to an odd number of test cases), and one code with only a single failing test case.

B LLM Prompts

In this section of the Appendix, we include all prompts provided to the LLMs during the evaluation and experiments in our study. Where FSL was employed, the FSL examples are also included.

B.1 Zero-Shot Chain-of-Thought (CoT) Prompt

Your task is to determine if a given Python program is correct based on the provided problem description. Assume valid inputs as
 described in the problem description.
First, explain your reasoning step by step, then reply with:
 Correctness: `True` if the given program is correct.
 Correctness: `False` if the given program is incorrect.
Problem:
 (decription)
Program:
 (code)
Your response:
Reasoning:
Correctness: **True** or **False**

B.2 Vanilla Prompt (No Chain-of-Thought)

Your task is to determine if a given Python program is correct based on the provided problem description. Assume valid inputs as
described in the problem description.
Reply with:
 - Correctness: `True` if the given program is correct.
 - Correctness: `False` if the given program is incorrect.
 - Correctness: `False` if the given program is incorrect.
Problem:
{description}
Program:
{code}
Your response:
Correctness: **True** or **False**

B.3 Prompt for Input-Output Test Case Generation

Role: As a tester, your task is to create comprehensive test cases for the following coding problem. These test cases should encompass Basic and Edge scenarios to ensure the code's robustness, reliability, and scalability.
Problem Description: {description}
<pre>**1. Basic Test Cases**: - **Objective**: To verify the fundamental functionality of the `has_close_elements` function under normal conditions.</pre>
<pre>**2. Edge Test Cases**: - **Objective**: To evaluate the function's behavior under extreme or unusual conditions.</pre>
<pre>**Instructions**: - Implement a comprehensive set of test cases following the guidelines above Ensure each test case is complete (no omission) and well-documented with comments explaining the scenario it covers Pay special attention to edge cases as they often reveal hidden bugs Do not repeat, do not summarize.</pre>
All test cases you give need to strictly follow the problem description and format like this:
<pre># Test 1 **Input**:</pre>
Output:

B.4 HoarePrompt Correctness Classification Prompt

Your task is to determine if a given Python program is correct based on the problem description and the execution states of the program
provided as comments. Assume valid inputs as described in the problem description.

First, explain your reasoning, then reply with:
 - Correctness: `True` if the given program is correct.
 - Correctness: `False` if the given program is incorrect.

Problem:
{description}

Annotated Program:
{annotated_program}

Your response:
Reasoning:
Correctness: **True** or **False**

B.5 HoarePrompt Correctness Classification for Multi-Function Programs

Your task is to determine if a given Python program is correct based on the problem description and the execution states of the program provided as comments. Assume valid inputs as described in the problem. The program is made of multiple functions and the program is **correct** only if all its functions together meet the problem description.

First, explain your reasoning, then reply with: - Correctness: `True` if the given program is correct.

- Correctness: `False` if the given program is incorrect.

Problem:
{description}

Annotated Functions:
{functions}

Your response: Reasoning: Correctness: **True** or **False**

B.6 Precondition Extraction Prompt

```
You are given a programming problem description and a function definition for a function that solves this problem. From the problem
     description, extract a description of the values of the program's input variables and the relationships between these variables.
     We refer to this description as the **precondition**. Print the precondition following the word **"Precondition"**, and surround
     it with double asterisks (**). Follow these examples:
### Example 1
**Problem description:** Write a function to find the minimum cost path to reach (m, n) from (0, 0) for the given cost matrix cost[][]
     and a position (m, n) in cost[][].
**Function definition:**
 ``python
def min_cost(cost, m, n):
**Precondition:** **cost is a 2D list of non-negative integers, m and n are non-negative integers such that 0 <= m < len(cost) and 0 <=
      n < len(cost[0]).**</pre>
### Example 2
**Problem description:** Write a function to find the similar elements from the given two tuple lists.
**Function definition:**
••• python
def similar_elements(test_tup1, test_tup2):
**Precondition:** **test_tup1 and test_tup2 are tuples.**
### Example 3
**Problem description:** Write a Python function to identify non-prime numbers.
**Function definition:**
 ``pvthon
def is_not_prime(n):
**Precondition:** **n is an integer greater than 1.**
### Example 4
**Problem description:** Write a function to find the largest integers from a given list of numbers using the heap queue algorithm.
**Function definition:**
 ``python
def heap_queue_largest(nums, n):
**Precondition:** **nums is a list of integers, and n is a non-negative integer such that 0 <= n <= len(nums).**
### Example 5
**Problem description:** Write a function to find the number of ways to fill it with 2 x 1 dominoes for the given 3 x n board.
**Function definition:**
••• python
def count_ways(n):
**Precondition:** **n is a non-negative integer.**
### Example 6
**Problem description:** Find the average of the positive integers in a list.
**Function definition:**
••• python
def func_1(numbers):
**Precondition:** **numbers is a list of integers.**
### **Your Task**
**Problem description:**
{description}
**Function definition:**
 ``python
{program}
```

B.7 Precondition Extraction Prompt for Multi-Function Programs

You are given a programming problem description and a function that contributes to the solution of this problem. The total solution comprises multiple functions, and this is just one of them.

```
From the problem description, and based on the variables used in the signature of this specific function, extract a description of the values of the variables in the function signature and the relationship between them. We refer to this description as the ** precondition**. Print the precondition following the word **Precondition**, and surround it with double asterisks (**). Follow these examples:
```

```
Remember, the function given may not solve the problem directly but may perform a side functionality that contributes to the total solution. Include information only about the variables in the function signature.
```

Example 1
Problem description: Write a function to find the minimum cost path to reach (m, n) from (0, 0) for the given cost matrix cost[][]
and a position (m, n) in cost[][].

```
**Program:**
```

```
'`python

def min_cost(cost, m, n):

    tc = [[0 for x in range(C)] for x in range(R)]

    tc[0][0] = cost[0][0]

    for i in range(1, m+1):

        tc[i][0] = tc[i-1][0] + cost[i][0]

    for j in range(1, n+1):

        tc[0][j] = tc[0][j-1] + cost[0][j]

    for i in range(1, m+1):

        for j in range(1, m+1):

        tc[i][j] = min(tc[i-1][j-1], tc[i-1][j], tc[i][j-1]) + cost[i][j]

    return tc[m][n]
```

Precondition: **cost is a 2D list of non-negative integers, m and n are non-negative integers such that 0 <= m < len(cost) and 0 <=
 n < len(cost[0]).**</pre>

```
### Example 2
**Problem description:** Write a function to find the similar elements from the given two tuple lists.
**Program:**
 ``python
def are_similar(elem, elem1):
   if elem == elem1:
      return True
   else:
      return False
**Precondition:** **elem1 and elem are values of any type and value.**
### Example 3
**Problem description:** Write a Python function to identify if 2 consecutive integers in a list are not prime.
**Program:**
••• python
import math
def is_not_prime(n):
   result = False
   for i in range(2, int(math.sqrt(n)) + 1):
      if n % i == 0:
          result = True
   return result
...
**Precondition:** **n is an integer greater than 1.**
```

```
### Example 4
**Problem description:** Write a function to find the largest integers from a given list of numbers using the heap queue algorithm.
**Program:**
```python
import heapq as hq
def heap_queue_largest(nums, n):
 largest_nums = hq.nlargest(n, nums)
 return largest_nums
...
Precondition: **nums is a list of integers, and n is a non-negative integer such that 0 <= n <= len(nums).**

Your Task
Problem description:
(description)
Program:
```python
(program)
...</pre>
```

B.8 Simple Statement Execution Prompt

```
You have been assigned the role of a program executor, responsible for simulating the execution of Python code. You will be provided
     with an initial state and a Python code snippet. You need to provide the output state after running the Python code based on the
     initial state. Please avoid describing how the program runs. When a variable has a specific value, use that specific value
     directly for calculations. If a return takes place, make sure to always mention that a value or variable has been returned in the
      output state. You must adhere to the text format: **Output State: `output state`**.
Include all the information of the precondition that is still valid after the code has been executed. Just update the values of the
     variables that have been changed by the code.
I am giving you some examples to understand the task better. Then I am giving you your task.
---
### Example 1
**Initial State:** `str` is a string
••• python
n = int(input())
**Output State:** **`str` is a string, `n` is an input integer**
### Example 2
**Initial State:** Variables can hold any values
••• python
i += 1
**Output State:** **variable `i` is increased by 1**
____
### Example 3
**Initial State:** `n` is either 3 or 5
··· python
m = n + 1
**Output State:** **`n` is either 3 or 5; `m` is either 4 or 6**
### Example 4
**Initial State:** `x` is a positive integer; if `x` is greater than 10, then `z = 0`, else `z = 1`.
· · · pvthon
y = -z
**Output State:** **`x` is a positive integer, if `x` is greater than 10 then `z=0` and `y=0`, else `z=1` and `y=-1`**
---
### Example 5
**Initial State:** `total` is 0, `i` is 1
••• python
break
**Output State:** **`total` is 0, `i` is 1 and we break out of the most internal loop or if statement.**
```

Dimitrios Stamatios Bouras, Yihan Dai, Tairan Wang, Yingfei Xiong, and Sergey Mechtaev

```
### Example 6
**Initial State:** `total` is positive, `num` is negative, `x` is 0
```python
x = total - num
...
Output State: **`total` is positive, `num` is negative, `x` is a positive value equal to `total - num`.**
Your Task
Initial State:
{pre}
```python
{program}
}
```

B.9 Compound Simple Statements Execution Prompt

```
You have been assigned the role of a program executor, responsible for simulating the execution of Python code. You will be provided
     with an initial state and a Python code snippet consisting of multiple lines. Your task is to execute all the lines in sequence
     and provide the output state after the entire code block has been run. Avoid describing how the program runs step-by-step for
     individual lines but instead focus on the combined effect of all lines. When a variable has a specific value, use that specific
     value directly for calculations.
Include all the information from the precondition that remains valid after the code execution and update the values of any variables
      that are modified by the code. Provide the final state, including the state of all the variables after the execution of the code
      snippet. Use the text format: **Output State: `output state`**.
Here are some examples to help you understand the task:
____
### Example 1
**Initial State:** `a` is 5, `b` is 3
```python
c = a + b
d = c * 2
Output State: **a is 5, b is 3, c is 8, d is 16**

Example 2
Initial State: `x` is a positive integer
```python
n = int(input())
x += n
**Output State:** **x is a positive integer equal to its original value plus `n`, `n` is an integer**
____
### Example 3
**Initial State:** `n` is 3, `total` is 1
••• python
total += n
pass
n = max(total, n)
**Output State:** **n is 4, total is 4**
### **Your Task**
**Initial State:**
{pre}
••• python
{program}
Now, please analyze the entire block of code and provide the final output state. List the impact of all lines on the program, check the
      previous values of affected variables, and calculate the states of the variables after the code executes. Be as specific as
     possible, combining changes from all lines into a single coherent final state. Include all valid information from the
     precondition and update only what is modified by the code.
In your response, strictly use the format: **Output State: `the output state you calculate`.**, and describe this output state in
     natural language easily understandable by humans.
```

B.10 Print Commands Execution Prompt

```
You will be given an **initial state** (precondition) and a **Python code snippet** containing a `print` statement. Your task is to **
     determine exactly what will be printed** when the statement executes.
- If a variable or object has a known **explicit value**, use that value in the output.
- If a variable or object is defined by a **formula or condition**, describe its value using the given information.
- Always provide the most **precise** description possible based on the precondition.
- Format the final output as: **Output: `what is printed`**.
I am giving you some examples to understand the task better. Then I am giving you your task.
### Example 1
**Initial State:** `arr` is a list containing 1, 2, 3, 4, 5, and `sum` is the sum of all elements in the list `arr`.
 ``python
print(arr[2], sum)
**Output:** **3, sum (where sum is the sum of all elements in list `arr`)**
___
### Example 2
**Initial State:** The `points` list is a list of points. The `shoelace_sum` is the sum of all terms calculated as \(x_1 * y_2 - y_1 *
     x_2) for each consecutive pair of points in the `points' list. The `area` is the absolute value of `shoelace_sum` divided by 2.0.
      'i' is equal to `len(points) - 2`, and `x1` is the first element of `points[i]`, `y1` is the second element of `points[i]`,
     while 'x2' is the first element of 'points[i + 1]', and 'y2' is the second element of 'points[i + 1]'.
••• python
print(area)
**Output:** **area (where area is the area of the polygon formed by the points in the `points` list)**
### Example 3
**Initial State:** `balances` is a list of integers, `A` is the first element of the `balances` list, `B` is the second element of the
     `balances` list, and `amount` is an integer less than or equal to `A`.
... python
print(f"The amount {amount} is less than or equal to {A}")
**Output:** **The amount [amount] is less than or equal to [A] (where `amount` is the value of `amount` and `A` is the first element of
      the `balances` list)**
___
### **Your Task**
**Initial State **
{pre}
••• python
{program}
Now, please think step by step. Based on the precondition that describes the state of the program, variables, objects, etc., before the
      code is executed, calculate what will be printed when the `print` statement is executed. Explain the values of the variables,
     objects, etc., that are printed.
Use natural language to describe the output, ensuring it is easily understandable by a human. Strictly adhere to the format **Output: `
     what is printed **.
```

B.11 Return Command Execution Prompt

```
You have been assigned the role of a program executor, responsible for simulating the execution of Python code. You will be provided
     with an **initial state** and a **Python code snippet**. Your task is to determine what the program **returns** based on the
     given initial state.
- Avoid describing how the program runs step by step.
- If a variable has a **specific value**, use that value directly.
- If a return statement is executed, **always mention the returned value explicitly** in the output state.
- Adhere to the text format: **Output State: `output state` **.
{\rm I} am giving you some examples to understand the task better. Then {\rm I} am giving you your task.
### Example 1
**Initial State:** `str` is a string, 'str' has 3 or more characters
••• python
return str
**Output State:** **The program returns string `str` that has 3 or more characters**
### Example 2
**Initial State:** `numbers` is an empty list, `total` is the sum of all positive integers that were in the original `numbers` list, `
     count' is the number of positive integers that were in the original `numbers' list, `average' is equal to `total / count'
••• python
return average
**Output State:** **The program returns `average`, which is equal to `total/count`, where `total` is the sum of all positive integers
     in the original `numbers` list, and `count` is the number of positive integers in the original `numbers` list.**
### Example 3
**Initial State:** `n` is either 3 or 5
 ``python
return n + 1
**Output State:** **The program returns 4 or 6**
### Example 4
**Initial State:** `x` is 1, `y` is greater than 3, `z` is 0
 ``python
return y + x
**Output State:** **The program returns `y + 1`, where `y` is greater than 3**
### Example 5
**Initial State:** `count` contains the number of numbers greater than 1 in the list `numbers`, `numbers` is a list of integers, `total
     · is 0
••• python
return count
**Output State:** **The program returns the number of integers greater than 1 in list `numbers`**
### **Your Task**
**Initial State:**
{pre}
>>`python
{program}
Now, please think step by step: List the impact of the code on the program, check the previous values of the affected variables, and
     then calculate what the program returns. Any variable or value that is included in the return should be fully described with all
     available information.
Strictly adhere to the format: **Output State: `the output state you calculate`**, and describe this output state in **natural language
      easily understandable by humans**.
```

B.12 Try-Except Statement Execution Prompt

```
You have been assigned the role of a program verifier, responsible for summarizing the state of the function after executing a Python `
     try' statement. You will be provided with the **final state of the program** after executing the `try' block, along with the **
     changes in the program after executing one or more `except` blocks** in any situation. Your task is to **combine this information
      to summarize the program's state after the complete execution of the `try` statement**.
- If a `return` statement is executed, **always include it in the output state**.
- Adhere to the text format: **Output State: `output state` **.
I am giving you some examples to understand the task better. Then I am giving you your task.
### Example 1
**Initial State:** `a` is an integer, `b` is an integer.
 ``python
trv:
   result = a / b
   return result
except ZeroDivisionError:
  return None
**Output state after executing the `try` block:** `a` is an integer, `b` is an integer, `result` is `a` divided by `b`, and the
     function returns `result`.
**Output state after executing the `except` block:** If a `ZeroDivisionError` occurs (i.e., `b` is 0), the function returns `None`.
**Final Output State:**
A 'ZeroDivisionError' might be triggered at 'result = a / b'. If 'b' is 0, the function returns 'None'. Otherwise, the function returns
     the value of `a` divided by `b`.
**Output State:** **`a` and `b` are integers. If `b` is zero, the function returns `None`, otherwise the function returns the value of
      `a` divided by `b`.**
____
### Example 2
**Initial State:** `file_path` is a string that's supposed to be a path to a file.
 ``python
def read_file(file_path):
   try:
       with open(file_path, 'r') as file:
          data = file.read()
          print("File content successfully read.")
          return data
   except FileNotFoundError:
       print("Error: The file was not found. Please check the file path.")
       return None
   except PermissionError:
       print("Error: You do not have permission to read this file.")
       return None
**Output state after executing the `try` block:** `file_path` is a string representing a file path, `data` contains the file content,
     and the function returns `data`.
**Output state after executing the `except` block(s):**
- If a `FileNotFoundError` occurs, the function prints an error message and returns `None`.
- If a `PermissionError` occurs, the function prints a different error message and returns `None`.
**Final Output State:**
The program could raise a `FileNotFoundError` if the file is not found at the specified path or a `PermissionError` if the user does
     not have permission to read the file. If the file is found and the user has permission, the function reads the file content and
     returns it.
**Output State:** **`file_path` is a string representing a file path. If the file exists and the user has permission, the function
     returns the file content; otherwise, it prints an error message and returns `None`.**
```

Your Task
Initial State:
{pre}
Code for the try-except block:
```python
{code}
```
Output state after executing the `try` block:
{try_post}
Output state after executing the `try` block(s):
{except_post}
Now, please think step by step: At which point in the program could such an exception occur? Summarize what the `try-except` statement
accomplishes and what the program output state is after execution.
Strictly adhere to the format: **Output State: `the output state you calculate`**, and describe this output state in **natural language
easily understandable by humans**.

B.13 Function Functionality and Return Summary Prompt

```
You have been assigned the task of a program verifier, responsible for describing the functionality of a Python function. You will be
     provided with the **constraints and relationships** between the input parameters, as well as the **resulting output** of the
     function based on these inputs. Your task is to **organize this information and describe the functionality of the function**.
- Avoid describing how the function operates (e.g., local variable initialization or step-by-step execution).
- Focus only on **what parameters the function accepts** and **what it returns**.
- If there are multiple return points in the function, we will split them into **cases** labeled sequentially (Case 1, Case 2, etc.).
- If one case is fulfilled, **none of the others are executed**.
- Adhere strictly to the format: **Functionality: `functionality description`**.
I am giving you some examples to understand the task better. Then I am giving you your task.
### Example 1
**Parameter constraints and relationships:** `number` is an integer.
••• python
def func(number):
**Output:**
- Case 1: If `number` is even, the function returns `True`.
- Case 2: If `number` is not even, the function returns `False`.
**Final Answer:**
The function `func` accepts a parameter `number` and returns `True` if `number` is even. If `number` is not even, it returns `False`.
**Functionality:** **The function accepts a parameter `number`, returns `True` if `number` is even. If `number` is not even, it returns
      `False`.**
### Example 2
**Parameter constraints and relationships:** `age` is an integer.
``python
def func(age):
**Output:**
- Case 1: If `age` is less than 0, the function returns an error message stating that ages can't be negative.
- Case 2: If `age` is between 0 and 18, the function returns "minor".
- Case 3: Otherwise, the function returns "adult".
**Final Answer:**
The function `func' accepts a parameter `age`. If `age` is below 0, the function returns an error message. If `age` is between 0 and
     18, it returns "minor". Otherwise, it returns "adult".
**Functionality:** **The function accepts an integer `age`, returns an error if `age` is negative, "minor" if `age` is between 0 and
     18, and "adult" otherwise.**
### **Your Task**
**Parameter constraints:**
{pre}
>>`pvthon
{head}
**Output:**
{body_post}
Now, please think step by step: What are the parameters the function accepts, and what does it return?
Strictly adhere to the format: **Functionality: `the functionality you calculate`**, and describe this functionality in **natural
     language easily understandable by humans**.
```

B.14 If Condition Precondition Extraction Prompt

```
You are assigned the role of a program verifier, responsible for finding the **postcondition** of an `if` statement based on its
     condition. You will be given:
- A **precondition**, describing the initial state of the program variables before entering the `if` statement.
- An **if condition**, which determines whether the program enters the `if` block.
Your task is to determine the **postcondition**, which describes the state of the program variables after entering the `if` block. The
     postcondition must extend the precondition by ensuring that the `if` condition is true. This description should include both the
     values of the variables and the relationships between them.
- **Do not explain how the program runs**; only focus on variable values and relationships.
- Ensure that the postcondition retains all valid information from the precondition while incorporating the truth of the `if` condition.
- Follow the format: **Postcondition: `calculated postcondition`**.
I am giving you some examples to understand the task better. Then I am giving you your task.
____
### Example 1
**Precondition:** `str` is a string
**If condition:**
 ``pvthon
if len(str) < 3:
**Postcondition:** **`str` is a string, and the length of `str` is less than 3**
---
### Example 2
**Precondition:** `n` can have any value
**If condition:**
••• python
if isinstance(n, int):
**Postcondition:** **`n` is an integer of any value**
____
### Example 3
**Precondition:** `x` is a positive integer
**If condition:**
 ••• python
if x < 2:
**Postcondition:** **`x` is a positive integer less than 2**
___
### Example 4
**Precondition:** `m` is an integer. If `m` is higher than 10, then `n` equals `-m`. `a` is a list of integers.
**If condition:**
••• python
if n < 0:
**Postcondition:** **`m` is an integer, if `m` is higher than 10, `n` equals `-m`. `a` is a list of integers. The current value of `n`
      is less than 0**
```

<pre>### Example 5 **Precondition:** `x` is an integer, `a` is a list of integers. **If condition:** ```python if a[0] != 0:</pre>
Postcondition: **`x` is an integer, `a` is a list of integers. The first element of `a` is not 0**
Your Task
Precondition:
{precondition}
If condition:
••• python
{program_fragment}
Your task is to complete the **postcondition**. Ensure that:
- All valid information from the **precondition** is retained.
- The **if condition** is now assumed to be **true**.
 - If variables have values related to previous conditions, put that early in the postcondition and state the **current** value of the variable clearly.
- The final state of the program **after entering the if block** is fully described.
Strictly adhere to the format: **Postcondition: `the postcondition you calculate`**, and describe this postcondition in **natural language easily understandable by humans**.

B.15 Else Condition Precondition Extraction Prompt

You are assigned the role of a program verifier, responsible for finding the **postcondition** of an `else` statement based on the condition of the corresponding `if` statement. You will be given: - A **precondition**, describing the initial state of the program variables before evaluating the `if` condition. - An **if condition**, which determines whether the program enters the `if` block. **In this case, we do not enter the `if` block but instead follow the `else` block**. Your task is to determine the **postcondition**, which describes the state of the program variables after entering the `else` block. The postcondition must extend the precondition by ensuring that the `if` condition is **false**. This description should include both the values of the variables and their relationships. - **Do not explain how the program runs**; only focus on variable values and relationships. - Ensure that the postcondition retains all valid information from the precondition while incorporating the negation of the `if` condition. - Follow the format: **Postcondition: `calculated postcondition`**. I am giving you some examples to understand the task better. Then I am giving you your task. ### Example 1 **Precondition:** `str` is a string **If condition:** ```python if len(str) < 3: **Postcondition:** **`str` is a string, and the length of `str` is greater than or equal to 3** ### Example 2 **Precondition:** `n` can have any value **If condition:** ```python if isinstance(n, int): **Postcondition:** **`n` can have any value except an integer** ____ ### Example 3 **Precondition:** `x` is a positive integer **If condition:** ••• python if x < 2: **Postcondition:** **`x` is a positive integer greater than or equal to 2** ---### Example 4 **Precondition:** `m` is an integer, `n` is an integer, `a` is a list of integers. **If condition:** ```python if n <= 0: **Postcondition:** **`m` and `n` are integers, `n` is greater than 0, `a` is a list of integers**

## ** ** if	<pre>## Example 5 #Precondition:** `x` is an integer, `a` is a list of integers. #If condition:** '`python f a[0] != 0:</pre>
**	*Postcondition:** **`x` is an integer, `a` is a list of integers. The first element of `a` is 0**
##	## **Your Task**
** {p	<pre>Precondition:** precondition}</pre>
** {F	<pre>*If condition:** ``python orogram_fragment}</pre>
Yc - - -	pur task is to complete the **postcondition**. Ensure that: All valid information from the **precondition** is retained. The **if condition** is now assumed to be **false**. If variables have values related to previous conditions, put that early in the postcondition and state the **current** value of the variable clearly. The final state of the program **after entering the else block** is fully described.
St	rictly adhere to the format: **Postcondition: `the postcondition you calculate`**, and describe this postcondition in **natural language easily understandable by humans**.

B.16 If-Else Statement Postcondition Extraction Prompt

```
You are assigned the role of a program verifier, responsible for completing the **overall postcondition** of Hoare triples for `if`
     statements based on the postconditions of both the `if` and `else` parts. You will be given:
- A **precondition**, describing the initial state of the program variables before the execution of the program fragment.
- A **program fragment**, which contains an `if` condition and possibly an `else` block.
- The **postcondition of the `if` part**, describing the state after entering the `if` block.
- The **postcondition of the `else` part**, describing the state after entering the `else` block (if an `else` exists).
Your task is to **combine the postconditions of both the `if` and `else` parts** (if an `else` exists), taking into account the `if`
     condition, to derive the **overall postcondition of the entire `if-else` block**.
- **Do not explain how the program runs**: only focus on variable values and relationships.
- Ensure that the postcondition retains all valid information from the precondition while incorporating both branches of the `if-else`
     logic.
- Summarize the `if` statement in a **coherent paragraph**, rather than discussing it in separate sections.
- Follow the format: **Postcondition: `calculated postcondition`**.
I am giving you some examples to understand the task better. Then I am giving you your task.
---
### Example 1
**Precondition:** `str` is a string
**Program Fragment:**
••• pvthon
if len(str) < 3:
**If part:** `str` is a string with length less than 3, the function returns `None`
**Else part:** There is no `else` part in the code
**Postcondition:** **`str` is a string. If the length of `str` is less than 3, the function returns `None`.**
### Example 2
**Precondition:** `n` can have any value
**Program Fragment:**
••• python
if isinstance(n, int):
else:
**If part:** `n` is an integer of any value, and the function returns `n`
**Else part:** `n` can have any value except an integer, and the function returns `int(n)`
**Postcondition:** **If `n` is an integer, the function returns `n` itself. Otherwise, the function returns `int(n)`.**
___
### Example 3
**Precondition:** `x` is a positive integer
**Program Fragment:**
••• python
if x < 2:
else:
**If part:** `x` is a positive integer less than 2, and the function returns `False`
**Else part:** `x` is a positive integer greater than or equal to 2, and the function returns `True`
**Postcondition:** **`x` is a positive integer. If `x` is less than 2, the function returns `False`. Otherwise, the function returns `
     True`.**
```

```
### Example 4
**Precondition:** `m` is an integer, `n` is an integer
**Program Fragment:**
••• python
if n < 0:
else
**If part:** The integer `n` was originally negative, `n` is updated to its negation, and `m` is increased by 1
**Else part:** If `n` is 0, the function returns `m`. Otherwise, `n` is decreased by 13, and `m` is increased by 1
**Postcondition:** **`m` and `n` are integers. If `n < 0`, `m` is increased by 1 and `n` is negated. If `n == 0`, the function returns
      `m`. Otherwise, `n` is decreased by 13 and `m` is increased by 1.**
---
### Example 5
**Precondition:** `x` is an integer, `y` is zero
**Program Fragment:**
••• python
if x > 0:
**If part:** `x` is a positive integer. If `x > 10`, `y` is set to twice the value of `x`. Otherwise, `y` is set to `x + 5`.
**Else part:** There is no `else` part in the code
**Postcondition:** ** x ` is an integer. If `x > 10`, `y` is set to twice the value of `x`. If `x` is greater than 0 but less than 10, `
     y` is set to `x + 5`.**
### **Your Task**
**Precondition:**
{precondition}
**Program Fragment:**
 ``python
{program_fragment}
**If part:**
{postconditions_if}
**Else part:**
{postconditions_else}
Your task is to **complete the overall postcondition of the entire if-else block**. Summarize all cases and describe the final state of
      the program **after executing the if-else statement**.
Strictly adhere to the format: **Postcondition: `the postcondition you calculate`**, and describe this postcondition in **natural
     language easily understandable by humans**.
```

B.17 While Loop First Execution Necessary Condition Prompt

```
You have been assigned the task of a program verifier, responsible for modifying the **program state** so that the first iteration of
     the `while` loop can proceed. You will be provided with the **program state right before the loop**, which you need to modify,
     and the `while` loop statement.
- If the loop is a `while True` loop or if the loop **can certainly execute at least once**, simply repeat the program state right
     before the loop.
- **Do not make any assumptions** beyond the provided information.
- Only modify the states of **objects in the loop condition** that affect whether the loop executes.
- **Follow the text format:** **State: `state`**.
I am giving you some examples to understand the task better. Then I am giving you your task.
### Example 1
**State right before the while loop:** `total` is 10, `i` is 0, `n` is an integer.
**While loop:**
··· python
while i < n:
# the loop body is omitted
Now, please think step by step: Which states need to be adjusted for the loop to execute the first time? **Only the states of objects
     in the loop head can be adjusted.**
**Example Answer:**
The variables in the loop condition are `i` and `n`, so we can only adjust them. The loop executes while `i < n`. Right before the loop
      , `i` is 0 and `n` is an integer. Since `n` being an integer does not ensure the loop executes, it needs to be modified to `n` is
      greater than 0.
**State:** **`total` is 10, `i` is 0, `n` must be greater than 0**
### Example 2
**State right before the while loop:** `total` is 0, `students` is 2 less than its initial value.
**While loop:**
``python
while students >= 1:
# the loop body is omitted
Now, please think step by step: Which states need to be adjusted for the loop to execute the first time? **Only the states of objects
     in the loop head can be adjusted.**
**Example Answer:**
The only variable in the loop condition is `students`. The loop executes while `students >= 1`. Right before the loop, `students` is
     **2 less than its initial value**, so for the loop to execute at least once, the initial value of `students` must have been at
     least 3, and its current value must be greater than or equal to 1.
**State:** **`total` is 0, `students` is 2 less than its initial value, and `students` must currently be greater than or equal to 1**
### **Your Task**
**State right before the while loop:**
{post}
··· python
{loop_head}
# the loop body is omitted
Now, please think step by step: Which states need to be adjusted for the loop to execute the first time? **Only modify the states of
     objects in the loop head.*
Strictly adhere to the format: **State: `the state you calculate`**, and describe this state in **natural language easily
     understandable by humans**.
```

B.18 While Loop Prerequisite for Next Execution Prompt

```
You have been assigned the task of a program verifier, responsible for modifying the **program state** so that the next iteration of
     the `while` loop can proceed. You will be provided with the **program state after the previous iteration**, which you need to
     modify, and the `while` loop statement.
- If the loop is a `while True` loop or if the loop **can certainly execute one more time**, simply repeat the program state at the end
      of the previous iteration.
- **Do not make any assumptions** beyond the provided information.
- Only modify the states of **objects in the loop condition** that affect whether the loop executes.
- **Follow the text format:** **State: `state`**.
I am giving you some examples to understand the task better. Then I am giving you your task.
### Example 1
**State at the end of the previous iteration:** `total` is 10, `i` is 4, `n` is greater than 3.
**While loop:**
··· python
while i < n:
# the loop body is omitted
Now, please think step by step: Which states need to be adjusted for the loop to execute one more time? **Only the states of objects in
      the loop head can be adjusted.**
**Example Answer:**
The variables in the loop condition are `i` and `n`, so we can only adjust them. The loop executes while `i < n`. At the end of the
     last iteration, 'i' is 4, 'n' is greater than 3. 'n' being greater than 3 does not ensure another execution, so it needs to be
     modified to `n` is greater than 4.
**State:** **`total` is 10, `i` is 4, `n` must be greater than 4**
### Example 2
**State at the end of the previous iteration:** `total` is 0, `students` is 3 less than its initial value.
**While loop:**
··· python
while students >= 1:
# the loop body is omitted
Now, please think step by step: Which states need to be adjusted for the loop to execute one more time? **Only the states of objects in
      the loop head can be adjusted.**
**Example Answer:**
The only variable in the loop condition is `students`. The loop executes while `students >= 1`. At the end of the last iteration, `
     students` is **3 less than its initial value**, so for the loop to execute again, the initial value of `students` must have been
     at least 4, and its current value must be greater than or equal to 1.
**State:** **`total` is 0, `students` is 3 less than its initial value, and `students` must currently be greater than or equal to 1**
### **Your Task**
**State at the end of the previous iteration:**
{post}
••• python
{loop head}
# the loop body is omitted
Now, please think step by step: Which states need to be adjusted for the loop to execute one more time? **Only modify the states of
     objects in the loop head.**
Strictly adhere to the format: **State: `the state you calculate`**, and describe this state in **natural language easily
     understandable by humans**.
```

B.19 For Loop First Execution Necessary Condition Prompt

```
You have been assigned the task of a program verifier, responsible for understanding the **program state at the start of the `for` loop
      **. You will be provided with the **program state before the first execution of the `for` loop**, which you need to modify, and
     the `for` loop statement.
- **Do not make any assumptions** beyond the provided information.
- Only modify the states of **objects in the loop condition** that affect whether the loop executes.
- **Follow the text format:** **State: `state`**.
{\rm I} am giving you some examples to understand the task better. Then {\rm I} am giving you your task.
### Example 1
**State before the `for` loop:** `total` is 10.
**For loop:**
  ``python
for i in range(n):
  # the loop body is omitted
Now, please think step by step: Which states need to be adjusted for the loop to execute? **Only the states of objects in the loop head
      can be adjusted.**
**Example Answer:**
The only variables in the loop head are `i` and `n`, so we can only adjust those. The loop executes while `n` is at least 1. Since `
     total being 10 does not ensure that the loop will execute, `n` needs to be adjusted to be greater than 0, and `i` is initialized
      to 0
**State:** **`total` is 10, `i` is 0, `n` must be greater than 0**
### Example 2
**State before the loop starts:** `total` is 0, `students_list` is a list of students.
**For loop:**
 ••• python
for index, student in enumerate(students_list):
  # the loop body is omitted
Now, please think step by step: Which states need to be adjusted for the loop to execute? **Only the states of objects in the loop head
      can be adjusted.**
**Example Answer:**
The only objects in the loop head are `index`, `student`, and `students_list`, so we can only adjust those. The loop executes if `
     students_list` has at least 1 student. Since the `total` value does not impact execution, we focus on ensuring that
     students_list contains at least 1 student. The `index' starts at 0, and `student' is set to the first student in the list.
**State:** **`total` is 0. `students list` is a list of students that must have at least 1 student. `student` is the first student in
     the list, `index` is 0**
### **Your Task**
**State before the loop starts:**
{post}
··· python
{loop_head}
# the loop body is omitted
Now, please think step by step: Which states need to be adjusted for the loop to execute? **Only modify the states of objects in the
     loop head.**
Strictly adhere to the format: **State: `the state you calculate`**, and describe this state in **natural language easily
     understandable by humans**.
```

B.20 For Loop Prerequisite for Next Execution Prompt

You have been assigned the task of a program verifier, responsible for understanding the **program state at the start of the next iteration of a `for` loop**. You will be provided with the **program state after the previous iteration**, which you need to modify, and the `for` loop statement. - **Do not make any assumptions** beyond the provided information. - Only modify the states of **objects in the loop condition** that affect whether the loop executes again. - **Follow the text format:** **State: `state`**. I am giving you some examples to understand the task better. Then I am giving you your task. ### Example 1 **State at the end of the previous iteration:** `total` is 10, `i` is 3, `n` must be greater than 3. **For loop:** ```python for i in range(n): # the loop body is omitted Now, please think step by step: Which states need to be adjusted at the start of the next iteration of the loop? **Only the states of objects in the loop head can be adjusted.** **Example Answer:** The only variables in the loop head are `i` and `n`, so we can only adjust those. The loop executes while `i` is less than `n`. At the end of the last iteration, `i` is 3, `n` is greater than 3. Since `i` is incremented by 1 in each iteration, for the loop to execute again, `i` must be 4 and `n` must be greater than 4. **State:** **`total` is 10, `i` is 4, `n` must be greater than 4** ### Example 2 **State at the end of the previous iteration:** `total` is 0, `students_list` is a list of students that must have at least 2 students, `student` is the second student in the list, `index` is 1. **For loop:** ••• python for index, student in enumerate(students_list): # the loop body is omitted Now, please think step by step: Which states need to be adjusted for the loop to execute one more time? **Only the states of objects in the loop head can be adjusted.** **Example Answer:** The only objects in the loop head are `index`, `student`, and `students_list`, so we can only adjust those. The loop executes if ` students_list has at least 3 students. At the end of the last iteration, `students_list has at least 2 students, `student` is the second student in the list, and `index` is 1. So, for the loop to execute one more time, `students_list` must have at least 3 students, `index` must be 2, and `student` must be the third student in the list. **State:** **`total` is 0, `students_list` is a list of students that must have at least 3 students, `student` is the third student in the list, `index` is 2** ### **Your Task** **State at the end of the previous iteration:** {post} ··· python {loop_head} # the loop body is omitted Now, please think step by step: Which states need to be adjusted for the loop to execute one more time? **Only modify the states of objects in the loop head.** Strictly adhere to the format: **State: `the state you calculate`**, and describe this state in **natural language easily understandable by humans**.

B.21 Total While Loop Execution with Unrolling Prompt

Given a Python loop, an initial execution state, and the output states after the first {times} iterations of the loop, determine the output state after all the executions of the loop have finished.

You must adhere to the text format: Output State: **output state.**

Initial State: {pre}
Code of the loop:
{loop_code}

The output state after the loop executes the first {times} times includes what needed to be true for the loop to execute at least that number of times:

{loop_unrolled}

What is the ouput state after the loop executes all the iterations? Change the values of only the variables in the loop head and body. The state of the other variables in the precondition that are not affected by the loop head and body must remain unchanged. In your response strictly use the format: Output State: **the output state you calculate.**, and describe this output state in Natural language easily understandable by humans.

B.22 Total While Loop Execution Without Unrolling Prompt

Given a Python loop and an initial execution state, determine the output state after all the executions of the loop have finished.

You must adhere to the text format: Output State: **output state.**

Initial State: {pre}
Code of the loop:
{loop_code}

What is the output state after the loop executes all the iterations? Change the values of only the variables in the loop head and body. The state of the other variables in the precondition that are not affected by the loop head and body must remain unchanged. In your response strictly use the format: Output State: **the output state you calculate.**, and describe this output state in Natural language easily understandable by humans.

B.23 Total For Loop Execution with Unrolling Prompt

Given a Python loop, an initial execution state, and the output states after the first {times} iterations of the loop, determine the output state after all the executions of the loop have finished.

You must adhere to the text format: Output State: **output state.**

Initial State: {pre}
Code of the loop:
{loop_code}

The output state after the loop executes the first {times} of times includes what needed to be true for the loop to execute at least that number of times:

{loop_unrolled}

What is the ouput state after the loop executes all the iterations? Change the values of only the variables in the loop head and body. The state of the other variables in the precondition that are not affected by the loop head and body must remain unchanged. In your response strictly use the format: Output State: **the output state you calculate.**, and describe this output state in Natural language easily understandable by humans.

B.24 Total For Loop Execution Without Unrolling Prompt

Given a Python loop, and an initial execution state, determine the output state after all the executions of the loop have finished.

You must adhere to the text format: Output State: **output state.**

Initial State: {pre}
Code of the loop:
{loop_code}

What is the ouput state after the loop executes all the iterations? Change the values of only the variables in the loop head and body. The state of the other variables in the precondition that are not affected by the loop head and body must remain unchanged. The output state must be in a similar format as the initial execution state. Describe this output state in Natural language easily understandable by humans. In your response strictly use the format: Output State: **the output state you calculate.**.