Learning 3D Object Spatial Relationships from Pre-trained 2D Diffusion Models

Sangwon Beak¹ Hyeonwoo Kim¹ Hanbyul Joo^{1,2}

¹Seoul National University ²RLWRLD

https://tlb-miss.github.io/oor/



our method models OOR, representing their relative poses and scales with respect to the text. We obtain synthetic OOR samples using off-the-shelf models and a proposed mesh registration method, then learn their distribution through OOR diffusion. During inference, our OOR diffusion model generates OOR samples conditioned on the text input.

Abstract

We present a method for learning 3D spatial relationships between object pairs, referred to as object-object spatial relationships (OOR), by leveraging synthetically generated 3D samples from pre-trained 2D diffusion models. We hypothesize that images synthesized by 2D diffusion models inherently capture plausible and realistic OOR cues, enabling efficient ways to collect a 3D dataset to learn OOR for various unbounded object categories. Our approach begins by synthesizing diverse images that capture plausible OOR cues, which we then uplift into 3D samples. Leveraging our diverse collection of plausible 3D samples for the object pairs, we train a score-based OOR diffusion model to learn the distribution of their relative spatial relationships. Additionally, we extend our pairwise OOR to multi-object OOR by enforcing consistency across pairwise relations and preventing object collisions. Extensive experiments demonstrate the robustness of our method across various object-object spatial relationships, along with its applicability to realworld 3D scene arrangement tasks using the OOR diffusion model.

1. Introduction

In real-world scenes, specific spatial and functional patterns exist between objects. While some of these patterns are constrained by physical laws (e.g., objects can rest on others but cannot float in mid-air), many originate from functional usage, reflecting how humans interact with and arrange these objects. For instance, chairs are commonly positioned around tables, and items such as cups and bottles are usually placed on tables rather than chairs, despite the physical possibility of alternative arrangements. More sophisticated patterns also exist; for example, a pizza cutter is typically angled relative to the pizza to facilitate slicing across its diameter (as shown in Fig. 1). These intuitive yet diverse relationships between objects, which we refer to as object-object relationships (OOR), capture the relative poses and scales between object pairs. Enabling machines to understand and generate these natural layouts and spatial relationships is crucial for various applications, including content creation, immersive VR/AR experiences, and robotic manipulation tasks aimed at mimicking human behaviors. However, the diversity of object relationships, considering object categories, contexts, and scenarios, makes it challenging to model these patterns through manual annotation or data collection in controlled setups.

One promising approach is to learn spatial relationships between objects from 2D images. However, raw images from the Internet are often cluttered and overly "wild", complicating the learning of precise 3D spatial relationships between objects. To overcome this limitation, we present an approach to learn 3D object-object relationships from synthetically generated 3D samples capturing plausible OORs. Our method is inspired by recent approaches that pursue humanobject interaction and affordances through synthetic images generated by pre-trained image diffusion models [17, 26], where the 2D diffusion model offers effective ways to generate samples for learning such relations.

We begin by rigorously formalizing our definition of OOR, considering the relative scale and pose between object categories. To address the scarcity of available 3D data for learning OORs across diverse object pairs, we introduce a framework that efficiently generates diverse and realistic 3D spatial relationship samples from synthesized 2D images, eliminating the need for labor-intensive data collection or manual annotation. Our 3D lifting pipeline provides a robust solution to reconstruct 3D samples from synthetically generated multi-view 2D images of object-pairs. Next, we present a text-conditioned OOR diffusion based on a score-based model [59, 73] in the spatial parametric space, capable of modeling relative rotations, translations, and scales between objects across diverse scenarios. Our OOR diffusion generates various OOR patterns conditioned on a text prompt describing the scene context. To enhance generalization, we leverage LLM [42] for text context augmentation, expanding our dataset to cover 475 distinct OOR scenarios. In addition, we extend our pairwise OOR modeling to multi-object settings, capturing the spatial relationships among multiple objects within a shared 3D space. Through extensive experiments, we demonstrate the robustness of our method across various object-object spatial relationships. Furthermore, we present several real-world 3D scene arrangement tasks as key applications of our OOR diffusion model.

In summary, our main contributions are as follows: (1) We formulate a novel representation for object-object spatial relationships (OOR); (2) We introduce an effective pipeline for generating diverse 3D OOR data from synthetic images, incorporating prompting strategies, data augmentation, and filtering; (3) We propose a text-conditioned score-based diffusion model to effectively model the OOR distribution. To improve generalization across diverse OOR scenarios, we incorporate LLM-based text augmentation. Moreover, we extend pairwise OOR modeling to the multi-object setting by introducing an optimization strategy guided by novel inference losses; (4) We demonstrate the capability of our OOR diffusion model for 3D scene editing through an optimization technique that directly leverages the score function of the underlying distribution—a key property of score-based models.

2. Related Work

Learning Object Spatial Relationships. In the field of robotics, research on spatial relations between objects has primarily focused on teaching robots to learn and replicate object placement [3, 20, 24, 29, 37, 40, 45, 52, 67]. However, these methods often overlook complex relationships, like "a teapot pouring tea into a teacup." In object detection, there is a growing emphasis on leveraging spatial relationships between objects to improve detection performance, particularly for identifying occluded or challenging-to-recognize objects [33, 76]. For indoor scenes, the availability of 3D datasets [5, 11, 22, 51, 56, 60] capturing object-object spatial relationships has accelerated progress in layout estimation [32, 78], CAD model retrieval [12, 16, 23, 28, 31, 38], and scene generation [44, 70]. However, these methods are limited to predefined object categories, whereas our approach addresses unbounded object pairs.

Learning from Pre-trained 2D Diffusion Models. Advent of diffusion models [7, 18, 55] significantly boosting performance and accelerating advancements in the field. Accordingly, various research efforts have focused on leveraging the vast 2D knowledge embedded in pre-trained diffusion models to extract new insights and enable novel applications. CHORUS [17] and ComA [26] propose a method to learn human-object relationships and interactions from inconsistent 2D image pools generated by diffusion. Our method is inspired by these and models object-object relationships beyond human-object relationships. However, unlike humans, pose estimation of objects is more difficult, making our task a bit more challenging. Moreover, various approaches have been developed to extract semantic features from images using pre-trained diffusion models[39, 69, 71, 72, 75].

Score-based Diffusion Models. A score-based generative model [57, 58] models a distribution using the score function, which is often more tractable than directly computing the likelihood. Also in [59], it was integrated with diffusion models. Score-based approaches are widely adopted not only for image generation but also for pose generation and estimation tasks for objects [21, 73] and humans [4, 36, 53]. In particular, GenPose [73] is the backbone of our OOR diffusion, which estimates the 6D pose of a given point cloud. However, our OOR diffusion takes text as a condition instead of point clouds, and models not only object poses but also scales.

3. Method

We present a method for learning object-object spatial relationships (OOR) from synthetically generated 2D images by pre-trained diffusion models. We model OOR based on relative poses and scales of a pair of objects in canonical space. In Sec. 3.1 we formalize our definition of OOR. Then, in Sec. 3.2, we describe our pipeline for constructing 3D OOR dataset by generating 2D synthetic images and uplifting them to 3D. Finally, in Sec. 3.3, we present our OOR diffusion model trained on the generated 3D OOR dataset to learn the distribution of object-object relationships. We further extend our approach from pairwise to multi-object OORs, enabling the modeling of spatial relationships among multiple objects within a shared space.

3.1. Formulating Object-Object Relationship

We define OOR as the relative poses and scales between a pair of object categories within a context specified by a text prompt c which describes object categories and their spatial relationships. Each 3D object instance is represented within an *instance canonical space* where coordinates are defined by centering the origin at the midpoint of the object's tightest 3D bounding box. The 3D Bbox's up-vector is aligned to the *y*-axis, and its ground plane is parallel with the x-z plane. The frontal side of the object, typically the most observable view, faces the positive z-axis, although our method accommodates any canonical orientation. In this canonical space, the scale is normalized such that the longest edge of the 3D bounding box is set to 1, while keeping the aspect ratios of the objects. See Fig. 2 for an example. To account for varying aspect ratios within the same object category for spatial relation modeling, we further consider the scale-normalized canonical space where the 3D bounding box is normalized into a unit cube with length 1 with all axes. We consider the scaling factor $\mathbf{s} \in \mathbb{R}^3_+$ defined per each object instance to recover the original aspect ratio from the scale-normalized one: $\mathbf{x} = \mathbf{s} \cdot \hat{\mathbf{x}}$, where $\hat{\mathbf{x}} \in \mathbb{R}^3$ is the 3D point in the scale-normalized canonical space and $\mathbf{x} \in \mathbb{R}^3$ is the 3D point in the original instance canonical space with original aspect ratio.

Given a pair of objects, we denote one as a base object and the other as a target, formulating OOR as the relative poses and scales of a target object with respect to a base object. For example, given a context addressed as a text prompt c, "A teapot pouring tea into a teacup", we model the OOR as the relative poses and scales of the teapot (a target object) with respect to the teacup (a base object) in the teacup's canonical space. Note that we can consider either object as the base object without loss of generality.

Specifically, given a text prompt c describing the OOR context, a base object category \mathcal{B} , and a target object category \mathcal{T} , their OOR distribution $p_{c}^{\mathcal{T} \to \mathcal{B}}$ and OOR sample ϕ are



Figure 2. **Our Coordinate Systems.** We conceptually model the transformation from a scale-normalized space, where the tightest 3D bounding box of each object is normalized to the unit cube, to a canonical space for each object instance within an object category.

defined as follows:

$$\phi \sim p_{\mathbf{c}}^{\mathcal{T} \to \mathcal{B}}, \ \phi = (\mathbf{R}^{\mathcal{T} \to \mathcal{B}}, \mathbf{t}^{\mathcal{T} \to \mathcal{B}}, \mathbf{s}^{\mathcal{T} \to \mathcal{B}}, \mathbf{s}^{\mathcal{B}}),$$
(1)

where $\mathbf{R}^{\mathcal{T}\to\mathcal{B}} \in SO(3)$, $\mathbf{t}^{\mathcal{T}\to\mathcal{B}} \in \mathbb{R}^3$, and $\mathbf{s}^{\mathcal{T}\to\mathcal{B}} \in \mathbb{R}^3_+$ represent the rotation, translation, and scale transformations that convert a point $\hat{\mathbf{x}}_{\mathcal{T}} \in \mathcal{T}$ of the *target object* (in the scale-normalized canonical space) into the instance canonical space of the *base object*, resulting in $\mathbf{x}_{\mathcal{T}\to\mathcal{B}}$:

$$\mathbf{x}_{\mathcal{T}\to\mathcal{B}} = \mathbf{R}^{\mathcal{T}\to\mathcal{B}} \cdot (\mathbf{s}^{\mathcal{T}\to\mathcal{B}} \odot \mathbf{\hat{x}}_{\mathcal{T}}) + \mathbf{t}^{\mathcal{T}\to\mathcal{B}}, \qquad (2)$$

where \odot denotes the element-wise product. The $s^{\mathcal{B}} \in \mathbb{R}^3_+$ is the scaling factor to convert from the point in the scalenormalized space, $\hat{\mathbf{x}}_{\mathcal{B}}$, into the instance space with the original aspect ratio of it:

$$\mathbf{x}_{\mathcal{B}} = \mathbf{s}^{\mathcal{B}} \odot \mathbf{\hat{x}}_{\mathcal{B}}.$$
 (3)

Intuitively, an OOR sample ϕ represents a plausible relative spatial relationship for the target object relative to the base object. The use of a non-isotropic scaling factor $s^{\mathcal{B}} \in \mathbb{R}^{3}_{+}$ that accounts for the original aspect ratio of the 3D BBox is important, as OOR is inherently influenced by object size and shape. For instance, understanding the dimensions and height of a table's top panel is essential when positioning objects on it, an aspect we approximate using the bounding box scale in our formulation.

3.2. 3D OOR Samples Generation

To effectively learn OOR defined in Eqs. 1-3, diverse 3D samples showing plausible spatial relationships of each object pair are required. In particular, we consider the distributions conditioned on each text prompt c, to capture the contextual nuances of these relationships, as spatial configurations can vary across different contexts even for the same object pair. Given the fact that obtaining such 3D samples from the real-world is challenging, we present a novel pipeline for synthetically collecting diverse 3D samples, leveraging pre-trained 2D diffusion models and an advanced 3D uplifting process to generate 3D OOR samples. **High-quality 2D OOR Images Synthesis.** We use an off-the-shelf text-to-image model [2] to generate images that



Figure 3. **Dataset Generation Overview.** For a given text prompt related to an object pair, we obtain multi-view images and point clouds using off-the-shelf models. Then, we lift pixel features to obtain 3D point features. We repeat the same process for the rendered images of collected meshes. Finally, we perform Procrustes analysis with RANSAC to estimate the relative pose and scale of each object.

aligned to the desired OOR context specified by a text prompt c. We design the prompt with specific strategies to facilitate the later 3D lifting process, including: (1) appending "white background" to the end of the prompt to ensure the full shape of each object is clearly visible; (2) incorporating object shape descriptions to better align with our template object meshes for categories with diverse shapes, such as chairs; (3) Adjusting the viewpoint to mitigate image frame constraints for category pairs with large scale differences, such as (table, teacup). Additionally, we further diversify the OOR image samples using the image-to-video model [62] to generate diverse OORs within the context. Each frame of the synthesized video is used as an additional synthesized 2D sample, ignoring temporal information. Further discussion of prompting and augmentation strategies is provided in Sec. A.

Pseudo Multi-view Generation and SfM. Given an image that includes the OOR cues for the target object pair, we produce pseudo-multi-view images using an off-the-shelf novel view synthesis method, SV3D [64], which generates novel view images on the orbital viewpoint changes by taking a single image input. To enhance multi-view synthesis quality, we first apply a segmentation method [25, 30, 35, 50] to remain the relevant object pair only, removing all background clutter. While the pseudo-multi-view synthesis produces visually plausible outputs, it does not guarantee perfect geometric consistency across views. Interestingly, we find that the recent learning-based structure-from-motion (SfM) approach, VGGSfM [65], produces plausible 3D reconstruction outputs from synthesized multi-view inputs. However, this method still occasionally fails to produce reliable 3D outputs, so we filter out unsuccessful reconstructions by checking the number of 3D points in the resulting point clouds. As the output of SfM, we obtain the 3D point cloud $\mathcal{P} = \{\mathbf{P}_j\}_{j=1}^N, \ \mathbf{P}_j \in \mathbb{R}^3$, and their corresponding 2D keypoints, $\{\mathbf{p}_{j}^{k}\}_{k=1}^{m_{j}}, \mathbf{p}_{j}^{k} \in \mathbb{R}^{2}$, where N denotes the number of 3D points, and m_i is the number of corresponding 2D keypoints for the *j*-th 3D point.

Pose and Scale Extraction through Mesh Registration. Given the point cloud \mathcal{P} reconstructed in a certain coordinate

system (denoted as point cloud space), we register the base object's template mesh $\mathcal{M}_{\mathcal{B}}$ and the target object's template mesh $\mathcal{M}_{\mathcal{T}}$ from their canonical spaces to the point cloud. From this registration, we compute their relative spatial transformation $T_{\rm rel}$, which is parameterized by Eq. 1.

We first separate the 3D points cloud into the base object part and the target object part, resulting in the base object points $\mathcal{P}_{\mathcal{B}}$ and target object points $\mathcal{P}_{\mathcal{T}}$. To achieve this, we apply a 2D segmentation method on the pseudo-multiview 2D images. We find that treating the pseudo-multiview images as a video and applying a video segmentation model [48, 49] shows better segmentation quality. Next, we register each template mesh into the corresponding point cloud. For simplicity, we omit the object indicator, and denote the point clouds as \mathcal{P} and the template mesh in the canonical space as \mathcal{M} .

To register each mesh to the point cloud space, we leverage the semantic correspondence features [72] by extracting the cues from 2D views. Specifically, for each 3D point \mathbf{P}_{i} , we consider its corresponding 2d projections in the corresponding 2D image space $\{\mathbf{p}_j^k\}_{k=1}^{m_j}$ and extract the semantic features $\mathbf{f}_i^k \in \mathbb{R}^F$ at each pixel via the method of [72], where F is the semantic feature dimension (F=768 in practice). We apply the same 2D semantic feature extraction process for each point on the template mesh model M_i from its rendered 2D views. Then we aggregate the semantic features from 2D views into a single feature vector for the corresponding 3D point. Rather than directly taking the mean of the 2D feature vectors, we find that it is more effective to reduce the dimension of the semantic features by applying PCA [19] as a way to extract more important signals and reduce noisy parts. To apply PCA, we aggregate all 2D features from both pseudomulti-view images and rendered template mesh images, and reduce the semantic feature dimensions to $\mathbf{f'}_{j}^{k} \in \mathbb{R}^{F'}$, where F' < F (F'= 15 in practice). Finally, for each 3D point, we compute the mean feature vector from the corresponding 2D features in the reduced feature dimension. The effectiveness of this PCA-based dimensionality reduction for registration is demonstrated in our experiments (Sec. 4.4).



Figure 4. Training Process of OOR Diffusion. Our OOR diffusion generates OOR samples by taking the context c, base object category \mathcal{B} , and target object category \mathcal{T} as text conditions.

Given the semantic features associated with the 3D point cloud and template mesh points, we establish correspondences by identifying nearest neighbors based on cosine similarity among semantic features. We retain only those whose similarity exceeds a certain threshold. We use Procrustes analysis [14, 15] with RANSAC [10] for the registration, followed by ICP to further refine it [1]. To this end, we obtain the transformation T from \mathcal{M} to \mathcal{P} :

$$T\left(\mathcal{M}; s, \mathbf{R}, \mathbf{t}\right) = s \cdot \mathbf{R}\mathcal{M} + \mathbf{t} \approx \mathcal{P},\tag{4}$$

where T is parameterized by 3D rotation $\mathbf{R} \in SO(3)$, 3D translation $\mathbf{t} \in \mathbb{R}^3$, and an isotropic scaling factor $s \in \mathbb{R}_+$, transforming the point in the mesh template \mathcal{M} into the point cloud space \mathcal{P} .

By applying this registration process per each template model, we can compute the transformation from each mesh template model into a common point cloud space: $T_{\mathcal{B}\to\mathcal{P}}$ and $T_{\mathcal{T}\to\mathcal{P}}$. Finally, we can find the relative pose and scale of the $\mathcal{M}_{\mathcal{T}}$ relative to $\mathcal{M}_{\mathcal{B}}$, denoted as $T_{\mathcal{T}\to\mathcal{B}}$:

$$T_{\mathcal{T}\to\mathcal{B}} = T_{\mathcal{P}\to\mathcal{B}} \circ T_{\mathcal{T}\to\mathcal{P}},$$

$$T_{\mathcal{T}\to\mathcal{B}} : \mathcal{M}_{\mathcal{T}} \mapsto s_{\mathcal{T}\to\mathcal{B}} \cdot \mathbf{R}_{\mathcal{T}\to\mathcal{B}} \mathcal{M}_{\mathcal{T}} + \mathbf{t}_{\mathcal{T}\to\mathcal{B}},$$
 (5)

where $T_{\mathcal{P}\to\mathcal{B}}$ is the inverse transformation of $T_{\mathcal{B}\to\mathcal{P}}$. Note that we use an isotropic scaling factor $s \in \mathbb{R}_+$ for simplicity during the registration by keeping the original aspect ratio. After the registration, we multiply the size of the tightest 3D bounding box to represent the same 3D bbox scale representation defined in Eq. 1, as follows:

$$\mathbf{s}^{\mathcal{T} \to \mathcal{B}} := s_{\mathcal{T} \to \mathcal{B}} * \mathrm{BBOX}(\mathcal{T}),$$
$$\mathbf{s}^{\mathcal{B}} := \mathrm{BBOX}(\mathcal{B}).$$
(6)

Fig. 3 shows the overview of OOR dataset generation process. In practice, to account for the shape difference between the template mesh and the reconstructed outputs, we use several template meshes as candidates and select the one that best fits the reconstructed object based on the DINO [6, 43] features. We also apply a series of automatic filtering processes to remove unreliable samples. See Sec. A for details.

3.3. OOR Diffusion

We model the pairwise OOR distribution $p_{\mathbf{c}}^{\mathcal{T} \to \mathcal{B}}$ via a diffusion model conditioned by various OOR contexts \mathbf{c} , with



Figure 5. Scene Graph Example. The scene graph for multi-object OOR is represented as a connected DAG with one start node.

our collected dataset in Sec. 3.2. Our OOR diffusion model is based on a score-based model, following the approach of GenPose [73] that is originally introduced for 6D object pose estimation. Let our OOR diffusion Ψ_{θ} , parameterized with θ . Then Ψ_{θ} models the noised score function at time step t of the $p_{\mathbf{c}}^{\mathbf{T} \to \mathcal{B}}$:

$$\Psi_{\theta}(\phi_t, t | \mathbf{c}, \mathcal{B}, \mathcal{T}) = \nabla_{\phi_t} \log p_{\mathbf{c}}^{\mathcal{T} \to \mathcal{B}}(\phi_t), \tag{7}$$

where ϕ_t is a noised OOR sample at time step t, c is the text prompt of OOR context, \mathcal{B} , and \mathcal{T} represent base object category and target object category, respectively. Specifically, we take c, \mathcal{B} , and \mathcal{T} as text input and encode them with the pre-trained T5 text encoder [47]. According to Denoising Score Matching(DSM) [63], by optimizing the following objective function, we can obtain Eq. 7:

$$\mathcal{L}_{\text{score}}(\theta) = \mathbb{E}_t \left[\lambda_t \mathbb{E}_{\phi, \phi_t} \left[\left\| \Psi_{\theta}(\phi_t, t | \mathbf{c}, \mathcal{B}, \mathcal{T}) - \frac{\phi - \phi_t}{\sigma(t)^2} \right\|_2^2 \right] \right], \quad (8)$$

where $t \sim (\epsilon, 1)$ with minimal noise level ϵ , $\phi \sim p_{c}^{T \to B}$, $\phi_{t} \sim \mathcal{N}(\phi, \sigma^{2}(t)\mathbf{I}), \sigma^{2}(t)$ is variance factor that increases exponentially with noise level, and λ_{t} is regularization term according to noise level. The model architecture and training process of our OOR diffusion are shown in Fig. 4. For the inference, we can sample an OOR $\phi \sim p_{c}^{T \to B}$, from pure Gaussian noise using the reverse ODE process [8, 59], which solves the following Probability Flow ODE from t = 1 to $t = \epsilon$:

$$\frac{d\phi_t}{dt} = -\sigma(t)\dot{\sigma}(t)\nabla_{\phi_t}\log p_{\mathbf{c}}^{\mathcal{T}\to\mathcal{B}}(\phi_t).$$
(9)

Text Context Augmentation. For better generalization, we leverage an LLM [42] to diversify the OOR context c in two ways. First, we augment c with variations in prompt phrasing (e.g., verbs and sentence structure), while preserving the original semantic meaning. Second, we also diversify the object categories where the same relations hold. For example, the context "A teapot pours tea into a teacup" can represent similar spatial relations with "A kettle pours tea into a cup", despite referring to different object categories with similar shapes and sizes that can substitute the context c, while preserving the same OOR distributions. We find that our text context augmentation improves generalization by enabling OOR modeling under a broader range

of contextual conditions. For details on data augmentation, see Sec. B. As a result, we train our model for 475 distinct contexts with 23750 text prompts, each capturing various spatial relationships between object pairs across 188 object categories.

Extend to Multi-object OOR. To model the spatial relationships of multiple objects within a shared 3D space, we present a method to extend our pairwise OOR contexts into multi-object OORs. Given a set of pairwise contextual conditions describing a scene with multiple objects (e.g., Fig. 5), we aim to generate multi-object OORs from n pairwise OOR distributions, $\{\phi_t^{p_i}\}_{i=1}^n \sim \{p_i\}_{i=1}^n$, where p_i represent the *i*-th pairwise OOR. Specifically, we represent a scene as a connected Directed Acyclic Graph (DAG) with a single starting node (global base), as shown in Fig. 5. Each node represents an object, while each edge represents a pairwise OOR, where base-target object relationships are structured as parent and child nodes. The final scene layout is determined by setting the global base node as the reference for the global coordinate system, and sequentially applying the sampled pairwise spatial relations($\phi_t^{p_i}$) following the graph path to position all objects within the global coordinate system.

However, naively sampling from each pairwise OOR introduces two critical challenges: (1) collisions may occur between objects, (2) inconsistency issues arise when multiple pairwise relations define an object's pose and scale differently. For instance, in Fig. 5, the keyboard's spatial pose and scale can be determined via two distinct paths, relative to either the monitor or the mouse. Since these paths may yield different OOR layouts, a simple averaging of multiple available OOR cues may not produce a plausible final arrangement.

To address these issues, we present an approach to infer all multi-object OORs $\Phi = \{\phi_t^{p_i}\}_{i=1}^n$ simultaneously, by including our novel loss terms: collision loss $C(\Phi)$ and inconsistency loss $I(\Phi)$. This modifies the reverse ODE process in Eq. 9 for all *i* as follows:

$$\frac{d\phi_t^{p_i}}{dt} = -\sigma(t)\dot{\sigma}(t)\nabla_{\phi_t^{p_i}}\log p_i(\phi_t^{p_i})
+\lambda_1\nabla_{\phi_t^{p_i}}C(\Phi) + \lambda_2\nabla_{\phi_t^{p_i}}I(\Phi),$$
(10)

where λ_1 and λ_2 are weight terms. The collision loss penalizes overlapping axis-aligned bounding boxes of positioned objects based on the sampled OOR cues. Note that the collision loss is only applied to object pairs without an explicitly defined OOR(i.e., two non-adjacent nodes) in the scene. In other words, for each object pair without an explicitly defined OOR, we assume that their spatial relationship corresponds to a non-colliding configuration. The inconsistency loss minimizes the variance among OOR cues for the same object from different base object paths. See Sec. B for details of inconsistency loss.

Metrics	SMC [61]	SceneTeller [41]	Ours
CLIP Score ↑	28.54	29.06	29.11
VQA Score ↑	0.61	0.68	0.69
VLM Score ↑	49.83	64.67	75.67
User Study(%) ↑	22.21	23.77	54.02

Table 1. Quantitative Comparisons of Pairwise OOR Generation. For each method, we evaluate the CLIP score [46], the VQA score [34], our proposed VLM score [68], and conduct a user study.

4. Experiments

We demonstrate the practical efficacy and generalization of our method through four main experiments. In Sec. 4.1, we show that our diffusion model generates OORs that fit the text context more plausibly and effectively than other methods. Sec. 4.2 demonstrates our advanced sampling approach produces significantly better results compared to text-to-3D models. In Sec. 4.3, we present an optimization technique that leverages the characteristics of the score-based model as an application of our OOR diffusion. Finally, Sec 4.4 presents an ablation study, verifying the superiority of our dataset generation method.

4.1. Pairwise OOR Generation

Baseline Methods. Since the concept of object-object spatial relationships (OOR) is new in the field, there exists no existing competitor with the same goal. Thus, we compare our method with LLM-based methods that achieve similar goals: SceneMotifCoder(SMC) [61], which focuses on 3D object alignments, and SceneTeller [41], which deals with 3D layout on a plane.

SceneMotifCoder (SMC) [61] is an example-driven visual program learning method. It takes text prompts as input and produces 3D object alignments by selecting and arranging meshes from a mesh pool. Given an example of a GT text prompt and mesh alignments in training, SMC analyzes patterns within the input, generates programs, and updates the program when new examples are introduced. During the inference process, when an input text comes in, LLM maps it to an appropriate task, and the program produces 3D object arrangements with the retrieved meshes from the candidate mesh pool. We convert our template mesh pairs obtained in the dataset generation process (Sec. 3.2) into the SMC format. Since SMC is not concerned about the relative scale between objects, we use meshes with scales in our OOR dataset as a mesh pool during inference.

SceneTeller [41] leverages LLMs for in-context learning by providing the LLM with pairs of (*GT text prompt*, *GT scene layout*), enabling it to generate the appropriate scene layout for a test prompt. However, existing methods only focus on the layout for placement on the plane. To generate (*GT text prompt*, *GT OOR*) pairs, we instruct the LLM with our world coordinate system and object canonical space. Then, we provide the GT OORs for generating



Figure 6. **Qualitative Comparisons of Pairwise OOR Generation.** Our method models object-object spatial relationships better than LLM-based baselines.

corresponding text prompts. It also allows LLM to generate additional prompts for inference based on the generated GT prompts. For rotation, Euler angles format is chosen as the representation because LLMs tend to generate incomplete SO(3) matrices.

Metrics. Since there is no existing metric for OOR, we introduce several evaluation metrics to assess text prompt alignment with the plausibility of spatial relationship outputs in multi-view renderings. The CLIP score [46] measures text-image alignment by averaging CLIP model logits. The VQA score [34] leverages a VQA model to assess object composition and relations. However, since these methods evaluate per single image, we adopt GPTEval3D [68] to evaluate the text-to-3D alignment in multi-view images by leveraging

VLMs [42]. Inspired by this, we propose the VLM score, which evaluates how well OOR is represented in multi-view images. The VLM score is measured in a pairwise manner, averaging the percentage of times a method is preferred (with a maximum score of 100), while allowing ties. Additionally, we conduct a user study on CloudResearch, surveying a total of 92 respondents. Details on guided prompts for VLM and the questionnaire for user study are in Sec. C.

Results. We evaluate both our method and the baselines on a total of 150 scenes derived from 30 category pairs with 5 scenes generated per prompt. Each scene is rendered into 10 views with a white background. SMC provides the arranged meshes itself, while SceneTeller provides the relative pose and scale. The baselines can reason about simple spatial re-



Figure 7. Qualitative Comparisons of Multi-object OOR Generation. We generate multi-object OOR by combining each sample from our pairwise OOR diffusion model. Our method better captures multi-object OOR compared to the diffusion-based text-to-3D model.

	Canny Edge ControlNet		Depth ControlNet	
Metrics	GraphDreamer [13]	Ours	GraphDreamer	Ours
CLIP Score ↑	27.09	28.73	28.51	28.47
VQA Score ↑	0.44	0.71	0.62	0.79
	Original Rendering			
Metrics	GraphDreamer		Ours	
VLM Score ↑	2.50		97.50	
User Study(%) ↑	11.88		88.12	

 Table 2. Quantitative Comparisons of Multi-object OOR Generation.

lationships such as "on" or "next to" reasonably but struggle with functional relationships. Fig. 6 shows a qualitative comparison for rendered multi-view images between our method and baselines for these examples. In the case of SMC, despite the program handling translation appropriately, it often completely misinterprets rotation information. SceneTeller, on the other hand, benefits from the strong in-context learning capability of LLMs, enabling reasonable estimations. However, due to the inherent limitation of estimating 3D information without direct 3D data, it lacks fine-grained control. In contrast, our OOR diffusion demonstrates superior sampling capabilities compared to the baselines, leveraging its effective learning of the OOR distribution with respect to the text context. Tab. 1 shows that our method outperforms baselines for all metrics.

4.2. Multi-object OOR Generation

Implementation Details. The specific settings for the weight terms in Eq. 10 are as follows: (1) $\lambda_1 = \min(\frac{100}{t}), 10^4$); (2) $\lambda_2 = \min(\frac{100}{t^2}, 10^5)$. Additionally, this constraint is applied starting from t = 0.5.

Baseline Method. Since SMC and SceneTeller cannot be directly extended to multi-object OOR using only pairwise OOR data, we compare our model to another baseline Graph-Dreamer [13], which generates compositional 3D scenes from text inputs. While GraphDreamer generates multiple objects, it employs neural implicit representation [66] for 3D objects, which may result in low texture quality. This difference makes direct comparison challenging, as our method

renders scenes with template meshes. To mitigate the impact of rendering quality, we use ControlNet [74] to standardize the output style of synthesized images by using Canny edge or depth as guidance.

Metrics. We use the same metrics as in Sec. 4.1. However, for per-image scores such as CLIP score and VQA score, we apply them only to the ControlNet-generated images. Meanwhile, for multi-view-dependent metrics such as VLM score and user study(conducted with 81 respondents), we evaluate the original renderings. We guide both the VLM and human evaluators to ignore rendering quality and focus primarily on OOR.

Results. We evaluate 20 scenes where 3 to 5 objects have spatial relations with each other. As shown in Fig. 7, Graph-Dreamer often fails to capture OOR (e.g., "A knife cuts an apple."). It even omits certain objects, such as a computer mouse or a salt shaker. In contrast, our method reliably generates multi-object OOR by leveraging pairwise OOR knowledge. The quantitative comparison in Tab. 2 further demonstrates the superiority of our method, especially in the case of VLM score and user study.

4.3. Applications of OOR for Scene Editing

Our OOR diffusion, built on a score-based model, enables the application of optimization techniques in various 3D scene editing scenarios.

Denoising 3D Scene Arrangement. Given a scene with multiple objects in a noisy arrangement, we use our method to "denoise" the arrangement, producing a more plausible and realistic object arrangement. Intuitively, we use our OOR diffusion to guide the noisy input arrangements toward high-likelihood regions in the OOR distribution. For simplicity, consider a scene with a pair of objects, a base object and a target object, $(\mathcal{B}, \mathcal{T})$, with a relationship defined by context c. Given a noisy scene arrangement ϕ_0 as input, our method optimizes the OOR $\phi \sim p_c^{\mathcal{T} \to \mathcal{B}}$ by minimizing the following objective function:

$$\mathcal{L}_{\text{arrange}}(\phi) = ||\phi - \phi_0||_2^2 - \lambda_1 \log p_{\mathbf{c}}^{\mathcal{T} \to \mathcal{B}}(\phi), \qquad (11)$$

where λ_1 is a weight term. By minimizing Eq. 11, our method projects the input arrangement ϕ_0 into a higher-likelihood region under $p_c^{\mathcal{T} \to \mathcal{B}}$. The gradient of the objective function is:

$$\nabla_{\phi} \mathcal{L}_{\text{arrange}}(\phi) = 2(\phi - \phi_0) - \lambda_1 \nabla_{\phi} \log p_{\mathbf{c}}^{\mathcal{T} \to \mathcal{B}}(\phi).$$
(12)

Using Eq. 7, we can approximate the gradient of loglikelihood term as, $\Psi_{\theta}(\phi, \epsilon | \mathbf{c}, \mathcal{B}, \mathcal{T}) \approx \nabla_{\phi} \log p_{\mathbf{c}}^{\mathcal{T} \to \mathcal{B}}(\phi)$. Thus, we update ϕ with the following gradient descent:

$$\phi \leftarrow \phi - \eta [(\phi - \phi_0) - \lambda_1 \Psi_\theta(\phi, \epsilon | \mathbf{c}, \mathcal{B}, \mathcal{T})], \qquad (13)$$

where $\eta = 0.01$ and $\lambda_1 = 0.01$. Since the scale of each object is predetermined here, we only need to update the





Figure 8. Scene Editing Results. Results of editing the original ParaHome scene, which includes a table, chair, teacup, and teapot, using our OOR diffusion. (a) adding random noise to the original scene and then rearranging it. (b) applying the context "A teapot pouring tea into a teacup" to the original scene. (c) adding a pan and a salt shaker to the original scene and applying "A salt shaker sprinkles salt into a pan."

relative pose $\phi' = (\mathbf{R}^{\mathcal{T} \to \mathcal{B}}, \mathbf{t}^{\mathcal{T} \to \mathcal{B}})$. For multi-object scenarios, we leverage the introduced loss terms, $C(\Phi)$ and $I(\Phi)$, in Eq. 10. In practice, optimization is completed within 50 steps.

Applying Different Contexts for the Rearrangement. We use our method to apply different scene contexts c given a scene arrangement. This can be performed by replacing the input context c in our OOR diffusion and applying the rearrangement with our optimization pipeline (Eqs. 11-13).

Adding New Objects. Our method enables adding new objects into the scene by applying multi-object OOR generation (Eq. 10) to optimize their relative poses, while keeping the OORs in the existing scene and the scale of the inserted objects fixed.

Results. We demonstrate the efficacy of our OOR models for scene arrangement tasks using ParaHome DB [27], which provides 3D scenes with separate object meshes. Fig. 8(a) shows the result of rearranging (denoising) a scene after adding random noise to the original scene. In Fig. 8(b), we apply a scene context, where the teapot, which is initially placed next to the teacup, is adjusted to pour tea into the teacup. Finally, in Fig. 8(c), we demonstrate adding a pan and a salt shaker which are not originally present in the table, and then applying an optimization with a different scene context: "A salt shaker sprinkles salt into a pan".





4.4. Ablation Study

We compare our OOR distribution to the real data distribution and perform an ablation study to provide further justification for our OOR data generation pipeline.

Dataset. We use the ParaHome DB [27], which captures dynamic 3D movements of humans and objects in a home environment. We extract three OOR distributions: ('cutter board', 'knife'), ('teacup, 'teapot'), and ('pan', 'salt shaker'). To exclude the approach and departure of humans relative to an object, we use the middle 70% of sequences. Since there is only one instance for each category, the scale is constant. Therefore, we construct a joint distribution for $(\mathbf{R}^{T \to B}, \mathbf{t}^{T \to B})$.

Baseline Methods. We ablate our mesh registration pipeline (Sec. 3.2) by removing point cloud separation and PCA on semantic features (SD+DINO [72]), comparing them with

Methods		Fráchet distance (FD)	
PCA	Segmentation	The check distance $(\Gamma D) \downarrow$	
\checkmark		1.87	
	\checkmark	1.50	
\checkmark	\checkmark	1.43	

Table 3. Ablation Study for Data Generation. We demonstrate the superiority of our data generation method through an ablation study. We compare the similarity between real data's OOR distributions and synthetic OOR distributions produced by our approach.

our full pipeline.

Metric. We use the Fréchet distance (FD) [9] to measure distribution similarity. When two distributions p and q are approximated by a multivariate Gaussian, the FD score d of the two distributions is given by:

$$d^{2} = \|\mu_{p} - \mu_{q}\|^{2} + \operatorname{tr}\left(\Sigma_{p} + \Sigma_{q} - 2\left(\Sigma_{p}\Sigma_{q}\right)^{1/2}\right), \quad (14)$$

where μ_p is mean of p, μ_q is mean of q, Σ_p is covariance matrix of p, and Σ_q is covariance matrix of q. Since rotation and translation have different units in each context, we train a 3-layer MLP encoder-decoder on 50M randomly sampled rotation matrix and translation vector. Then we compute FD in the learned 128D feature space.

Results. Tab. 3 shows that our method produces closer OOR distributions to real data than baselines, validating our full pipeline. Fig. 9 further demonstrates the advantage of our segmentation and PCA modules. Without segmentation, registration often misaligns objects, and PCA enhances accuracy, yielding more realistic OOR samples.

5. Discussion

We present a novel approach to learning object-object spatial relationships (OOR) from synthetic 3D samples, leveraging pre-trained 2D diffusion models. We formulate a novel concept of OOR, and introduce a comprehensive pipeline for synthesizing 3D OOR samples, which can be applicable for any unbounded object categories. We develop a score-based diffusion model specifically designed to model 3D spatial relationships between objects. Furthermore, we demonstrate the scalability of our method by proposing a method to generate muti-object OOR by extending our pairwise OOR models. We also demonstrate the potential of our method for real-world tasks by showing that scene editing can be effectively implemented via score-based updates. As a future direction, more factors, such as detailed object shapes, can be considered as additional factors to determine OOR.

Acknowledgements. We thank Inhee Lee and Taeksoo Kim for their assistance in conducting the user study. This work was supported by RLWRLD, NRF grant funded by the Korean government (MSIT) (No. 2022R1A2C2092724), and IITP grant funded by the Korea government (MSIT) [No. RS-2024-00439854, RS-2021-II211343, and No.2022-0-00156]. H. Joo is the corresponding author.

References

- P.J. Besl and Neil D. McKay. A method for registration of 3-d shapes. *TPAMI*, 14(2):239–256, 1992. 5
- [2] black-forest labs. Flux.1-dev. https://huggingface. co/black-forest-labs/FLUX.1-dev, 2024. 3, 13
- [3] Shizhe Chen, Pierre-Louis Guhur, Makarand Tapaswi, Cordelia Schmid, and Ivan Laptev. Language conditioned spatial relation reasoning for 3d object grounding. In *Neurips*, 2022. 2
- [4] Hai Ci, Mingdong Wu, Wentao Zhu, Xiaoxuan Ma, Hao Dong, Fangwei Zhong, and Yizhou Wang. Gfpose: Learning 3d human pose prior with gradient fields. In *CVPR*, 2023. 2
- [5] Angela Dai, Angel X Chang, Manolis Savva, Maciej Halber, Thomas Funkhouser, and Matthias Nießner. Scannet: Richlyannotated 3d reconstructions of indoor scenes. In CVPR, 2017. 2
- [6] Timothée Darcet, Maxime Oquab, Julien Mairal, and Piotr Bojanowski. Vision transformers need registers. In *ICLR*, 2024. 5, 13
- [7] Prafulla Dhariwal and Alexander Nichol. Diffusion models beat gans on image synthesis. In *Neurips*, 2021. 2
- [8] John R Dormand and Peter J Prince. A family of embedded runge-kutta formulae. *Journal of computational and applied mathematics*, 6(1):19–26, 1980. 5
- [9] DC Dowson and BV666017 Landau. The fréchet distance between multivariate normal distributions. *Journal of multi*variate analysis, 12(3), 1982. 10
- [10] Martin A Fischler and Robert C Bolles. Random sample consensus: a paradigm for model fitting with applications to image analysis and automated cartography. *Communications* of the ACM, 24(6):381–395, 1981. 5
- [11] Huan Fu, Bowen Cai, Lin Gao, Ling-Xiao Zhang, Jiaming Wang, Cao Li, Qixun Zeng, Chengyue Sun, Rongfei Jia, Binqiang Zhao, et al. 3d-front: 3d furnished rooms with layouts and semantics. In *ICCV*, 2021. 2
- [12] Daoyi Gao, Dávid Rozenberszki, Stefan Leutenegger, and Angela Dai. Diffcad: Weakly-supervised probabilistic cad model retrieval and alignment from an rgb image. ACM Transactions on Graphics (TOG), 43(4):1–15, 2024. 2
- [13] Gao Gege, Liu Weiyang, Chen Anpei, Geiger Andreas, and Schölkopf Bernhard. Graphdreamer: Compositional 3d scene synthesis from scene graphs. In CVPR, 2024. 8
- [14] Colin Goodall. Procrustes methods in the statistical analysis of shape. *Journal of the Royal Statistical Society*, 53(2): 285–321, 1991. 5
- [15] John C Gower. Generalized procrustes analysis. *Psychometrika*, 40:33–51, 1975. 5
- [16] Can Gümeli, Angela Dai, and Matthias Nießner. Roca: Robust cad model retrieval and alignment from a single image. In CVPR, 2022. 2
- [17] Sookwan Han and Hanbyul Joo. Learning canonicalized 3d human-object spatial relations from unbounded synthesized images. In *ICCV*, 2023. 2
- [18] Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. In *Neurips*, 2020. 2

- [19] Harold Hotelling. Analysis of a complex of statistical variables into principal components. *Journal of educational psychology*, 24(6):417, 1933. 4
- [20] Jiawei Hou, Wenhao Guan, Xiangyang Xue, and Taiping Zeng. Lop-field: Brain-inspired layout-object-position fields for robotic scene understanding. arXiv preprint arXiv:2406.05985, 2024. 2
- [21] Tsu-Ching Hsiao, Hao-Wei Chen, Hsuan-Kung Yang, and Chun-Yi Lee. Confronting ambiguity in 6d object pose estimation via score-based diffusion on se(3). In *CVPR*, 2024.
 2
- [22] Binh-Son Hua, Quang-Hieu Pham, Duc Thanh Nguyen, Minh-Khoi Tran, Lap-Fai Yu, and Sai-Kit Yeung. Scenenn: A scene meshes dataset with annotations. In *3DV*, 2016. 2
- [23] Hamid Izadinia, Qi Shan, and Steven M Seitz. Im2cad. In CVPR, pages 5134–5143, 2017. 2
- [24] Rainer Kartmann, Danqing Liu, and Tamim Asfour. Semantic scene manipulation based on 3d spatial object relations and language instructions. In *ICHR*, 2021. 2
- [25] Lei Ke, Mingqiao Ye, Martin Danelljan, Yifan Liu, Yu-Wing Tai, Chi-Keung Tang, and Fisher Yu. Segment anything in high quality. In *NeurIPS*, 2023. 4
- [26] Hyeonwoo Kim, Sookwan Han, Patrick Kwon, and Hanbyul Joo. Beyond the contact: Discovering comprehensive affordance for 3d objects from pre-trained 2d diffusion models. In *ECCV*, 2024. 2
- [27] Jeonghwan Kim, Jisoo Kim, Jeonghyeon Na, and Hanbyul Joo. Parahome: Parameterizing everyday home activities towards 3d generative modeling of human-object interactions. 2401.10232.arXiv.cs.CV, 2024. 9
- [28] Young Min Kim, Niloy J Mitra, Dong-Ming Yan, and Leonidas Guibas. Acquiring 3d indoor environments with variability and repetition. ACM Transactions on Graphics (TOG), 31(6):1–11, 2012. 2
- [29] DA Sasi Kiran, Kritika Anand, Chaitanya Kharyal, Gulshan Kumar, Nandiraju Gireesh, Snehasis Banerjee, Ruddra Dev Roychoudhury, Mohan Sridharan, Brojeshwar Bhowmick, and Madhava Krishna. Spatial relation graph and graph convolutional network for object goal navigation. In *CASE*, 2022.
- [30] Alexander Kirillov, Eric Mintun, Nikhila Ravi, Hanzi Mao, Chloe Rolland, Laura Gustafson, Tete Xiao, Spencer Whitehead, Alexander C. Berg, Wan-Yen Lo, Piotr Dollár, and Ross Girshick. Segment anything. In *ICCV*, 2023. 4
- [31] Florian Langer, Gwangbin Bae, Ignas Budvytis, and Roberto Cipolla. Sparc: Sparse render-and-compare for cad model alignment in a single rgb image. *arXiv preprint arXiv:2210.01044*, 2022. 2
- [32] Chen-Yu Lee, Vijay Badrinarayanan, Tomasz Malisiewicz, and Andrew Rabinovich. Roomnet: End-to-end room layout estimation. In *ICCV*, 2017. 2
- [33] Zheng Li, Xiaocong Du, and Yu Cao. Gar: Graph assisted reasoning for object detection. In *ICCV*, 2020. 2
- [34] Zhiqiu Lin, Deepak Pathak, Baiqi Li, Jiayao Li, Xide Xia, Graham Neubig, Pengchuan Zhang, and Deva Ramanan. Evaluating text-to-visual generation with image-to-text generation. In *ECCV*, 2024. 6, 7

- [35] Shilong Liu, Zhaoyang Zeng, Tianhe Ren, Feng Li, Hao Zhang, Jie Yang, Chunyuan Li, Jianwei Yang, Hang Su, Jun Zhu, et al. Grounding dino: Marrying dino with grounded pre-training for open-set object detection. In ECCV, 2024. 4
- [36] Junzhe Lu, Jing Lin, Hongkun Dou, Ailing Zeng, Yue Deng, Yulun Zhang, and Haoqian Wang. Dposer: Diffusion model as robust 3d human pose prior. arxiv:2312.05541, 2023. 2
- [37] Qian Luo, Yunfei Li, and Yi Wu. Grounding object relations in language-conditioned robotic manipulation with semanticspatial reasoning. *arXiv preprint arXiv:2303.17919*, 2023.
 2
- [38] Kevis-Kokitsi Maninis, Stefan Popov, Matthias Nießner, and Vittorio Ferrari. Vid2cad: Cad model alignment using multiview constraints from videos. *TPAMI*, 45(1):1320–1327, 2022.
 2
- [39] Octave Mariotti, Oisin Mac Aodha, and Hakan Bilen. Improving semantic correspondence with viewpoint-guided spherical maps. In CVPR, 2024. 2
- [40] Oier Mees, Alp Emek, Johan Vertens, and Wolfram Burgard. Learning object placements for relational instructions by hallucinating scene representations. In *ICRA*, 2020. 2
- [41] Başak Melis Öcal, Maxim Tatarchenko, Sezer Karaoglu, and Theo Gevers. Sceneteller: Language-to-3d scene generation. In ECCV, 2024. 6
- [42] OpenAI. Chatgpt: Chat-based ai language model. https: //chat.openai.com, 2024. 2, 5, 7, 13, 14
- [43] Maxime Oquab, Timothée Darcet, Theo Moutakanni, Huy V. Vo, Marc Szafraniec, Vasil Khalidov, Pierre Fernandez, Daniel Haziza, Francisco Massa, Alaaeldin El-Nouby, Russell Howes, Po-Yao Huang, Hu Xu, Vasu Sharma, Shang-Wen Li, Wojciech Galuba, Mike Rabbat, Mido Assran, Nicolas Ballas, Gabriel Synnaeve, Ishan Misra, Herve Jegou, Julien Mairal, Patrick Labatut, Armand Joulin, and Piotr Bojanowski. Dinov2: Learning robust visual features without supervision. In *TMLR*, 2023. 5, 13
- [44] Despoina Paschalidou, Amlan Kar, Maria Shugrina, Karsten Kreis, Andreas Geiger, and Sanja Fidler. Atiss: Autoregressive transformers for indoor scene synthesis. In *Neurips*, 2021.
 2
- [45] Christian Pek, Georg Friedrich Schuppe, Francesco Esposito, Jana Tumova, and Danica Kragic. Spatial: monitoring and planning of robotic tasks using spatio-temporal logic specifications. *Autonomous Robots*, 47(8):1439–1462, 2023. 2
- [46] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. In *ICML*, 2021. 6, 7
- [47] Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *JMLR*, 21:1–67, 2020. 5, 13
- [48] Nikhila Ravi, Valentin Gabeur, Yuan-Ting Hu, Ronghang Hu, Chaitanya Ryali, Tengyu Ma, Haitham Khedr, Roman Rädle, Chloe Rolland, Laura Gustafson, Eric Mintun, Junting Pan, Kalyan Vasudev Alwala, Nicolas Carion, Chao-Yuan Wu, Ross Girshick, Piotr Dollár, and Christoph Feichtenhofer. Sam 2: Segment anything in images and videos, 2024. 4

- [49] Tianhe Ren, Qing Jiang, Shilong Liu, Zhaoyang Zeng, Wenlong Liu, Han Gao, Hongjie Huang, Zhengyu Ma, Xiaoke Jiang, Yihao Chen, Yuda Xiong, Hao Zhang, Feng Li, Peijun Tang, Kent Yu, and Lei Zhang. Grounding dino 1.5: Advance the "edge" of open-set object detection, 2024. 4
- [50] Tianhe Ren, Shilong Liu, Ailing Zeng, Jing Lin, Kunchang Li, He Cao, Jiayu Chen, Xinyu Huang, Yukang Chen, Feng Yan, Zhaoyang Zeng, Hao Zhang, Feng Li, Jie Yang, Hongyang Li, Qing Jiang, and Lei Zhang. Grounded sam: Assembling openworld models for diverse visual tasks. arXiv:2401.14159, 2024. 4
- [51] Mike Roberts, Jason Ramapuram, Anurag Ranjan, Atulit Kumar, Miguel Angel Bautista, Nathan Paczan, Russ Webb, and Joshua M Susskind. Hypersim: A photorealistic synthetic dataset for holistic indoor scene understanding. In CVPR, 2021. 2
- [52] Benjamin Rosman and Subramanian Ramamoorthy. Learning spatial relationships between objects. *The International Journal of Robotics Research*, 30(11):1328–1342, 2011. 2
- [53] Wenkang Shan, Zhenhua Liu, Xinfeng Zhang, Zhao Wang, Kai Han, Shanshe Wang, Siwei Ma, and Wen Gao. Diffusionbased 3d human pose estimation with multi-hypothesis aggregation. In *ICCV*, 2023. 2
- [54] Sketchfab. Sketchfab publish & find 3d models online. https://sketchfab.com, 2024. 13
- [55] Jascha Sohl-Dickstein, Eric Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In *ICML*, 2015. 2
- [56] Shuran Song, Samuel P Lichtenberg, and Jianxiong Xiao. Sun rgb-d: A rgb-d scene understanding benchmark suite. In *CVPR*, 2015. 2
- [57] Yang Song and Stefano Ermon. Generative modeling by estimating gradients of the data distribution. In *Neurips*, 2019.2
- [58] Yang Song and Stefano Ermon. Improved techniques for training score-based generative models. In *Neurips*, 2020. 2
- [59] Yang Song, Jascha Sohl-Dickstein, Diederik P Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-based generative modeling through stochastic differential equations. In *ICLR*, 2021. 2, 5
- [60] Julian Straub, Thomas Whelan, Lingni Ma, Yufan Chen, Erik Wijmans, Simon Green, Jakob J. Engel, Raul Mur-Artal, Carl Ren, Shobhit Verma, Anton Clarkson, Mingfei Yan, Brian Budge, Yajie Yan, Xiaqing Pan, June Yon, Yuyang Zou, Kimberly Leon, Nigel Carter, Jesus Briales, Tyler Gillingham, Elias Mueggler, Luis Pesqueira, Manolis Savva, Dhruv Batra, Hauke M. Strasdat, Renzo De Nardi, Michael Goesele, Steven Lovegrove, and Richard Newcombe. The Replica dataset: A digital replica of indoor spaces. arXiv preprint arXiv:1906.05797, 2019. 2
- [61] Hou In Ivan Tam, Hou In Derek Pun, Austin T. Wang, Angel X. Chang, and Manolis Savva. Scenemotifcoder: Example-driven visual program learning for generating 3d object arrangements. In *3DV*, 2025. 6
- [62] Kuaishou Technology. Kling ai. https://www. klingai.com, 2024. 4, 13

- [63] Pascal Vincent. A connection between score matching and denoising autoencoders. *Neural computation*, 23(7):1661– 1674, 2011. 5
- [64] Vikram Voleti, Chun-Han Yao, Mark Boss, Adam Letts, David Pankratz, Dmitrii Tochilkin, Christian Laforte, Robin Rombach, and Varun Jampani. SV3D: Novel multi-view synthesis and 3D generation from a single image using latent video diffusion. In ECCV, 2024. 4
- [65] Jianyuan Wang, Nikita Karaev, Christian Rupprecht, and David Novotny. Vggsfm: Visual geometry grounded deep structure from motion. In *CVPR*, 2024. 4
- [66] Peng Wang, Lingjie Liu, Yuan Liu, Christian Theobalt, Taku Komura, and Wenping Wang. Neus: Learning neural implicit surfaces by volume rendering for multi-view reconstruction. In *NeurIPS*, 2021. 8
- [67] Chuan Wen, Dinesh Jayaraman, and Yang Gao. Can transformers capture spatial relations between objects? arXiv preprint arXiv:2403.00729, 2024. 2
- [68] Tong Wu, Guandao Yang, Zhibing Li, Kai Zhang, Ziwei Liu, Leonidas Guibas, Dahua Lin, and Gordon Wetzstein. Gpt-4v(ision) is a human-aligned evaluator for text-to-3d generation. In *CVPR*, 2024. 6, 7, 14
- [69] Weilai Xiang, Hongyu Yang, Di Huang, and Yunhong Wang. Denoising diffusion autoencoders are unified self-supervised learners. In *ICCV*, 2023. 2
- [70] Haitao Yang, Zaiwei Zhang, Siming Yan, Haibin Huang, Chongyang Ma, Yi Zheng, Chandrajit Bajaj, and Qixing Huang. Scene synthesis via uncertainty-driven attribute synchronization. In *ICCV*, 2021. 2
- [71] Junyi Zhang, Charles Herrmann, Junhwa Hur, Luisa Polania Cabrera, Varun Jampani, Deqing Sun, and Ming-Hsuan Yang. A Tale of Two Features: Stable Diffusion Complements DINO for Zero-Shot Semantic Correspondence. In *Neurips*, 2023. 2
- [72] Junyi Zhang, Charles Herrmann, Junhwa Hur, Eric Chen, Varun Jampani, Deqing Sun, and Ming-Hsuan Yang. Telling left from right: Identifying geometry-aware semantic correspondence. In CVPR, 2024. 2, 4, 9
- [73] Jiyao Zhang, Mingdong Wu, and Hao Dong. Generative category-level object pose estimation via diffusion models. In *NeurIPS*, 2024. 2, 5, 13
- [74] Lvmin Zhang, Anyi Rao, and Maneesh Agrawala. Adding conditional control to text-to-image diffusion models. In *ICCV*, 2023. 8
- [75] Zijian Zhang, Zhou Zhao, and Zhijie Lin. Unsupervised representation learning from pre-trained diffusion probabilistic models. In *Neurips*, 2022. 2
- [76] Jianjun Zhao, Jun Chu, Lu Leng, Chaolin Pan, and Tao Jia. Rgrn: Relation-aware graph reasoning network for object detection. *Neural Computing and Applications*, 35(22):16671– 16688, 2023. 2
- [77] Yi Zhou, Connelly Barnes, Jingwan Lu, Jimei Yang, and Hao Li. On the continuity of rotation representations in neural networks. In *CVPR*, 2019. 14
- [78] Chuhang Zou, Alex Colburn, Qi Shan, and Derek Hoiem. Layoutnet: Reconstructing the 3d room layout from a single rgb image. In *CVPR*, 2018. 2



Figure 10. Controllability of Diffusion Models Through Text **Prompts.** Each is an output image of diffusion generated with the following prompt: (a) "A table with a teacup on top." (b) Adding "White background." to the end of the prompt. (c) Specifying the shape and texture of the table as "four-legged rectangular marble table." (d) Specifying the camera view via ", from a diagonal angle."

A. Details on Dataset Generation

Text Prompts for Image Generation. The controllability of diffusion via text prompts offers advantages in learning OOR from synthetic images over real-world images by generating realistic OOR images while simultaneously enhancing their learnability through precise control. Fig. 10 illustrates this clearly. (a) shows an image generated with a simple prompt: "A table with a teacup on top." While the image is highly realistic, it poses challenges for learning the OOR between the "table" and "teacup" because the full shape of the table is not visible. (b) shows the result of adding "White background." to the end of the prompt, which directs focus to the two objects and ensures that their full shapes are captured within the image frame without the need for additional context. (c) demonstrates control over the object's shape and texture in the generated image. This facilitates the registration of template object meshes. Finally, (d) shows how to mitigate frame size constraints by controlling the camera view. This is useful for capturing OOR between objects with large size differences, such as a table and a teacup, or between objects positioned at some distance, such as a monitor and a keyboard. We use the FLUX.1-dev [2] in all image generation.

Synthetic Image Augmentation via Video Diffusion. We further augment 2D OOR images using the I2V model [62] for contexts where dynamic OOR can be generated by humans. The motivation for using the image-to-video model is to generate a broader range of relative object relationships within each context, as image diffusion models typically produce the most representative configuration (e.g., the pizza cutter tends to be in the center of a pizza). We then use each frame from the synthesized videos as additional synthetic 2D samples, disregarding their temporal information. See Fig. 11 for the example result.

Best Template Selection. If the shape of the object in the synthetic image and the template mesh are very different, mesh registration often fails. Therefore, for each category, we collect several template meshes as candidates and select the template that best matches the object in the image. To do this, we obtain DINO [6, 43] features for M pseudo multi-



Figure 11. **Image Augmentation via Image-to-Video Model.** We diversify scenes with dynamic object-object spatial relationships using the image-to-video model.

view images and N mesh multi-view renderings, and select the mesh with the highest value by calculating the average of cosine similarity for $N \times M$ pairs. We collect template meshes from Sketchfab [54]. There are 96 template meshes used for data generation.

Filtering Process. Our filtering process is automated in the following steps: First, we filter out all the bad quality images where segmentation and SfM fail. In the process from SfM to feature matching, we filter out if the number of points corresponding to each base object and target object is less than 100. The cosine similarity threshold is set to 0.7 in most cases. There may still be misalignment between the registered mesh and the point clouds. We use the Chamfer Distance from the mesh to the point clouds. The threshold is adjusted according to the scale of the registered mesh. Most of the bad samples are filtered out through a series of processes, but some cases, such as flipped meshes, may remain. We use VLM [42] to filter out the last remaining bad samples. Specifically, we render combinations of base and target objects, and then ask VLM to judge whether the multi-view images align well with the text prompt, using the same criteria as when measuring the VLM score. The filtering ratio is 0.46 to 0.88. However, since our approach is based on fully synthetic data, we can iterate this process as needed to obtain a sufficient number of high-quality 3D outputs. We obtain 30 to 216 samples per context.

B. Details on OOR Diffusion.

Our OOR diffusion is trained for 20,000 epochs, taking about 10 hours on an RTX 6000 48GB.

Architecture Implementation. We follow the implementation of ScoreNet in GenPose [73] for our score-based OOR diffusion. However, we take text as a condition instead of point clouds. For this, we introduce the T5 text encoder [47]. Also, unlike Genpose, which only deals with the scores of rotation, translation, we also consider the 3-dimensional



Context Augmentation. LLM augments on text context c via the following guided prompt.

scale. For this, in the inference reverse ODE process, we add guidance to make the scale positive. Following GenPose, we consider a 6D representation [77] for rotation. Therefore, our OOR diffusion is learned in a 15-dimensional space (6D target object rotation, 3D target object translation, 3D target object scale, 3D base object scale).

Text Context Augmentation. As proposed in Sec. 3.3, we perform text context augmentation to increase the generality of OOR diffusion. Through the guided prompts in Fig. 12, LLM generates various text prompts that describe a given context c. Object categories are augmented by asking the LLM to present categories with similar shape and scale that could replace \mathcal{B} and \mathcal{T} in the given text context c.

Inconsistency Loss. The inconsistency loss introduced in Eq. 10 is computed as the average of the following three inconsistency parts: (1) The scale variance of a global base object; (2) The pose and scale variance in the global coordinate system derived from different parents; (3) The variance of each component's ratio between the scale in the global coordinate system and the base scale in pairwise OOR, measured for parent nodes that are not global bases. Specifically, (1) corresponds to the part related to the desk in Fig. 5. OOR diffusion generates different $s^{\mathcal{B}}$ for each pair, (desk, monitor), (desk, keyboard), and (desk, mouse), within the batch. In this case, (1) takes the variance of three $s^{\mathcal{B}}$ as a loss term. (2) is the part corresponding to the keyboard in Fig. 5. The pose and scale of each object in the global coordinate system are obtained as many times as the number of parent nodes of the corresponding node in the scene graph. Thus, the variance of three different poses and scales in global coordinate systems of the keyboard obtained from the desk, monitor, and mouse is the loss term in (2). (3) relates to the scale

Figure 13. **Questionnaire for User Study.** Participants select the multi-view image set that best captures the given OOR as instructed in the questionnaire.

ratio consistency of monitor and mouse, which are parent nodes but not the global base. For example, the monitor should maintain consistency between its scale in the global coordinate system obtained from paths in the scene graph and the $s^{\mathcal{B}}$ of the (monitor, keyboard) OOR sample. They do not have to be equal, but the ratio of each component should be constant. For example, if the obtained monitor scale in the global coordinate system is (0.5, 0.4, 0.2), then the $s^{\mathcal{B}}$ in the (monitor, keyboard) OOR sample should be (1.0, 0.8, 0.4). The variance of the ratio of each component of the relevant scales is the loss term in (3).

C. Experiments Details

VLM Score. As described in Sec. 4.1, we propose the VLM score, inspired by GPTEval3D [68], to evaluate the alignment between the text context of OOR and multi-view images. We use VLM (specifically GPT-4o [42]) to compare two sets of multi-view images, each containing 10 images. These image sets are generated using our method or baselines. VLM is tasked with selecting the image set that better represents the spatial relationship between objects described in the text prompt. To ensure a fair comparison, we instruct VLM to ignore texture quality and focus solely on OOR. Fig. 14 illustrates the guided prompt we provided to VLM along with an example response from VLM.

User Study. For the user study, we randomly select one scene from each of the object pairs per method to create a total of 30 questions for pairwise OOR generation. Similar to the VLM score evaluation, participants are instructed to disregard factors such as texture quality and focus solely on

System Prompt

You are an evaluator who examines multi-view images and determines whether they align well with the text prompt.

User Prompt

You are tasked with reviewing and evaluating multi-view images generated from a text prompt describing the relationship between two objects, '{object_tuple[0]}' and '{object_uple[1]}'. Prompt: '{prompt}

There are a total of 20 images provided. The first 10 images are multi-view images generated using Method A, while the next 10 images are generated using Method B.

You are to carefully review and determine which method better satisfies the following criteria:

1. Both objects, '{object_tuple[0]}' and '{object_tuple[1]}', should be present in 3D space. Because these are multi-view images, there may be occlusions in some views. You need to think in 3D space, combining multi-view images rather than just looking at one image at a time.

2. The spatial relationship between the two objects, as described in the text prompt, should be clearly represented in the multi-view images.

3. The texture of the images or the geometry of each object is not a consideration. As long as the objects are recognizable, you can ignore texture and geometry. Focus solely on the object-to-object relationship.

Once again, the first 10 images are generated using method A, the next 10 images are generated using method B. The text prompt specifies the relationship between the two objects '{object_tuple[0]}' and '{object_tuple[1]}': '{prompt}'

Indicate which method better satisfies the criteria above and provide a brief explanation for your choice.

Please make your choice clear by including the phrase 'Choose: Method_' at the end. \nMultiple selection is not allowed. However, if it is difficult to determine which is the best, do not choose anything and just print the word 'Cannot choose'.

Example Response

To evaluate which method better satisfies the criteria, let's analyze the images:

Method A:

All images clearly show both the apple and the knife. The knife is consistently shown cutting into the apple, accurately representing the spatial relationship described in the prompt.

Method B:

All images include both the apple and the knife. However, the knife is not consistently shown cutting the apple. In some images, the knife is merely near the apple without cutting it. Based on the criteria, Method A better satisfies the requirement of depicting the knife cutting the apple.

Choose: Method A

Figure 14. Guided Prompt Provided to VLM for VLM Score Evaluation. Using the guided prompt above, VLM selects the preferred multi-view image set between the two generated by the different methods.

the OOR. For each question, multi-view image sets generated by methods A, B, and C are presented, and participants are asked to select the method that best represents the OOR described in the text prompt. To prevent bias, the order of A, B, and C is randomized for each question. We collect responses from 92 participants in total(81 participants for multi-OOR evaluation). The detailed questionnaire structure is illustrated in Fig. 13.

D. Generality of Our methods

Fig. 15 demonstrates the generality of our OOR modeling. Our OOR diffusion generates appropriate relative poses and scales even for instances other than the template meshes used to generate the dataset. We consider the following scales to maintain the aspect ratio of each instance for both the base object and the target object:

$$\mathbf{s}' := \operatorname{Mean}(\mathbf{s}/\operatorname{BBOX}(\mathcal{M})) \cdot \operatorname{BBOX}(\mathcal{M}), \quad (15)$$



Figure 15. **Applying Our OOR Diffusion Samples to Unseen Instances.** Our OOR diffusion still works when applied to instances other than the template meshes used to generate the dataset.

where s is 3-dimensional scale from OOR diffusion, and \mathcal{M} is an instance mesh.

Fig. 16 shows that our OOR diffusion still produces plausible outputs even for text prompts that are not seen during training. In the first example, the spatial relation "pour" is learned, but the object categories "moka pot" and "mug"



Figure 16. **Our OOR Diffusion Sampling Results Under Unseen Text Prompt Condition.** Our OOR diffusion also works on text prompts that are not explicitly seen in training (including new categories and spatial relations).

are not seen during training. In the second example, both "steak" and "knife" are categories seen during training, but the spatial relationship of "cutting steak with a knife" is not learned. The last example shows a case of multi-object OOR. The spatial relation of placing a "cutting board" somewhere is not seen during training, but thanks to the generality of OOR diffusion, it is correctly placed on the "table".