

A parallel branch-and-bound-and-prune algorithm for irregular strip packing with discrete rotations

Juan J. Lastra-Díaz^{a,*}, M. Teresa Ortuño^a

^aDepartment of Statistics and Operational Research, Institute of Interdisciplinary Mathematics, UCM Research Group HUMLOG, Complutense University of Madrid, Spain

ARTICLE INFO

Keywords:

Packing
Irregular strip packing
Integer programming
Branch-and-Bound-and-Prune
Forward-checking

ABSTRACT

The irregular strip-packing problem consists of the computation of a non-overlapping placement of a set of polygons onto a rectangular strip of fixed width and the minimal length possible. Recent performance gains of the Mixed-Integer Linear Programming (MILP) solvers have encouraged the proposal of exact optimization models for nesting. The Dotted-Board (DB) MILP model solves the discrete version of the nesting problem by constraining the positions of the polygons to be on a grid of fixed points. However, its number of non-overlapping constraints grows exponentially with the number of dots and types of polygons, which encouraged the proposal of a reformulation called the DB Clique Covering (DB-CC) that sets the current state-of-the-art by significantly reducing the constraints required. However, DB-CC requires a significant preprocessing time to compute edge and vertex clique coverings. Moreover, current knowledge of the stable set polytope suggests that achieving a tighter formulation is unlikely. Thus, our hypothesis is that an ad-hoc exact algorithm requiring no preprocessing might be a better option to solve the DB model than the costly Branch-and-Cut approach. This work proposes an exact branch-and-bound-and-prune algorithm to solve the DB model from the conflict inverse graph based on ad-hoc data structures, bounding, and forward-checking for pruning the search space. We introduce two 0-1 ILP DB reformulations with discrete rotations and a new lower-bound algorithm as by-products. Our experiments show that DB-PB significantly reduces the resolution time compared to our replication of the DB-CC model. Seventeen open instances are solved up to optimality.

1. Introduction

Cutting and packing regular (convex) and irregular (non-convex) polygons onto a rectangular strip with unbounded length is a tedious and usual task in most manufacturing industries based on the cutting of any flat material. For instance, Milenkovic et al. [84] study the nesting problem for the fashion and apparel industry, whilst Heistermann and Lengauer [64] and Whelan and Batchelor [124] do it for leather manufacturing, Elamvazuthi et al. [45] in furniture, Han et al. [62] in the glass industry, Alves et al. [8] in the automotive industry, and Cheok and Nee [29] and Hamada et al. [61] in shipbuilding. The irregular strip-packing problem is also known as *nesting* or *marker making* in the industry, and it consists in computing a non-overlapping placement of a set of irregular polygons, called *pieces*, onto a fixed-width rectangular strip with unbounded length, called the *board*, whose length is the minimum possible. Another closely related problem, called two-dimensional bin packing [80, 66], is defined as the computation of a non-overlapping placement of a set of polygons onto a larger closed polygon, called the *bin*, to minimize the number of bins required. Regular and irregular strip and bin packing problems, and all their variants concerning the geometry of the pieces

*Corresponding author

 jlastra@ucm.es (J.J. Lastra-Díaz); mteresa@ucm.es (M.T. Ortuño)

ORCID(s): 0000-0003-2522-4222 (J.J. Lastra-Díaz); 0000-0002-5568-9496 (M.T. Ortuño)

or boards, belong to the broader family of Cutting and Packing (C&P) problems categorized by Dyckhoff [44] and Wäscher et al. [122], and extensively reviewed by Sweeney and Paternoster [116], Dowsland and Dowsland [41], Wang and Wäscher [120], and Bennell et al. [18], among others.

Research on the irregular strip and bin packing problems can be traced back to the pioneering Linear Programming (LP) models for rectangular bin packing introduced by Gilmore and Gomory [55], and the pioneering heuristic methods for irregular strip packing proposed by Art [10], Adamowicz and Albano [4, 3], and Albano and Sapuppo [6] in the late nineteen sixties and seventies. These early works introduce many of the basic ideas subsequently exploited by all heuristics methods reported in the literature, such as the notion of a feasible non-overlapping region between pieces based on the No-Fit Polygon (NFP) representation [16], and the sequential placement of pieces based on bottom-left heuristics. The boundary and outer region of the no-fit polygon NFP_{AB} set the feasible positions in which polygon B can be placed, without rotating, into a non-overlapping position with respect to polygon A . Thus, the no-fit polygon allows one to compute the feasible relative placements between polygons A and B a priori by checking whether their relative position vector $\delta_{AB} = r_B - r_A$ belongs to either the boundary or the outer region of NFP_{AB} , where r_A and r_B denote their corresponding reference points. This property has converted the NFP into the most broadly adopted and effective geometric representation for nesting reported in the literature, both for the families of heuristics methods [17] and for exact mathematical models [73].

Fowler et al. [51] show that the irregular strip-packing problem is NP-complete. For this reason, most practical solutions reported in the literature since the pioneering work of Art [10] are based on sequential placement heuristics to build efficiently feasible solutions that are combined with meta-heuristics for exploring the space of feasible solutions, as shown in most of surveys on nesting [42, 43, 65, 17, 102]. Elkeran [46] introduces the current state-of-the-art heuristic method for nesting, called Guided Cuckoo Search (GCS), which defines a two-stage method based on piece clustering and NFP-based bottom-left heuristics [57] to build an initial feasible solution that is shrunk by solving an overlap minimization problem using a variant of the cuckoo search meta-heuristics. Although GCS was introduced more than a decade ago, subsequent works have been unable to outperform its results, as shown by Pinheiro et al. [98, table 3], Sato et al. [107, table 5], Cherri et al. [30, table 4], Mundim et al. [87, table 6], Amaro Júnior et al. [9, table 2], and Sato et al. [106, tables 4-5]. More recently, other authors have introduced new heuristics for the continuous and discrete versions of the nesting problem, such as the works of Fang et al. [48], Na and Yang [88], Guo et al. [60], Sato et al. [108], Queiroz and de Queiroz [101], Umetani and Murakami [119], and Queiroz and Andretta [100]. For a recent comparison of heuristics and exact mathematical models for nesting, we refer the readers to the comparative evaluation carried out by Giovenali et al. [56].

The recent performance gains achieved by state-of-the-art Mixed-Integer Programming (MIP) solvers [22, 2, 67] have encouraged the proposal of exact mathematical models for nesting during the last decade, as shown by the literature reviews of Leao et al. [73] and Lastra-Díaz and Ortuño [70]. The exact mathematical models for nesting can be categorized into mixed-integer linear programming models, Constraint Programming (CP) models, and non-linear programming models, as shown in the categorization of Lastra-Díaz and Ortuño [70, Fig. 1]. In turn, the family of mathematical programming models for nesting can be categorized into three large families according to the type of decision variables used to represent the position of the pieces as follows. Firstly, the family of continuous models, such as the pioneering MILP model of Li [76, §8], and the subsequent MILP models proposed by Dean [37, §5], Fischetti and Luzzi [50], Alvarez-Valdes et al. [7], Cherri et al. [32], Rodrigues et al. [104], Lastra-Díaz and Ortuño [70], and Pantoja-Benavides et al. [96]. Secondly, the family of discrete ILP models for nesting to which this work belongs, whose pioneering model is the Dotted-Board (DB) model introduced by Toledo et al. [117], subsequently improved by Rodrigues and Toledo [105], and more recently extended by Rodrigues de Souza and Andretta [113, 114] to deal with the uncertainty in the demand of pieces by formulating a two-stage stochastic programming model. And thirdly, the semi-continuous MILP model of Leao et al. [72] whose

aim is to overcome the limitations of the grid resolution in the DB model [117] by dividing the board into continuous horizontal slices at regular y-axis discrete positions to enlarge the space of feasible positions for the pieces. We refer the reader to the aforementioned works [73, 70] for a comprehensive and updated review of the families of exact methods for nesting.

The first exact mathematical models for nesting reported in the literature tackled the continuous version of the problem. Li [76, §8] introduces the first continuous MIP model for nesting reported in the literature to solve a limitation of the pioneering LP compaction model of Li and Milenkovic [77, 78]. Although Li's model was not experimentally evaluated, it sets the two main features of the family of continuous exact MIP models based on the NFP as follows: (1) the convex decomposition of the outer NFP feasible regions; and (2) the definition of mutually-exclusive binary variables to set the pairwise non-overlapping constraints between pieces defining the feasible regions for their relative placement. For instance, Dean [37, §5] introduces and evaluates for the first time a MIP model for nesting based on a refinement of the Daniels et al. [35] bin packing model that is essentially identical to the Li's model. Subsequently, Fischetti and Luzzi [50] (F&L) introduce a refinement of Li's model based on lifting the big-M formulation and a branching-priority algorithm to guide the Branch&Bound (B&B) exploration. Alvarez-Valdes et al. [7] improve the F&L [50] model by introducing a new MIP model called HS2, which is based on a detailed convex decomposition of the feasible regions into horizontal slices, a lifting for the bound constraints of the continuous variables, six new branching strategies, and the x-axis ordering of identical pieces to remove all symmetric solutions derived from their permutation. Cherri et al. [32] introduce two continuous MILP models improving the HS2 model [7], together with the first continuous MIP model integrating discrete rotations, which are based on the convex decomposition of the pieces and the definition of the non-overlapping constraints between pieces by using the convex no-fit polygons among their convex parts, together with some families of valid inequalities, and the same x-axis symmetry-breaking for identical pieces proposed by Alvarez-Valdes et al. [7]. Subsequently, Rodrigues et al. [104] improve the NFP-CM model by breaking the symmetries of the feasible space for the relative placements between pieces. More recently, Lastra-Díaz and Ortuño [70] introduce two continuous MILP models without rotations called NFP-CM based on Vertical Slices (NFP-CM-VS), which are two reformulations of the NFP-CM model of Cherri et al. [32] based on a new convex decomposition of the feasible space of relative placements between pieces into vertical slices, together with a large set of logical objects to tighten the formulation derived from the former convex decomposition, such as a new family of valid inequalities, symmetry breakings, variable eliminations, and a family of feasibility cuts among three pieces. The family of NFP-CM-VS MIP models proposed by Lastra-Díaz and Ortuño [70] set the current state-of-the-art in terms of performance among the family of exact continuous mathematical models for irregular strip packing without rotations. Finally, Pantoja-Benavides et al. [96] introduces a reformulation of the DTM model with rotations of Cherri et al. [32] that includes a separation constraint and a new set of valid inequalities that allows them to set the state of the art for the exact continuous problem with discrete rotations.

Concerning the families of discrete and semi-continuous MILP models for nesting, Toledo et al. [117] introduces the pioneering discrete MILP model for nesting, called Dotted-Board (DB), which is based on a set of binary decision variables for constraining the positions of the polygons to be on a grid of fixed points. The DB model has several nice properties, as follows. Firstly, the DB model reduces the definition of non-overlapping constraints among pieces to a set of edge inequalities for pairs of binary variables encoding each infeasible placement between pairs of pieces, which provides one formulation that is independent of both the geometry of the pieces and the board, allowing the representation of irregular pieces with or without holes, as well as any geometry for the board in the same way (e.g. rectangular, leathers with quality zones and defects, etc). Secondly, the DB model preserves the exact geometry of the pieces, unlike other discrete methods which discretize both the pieces and the board, such as the heuristics proposed by Segenreich and Faria Braga [111], Oliveira and Ferreira [93], Babu and Babu [13] and Chehrazad et al. [26] among others. And thirdly,

the DB model might be interpreted as a particular case of the more general set packing problem [14], whose polytope corresponds to the well-known polytope defined by the ILP formulation of the maximum stable set problem [54, 75] for an undirected graph $G = (V, E)$, denoted by $STAB(G)$, which can be traced back up to the pioneering work of Padberg [95]. Thus, this latter property of the DB formulation might potentially allow us to benefit from the large corpus of knowledge and valid inequalities proposed for the Stable Set problem (SSP). However, the DB model has several drawbacks and limitations as follows: (1) its number of non-overlapping constraints grows exponentially with the number of dots and polygon types; (2) it does not consider rotations of the pieces; (3) the quality of the discrete solutions produced by the DB model depends both on the grid resolution, as argued by Toledo et al. [117] and shown experimentally by Sato et al. [109], and the distribution of the points within the board; and finally, (4) it is a mixed-integer programming model, which prevents its resolution with either CP and SAT-based methods or exact implicit enumeration algorithms as done herein. Cherri et al. [31] bridge the second and third aforementioned drawbacks of the DB model by proposing the use of non-regular grids and one extension of the DB model considering discrete rotations of the pieces. Rodrigues and Toledo [105] successfully solve the first drawback detailed above and set the current state of the art of the discrete nesting problem by proposing a Clique Covering MILP reformulation of the DB model that we call DB Clique Covering (DB-CC) model here, which uses edge and vertex clique coverings to reduce significantly the number of constraints and tighten the LP relaxation of the model. However, DB-CC requires a significant preprocessing time to compute the edge and vertex clique coverings, and the lack of a discrete DB formulation without continuous variables is still an open question. Finally, the difficulty of solving exactly the DB model [117] has encouraged the proposal of metaheuristics to find near-optimal solutions in reasonable running times, such as the Biased Random-Key Genetic Algorithm (BRKGA) introduced by Mundim et al. [87] and the Raster Overlap Minimization Algorithm (ROMA) proposed by Sato et al. [106]. However, no exact alternative algorithm to the traditional Branch-and-Cut approach [94, 59, 86] implemented by all MIP solvers has been proposed yet.

Concerning the exploration and proposal of new tightening valid inequalities for the DB model [117], the current knowledge about the stable set polytope suggests that achieving a tighter formulation that might be efficiently solved with the standard Branch-and-Cut approach is unlikely, as pointed out by Giandomenico et al. [54] who argue that despite the large set of valid inequalities proposed for the stable set problem, such as clique inequalities [95], odd-hole inequalities [95, 90], web and antiweb inequalities [118], wheel inequalities [27], and anti-wheel inequalities [28], “none of them, to the best of our knowledge, gave any computational outcome” [54, p.108]. For this reason, this work focuses on proposing exact alternative algorithms to the standard Branch-and-Cut framework to bridge the performance and scalability gaps of the DB model.

The main motivation of this work is to solve efficiently the first drawback of the DB model enumerated above and the preprocessing drawback of the DB-CC model by introducing an exact algorithm called Dotted-Board Parallel Backtracking (DB-PB) to solve the DB model from the conflict inverse graph based on ad-hoc data structures, bounding, and forward-checking for pruning the search space. Likewise, we introduce two 0-1 ILP reformulations with discrete rotations of the current family of DB models [117, 105] called the Binary Dotted-Board (BDB) model and the Binary Dotted-Board Clique Covering model (BDB-CC), respectively, to bridge the fourth drawback of the DB model [117]. Finally, we introduce a new lower-bound algorithm called (DB-PB-LB) as a by-product. Our main hypothesis is that an ad-hoc exact algorithm requiring no preprocessing might be a better option to solve the DB model than the costly general-purpose Branch-and-Cut or hybrid CP-SAT methods, in addition to avoiding the need for computing edge and vertex clique coverings. A second aim of this work is to carry out a fair and reproducible comparison of our new exact algorithms and 0-1 DB ILP models with the state-of-the-art discrete DB-CC MILP model of Rodrigues and Toledo [105] by exactly replicating both their clique covering model and the experiments reported in their article [105] into a single software and hardware platform based on our C# implementation of our exact algorithms in the .NET 8 platform and the state-of-the-art Gurobi and Google CPSat solvers. Finally, a third aim is to bridge

the lack of reproducibility resources hampering the independent replication and confirmation of previously reported methods and results by providing a detailed reproducibility protocol and dataset as supplementary material to allow the exact replication of all our methods, experiments, and results.

The main research problem tackled by this work is the proposal of efficient exact algorithms for the resolution of the discrete DB MILP model [117] for nesting requiring no preprocessing, together with two 0-1 DB ILP reformulations to remove the continuous variables, and a new lower algorithm for discrete nesting. Thus, our main contribution is the introduction of an ad-hoc parallel branch-and-bound-and-prune algorithm for the efficient solution of the DB model, called Dotted-Board Parallel Backtracking (DP-PB) algorithm. A second contribution is the proposal of two 0-1 ILP reformulations of the DB model considering discrete rotations, called Binary DB model and Binary DB Clique Covering model, respectively. A third contribution is the proposal of a new lower bound algorithm as a by-product of our new DB-PB algorithm. Finally, a fourth contribution is the exact replication of the DB Clique Covering model and the experiments introduced by Rodrigues and Toledo [105], together with a set of reproducibility resources provided as supplementary material to allow the exact replication of all our methods, experiments, and results.

The rest of the paper is structured as follows. Section 2 introduces the formulation and notation of the current family of DB models for nesting to make the comprehension of our new methods and contributions easier. Section 3 introduces our two 0-1 ILP reformulations of the former DB and DB-CC models [117, 105], whilst Section 4 introduces our exact parallel branch-and-bound-and-prune algorithm to solve efficiently the DB model [117] with no preprocessing, and Section 5 introduces our new lower bound algorithm for nesting. Section 6 details our experimental setup and results, whilst section 7 introduces our discussion of the results. The final section summarizes our main conclusions and future work. Finally, Appendix A introduces the best solutions obtained for all problem instances in our experiments, whilst Appendix B introduces a detailed reproducibility protocol based on our supplementary dataset [71] to allow the exact replication of all our models, experiments, and results. Both appendices are provided as supplementary materials.

2. Preliminary concepts and problem definition

This section introduces the DB model of Toledo et al. [117] and its reformulation based on clique coverings proposed by Rodrigues and Toledo [105] that we called DB-CC in this work, as well as the notation shared by all ILP models and exact algorithms introduced herein, including the decision variables and indexes for the DB model with discrete rotations introduced by Cherri et al. [31]. The discrete nesting problem with discrete rotations can be formalized as follows. Let $\mathcal{P} = \{P_1, \dots, P_N\}$ be a set of irregular polygons not necessarily different with reference points $r_i \in \mathbb{R}^2$, called *pieces*, and let $\mathcal{T} = \{1, \dots, T\}$ be a set of types of pieces, such that each piece $P_i \in \mathcal{P}$ belongs to some $t \in \mathcal{T}$, and $\Theta = \bigcup_{t \in \mathcal{T}} \Theta_t$ the set of feasible rotations, such that $\Theta_t = \{\theta_t^k \in [0, 2\pi], k = 1, \dots, K_t\}$ is the discrete set of feasible rotations for each type of piece $t \in \mathcal{T}$. Let $\mathcal{B} \subset \mathbb{R}^2$ be an open rectangle with fixed width W and length variable L called the *board*, and $\mathcal{D} \subset \mathcal{B}$ a finite set of points defining a discretization of \mathcal{B} , as shown in Figure 1c. Then, the minimization problem (2.1) defines the optimal solution to the discrete irregular strip-packing problem, where $P_i(\theta_i)$ denotes an orientation of the piece P_i respect to its reference point r_i and $P_i(\theta_i) \oplus d_i$ denotes a translation of the piece such that its reference point is positioned at $d_i \in \mathcal{D}$. Constraints (2.2) prevent the overlapping of pieces, whilst Constraints (2.3) force the pieces to be entirely contained in the board.

$$\min_{d_i, \theta_i, L} z = L \quad (2.1)$$

$$s.t. \quad \text{int}(P_i(\theta_i) \oplus d_i) \cap \text{int}(P_j(\theta_j) \oplus d_j) = \emptyset, \quad 1 \leq i < j \leq N \quad (2.2)$$

$$(P_i(\theta_i) \oplus d_i) \subseteq \mathcal{B}, \quad 1 \leq i \leq N \quad (2.3)$$

$$d_i \in \mathcal{D}, \theta_i \in \Theta, \quad 1 \leq i \leq N \quad (2.4)$$

$$L \in \mathbb{R}^+ \quad (2.5)$$

2.1. The Dotted-Board (DB) model

The Dotted-Board (DB) model [117] is defined by the Objective function (2.7) and the Constraints (2.8) to (2.12), together with the decision variables, parameters, and index sets detailed below. The basic DB model is based on a regular discretization of the board; however, it admits any sort of regular or irregular point pattern, as shown by Cherri et al. [31]. Given any piece of type $t \in \mathcal{T}$, its Inner-Fit Polygon, denoted by IFP_t , defines the set of feasible positions $d \in \mathcal{D}$ in which the piece is completely contained in the board. Concerning the representation of the non-overlapping constraints between pairs of pieces, given two piece instances $P_i, P_j \in \mathcal{P}$ with types $t, u \in \mathcal{T}$ respectively, we call P_i the static piece and P_j the orbiting one, then the non-overlapping relative feasible positions $d, d' \in \mathcal{D}$ between both pieces are defined as the complementary set of their no-Fit polygon, denoted by \mathcal{NFP}_{tu}^d . Every grid point $d \in \mathcal{D}$ defines a set of binary decision variables δ_t^d whose activation in any feasible solution indicates that a piece of type $t \in \mathcal{T}$ is placed in that position. Thus, the number of binary decision variables in the DB model is proportional to $D \times T$, and it grows linearly with the number of points and type of pieces.

Decision variables

δ_t^d	Binary variables indicating that one piece of type $t \in \mathcal{T}$ is placed in the dot $d \in \mathcal{D}$.
L	Continuous positive decision variable representing the length of the board B .

Parameters

W	Board width
\bar{L}	Upper Bound (UB) for the length of the board.
\underline{L}	Lower Bound (LB) for the length of the board.
g_x	Horizontal x-axis grid resolution.
g_y	Vertical y-axis grid resolution.
q_t	Number of pieces demanded for each piece type.
T	Number of different piece types.
$N = \sum_{t=1}^T q_t$	Total number of pieces.
x_t^m	Horizontal distance from the leftmost point of any piece to its reference point r_i .
x_t^M	Horizontal distance from the rightmost point of any piece to its reference point r_i .
y_t^m	Vertical distance from the bottommost point of any piece to its reference point r_i .
y_t^M	Vertical distance from the topmost point of any piece to its reference point r_i .
l_t	Length of pieces of type $t \in \mathcal{T}$.
a_t	Area of pieces of type $t \in \mathcal{T}$.
$C = \left\lceil \frac{\bar{L}}{g_x} \right\rceil + 1$	Number of columns.
$R = \left\lceil \frac{W}{g_y} \right\rceil + 1$	Number of rows.
$D = C \times R$	Total number of dots.

The Objective function (3.2) sets the minimization of the decision variable L encoding the length of the board. The continuous L decision variable is defined by all current MILP models for nesting to linearize the objective function $z = \min\{\max\{x_i + x_i^M : 1 \leq i \leq N\}\}$, where x_i denotes the position of any piece instances P_i of type t that is placed into the board. Constraints (2.8) force all pieces to be inside the board. Constraints (2.9) set the demand constraints by forcing the placement of all pieces in any feasible solution. Constraints (2.10) encode the non-overlapping constraints among pieces, called edge inequalities

A parallel branch-and-bound-and-prune algorithm for irregular strip packing with discrete rotations

in the literature on set packing because they define an edge in the conflict graph $G = (V, E)$, where each vertex $v \in V$ represents a binary decision variable δ_v^d and there is an edge $e \in E$ for every pair of variables δ_u^d, δ_t^d appearing in one Constraint (2.10). Finally, Constraints (2.11) and (2.12) set the domains of the decision variables. The trivial lower bound for the length of the board used by the DB model and most of nesting MILP models is set by the formula (2.6) below.

$$\underline{L} = \max \left\{ \frac{1}{W} \sum_{t=1}^T a_t q_t, \max \left\{ \bigcup_{t=1}^T l_t \right\} \right\} \quad (2.6)$$

Index sets

$\mathcal{P} = \{1, \dots, N\}$

Indexes for every piece instance P_i to be placed in the board \mathcal{B} .

$\mathcal{D} = \{0, 1, 2, \dots, D-1\}$

Indexes representing every dot $d = c_d \times R + r_d \in \mathcal{D}$ in the board, where c_d and r_d are the column and row indexes corresponding to dot $d \in \mathcal{D}$.

$\mathcal{T} = \{1, 2, \dots, T\}$

Indexes denoted by $t \in \mathcal{T}$ representing every different type of piece.

$\mathcal{IFP}_t = \{d \in \mathcal{D} : P_t \oplus d \subseteq \mathcal{B}\}$

Indexes for the feasible positions of pieces of type $t \in \mathcal{T}$.

$\mathcal{NFP}_{tu}^d = \{d' \in \mathcal{IFP}_u : \text{int}(P_t \oplus d) \cap \text{int}(P_u \oplus d') \neq \emptyset\}$

Set of infeasible relative positions between pieces of type t and u when the former one is placed at point $d \in \mathcal{D}$.

Dotted-Board (DB) model [117]

$$\min_{\delta_t^d, L} \quad z = L \quad (2.7)$$

$$\text{s.t.} \quad (c_d g_x + x_t^M) \delta_t^d \leq L, \quad \forall d \in \mathcal{IFP}_t, \forall t \in \mathcal{T} \quad (2.8)$$

$$\sum_{d \in \mathcal{IFP}_t} \delta_t^d = q_t, \quad \forall t \in \mathcal{T} \quad (2.9)$$


$$\delta_u^d + \delta_t^d \leq 1, \quad \forall d' \in \mathcal{NFP}_{tu}^d, \forall (t, u) \in \mathcal{T} \times \mathcal{T}, \forall d \in \mathcal{IFP}_t \quad (2.10)$$

$$\delta_t^d \in \{0, 1\}, \quad \forall d \in \mathcal{IFP}_t, \quad \forall t \in \mathcal{T} \quad (2.11)$$


$$L \in [\underline{L}, \bar{L}] \subset \mathbb{R}_+ \quad (2.12)$$

Computation of the no-fit polygons. Given two polygons $X, Y \subset \mathbb{R}^2$, their Minkowski sum is defined as $X \oplus Y = \{x + y : x \in X, y \in Y\}$. Using the Minkowski sum, the no-fit polygon between polygons A and B is defined as $\mathcal{NFP}_{AB} = A \oplus -B$, where A is the static polygon and B the orbiting one. Currently, there are three main families of methods for the computation of the NFP as follows: (1) the family of orbiting methods, such as those introduced by Mahadevan [82], Ghosh [53], Dean et al. [38], Burke et al. [23], Burke et al. [24], and the method restricted to convex pieces of Cuninghame-Green [34], whose core idea is to slide the orbiting polygon around the static polygon; (2) the family of methods based on Minkowski sums, such as those methods proposed by Bennell et al. [15], Bennell and Song [19], and Milenkovic and Sacks [85], whose core idea is to exploit the definition of the NFP as a Minkowski sum; and finally, (3) the family of decomposition methods, whose core idea is to decompose the problem in three steps as follows: (a) decomposition of the input polygons into convex or star-shaped sub-parts, such as done by Watson and Tobias [123], Licari and Lo Valvo [79] and Li and Milenkovic [78, §4], respectively; (b) computation of the NFP between convex or star-shaped polygons using any specialized algorithm, such as the orbiting methods of Cuninghame-Green [34] or Minkowski sums [20, p.299] for convex polygons; and (c) the recombination of the convex or star-shaped NFP parts to obtain the overall NFP, as detailed by Agarwal et al. [5, §4]. To build the non-overlapping constraints (2.10) above, we use the same approach introduced in our previous work [70]


A parallel branch-and-bound-and-prune algorithm for irregular strip packing with discrete rotations




(a) Representation of the geometry of piece P_i of type $t \in \mathcal{T}$, where r_i sets its reference point, whilst that x_i^m and x_i^M denotes its minimal and maximal horizontal coordinates regarding r_i and y_i^m and y_i^M denotes its minimal and maximal vertical coordinates. The point r_i is set to the bottom-left point of its bounding box by default.



(b) No-fit polygon NFP_{AB} between the polygons A and B computed in \mathbb{R}^2 . The no-fit polygons between pair of pieces can be pre-calculated and referenced to the reference point of the static pieces to compute later the NFP dots by intersecting the grid dots with the NFP continuous regions.



(c) Regular discretization of the board B and Inner Fit Polygon (IFP) for a piece of triangle type t regarding the discrete board as defined by the Dotted-Board model [117]. The blue point at the origin sets the reference point of the piece, whilst black dots set its feasible positions within the board. The values g_x and g_y denote the horizontal and vertical dimensions of the grid, although any irregular grid might be used [31].



(d) Black dots define the set of discrete positions belonging to the $NFP_{ts}^{(0,0)}$ defining the infeasible positions for pieces of square type s regarding pieces of triangle type t when a triangle is positioned in the grid point $(0, 0)$.

in which we decompose all pieces into convex parts using the Greene's convex decomposition algorithm [58] implemented by the CGAL .NET wrapper [110], and then, we compute all pairwise convex no-fit polygons between convex parts of two different pieces by using the Minkowski sum for convex polygons [70, Algorithm 1]. However, the readers might use any known NFP algorithm for this aim.

The DB model with discrete rotations. For the sake of completeness, we introduce below the binary decision variables $\delta_i^{d\theta}$, parameters, and index sets required by the formulation of the DB model with discrete rotations [31], denoted by DB-Rot here, which will be used in our 0-1 DB reformulations. The DB-Rot model [31] is easily derived from the basic DB model [117] above by substituting the binary variables δ_i^d by its extended version $\delta_i^{d\theta}$ indicating that a piece of type $t \in \mathcal{T}$ is placed in point $d \in \mathcal{D}$ with orientation $\theta \in \Theta_t$. Finally, it is needed to define the index sets for the discrete rotations Θ , inner-fit polygons IFP_t^θ , and no-fit polygons $\mathcal{NFP}_{tu}^{d\theta}$, as detailed in eq. (2.13) to (2.15).

$$\Theta = \bigcup_{\forall t \in \mathcal{T}} \Theta_t, \quad \Theta_t = \{\theta_t^k \in [0, 2\pi], k = 1, \dots, K_t\} \quad (2.13)$$

$$\mathcal{IFP}_t^\Theta = \{(d, \theta) \in \mathcal{D} \times \Theta_t : P_t(\theta) \oplus d \subseteq B\} \quad (2.14)$$

$$\mathcal{NFP}_{tu}^{d\theta} = \{(d', \theta') \in \mathcal{IFP}_u^\Theta : \text{int}(P_t(\theta) \oplus d) \cap \text{int}(P_u(\theta') \oplus d') \neq \emptyset\} \quad (2.15)$$

Extended decision variables, parameters, and index sets for the DB model with rotations [31]

- $\delta_t^{d\theta}$ Binary variables indicating that one piece of type $t \in \mathcal{T}$ with orientation $\theta \in \Theta_t$ is placed in $d \in \mathcal{D}$.
- $x_{t\theta}^M$ Distance from the rightmost point of one piece of type $t \in T$ with orientation $\theta \in \Theta_t$ to its reference point, as shown in Figure 1a.

2.2. The Dotted-Board Clique Covering (DB-CC) model

As mentioned above, the main drawback of the DB model [117] to be efficiently solved within the standard Branch-and-Cut framework [94, 59] is that the number of non-overlapping constraints defined by Constraints (2.10) grows exponentially with the number of dots and types of piece. Rodrigues and Toledo [105] solve this latter scalability drawback, and set the current state of the art among the family of discrete mathematical models for nesting, by proposing a new polynomial-size clique-based reformulation of the DB model called Dotted-Board Clique Covering (DB-CC) model here, which is defined by the Objective function (2.16) and Constraints (2.17) to (2.21) detailed below.

The representation of constraints among binary variables as conflict graphs, and the computation of clique covering cuts is a well-known technique in integer programming, as discussed by Atamtürk et al. [11] and efficiently applied to the discrete nesting problem by Rodrigues and Toledo [105]. The conflict graph $G = (V, E)$ of any DB problem instance is defined as follows, the vertex set V contains one vertex for each binary decision variable δ_t^d and one edge $(\delta_t^d, \delta_u^{d'}) \in E$ if the DB model contains one non-overlapping Constraint (2.10) for these pair of variables, as detailed above. On the other hand, the subset of variables δ_t^d whose associated length bound L_t^d as defined in equation (2.22) is greater than the lower bound for the board's length \underline{L} induces the sub-graph $G_{\underline{L}^+} = (V_{\underline{L}^+}, E_{\underline{L}^+}) \subset G$ that allows defining a vertex clique covering $\mathcal{V}_{\underline{L}^+}$ to partition $V_{\underline{L}^+}$ into a collection of independent vertex sets in $G_{\underline{L}^+}$. One edge clique covering \mathcal{E} of the graph G can be computed with any minimal Edge Clique Covering algorithm, such as those introduced by Rodrigues [103] and Conte et al. [33], whilst one vertex clique covering $\mathcal{V}_{\underline{L}^+}$ of the sub-graph $G_{\underline{L}^+}$ can be computed with any graph coloring algorithm, such as the Recursive Largest First (RLF) heuristics proposed by Leighton [74] and implemented by Rodrigues and Toledo [105] to build the Constraints (2.17).

Dotted-Board Clique Covering (DB-CC) model [105]

$$\min_{\delta_t^d, L} z = L \quad (2.16)$$

$$\text{s.t. } \underline{L} + \sum_{\forall (d,t) \in K} (c_d g_x + x_t^M - \underline{L}) \delta_t^d \leq L, \quad \forall K \in \mathcal{V}_{\underline{L}^+} \quad (2.17)$$

$$\sum_{\forall d \in \mathcal{IFP}_t} \delta_t^d = q_t, \quad \forall t \in \mathcal{T} \quad (2.18)$$

$$\sum_{\forall (d,t) \in K} \delta_t^d \leq 1, \quad \forall K \in \mathcal{E} \quad (2.19)$$

$$\delta_t^d \in \{0, 1\}, \quad \forall d \in \mathcal{IFP}_t, \quad \forall t \in \mathcal{T} \quad (2.20)$$

$$L \in [\underline{L}, \bar{L}] \subset \mathbb{R} \quad (2.21)$$

The DB-CC model is based on the definition of the conflict graph $G = (V, E)$ and its corresponding sub-graph $G_{\underline{L}^+}$ of variables with length bounds greater than \underline{L} in expressions (2.23) to (2.28) and two smart transformations of the DB model detailed below, which contribute to tightening the LP relaxation of the DB-CC model in comparison with the basic DB model [117].

$$L_t^d = c_d g_x + x_t^M, \quad \forall d \in \mathcal{D} \quad (2.22)$$

$$G = (V, E) \quad (2.23)$$

$$V = \{\delta_t^d, \forall d \in \mathcal{IFP}_t, \forall t \in \mathcal{T}\} \quad (2.24)$$

$$E = \{(\delta_t^d, \delta_u^{d'}) \in V \times V : d' \in \mathcal{NFPP}_{tu}^d \wedge (t, u) \in \mathcal{T} \times \mathcal{T} \wedge d \in \mathcal{IFP}_t\} \quad (2.25)$$

$$G_{\underline{L}^+} = (V_{\underline{L}^+}, E_{\underline{L}^+}) \quad (2.26)$$

$$V_{\underline{L}^+} = \{\delta_t^d \in V : L_t^d > \underline{L}\} \quad (2.27)$$

$$E_{\underline{L}^+} = \{\delta_t^d, \delta_u^{d'} \in V_{\underline{L}^+} : \exists(\delta_t^d, \delta_u^{d'}) \in E\} \quad (2.28)$$

Transformation of the DB non-overlapping constraints. The non-overlapping Constraints (2.10) of the DB model are substituted by their edge-clique covering reformulation (2.19) derived from the conflict graph $G = (V, E)$ induced by the edge inequalities (2.10) above.

Transformation of the DB inner-fit constraints. The inner-fit Constraints (2.8) of the DB model are substituted by their vertex-clique covering reformulation (2.17). This transformation is based on the fact that the inner-fit Constraints (2.8) of the DB model are always met by all variables for which $L_t^d \leq \underline{L}$. Thus, these latter constraints can be removed from the model and the remaining ones factorized by using one vertex clique covering, as defined by the Constraints (2.17) above. The variables belonging to the same vertex clique $K \in \mathcal{V}_{\underline{L}^+}$ can be activated at the same time because they belong to an independent set of G . Thus, they can be summed in the same inequality, as done in (2.17).

3. The two new 0-1 ILP reformulations for nesting

This section introduces two 0-1 Integer Linear Programming reformulations of the family of DB models [117, 105, 31] with discrete rotations based on defining a set of binary variables to encode all feasible values for the length upper bounds of the problem. We call these two 0-1 DB ILP reformulations the Binary Dotted-Board (0-1 DB) model and the Binary Dotted-Board Clique Covering model (0-1 DB-CC), respectively. All coefficients of the constraints matrix and objective function of the new 0-1 ILP models take integer values in the set $\{1, 0, -1, N\}$. These two 0-1 ILP formulations have been devised to make the family of DB models amenable to being solved either by state-of-the-art CP solvers, such as Google CP-Sat [97], or ad-hoc exact algorithms as the one proposed in section 4. Finally, our 0-1 ILP models open the possibility to explore SAT-based reformulations that might be solved with state-of-the-art incremental SAT solvers, such as CaDiCal [21], Glucose [12] and MiniSAT [47, 112] among others. Next, we introduce the extended sets of decision variables, parameters, and index sets used in our formulations.

Extended decision variables, parameters, and index sets

z_m	Binary variables indicating that the length upper bound $\mathcal{L}_m > \underline{L}$ is enabled in the solution, and thus, solutions with length $L \leq \mathcal{L}_m$ are feasible.
$L_t^{d\theta} = c_d g_x + x_t^M$	Length bound induced by every feasible orientation $\theta \in \Theta_t$ of a piece of type $t \in \mathcal{T}$ when it is placed in dot $d \in \mathcal{D}$.
$\mathcal{L}^+ = \{\mathcal{L}_m \in (\underline{L}, \bar{L}], 1 \leq m \leq M\}$	Set of all feasible length upper bounds as defined in (3.1).

We use the same notation introduced in Section 2 to formalize our new 0-1 DB ILP models. However, we introduce a new set of binary decision variables, denoted by z_m , to encode the ordered set of length upper bounds \mathcal{L}^+ , and the index set M for indexing the variables z_m and their corresponding length upper bounds \mathcal{L}_m . To discretize the feasible length values of the problem, the statement (3.1) defines the set of all feasible length upper bounds \mathcal{L}^+ , which is converted into a total ordered set $(\mathcal{L}^+, \leq_{\mathbb{R}})$ by using the standard order relation of the real numbers. All length upper bounds are sorted in ascending order, such that $\underline{L} < \mathcal{L}_1 < \mathcal{L}_2 < \dots < \mathcal{L}_M$ and one z_m binary decision variable is defined to enable all feasible solutions whose associated length upper bound is equal or greater than \mathcal{L}_m .

$$\mathcal{L}^+ := \left\{ \mathcal{L} \in \bigcup_{\forall t \in \mathcal{T}} \left(\bigcup_{\forall (d, \theta) \in IFP_t^\ominus} L_t^{d\theta} \in \mathbb{R} \right) : \mathcal{L} > \underline{L} \right\}, \quad M = |\mathcal{L}^+| \quad (3.1)$$

3.1. The Binary Dotted-Board model

The Binary Dotted-Board (0-1 DB) model is defined by the objective function (3.2) and the Constraints (3.3) to (3.8), together with the decision variables, parameters, and index sets detailed above. Constraints (3.3) enable the length upper bounds represented by the binary decision variable z_m according to the order relationship for the upper bound set \mathcal{L}^+ . Constraints (3.4) set the demand constraints by forcing the placement of all pieces in any feasible solution. Constraints (3.5) encode the non-overlapping constraints associated with any infeasible relative positioning and orientation between two pieces. Constraints (3.6) enable the feasible placements of the pieces corresponding to each feasible length upper bound \mathcal{L}_m . Finally, Constraints (3.7) and (3.8) set the domains of the decision variables.

Binary DB (0-1 DB) model

$$\min_{\delta_t^{d\theta}, z_m} \quad z = \sum_{m=1}^M z_m \quad (3.2)$$

$$s.t. : \quad z_m \leq z_{m-1}, \quad 1 < m \leq M \quad (3.3)$$

$$\sum_{\forall (d, \theta) \in IFP_t^\ominus} \delta_t^{d\theta} = q_t, \quad \forall t \in \mathcal{T} \quad (3.4)$$

$$\delta_u^{e\theta'} + \delta_t^{d\theta} \leq 1, \quad \forall (e, \theta') \in \mathcal{NFP}_{tu}^{d\theta}, \forall (d, \theta) \in IFP_t^\ominus \quad (3.5)$$

$$\sum_{t=1}^T \sum_{\forall (d, \theta) \in IFP_t^\ominus : L_t^{d\theta} \geq \mathcal{L}_m} \delta_t^{d\theta} \leq N z_m, \quad 1 \leq m \leq M \quad (3.6)$$

$$\delta_t^{d\theta} \in \{0, 1\}, \quad \forall t \in \mathcal{T}, \forall (d, \theta) \in IFP_t^\ominus \quad (3.7)$$

$$z_m \in \{0, 1\}, \quad 1 \leq m \leq M \quad (3.8)$$

Given any feasible solution to the 0-1 DB model above, its length L is defined by the formula (3.9) below, where \mathcal{L}_z is the length upper bound indexed by the value of the objective function (3.2).

$$L = \begin{cases} \underline{L}, & z = 0 \\ \mathcal{L}_z, & z > 0 \end{cases} \quad (3.9)$$

3.2. The Binary DB Clique Covering model

The Binary Dotted-Board Clique Covering (0-1 DB-CC) model is defined by the Objective function (3.10) and the Constraints (3.11) to (3.16). Constraints (3.11) enable the ordered set $(\mathcal{L}^+, \leq_{\mathbb{R}})$ of feasible

length upper bounds. Constraints (3.12) set the demand constraints by forcing the placement of all pieces in any feasible solution. Constraints (3.13) encode the non-overlapping constraints associated to the cliques $\mathcal{K} \in \mathcal{E}$ of mutually infeasible relative placements of pieces defined by the conflict graph $G = (V, E)$ of every problem instance, where \mathcal{E} is any edge clique covering of the conflict graph G , as explained in Section 2.2. Constraints (3.14) enable the feasible placements of the pieces corresponding to each feasible length upper bound \mathcal{L}_m . Finally, Constraints (3.15) and (3.16) set the domains of the decision variables.

Binary DB Clique Covering (0-1 DB-CC) model

$$\min_{\delta_t^{d\theta}, z_m} z = \sum_{m=1}^M z_m \quad (3.10)$$

$$s.t. : z_m \leq z_{m-1}, \quad 1 < m \leq M \quad (3.11)$$

$$\sum_{\forall (d,\theta) \in IFP_t^\ominus} \delta_t^{d\theta} = q_t, \quad \forall t \in \mathcal{T} \quad (3.12)$$

$$\sum_{\forall (t,d,\theta) \in \mathcal{K}} \delta_t^{d\theta} \leq 1, \quad \forall \mathcal{K} \in \mathcal{E} \quad (3.13)$$

$$\sum_{t=1}^T \sum_{\forall (d,\theta) \in IFP_t^\ominus : L_t^{d\theta} \geq \mathcal{L}_m} \delta_t^{d\theta} \leq N z_m, \quad (3.14)$$

$$\delta_t^{d\theta} \in \{0, 1\}, \quad \forall t \in \mathcal{T}, \forall (d, \theta) \in IFP_t^\ominus \quad (3.15)$$

$$z_m \in \{0, 1\}, \quad 1 \leq m \in M \quad (3.16)$$

4. The parallel branch-and-bound-and-prune algorithm for nesting

This section introduces our parallel branch-and-bound-and-prune algorithm for the discrete nesting problem, which is based on a parallel backtracking enumeration with bounding and forward-checking to prune the solution space of any Dotted-Board problem instance, together with a set of ad-hoc data structures for their efficient implementation. Our Dotted-Board Parallel Backtracking (DB-PB) algorithm is made up of the following components: (1) the ad-hoc global data structures detailed in Table 1; (2) the initialization procedure detailed in Algorithm 1; (3) the main solving function detailed in Algorithm 2; (4) the branch-and-bound-and-prune algorithm detailed in Algorithm 3; (5) an ad-hoc forward-checking [63] algorithm detailed in Algorithm 4; and (6) the thread-safe incumbent updating and dominated variable pruning detailed in Algorithm 5. The efficiency of DB-PB is achieved by an appropriate integration of the features detailed in the paragraphs below.

BitArray representation. All non-overlapping constraints of any DB problem instance are encoded in the adjacency matrix $\Pi_{\tilde{G}}$ of the complement or inverse graph $\tilde{G} = (V, \tilde{E})$ of the conflict graph $G = (V, E)$, as detailed in Table 1. $\Pi_{\tilde{G}}$ is represented in memory by an array of BitArray objects with only a memory space complexity of $\mathcal{O}(\frac{V^2}{8})$ bytes, which allows DB-PB implementing a very efficient binary constraint propagation by using the fast bitwise AND operation. Thus, our BitArray representation makes unnecessary any clique cover reformulation of the DB model [105], because our algorithms can efficiently solve any DB problem instance directly from the inverse of the conflict graph, denoted by $\tilde{G} = (V, \tilde{E})$. For instance, a DB problem instance with half a million binary decision variables and thousands of millions of constraints might be represented and solved with roughly 30 GB of RAM. However, state-of-the-art general-purpose MIP and hybrid CPSat solvers might find serious difficulties in representing and solving these large problem instances,

Table 1

Global data structures shared and required by all algorithms introduced herein.

Global object	Description
$\pi_{\delta_i^{d\theta}}^V$	Mapping function from a DB decision variable $\delta_i^{d\theta}$ to its corresponding vertex index $v \in V$ in the conflict inverse graph \tilde{G} .
$\pi_V^{\delta_i^{d\theta}}$	Inverse mapping from a vertex index $v \in V$ to its corresponding variable.
$\Pi_{\tilde{G}} \in \{0, 1\}^{V \times V}$	BitArray matrix corresponding to the adjacency matrix of inverse graph \tilde{G} of the conflict graph $G = (V, E)$ together with the symmetry-breaking for identical pieces detailed in Algorithm 1, where each vertex $v \in V$ corresponds to a binary decision variable $\delta_i^{d\theta}$, such that $\Pi_{\tilde{G}}^{ij} = 0$, if $\exists (v_i, v_j) \in E$, or $\Pi_{\tilde{G}}^{ij} = 1$, otherwise.
$\pi_{inst} \in \mathbb{Z}^N$	Integer array storing the indexes of piece instances denoted by $\pi_{inst} \in \mathbb{Z}^N$.
$\pi_{idVar} \in \mathbb{Z}^{V \times 2}$	Integer matrix storing the index intervals defining the decision variables corresponding to each piece type within the BitArray $\pi_{nonDomVar}$ representing the values for all binary decision variables.
$\pi_{type} \in \mathcal{T}^N$	Integer array encoding the piece type for each piece instance $P_i \in \mathcal{P}$.
$\pi_{nonDomVar} \in \{0, 1\}^V$	BitArray encoding the feasibility state of all binary decision variables $\delta_i^{d\theta}$.
$\pi_{pieceTypeVarMask} \in \{0, 1\}^{T \times V}$	BitArray vector encoding the variable masks for each piece type $t \in \mathcal{T}$.
$L_i^V \in \mathbb{R}^V$	Real-value array encoding the length upper bound $L_i^{d\theta}$ of each indexed decision variable $\delta_i^{d\theta}$, such that exists an unique vertex index $v \in V$ for each binary decision variable.
$x_{inc} \in V^N$	Integer array encoding the index set of the binary decision variables selected in the incumbent solution for each piece instance.
$L_{inc} \in \mathcal{L}^+ \cup \underline{L}$	Objective value for the incumbent solution x_{inc} .
$opt_{proof} \in \{\bar{T}, F\}$	Boolean variable indicating that the optimality has been proven.

even their clique cover reformulations. On the other hand, for even larger problem instances, we might extend our data structures and algorithms to use sparse BitArray representations or virtual memory.

Symmetry-breaking for identical pieces. Algorithm 1 details the initialization of the main data structures supporting our algorithms, among which the most important one is the adjacency matrix $\Pi_{\tilde{G}}$ of the conflict inverse graph, because each row of this matrix encodes the constraints induced by the selection of any feasible position and orientation (binary variable) of a piece instance in the solution. Every time a piece instance is placed on the board at one decision level of our DB-PB algorithm by selecting a feasible binary variable in the solution, the constraints encoded by its corresponding row are propagated, setting to 0 all conflicting decision variables in subsequent decision levels. To break the symmetries generated by any permutation of the binary decision variables of the same piece type, we disable all binary variables of the same piece type corresponding to the precedent positions of the activated variable, according to the non-decreasing length bound order of the variables of each piece type, as shown in step 19 of Algorithm 1. These latter symmetries appear in our sequential solving and any CP formulation, but not in the family of DB integer programming models [117, 105, 31].

Piece-driven Binary Constraint Propagation (BCP). Algorithm 2 details the solving function of our DB-PB algorithm that solves the problem by using an exact backtracking enumeration with N decision levels, one for each piece instance, which is based on an ad-hoc piece-driven BCP approach. Unlike the general-purpose MIP, CP, and SAT solvers, whose decision level is a single binary decision variable, the overall efficiency of DB-PB is achieved because the BCP induced by each decision level can be efficiently implemented by a single bitwise AND operation between the input feasibility BitArray and the row of $\Pi_{\tilde{G}}$ matrix corresponding to the selected decision variable, as shown in step 10 of Algorithm 3, which starts with the current set of non-dominated variables represented by the BitArray $\pi_{nonDomVar}$, as shown in step

Algorithm 1 Our initialization algorithm to build the data structures detailed in Table 1 that are used by DB-PB to solve any DB problem instance, which includes the symmetry-breaking of all solutions induced by any permutation of the binary decision variables $\delta_t^{d\theta}$ for identical pieces during the solving stage.

Input: Dotted-Board problem instance

Output: Initialization of the main global data structures detailed in Table 1.

```

1: procedure INITIALIZATION
2:    $\pi_{\delta_t^{d\theta}}^V \leftarrow \text{sortVariableVector}()$      $\triangleright$  non-decreasing order of the decision variables according to  $L_t^{d\theta}$ 
3:    $\pi_V^{\delta_t^{d\theta}} \leftarrow (\pi_{\delta_t^{d\theta}}^V)^{-1}$      $\triangleright$  gets the inverse mapping
4:    $\pi_{nonDomVar} \leftarrow \mathbf{1}^V$      $\triangleright$  enabling all decision variables
5:    $L_t^V \leftarrow \mathbf{0}^V$ 
6:   for  $\forall v \in V$  do
7:      $L_t^V(v) \leftarrow L_t^{d\theta} : \text{index}(\delta_t^{d\theta} = v)$      $\triangleright$  initializes length bounds of variables
8:   end for
9:    $\Pi_{\tilde{G}} \leftarrow \mathbf{1}^{V \times V}$      $\triangleright$  initializes the adjacency (constraint) matrix
10:  for  $\forall (v, w) \in V \times V : v \neq w$  do     $\triangleright$  fills the adjacency matrix of the inverse conflict graph  $\tilde{G}$ 
11:    if  $\exists (\delta_t^{d\theta}(v), \delta_t^{d\theta}(w)) \in E$  then     $\triangleright (v, w) \in V \times V$  is an edge of the conflict graph  $G = (V, E)$ 
12:       $\Pi_{\tilde{G}}(v, w) \leftarrow 0$ 
13:       $\Pi_{\tilde{G}}(w, v) \leftarrow 0$ 
14:    end if
15:  end for
16:  for  $\forall t \in \mathcal{T}$  do     $\triangleright$  symmetry-breaking for identical pieces
17:    for  $i = \pi_{idVar}(t, 0)$  to  $\pi_{idVar}(t, 1) - 1$  do
18:      for  $j = \pi_{idVar}(t, 0)$  to  $i$  do
19:         $\Pi_{\tilde{G}}(i, j) \leftarrow 0$      $\triangleright$  disables all previous feasible variables, including the current one
20:      end for
21:    end for
22:  end for
23: end procedure

```

14 of Algorithm 2 and defined in Table 1. This latter feature allows DB-PB to ensure that every time one decision variable is included in any partial solution, hundreds or thousands of conflicting decision variables in subsequent decision levels can be disabled in microseconds. Likewise, our piece-driven BCP approach allows DB-PB to carry out a complete and very efficient pruning of infeasible partial solutions at the earliest decision level by forward-checking, as detailed in Algorithm 4.

Parallel backtracking. As mentioned above, Algorithm 2 details the solving function of our DB-PB algorithm which solves the problem by using a parallel backtracking enumeration with N decision levels based on partitioning the binary decision variables corresponding to the piece type of the first piece instance, called the root level, and calling the recursive *BranchAndBoundAndPrune* function detailed in Algorithm 3 from multiple threads, one for each subset of root decision variables. During the initialization detailed in Algorithm 1, all piece types and instances are first ordered in non-increasing area order, and later, the decision variables for each piece type are ordered in non-decreasing length bound order. Thus, the feasible positions of the root piece disable a larger number of feasible positions for the subsequent decision levels.

Algorithm 2 The main function of our exact Dotted-Board Parallel Backtracking (DB-PB) algorithm for discrete nesting. This function randomly partitions all feasible solutions for the first piece among all available threads, which are subsequently extended in parallel to complete a feasible solution by Algorithm 3.

Input: The global data structures detailed in Table 1 and initialized by Algorithm 1 1.

Output: The incumbent solution x_{inc} , incumbent objective value L_{inc} , and optimality proof opt_{proof} .

```

1: function DBPBsolve
2:    $opt_{proof} \leftarrow F$                                 ▷ initialization of optimality proof (global variable)
3:    $x_{inc} \leftarrow \emptyset$                             ▷ initialization of incumbent (global variable)
4:    $L_{inc} \leftarrow \infty$                             ▷ initialization of incumbent objective value (global variable)
5:    $mutex \leftarrow \text{new Mutex}()$                     ▷ initialization of the global mutex object
6:    $p_{root} \in [N] \leftarrow \pi_{inst}(1)$               ▷ gets the index of the root piece instance  $P_i \in (P)$  at decision level 1
7:    $t_{root} \in C \leftarrow \pi_{type}(p_{root})$           ▷ gets the piece type for the root piece instance
8:    $V_{root} \leftarrow \{v \in V : \pi_{idVar}(t_{root}, 0) \leq v < \pi_{idVar}(t_{root}, 1)\}$  ▷ gets the indexes for all variables of root
   piece
9:    $V_{root} \leftarrow \text{randSort}(V_{root})$             ▷ random sorting of the root-level decision variable indexes
10:  while  $opt_{proof} \neq T$  do
11:    for parallel  $\forall v \in V_{root}$  do                ▷ parallel solution space exploration from the root
12:      if  $\pi_{nonDomVar}(v)$  then                    ▷ prunes the dominated variables
13:         $x \leftarrow \emptyset$                       ▷ initializes an empty stack to store the variable indexes in the solution
14:         $x \leftarrow x \cup v$                       ▷ start a new partial solution at the root decision level (push)
15:         $\phi_1 \leftarrow \pi_{nonDomVar} \ \& \ \Pi_{\bar{G}}(v)$   ▷ propagates all constraints induced by the variable  $v$ 
16:        if  $|x| < N$  then
17:          if  $\text{ForwardChecking}(\phi_1, 1)$  then      ▷ pruning by detecting any future dead end
18:             $\text{BranchAndBoundAndPrune}(1, \phi_1, x, L_t^V(v), \pi_{inst})$   ▷ next decision level
19:          end if
20:          else
21:             $\text{UpdateIncumbent}(x, L_t^V(v))$           ▷ thread-safe updates incumbent
22:          end if
23:           $x \leftarrow x \setminus v$                 ▷ removes the latest tested variable index  $v$  (pop)
24:          if  $(\text{currentTime} > \text{timeLimit})$  or  $(opt_{proof} = T)$  then
25:            break
26:          end if
27:        end if
28:      end for
29:    end while
30:    return  $\{x_{inc}, L_{inc}, opt_{proof}\}$ 
31: end function

```

Branch-and-Bound-and-Prune. Algorithm 3 implements the core function of our DB-PB algorithm, which introduces a chronological backtracking enumeration empowered with the following pruning techniques. First, pruning by bounding on the length of the current partial solutions in steps 2, 5 and 8. Second, pruning of dominated variables by escaping from the loop in step 5, because all variables $\delta_t^{d\theta}$ encoding the feasible positions and orientations of each piece type $t \in \mathcal{T}$ are ordered in non-decreasing length-bound order, according to their $L_t^{d\theta}$ bounds. Thus, the loop 5 can be aborted whenever any dominated variable is found. And third, pruning by forward-checking in step 12 to avoid the expansion of any partial solution that would lead to a dead end in any subsequent decision level. As mentioned above, our BitArray representation

Algorithm 3 The Branch-and-Bound-and-Prune algorithm that visits all feasible solutions at each decision level using bounding and forward-checking for pruning the search space at the topmost decision level.

Input: (1) the decision level $\Delta \in [N]$; (2) a BitArray $\phi_{\Delta-1} \in \{0, 1\}^V$ setting the feasibility vector for all decision variables $\delta_t^{d\theta}$ at previous decision level, where V denotes the total number of binary variables; (3) the input partial solution $x \in V^{\Delta-1}$ represented by a stack containing the integer indexes of the variables selected in the solution; (4) the length upper bound $L_{\Delta-1}^x \in \mathbb{R}$ set by input partial solution x ; and (5) the indexes of the piece instances $\pi_{inst} \in \mathbb{Z}^N$ sorted in non-increasing area order.

```

1: procedure BRANCHANDBOUNDANDPRUNE( $\Delta, \phi_{\Delta-1}, x, L_{\Delta-1}^x, \pi_{inst}$ )
2:   if  $L_{\Delta-1}^x < L_{inc}$  then  $\triangleright$  prune current partial solution by comparing to the best objective value  $L_{inc}$ 
3:      $p_i \in \mathbb{Z} \leftarrow \pi_{inst}(\Delta)$   $\triangleright$  gets the index of the piece instance  $P_i \in (P)$  at decision level  $\Delta$ 
4:      $t \in \mathcal{C} \leftarrow \pi_{type}(p_i)$   $\triangleright$  gets the piece type for the piece instance to solve at decision level  $\Delta$ 
        $\triangleright$  the for loop below tests all level decision variables in non-decreasing order
        $\triangleright$  regarding their length upper bound  $L_t^v$ , where index  $v$  refers a variable  $\delta_t^{d\theta}$ 
5:     for  $v = \pi_{idVar}(t, 0)$  to  $\pi_{idVar}(t, 1) - 1$  while  $\pi_{nonDomVar}(v)$  and  $(L_{\Delta-1}^x < L_{inc})$  do
6:       if  $\phi_{\Delta-1}(v)$  then  $\triangleright$  test that the variable  $\delta_t^{d\theta}$  with index  $v$  is enabled
7:          $L_{\Delta}^{x \cup v} = \max\{L_{\Delta-1}^x, L_t^v\}$   $\triangleright$  gets the length UB for the extended solution  $x = x \cup v$ 
8:         if  $L_{\Delta}^{x \cup v} < L_{inc}$  then  $\triangleright$  prune next partial solution by bounding before propagating it
9:            $x \leftarrow x \cup v$   $\triangleright$  expands the partial solution (push)
10:           $\phi_{\Delta} \leftarrow \phi_{\Delta-1} \& \Pi_{\tilde{G}}(v)$   $\triangleright$  propagates all constraints induced the variable  $v$ 
11:          if  $|x| < N$  then  $\triangleright$  tests if the solution needs to be completed
12:            if ForwardChecking( $\phi_{\Delta}, \Delta$ ) then  $\triangleright$  pruning by detecting any future dead end
13:              BranchAndBoundAndPrune( $\Delta + 1, \phi_{\Delta}, x, L_{\Delta}^{x \cup v}, \pi_{inst}$ )  $\triangleright$  next decision level
14:            end if
15:          else
16:            UpdateIncumbent( $x, L_{\Delta}^{x \cup v}$ )  $\triangleright$  thread-safe incumbent updating
17:          end if
18:           $x \leftarrow x \setminus v$   $\triangleright$  removes the latest tested variable index  $v$  (pop)
19:        end if
20:      end if
21:    end for
22:  end if
23: end procedure

```

allows both a very efficient constraint propagation in step 10 and efficient forward-checking in step 12. The branching order of DB-PB is fixed a priori by the length-bound ordering of the variables, which allows saving computational time and escaping from the loop in step 5. Despite other branching heuristics are possible, they might require an extra computational cost that would negatively impact the global performance of our algorithms.

Forward-checking. Algorithm 4 details our ad-hoc forward-checking algorithm based on pruning dead ends by checking in step 7 that the current partial solution has not disabled all decision variables for the subsequent decision levels defined by their corresponding piece types. The input feasibility vector ϕ_{Δ} encodes the propagation of all conflicts from the root to the current decision level Δ . The current performance of our forward-checking algorithm avoids DB-PB's need to implement costly conflict-driven learning approaches to filter recurrent conflict sets of infeasible variables, as commonly done by most of CP [39, 52, 25, 97], SAT [83, 92, 49, 115], MIP [1, 2, 125, 126, 91], and hybrid CP-Sat solvers [97].

Algorithm 4 Our forward-checking algorithm to prune the expansion of partial solutions leading to infeasible solutions (dead ends) by checking that there still are feasible solutions for all pieces at the next decision levels.

Input: (1) a BitArray $\phi_\Delta \in \{0, 1\}^V$ setting the feasibility vector for all decision variables $\delta_t^{d\theta}$, where V is equal to the total number of decision variables; and (2) $\Delta \in [N]$ denotes the current decision level.

Output: Boolean value indicating that the current partial solution is feasible or sets a conflict (dead end).

```

1: function FORWARDCHECKING( $\phi_\Delta, \Delta$ )
2:   feasible  $\leftarrow T$ 
3:    $\mathcal{T}_{next} \subset \mathcal{T} \leftarrow \pi_{nextPieceTypes}(\Delta)$   $\triangleright$  retrieves the set of piece types for next decision levels
4:   for  $\forall t \in \mathcal{T}_{next}$  do
5:      $\phi_t \in \{0, 1\}^V \leftarrow clone(\pi_{pieceTypeVarMask}(t))$   $\triangleright$  gets the variable mask for the piece type
6:      $\phi_t^\Delta \leftarrow \phi_t \& \phi_\Delta$   $\triangleright$  binary constraint forward-propagation for a child piece type
7:     if  $\phi_t^\Delta = \mathbf{0}^V$  then  $\triangleright$  check that there exist feasible solutions for  $t \in \mathcal{T}$ 
8:       feasible  $\leftarrow F$ 
9:     break
10:  end if
11: end for
12: return feasible
13: end function

```

Algorithm 5 Thread-safe incumbent update function called from any thread.

Input: (1) a new incumbent candidate $x \in V^N$, and (2) its associated objective incumbent value $L_x \in \mathbb{R}$.

```

1: procedure UPDATEINCUMBENT( $x, L_x$ )
2:   mutex.Wait()  $\triangleright$  waits until the incumbent data is released
3:   if  $opt_{proof} = F$  and  $L_x < L_{inc}$  then  $\triangleright$  checks that none thread had improved the incumbent
4:     for  $\forall v \in V$  do
5:       if  $L_t^V(v) \geq L_x$  then
6:          $\pi_{nonDomVar}(v) \leftarrow F$   $\triangleright$  disables all dominated decision variables
7:       end if
8:     end for
9:     for  $\forall t \in \mathcal{T}$  do  $\triangleright$  disable all dominated variables in the mask of each piece type
10:       $\pi_{pieceTypeVarMask}(t) \leftarrow \pi_{pieceTypeVarMask}(t) \& \pi_{nonDomVar}$ 
11:    end for
12:     $L_{inc} \leftarrow L_x$   $\triangleright$  updates incumbent objective value
13:     $x_{inc} \leftarrow x$   $\triangleright$  updates incumbent solution
14:    if  $L_{inc} = \underline{L}$  then  $\triangleright$  optimality test
15:       $opt_{proof} \leftarrow T$ 
16:    end if
17:    if  $opt_{proof} = T$  then
18:       $\pi_{nonDomVar}(v) \leftarrow \mathbf{0}^V$   $\triangleright$  disables all variables
19:    end if
20:  end if
21:  mutex.Release()  $\triangleright$  releases the mutex
22: end procedure

```

Algorithm 6 Our DB Parallel Backtracking Lower Bound (DB-PB-LB) algorithm, which searches for a tight lower bound by iteratively solving the problem instance from the trivial lower bound (2.6) up to the optimal.

Input: The global data structures detailed in Table 1 and initialized by Algorithm 1.

Output: A tighter lower bound value \underline{L} , the optimal solution x_{inc} , and optimality proof opt_{proof} , if found.

```

1: function DBPBBSOLVELOWERBOUND
2:    $opt_{proof} \leftarrow F$  ▷ initialization of optimality proof (global variable)
3:    $x_{inc} \leftarrow \emptyset$  ▷ initialization of incumbent (global variable)
4:    $L_{inc} \leftarrow \infty$  ▷ initialization of incumbent objective value (global variable)
5:    $\underline{L} \leftarrow \underline{L}_{trivial}$  ▷ Initialization to the trivial LB value in equation (2.6)
6:    $mutex \leftarrow \text{new Mutex}()$  ▷ initialization of the global mutex object
7:    $p_{root} \in [N] \leftarrow \pi_{inst}(1)$  ▷ gets the index of the root piece instance  $P_i \in (P)$  at decision level 1
8:    $t_{root} \in C \leftarrow \pi_{type}(p_{root})$  ▷ gets the piece type for the root piece instance
9:   while  $opt_{proof} = F$  do
10:    for  $\forall v \in V$  do ▷ enables only the non-dominated decision variables
11:      if  $L_t^V(v) \leq \underline{L}$  then
12:         $\pi_{nonDomVar}(v) \leftarrow T$ 
13:      else
14:         $\pi_{nonDomVar}(v) \leftarrow F$ 
15:      end if
16:    end for
17:     $V_{root} \leftarrow \{v \in V : \pi_{idVar}(t_{root}, 0) \leq v < \pi_{idVar}(t_{root}, 1)\}$  ▷ gets all root decision variables
18:     $V_{root} \leftarrow \text{randSort}(V_{root})$  ▷ random sorting of the root-level decision variable indexes
19:    for parallel  $\forall v \in V_{root}$  do ▷ parallel solution space exploration from the root
20:      if  $\pi_{nonDomVar}(v)$  then ▷ prunes the dominated variables with  $L_t^V(v) \geq L_{inc}$ 
21:         $x \leftarrow \emptyset$  ▷ initializes an empty stack to store the variable indexes in the solution
22:         $x \leftarrow x \cup v$  ▷ start a new partial solution at the root decision level (push)
23:         $\phi_1 \leftarrow \pi_{nonDomVar} \ \& \ \Pi_{\bar{G}}(v)$  ▷ propagates all constraints induced by the variable  $v$ 
24:        if  $|x| < N$  then
25:          if  $\text{ForwardChecking}(\phi_1, 1)$  then ▷ pruning by detecting any future dead end
26:             $\text{BranchAndBoundAndPrune}(1, \phi_1, x, L_t^V(v), \pi_{inst})$  ▷ next decision level
27:          end if
28:        else
29:           $\text{UpdateIncumbent}(x, L_t^V(v))$  ▷ thread-safe update incumbent
30:        end if
31:         $x \leftarrow x \setminus v$  ▷ removes the latest tested variable index  $v$  (pop)
32:        if  $(\text{currentTime} > \text{timeLimit})$  or  $(opt_{proof} = T)$  then
33:          break
34:        end if
35:      end if
36:    end for
37:    if  $opt_{proof} = F$  then ▷ test the infeasibility of current lower bound  $\underline{L}$ 
38:       $\underline{L} \leftarrow \arg \min_{\lambda} \{\lambda \in (\mathcal{L}^+, \leq_{\mathbb{R}}) : \lambda > \underline{L}\}$  ▷ raises the lower bound to the next feasible value
39:    end if
40:  end while
41:  return  $\{\underline{L}, x_{inc}, opt_{proof}\}$ 
42: end function

```

Incumbent update. Algorithm 5 details the thread-safe function responsible of updating the incumbent values in steps 12 to 13 and of disabling all dominated variables in step 6, as well as the masks of decision variables for each piece type in step 10. Finally, this latter function checks the optimality of the new incumbent in step 15 and disables all variables whenever the optimal solution has been found, which produces the automatic suspension of all backtracking loops in all threads. We use a mutually-exclusive (mutex) object to update the incumbent values and feasibility state of all decision variables in a thread-safe manner. The *UpdateIncumbent* is the only synchronization point among threads to avoid costly interruptions.

5. The new lower bound algorithm for nesting

Algorithm 6 details our DB-PB-LB lower bound algorithm, which is based on using our base DB-PB algorithm introduced in Section 4 to solve any problem instance by setting \bar{L} to the trivial lower bound to disable all dominated variables and iteratively increasing the lower bound up to find the optimal solution or reaching the time limit. Algorithm 6 iteratively fixes the length lower and upper bounds of our DB-PB data structures to each feasible length bound in the ordered set $(\mathcal{L}^+ \cup \underline{L}, \leq_{\mathbb{R}})$, starting with the trivial lower bound \underline{L} in formula (2.6). Then, DB-PB-LB disables all dominated variables $v \in V$, such that $L_i^V(v) > \underline{L}$, as done in steps 9 to 13. Next, it searches for any feasible solution in one iteration of the main loop detailed in steps 8 to 37. If any feasible is found, then it is optimal, otherwise DB-PB-LB proves the infeasibility for the current length lower bound, and thus, \underline{L} can be increased to the next feasible length upper bound in $\mathcal{L}_m \in \mathcal{L}^+$ for the next iteration, as done in step 35. In short, DB-PB-LB uses our basic DB-PB algorithm to solve one problem instance from the trivial lower bound (2.6) up to the optimal.

6. Evaluation

The goals of the experiments in this section are as follows: (1) to evaluate the performance of our new exact DB-PB algorithm; (2) to test our main hypothesis, claiming that an ad-hoc exact algorithm requiring no preprocessing might be a better option to solve the DB model than the costly general-purpose Branch-and-Cut or hybrid CP-SAT methods by comparing our new DB-PB algorithm with our replication of the DB-CC model [105] and our new reformulation 0-1 DB-CC with the state-of-the-art Gurobi and Google CPSat solvers; (3) to evaluate the performance of our new 0-1 ILP reformulation of the family of DB models [117, 105]; (4) to carry out a fair comparison of the performance of our new exact methods with current state-of-the-art exact methods for discrete nesting by implementing them into the same hardware and software platform; (5) to replicate the DB-CC model [105] from scratch; (6) to develop a reproducible benchmark of state-of-the-art exact methods for the discrete besting problem based on our software implementation of all models and exact algorithms evaluated herein into the same software library, which is provided as supplementary material (see Appendix B); (7) the independent replication and confirmation of previous findings and results reported in [105]; and finally, (8) to elucidate the current state of the art of the problem in a sound and reproducible way.

6.1. Experimental setup

We exactly replicate the same experiments carried out by Rodrigues et al. [104, Table 1] to evaluate all mathematical programming models and exact algorithms detailed in Table 2 in the same set of eighty-one instances proposed by the former authors. Table 2 lists the state-of-the-art integer programming models and exact algorithms for the discrete nesting problem evaluated herein and the details of our software implementation. We use the same iterative LB values for the length of the problem instances that were generated by the lower-bound algorithm of Rodrigues and Toledo [105, Algorithm 1] and used in their experiments, as reported in [104, Table 2], whilst the length upper bounds defined by the length of the board for each problem instance in Table 3 were also obtained by Rodrigues et al. [104] with a heuristics.

Table 2

Implementation details for all mathematical programming models and algorithms evaluated herein. All models are built by ordering the pieces by non-increasing area to build the models.

Method	Reference	Implementation details
DB-CC	Rodrigues and Toledo [105]	Exact replication of the Dotted-Board Clique Covering model [32] as detailed in Section 2.2, which is solved by Gurobi 11.0.3 with default parameters.
0-1 DB-CC	this work	Our reformulation of the DB-CC model [105] called 0-1 DB-CC, which is introduced in Section 3.2 and solved by Google CPSat 9.11.4210 with default parameters.
DB-PB	this work	Exact Dotted-Board Parallel Backtracking (DP-PB) algorithm introduced in Section 4, which is implemented in C# language and .NET 8 platform.
DB-CC-LB	Rodrigues and Toledo [105]	Lower bound algorithm proposed by Rodrigues and Toledo [105, Algorithm 1] as a by-product of their DB-CC model whose results are copied for comparison herein.
DB-PB-LB	this work	New lower-bound algorithm for the discrete nesting problem introduced in Section 5, which is implemented in C# language and .NET 8 platform.

All our experiments are based on our software implementation of all mathematical programming models and exact algorithms evaluated herein in the same software and hardware Windows 10 Pro platform. Thus, all our results can be directly compared in a fair and unbiased way. Our software is coded in C# programming language and .NET 8 platform on Windows 10. However, it is written in portable C# .NET 8 platform, which might be used in Windows or UBUNTU platforms. The DB-CC problem instances of Rodrigues and Toledo [105] are solved with Gurobi 11.0.3, whilst the problem instances of our new 0-1 DB-CC model are solved with Google CPSat 9.11.4210. Google CPSat [97] is a state-of-the-art lazy-clause generation hybrid CP solver [69] based on combining four solving strategies as follows: a traditional Branch-and-Cut MIP solver, a Constraint Programming (CP) solver on top of an incremental SAT engine, and a Large Neighbourhood Search (LNS) metaheuristics based on RINS [36]. There are many works reporting competitive or outperforming results of CP formulations regarding their equivalent state-of-the-art MILP formulations in scheduling problems [121, 81, 89], resource availability [68], and guillotine rectangular cutting [99]. For instance, Polyakovskiy and Stuckey [99] introduce a CP formulation for a guillotine rectangular cutting problem that outperforms state-of-the-art MILP formulations solved with Gurobi when it is solved with Google CPSat. For these reasons, we argue that the comparison of our new ad-hoc DB-PB exact algorithm with the state-of-the-art MILP models for discrete nesting solved with Gurobi and Google CPSat is a sound way of testing our main hypothesis.

Our source code and a pre-compiled version of our software are publicly available in our reproducibility dataset [71]. We have replicated the state-of-the-art DB-CC model [105] from scratch by integrating all required steps to evaluate all problem instances as follows: (1) preprocessing to decompose the pieces into convex parts based on the CGAL implementation of the Greene's algorithm [58] to compute subsequently the no-fit polygons between the convex parts of pieces; (2) computation of the vertex clique covering of every problem instance using our own software implementation of the RLF algorithm [74], as proposed in [105]; (3) computation of the edge clique covering of every problem instance using the ECC8 software library of Conte et al. [33] instead of the MAX1_EK algorithm of Rodrigues [103] proposed in [105], because no software implementation of MAX1_EK is available; (4) in-memory building of the DB-CC and 0-1 DB-CC models by calling the C# API of Gurobi 11.0.3 and Google CPSat 9.11.4210, respectively; and (5) resolution of the optimization models by calling the proper solver's functions with its default parameters. All our experiments were implemented on a Windows 10 Pro laptop computer with an Intel Core i7-10510U

CPU@1.8GHz and 48 GB of RAM, which is a modest performance CPU with 4 cores (up to 8 parallel threads) that is 19% slower¹ than the Intel Core i7-2600 CPU@3.4 GHz used by Rodrigues and Toledo [105] in their experiments. Thus, any performance improvement in our experiments replicating the DB-CC [105] model regarding the results reported by Rodrigues and Toledo [105, Table 4] can be only attributed to the technological advances in Gurobi 11.0.3.

6.2. Reproducing our benchmarks

All our experiments were generated by running the *DBLNSNestingApp* program distributed with our DBLNSNesting VIR1 software library [71] with four reproducible benchmark files in XML file format that include all problem instances and methods evaluated herein. All problem instances are defined in ESICUP XML file format and provided with our raw output data in our reproducibility dataset [71]. The evaluation of every exact method in Table 2 generates a Scalable Vector Graphics (SVG) file and another LaTeX TikZ picture text file providing an image of the solution, and a raw output file in (*.csv) file format reporting the following data for each problem instance: (1) name of the problem instance; (2) number of pieces; (3) nesting efficiency; (4-5) lower and upper bounds of the solution; (6) solution gap; (7) number of binary variables; (8) number of B&B, CP, or backtracking nodes; (9) running time in seconds; (10) the number of constraints; (11) time in seconds to get the best solution (only for DB-PB method); (12) backtracking node where the best solution was found; and (13) building time of the model in seconds. All the data reported here is automatically generated by running the *benchmark_report* R-language script file on the collection of raw output files. Finally, all our methods, experiments, and results can be exactly reproduced by following the instructions detailed in Appendix B, which also explains how to evaluate the exact methods models detailed in Table 2 in other problem instances provided in the ESICUP XML file format. The aim of our reproducibility resources is not only to allow our results to be easily reproduced, but also to evaluate unseen instances provided in the ESICUP XML file format. Likewise, to allow the direct evaluation of all problem instances with the command-line tools provided by Gurobi, Google CPSat, or other MIP solvers without using our software, our reproducibility dataset [71] provides the DB-CC [105] and 0-1 DB-CC models generated for all problem instances in the LP and MPS file formats by Gurobi, and all the corresponding CPSat models in *.txt file format generated for the 0-1 DB-CC problem instances.

6.3. Evaluation metrics

To evaluate the performance of the exact mathematical programming models and algorithms detailed in table 2, we compare the Upper Bound (UB), Lower Bound (LB), terminating gap in %, as well as the building time of the model, resolution time, and total time in seconds obtained by each exact method in the evaluation of all problem instances. To provide a fair and unbiased comparison of the performance of all exact methods evaluated here, we adopt the same approach proposed by Cherri et al. [32] and Lastra-Díaz and Ortuño [70], which uses performance profiles [40] based on the ratios between the computation time of each method and the best computation time obtained by any method as a performance metric. Let Φ and M be the sets of problem instances and exact methods evaluated in this study, respectively. Then the ratio of computation times $t_{\phi,m}$ for each exact method $m \in M$ is defined by $r_{\phi,m}$ in formula (6.1), considering that the computation time is infinite whenever the methods are unable to solve the problem instance up to optimality. We assume an arbitrary parameter $r_M \geq r_{\phi,m} \forall (\phi, m) \in \Phi \times M$, such that $r_{\phi,m} = r_M$ if and only if the method m is unable to solve the problem ϕ . Dolan and Moré [40] define a *performance profile* of a solver or optimization model as the Cumulative Distribution Function (CDF) of the computation time ratios $r_{\phi,m}$, denoted by $\rho_m(\tau)$, and defined in formula (6.2) below. The performance profiles defined by the $\rho_m(\tau)$ function set a well-founded and broadly adopted metric to compare exact optimization methods by avoiding any bias derived from a particular set of problem instances and dealing with those cases in which

¹<https://cpu.userbenchmark.com/Compare/Intel-Core-i7-2600-vs-Intel-Core-i7-10510U/620vsm891469>

A parallel branch-and-bound-and-prune algorithm for irregular strip packing with discrete rotations the methods are unable to solve the problem up to optimality.

$$r_{\phi,m} = \frac{t_{\phi,m}}{\min\{t_{\phi,i} : i \in M\}}, \quad \forall(\phi, m) \in \Phi \times M \quad (6.1)$$

$$\rho_m(\tau) = \frac{1}{n_\phi} \{\phi \in \Phi : r_{\phi,m} \leq \tau\}, \quad \forall(m, \tau) \in M \times [1, r_M] \quad (6.2)$$

6.4. Results obtained

Table 3 details the features of the eighty-one problem instances used for comparing all exact methods evaluated herein, which exactly correspond to the set of problem instances proposed by Rodrigues and Toledo [105, Table 1] for the evaluation of their DB-CC model. Table 4 compares the results of the iterative LB algorithm of Rodrigues and Toledo [105, Table 2] with our new DB-PB-LB lower bound algorithm in raising the trivial LB (2.6) of the problem. The results reported in Table 4 for the iterative LB algorithm were copied from [105, Table 2], whilst our new DB-PB-LB algorithm was evaluated herein with a time limit of 600 seconds. The column named *Optimality proof* in Table 4 indicates when our DB-PB-LB algorithm found the optimal solution. Figure 2 compares the optimal solution obtained by our DB-PB algorithm for the same problem instance, either without considering rotations or considering two discrete rotations for two distinct pieces, to show the correctness of the new mathematical models and algorithms considering rotations.




Figure 2: Two solutions obtained by DB-PB for the same problem instance without rotations and with them.

Table 5 reports the Upper Bound (UB), Lower Bound (LB), and terminating gap in %, as well as the preprocessing time, resolution time, and total running time in seconds obtained by the DB-CC [105] model solved with Gurobi and our new exact DB-PB algorithm in the evaluation of all problem instances detailed in Table 3 with a Time Limit (TL) of 1 hour, whilst Table 6 reports the results comparing our new 0-1 DB-CC model solved with Google CP Sat with our new exact DB-PB algorithm. The preprocessing times include the running times to compute the vertex and edge clique coverings, and the time to build the models in memory before solving them. The best total solution times or UB values are shown in bold red, whilst the 'X' symbol in Tables 5 and 6 denotes that no feasible solution was found. The problem instances solved up to optimality within 1 hour for the first time in the literature are marked with an asterisk (*).

Figures 3a and 3b show the performance profile curves comparing the performance ratio (6.2) for resolution time and total time obtained by all methods in the evaluation of all problem instances. Table 7 reports the number of binary variables and constraints required by each mathematical programming model and our exact algorithm for solving all problem instances. Figure 4 shows the optimal solutions for seventeen open problem instances solved up to optimality within one hour for the first time in the literature. Figure 5 shows the new best solutions obtained within one hour for ten open problem instances by reducing the current upper bounds reported in [105]. Fifty-six problem instances are solved up to optimality within one hour.

Table 3

Features of the problem instances.

Instance	Pieces		Board	
	Total	Types	Width	Length
three	3	3	7	7
threep2	6	3	7	11
threep2w9	6	3	9	9
threep3	9	3	7	16
threep3w9	9	3	9	13
shapes4	4	4	13	24
shapes8	8	4	20	28
SHAPES-2	8	4	40	16
SHAPES-4	16	4	40	28
SHAPES-5	20	4	40	35
SHAPES-7	28	4	40	48
SHAPES-9	34	4	40	54
SHAPES-15	43	4	40	67
blasz2	20	4	15	27
BLAZEWCZ1	7	7	15	8
BLAZEWCZ2	14	7	15	16
BLAZEWCZ3	21	7	15	22
BLAZEWCZ4	28	7	15	29
BLAZEWCZ5	35	7	15	36
RCO1	7	7	15	8
RCO2	14	7	15	17
RCO3	21	7	15	25
RCO4	28	7	15	29
RCO5	35	7	15	41
artif1_2	13	8	27	8
artif2_4	26	8	27	14
artif3_6	39	8	27	20
artif4_8	52	8	27	28
artif5_10	65	8	27	34
artif6_12	78	8	27	41
artif7_14	91	8	27	48
artif	99	8	27	53
shirts1_2	13	8	40	13
shirts2_4	26	8	40	20
shirts3_6	39	8	40	26
shirts4_8	52	8	40	35
shirts5_10	65	8	40	42
dagli1	10	10	60	25
fu5	5	4	38	18
fu6	6	5	38	24
fu7	7	6	38	24
fu8	8	7	38	24
fu9	9	8	38	29
fu10	10	9	38	34
fu	12	11	38	38
J1-10-10-0	10	9	10	20
J1-10-10-1	10	10	10	19
J1-10-10-2	10	9	10	21
J1-10-10-3	10	10	10	23
J1-10-10-4	10	10	10	15
J1-12-20-0	12	11	20	12
J1-12-20-1	12	11	20	11
J1-12-20-2	12	12	20	14
J1-12-20-3	12	12	20	10
J1-12-20-4	12	12	20	16
J1-14-20-0	14	13	20	14
J1-14-20-1	14	13	20	14
J1-14-20-2	14	14	20	16
J1-14-20-3	14	13	20	12
J1-14-20-4	14	13	20	16
J2-10-35-0	10	9	35	28
J2-10-35-1	10	9	35	28
J2-10-35-2	10	10	35	27
J2-10-35-3	10	9	35	25
J2-10-35-4	10	10	35	22
J2-12-35-0	12	11	35	31
J2-12-35-1	12	11	35	29
J2-12-35-2	12	10	35	30
J2-12-35-3	12	11	35	25
J2-12-35-4	12	11	35	29
J2-14-35-0	14	13	35	34
J2-14-35-1	14	13	35	33
J2-14-35-2	14	11	35	33
J2-14-35-3	14	13	35	29
J2-14-35-4	14	13	35	31
Poly1a	15	15	40	18
Poly1b	15	15	40	21
Poly1c	15	15	40	14
Poly1d	15	15	40	14
Poly1e	15	15	40	13
Jakobs1	25	22	40	13

Table 4

Comparison of the iterative and DB-PB-LB lower bound algorithms.

Tightest or optimal-proven* LB values and solutions are shown in red.

Instance	Trivial LB	Iterative lower bound [105]		DB-PB-LB (this work)			
		LB	Impr.(%)	Time (secs)	LB	Impr. (%)	Time (secs)
three	4	6	50.00	0.00	6*	50.00	0.01
threep2	7	10	42.86	0.00	10*	42.86	0.00
threep2w9	6	8	33.33	0.01	8*	33.33	0.00
threep3	10	14	40.00	0.01	14*	40.00	0.05
threep3w9	8	11	37.50	0.01	12*	50.00	0.11
Shapes4	14	23	64.29	0.16	24*	71.43	0.00
Shapes8	16	23	43.75	7.57	26*	62.50	2.24
SHAPES-2	14	14	0.00	0.08	14*	0.00	0.00
SHAPES-4	16	21	31.25	127.73	19	18.75	600.00
SHAPES-5	20	25	25.00	28.49	22	10.00	600.00
SHAPES-7	28	34	21.43	108.49	28	0.00	600.00
SHAPES-9	33	38	15.15	133.25	33	0.00	600.00
SHAPES-15	40	47	17.50	281.59	40	0.00	600.00
Blasz2	19	24	26.32	1.00	19	0.00	600.00
BLAZEWCZ1	6	8	33.33	0.07	8*	33.33	0.01
BLAZEWCZ2	11	13	18.18	1.46	14*	27.27	15.65
BLAZEWCZ3	17	19	11.76	5.69	17	0.00	600.00
BLAZEWCZ4	22	25	13.64	18.41	22	0.00	600.00
BLAZEWCZ5	27	31	14.81	48.46	27	0.00	600.00
RCO1	7	8	14.29	0.02	8*	14.29	0.00
RCO2	13	14	7.69	0.33	15*	15.38	35.35
RCO3	19	21	10.53	1.72	19	0.00	600.00
RCO4	26	27	3.85	2.26	26	0.00	600.00
RCO5	32	34	6.25	0.97	32	0.00	600.00
artif1_2	7	7	0.00	0.02	7*	0.00	0.00
artif2_4	10	12	20.00	9.57	12	20.00	600.00
artif3_6	14	17	21.43	6.35	14	0.00	600.00
artif4_8	19	22	15.79	14.74	19	0.00	600.00
artif5_10	23	27	17.39	25.49	23	0.00	600.00
artif6_12	28	33	17.86	41.78	28	0.00	600.00
artif7_14	33	38	15.15	65.05	33	0.00	600.00
artif	36	41	13.89	96.36	36	0.00	600.00
shirts1_2	13	13	0.00	0.01	13*	0.00	0.00
shirts2_4	14	17	21.43	3.50	17*	21.43	5.01
shirts3_6	21	24	14.29	14.47	24	14.29	600.00
shirts4_8	28	31	10.71	58.80	28	0.00	600.00
shirts5_10	35	37	5.71	80.54	35	0.00	600.00
Dagli1	23	23	0.00	32.07	23*	0.00	0.00
fu5	14	18	28.57	0.04	18*	28.57	0.03
fu6	17	23	35.29	3.80	23*	35.29	0.11
fu7	19	24	26.32	4.90	24*	26.32	0.22
fu8	20	24	20.00	15.90	24*	20.00	0.19
fu9	23	24	4.35	10.16	25*	8.70	2.54
fu10	26	28	7.69	21.58	29*	11.54	357.37
fu	29	31	6.90	182.71	30	3.45	600.00
J1-10-10-0	16	18	12.50	0.27	18*	12.50	0.00
J1-10-10-1	16	16	0.00	0.14	17*	6.25	0.00
J1-10-10-2	18	19	5.56	0.16	20*	11.11	0.01
J1-10-10-3	18	20	11.11	0.82	21*	16.67	0.07
J1-10-10-4	11	12	9.09	0.08	13*	18.18	0.01
J1-12-20-0	10	11	10.00	0.53	12*	20.00	0.00
J1-12-20-1	9	10	11.11	0.53	10*	11.11	0.01
J1-12-20-2	11	12	9.09	0.72	12*	9.09	0.01
J1-12-20-3	7	8	14.29	0.34	8*	14.29	0.01
J1-12-20-4	12	12	0.00	0.47	13*	8.33	0.12
J1-14-20-0	11	12	9.09	1.00	12*	9.09	0.03
J1-14-20-1	11	11	0.00	0.21	12*	9.09	0.79
J1-14-20-2	13	13	0.00	0.65	14*	7.69	2.17
J1-14-20-3	9	10	11.11	0.48	10*	11.11	0.02
J1-14-20-4	12	13	8.33	5.66	14*	16.67	0.26
J2-10-35-0	19	22	15.79	102.08	24*	26.32	10.28
J2-10-35-1	16	22	37.50	107.56	24*	50.00	19.90
J2-10-35-2	17	21	23.53	76.72	23*	35.29	3.77
J2-10-35-3	16	18	12.50	29.21	20*	25.00	2.49
J2-10-35-4	14	17	21.43	34.77	19*	35.71	1.15
J2-12-35-0	22	25	13.64	249.24	29*	31.82	542.15
J2-12-35-1	18	23	27.78	179.60	25*	38.89	243.83
J2-12-35-2	18	21	16.67	148.62	24*	33.33	245.41
J2-12-35-3	16	19	18.75	75.31	21*	31.25	191.36
J2-12-35-4	20	24	20.00	114.18	26*	30.00	351.03
J2-14-35-0	24	26	8.33	254.99	28	16.67	600.00
J2-14-35-1	22	25	13.64	238.19	26	18.18	600.00
J2-14-35-2	21	23	9.52	145.02	24	14.29	600.00
J2-14-35-3	21	22	4.76	112.94	24	14.29	600.00
J2-14-35-4	21	24	14.29	191.63	25	19.05	600.00
Poly1a	13	14	7.69	24.36	15	15.38	600.00
Poly1b	13	16	23.08	71.23	18*	38.46	125.82
Poly1c	13	13	0.00	2.72	13*	0.00	0.00
Poly1d	11	11	0.00	3.93	12*	9.09	29.28
Poly1e	10	11	10.00	5.09	12*	20.00	452.47
Jakobs1	10	11	10.00	2.36	10	0.00	600.00
# Improvements			71			57	
# Optimal			0			51	
# Best LB/ties			24			59	

7. Discussion

7.1. Comparison of lower bound algorithms

Our new DB-PB-LB lower algorithm finds the optimal solutions in 51 of 81 problem instances, and obtains the best LB value for 59 of them, as shown in Table 4, whilst the iterative LB algorithm of Rodrigues et al. [104] only obtains the best LB values 24 times. However, the iterative LB algorithm improves the trivial LB (2.6) value for 71 instances, whilst DB-PB-LB can only do it for 57 problem instances, respectively.

Our new DB-PB-LB algorithm solves 51 problem instances up to optimality within 10 minutes, whilst the DB-CC model [105] only solves 47 ones within 1 hour, as drawn from the results shown in Tables 4 and 5. Thus, our new lower bound algorithm outperforms both the iterative LB algorithm and the DB-CC model of Rodrigues and Toledo [105] in obtaining tighter LB values and solving problem instances.

7.2. Comparison of the exact methods

Our new exact DP-PB algorithm significantly outperforms the DB-CC and 0-1 DB-CC models in solving faster 53 and 55 problem instances, respectively, as shown in Tables 5 and 6. Among the instances solved up to optimality, the DB-CC [105] model and our 0-1 DB-CC reformulation only outperform DB-PB in 6 and 1 problem instances, respectively. In addition, the performance profiles shown in Figures 3a and 3b show that our DB-PB algorithm outperforms the two former ILP models by two orders of magnitude in most of the problem instances, even if the preprocessing is not considered.

Our new exact DP-PB algorithm solves nine problem instances up to optimality more than the DB-CC model and fourteen instances more than our 0-1 DB-CC reformulation, as shown in Tables 5 and 6, respectively. However, our DB-PB algorithm cannot solve up to optimality four problem instances solved by the DB-CC [105] model, among which we have *Blasz2*, *BLAZEWICZ3*, *RCO3*, and *shirt3_6*. Likewise, the DB-CC [105] model obtains tighter upper bounds than our DB-PB algorithm in most of the unsolved problem instances and two more feasible solutions, as shown in Table 5. On the other hand, our 0-1 DB-CC reformulation can find feasible solutions for all problem instances, as shown in Table 6. We attribute the outperformance of the DB-CC and 0-1 DB-CC models in obtaining tighter upper bounds than DB-PB among the unsolved problem instances to the set of feasibility pump and primal heuristics implemented by Gurobi and Google CPSat, as well as the lack of these type of primal heuristics in our new DB-PB algorithm, which we plan to tackle as forthcoming work.

Our new exact DB-PB algorithm finds the optimal solution for seventeen open instances, whilst DB-CC only solves four of them, as shown in Figure 4. However, the new open instances solved by the DB-CC model in comparison with the results reported in its introductory paper [105, Table 4] can only be attributed to the technological advances in Gurobi, as mentioned in Section 6.1.

The DB-CC model solves five problem instances more than our new 0-1 DB-CC reformulation, and DB-CC is slightly faster than the last one, as shown in Tables 5 and 6, and the performance profile shown in Figure 3b. However, we cannot discard the potential performance gain of Gurobi regarding Google CPSat in solving the two former models, respectively. Anyway, the main aim of evaluating our new 0-1 DB-CC reformulation was not to introduce a tighter formulation of the DB-CC model [105] else to test our main hypothesis concerning the option of efficiently solving the DB model [117] with an ad-hoc exact algorithm instead of using traditional Branch-and-Cut and Constraint Programming frameworks.

Our experimental results positively confirm our main hypothesis claiming that the preprocessing time required by the DB-CC is unnecessary and counterproductive, and that an ad-hoc exact algorithm might be a better option to solve the discrete nesting problem in comparison with costly general-purpose Branch-and-Cut and CP-SAT methods.

The DB-CC model and our DB-PB algorithm share exactly the same number of binary of variables in all problem instances, but both significantly differ in the number of constraints, as shown in Table 7. As expected, the clique covering formulation of Rodrigues and Toledo [105] significantly reduces the number




Figure 3: Performance profiles [40] showing the Cumulative Distribution Function (CDF) for the performance ratio $r_{\phi,m}$ comparing the performance of all exact DB methods in the evaluation of all problem instances.

of constraints required to solve the original DB model [117]. However, the results for our exact DB-PB algorithm shown in Tables 5 and 6, and Figures 3b and 3b, positively confirm our main hypothesis claiming that the preprocessing time required by the DB-CC model [105] is unnecessary and counterproductive.

Our 0-1 DB-CC model requires a lower number of constraints than DB-CC in all problem instances, excepting shirts1_2, fu5, and RCO1, as detailed in Table 7. We attribute this reduction in the number of constraints to the new Constraints (3.14) that substitute the vertex clique Constraints (2.17) of the DB-CC model. On the other hand, Table 7 shows that our new 0-1 DB-CC requires a few more binary variables than DB-CC to define the variables z_m used to represent the set of feasible length upper bounds \mathcal{L}^+ .

Our replication of the DB-CC mode [105] allows us to confirm independently the results reported by Rodrigues and Toledo [105] and to draw some conclusions on the impact of the technological advances of MIP solvers. The DB-CC model implemented with Gurobi 11.0.3 herein solves two instances more within one hour than the same model in its introductory paper [105] and also finds two feasible solutions more, as shown in Table 5. Likewise, it also improves eight upper bounds among the unsolved problem instances, as shown in Figure 5. However, these improvements can only be attributed to the technological advances of Gurobi 11.0.3 compared to CPLEX 12.6 [105], as mentioned in Section 6.1. On the other hand, our DB-CC replication could not find a feasible solution for SHAPES-9 problem instance as done in [105, Table 4],

7.3. The new state of the art

Our new Dotted-Board Parallel Backtracking (DB-PB) algorithm sets the new state of the art among the family of exact methods for the discrete nesting problem, as shown in Tables 5 and 6, and Figures 3b and 3b. However, our DB-PB algorithm lacks of a feasibility pump and primal heuristics that help it to get better feasible solutions on those cases in which it cannot solve the problem instances up to optimality, as shown in Tables 5 and 6.

Table 5

Comparison of DB-CC model [105] solved with Gurobi and our DB-PB algorithm with TL = 3600 seconds.

Instance	Dotted-Board Clique Covering (DB-CC) model [105]						Dotted-Board Parallel-Backtracking (DB-PB) method (this work)					
	UB	LB	Gap (%)	Prep (secs)	Solve (secs)	Total (secs)	UB	LB	Gap	Prep (secs)	Solve (secs)	Total (secs)
three	6	6	0	0.598	0.019	0.617	6	6	0	0.027	0.006	0.033
threep2	10	10	0	0.77	0.021	0.791	10	10	0	0.003	0	0.003
threep2w9	8	8	0	0.767	0.019	0.786	8	8	0	0.004	0	0.004
threep3	14	14	0	0.829	0.036	0.865	14	14	0	0.005	0.004	0.009
threep3w9	12	12	0	0.919	0.097	1.016	12	12	0	0.006	0.108	0.114
Shapes4	24	24	0	1.889	0.067	1.956	24	24	0	0.031	0	0.031
Shapes8	26	26	0	4.812	7.188	12	26	26	0	0.085	1.31	1.395
SHAPES-2	14	14	0	3.161	0.913	4.074	14	14	0	0.101	0.001	0.102
SHAPES-4	25	23	8	17.47	TL	TL	28	21	25	0.282	TL	TL
SHAPES-5	30	28	6.67	28.71	TL	TL	35	25	28.57	0.617	TL	TL
SHAPES-7	42	35	16.67	63.56	TL	TL	X	34	X	0.819	TL	TL
SHAPES-9	X	38	X	81.24	TL	TL	X	38	X	0.914	TL	TL
SHAPES-15	X	47	X	126.3	TL	TL	X	47	X	1.08	TL	TL
Blasz2	26	26	0	3.335	35.07	38.4	27	24	11.11	0.085	TL	TL
BLAZEWICZ1	8	8	0	1.315	0.081	1.396	8	8	0	0.027	0	0.027
BLAZEWICZ2	14	14	0	3.68	14.06	17.74	14	14	0	0.045	18.75	18.8
BLAZEWICZ3	20	20	0	5.164	170.8	176	21	19	9.52	0.079	TL	TL
BLAZEWICZ4	28	26	7.14	7.317	TL	TL	29	25	13.79	0.136	TL	TL
BLAZEWICZ5	34	31	8.82	9.993	TL	TL	X	31	X	0.181	TL	TL
RCO1	8	8	0	1.477	0.075	1.552	8	8	0	0.047	0	0.047
RCO2	15	15	0	3.726	7.525	11.25	15	15	0	0.059	37.79	37.85
RCO3	22	22	0	6.01	133	139	22	21	4.55	0.062	TL	TL
RCO4	29	28	3.45	7.77	TL	TL	X	27	X	0.144	TL	TL
RCO5	36	35	2.78	11.6	TL	TL	37	34	8.11	0.372	TL	TL
artif1_2	7	7	0	2.298	0.208	2.506	7	7	0	0.068	0.003	0.071
artif2_4	13	12	7.69	7.28	TL	TL	13	12	7.69	0.17	TL	TL
artif3_6	19	17	10.53	15.43	TL	TL	20	17	15	0.214	TL	TL
artif4_8	26	22	15.38	26.64	TL	TL	26	22	15.38	0.279	TL	TL
artif5_10	33	27	18.18	38.69	TL	TL	34	27	20.59	0.333	TL	TL
artif6_12	38	33	13.16	54.8	TL	TL	41	33	19.51	0.427	TL	TL
artif7_14	46	38	17.39	76.9	TL	TL	47	38	19.15	0.486	TL	TL
artif	49	41	16.33	94.06	TL	TL	52	41	21.15	0.579	TL	TL
shirts1_2	13	13	0	4.638	0.021	4.659	13	13	0	0.095	0	0.095
shirts2_4	17	17	0	24.15	24.81	48.96	17	17	0	0.246	0.707	0.953
shirts3_6	24	24	0	55.67	1022	1078	25	24	4	0.496	TL	TL
shirts4_8	32	31	3.12	128.6	TL	TL	33	31	6.06	1.104	TL	TL
shirts5_10	41	38	7.32	205	TL	TL	42	37	11.9	1.244	TL	TL
Dagll1	23	23	0	296.3	3.647	299.9	23	23	0	1.963	0.003	1.966
fu5	18	18	0	3.146	0.139	3.285	18	18	0	0.057	0	0.057
fu6	23	23	0	14.98	0.642	15.62	23	23	0	0.158	0.007	0.165
fu7	24	24	0	25.74	0.231	25.98	24	24	0	0.266	0.016	0.282
fu8	24	24	0	40.38	1.809	42.19	24	24	0	0.44	0.035	0.475
fu9	25	25	0	120	105.5	225.5	25	25	0	1.297	4.714	6.011
fu10	29	29	0	267.1	3182	3449	29	29	0	2.013	256	258
fu	34	31	8.82	636	TL	TL	34	31	8.82	3.407	TL	TL
J1-10-10-0	18	18	0	3.408	0.681	4.089	18	18	0	0.047	0.001	0.048
J1-10-10-1	17	17	0	3.793	2.4	6.193	17	17	0	0.048	0.001	0.049
J1-10-10-2	20	20	0	3.593	2.217	5.81	20	20	0	0.045	0.001	0.046
J1-10-10-3	21	21	0	5.717	15.52	21.24	21	21	0	0.066	0.07	0.136
J1-10-10-4	13	13	0	3.332	1.46	4.792	13	13	0	0.042	0.004	0.046
J1-12-20-0	12	12	0	6.365	3.874	10.24	12	12	0	0.104	0.003	0.107
J1-12-20-1	10	10	0	4.653	3.43	8.083	10	10	0	0.074	0.008	0.082
J1-12-20-2	12	12	0	10.57	7.575	18.15	12	12	0	0.176	0.01	0.186
J1-12-20-3	8	8	0	4.191	1.131	5.322	8	8	0	0.072	0.005	0.077
J1-12-20-4	13	13	0	14.41	23.86	38.27	13	13	0	0.197	0.049	0.246
J1-14-20-0	12	12	0	12.42	24.83	37.25	12	12	0	0.187	0.03	0.217
J1-14-20-1	12	12	0	10.72	42.47	53.18	12	12	0	0.154	0.936	1.09
J1-14-20-2	14	14	0	18.75	105.4	124.2	14	14	0	0.265	2.271	2.536
J1-14-20-3	10	10	0	8.146	6.53	14.68	10	10	0	0.125	0.013	0.138
J1-14-20-4	14	14	0	15.97	61.71	77.69	14	14	0	0.215	0.319	0.534
J2-10-35-0*	24	24	0	121.6	1847	1968	24	24	0	1.499	5.572	7.071
J2-10-35-1*	24	22	8.33	126.2	TL	TL	24	24	0	1.123	18.22	19.34
J2-10-35-2*	23	23	0	139.8	3598	3738	23	23	0	1.351	3.609	4.96
J2-10-35-3*	20	20	0	97.43	192.6	290	20	20	0	1.187	0.636	1.823
J2-10-35-4*	19	19	0	87.12	1603	1691	19	19	0	1.193	1.493	2.686
J2-12-35-0*	30	26	13.33	285.7	TL	TL	29	29	0	2.304	428.3	430.6
J2-12-35-1*	26	23	11.54	228	TL	TL	25	25	0	1.822	196.7	198.6
J2-12-35-2*	24	22	8.33	202.6	TL	TL	24	24	0	1.606	205.1	206.7
J2-12-35-3*	22	20	9.09	210.3	TL	TL	21	21	0	1.217	143.5	144.8
J2-12-35-4*	26	24	7.69	239.4	TL	TL	26	26	0	1.805	279.3	281.1
J2-14-35-0*	30	26	13.33	592.1	TL	TL	30	30	0	3.242	2192	2195
J2-14-35-1	30	25	16.67	537.9	TL	TL	29	25	13.79	2.911	TL	TL
J2-14-35-2*	26	23	11.54	353.6	TL	TL	26	26	0	2.209	2354	2356
J2-14-35-3	27	22	18.52	389.1	TL	TL	26	22	15.38	2.811	TL	TL
J2-14-35-4*	27	24	11.11	578.4	TL	TL	26	26	0	4.244	1815	1820
Poly1a*	17	14	17.65	136.5	TL	TL	15	15	0	1.035	2422	2423
Poly1b*	19	16	15.79	240.8	TL	TL	18	18	0	1.985	53.9	55.88
Poly1c	13	13	0	50.21	3.793	54	13	13	0	0.405	0	0.405
Poly1d*	13	11	15.38	67.92	TL	TL	12	12	0	0.608	36.08	36.69
Poly1e*	12	11	8.33	39.58	TL	TL	12	12	0	0.351	527.9	528.2
Jakobs1	11	11	0	137.7	164.4	302	11	11	0	0.969	791.1	792.1
# Feasible	79						76					
# Optimal			47					56				
# Best total						6						53
# Best UB/ties	18						5					
Preprocessing				7518.224					58.247			

Table 6

Comparison of our 0-1 DB-CC model solved with Google CPSat and our DB-PB algorithm with TL = 3600 secs.

Instance	Binary DB Clique Covering (0-1 DB-CC) model (this work)						DB Parallel-Backtracking (DB-PB) method (this work)					
	UB	LB	Gap (%)	Prep (secs)	Solve (secs)	Total (secs)	UB	LB	Gap	Prep (secs)	Solve (secs)	Total (secs)
three	6	6	0	0.578	0.02	0.598	6	6	0	0.027	0.006	0.033
threep2	10	10	0	0.642	0.043	0.685	10	10	0	0.003	0	0.003
threep2w9	8	8	0	0.62	0.04	0.66	8	8	0	0.004	0	0.004
threep3	14	14	0	0.778	0.121	0.899	14	14	0	0.005	0.004	0.009
threep3w9	12	12	0	0.682	0.637	1.319	12	12	0	0.006	0.108	0.114
Shapes4	24	24	0	1.373	0.035	1.408	24	24	0	0.031	0	0.031
Shapes8	26	26	0	4.111	2.928	7.039	26	26	0	0.085	1.31	1.395
SHAPES-2	14	14	0	2.367	0.479	2.846	14	14	0	0.101	0.001	0.102
SHAPES-4	25	23	8	14.84	TL	TL	28	21	25	0.282	TL	TL
SHAPES-5	31	25	19.35	29.06	TL	TL	35	25	28.57	0.617	TL	TL
SHAPES-7	43	34	20.93	63.29	TL	TL	X	34	X	0.819	TL	TL
SHAPES-9	52	38	26.92	81.16	TL	TL	X	38	X	0.914	TL	TL
SHAPES-15	64	47	26.56	126.5	TL	TL	X	47	X	1.08	TL	TL
Blasz2	26	24	7.69	3.475	TL	TL	27	24	11.11	0.085	TL	TL
BLAZEWICZ1	8	8	0	1.772	0.125	1.897	8	8	0	0.027	0	0.027
BLAZEWICZ2	14	14	0	4.136	1099	1103	14	14	0	0.045	18.75	18.8
BLAZEWICZ3	21	19	9.52	6.492	TL	TL	21	19	9.52	0.079	TL	TL
BLAZEWICZ4	28	25	10.71	8.568	TL	TL	29	25	13.79	0.136	TL	TL
BLAZEWICZ5	35	31	11.43	10.56	TL	TL	X	31	X	0.181	TL	TL
RCO1	8	8	0	1.827	0.087	1.914	8	8	0	0.047	0	0.047
RCO2	15	15	0	4.473	237.4	241.9	15	15	0	0.059	37.79	37.85
RCO3	22	21	4.55	7.08	TL	TL	22	21	4.55	0.062	TL	TL
RCO4	29	27	6.9	7.23	TL	TL	X	27	X	0.144	TL	TL
RCO5	37	34	8.11	12.81	TL	TL	37	34	8.11	0.372	TL	TL
artif1_2	7	7	0	2.371	0.251	2.622	7	7	0	0.068	0.003	0.071
artif2_4	13	12	7.69	7.059	TL	TL	13	12	7.69	0.17	TL	TL
artif3_6	20	17	15	15.18	TL	TL	20	17	15	0.214	TL	TL
artif4_8	26	22	15.38	25.75	TL	TL	26	22	15.38	0.279	TL	TL
artif5_10	33	27	18.18	50.58	TL	TL	34	27	20.59	0.333	TL	TL
artif6_12	39	33	15.38	71.35	TL	TL	41	33	19.51	0.427	TL	TL
artif7_14	46	38	17.39	98.39	TL	TL	47	38	19.15	0.486	TL	TL
artif	50	41	18	111.2	TL	TL	52	41	21.15	0.579	TL	TL
shirts1_2	13	13	0	6.587	0.473	7.06	13	13	0	0.095	0	0.095
shirts2_4	17	17	0	33.8	20.16	53.96	17	17	0	0.246	0.707	0.953
shirts3_6	25	24	4	74.01	TL	TL	25	24	4	0.496	TL	TL
shirts4_8	33	31	6.06	181.1	TL	TL	33	31	6.06	1.104	TL	TL
shirts5_10	41	37	9.76	268	TL	TL	42	37	11.9	1.244	TL	TL
Dagll1	23	23	0	335.2	10.67	345.8	23	23	0	1.963	0.003	1.966
fu5	18	18	0	3.355	0.089	3.444	18	18	0	0.057	0	0.057
fu6	23	23	0	14.43	2.245	16.67	23	23	0	0.158	0.007	0.165
fu7	24	24	0	23.78	1.284	25.06	24	24	0	0.266	0.016	0.282
fu8	24	24	0	40.96	3.221	44.18	24	24	0	0.44	0.035	0.475
fu9	25	25	0	109.5	80.78	190.3	25	25	0	1.297	4.714	6.011
fu10	29	28	3.45	261.1	TL	TL	29	29	0	2.013	256	258
fu	34	31	8.82	642.9	TL	TL	34	31	8.82	3.407	TL	TL
J1-10-10-0	18	18	0	4.151	0.288	4.439	18	18	0	0.047	0.001	0.048
J1-10-10-1	17	17	0	4.009	1.072	5.081	17	17	0	0.048	0.001	0.049
J1-10-10-2	20	20	0	4.039	0.708	4.747	20	20	0	0.045	0.001	0.046
J1-10-10-3	21	21	0	5.403	10.73	16.13	21	21	0	0.066	0.07	0.136
J1-10-10-4	13	13	0	2.842	1.244	4.086	13	13	0	0.042	0.004	0.046
J1-12-20-0	12	12	0	6.789	1.642	8.431	12	12	0	0.104	0.003	0.107
J1-12-20-1	10	10	0	6.333	0.756	7.089	10	10	0	0.074	0.008	0.082
J1-12-20-2	12	12	0	11.5	0.668	12.17	12	12	0	0.176	0.01	0.186
J1-12-20-3	8	8	0	4.352	0.656	5.008	8	8	0	0.072	0.005	0.077
J1-12-20-4	13	13	0	14.8	13.57	28.36	13	13	0	0.197	0.049	0.246
J1-14-20-0	12	12	0	12.29	31.92	44.21	12	12	0	0.187	0.03	0.217
J1-14-20-1	12	12	0	11.5	182.9	194.4	12	12	0	0.154	0.936	1.09
J1-14-20-2	14	14	0	21.02	675.8	696.8	14	14	0	0.265	2.271	2.536
J1-14-20-3	10	10	0	9.891	2.554	12.44	10	10	0	0.125	0.013	0.138
J1-14-20-4	14	14	0	17.58	72.76	90.34	14	14	0	0.215	0.319	0.534
J2-10-35-0*	24	24	0	121.7	640.8	762.5	24	24	0	1.499	5.572	7.071
J2-10-35-1*	24	23	4.17	126.4	TL	TL	24	24	0	1.123	18.22	19.34
J2-10-35-2*	23	23	0	148.6	1491	1640	23	23	0	1.351	3.609	4.96
J2-10-35-3*	20	20	0	100.7	148.7	249.4	20	20	0	1.187	0.636	1.823
J2-10-35-4*	19	19	0	84.72	180.8	265.5	19	19	0	1.193	1.493	2.686
J2-12-35-0*	29	25	13.79	285.4	TL	TL	29	29	0	2.304	428.3	430.6
J2-12-35-1*	25	23	8	226.3	TL	TL	25	25	0	1.822	196.7	198.6
J2-12-35-2*	24	22	8.33	201.6	TL	TL	24	24	0	1.606	205.1	206.7
J2-12-35-3*	21	20	4.76	162.3	TL	TL	21	21	0	1.217	143.5	144.8
J2-12-35-4*	26	24	7.69	244.4	TL	TL	26	26	0	1.805	279.3	281.1
J2-14-35-0*	30	26	13.33	592.3	TL	TL	30	30	0	3.242	2192	2195
J2-14-35-1	30	25	16.67	532	TL	TL	29	25	13.79	2.911	TL	TL
J2-14-35-2*	26	23	11.54	338.9	TL	TL	26	26	0	2.209	2354	2356
J2-14-35-3	26	22	15.38	382.5	TL	TL	26	22	15.38	2.811	TL	TL
J2-14-35-4*	27	24	11.11	570.8	TL	TL	26	26	0	4.244	1815	1820
Poly1a*	16	14	12.5	192.5	TL	TL	15	15	0	1.035	2422	2423
Poly1b*	18	17	5.56	233.8	TL	TL	18	18	0	1.985	53.9	55.88
Poly1c	13	13	0	52.14	3.63	55.77	13	13	0	0.405	0	0.405
Poly1d*	12	11	8.33	66.74	TL	TL	12	12	0	0.608	36.08	36.69
Poly1e*	12	11	8.33	44.5	TL	TL	12	12	0	0.351	527.9	528.2
Jakobs1	11	11	0	140.2	134.6	274.9	11	11	0	0.969	791.1	792.1
# Feasible	81						76					
# Optimal			42					56				
# Best time						1						55
# Best UB/ties	24						11					
Preprocessing				7755.892					58.247			

Table 7

Number of binary decision variables and constraints defined by each exact model and algorithm.

Instance	Total number of binary variables per instance			Total number of constraints per instance		
	DB-CC [105]	0-1 DB-CC (this work)	DB-PB (this work)	DB-CC [105]	0-1 DB-CC (this work)	DB-PB (this work)
three	61	62	61	42	34	1266
threep2	117	118	117	98	75	3006
threep2w9	127	128	127	96	84	3394
threep3	187	189	187	151	139	5181
threep3w9	207	209	207	178	166	6150
Shapes4	389	390	389	326	323	46060
Shapes8	1008	1013	1008	1104	1062	201702
SHAPES-2	848	850	848	960	906	92766
SHAPES-4	2468	2475	2468	3137	3006	604259
SHAPES-5	3413	3423	3413	4455	4253	939916
SHAPES-7	5168	5182	5168	6740	6456	1563279
SHAPES-9	5978	5994	5978	7719	7634	1850985
SHAPES-15	7733	7753	7733	9944	9821	2474348
Blasz2	1080	1083	1080	876	854	91670
BLAZEWCZ1	432	432	432	280	276	35462
BLAZEWCZ2	1096	1099	1096	854	761	120814
BLAZEWCZ3	1594	1597	1594	1199	1137	184828
BLAZEWCZ4	2175	2179	2175	1673	1589	259511
BLAZEWCZ5	2756	2761	2756	2079	2040	334194
RCO1	432	432	432	199	202	36049
RCO2	1179	1182	1179	679	609	133924
RCO3	1843	1847	1843	1054	973	220924
RCO4	2175	2177	2175	1185	1124	264424
RCO5	3171	3178	3171	1784	1714	394924
artif1_2	947	948	947	604	584	68540
artif2_4	2099	2101	2099	1687	1585	250220
artif3_6	3251	3254	3251	2767	2675	437228
artif4_8	4787	4793	4787	4205	4129	686572
artif5_10	5939	5946	5939	5289	5274	873580
artif6_12	7283	7291	7283	6538	6444	1091756
artif7_14	8627	8637	8627	7767	7609	1309932
artif	9587	9599	9587	8676	8552	1465772
shirts1_2	1924	1924	1924	603	609	147101
shirts2_4	4010	4013	4010	1910	1822	736227
shirts3_6	5798	5800	5798	3121	3041	1364984
shirts4_8	8480	8484	8480	5085	4957	2319578
shirts5_10	10566	10571	10566	6563	6445	3062040
Dagli1	6911	6913	6911	5452	5211	6170439
fu5	721	721	721	226	230	120663
fu6	1722	1723	1722	762	736	734345
fu7	2172	2172	2172	849	837	1124614
fu8	2772	2772	2772	1374	1317	1616281
fu9	4202	4207	4202	2555	2210	3446231
fu10	5982	5988	5982	3440	2942	6365641
fu	8642	8649	8642	6739	6086	11355356
J1-10-10-0	1063	1065	1063	581	525	118778
J1-10-10-1	1065	1068	1065	766	680	154905
J1-10-10-2	1073	1075	1073	576	500	140430
J1-10-10-3	1284	1287	1284	702	624	232436
J1-10-10-4	896	899	896	403	340	96289
J1-12-20-0	1597	1598	1597	727	685	260436
J1-12-20-1	1377	1378	1377	752	728	207624
J1-12-20-2	2039	2041	2039	938	838	445512
J1-12-20-3	1363	1365	1363	621	554	172873
J1-12-20-4	2408	2412	2408	1186	1034	580191
J1-14-20-0	2344	2346	2344	934	863	469901
J1-14-20-1	2319	2322	2319	1227	1056	459468
J1-14-20-2	2781	2784	2781	1133	969	776783
J1-14-20-3	1979	1981	1979	651	537	348312
J1-14-20-4	2631	2634	2631	1481	1326	634924
J2-10-35-0	4486	4492	4486	4787	4353	3505202
J2-10-35-1	4572	4578	4572	4807	4416	3566129
J2-10-35-2	4892	4898	4892	4744	4225	3811214
J2-10-35-3	4328	4335	4328	3335	2930	2872285
J2-10-35-4	3992	3997	3992	3717	3353	2678511
J2-12-35-0	6240	6246	6240	5947	5416	6493492
J2-12-35-1	6100	6106	6100	6103	5653	5234224
J2-12-35-2	5852	5861	5852	5878	5366	4829349
J2-12-35-3	5420	5426	5420	4729	4291	4143829
J2-12-35-4	6256	6261	6256	4804	4376	5439275
J2-14-35-0	8718	8726	8718	8024	7353	10155708
J2-14-35-1	8620	8628	8620	7768	7140	9308609
J2-14-35-2	7484	7494	7484	6888	6247	6813466
J2-14-35-3	7552	7559	7552	6362	5687	7557702
J2-14-35-4	8056	8063	8056	6826	6202	8157073
Poly1a	5620	5624	5620	5104	4815	3283976
Poly1b	6858	6863	6858	6507	6261	4922042
Poly1c	4437	4438	4437	3356	3224	1513472
Poly1d	4527	4530	4527	3639	3412	1946264
Poly1e	3638	3640	3638	2956	2873	1301254
Jakobs1	7460	7462	7460	2472	2354	2846369

8. Conclusions and future work

We introduce a parallel exact branch-and-bound-and-prune algorithm requiring no pre-processing to solve efficiently the discrete nesting problem with rotations, together with two binary linear programming models for the same problem based on two reformulations of the family of Dotted-Board models [117, 105, 31] and a new lower bound algorithm as by-products. Finally, we introduce a detailed reproducibility protocol and dataset to allow the exact replication of all our models, experiments, and results.

We reproduce the same benchmark introduced by Rodrigues and Toledo [105] to compare the current state-of-the-art DB-CC [105] model with our 0-1 DB-CC model and our ad-hoc exact DB-PB algorithm by replicating and implementing all methods evaluated herein into the same software and hardware platform. Our experiments shows that DB-PB significantly outperforms the DB-CC and 0-1 DB-CC models both in number of problem instances solved up to optimality and solving time. Our ad-hoc exact DB-PB algorithm outperforms the current state-of-the-art DB-CC model and our new 0-1 DB-CC reformulation by two orders of magnitude in most of problem instances without requiring their costly preprocessing time to compute the edge and vertex clique coverings. Our experiments positively confirm our main hypothesis claiming that the preprocessing time required by the DB-CC is unnecessary and counterproductive, and that an ad-hoc exact algorithm might be a better option to solve the discrete nesting problem in comparison with costly state-of-the-art Branch-and-Cut, Constraint Programming, or hybrid CP-SAT approaches. Finally, our experiments show that our DP-PB-LB lower bound algorithm outperforms the iterative lower algorithm of Rodrigues and Toledo [105] by solving 51 problem instances up to optimality within 10 minutes, that means 4 problem instances more than DB-CC within 1 hour. On the other hand, the DB-CC [105] model obtains tighter upper bounds than our DB-PB algorithm in most of unsolved problem instances and two feasible solutions more, which we attribute to the set of feasibility pump and primal heuristics implemented by Gurobi and Google CPSat, as well as the lack of these in our new DB-PB algorithm. Finally, our experiments solve seventeen open problem instances within 1 hour for the first time in the literature and improve the best known upper bound for other ten instances.

As forthcoming activities, we plan to devise ad-hoc feasibility pump and primal heuristics to improve the capability of our current DB-PB algorithm of finding high-quality solutions for all problem instances, specially when they cannot be solved up to optimality within the time limits. Likewise, we plan to devise new nesting heuristics based on our DB-PB framework, which can compete with current state-of-the-art heuristics for the continuous nesting problem.

Acknowledgments

We thank Hervé Gateuil for the access to a high-performance Lectra computer to validate our algorithms.

A. Appendix A: Best solutions obtained for all problem instances

This appendix introduces the best solutions for all problem instances in our experiments.

B. Appendix B: The reproducible experiments on irregular strip-packing

This appendix introduces a detailed reproducibility protocol and dataset [71] providing our raw output data and a collection of software and data resources to allow the replication of all our experiments and results.

References

- [1] Achterberg, T., 2007. Conflict analysis in mixed integer programming. *Discrete optimization* 4, 4–20.
- [2] Achterberg, T., Wunderling, R., 2013. Mixed Integer Programming: Analyzing 12 Years of Progress, in: Jünger, M., Reinelt, G. (Eds.), *Facets of Combinatorial Optimization: Festschrift for Martin Grötschel*. Springer Berlin Heidelberg, Berlin, Heidelberg, pp. 449–481.

A parallel branch-and-bound-and-prune algorithm for irregular strip packing with discrete rotations




Figure 4: Seventeen open problem instances solved up to optimality within one hour for the first time in the literature. Rodrigues and Toledo [105] reported a wrong optimal solution for J2-10-35-3 with $L = 21$ instead of the optimal solution with $L^* = 20$ shown above, which we attribute to a minor tolerance error in their experiments. All the new optimal solutions shown above are found by our DB-PB algorithm, although the DB-CC model [113] also finds four of them. However, this latter improvement can be attributed only to the advances in Gurobi 11.0.3 compared to CPLEX 12.6 [105].

- [3] Adamowicz, M., Albano, A., 1976a. Nesting two-dimensional shapes in rectangular modules. *Comput. Aided Des. Appl.* 8, 27–33.
- [4] Adamowicz, M., Albano, A., 1976b. A solution of the rectangular Cutting-Stock problem. *IEEE Trans. Syst. Man Cybern.* SMC-6, 302–310.
- [5] Agarwal, P.K., Flato, E., Halperin, D., 2002. Polygon decomposition for efficient construction of Minkowski sums. *Computational geometry: theory and applications* 21, 39–61.
- [6] Albano, A., Sapuppo, G., 1980. Optimal allocation of Two-Dimensional irregular shapes using heuristic search methods. *Systems, Man and Cybernetics, IEEE Transactions on* 10, 242–248.
- [7] Alvarez-Valdes, R., Martinez, A., Tamarit, J.M., 2013. A branch & bound algorithm for cutting and packing irregularly shaped pieces. *Int. J. Prod. Econ.* 145, 463–477.
- [8] Alves, C., Brás, P., Valério de Carvalho, J., Pinto, T., 2012. New constructive algorithms for leather nesting in the automotive industry. *Computers & operations research* 39, 1487–1505.
- [9] Amaro Júnior, B., Pinheiro, P.R., Coelho, P.V., 2017. A parallel biased Random-Key genetic algorithm with multiple populations applied to irregular strip packing problems. *Math. Probl. Eng.* 2017.
- [10] Art, Jr, R.C., 1966. An approach to the two dimensional irregular cutting stock problem. Ph.D. thesis. Massachusetts Institute of Technology.
- [11] Atamtürk, A., Nemhauser, G.L., Savelsbergh, M.W.P., 2000. Conflict graphs in solving integer programming problems. *European journal of operational research* 121, 40–55.
- [12] Audemard, G., Simon, L., 2018. On the Glucose SAT solver. *International journal of artificial intelligence tools: architectures, languages, algorithms* 27, 1840001.
- [13] Babu, A.R., Babu, N.R., 2001. A generic approach for nesting of 2-D parts in 2-D sheets using genetic and heuristic algorithms. *Computer-Aided Design and Applications* 33, 879–891.
- [14] Balas, E., Padberg, M.W., 1972. On the set-covering problem. *Operations research* 20, 1152–1161.

A parallel branch-and-bound-and-prune algorithm for irregular strip packing with discrete rotations




Figure 5: Ten open problem instances whose upper bounds are improved in this work. Eight of these improvements are obtained by the DB-CC [105] model solved with Gurobi 11.0.3, whilst two others are obtained by our 0-1 DB-CC model solved with Google CPSat 9.11.4210. Most of the solutions above are likely to be the optimal despite it could not be proven.

- [15] Bennell, J.A., Dowsland, K.A., Dowsland, W.B., 2001. The irregular cutting-stock problem—a new procedure for deriving the no-fit polygon. *Comput. Oper. Res.* 28, 271–287.
- [16] Bennell, J.A., Oliveira, J.F., 2008. The geometry of nesting problems: A tutorial. *Eur. J. Oper. Res.* 184, 397–415.
- [17] Bennell, J.A., Oliveira, J.F., 2009. A tutorial in irregular shape packing problems. *J. Oper. Res. Soc.*, S93–S105.
- [18] Bennell, J.A., Oliveira, J.F., Wäscher, G., 2013. Cutting and packing. *International Journal of Production Economics* 145, 449–450.
- [19] Bennell, J.A., Song, X., 2008. A comprehensive and robust procedure for obtaining the nofit polygon using minkowski sums. *Comput. Oper. Res.* 35, 267–281.
- [20] de Berg, M., Van Kreveld, M., Overmars, M., Schwarzköpf, O., 1997. *Computational Geometry: Algorithms and Applications*. Springer.
- [21] Biere, A., Faller, T., Fazekas, K., Fleury, M., Froleyks, N., Pollitt, F., 2024. CaDiCaL 2.0, in: *Computer Aided Verification*. Springer Nature Switzerland, Cham. *Lecture notes in computer science*, pp. 133–152.
- [22] Bixby, R.E., 2002. Solving Real-World Linear Programs: A Decade and More of Progress. *Operations research* 50, 3–15.
- [23] Burke, E.K., Hellier, R.S.R., Kendall, G., Whitwell, G., 2007. Complete and robust no-fit polygon generation for the irregular stock cutting problem. *European Journal of Operational Research* 179, 27–49.
- [24] Burke, E.K., Hellier, R.S.R., Kendall, G., Whitwell, G., 2010. Irregular Packing Using the Line and Arc No-Fit Polygon. *Operations research* 58, 948–970.
- [25] Chai, D., Kuehlmann, A., 2003. A fast pseudo-boolean constraint solver, in: *Proceedings of the 40th annual Design Automation Conference*, ACM, New York, NY, USA. pp. 830–835.
- [26] Chehrzad, S., Roose, D., Wauters, T., 2022. A fast and scalable bottom-left-fill algorithm to solve nesting problems using a semi-discrete representation. *European journal of operational research* 300, 809–826.
- [27] Cheng, E., Cunningham, W.H., 1997. Wheel inequalities for stable set polytopes. *Mathematical programming* 77, 389–421.
- [28] Cheng, E., de Vries, S., 2002. Antiweb-wheel inequalities and their separation problems over the stable set polytopes. *Mathematical programming* 92, 153–175.
- [29] Cheok, B.T., Nee, A.Y.C., 1991. Algorithms for nesting of ship/offshore structural plates. *American Society of Mechanical Engineers, Design Engineering Division (Publication) DE* 32, 221–226.

- [30] Cherri, L.H., Carravilla, M.A., Toledo, F.M.B., 2016a. A model-based heuristics for the irregular strip packing problem. *Pesquisa Operacional* 36, 447–468.
- [31] Cherri, L.H., Cherri, A.C., Carravilla, M.A., Oliveira, J.F., Toledo, F.M.B., Vianna, A.C.G., 2018. An innovative data structure to handle the geometry of nesting problems. *International Journal of Production Research* 56, 7085–7102.
- [32] Cherri, L.H., Mundim, L.R., Andretta, M., Toledo, F.M.B., Oliveira, J.F., Carravilla, M.A., 2016b. Robust mixed-integer linear programming models for the irregular strip packing problem. *European Journal of Operational Research* 253, 570–583.
- [33] Conte, A., Grossi, R., Marino, A., 2020. Large-scale clique cover of real-world networks. *Information and Computation* 270, 104464.
- [34] Cuninghame-Green, R., 1989. Geometry, shoemaking and the milk tray problem. *New scientist* 123, 50–53.
- [35] Daniels, K., Li, Z., Milenkovic, V., 1994. Multiple containment methods. Technical Report TR-12-94. Harvard Computer Science Group.
- [36] Danna, E., Rothberg, E., Pape, C.L., 2005. Exploring relaxation induced neighborhoods to improve MIP solutions. *Mathematical Programming. A Publication of the Mathematical Programming Society* 102, 71–90.
- [37] Dean, H.T., 2002. Minimizing waste in the 2-dimensional cutting stock problem. Ph.D. thesis. Department of Mechanical Engineering, University of Canterbury. Christchurch, New Zealand.
- [38] Dean, H.T., Tu, Y., Raffensperger, J.F., 2006. An improved method for calculating the no-fit polygon. *Comput. Oper. Res.* 33, 1521–1539.
- [39] Dechter, R., 1990. Enhancement schemes for constraint processing: Backjumping, learning, and cutset decomposition. *Artif. Intell.* 41, 273–312.
- [40] Dolan, E.D., Moré, J.J., 2002. Benchmarking optimization software with performance profiles. *Mathematical Programming. A Publication of the Mathematical Programming Society* 91, 201–213.
- [41] Dowland, K.A., Dowland, W.B., 1992. Packing problems. *Eur. J. Oper. Res.* 56, 2–14.
- [42] Dowland, K.A., Dowland, W.B., 1995. Solution approaches to irregular nesting problems. *Eur. J. Oper. Res.* 84, 506–521.
- [43] Dowland, K.A., Vaid, S., Dowland, W.B., 2002. An algorithm for polygon placement using a bottom-left strategy. *European Journal of Operational Research* 141, 371–381.
- [44] Dyckhoff, H., 1990. A typology of cutting and packing problems. *Eur. J. Oper. Res.* 44, 145–159.
- [45] Elamvazuthi, I., Kamaruddin, S., Azmi, M.S., 2009. Automation of nesting and cutting processes of leather furniture production: a case study. *International Journal of Mechanical & Mechatronics Engineering IJMME* 9.
- [46] Elkeran, A., 2013. A new approach for sheet nesting problem using guided cuckoo search and pairwise clustering. *Eur. J. Oper. Res.* 231, 757–769.
- [47] Eén, N., Sörensson, N., 2004. An Extensible SAT-solver, in: *Theory and Applications of Satisfiability Testing*. Springer Berlin Heidelberg, Berlin, Heidelberg. Lecture notes in computer science, pp. 502–518.
- [48] Fang, J., Rao, Y., Zhao, X., Du, B., 2023. A Hybrid Reinforcement Learning Algorithm for 2D Irregular Packing Problems. *Mathematics* 11.
- [49] Feydy, T., Stuckey, P.J., 2009. Lazy Clause Generation Reengineered, in: *Principles and Practice of Constraint Programming - CP 2009*, Springer Berlin Heidelberg. pp. 352–366.
- [50] Fischetti, M., Luzzi, I., 2009. Mixed-integer programming models for nesting problems. *Journal of Heuristics* 15, 201–226.
- [51] Fowler, R.J., Paterson, M.S., Tanimoto, S.L., 1981. Optimal packing and covering in the plane are NP-complete. *Inf. Process. Lett.* 12, 133–137.
- [52] Frost, D., Dechter, R., 1994. Dead-end driven learning, in: *National Conference on Artificial Intelligence*, cdn.aaai.org. pp. 294–300.
- [53] Ghosh, P.K., 1991. An algebra of polygons through the notion of negative shapes. *CVGIP: Image Understanding* 54, 119–144.
- [54] Giandomenico, M., Rossi, F., Smriglio, S., 2013. Strong lift-and-project cutting planes for the stable set problem. *Mathematical programming* 141, 165–192.
- [55] Gilmore, P.C., Gomory, R.E., 1965. Multistage cutting stock problems of two and more dimensions. *Oper. Res.* 13, 94–120.
- [56] Giovenali, N., Bruno, G., Chiabert, P., 2025. Comparative evaluation of irregular shape strip-packing algorithms, in: *Communications in Computer and Information Science*. Springer Nature Switzerland, Cham. Communications in computer and information science, pp. 115–127.
- [57] Gomes, A.M., Oliveira, J.F., 2002. A 2-exchange heuristic for nesting problems. *Eur. J. Oper. Res.* 141, 359–370.
- [58] Greene, D.H., 1983. The decomposition of polygons into convex parts, in: Preparata, F. (Ed.), *Computational Geometry*. JAI Press, Greenwich, Connecticut (USA). volume 1 of *Adv. Comput. Res.*, pp. 235–259.
- [59] Grötschel, M., Holland, O., 1991. Solution of large-scale symmetric travelling salesman problems. *Mathematical programming* 51, 141–202.
- [60] Guo, B., Li, J., Zhang, Y., Wu, F., Peng, Q., 2023. Efficient 2D Irregular Layout by Vector Superposition NFP and Mixed-integer Programming. *Expert systems with applications*, 120548.
- [61] Hamada, K., Ikeda, Y., Tokumoto, H., Hase, S., 2019. Development of automatic nesting system for shipbuilding using the branch-and-bound method. *Journal of Marine Science and Technology* 24, 398–409.
- [62] Han, W., Bennell, J.A., Zhao, X., Song, X., 2013. Construction heuristics for two-dimensional irregular shape bin packing with guillotine constraints. *Eur. J. Oper. Res.* 230, 495–504.
- [63] Haralick, R.M., Elliott, G.L., 1980. Increasing tree search efficiency for constraint satisfaction problems. *Artificial intelligence* 14, 263–313.
- [64] Heistermann, J., Lengauer, T., 1995. The nesting problem in the leather manufacturing industry. *Ann. Oper. Res.* .
- [65] Hopper, E., Turton, B.C.H., 2001. A review of the application of Meta-Heuristic algorithms to 2D strip packing problems. *Artificial Intelligence Review* 16, 257–300.
- [66] Iori, M., de Lima, V.L., Martello, S., Miyazawa, F.K., Monaci, M., 2021. Exact solution techniques for two-dimensional cutting and packing. *European Journal of Operational Research* 289, 399–415.
- [67] Koch, T., Berthold, T., Pedersen, J., Vanaret, C., 2022. Progress in mathematical programming solvers from 2001 to 2020. *EURO Journal on Computational Optimization* 10, 100031.
- [68] Kreter, S., Schutt, A., Stuckey, P.J., Zimmermann, J., 2018. Mixed-integer linear programming and constraint programming formulations for solving resource availability cost problems. *European journal of operational research* 266, 472–486.

- [69] Krupke, D., . The CP-SAT Primer - Using and Understanding Google OR-Tools' CP-SAT Solver. https://d-krupke.github.io/cpsat-primer/00_intro.html. Accessed: 2025-2-27.
- [70] Lastra-Díaz, J.J., Ortuño, M.T., 2024. Mixed-integer programming models for irregular strip packing based on vertical slices and feasibility cuts. *European Journal of Operational Research* 313, 69–91.
- [71] Lastra-Díaz, J.J., Ortuño, M.T., 2025. Reproducibility dataset for a branch-and-bound-and-prune algorithm for irregular strip packing. Mendeley Data v1. <http://dx.doi.org/10.17632/k7tb42dj4f.1>.
- [72] Leao, A.A.S., Toledo, F.M.B., Oliveira, J.F., Carravilla, M.A., 2016. A semi-continuous MIP model for the irregular strip packing problem. *International Journal of Production Research* 54, 712–721.
- [73] Leao, A.A.S., Toledo, F.M.B., Oliveira, J.F., Carravilla, M.A., Álvarez-Valdés, R., 2020. Irregular packing problems: A review of mathematical models. *European Journal of Operational Research* 282, 803–822.
- [74] Leighton, F.T., 1979. A Graph Coloring Algorithm for Large Scheduling Problems. *JOURNAL OF RESEARCH of the Notional Bureau of Standards* 84, 489–506.
- [75] Letchford, A.N., Rossi, F., Smriglio, S., 2020. The stable set problem: Clique and nodal inequalities revisited. *Computers & operations research* 123, 105024.
- [76] Li, Z., 1994. *Compaction algorithms for non-convex polygons and their applications*. Ph.D. thesis. Harvard University. <http://nrs.harvard.edu/urn-3:HUL.InstRepos:25619464>.
- [77] Li, Z., Milenkovic, V., 1993. A compaction algorithm for non-convex polygons and its application, in: *Proceedings of the Ninth Annual Symposium on Computational Geometry*, ACM, New York, NY, USA. pp. 153–162.
- [78] Li, Z., Milenkovic, V., 1995. Compaction and separation algorithms for non-convex polygons and their applications. *Eur. J. Oper. Res.* 84, 539–561.
- [79] Licari, R., Lo Valvo, E., 2011. Optimal positioning of irregular shapes in stamping die strip. *International Journal of Advanced Manufacturing Technology* 52, 497–505.
- [80] Lodi, A., Martello, S., Vigo, D., 2002. Recent advances on two-dimensional bin packing problems. *Discrete Appl. Math.* 123, 379–396.
- [81] Lunardi, W.T., Birgin, E.G., Laborie, P., Ronconi, D.P., Voos, H., 2020. Mixed Integer linear programming and constraint programming models for the online printing shop scheduling problem. *Computers & operations research* 123, 105020.
- [82] Mahadevan, A., 1984. *Optimization in Computer-aided Pattern Packing (Marking, Envelopes)*. Ph.D. thesis. North Carolina State University.
- [83] Marques-Silva, J., Lynce, I., Malik, S., 2009. Conflict-driven clause learning SAT solvers. *Handbook of satisfiability* , 131–153.
- [84] Milenkovic, V., Daniels, K., Li, Z., 1991. Automatic marker making, in: *Proceedings of the Third Canadian Conference on Computational Geometry*, nereida.deioc.ull.es. pp. 243–246.
- [85] Milenkovic, V., Sacks, E., 2010. TWO APPROXIMATE MINKOWSKI SUM ALGORITHMS. *Int. J. Comput. Geom. Appl.* 20, 485–509.
- [86] Mitchell, J.E., 2002. Branch-and-cut algorithms for combinatorial optimization problems. *Handbook of applied optimization* .
- [87] Mundim, L.R., Andretta, M., de Queiroz, T.A., 2017. A biased random key genetic algorithm for open dimension nesting problems using no-fit raster. *Expert Syst. Appl.* 81, 358–371.
- [88] Na, G.Y., Yang, J., 2023. Two-dimensional polygon classification and pairwise clustering for pairing in ship parts nesting. *Journal of intelligent manufacturing* .
- [89] Naderi, B., Ruiz, R., Roshanaei, V., 2023. Mixed-Integer Programming vs. Constraint Programming for Shop Scheduling Problems: New Results and Outlook. *INFORMS journal on computing* 35, 817–843.
- [90] Nemhauser, G.L., Sigismondi, G., 1992. A strong cutting plane/branch-and-bound algorithm for node packing. *The Journal of the Operational Research Society* 43, 443–457.
- [91] Nieuwenhuis, R., Oliveras, A., Rodríguez-Carbonell, E., 2023. IntSat: integer linear programming by conflict-driven constraint learning. *Optimization methods & software* , 1–28.
- [92] Ohrimenko, O., Stuckey, P.J., Codish, M., 2009. Propagation via lazy clause generation. *Constraints: an international journal* 14, 357–391.
- [93] Oliveira, J.F.C., Ferreira, J.A.S., 1993. Algorithms for nesting problems, in: Vidal, R.V.V. (Ed.), *Applied Simulated Annealing*. Springer Berlin Heidelberg, Berlin, Heidelberg, pp. 255–273.
- [94] Padberg, M., Rinaldi, G., 1991. A Branch-and-Cut Algorithm for the Resolution of Large-Scale Symmetric Traveling Salesman Problems. *SIAM Review* 33, 60–100.
- [95] Padberg, M.W., 1973. On the facial structure of set packing polyhedra. *Mathematical programming* 5, 199–215.
- [96] Pantoja-Benavides, G., Álvarez Martínez, D., Parreño Torres, F., 2024. The Normalized Direct Trigonometry Model for the two-dimensional Irregular Strip Packing Problem. *Mathematics* 12, 2414.
- [97] Perron, L., Didier, F., Gay, S., 2023. The CP-SAT-LP solver (invited talk), in: *29th International Conference on Principles and Practice of Constraint Programming (CP 2023)*, Schloss Dagstuhl - Leibniz-Zentrum für Informatik. pp. 3:1–3:2.
- [98] Pinheiro, P.R., Amaro Júnior, B., Saraiva, R.D., 2016. A random-key genetic algorithm for solving the nesting problem. *Int. J. Comput. Integr. Manuf.* 29, 1159–1165.
- [99] Polyakovskiy, S., Stuckey, P.J., 2023. A Constraint Programming Solution to the Guillotine Rectangular Cutting Problem. *Proceedings of the International Conference on Automated Planning and Scheduling* 33, 352–360.
- [100] Queiroz, L.R.d.S., Andretta, M., 2020. Two effective methods for the irregular Knapsack problem. *Applied soft computing* , 106485.
- [101] Queiroz, L.R.d.S., de Queiroz, T.A., 2023. A VNS Based Heuristic for a 2D Open Dimension Problem, in: *Variable Neighborhood Search*, Springer Nature Switzerland. pp. 125–136.
- [102] Riff, M.C., Bonnaire, X., Neveu, B., 2009. A revision of recent approaches for two-dimensional strip-packing problems. *Engineering applications of artificial intelligence* 22, 823–827.
- [103] Rodrigues, M.O., 2021. Fast constructive and improvement heuristics for edge clique covering. *Discrete Optimization* 39, 100628.
- [104] Rodrigues, M.O., Cherri, L.H., Mundim, L.R., 2017. MIP models for the irregular strip packing problem: new symmetry breaking constraints. *ITM Web of Conferences* 14, 00005.

- [105] Rodrigues, M.O., Toledo, F.M.B., 2017. A clique covering MIP model for the irregular strip packing problem. *Comput. Oper. Res.* 87, 221–234.
- [106] Sato, A.K., Martins, T.C., Gomes, A.M., Tsuzuki, M.S.G., 2019. Raster penetration map applied to the irregular packing problem. *European Journal of Operational Research* 279, 657–671.
- [107] Sato, A.K., Martins, T.d.C., Tsuzuki, M.d.S.G., 2016a. A pairwise exact placement algorithm for the irregular nesting problem. *International Journal of Computer Integrated Manufacturing* 29, 1177–1189.
- [108] Sato, A.K., Mundim, L.R., Martins, T.C., Tsuzuki, M.S.G., 2023. A separation and compaction algorithm for the two-open dimension nesting problem using penetration-fit raster and obstruction map. *Expert systems with applications* 220, 119716.
- [109] Sato, A.K., de Sales Guerra Tsuzuki, M., de Castro Martins, T., Gomes, A.M., 2016b. Study of the grid size impact on a raster based strip packing problem solution. *IFAC-PapersOnLine* 49, 143–148.
- [110] Scrawk, J., 2022. CGALDotNet project. .NET wrapper for the Computational Geometry Algorithms Library. <https://github.com/Scrawk/CGALDotNet>.
- [111] Segenreich, S.A., Faria Braga, L.M.P., 1986. Optimal nesting of general plane figures: A monte carlo heuristical approach. *Comput. Graph.* 10, 229–237.
- [112] Sorensson, N., Een, N., 2005. Minisat v1.13-a sat solver with conflict-clause minimization. *SAT* 2005, 1–2.
- [113] Rodrigues de Souza, L., Andretta, M., 2020. Modelo de programação estocástica para um problema de corte de itens irregulares, in: *LII Simpósio Brasileiro de Oesquisa Operacional*.
- [114] Rodrigues de Souza, L., Andretta, M., 2022. A branch-and-cut algorithm for the irregular strip packing problem with uncertain demands. *International transactions in operational research: a journal of The International Federation of Operational Research Societies* .
- [115] Stuckey, P.J., 2010. Lazy Clause Generation: Combining the Power of SAT and CP (and MIP?) Solving, in: *Integration of AI and OR Techniques in Constraint Programming for Combinatorial Optimization Problems*, Springer Berlin Heidelberg. pp. 5–9.
- [116] Sweeney, P.E., Paternoster, E.R., 1992. Cutting and packing problems: A categorized, Application-Orientated research bibliography. *J. Oper. Res. Soc.* 43, 691–706.
- [117] Toledo, F.M.B., Carravilla, M.A., Ribeiro, C., Oliveira, J.F., Gomes, A.M., 2013. The Dotted-Board model: A new MIP model for nesting irregular shapes. *Int. J. Prod. Econ.* 145, 478–487.
- [118] Trotter, Jr, L.E., 1975. A class of facet producing graphs for vertex packing polyhedra. *Discrete mathematics* 12, 373–388.
- [119] Umetani, S., Murakami, S., 2022. Coordinate descent heuristics for the irregular strip packing problem of rasterized shapes. *European journal of operational research* 303, 1009–1026.
- [120] Wang, P.Y., Wäscher, G., 2002. Cutting and packing. *European Journal of Operational Research* 141, 239–240.
- [121] Wang, T., Meskens, N., Duvivier, D., 2015. Scheduling operating theatres: Mixed integer programming vs. constraint programming. *European journal of operational research* 247, 401–413.
- [122] Wäscher, G., Haubner, H., Schumann, H., 2007. An improved typology of cutting and packing problems. *Eur. J. Oper. Res.* 183, 1109–1130.
- [123] Watson, P.D., Tobias, A.M., 1999. An efficient algorithm for the regular W1 packing of polygons in the infinite plane. *The Journal of the Operational Research Society* 50, 1054–1062.
- [124] Whelan, P.F., Batchelor, B.G., 1993. Automated packing systems: Review of industrial implementations. *Mach. Vis. Appl.* .
- [125] Witzig, J., Berthold, T., Heinz, S., 2017. Experiments with conflict analysis in mixed integer programming, in: *Integration of AI and OR Techniques in Constraint Programming*. Springer International Publishing, Cham. Lecture notes in computer science, pp. 211–220.
- [126] Witzig, J., Gleixner, A., 2021. Conflict-Driven Heuristics for Mixed Integer Programming. *INFORMS journal on computing* 33, 706–720.