# Are We Solving a Well-Defined Problem? A Task-Centric Perspective on Recommendation Tasks

Aixin Sun

axsun@ntu.edu.sg Nanyang Technological University Singapore, Singapore

#### Abstract

Recommender systems (RecSys) leverage user interaction history to predict and suggest relevant items, shaping user experiences across various domains. While many studies adopt a general problem definition, i.e., to recommend preferred items to users based on past interactions, such abstraction often lacks the domain-specific nuances necessary for practical deployment. However, models are frequently evaluated using datasets from online recommender platforms, which inherently reflect these specificities. In this paper, we analyze RecSys task formulations, emphasizing key components such as input-output structures, temporal dynamics, and candidate item selection. All these factors directly impact offline evaluation. We further examine the complexities of user-item interactions, including decision-making costs, multi-step engagements, and unobservable interactions, which may influence model design and loss functions. Additionally, we explore the balance between task specificity and model generalizability, highlighting how well-defined task formulations serve as the foundation for robust evaluation and effective solution development. By clarifying task definitions and their implications, this work provides a structured perspective on RecSys research. The goal is to help researchers better navigate the field, particularly in understanding specificities of the RecSys tasks and ensuring fair and meaningful evaluations.

# **CCS** Concepts

• Information systems → Recommender systems.

# Keywords

Recommender Systems, Task Formulation, Evaluation, User cost

# ACM Reference Format:

Aixin Sun. 2025. Are We Solving a Well-Defined Problem? A Task-Centric Perspective on Recommendation Tasks. In *Proceedings of Draft (Work in progress)*. ACM, New York, NY, USA, 9 pages. https://doi.org/XXXXXXX XXXXXXX

# 1 Introduction

In many recommender systems (RecSys) studies, solutions are proposed for a commonly adopted problem: given a set of users, items, and their interactions, the goal is to recommend items that align with users' interests or preferences. While this general problem definition captures common patterns across recommendation scenarios, its abstraction overlooks critical details needed for practical RecSys applications. Furthermore, discussions on task definition often lack clarity, particularly regarding its scope and practical implications. At the same time, RecSys research is closely tied to real-world applications, where models are primarily evaluated using datasets obtained from operational recommender platforms. The mismatch between abstract problem definitions and domain-specific evaluations leads to inconsistent settings and findings across experiments [17, 29]. In this paper, we present a comprehensive analysis of different RecSys tasks, highlighting their key distinctions and implications for evaluation and real-world deployment.

Recommender systems are not a new research area, and numerous influential works exist. We begin our discussion in Section 2 with a review of several highly cited works in RecSys, emphasizing task formulations. Interestingly, key factors in RecSys were well defined and discussed decades ago. Yet, the community still disagrees on the choice of baselines and datasets [4, 6].

One main contribution of this paper is a detailed examination of task definition in Section 3, focusing primarily on the input and output of a mapping function, *i.e.*, a recommender. We discuss a missing element in task formulation *i.e.*, time, and the selection of candidate items for recommendation, both of which have a significant impact on offline evaluation.

Another contribution of this paper is a detailed analysis of the life cycle of user-item interactions in Section 4. In the pre-interaction judgment stage, users are presented with a list of choices or recommended items. Users incur costs when making informed (or sometimes uninformed) decisions to select a recommendation, which serves as a clear indication of user preferences. We then explore the complexity of user-item interactions. For example, some interactions can involve multiple steps, as in e-commerce, where a user may add an item to their cart, proceed to payment, await delivery, interact with the product, and possibly return it. In music streaming, users are not offered a choice but can only skip or fastforward a recommended song. In some cases, true user-item interactions may not be directly observable as in job recommendation.

Based on the task definition and the framework for understanding it, we present our perspectives in Section 5. We consider (i) the ultimate goal of recommendation, *i.e.*, reducing user cost, (ii) the relationship between task formulation, solution, and evaluation, and (iii) the intersection of task specificity and model generalizability. In our discussion, we use a few examples to show the differences in RecSys tasks based on the presented dimensions, *i.e.*, candidate item selection, pre-interaction judgment, and user-item interaction. We hope that this paper provides researchers, particularly those new to recommender systems, with a clearer understanding of the research topic. After establishing a clear understanding, subsequent research can precisely define specific RecSys tasks, select appropriate baselines, and design experiments that account for task specificity.

Work in progress, March 2025, ACM Template 2025. ACM ISBN 978-1-4503-XXXX-X/18/06 https://doi.org/XXXXXXXXXXXXXX

Work in progress, March 2025, ACM Template

### 2 A Historical Review of Task Formulation

We begin with four of the most widely cited papers,<sup>1</sup> each with over 8,000 citations. As foundational works in this field, these papers have influenced many researchers, and the tasks they define have likely shaped numerous follow-up studies. The four papers reviewed were published between 2004 and 2011 [1, 5, 13, 22].

**The Recommendation Problem.** In one of the most influential survey papers in RecSys, Adomavicius and Tuzhilin [1] formally define the *recommendation problem* as follows:

DEFINITION 1 (RECOMMENDATION PROBLEM). Let U be the set of all users and let I be the set of all possible items that can be recommended. Let r be a utility function that measures the usefulness of item i to user u, i.e.,  $r \in U \times I \rightarrow R$ , where R is a totally ordered set (i.e., nonnegative integers or real numbers within a certain range). Then, for each user  $u \in U$ , we want to choose such item  $i' \in I$  that maximizes the user's utility:

$$\forall u \in U, i'_u = \arg\max_{i \in I} r(u, i) \tag{1}$$

The authors further note that "the utility of an item is usually represented by a rating, which indicates how a particular user liked a particular item," a concept commonly known as *explicit feedback*. Nevertheless, in most subsequent RecSys studies, *implicit feedback* has become far more prevalent [21]. As a result, the utility of an item to a user is often inferred from binary feedback, whether the user has interacted with the item, such as listening to a song, purchasing a watch, or staying at a hotel. Notably, the difference between explicit and implicit feedback primarily affects data modeling and the loss function design when learning r, while the core recommendation problem remains unchanged.

**Collaborative Filtering.** Koren et al. [13] do not formally define tasks in recommender systems but instead compare the two primary approaches: content filtering and collaborative filtering. They describe *content filtering* as a method that creates user or item profiles to capture their characteristics, enabling the recommender to associate users with relevant items. In contrast, *collaborative filtering* relies exclusively on past user-item interactions, such as previous transactions or product ratings. The authors highlight that "a major appeal of collaborative filtering is that it is domain-free, yet it can address data aspects that are often elusive and difficult to profile using content filtering," further noting that collaborative filtering is "generally more accurate than content-based techniques."

Due to these advantages, collaborative filtering solutions are often considered more generalizable, aligning well with one of the key objectives in academic research. However, the authors also acknowledge the cold start problem in collaborative filtering, which arises when new users or items have no past interactions [23].

Although solutions such as content-based, collaborative, and hybrid filtering are independent of problem definitions, the widespread adoption of collaborative filtering in recent research leads us to assume that *user-item interactions remain a key input for typical recommender systems*. With this in mind, we reiterate the points made in [13], emphasizing that collaborative filtering relies exclusively on *past* user-item interactions, such as *previous* transactions or product ratings.

**User Feedback and Preference.** In the introduction chapter of the RecSys Handbook, Ricci et al. [22] describe personalized recommendations as ranked lists of items, where recommender systems aim to "predict what the most suitable products or services are, based on the user's preferences and constraints." Regarding user preferences, the authors highlight that these can also be inferred from their actions, such as navigating to a specific product page. In this context, user feedback can take multiple forms: *explicit* feedback, such as ratings; *implicit* feedback, derived from user-item interactions; and *inferred preferences* based on observed user behavior.

Task Diversity. Herlocker et al. [5] provide a thorough discussion on user tasks for recommender systems. Their discussion focuses on end-user tasks (*i.e.*, not marketers or other system stakeholders),<sup>2</sup> which aligns well with the RecSys tasks to be discussed in this paper. The key user task is to find good items, such as providing users with a ranked list of recommended items. The authors highlight that "there are likely to be many specializations of the tasks within each domain," and the domain-specific characteristics are reflected in the properties of the datasets, e.g., the need for novelty versus quality, as well as the cost/benefit ratio of false/true positives/negatives. Regarding novelty, in certain domains, "the user goal is dominated by finding recommendations for things a user does not already know about." In other domains, users expect recommendations to help them find high-quality items among many choices. Regarding cost/benefit, the authors provide an example of the relatively low cost of false-positive movie recommendations. However, in other settings, e.g., if an item comes with a high price tag, then false positives may carry a much higher cost.

**Summary.** From this historical review, we derive the following main points: (i) The primary task of a recommender system is to suggest items to users based on their preferences. (ii) Collaborative filtering is a widely adopted approach that leverages past user-item interactions. (iii) In most cases, users provide implicit feedback, and their preferences can also be inferred from their actions. (iv) Recommendation tasks can be domain-specific, with various factors to consider, such as the desired level of novelty and quality, as well as the trade-off between cost and benefit.

# 3 A Closer Look at the Task Definition

Based on the above discussion and the main points identified, we now examine the RecSys task definition from multiple perspectives. For ease of presentation, we rewrite Definition 1 by specifying recommender as a mapping from its input to output.


DEFINITION 2 (RECOMMENDATION). Let U be a set of users and I be a set of items. A recommender system aims to produce a ranked list of items for a user u, based on user-item interactions  $U \times I$ .

$$\langle u, U \times I, I \rangle \to R^u$$
 (2)

In this rewritten definition, the recommender system's input consists of three components: (i) the user u for whom recommendations

<sup>&</sup>lt;sup>1</sup>Citation counts were obtained via a Google Scholar search for papers with the title words "recommender systems" or "recommender system" on February 12, 2025.

<sup>&</sup>lt;sup>2</sup>We refer readers to [29] for more detailed discussion on other users in a recommender system like item provider, platform provider, and other stakeholders.



Interactions of A

Figure 1: The classic task definition of recommendation, where user-item interactions are represented in a matrix form. The objective is to predict the missing values, which correspond to unobserved user-item interactions.

are to be made, (ii) the set of user-item interactions  $U \times I$ , which includes all existing interactions made by all users and all items, and (iii) the set of available items *I* from which recommendations are being made. The system outputs a ranked list of recommended items for *u*, denoted by  $R^u$ .

Following the tradition of illustrating recommender system tasks in matrix form, we present Definition 2 in Figure 1. In this figure, the goal is to generate a ranked list of recommended items for  $u_3$ . The items  $i_1$  to  $i_n$  collectively form the item set I, and the interactions encompass all interactions made between the m users and n items.

Note that this definition is generic to cover all attributes or side information of users or items, because all such information or metadata can be easily derived given a user ID or item ID. As we focus on the core problem definition of RecSys in this paper, we omit all these details.

#### 3.1 The Missing Input: Time

Recall that in [13], the authors note that collaborative filtering relies exclusively on *past* user-item interactions to make recommendations. In practical scenarios, whether recommending a product for purchase or a song to listen to, it is common sense that recommendations made at a time point t should be based on all information available at or before t. Ideally, the user will find the recommendations appealing, then choose to interact with them after the new recommendations are made at t.

Adding Time to the Input. With that, we rewrite the mapping function in Definition 2 to consider the time dimension. We also make an assumption that each interaction between a user u and item i is associated with a time stamp  $t_x$  when the interaction occurred, denoted by  $(u, i, t_x) \in U \times I$ .

$$\langle u, t, (U \times I)_{\leq t}, I_{\leq t} \rangle \to R_t^u$$
 (3)

In this rewritten form, we introduce a time point *t*, indicating a recommendation is to be made for user *u* at time point *t*. We use  $(U \times I)_{\leq t}$  to represent all user-item interactions that occurred before time *t*, a simplified form of  $\{(u, i, t_x) \in U \times I | t_x \leq t\}$ . Accordingly, the candidate items available for recommendation are those that were registered in the system and accessible to the recommender as at *t*, denoted by  $I_{\leq t}$ .

While this reformulation may seem trivial and may not impact real-world or online RecSys recommendations, strictly adhering to




Figure 2: The recommendation task along time line. Recommendations are to be made for user  $u_2$  at time point  $t_e$ . A model is expected to learn from interactions occurred before  $t_e$  *i.e.*,  $(U \times I)_{\leq t_e}$  and make recommendation among items available at  $t_e$ , denoted by  $I_{\leq t_e}$ .

this task definition poses significant challenges for offline evaluations [25].

**Impact to Offline Evaluation.** In offline evaluations, user-item interactions in a dataset must be partitioned into training and test sets. The former is used to train the RecSys model, while the latter is used to assess its performance. According to the task formulation in Equation 3, evaluating a model's performance at time *t* for a user *u* requires that the model only access or learn from the interactions that occurred before *t*, *i.e.*,  $(U \times I) \leq t$ , and generate recommendations from  $I \leq t$ , the items available at or before *t*.

Figure 2 provides an illustration where the items interacted with by each user are plotted to the right of the user along a global timeline. For example, user  $u_1$  interacted with item  $i_1$  at time point  $t_1$ . If we use the user-based leave-last-one-out data split to evaluate our model's accuracy for user  $u_2$ , the last interaction of  $u_2$  at time  $t_e$  is masked as the test instance. The recommender can learn from all user-item interactions that occurred before  $t_e$ , *i.e.*,  $(U \times I)_{\leq t_e}$ . The items available for recommendation to  $u_2$  at  $t_e$  are those that have been interacted with by any user before  $t_e$ . Notably, items  $i_7$  and  $i_8$  received their first interaction after  $t_e$ , the system has no interaction data for these items at  $t_e$ , and they should not be recommended to  $u_2$ .<sup>3</sup>

Finally, note that the user-based leave-last-one-out data split results in each user having their own  $(U \times I) \leq t$  and  $I \leq t$ , since not all users have their last interaction at a common time. Without enforcing a global time point, many widely adopted data partitioning schemes, such as random splitting or user-based leave-last-one-out, lead to data leakage [10]. This occurs when user-item interactions from the future (relative to time *t* in Equation 3 or  $t_e$  in Figure 2) are used to train the model and make recommendations.

In other words, when recommending items for a specific user, the model does not rely solely on that user's interaction history but also leverages interactions from other users who may share similar preferences. The time point constrains all user-item interactions accessible to the system.

The incorporation of factor t into the task formulation also directly impacts the implementation of certain baseline models. For instance, the widely used popularity baseline, which simply counts item occurrences in the training data, does not accurately reflect

<sup>&</sup>lt;sup>3</sup>Note that our discussion assumes the recommendation model is based on collaborative filtering, to avoid the possible misunderstanding that items  $i_7$  and  $i_8$  could be recommended based on profile matching.




Figure 3: The recommendation for repeated consumption for user  $u_2$  at time  $t_e$ . The search space for repeated consumption is the two items  $i_2$  and  $i_5$ . To recommend new items, the candidate items will be the remaining items in  $I_{\leq t_e} \setminus \{i_2, i_5\}$ .

real-life item popularity. In practice, item popularity is typically associated with a reference time point and a specific time range, *e.g.*, the top-selling books from last week or last month. By introducing a time point t in problem definition, item popularity can be derived with reference to that specific time point [8, 9].

# 3.2 The Missing Constraints on Candidate Items

Next, we focus on the available items that can be recommended to a user u at time t. Herlocker et al. [5] discuss recommender system tasks from the perspective of novelty and quality, assuming that users generally expect recommended items to be new and previously unconsumed. However, this assumption may not always hold, as a recommender system is ultimately designed to help users find preferred items more easily and quickly.

In many scenarios, users may prefer to interact with items they are already familiar with and confident in [2]. Groceries shopping [3, 11], e-commerce [19, 28], food delivery ordering [14], and song listening [20, 27] are a few examples where a user may prefer to have earlier consumed items to be recommended for easy selection.

Let  $I_t^u$  be the items that u has interacted with in the past at time point t. We use  $I_t^{\bar{u}}$  to denote the remaining items available at tthat are new to u, then the recommendation in Equation 3 can be divided into two formulations for repeated consumption  $R_t^{ur}$  and for exploration  $R_t^{ue}$  recommendations, respectively.

$$\langle u, t, (U \times I)_{\leq t}, I^{u}_{< t} \rangle \to R^{ur}_{t}$$
 (4)

$$\langle u, t, (U \times I)_{\leq t}, I^u_{< t} \rangle \to R^{ue}_t$$
 (5)

Note that, how to present  $R_t^{ur}$  and  $R_t^{ue}$  to users through a web or app interface, *e.g.*, as two separate rankings or as a merged ranking of items from both recommendations, is orthogonal to our discussion in this paper.

**Impact to Offline Evaluation.** Again, the partitioning of candidate items for recommendation I into  $I^u$  and  $I^{\bar{u}}$  may seem trivial (here, we omit the subscript t for clarity), but this partitioning leads to (i) significant differences in the search space for a recommender, because  $|I^u| \ll |I^{\bar{u}}|$  and  $|I^{\bar{u}}| \approx |I|$ , and (ii) subsequently significant differences or impacts on evaluation.

It is important to note that if repeated consumption and exploration are not clearly distinguished, the evaluation results may be significantly biased toward repeated consumption. Because of the much smaller item search space for recommendation and a large portion of, if not all, items being users' preferred items, the chances of making a good recommendation among the repeated items are much higher than picking an item from a much larger pool of items, especially those the user has no experience with. The recommendation accuracy could be easily dominated by the repeated items if repeated consumption is common like food ordering and groceries shopping. Hence, the separation of evaluations of repeated consumption and exploration better reflects the model's accuracy; a detailed discussion and comparison is presented in [14] for food delivery recommendation. Additionally, due to the much smaller search space, recommending repeated items is significantly more efficient than recommending items for exploration.

Candidate Item Selection. The repeated consumption and exploration is just one example of candidate item selection. The candidate items suitable for recommendation can be directly specified by users. For example, if a user is planning a trip to a city, hotel recommendations would only be meaningful if they are located in that city and available during the user's travel dates. Although this may seem trivial and makes the recommendation problem more similar to a search problem, the vast majority of recommendation work using the Yelp dataset does not consider users' geographical constraints, to the best of our knowledge. That is, if a user resides in New York City and primarily visits restaurants within a relatively small region of NYC, recommending a restaurant from a different state would be far less practical for this user. On the other hand, the candidate items suitable for recommendation could also be derived based on user intent mining through search logs and other means. Note that the user intent mining here is different from the line of research on intent-aware recommender systems [7, 24], which will be discussed in Section 5.2. One key difference is that, in our discussion on candidate item selection, the set of eligible items to be recommended is determined before running the recommender system, hence is part of the input to the problem definition and can be specified by users, illustrated in Figure 4.

#### 3.3 Yet Another Rewritten Task Formulation

We can now combine Equations 4 and 5 into a more general formulation by introducing a selection condition on the candidate items, denoted as  $s(I_{\leq t})$ . Specifically,  $s(\cdot)$  can represent selection criteria based on user interaction history *e.g.*, for repeated consumption, or be specified by users with temporal, spatial, or other attribute-based conditions. However, by listing  $s(I_{\leq t})$  as part of the input to the recommendation task, the candidate set of items is determined *before* a model ranks them.

DEFINITION 3 (RECOMMENDATION TASK). Let U be a set of users and I be a set of items. A recommender system aims to produce a ranked list of items for a user u at time t, based on user-item interactions  $U \times I$  that is available at t, and the conditions specified on the candidate items.

$$\langle u, t, (U \times I)_{\leq t}, s(I_{\leq t}) \rangle \to R_t^u$$
 (6)

Now, we define the recommendation task as making a recommendation at time *t* for user *u* by referencing user-item interactions that occurred before *t* and selecting suitable candidate items that satisfy the selection criteria  $s(\cdot)$  to meet the inferred user preference. Following the example of repeat consumption and exploration, the final recommendation items presented to a user could be the




Figure 4: User costs after recommendations made at time t: from pre-interaction judgment, to interaction, then to an optional post-interaction feedback. Among the recommended items,  $i_2$  satisfies selection criteria  $S(\cdot)$ .

results of running multiple recommendations made from multiple sets of candidate items conditioned on different multiple  $s(\cdot)'s$ . Nevertheless, in terms of model evaluation, it is more meaningful to independently evaluate each model specific to candidate items on one selection function  $s(\cdot)$ .

#### 4 From Recommendation to User Consumption

So far, we have discussed the importance of explicitly incorporating the time factor into the problem definition and examined suitable candidate items for recommendation based on the context of the recommendation task. We consider these to be essential factors in the task definition due to their direct impact on model evaluation, which in turn directly impact the model design. Next, we take a closer look at user-item interactions  $U \times I$  and analyze their meaning, as instances  $(u, i, t_x)$  are widely used to train recommender systems in academic research.

There are many reasons for a user to interact with an item, such as through an intentional search rather than a recommendation. Since we are discussing recommendations, we make a general assumption that *if a user interacts with an item, it reflects some form of preference for that item.* However, we aim to explore the various stages from a recommended item  $i \in \mathbb{R}_t^u$  to an interaction  $(u, i, t_x)$ , and to what extent a model can learn from the interaction. This process can be considered as another form a mapping:

$$\langle u, R_t^u \rangle \to (u, i, t_x) \quad \text{where} \quad i \in R_t^u$$
(7)

# 4.1 User-Item Interaction: The Life Cycle

In the early stages of RecSys research, many studies focused on explicit user feedback, such as ratings *e.g.*, a user giving a movie a 5 out of 5 rating [5]. However, since explicit feedback is often difficult to obtain, implicit feedback has become the mainstream in academic research *e.g.*, a user has watched a movie. Nevertheless, Ricci et al. [22] suggest that user preference can also be inferred from actions such as navigating to a product page *e.g.*, a user clicking on a movie for more details among a list of candidate movies. However, there is a lack of detailed discussion on to what extent such feedback contribute to accurately modeling user preference.

In our discussion, we divide user-item interactions into three stages: *pre-interaction judgment, interaction*, and *post-interaction*  *feedback*, illustrated in Figure 4. While these stages may not apply to all recommendation scenarios, they provide a useful framework for understanding the relationship between user-item interactions and user preferences.

Consider a user searching for a hotel in Padua, Italy, a city she has never visited, for a conference. She is presented with a list of 10 hotels on a booking website, initiating the *pre-interaction judgment* stage. She clicks on one hotel for more details, a decision influenced by factors such as images, branding, location, price, or other readily available attributes. Next, she enters the deliberate evaluation phase, where she reads the hotel description, checks room facilities, and reviews user feedback before deciding to book. All these effort happens before the user stays at the hotel.

A few months later, after her paper is accepted, she attends the conference and stays at the hotel. This marks the *interaction* stage, where she gains firsthand experience. Finally, after checking out, she provides feedback in the form of a rating and review, entering the *post-interaction feedback* stage. This feedback may consider various factors in a typical hotel review, such as location convenience, price, food, service quality, and hygiene.

Both quick judgments and deliberate evaluations in the preinteraction stage come at a cost, the user's time and effort in gathering relevant information. The outcomes of these efforts strongly indicate user preference, especially in similar future situations, *e.g.*, planning another trip or booking a restaurant.

Post-interaction feedback, however, may not always accurately reflect user preference. While a review can highlight the primary reasons for choosing a hotel, representing genuine user preference, it may also describe aspects such as expectation gaps and booking effort, which are not necessarily preference indicators. A rating, influenced by these factors, may not always be a reliable measure of *preference* compared to the concrete fact that the user chose to stay at the hotel. In fact, in many practical scenarios, post-interaction feedback is often difficult to collect, as it requires users to put in additional effort to provide a rating or write a review. Hence, in our following discussion, we focus on the other two stages.

In general, recommendations are presented as a list of candidate items before any user-item interaction occurs. At this stage, the user relies solely on their judgment, which inherently reflects preference, as they would likely make the same choice in similar circumstances. However, most academic datasets only contain actual interactions, lacking context on the reasons behind them. This limitation makes it challenging to model user preference purely based on observed interactions. Thus, a deeper understanding of the user decisionmaking process is crucial for more effective preference modeling.

# 4.2 Complexity of Pre-Interaction Judgment

We now focus on the pre-interaction judgment, which often takes the form of quick judgment or deliberate evaluation before a choice is made. The complexity of this judgment from the user's perspective may arise from several dimensions.

**Informed vs Uninformed Decision**. One major factor from the user's perspective is whether they possess the knowledge to accurately judge an item before interacting with it. For familiar items like books, movies, or other products the user has prior experience

with, they can make an informed decision based on available attributes or other relevant information. Take movies as an example, users may decide whether to watch a film based on the director, cast, genre, a brief synopsis, or simply the poster. However, if a user has never used a robot vacuum before, many of the terms in the product description may be unfamiliar to them. Even after reading the machine specifications and user reviews, they may struggle to discern the pros and cons of a specific model, with references to her own home layout and floor conditions.

These uninformed decisions may not necessarily indicate user preferences. It is also challenging for a recommendation platform to determine whether a user's decision was based on prior knowledge or made without a full understanding of the item. This distinction is crucial, as recommendations based on uninformed interactions might not truly reflect user interests, potentially leading to less effective personalization. For example, after using a robot vacuum for some time, the user may realize that he should purchase another model with features better suited to his floor conditions.

Items in One vs. Multiple Types/Categories. Many studies in recommendation are conducted on datasets containing only one type of item, such as books, movies, news, or music. In these cases, there are common characteristics, such as genre, director, or artist, that users can rely on for pre-interaction judgment before actually interacting with a recommended item. However, in the context of online shopping, where products span thousands of categories, users apply different criteria and expectations when making judgments for different types of items, for informed decisions.

In such a diverse setting, user preferences learned from interactions across multiple item types may be shaped more by general associative patterns than by genuine preferences for specific products. However, distinguishing between personal preferences and co-purchasing patterns remains challenging, as these so-called preferences may be expressed for broader item categories rather than specific items. Nevertheless, we acknowledge that user preference is a complex concept [12].

#### 4.3 Recognition of User-Item Interaction

After the pre-interaction judgment phase, the user makes a decision and interacts with an item. In most datasets used for RecSys evaluation, user-item interactions are recorded in the form of  $(u, i, t_x)$ . However, interactions may appear in different forms depending on the recommendation context.

**Interaction Process Can Be Complicated.** Taking online shopping as an example, the process does not end when a user clicks on a recommended item. After deciding on a product, the user might add the item to their cart, proceed to payment, receive the delivery, and ultimately complete the purchase. From the shopping platform's perspective, this sequence of events marks a successful interaction. However, complications can arise if the user later decides to return the product due to reasons such as quality issues, unmet expectations, or simply a change of mind.

This raises an important question: should an unsuccessful purchase (*i.e.*, one that results in a return) still be considered a valid user-item interaction for learning user preferences? On one hand, the initial decision to purchase the item indicates some level of interest or preference. On the other hand, the return suggests dissatisfaction or misalignment with the user's expectations. If returns are not accounted for, the model might incorrectly reinforce recommendations for similar items, leading to suboptimal suggestions. Therefore, when incorporating interaction data into preference modeling, it is crucial to differentiate between successful and unsuccessful purchases and consider additional contextual signals, such as return rates, to better understand user preferences.

**Absence of Pre-Interaction Judgment.** Some of the user-item interactions happen without a pre-interaction judgment phase. This is especially common in scenarios like music streaming and short-video viewing, where users often do not actively select each item. Instead, they are presented with an initial set of options, and after selecting the first item, subsequent content is automatically fed to users by the recommendation engine, *e.g.*, a playlist or streaming.

In such cases, user engagement signals, such as skipping, fastforwarding, or continuing to watch/listen, play a crucial role in modeling preferences. Unlike traditional recommendation settings where users consciously evaluate and select items before interaction, here, user preferences are inferred more dynamically based on real-time behaviors, or the interaction itself. In fact, users are less likely to explicitly express "like" in a streaming setting but are more likely to express "dislike". This distinction raises important challenges for recommendation models, as they must distinguish between passive exposure and active preference while adapting to continuously evolving user interests. In this case, the common form of user-item interaction  $(u, i, t_x)$  becomes less accurate compared to other settings. Such recommendation in streaming form also post questions in item attribute modeling e.g., evaluating whether the cover image of a short video influence user viewing as the user may not even has the chance of viewing the cover image for each video in the streaming.

**Unobservable Interaction.** There are also recommendation scenarios where user-item interactions are not directly observable and can only be inferred from external sources.

One example is job recommendation, where matching is based on a user's skills and knowledge against job requirements. Unlike traditional recommender systems where user engagement signals (such as clicks, purchases, or views) are readily available, the job application process involves significant effort on both ends, applicants must prepare resumes and cover letters, while companies conduct interviews before making offers. As a result, direct interactions, such as applying for a job or receiving an offer, may not always be captured by a job recommendation platform. Instead, implicit signals, such as a user frequently viewing job postings in a particular field or updating their profile, might be used to infer their interests and preferences.

This lack of direct interaction data introduces challenges in preference modeling, as user engagement may not always reflect strong interest, and external factors *e.g.*, hiring decisions, can influence the outcome. Thus, in such cases, recommender systems must rely on richer contextual information and alternative feedback mechanisms to refine their predictions. Are We Solving a Well-Defined Problem? A Task-Centric Perspective on Recommendation Tasks




Figure 5: Reasons for a bad recommendation. The option "unrelated to the current video" suggests the dependency between the next recommendation and the current item.

# 4.4 Interdependency Across Recommendations

Recommendations can occur either independently, as in hotel booking, or within a session-based context, such as music streaming and short-video viewing. In the latter case, subsequent recommendations may be influenced by the previous selections or even the initial choice made at the start of the session.

Figure 5 shows a feedback form for assessing video recommendation quality from YouTube. Notably, one of the options for a poor recommendation is labeled as "unrelated to the current video." This indicates that the recommendation system tailors the next suggested video based on the one currently being played. The inclusion of this feedback option emphasizes users' expectations that recommendations within a session should maintain contextual relevance. This is a key characteristic of session-based recommendation, a specialized type of recommendation task [15]. A detailed discussion on the recommendation flow is made in [26].

This example further highlights the complexity of recommendation systems and the variety of factors that need to be accounted for when designing different recommendation tasks. Each recommendation scenario, whether based on user preferences, session context, or product types, requires careful formulation to ensure that the user experience is optimized and that the system accurately reflects user intent.

## 5 Discussion and Perspectives

Next, we discuss the ultimate goal of recommendation, *i.e.*, reducing user cost, the relationship between task formulation, solution, and evaluation, and the intersection of task specificity and model generalizability, along with our perspectives on RecSys.

#### 5.1 Recommendation vs User Cost

The ultimate goal of a recommender system is to reduce user effort in finding products or services of interest, enhance their enjoyment of recommendations, and build trust in the system. However, users still incur different costs at various stages of the interaction process. In the pre-interaction judgment stage, users must evaluate recommendations based on available information, such as descriptions, images, reviews, or other metadata, which requires cognitive effort and time. This cost is higher when users lack prior knowledge of the item category or when the recommendation list is overwhelming. During the interaction stage, users experience the actual product or service, which may involve monetary costs (e.g., purchasing a product), time investment (e.g., watching a recommended movie), or engagement effort (e.g., exploring an unfamiliar interface). If the recommendation is poor, users may feel frustrated, leading to dissatisfaction and disengagement. Notably, such negative experiences can accumulate over time, eventually causing users to leave the platform, confirmed by a recent large scale survey [30]. Finally, in the post-interaction stage, users may be asked to provide feedback, such as ratings or reviews. While valuable for possibly improving recommendation quality, this step requires additional effort, and many users may choose not to participate.

Understanding and minimizing all such costs at each of the three stages is essential for enhancing user experience and optimizing the effectiveness (and even trust) of recommender systems. The task definition discussed above primarily expresses the *inputs* that a recommender model should consider and the desired *output*. However, the various costs incurred by users at different stages are not explicitly represented in the problem definition, but can be incorporated into the loss function design in the proposed models.

#### 5.2 Task, Solution, and Evaluation

A task formulation is often a formal abstraction of real-world applications. While such abstractions may omit details specific to certain recommendation platforms, the solutions developed should remain confined to the defined input and output of the task formulation. Consequently, since offline evaluation often serves as a proxy for selecting the most promising solutions for online evaluation, it should be designed to assess a solution's performance with respect to the task formulation itself.

In RecSys research, evaluation is sometimes tailored to fit the proposed solutions rather than being aligned with the task formulation. One example is the evaluation of Bandits and reinforcement learning-based RecSys solutions. As reported in [25], when examining dataset partitioning methods, it was observed that only a small number of papers followed the timeline and simulated user interactions over time, which is a good practice. However, the evaluation was not motivated by the task itself, but because reinforcement learning solutions require reward signals based on user actions, leading to an evaluation setup that caters to the proposed solution.

Some existing RecSys tasks are not well formulated. Sequential recommendation and intent-aware recommendation are two examples; they do not fundamentally differ from a typical recommendation problem. In the survey paper, Jannach and Zanker [7] defines: intent-aware recommender "is a recommender system that is designed to capture the users' underlying current motivations and goals in order to support them." If we view the problem definition by its inputs and outputs, there is no significant difference from the definition in Equation 6. Probably due to a less distinctive problem formulation, there are questions on the progress made [24]. In the survey paper [18], the task of sequential recommendation is Table 1: Example recommendation tasks across different domains. The characteristics are based on our best understanding, which may not be applicable to any specific platform. The "price" attribute is ignored from pre-interaction judgment.

Domain	Item Type	Session	Candidate Item Selection	Pre-Interaction Judgment	User-Item Interaction
Music streaming	Single	Yes	Repeat, Exploration	No, except the first song	Progress ratio, Skip
Short video	Single	Yes	No, or non-repeat	No, except the first video	Progress ratio, Watching speed, Skip
Online shopping	Multi	Might	Repeat, Exploration	Description, Image, Review	Payment, Return
News	Single	Yes	Region, Genre	Title, Source	Click, View
Job	Single	No	Location	Description	Unobservable, Post-interaction inference
Course	Single	No	Meeting pre-requisite	Description, Instructor, Institute	Progress, completion
Food delivery	Single	No	Repeat, Exploration, Delivery distance/time	Image, Description, Review	Payment
POI	Multi	Might	Region, Repeat, Exploration	Description, Image, Travel cost, Review	Unobservable, Post-interaction inference

defined as follows: "In sequential recommendation, we often have one or more sequences of interacted items w.r.t. each user, as well as some auxiliary information to help learn user preferences. Our goal is then to generate a ranked list of items accurately for each user". This is basically a different view of the very same  $U \times I$ . Naturally all items interacted with by a user form a sequence as illustrated in Figure 2. Solutions that pay attention on such sequences may be able to achieve a better recommendation accuracy, particularly in the RecSys settings with items of a single type *e.g.*, music, movie, book, and news. However, the task to be addressed remains a generic recommendation.

A comparable research challenge in the past was imbalanced classification. In that domain, all classification problems with imbalanced class distributions were broadly categorized as "imbalanced classification problems," and researchers sought a common solution to address the imbalance while often overlooking the true underlying reasons for it. However, data imbalance can arise from multiple causes, and while imbalance is an easily observable characteristic of data distribution, it is not itself the root cause [16]. As a result, solutions designed specifically for "imbalanced classification", the surface form of the data imbalance, may or may not be effective, leading to inconclusive results.

The proposed task-centric framework provides a set of dimensions to consider and compare RecSys tasks. Accordingly, the proposed solutions can be evaluated in a fair and meaningful way.

# 5.3 Task Specificity vs Model Generalizability

Recommender systems represent a fascinating intersection between theoretical research and practical deployment. On the one hand, they are directly linked to real-world applications, where performance improvements can lead to tangible business benefits and enhanced user experiences. On the other hand, academic research often strives to develop generic models that generalize well across diverse datasets and application scenarios. The tension between these two objectives creates an interesting challenge: we need models that perform well across multiple datasets representing different recommendation settings, yet optimizing a model for a specific application often requires customization in terms of input features, objective functions, and even model architecture.

This trade-off between task specificity and model generalizability is a fundamental issue in recommender system research. Highly specialized models, fine-tuned for a particular domain, can achieve state-of-the-art performance in their respective tasks but may struggle when applied to other recommendation settings. Conversely, more general models that are designed to work across various domains often sacrifice performance in any given task, as they cannot fully exploit the domain-specific characteristics that drive user preferences. This issue is further exacerbated by the diverse nature of recommendation tasks, as discussed earlier.

One potential approach to addressing this challenge is to establish *a broad categorization of recommendation tasks* based on key dimensions, such as candidate item selection, single- vs. multi-category recommendations, the cost and information available during pre-interaction judgment, the nature of user-item interactions, and the availability of post-interaction feedback. Table 1 provides an overview of several example recommendation domains and highlights their distinguishing characteristics.

From the table, we observe that music streaming and short-video recommendations share many common characteristics, except that users rarely prefer to repeatedly watch the same short videos. However, both domains differ significantly from POI (Point of Interest) recommendation. In POI recommendation, items include restaurants, parks, and historical landmarks, making it a multi-category recommendation task. Additionally, there is a fundamental distinction between recommending previously visited places (*e.g.*, on a map or navigation interface) and suggesting new locations for exploration. This contrast underscores the importance of defining recommendation tasks based on their inherent characteristics rather than treating them as a single unified problem.

Such categorization ensures that all solutions are fairly evaluated on benchmark datasets regardless of the techniques used. We believe that, a detailed understanding and categorization of research tasks can provide insights into selecting appropriate baselines [6] and datasets [4]. Ultimately, the effectiveness of a recommender system depends not necessarily on the sophistication of the model but on how well it aligns with the specific characteristics of the recommendation task at hand. Striking the right balance between generalizability and task specificity remains an open challenge and a key research direction for advancing the field.

By categorizing recommendation tasks along these dimensions, we provide a structured framework for understanding the diversity of recommender system applications. Future work should focus on refining these categorizations and developing standardized evaluation protocols that account for the unique characteristics of each recommendation task.

#### 6 Conclusion

While foundational works in recommender systems have been well established, there remains a lack of consensus within the community regarding baseline models and datasets. This gap is likely due to an insufficient understanding of RecSys tasks. In this paper, we provide an in-depth analysis of recommender system task formulations, emphasizing the need for clear and well-defined problem definitions to support effective evaluation and the development of more applicable solutions. We stress the importance of understanding input-output relationships in recommendation models, considering factors such as temporal dynamics and candidate item selection. Additionally, we examine the complexities of user-item interactions, including user-incurred costs during decision-making and the challenges posed by multi-step interactions in real-world scenarios. We also emphasize the goal of RecSys is to minimum (all forms of) user costs which may occur at any stage.

Many points discussed here may have been mentioned in previous literature or are common practices in the industry. Our goal, as a perspective paper, is not to provide a comprehensive survey. Instead, we aim to present a cohesive framework for better characterizing RecSys tasks, thereby guiding future academic research toward more meaningful contributions. This also calls for more details to be included in datasets released by the industry, as offline evaluations are particularly important for academic researchers who do not have access to A/B testing.

Ultimately, this paper seeks to clarify the relationship between task formulation, solution development, and evaluation (more specifically offline evaluation). By fostering a more structured and comprehensive understanding of these key elements, we hope to provide valuable insights for both new and experienced researchers, contributing to the continued advancement of the field of recommender systems across diverse real-world domains.

#### References

- Gediminas Adomavicius and Alexander Tuzhilin. 2005. Toward the Next Generation of Recommender Systems: A Survey of the State-of-the-Art and Possible Extensions. *IEEE TKDE* 17, 6 (2005), 734–749. https://doi.org/10.1109/TKDE.2005.99
- [2] Ashton Anderson, Ravi Kumar, Andrew Tomkins, and Sergei Vassilvitskii. 2014. The dynamics of repeat consumption. In WWW. 419–430.
- [3] Mozhdeh Ariannezhad, Sami Jullien, Ming Li, Min Fang, Sebastian Schelter, and Maarten de Rijke. 2022. ReCANet: A repeat consumption-aware neural network for next basket recommendation in grocery shopping. In ACM SIGIR. 1240–1250.
- [4] Joeran Beel, Lukas Wegmeth, Lien Michiels, and Steffen Schulz. 2024. Informed Dataset Selection with 'Algorithm Performance Spaces'. In ACM RecSys. ACM, 1085–1090. https://doi.org/10.1145/3640457.3691704
- [5] Jonathan L. Herlocker, Joseph A. Konstan, Loren G. Terveen, and John Riedl. 2004. Evaluating collaborative filtering recommender systems. ACM TOIS 22, 1 (2004), 5–53. https://doi.org/10.1145/963770.963772

- [6] Veronika Ivanova, Oleg Lashinin, Marina Ananyeva, and Sergey Kolesnikov. 2023. RecBaselines2023: a new dataset for choosing baselines for recommender models. In Workshop on Bibliometric-enhanced Information Retrieval (CEUR Workshop Proceedings, Vol. 3617). CEUR, 52–65. ISSN: 1613-0073.
- [7] Dietmar Jannach and Markus Zanker. 2024. A Survey on Intent-aware Recommender Systems. ACM TORS 3, 2, Article 23 (Dec. 2024), 32 pages. https://doi.org/10.1145/3700890
- [8] Yitong Ji, Aixin Sun, Jie Zhang, and Chenliang Li. 2020. A Re-visit of the Popularity Baseline in Recommender Systems. In ACM SIGIR. 1749–1752. https://doi.org/10. 1145/3397271.3401233
- [9] Yitong Ji, Aixin Sun, Jie Zhang, and Chenliang Li. 2022. Do Loyal Users Enjoy Better Recommendations?: Understanding Recommender Accuracy from a Time Perspective. In ACM ICTIR. 92–97. https://doi.org/10.1145/3539813.3545124
- [10] Yitong Ji, Aixin Sun, Jie Zhang, and Chenliang Li. 2023. A Critical Study on Data Leakage in Recommender System Offline Evaluation. ACM TOIS 41, 3 (2023), 75:1–75:27. https://doi.org/10.1145/3569930
- [11] Ori Katz, Oren Barkan, Noam Koenigstein, and Nir Zabari. 2022. Learning to Ride a Buy-Cycle: A Hyper-Convolutional Model for Next Basket Repurchase Recommendation. In ACM RecSys. 316–326.
- [12] Jon M. Kleinberg, Sendhil Mullainathan, and Manish Raghavan. 2022. The Challenge of Understanding What Users Want: Inconsistent Preferences and Engagement Optimization. In ACM Conference on Economics and Computation (EC). https://doi.org/10.1145/3490486.3538365
- [13] Yehuda Koren, Robert M. Bell, and Chris Volinsky. 2009. Matrix Factorization Techniques for Recommender Systems. *Computer* 42, 8 (2009), 30–37. https: //doi.org/10.1109/MC.2009.263
- [14] Jiayu Li, Aixin Sun, Weizhi Ma, Peijie Sun, and Min Zhang. 2024. Right Tool, Right Job: Recommendation for Repeat and Exploration Consumption in Food Delivery. In ACM RecSys. 643–653. https://doi.org/10.1145/3640457.3688119
- [15] Zihao Li, Chao Yang, Yakun Chen, Xianzhi Wang, Hongxu Chen, Guandong Xu, Lina Yao, and Michael Sheng. 2025. Graph and Sequential Neural Networks in Session-based Recommendation: A Survey. ACM Comput. Surv. 57, 2 (2025), 40:1–40:37. https://doi.org/10.1145/3696413
- [16] Victoria López, Alberto Fernández, Salvador García, Vasile Palade, and Francisco Herrera. 2013. An insight into classification with imbalanced data: Empirical results and current trends on using data intrinsic characteristics. *Inf. Sci.* 250 (2013), 113–141. https://doi.org/10.1016/J.INS.2013.07.007
- [17] Duncan C. McElfresh, Sujay Khandagale, Jonathan Valverde, John Dickerson, and Colin White. 2022. On the Generalizability and Predictability of Recommender Systems. In *NeurIPS*.
- [18] Liwei Pan, Weike Pan, Meiyan Wei, Hongzhi Yin, and Zhong Ming. 2024. A Survey on Sequential Recommendation. arXiv:2412.12770 [cs.IR]
- [19] Shigang Quan, Shui Liu, Zhenzhe Zheng, and Fan Wu. 2023. Enhancing Repeat-Aware Recommendation from a Temporal-Sequential Perspective. In ACM CIKM. 2095–2105.
- [20] Markus Reiter-Haas, Emilia Parada-Cabaleiro, Markus Schedl, Elham Motamedi, Marko Tkalcic, and Elisabeth Lex. 2021. Predicting music relistening behavior using the ACT-R framework. In ACM RecSys. 702–707.
- [21] Steffen Rendle, Christoph Freudenthaler, Zeno Gantner, and Lars Schmidt-Thieme. 2009. BPR: Bayesian personalized ranking from implicit feedback. In Conference on Uncertainty in Artificial Intelligence. AUAI Press, 452–461.
- [22] Francesco Ricci, Lior Rokach, and Bracha Shapira. 2011. Introduction to Recommender Systems Handbook. In *Recommender Systems Handbook*, Francesco Ricci, Lior Rokach, Bracha Shapira, and Paul B. Kantor (Eds.). Springer, 1–35. https://doi.org/10.1007/978-0-387-85820-3\_1
- [23] Andrew I. Schein, Alexandrin Popescul, Lyle H. Ungar, and David M. Pennock. 2002. Methods and metrics for cold-start recommendations. In ACM SIGIR. ACM, 253–260. https://doi.org/10.1145/564376.564421
- [24] Faisal Shehzad, Maurizio Ferrari Dacrema, and Dietmar Jannach. 2025. A Worrying Reproducibility Study of Intent-Aware Recommendation Models. arXiv:2501.10143 [cs.IR] https://arxiv.org/abs/2501.10143
- [25] Aixin Sun. 2023. Take a Fresh Look at Recommender Systems from an Evaluation Standpoint. In ACM SIGIR. 2629–2638. https://doi.org/10.1145/3539618.3591931
- [26] Aixin Sun. 2024. Beyond Collaborative Filtering: A Relook at Task Formulation in Recommender Systems. SIGWEB Newsl. 2024, Spring (2024), 1–11. https: //doi.org/10.1145/3663752.3663756
- [27] Kosetsu Tsukuda and Masataka Goto. 2020. Explainable recommendation for repeat consumption. In ACM RecSys. 462-467.
- [28] Chenyang Wang, Min Zhang, Weizhi Ma, Yiqun Liu, and Shaoping Ma. 2019. Modeling item-specific temporal dynamics of repeat consumption for recommender systems. In WWW. 1977–1987.
- [29] Eva Zangerle and Christine Bauer. 2022. Evaluating Recommender Systems: Survey and Framework. ACM Comput. Surv. 55, 8, Article 170 (Dec. 2022), 38 pages. https://doi.org/10.1145/3556536
- [30] Kuan Zou, Aixin Sun, Xuemeng Jiang, Yitong Ji, Hao Zhang, Jing Wang, and Ruijie Guo. 2024. Hesitation and Tolerance in Recommender Systems. CoRR abs/2412.09950 (2024). https://doi.org/10.48550/ARXIV.2412.09950 arXiv:2412.09950