# COMI-LINGUA: Expert Annotated Large-Scale Dataset for Multitask NLP in Hindi-English Code-Mixing

Rajvee Sheth, Himanshu Beniwal, Mayank Singh

LINGO, Indian Institute of Technology Gandhinagar, India Correspondence: lingo@iitgn.ac.in

#### Abstract

The rapid growth of digital communication has driven the widespread use of code-mixing, particularly Hindi-English, in multilingual communities. Existing datasets often focus on romanized text, have limited scope, or rely on synthetic data, which fails to capture realworld language nuances. Human annotations are crucial for assessing the naturalness and acceptability of code-mixed text. To address these challenges, We introduce COMI-LINGUA, the largest manually annotated dataset for code-mixed text, comprising 100,970 instances evaluated by three expert annotators in both Devanagari and Roman scripts. The dataset supports five fundamental NLP tasks: Language Identification, Matrix Language Identification, Part-of-Speech Tagging, Named Entity Recognition, and Translation. We evaluate LLMs on these tasks using COMI-LINGUA, revealing limitations in current multilingual modeling strategies and emphasizing the need for improved code-mixed text processing capabilities. COMI-LINGUA is publically availabe at: https://huggingface.co/ datasets/LingoIITGN/COMI-LINGUA.

#### 1 Introduction

Code-mixing, the use of multiple languages within the same occurrence, is increasingly common in multilingual societies, particularly on social media platforms Jamatia et al. (2020); Srivastava and Singh (2020). More than half of the world's population speaks two or more languages and widely uses the blended version of both in their writings (Grosjean, 2021). Code-mixed text, specifically Hinglish, is widely used on social media platforms. The fusion of Hindi-English languages presents a unique script with significant computational challenges due to its orthographic complexity (Bali et al., 2014; Takawane et al., 2023; Thara and Poornachandran, 2018). A distinctive characteristic of such text is the frequent alternation between




Figure 1: Evaluating LLMs' capabilities to handle Hinglish codemixed text: Predictions from the two *open-source* and three *closed-source* models on the given prompts.

Devanagari and Roman scripts, with speakers employing romanized Hindi lexemes and Devanagariscripted English tokens within single utterances. For instance, in "Kal mujhe ऑफिस जाना hai, but ट्राफिक will be an issue.", Hindi ("कल मुझे") is intertwined with English, and some English words like "office" and "traffic" are written in Devanagari script. (English Translation: "Tomorrow I have to go to the office, but traffic will be an issue.")

**Research Gap** Analysis of code-mixed corpora provides critical insights into contemporary multilingual communication patterns, particularly regarding sentiment expression across linguistic contexts. However, as noted by Hovy and Lavid (2010), developing high-quality annotated resources requires substantial manual effort, temporal investment, domain expertise, and linguistic understanding. Existing Hindi-English code-mixed datasets exhibit several critical limitations: (1) Predominant focus on romanized text, failing to capture script variation patterns Begum et al. (2016); Bali et al. (2014); Srivastava et al. (2020), (2) Limited scope and scale of annotated resources. Srivastava and Singh (2021a); Kumar et al. (2018); Tiwari et al. (2024); Kartik et al. (2024), (3) Insufficient coverage of diverse NLP tasks within unified datasets, making it difficult to evaluate models' performance across different linguistic capabilities simultaneously Aguilar et al. (2020); Khanuja et al. (2020); Bohra et al. (2018); Khanuja et al. (2020); Bohra et al. (2018); Khanuja et al. (2020), and (4) Over-reliance on synthetic data generation methods rather than manually curated data for human annotation Chatterjee et al. (2022); Srivastava and Singh (2021c); Kartik et al. (2024); Sravani and Mamidi (2023).

**Contributions**: To address these limitations, we present a novel comprehensive dataset **COMI-LINGUA** (**CO**de-**MI**xing and **LING**uistic Insights on Natural Hinglish Usage and Annotation)<sup>1</sup>. that advances Hindi-English code-mixing research with key contributions:

- The dataset encompasses both Devanagari and Roman scripts, capturing real-world codemixing patterns observed in textual modality.
- With 1,00,970 manually annotated instances, covering five key NLP tasks: Matrix and Language identification, POS tagging, NER and Translation, establishing a comprehensive benchmark for multilingual systems.
- The dataset covers diverse domains, including social media, news, and informal conversations, ensuring broad linguistic and contextual diversity for real-world applicability.

Table 1 presents a curated selection of existing datasets for Hindi-English code-mixed NLP tasks, highlighting their size, script type, annotation quality, and sources. The proposed dataset (COMI-LINGUA) stands out due to its extensive coverage of fundamental NLP tasks, diverse domain representation, and a total of 1,00,970 annotated instances, each labeled by three annotators.

The annotation process presents significant methodological challenges, including maintaining data consistency, efficient management of largescale datasets, and mitigating annotator biases. To validate our annotation quality and establish benchmarks, we compared human annotator performance with predictions from state-of-the-art multilingual LLMs and existing NLP libraries to establish baseline performance metrics. This analysis serves two purposes: it substantiates the reliability of our annotations while providing insights into current technological capabilities and limitations in processing code-mixed text. Our evaluation revealed varying performance patterns in LLMs when handling codemixed text, particularly highlighting challenges in script adaptation, entity recognition, and model robustness.

The resulting dataset contributes significantly to code-mixing research, offering a comprehensive resource for developing and evaluating NLP systems capable of processing mixed-script Hindi-English text with extensibility to other language pairs.

## 2 Related Work

Code-mixing, the interleaving of multiple languages within a single conversation or text, presents significant challenges for Natural Language Processing tasks (Srivastava and Singh, 2021a). This phenomenon is particularly complex in language pairs such as Hindi and English, where fundamental differences in grammar and script systems create additional layers of complexity, as demonstrated by Bali et al. (2014). The lack of high-quality, annotated code-mixed data is a major bottleneck, as collecting and annotating such data is time-consuming and expensive Srivastava and Singh (2021a).

Previous research has laid the groundwork across multiple key areas, with language identification emerging as a fundamental task. Various techniques have been proposed to effectively detect language switches within code-mixed text, contributing to advancements in this domain (Shekhar et al., 2020; Singh et al., 2018a; Gundapu and Mamidi, 2018; Molina et al., 2016).

Several annotated corpora have been created for part-of-speech tagging, including a Twitter corpus (Singh et al., 2018b), a dataset from Facebook forums (Vyas et al., 2014). Pratapa et al. (2018) introduced an annotated dataset of synthetically generated code-mixed text to evaluate bilingual word embedding techniques and Sequiera et al. (2015) created an annotated corpus to explore various machine learning approaches for POS tagging. Additionally, Chatterjee et al. (2022) introduced PACMAN, a synthetically generated POS-tagged dataset of over 50,000 samples that achieved stateof-the-art performance.

<sup>&</sup>lt;sup>1</sup>Dataset is available here: https://huggingface.co/ datasets/LingoIITGN/COMI-LINGUA

Task	Data Source (Hi-En)	Dataset Size	Script	QA	Annotators/Models
	Facebook (Bali et al., 2014)	1,062	R & D	Yes	3
•	Twitter (Singh et al., 2018a)	2,079	R	Yes	3
~	Twitter (Swami et al., 2018)	5,250	R	Yes	Not mentioned
ΓD	Twitter (Mave et al., 2018)	5,567	R	Yes	3
	Facebook, Twitter, WhatsApp (Veena et al., 2018)	3,071	R	No	Embedding Model
	Twitter (Joshi and Joshi, 2022)	18,461	R	No	Not mentioned
	Twitter, YouTube, News (Ours)	23,541	R & D	Yes	3
	Twitter, Facebook (Sequiera et al., 2015)	628	R & D	No	1
ß	Facebook (Bali et al., 2014)	1,062	R & D	Yes	3
ing:	Twitter, Facebook (Jamatia et al., 2015)	1,106	R	No	2
Та	Twitter (Singh et al., 2018b)	1,190	R	Yes	3
POS Tagging	Synthetically generated (Chatterjee et al., 2022)	51,118	R & D	No	0
Ч	Existing Benchmarks (Kodali et al., 2022)	55,474	R	No	Trained POS tagger
	Twitter, YouTube, News (Ours)	20,684	R & D	Yes	3
ď	Facebook (Bali et al., 2014)	1,062	R & D	Yes	3
	Twitter (Singh et al., 2018a)	2,079	R	Yes	3
NER	Twitter (Bhargava et al., 2016)	2,700	R	No	Supervised algorithm
Z	Twitter (Singh et al., 2018c)	3,638	R	Yes	2
	Tourism, News (Murthy et al., 2022)	108,608	R & D	No	1
	Twitter, YouTube, News (Ours)	15,328	R & D	Yes	3
	TED Talks, News, Wikipedia (Kartik et al., 2024)	2,787	R & D	Yes	2
on	Twitter, Facebook (Srivastava and Singh, 2021b)	3,952	R & D	Yes	5
lati	Social Media (Dhar et al., 2018)	6,096	R	Yes	4
ans	Twitter, Facebook (Srivastava and Singh, 2020)	13,738	R	Yes	54 (400 instances)
Translation	Existing Benchmarks (Kunchukuttan et al., 2017)	14,95,854	R & D	No	PBSMT, NMT
	Twitter, YouTube, News (Ours)	22,541	R & D	Yes	2
	Twitter, Facebook (Sequiera et al., 2015)	628	R & D	No	1
ΓI	Facebook (Bali et al., 2014)	1,062	R & D	Yes	3
MLI	Social Media (Dhar et al., 2018)	6,096	R	Yes	4
	Twitter, YouTube, News (Ours)	18,876	R & D	Yes	3

Table 1: Comprehensive Comparison of Existing Datasets for Hindi-English Code-Mixing NLP Tasks, including the proposed dataset. NLP tasks covered in the dataset include Language Identification (LID), Part-of-speech (POS) tagging, Named Entity Recognition (NER) and Matrix Language Identification (MLI). (R) and (D) denote Roman and Devanagari scripts, respectively, while QA represents annotations by Qualified Annotators. *Takeaway*: The COMI-LINGUA dataset comprises 1,00,970 manually annotated instances by three annotators across five NLP tasks.

Researchers have explored various approaches for Named Entity Recognition. Dowlagar and Mamidi (2022) leveraged multilingual data, achieving a 6% improvement over baseline models, while Ansari et al. (2019) developed cross-script Hindi-English NER datasets using Wikipedia. Additionally, meta-embeddings and transformer-based models have been applied to Indian code-mixed corpora (Priyadharshini et al., 2020), significantly enhancing NER performance.

Machine translation for code-mixed content is a growing area of research. Dhar et al. (2018) and Srivastava and Singh (2020) contributed to creating parallel corpora for Hindi-English code-mixed sentences. More recently, Hegde and Lakshmaiah (2022) introduced MT models leveraging transliteration and pseudo-translation techniques, achieving competitive rankings in the MixMT shared task at WMT 2022.

Benchmark datasets and evaluation frameworks have been instrumental in advancing the field. Aguilar et al. (2020) developed LinCE as a growing benchmark for code-switched NLP, incorporating eleven corpora across four language pairs and multiple tasks. Similarly, Khanuja et al. (2020) introduced GLUECoS, demonstrating that multilingual models fine-tuned on code-switched data outperform cross-lingual models in various NLP tasks. Vijay et al. (2018) introduced a Hindi-English codemixed Twitter corpus with emotion, source language, and causal language annotations. Nayak and Joshi (2022) developed L3Cube-HingCorpus, which demonstrated improvements through specialized pre-trained BERT models. Building on this, recent work has expanded into emotion and sentiment analysis. Ghosh et al. (2023) developed an emotion-annotated dataset based on SentiMix, further advancing sentiment analysis in code-mixed contexts.

## **3** Dataset and Annotation

To ensure high-quality annotations, we follow a structured five-step framework that systematically processes raw data into a well-annotated dataset:

#### 3.1 Raw dataset curation

We curated raw data by scraping public platforms across diverse categories - news, politics, entertainment, social events, sports, and information - focusing on Indian subcontinent content. The dataset was expanded with code-mixed Hinglish data sourced from HuggingFace<sup>2</sup> and existing research works (Srivastava and Singh, 2020; Gupta et al., 2023; Singh et al., 2018c). Noting the scarcity of mixed Devanagari-Roman script samples in existing datasets, we collected additional data to build a more comprehensive Hindi-English code-mixing corpus.

The scraping process collected high-quality data from diverse sources article-wise. **News sources** included NDTV<sup>3</sup>, ABP News<sup>4</sup>, Zee News<sup>5</sup>, News18<sup>6</sup>, TV9<sup>7</sup>, and Aaj Tak.<sup>8</sup> **Digital platforms** like X (formerly "Twitter")<sup>9</sup> and YouTube<sup>10</sup> provided realtime discussions. **Political channels** from INC, BJP, and AAP were included, along with **official sources** such as *Mann Ki Baat*<sup>11</sup> and *Press Information Bureau* (*PIB*)<sup>12</sup>.

Each scraped article was carefully stored in structured CSV format. The curated data was passed through Regex-based quality checkers to remove noisy text such as advertisements, HTML tags, footers, or other irrelevant website-related content. The articles were then segmented into sentences, and their CMI index was calculated to assess the quality of code-mixing. A threshold of CMI greater than 9 was applied to select high-quality code-mixed data for further analysis.

#### 3.2 Dataset Processing

The preprocessing pipeline involves noise reduction to ensure the quality and relevance of the corpus. To create a clean and neutral dataset, we removed duplicate instances, hate speech, and abusive content. Sentences containing offensive or inappropriate language were identified and removed using the profanity filtering available in thisandagain<sup>13</sup> and Hate-Speech-Detection-in-Hindi<sup>14</sup>. Furthermore, during token-level preprocessing, sentences with a length of fewer than five tokens were removed to eliminate non-informative, short tokens such as fragments, abbreviations, and noisy text, which often result from typing errors, emojis, or filler words. For instance '#GuessTheSong', '\*during dinner\*', '@enlightenedme bas ek hi' were removed from the dataset.

Finally, the data underwent an additional round of refinement during the manual annotation phase, where annotators specifically eliminated sentences that were undetected by all the preprocessing steps and those instances were not annotated.

#### 3.3 Data Annotation

For annotating the Hindi-English Code-Mixed Corpus, we utilized COMMENTATOR (Sheth et al., 2024), a robust annotation framework explicitly designed to handle multilingual code-mixed text.

Our annotation team comprises three graduatelevel experts fluent in English and Hindi, with extensive experience navigating social media platforms. They possess strong programming skills and are proficient in using version control systems, ensuring efficient and reliable annotation processes.

We select a diverse set of tasks, including foundational ones that are well-explored with high accuracy and more complex challenges that have received minimal attention from the research commu-

<sup>&</sup>lt;sup>2</sup>https://huggingface.co/datasets/pardeep/

youtube-vidoes-transcripts-hindi-english/
 <sup>3</sup>https://ndtv.in/

<sup>&</sup>lt;sup>4</sup>https://www.abplive.com/

<sup>&</sup>lt;sup>5</sup>https://zeenews.india.com/hindi

<sup>&</sup>lt;sup>6</sup>https://hindi.news18.com/

<sup>&</sup>lt;sup>7</sup>https://www.tv9.com/

<sup>&</sup>lt;sup>8</sup>https://www.aajtak.in/

<sup>&</sup>lt;sup>9</sup>https://x.com/

<sup>&</sup>lt;sup>10</sup>https://www.youtube.com/

<sup>&</sup>lt;sup>11</sup>https://www.narendramodi.in/mann-ki-baat

<sup>&</sup>lt;sup>12</sup>https://pib.gov.in/

<sup>&</sup>lt;sup>13</sup>https://github.com/thisandagain/

washyourmouthoutwithsoap/blob/develop/README.md
 <sup>14</sup>https://github.com/victorknox/

Hate-Speech-Detection-in-Hindi/blob/main/README.
md

nity. Annotators are provided with some guidelines that include practical examples to familiarize them with the Annotation tasks.

During the manual data annotation stage, the following tasks were performed for each curated gold sentence:

A) Language Identification: For the Language Identification (LID) task, each word in the dataset was assigned one of three labels: English ('en'), Hindi ('hi'), or Unidentified ('un'). Initial language predictions were made using the Microsoft API<sup>15</sup>, which provided pre-assigned tags.

Sentence: Made in इंडिया ki ना केवल ग्लोबल डिमांड ho, बल्कि ग्लोबल acceptance ho हमे ये सुनिश्चित karna hai.

Language tags: en en en hi hi hi en en hi hi en en un hi hi hi hi hi hi un

**English Translation:** Made in India should not only have global demand but also global acceptance; we must ensure this.

B) Matrix Language Identification: Each sentence is annotated with a Matrix Language (MLI) tag that identifies the primary language that governs the sentence's grammatical structure. In code-mixed text, even when multiple languages are present, one language often dominates in terms of syntax and grammar.

Sentence: SBI ने चालू कारोबारी साल में Uttar Pradesh में 550 crore रुपए का गोल्ड लोन देने का लक्ष्य रखा है।

#### Matrix language: Hindi

**English Translation:** SBI has set a target of disbursing gold loans worth 550 crore rupees in Uttar Pradesh in the current financial year.

Sentence: India's automation and design expert pool is vast, और ज़्यादातर Global कंपनियों के इंजीनियरिंग सेंटर भी भारत में हैं।

# Matrix language: English

**English Translation:** India's automation and design expert pool is vast, and most global companies engineering centers are also in India.

C) *Named Entity Recognition:* In the NER annotation task, named entities were identified and tagged within the sentences to facilitate

Entity Type	Description
Person	Names of individuals
Place	Non-political physical locations
Organization	Institutions or companies
Date/Time	Temporal expressions (e.g., dates)
GPE	Geo-Political Entities
Hashtags	Words prefixed by '#'
Mentions	User mentions prefixed by '@'
Emoji	Emoticons conveying emotions

Table 2: Named entity types and their descriptions in our dataset.

detailed entity-level analysis in code-mixed Hindi-English text.

**Named Entity Categories:** The NER tags tags were generated using the CodeSwitch NLP library<sup>16</sup> was utilized to extract entities, focusing on sentences containing at least four named entities.

Sentence: Kendra Spade (Michaela Mc-Cormick) एक American Film Actress हैं और इनका जन्म 11 May 1998 को New Orleans, Louisiana, United States में हुआ था।

Named Entities: 'Kendra Spade (Michaela McCormick)': Person, '11 May 1998': Date, 'New Orleans', 'Louisiana': Place, 'United States': GPE.

**English Translation:** Kendra Spade (Michaela McCormick) is an American film actress, and she was born on May 11, 1998, in New Orleans, Louisiana, United States.

D) Part-of-Speech Tagging: For the Part-of-Speech tagging task, each word in the codemixed dataset was assigned a POS tag from the Universal POS tagset proposed by (Singh et al., 2018b). This tagset includes labels that are language independent and can be applied to both Hindi and English tokens within a code-mixed sentence. The tagset used is as follows:

# NOUN, PROPN, VERB, ADJ, ADV, ADP, PRON, DET, CONJ, PART, PRON\_WH, PART\_NEG, NUM, X

The POS tags predictions were assigned using the CodeSwitch NLP library<sup>17</sup>. Sentence: मीराबाई चानू ने 21st Commonwealth Games में India के लिए first Gold medal जीता था।

<sup>&</sup>lt;sup>15</sup>https://github.com/microsoft/LID-tool

<sup>&</sup>lt;sup>16</sup>https://github.com/sagorbrur/codeswitch <sup>17</sup>https://github.com/sagorbrur/codeswitch

POS tags: 'मीराबाई': PROPN, 'चानू': PROPN, 'ने': PART, '21st': NUM, 'Commonwealth': PROPN, 'Games': PROPN, 'मैं ': ADP, 'India': PROPN, 'के': ADP, 'लिए': ADP, 'first': ADJ, 'Gold': NOUN, 'medal': NOUN, 'जीता': VERB, 'था': VERB, 'l': X

**English Translation:** Mirabai Chanu won the first gold medal for India in the 21st Commonwealth Games.

E) Translation: In the translation task, we focus on constructing parallel monolingual sentences in both Romanized Hindi and Devanagari Hindi, along with their corresponding English translations.

HINGLISH Sentence: दिल्ली स्थित INDIAN NAVY हेडक्वार्टर और वेस्टर्न नेवल कमांड ने मिलकर ऑपरेशन के व्यूह की रचना की है।

**English Translation:** The Indian Navy headquarters located in Delhi and the Western Naval Command have jointly orchestrated the formation of the operation.

Romanized Hindi Translation: Dilli sthit Indian Navy headquarters aur Western Naval Command ne milkar operation ke vyuh ki rachna ki hai .

Devnagari Hindi Translation: दिल्ली स्थित इंडियन नेवी हेडक्वार्टर और वेस्टर्न नेवल कमांड ने मिलकर ऑपरेशन के व्यूह की रचना की है।

The Initial translation predictions were generated using the Llama 3.3 LLM  $^{18}$ .

## 3.4 Annotation Analysis

The annotation quality was assessed using the Fleiss Kappa (Fleiss, 1971) score to measure interannotator agreement (IAA) (Hallgren, 2012), ensuring the reliability and consistency of the annotations. Additionally, the degree of code-mixing in the annotated text was analyzed through the Code-Mixing Index (CMI) (Das and Gambäck, 2014), providing valuable insights into the linguistic diversity and complexity within the dataset.

We implemented a comprehensive annotation methodology to ensure high-quality and consistent annotations.

• All instances were independently annotated by three expert bilingual annotators, ensuring

Task	Raw data	Filtered data	Fleiss' Kappa		
LID	25,583	23,541	0.849		
MLI	20,918	18,876	0.976		
POS	22,453	20,684	0.790		
NER	16,648	15,328	0.878		
Translation	24,425	22,541	-		

Table 3: Inter-annotator Agreement (Fleiss' Kappa) and corpus Statistics across different Annotation Tasks. IAA was not calculated for the translation task.

high-quality labels, with Fleiss' Kappa scores greater than **0.780** across all tasks, indicating strong IAA, as shown in Table 3.

- We developed and implemented a structured annotation protocol with detailed guidelines to address script variations and ambiguous cases, and context-dependent language transitions, ensuring consistent and accurate annotations.
- The curated corpus maintains an average CMI score  $\geq 18$  across all tasks, ensuring a high degree of code-mixing.

## 3.5 Annotation Refinement:

The data underwent further refinement during the annotation phase to ensure quality and consistency. Annotators were instructed to provide feedback on sentences that should be excluded from the dataset (see Table 5 in Appendix A.1).

These included:

- 1. Monolingual English content and text written entirely in Devanagari script, as these did not represent genuine code-mixed instances.
- 2. Sentences that lacked relevant linguistic tags or named entities were devoid of meaningful content, or combined multiple instances into one were excluded from the analysis.
- 3. Instances containing languages other than Hindi and English, as these were outside the scope of this study.

This iterative refinement approach, driven by annotator feedback, was essential in maintaining corpus integrity and ensuring that the dataset contained only meaningful and high-quality Hindi-English code-mixed text.

#### 4 The Proposed dataset

The proposed dataset spans a variety of domains, including news, politics, and sports, offering a

<sup>&</sup>lt;sup>18</sup>https://github.com/meta-llama/llama-models/ blob/main/models/llama3\_3/MODEL\_CARD.md

Model/Library	LID		POS		NER			MLI				
	P	R	$F_1$									
claude-3.5	93.0	92.7	92.5	81.4	79.2	79.3	86.0	84.8	84.6	98.8	83.5	90.0
gpt-4o	92.3	92.4	92.2	81.6	78.0	78.9	76.6	74.9	74.9	98.4	98.0	98.2
gemini-1.5-Flash	80.2	76.5	74.4	72.9	64.6	68.0	20.3	20.4	20.1	48.9	39.8	41.0
LLaMA-3.3-instruct	90.3	89.6	89.3	85.1	84.0	84.1	79.2	78.6	77.7	98.8	97.8	98.2
mistral-instruct	72.1	70.0	70.1	77.3	66.9	69.8	64.8	49.8	56.0	98.3	88.1	92.7
Microsoft LID	80.2	76.5	74.4	-	-	-	-	-	-	-	-	-
codeswitch	-	-	-	89.1	87.8	88.2	81.6	83.1	81.2	-	-	-

Table 4: Performance metrics of test sets from the COMI-LINGUA dataset for various models and traditional NLP libraries across different NLP tasks: Language Identification (LID), Part-of-speech (POS) tagging, Named Entity Recognition (NER) and Matrix Language Identification (MLI). P, R and F1 denote Precision, Recall and F1-score respectively. '-' indicates that the task is not supported by the respective tool.

comprehensive view of Hindi-English code-mixing across different sectors. This diversity enables a deeper exploration of code-mixed language in both formal and informal contexts within the Indian subcontinent.

## 4.1 Corpus Statistics

The raw dataset underwent multiple stages of refinement across all annotation tasks, including the removal of duplicates, rigorous hate speech filtering, incorporating annotator feedback to exclude unsuitable instances. The raw and filtered data values for each task are provided in Table 3.

The annotation process included five tasks, each requiring different levels of manual review and refinement.

- LID: Annotators reviewed and corrected incorrect initial predictions, ensuring precise and reliable annotations. A total of 404,529 tokens were processed for LID task and, on average, each annotator modified approximately 95,325 tokens for the entire corpus.
- 2. MLI: For this task, annotator was supposed to determine the matrix language. No initial predictions were provided, and the entire corpus consisting 18,876 sentences was manually annotated.
- 3. **POS:** Annotators processed a total of 427,941 tokens for the POS tagging task. Out of these, they modified 63,002 tokens to ensure accurate annotations.
- NER: Annotators manually reviewed and refined the predicted tags, correcting misidentified entities. Out of 52,262 tokens, each annotator modified approximately 48,930 tokens.

5. **Translation:** Annotators manually reviewed and refined the predicted translations and the entire corpus consisting 22,541 sentences was manually updated for three separate translations.

# 5 Evaluating LLMs for Code-Mixing

The rise of Large Language Models (LLMs) has brought both opportunities and challenges in processing code-mixed text. While these models excel in monolingual settings (Brown et al., 2020), their effectiveness in handling code-mixed content remains under-explored. Zeng (2024) demonstrated the benefits of LLM-powered data augmentation for sentiment analysis, while Lee et al. (2024) introduced COMMIT, a framework adapting Englishcentric LLMs for low-resource language question answering through specialized code-mixing techniques.

Despite extensive evaluation of monolingual tasks, LLMs lack a comprehensive assessment of Hindi-English code-mixed text across multiple NLP tasks. To bridge this gap, we evaluate using standard metrics, including precision, recall and F1-score.

## 5.1 Task-Specific Evaluation

Our experiment aimed to assess the performance of various LLMs in handling code-mixed Hindi-English instances across five NLP task configurations. We evaluate the capabilities LLMs, both *open-source* and *closed-source* and traditional NLP libraries, on a diverse set of code-mixed samples. *Open-source* models include mistral-instruct (7B, Jiang et al. (2023)) and llama-3.3-instruct (70B, Touvron et al. (2023)) and three *closedsource* gpt-40 (Achiam et al. (2023), claude-3.5, and gemini-1.5-flash (Anil et al. (2023)). For the open-source models, we utilized the Krutrim platform<sup>19</sup>, while closed-source models were accessed through their respective official APIs.

# 5.2 Prompting LLMs

Our prompting method involves providing a consistent set of instructions across all NLP tasks to standardize model outputs. Each prompt includes task-specific guidelines, tagging rules, and formatting constraints. The prompts are refined iteratively to handle code-mixed text better.

**RQ1: How effectively can LLMs process and analyze code-mixed Hindi-English text across various NLP tasks?** To ensure a comprehensive evaluation, we employed the following methodology:

We randomly sampled 3,000 to 5,000 **COMI-LINGUA** instances with **CMI scores**  $\geq$  **12** to ensure script diversity. As demonstrated by (Srivastava and Singh, 2021a), data with moderate to high CMI scores ( $\geq$  12) captures natural code-mixing phenomena, substantial language alternation patterns and meaningful code-mixing behavior between languages.

Our experiments reveal several key observations regarding the performance of LLMs in handling code-mixed text:

**Key Observations:** The performance metrics in Table 4 highlight notable strengths and weaknesses of different LLMs in processing code-mixed Hinglish text.

- Challenges in handling Devanagari Script: All models struggled to accurately analyze "कोड" and "ओलंपिक" which are English borrowings written in Devanagari script and misclassified them as Hindi instead of English.
- Sentence truncation: Models frequently failed to maintain consistent output length, often truncating longer code-mixed sequences, leading to incomplete responses and loss of contextual meaning.
- **Duplicate generations:** For *open-source* models like gemini-1.5-flash and mistral-instruct, we observed repeated phrase patterns, where the models generated redundant or overly similar sequences within the same response.

- Subjectivity in responses: Models like gemini-1.5-flash and mistral-instruct sometimes generated explanations instead of extracting the required information from the given prompt. For instance, when asked to identify the matrix language, mistral-instruct responded: "Based on the given text, the overall matrix language is 'h'."
- Copying from the given prompt: LLMs were provided with clear instructions to identify the given entities or extract relevant tags from the given code-mixed sentence. However, in some cases, they exhibited a tendency to directly replicate input patterns, failing to apply meaningful analysis or interpretation.
- Failure to interpret sentences with high script variability: For some instances, all models failed to generate any output for sentences with higher variance in grammar and mixed-script usage. This issue was more prevalent in the gemini-1.5-flash and mistral-instruct models.

RQ2: What are the challenging NLP tasks in code-mixed text, and how can LLMs be improved to address them? LLMs demonstrate varying performance across different NLP tasks. While they achieve high precision in basic NLP tasks like LID and MLI, their performance in POS tagging and NER remains relatively low, revealing challenges in understanding dynamics such as linguistic ambiguity, and script variability. For instance, mistral-instruct mislabeled "बॉलीवुड" as an ORGANISATION and not X.

One major limitation is that these models are not explicitly trained to on code-mixed Hindi-English data, particularly from the Indian subcontinent. As a result, they often misclassify words, fail to recognize entities correctly, or even hallucinate responses.

By leveraging the proposed dataset (COMI-LINGUA), these models can be fine-tuned to improve their accuracy, better handle structural complexity, and enhance their overall reliability in extracting meaningful linguistic information.

**Data Post-Processing:** Prior to calculating performance metrics, post-processing steps addressed key challenges by filtering truncated responses, removing duplicates, and cleaning copied content while using regex quality checkers.

<sup>&</sup>lt;sup>19</sup>https://cloud.olakrutrim.com/

#### 6 Conclusion and Future Directions

An analysis of the post-processed results in Table 4 reveals varying performance across models and tasks. Proprietary models (claude-3.5 and gpt-40) consistently outperformed open-source alternatives, with claude-3.5 achieving the highest F1 scores in LID (92.5) and NER (84.6), while llama-3.3-instruct and gpt-40 led in MLI (98.2). Tasks like NER and POS tagging showed relatively lower performance across all models, whereas the codeswitch library outperformed all models in POS tagging. This highlights the need for further improvements in handling code-mixed text with LLMs. Future plans include expanding dataset curation and evaluating models on additional tasks such as translation, spelling correction, normalization, and sentiment analysis. These benchmark will serve as a valuable resource for refining and assessing existing models.

#### Limitations

While this study provides valuable insights into Hindi-english code-mixed text annotation and processing, several limitations should be noted:

- Language pair specificity: The patterns observed in Hindi-English code-mixed texts may not hold for other language pairs such as Spanish-english due to differences in linguistic structure, cultural context, and usage.
- 2. Demographic considerations: With a smaller, dedicated team of annotators it may introduce bias and limit the the generalizability of acceptability ratings.
- 3. Resource scarcity: Extending this work to other linguistic contexts is challenging due to lack of high-quality corpora the limited availability of models capable of handling diverse code-mixing patterns.

#### **Ethics**

We adhere to ethical guidelines in creating our benchmark dataset and evaluating existing LLMs for Hinglish code-mixing. Our approach ensures responsible data curation, prioritizing annotator well-being, data privacy, and bias mitigation. By upholding ethical standards, we strive to advance NLP research on multilingual code-mixing while promoting fairness, reliability, and linguistic diversity.

#### References

- Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*.
- Gustavo Aguilar, Sudipta Kar, and Thamar Solorio. 2020. LinCE: A centralized benchmark for linguistic code-switching evaluation. In *Proceedings of the Twelfth Language Resources and Evaluation Conference*, pages 1803–1813, Marseille, France. European Language Resources Association.
- Rohan Anil, Sebastian Borgeaud, Jean-Baptiste Alayrac, Jiahui Yu, Radu Soricut, Johan Schalkwyk, Andrew M Dai, Anja Hauth, Katie Millican, et al. 2023. Gemini: a family of highly capable multimodal models. *arXiv preprint arXiv:2312.11805*.
- Mohd Zeeshan Ansari, Tanvir Ahmad, and Md Arshad Ali. 2019. Cross script hindi english ner corpus from wikipedia. In *International Conference on*

Intelligent Data Communication Technologies and Internet of Things (ICICI) 2018, pages 1006–1012. Springer.

- Kalika Bali, Jatin Sharma, Monojit Choudhury, and Yogarshi Vyas. 2014. "I am borrowing ya mixing ?" an analysis of English-Hindi code mixing in Facebook. In Proceedings of the First Workshop on Computational Approaches to Code Switching, pages 116–126, Doha, Qatar. Association for Computational Linguistics.
- Rafiya Begum, Kalika Bali, Monojit Choudhury, Koustav Rudra, and Niloy Ganguly. 2016. Functions of code-switching in tweets: An annotation framework and some initial experiments. In Proceedings of the Tenth International Conference on Language Resources and Evaluation (LREC'16), pages 1644– 1650, Portorož, Slovenia. European Language Resources Association (ELRA).
- Rupal Bhargava, Bapiraju Vamsi, and Yashvardhan Sharma. 2016. Named entity recognition for code mixing in indian languages using hybrid approach. *Facilities*, 23(10).
- Aditya Bohra, Deepanshu Vijay, Vinay Singh, Syed Sarfaraz Akhtar, and Manish Shrivastava. 2018. A dataset of Hindi-English code-mixed social media text for hate speech detection. In *Proceedings of the Second Workshop on Computational Modeling of People's Opinions, Personality, and Emotions in Social Media*, pages 36–41, New Orleans, Louisiana, USA. Association for Computational Linguistics.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, et al. 2020. Language models are few-shot learners. *Advances in neural information processing systems*, 33:1877–1901.
- Arindam Chatterjee, Chhavi Sharma, Ayush Raj, and Asif Ekbal. 2022. Pacman: Parallel codemixed data generation for pos tagging. In *Proceedings of the* 19th International Conference on Natural Language Processing (ICON), pages 234–244.
- Amitava Das and Björn Gambäck. 2014. Identifying languages at the word level in code-mixed indian social media text. In *Proceedings of the 11th International Conference on Natural Language Processing*, pages 378–387.
- Mrinal Dhar, Vaibhav Kumar, and Manish Shrivastava. 2018. Enabling code-mixed translation: Parallel corpus creation and MT augmentation approach. In Proceedings of the First Workshop on Linguistic Resources for Natural Language Processing, pages 131– 140, Santa Fe, New Mexico, USA. Association for Computational Linguistics.
- Suman Dowlagar and Radhika Mamidi. 2022. Cmnerone at semeval-2022 task 11: Code-mixed named entity recognition by leveraging multilingual data. In *Proceedings of the 16th International Workshop on*

Semantic Evaluation (SemEval-2022), pages 1556–1561.

- Joseph L Fleiss. 1971. Measuring nominal scale agreement among many raters. *Psychological bulletin*, 76(5):378.
- Soumitra Ghosh, Amit Priyankar, Asif Ekbal, and Pushpak Bhattacharyya. 2023. Multitasking of sentiment detection and emotion recognition in codemixed hinglish data. *Knowledge-Based Systems*, 260:110182.
- François Grosjean. 2021. *The Extent of Bilingualism*, page 27–39. Cambridge University Press.
- Sunil Gundapu and Radhika Mamidi. 2018. Word level language identification in English Telugu code mixed data. In *Proceedings of the 32nd Pacific Asia Conference on Language, Information and Computation*, Hong Kong. Association for Computational Linguistics.
- Rahul Gupta, Vivek Srivastava, and Mayank Singh. 2023. MUTANT: A multi-sentential code-mixed Hinglish dataset. In *Findings of the Association for Computational Linguistics: EACL 2023*, pages 744– 753, Dubrovnik, Croatia. Association for Computational Linguistics.
- Kevin Hallgren. 2012. Computing inter-rater reliability for observational data: An overview and tutorial. *Tutorials in Quantitative Methods for Psychology*, 8:23–34.
- Asha Hegde and Shashirekha Lakshmaiah. 2022. MUCS@MixMT: IndicTrans-based machine translation for Hinglish text. In *Proceedings of the Seventh Conference on Machine Translation (WMT)*, pages 1131–1135, Abu Dhabi, United Arab Emirates (Hybrid). Association for Computational Linguistics.
- Eduard Hovy and Julia Lavid. 2010. Towards a 'science' of corpus annotation: a new methodological challenge for corpus linguistics. *International journal of translation*, 22(1):13–36.
- Anupam Jamatia, Björn Gambäck, and Amitava Das. 2015. Part-of-speech tagging for code-mixed englishhindi twitter and facebook chat messages. In *Proceedings of the International Conference Recent Advances in Natural Language Processing*, pages 239– 248.
- Anupam Jamatia, Steve Durairaj Swamy, Björn Gambäck, Amitava Das, and Swapan Debbarma. 2020. Deep learning based sentiment analysis in a codemixed english-hindi and english-bengali social media corpus. *International journal on artificial intelligence tools*, 29(05):2050014.
- AQ Jiang, A Sablayrolles, A Mensch, C Bamford, DS Chaplot, D de las Casas, F Bressand, G Lengyel, G Lample, L Saulnier, et al. 2023. Mistral 7b (2023). *arXiv preprint arXiv:2310.06825*.

- Ramchandra Joshi and Raviraj Joshi. 2022. Evaluating input representation for language identification in hindi-english code mixed text. In *ICDSMLA 2020: Proceedings of the 2nd International Conference on Data Science, Machine Learning and Applications*, pages 795–802. Springer.
- Kartik Kartik, Sanjana Soni, Anoop Kunchukuttan, Tanmoy Chakraborty, and Md Shad Akhtar. 2024. Synthetic data generation and joint learning for robust code-mixed translation. In Proceedings of the 2024 Joint International Conference on Computational Linguistics, Language Resources and Evaluation (LREC-COLING 2024), pages 15480–15492.
- Simran Khanuja, Sandipan Dandapat, Anirudh Srinivasan, Sunayana Sitaram, and Monojit Choudhury. 2020. GLUECoS: An evaluation benchmark for code-switched NLP. In Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics, pages 3575–3585, Online. Association for Computational Linguistics.
- Simran Khanujaa, Sandipan Dandapatb, Sunayana Sitarama, and Monojit Choudhurya. 2020. A new dataset for natural language inference from codemixed conversations. In *LREC 2020 Workshop Language Resources and Evaluation Conference 11–16 May 2020*, page 9.
- Prashant Kodali, Anmol Goel, Monojit Choudhury, Manish Shrivastava, and Ponnurangam Kumaraguru. 2022. SyMCoM - syntactic measure of code mixing a study of English-Hindi code-mixing. In *Findings of the Association for Computational Linguistics: ACL* 2022, pages 472–480, Dublin, Ireland. Association for Computational Linguistics.
- Ritesh Kumar, Aishwarya N. Reganti, Akshit Bhatia, and Tushar Maheshwari. 2018. Aggressionannotated corpus of Hindi-English code-mixed data. In Proceedings of the Eleventh International Conference on Language Resources and Evaluation (LREC 2018), Miyazaki, Japan. European Language Resources Association (ELRA).
- Anoop Kunchukuttan, Pratik Mehta, and Pushpak Bhattacharyya. 2017. The iit bombay english-hindi parallel corpus. *arXiv preprint arXiv:1710.02855*.
- Jaeseong Lee, YeonJoon Jung, and Seung-won Hwang. 2024. COMMIT: Code-mixing English-centric large language model for multilingual instruction tuning. In *Findings of the Association for Computational Linguistics: NAACL 2024*, pages 3130–3137, Mexico City, Mexico. Association for Computational Linguistics.
- Deepthi Mave, Suraj Maharjan, and Thamar Solorio. 2018. Language identification and analysis of codeswitched social media text. In *Proceedings of the Third Workshop on Computational Approaches to Linguistic Code-Switching*, pages 51–61, Melbourne, Australia. Association for Computational Linguistics.

- Giovanni Molina, Fahad AlGhamdi, Mahmoud Ghoneim, Abdelati Hawwari, Nicolas Rey-Villamizar, Mona Diab, and Thamar Solorio. 2016. Overview for the second shared task on language identification in code-switched data. In *Proceedings of the Second Workshop on Computational Approaches to Code Switching*, pages 40–49, Austin, Texas. Association for Computational Linguistics.
- Rudra Murthy, Pallab Bhattacharjee, Rahul Sharnagat, Jyotsana Khatri, Diptesh Kanojia, and Pushpak Bhattacharyya. 2022. Hiner: A large hindi named entity recognition dataset. In *Proceedings of the Thirteenth Language Resources and Evaluation Conference*, pages 4467–4476.
- Ravindra Nayak and Raviraj Joshi. 2022. L3cubehingcorpus and hingbert: A code mixed hindi-english dataset and bert language models. In *Proceedings of the WILDRE-6 Workshop within the 13th Language Resources and Evaluation Conference*, pages 7–12.
- Adithya Pratapa, Monojit Choudhury, and Sunayana Sitaram. 2018. Word embeddings for code-mixed language processing. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 3067–3072, Brussels, Belgium. Association for Computational Linguistics.
- Ruba Priyadharshini, Bharathi Raja Chakravarthi, Mani Vegupatti, and John P. McCrae. 2020. Named entity recognition for code-mixed indian corpus using meta embedding. In 2020 6th International Conference on Advanced Computing and Communication Systems (ICACCS), pages 68–72.
- Royal Sequiera, Monojit Choudhury, and Kalika Bali. 2015. POS tagging of Hindi-English code mixed text from social media: Some machine learning experiments. In *Proceedings of the 12th International Conference on Natural Language Processing*, pages 237–246, Trivandrum, India. NLP Association of India.
- Shashi Shekhar, Dilip Kumar Sharma, and Mirza Mohd. Sufyan Beg. 2020. Language identification framework in code-mixed social media text based on quantum lstm — the word belongs to which language? *Modern Physics Letters B*, 34:2050086.
- Rajvee Sheth, Shubh Nisar, Heenaben Prajapati, Himanshu Beniwal, and Mayank Singh. 2024. Commentator: A code-mixed multilingual text annotation framework. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 101–109, Miami, Florida, USA. Association for Computational Linguistics.
- Kushagra Singh, Indira Sen, and Ponnurangam Kumaraguru. 2018a. Language identification and named entity recognition in Hinglish code mixed tweets. In *Proceedings of ACL 2018, Student Research Workshop*, pages 52–58, Melbourne, Australia. Association for Computational Linguistics.

- Kushagra Singh, Indira Sen, and Ponnurangam Kumaraguru. 2018b. A Twitter corpus for Hindi-English code mixed POS tagging. In *Proceedings* of the Sixth International Workshop on Natural Language Processing for Social Media, pages 12–17, Melbourne, Australia. Association for Computational Linguistics.
- Vinay Singh, Deepanshu Vijay, Syed Sarfaraz Akhtar, and Manish Shrivastava. 2018c. Named entity recognition for Hindi-English code-mixed social media text. In *Proceedings of the Seventh Named Entities Workshop*, pages 27–35, Melbourne, Australia. Association for Computational Linguistics.
- Dama Sravani and Radhika Mamidi. 2023. Enhancing code-mixed text generation using synthetic data filtering in neural machine translation. In *Proceedings of the 27th Conference on Computational Natural Language Learning (CoNLL)*, pages 211–220, Singapore. Association for Computational Linguistics.
- Abhishek Srivastava, Kalika Bali, and Monojit Choudhury. 2020. Understanding script-mixing: A case study of hindi-english bilingual twitter users. In *Proceedings of the 4th Workshop on Computational Approaches to Code Switching*, pages 36–44.
- Vivek Srivastava and Mayank Singh. 2020. PHINC: A parallel Hinglish social media code-mixed corpus for machine translation. In Proceedings of the Sixth Workshop on Noisy User-generated Text (W-NUT 2020), pages 41–49, Online. Association for Computational Linguistics.
- Vivek Srivastava and Mayank Singh. 2021a. Challenges and limitations with the metrics measuring the complexity of code-mixed text. In *Proceedings of the Fifth Workshop on Computational Approaches to Linguistic Code-Switching*, pages 6–14.
- Vivek Srivastava and Mayank Singh. 2021b. HinGE: A dataset for generation and evaluation of code-mixed Hinglish text. In *Proceedings of the 2nd Workshop on Evaluation and Comparison of NLP Systems*, pages 200–208, Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Vivek Srivastava and Mayank Singh. 2021c. Quality evaluation of the low-resource synthetically generated code-mixed Hinglish text. In *Proceedings of the 14th International Conference on Natural Language Generation*, pages 314–319, Aberdeen, Scotland, UK. Association for Computational Linguistics.
- Sahil Swami, Ankush Khandelwal, Vinay Singh, Syed Sarfaraz Akhtar, and Manish Shrivastava. 2018. A corpus of english-hindi code-mixed tweets for sarcasm detection. arXiv preprint arXiv:1805.11869.
- Gauri Takawane, Abhishek Phaltankar, Varad Patwardhan, Aryan Patil, Raviraj Joshi, and Mukta S Takalikar. 2023. Language augmentation approach for code-mixed text classification. *Natural Language Processing Journal*, 5:100042.

- S Thara and Prabaharan Poornachandran. 2018. Codemixing: A brief survey. In 2018 International Conference on Advances in Computing, Communications and Informatics (ICACCI), pages 2382–2388.
- Paras Tiwari, Sawan Rai, and C Ravindranath Chowdary. 2024. Large scale annotated dataset for code-mix abusive short noisy text. *Language Resources and Evaluation*, pages 1–28.
- Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. 2023. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*.
- PV Veena, M Anand Kumar, and KP Soman. 2018. Character embedding for language identification in hindi-english code-mixed social media text. *Computación y Sistemas*, 22(1):65–74.
- Deepanshu Vijay, Aditya Bohra, Vinay Singh, Syed Sarfaraz Akhtar, and Manish Shrivastava. 2018. Corpus creation and emotion prediction for Hindi-English code-mixed social media text. In Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Student Research Workshop, pages 128–135, New Orleans, Louisiana, USA. Association for Computational Linguistics.
- Yogarshi Vyas, Spandana Gella, Jatin Sharma, Kalika Bali, and Monojit Choudhury. 2014. POS tagging of English-Hindi code-mixed social media content. In Proceedings of the 2014 Conference on Empirical Methods in Natural Language Processing (EMNLP), pages 974–979, Doha, Qatar. Association for Computational Linguistics.
- Linda Zeng. 2024. Leveraging large language models for code-mixed data augmentation in sentiment analysis. In *Proceedings of the Second Workshop on Social Influence in Conversations (SICon 2024)*, pages 85–101.

# A Appendix

# A.1 Examples of Noisy Text Instances in the scrapped Code-Mixed Data

Table 5 presents examples of challenging text patterns identified during the manual annotation stage. These instances, including incomplete variants, ambiguous scripts, cross-article concatenation, and mixed-script variations, were carefully reviewed and, in some cases, removed to ensure annotation quality. This process was part of our comprehensive annotation methodology and quality assurance framework, aimed at refining the dataset for improved consistency and reliability.

Category	Example Text
Incomplete vari- ant	), floppy disk, hard disk drive, magnetic stripe card, relational database, SQL प्रोग्रामिंग भाषा (DRAM) (Dynamic Random- Access Memory) शामिल
Ambiguous script	Menu[[चित्र:गिरिधर लाल अग्रवाल ]] ==+Image श्री गिरिधर लाल अग्रवाल / [[:en:Giridhar Lal Aggarwal Freedom Fighter   Giridhar Lal Aggarwal]] ==
Cross-article concatenation	दरअसल, गुरुवार शाम से लालू यादव [.] 08/10/2020 Thursday Satyam Kushwah Leave a Comment on मंत्री राम विलास पासवान का निधन।
Mixed-script variant	@Strawberigloz he barobar naahi aahe, aaplich manasa aaplyala paathi sodtat. Aaplya itithasacha garva asla pahije.

Table 5: Challenging Text Patterns in the dataset containing mixed content and transitions. *Takeaway*: These noisy text instances in the dataset reflect challenges in code-mixed annotation, require careful preprocessing.