Place Capability Graphs: A General-Purpose Model of Rust's Ownership and Borrowing Guarantees

ZACHARY GRANNAN, University of British Columbia, Canada

AUREL BÍLÝ, ETH Zurich, Switzerland

JONÁŠ FIALA, ETH Zurich, Switzerland

JASPER GEER, University of British Columbia, Canada

MARKUS DE MEDEIROS, University of British Columbia, Canada

PETER MÜLLER, ETH Zurich, Switzerland

ALEXANDER J. SUMMERS, University of British Columbia, Canada

Rust's novel type system has proved an attractive target for verification and program analysis tools, due to the rich guarantees it provides for controlling aliasing and mutability. However, fully understanding, extracting and exploiting these guarantees is subtle and challenging: existing models for Rust's type checking either support a smaller idealised language disconnected from real-world Rust code, or come with severe limitations in terms of precise modelling of Rust borrows, composite types storing them, function signatures and loops.

In this paper, we present a novel model of Rust's type-checking called *Place Capability Graphs*, which lifts these limitations, and which can be directly calculated from the Rust compiler's own programmatic representations and analyses. We demonstrate that our model supports over 98% of Rust functions in the most popular public crates, and show its suitability as a general-purpose basis for verification and program analysis tools by developing promising new prototype versions of the existing Flowistry and Prusti tools.

1 Introduction

Rust is a popular programming language, combining competitive performance with a rich and expressive type system that eliminates many common programming errors and unintended side-effects. Rust's type system applies a notion of *ownership* to all allocated memory, by default preventing access through any variable other than its owner, and defining its deallocation time (when its owner goes out of scope). Aliasing is restricted by a notion of *borrowed references* which may temporarily access memory that they alias but do not own. As the name suggests, the ability to access borrowed memory is taken temporarily, and then restored to its lender. Rust allows multiple aliases to the same memory to be usable at once only if none can mutate its content.

The restrictive aliasing discipline of Rust's type system makes the language attractive as a static analysis and verification target, given the challenges of reasoning about aliasing in general (the infamous *frame problem*). A wealth of formal techniques have grown up for Rust, including mechanisations in proof assistants, [14, 15, 20], (deductive) verification tools targeting specification-annotated Rust code [1, 8, 18, 19], and automated static analyses [2, 7, 26]. These projects leverage the rich guarantees provided by Rust's type-checking in the ways they internally model program memory, track aliasing and value information, and (where appropriate) interpret user-provided specifications of desired program properties.

Comprehensively modelling Rust's type-checking is technically challenging for a variety of reasons. The properties implied at different program points are *flow-sensitive*; for example, whether a variable currently owns memory is not visible from its declared type or its initialisation, as Rust

allows *move assignments* to transfer ownership between *places* (Rust's terminology for expressions denoting locations). Similarly, whether a place has been borrowed-from, and for how long, are flow-sensitive properties. Rust's type-checking includes *borrow-checking*¹, which determines whether consistent choices can be made for the extents of each borrow; the points at which borrows end are invisible in source code, but important for code understanding and analysis: this is when side-effects previously performed via the borrowed references become observable via the borrowed-from places.

Capturing Rust's notions of borrowing for general types and programs yields several sources of complexity: (1) instances of composite types (such as structs) may store borrowed references; these types are declared with *nested lifetimes*, used in Rust's type-checking to indicate types that must interact with borrow-checking to reflect the (possibly unbounded number of) borrows stored within them; notions of borrowing are generalised to the sets of borrows stored in these types. (2) Rust allows for *reborrowing*: transitively creating chains of borrows to (parts of) memory previously borrowed. These borrows can be created (and expired) differently in different paths through the program: precisely tracking their effects (and side-effects performed through them) requires *path-sensitive* (and flow-sensitive) information. (3) Programs with loops can create (re)borrows unboundedly many times; to capture Rust's type-checking in such cases, loops must be summarised in a way which matches the compiler's rules. (4) Rust reasons about function calls modularly, which in general also implies an abstraction over the potential (re)borrowing made across the execution of an entire function, including constraints on nested lifetimes; these must be modelled with care to reflect the possibility that the sets of borrows denoted may be different at different program points, in general. We explain the full details of these (and other) challenges in Sec. 2.

In this paper, we present a novel model of the results of Rust's type-checking, designed to address all of these technical challenges and to enable downstream tools to exploit the properties implied by Rust's design. Our model does *not* define Rust type-checking itself, but captures in detail the *results* of a successful type-checking of a Rust program (as defined by the standard Rust compiler). It seamlessly combines solutions to two technical objectives: (1) where computable, all information a downstream analysis might require is *precise*, and (2) where abstractions are necessary in general either for computability or modularity reasons (for loops, function calls and types containing sets of borrows), these abstractions are consistent with those employed by the compiler. Ours is the first model of Rust's type-checking addressing all (or most) of the features described above, particularly with respect to analysis of loops and support for (re)borrows concerning nested lifetimes.

More generally, we have designed our model to satisfy the following criteria:

- (1) The model provides a detailed, function-modular account of how and why a program type-checks, tracking at every program point in a function's body which places own and borrow which memory, which are currently borrowed-from and how, and when and how these borrowed capabilities (to read or write the aliased memory) flow back to their origins. Our model incorporates a novel representation for sets of borrows, allowing us to connect to the compiler's borrow-checking concepts as necessary, while abstracting over the concrete design decisions of any given borrow-checker algorithm or implementation, making it possible to connect to alternative Rust borrow checkers.
- (2) The model captures precise path-sensitive information for non-recursive control flow, and summarises function calls and loops with abstractions that precisely reflect the (implicit) shapes and structure of constraints imposed by borrow-checking (this turns out to be highly-complex for general loops that reborrow memory). The former precision allows

 $^{^{1}}$ In the rest of this paper, we will use "type-checking" to refer to the combination of classical type-checking concerns and the Rust-specific notions of *borrow-checking*.

- downstream tools the freedom to demand as much information as desired, while the detail of the latter abstractions allows supporting general Rust code (e.g. that following a summarised loop) while providing downstream tools with a suitable abstraction that could be enriched by further analysis or annotations. In particular, our loop and function summaries are suitable for connection with user specifications in a deductive verification setting.
- (3) All ingredients of the model have a clear and easily-checkable correspondence with notions in the Rust compiler, including the program representation and type-checking features (as a consequence, the model can be used to visualise and understand the compiler's type-checking itself). This close connection avoids potential gaps between the de-facto definition and semantics of Rust as defined by the compiler and the representations and information making up instances of our model.
- (4) Our model handles a substantial fragment of real-world Rust code written in practice (over 98% of the functions published in the top-500 crates), and can be automatically generated directly from runs of the Rust compiler. This is important to avoid limiting the applicability of tools built upon our model, and gain confidence in its generality in practice.
- (5) The model is suitable for consumption by a wide variety of static analysis and verification tools, providing at least the information they currently require, and potentially extending their reach to a wider class of Rust programs; this makes its definition a significant advance for designing and implementing detailed Rust analysis and verification tools.

As we explain in detail in Sec. 5, to our knowledge all existing models of Rust's type-checking do not meet multiple criteria from this list. Conversely, we believe that many existing verification and analysis tools could simply extract the information they rely on from our model, and that building new static tools on top of this model is a substantially simpler task.

In summary, this paper's key contributions are as follows:

- (1) We define and present *Place Capability Graphs* (PCGs), as a detailed and general-purpose model of Rust's type-checking satisfying the full criteria above; in particular, the model directly builds upon the Rust compiler's programmatic representations and analysis results.
- (2) We provide an implementation of our model, written as a standalone reusable artefact (crate) in Rust; we plan to open-source this implementation and submit it as an artifact.
- (3) We evaluate our model's generality by applying it to the entire codebases of the top-500 Rust crates at time of writing (along with a collection of challenging hand-crafted examples); we demonstrate support for over 98% of the published real-world code, and successfully generate models for all program points in these functions.
- (4) To provide confidence that our model accurately captures the *restrictions* imposed by Rust's type system (in terms of memory accesses it disallows), we employ a form of mutation testing to generate Rust programs that, according to our model, the compiler should *not* accept, and verify that the restrictions captured by our model match the compiler's results.
- (5) We develop new prototype versions of two existing Rust analysis tools as consumers of our model: the information-flow analysis Flowistry [7] and the deductive verifier Prusti [1]. Our PCGs successfully replace Flowistry's alias analysis and Prusti's proof annotation algorithm. By obviating the proof annotation algorithm, we dramatically simplified aspects of Prusti's implementation; all required annotations to drive its formal proofs can be simply and deterministically read off from our novel model.

Our paper is organised as follows. Sec. 2 presents specific challenges that arise in handling the full complexity of Rust ownership and borrowing, also presenting the reader with key background on Rust itself. Sec. 3 introduces our PCG model and defines the rules governing its construction based on information extracted from the Rust compiler. Our evaluation in Sec. 4 demonstrates

4 Zachary Grannan, Aurel Bílý, Jonáš Fiala, Jasper Geer, Markus de Medeiros, Peter Müller, and Alexander J. Summers

```
struct Pair { fst: String, snd: String }
fn replace_fst(mut pair: Pair, new_fst: String) -> Pair {
  let old_fst = pair.fst;
  pair.fst = new_fst;
  return pair;
}
```

Fig. 1. A simple function to illustrate Rust's move assignments and ownership of composite types.

the accuracy and wide applicability of our model. In Sec. 5, we compare our model to related work, and hypothesise how information provided by our model could benefit existing analysis and verification tools. Finally, we conclude and discuss future work in Sec. 6.

2 Capturing Rust

In this section, we provide a brief Rust background and illustrate the specific technical challenges involved in modeling Rust's type-checking in a way that is both useful to downstream consumers and an accurate reflection of the compiler.

2.1 Ownership

As explained in the introduction, ownership is one of the core concepts underpinning Rust's type-checking, but requires a flow-sensitive understanding of the program to capture accurately: although no memory can be owned by more than one owner, ownership can be changed via *move assignments*, as is illustrated by the simple function replace_fst in Fig. 1².

At function boundaries, the declared types of arguments imply more than in languages such as Java/C++: the arguments are guaranteed to refer to initialised, distinct memory which is owned by the arguments when the function is called: the argument pair owns an instance of the Pair struct, and new_fst owns a String. Ownership is transitive for most Rust types: owning a Pair can be alternately seen as owning the memory constituting its two fields. The assignment on Line 3 is a move assignment; it transfers ownership from (only) pair.fst to the local old_fst. Attempting to access pair.fst after this line would cause a type-checking error: despite its declared type, pair no longer has this capability according to Rust's rules.

Line 4 also transfers ownership, this time from new_fst to pair.fst. In combination with the never-removed ownership to pair.snd, this means pair is back to owning a complete Pair instance, which is moved out of the function call to its caller by the return statement. If Line 4 were omitted, this return would fail to type-check. We can see that tracking Rust's ownership rules requires notions of splitting and recombining ownership for type instances, and determining when to apply these operations to match the compiler's actions.

2.2 Borrowing, Borrow Extents and Borrow Checkers

Rust permits aliasing in a controlled manner through *borrowing*, in which temporary access to memory is given out through one or more references, enabling in-place mutation as illustrated by the variant of the previous example shown in Fig. 2. Like the example given in Fig. 1, replace_fst_borrow replaces the first element of a pair. Rather than moving values in and out of the caller, the function is given a *mutable borrow* which (for the duration of the borrow) is guaranteed to have exclusive read/write access to the borrowed-from pair. Such borrows can be created as on Line 7; the line afterwards passes this borrow as a function argument. Within replace_fst_borrow this borrowed

²In this and future examples, we use String for concreteness where any non-copy Rust type would work just as well.

```
fn replace_fst_borrow<'a>(pair: &'a mut Pair, new_fst: String) {
   let fst_ref = &mut (*pair).fst; // fst_ref: &'b mut String
   *fst_ref = new_fst;
}

fn caller(original: Pair, s: String) {
   let mut_borrow = &mut original; // mut_borrow: &'c mut String
   // accessing original is forbidden here (it is borrowed)
   replace_fst_borrow(mut_borrow, s);
// accessing original is allowed here (borrow has ended)
}
```

Fig. 2. A variation of the prior example to illustrate mutable borrows and in-place mutation.

memory is *reborrowed*: the new variable fst_ref borrows only the first element of the underlying pair.³ This borrow is dereferenced, exploiting its write access to this memory; after this line, since neither the reborrow nor the borrow pair are used again, both borrows can end, effectively returning exclusive access to this memory back to the place that pair borrowed-from. Note that borrows never change the *owners* of memory, but nonetheless one can observe that the rights to read/write the memory are indeed temporarily borrowed: for example, as commented in the example, an attempt to access the borrowed-from place original just after Line 7 would fail to type-check; the rights to access this memory are currently borrowed. In this paper, following prior literature on related type-systems [3–5, 11, 12, 25], we refer to these rights as *capabilities*: it is the (unique) capability to write the underlying memory which is borrowed. Rust's notion of *shared borrows* allows the flexibility of borrowing only read capability; while such borrows are live the borrowed-from places also retain only read capability.

In general, references can be (re)borrowed transitively any number of times; reborrows may borrow capabilities to either the full memory or only a part from the original borrow (e.g. by dereferencing fields as in our simple example above). For the duration of a borrow, the loaned capabilities cannot be used with the borrowed-from place; these can be seen to flow back — in the opposite order to (re)borrow creation — as these borrows are ended.

Borrow Extents and Borrow Checking. During borrow-checking, the Rust compiler attempts to assign each borrow a duration which we refer to as a borrow extent: a contiguous portion of the program (in the sense of its control flow) starting from where the borrow was created. Borrow extents are constrained in terms of one another: in particular, a place re-borrowed from (such as pair in our example) must be borrowed for at least as long as the newly-created reborrow (fst_ref in our example); these constraints are called outlives constraints, reflecting that one extent (typically something borrowed) must last at least as long as another (typically something borrowed-from).

In terms of Rust source code, a borrow extent is typically denoted by a named lifetime: these are identifiers following a single tick, such as 'a in our example above. We choose different terminology because explaining modern Rust in terms of lifetimes is challenging: (1) many relevant lifetimes are elided in source programs, although fully-elaborated types (including e.g. the types included in comments in our code examples) are explicit in the Rust compiler's Mid-Level Representation (MIR), (2) even after elaboration, some relevant lifetimes do not appear in the declared

³Rust allows many dereference operators to be elided, but in this section we make them explicit to aid understanding.

6 Zachary Grannan, Aurel Bílý, Jonáš Fiala, Jasper Geer, Markus de Medeiros, Peter Müller, and Alexander J. Summers

```
1 struct Pair { fst: String, snd: String } // as before
2 fn g(s: &mut String) { ... }
3 fn f(mut p: Pair, mut s: String, q: bool) -> Pair {
4    let a = &mut s; let b = &mut *a; // a: &'a mut String, b: &'b mut String, 'a: 'b
5    let c; // c: &'c mut String
6    if q { c = &mut p.fst; g(b); g(a); }
7    else { c = &mut p.snd; }
8    let d = &mut *c;
9    *c = s;
10    return p;
11 }
```

Fig. 3. An example designed to illustrate path-sensitivity with respect to (re)borrowing.

types of *any* variable, but are associated only with temporary sub-expressions, (3) The Rust compiler's newer borrow-checking algorithms, in particular Polonius [23, 24], work in terms of finergrained notions of borrow extents than named lifetimes, distinguishing extents for separate sets of borrows that correspond to the same source-level lifetime, for example when the same variable is assigned many times⁴. As multiple borrow-checking algorithms exist for Rust, it is desirable for a model of Rust's type system to avoid tying itself to the details of a specific implementation.

Despite these challenges, precisely modelling borrow creation and extents (in particular, when borrows end) is critical for downstream analyses that reason precisely about how memory is accessible, aliased and updated via (chains of) borrows. For tools which build their analysis around how borrowed capabilities flow back to their lenders (e.g. Prusti [1] and Aeneas [14]), and any other analyses demanding precise aliasing information, a model which also explains how and when these chains of borrows are (perhaps partially) expired and what exactly they borrow from is essential.

2.3 Path-Sensitivity

Although Rust's type-checking is flow insensitive in terms of observable *outcomes* (for example, whether a place currently has capability to read or write its underlying memory does not depend on the control flow taken), the chains of currently-active (re)borrows at a given program point may be different for different control flow paths; since these determine aliasing and therefore observable side-effects, Rust analyses may demand precise information concerning these flow-sensitive sequences of borrows (for example, for code without loops, Rust verifiers such as Prusti [1] and Creusot [8] aim for precise flow-sensitive reasoning in this sense).

The artificial program given in Fig. 3 is designed to illustrate the key issues that arise (in realistic code the control flow would be more complex and the branching often idiomatically due to pattern-matching). In each branch, c borrows from a (different) field of p; following the join point of these branches (Line 8), c is guaranteed to be initialised but its target *c could borrow capabilities from either p.fst or p.snd. The compiler will conservatively consider both to be borrowed-from here, but a precise analysis tool may need to differentiate these cases. However, summarising the effects of branching control-flow is not a problem local to the branches: in Rust it is possible for further borrows to be chained onto those surviving each branch (as on Line 8); it is also possible for borrows created *before* the control-flow branch to be forced to end during the branches themselves (for example, to justify the calls to g on Line 6). Given the effect of code within the branches on

⁴The Polonius term for its chosen notion of borrow extent is an *origin*; we use our terminology to remain generic over different implementation choices in the borrow checker.

analysis results both before the branch and after the join, one might assume that a precise pathsensitive analysis need reanalyse the entire function body twice per branching construct within it⁵. Perhaps surprisingly, we will show that it is possible to limit the need for duplicated analysis to the code of the branches themselves, sharing analysis results for the common parts, and produce precise results efficiently for virtually all real-world code arising in practice.

2.4 Function Calls

```
fn choose<'z,'x:'z,'y:'z>(x: &'x mut String, y: &'y mut String) -> &'z mut String {
   return &mut *y; // could just as well be &mut *x; or a choice between them
}

fn f(mut x: String, mut y: String, z: String) {
   let a = &mut x; // a: &'a mut String
   let b = &mut y; // b: &'b mut String
   let c = choose(a, b); // c: &'c mut String, 'a: 'c, 'b: 'c
   *c = z;
   choose(a, b);
}
```

Fig. 4. A function to illustrate modular type-checking of calls concerning reborrowing.

Rust's type system reasons about function calls in a modular fashion. The types in a function signature specify which capabilities are owned by arguments (and transferred in/out of a call by move assignments) and which are borrowed. To enable flexible in-place mutation Rust supports borrows whose extents span entire function calls. To enable modular type-checking, Rust computes from a function signature representations of the borrows potentially passed into a function as well as those whose extents survive the function call, and in particular a summary of which of the latter might potentially be taken from the former based on the declared (and various implicit) outlives constraints implied by the type signature. A precise model of Rust's type-checking needs to reflect a summary at least as precise as the compiler's summary.

As an example, consider the program given in Fig. 4: function g is parameterized by three lifetime parameters ('x, 'y and 'z, used to denote the extents of the two input parameters and output parameter, respectively. The syntax 'x: 'z declares 'x along with an outlives constraint: the extent of the borrow stored in x is required to last at least as long as the extent of the borrow returned in z. These constraints are sufficient to allow y (or x) to be reborrowed in the output of the function. At choose's *call-site* on Line 8, the compiler sees from the outlives constraints in the function signature that either argument (or more-generally, parts of their borrowed memory) may have been reborrowed in the output, and so treats the returned reference as if it reborrows from both: the returned borrow gets an extent which ends after Line 9. Despite this abstraction, once the returned borrow's extent ends, the intermediate borrows a and b become usable again, as evidenced by the call on Line 10⁶. Thus, the summaries used to reason modularly about calls must still connect with fine-grained reasoning about the borrows explicitly manipulated in the calling context.

While this example is intentionally simple, in the general case summary of a function signature can be substantially more-complex for several interacting reasons: (1) Rust types can use lifetimes

⁵Indeed, this concern is used to motivate the less-precise join definition in the Aeneas model for Rust [13].

⁶Technically, this is achieved by a compiler elaboration of all function calls which inserts an additional reborrow step before passing a mutable reference into a call; this is explicit in the MIR representation of the program, but we elide this detail for simplicity here.

as arguments to composite (struct) types: for example, the type &'a mut S<'b> denotes a mutable reference to a struct instance that itself stores references (with potentially different extents), (2) Outlives constraints are not only those explicitly declared in a signature, but are often implicit (for example, usage of a type &'a mut S<'b> implicitly declares 'b: 'a as a constraint, to avoid the possibility of a reference that can reach already-ended borrows), (3) Outlives constraints interact with variance rules for Rust types, and transitivity is implicitly required. A correct model of Rust's call summaries must account for the results of these rules together.

2.5 Loops

```
struct List { head: String, tail: Option<Box<List>> }
fn borrow_last<'b, 'a: 'b>(list: &'a mut List) -> &'b mut String {
   let mut current: &'a mut List = &mut *list;
   let mut acc: &'b mut String = &mut (*current).head;
   while let Some(ref mut tail) = (*current).tail {
      current = tail; acc = &mut (*current).head;
   }
   return acc;
}
```

Fig. 5. A function that takes a reference to a mutable list and returns a reborrow to its last element

Consider the program given in Fig. 5. Function borrow_last returns a mutable reference to the last element of a list via the loop at Line 5, at each iteration advancing current to point to the next node and borrowing current. head into acc. Like the example in Fig. 3, the borrow stored in acc at the join point depends on which the branch is taken. However, the loop body can be entered an arbitrary number of times, in accordance with the length of list. As a result, the target of acc at the join point cannot be determined statically. That is, as with function calls, it is not possible, in general, to maintain precise borrowing information across zero or more iterations of a loop.

Accounting for the borrowing that occurs across a loop raises additional challenges beyond that of function calls. Unlike functions, where the lifetimes in the signature summarise the borrowing that could occur, handling loops requires identifying a *loop invariant* that summarises potential borrowing. Furthermore, as we demonstrate in Sec. 3.6, the shape of this invariant can in general necessarily be described in terms of Rust lifetimes.

2.6 Nested Lifetimes

```
struct MutWrapper<'a> { val: &'a mut String }
fn g<'a, 'b>(bp1: &'a mut MutWrapper<'b>, bp2: &'a mut MutWrapper<'b>, s: &'a mut String) {...}
fn f(mut x: String, mut y: String, mut z: String) {
  let mut a = MutWrapper { val: &mut x }; let ra = &mut a; // ra: &'ra MutWrapper<'a>
  let mut b = MutWrapper { val: &mut y }; let rb = &mut b; // rb: &'rb MutWrapper<'b>
  g(ra, rb, &mut z); *a.val = z;
}
```

Fig. 6. Rust functions demonstrating nested borrows. The call to g() could change the target of a.val.

References to types which themselves contain borrows pose a unique challenge. Consider the example given in Fig. 6. The arguments to g() are references to values of the type MutWrapper<'b>,

a type that itself contains a *nested* reference with lifetime 'b. A downstream consumer — a dataflow analysis or verification tool — might need to know the set of memory locations which the write in Line 6 could have affected. Prior to the call, it is straightforward to identify that a.val and b.val borrow from x and y respectively. However, because g() is allowed to change the targets of these references, they cannot be known precisely after the call (in a modular analysis). A similar situation arises when types with nested lifetimes appear across loops. We note that this situation only arises for nested lifetimes: it is not possible e.g. for g() to change the target of rb. Thus, our model must soundly overapproximate the set of borrows held by types with nested lifetimes, while retaining more precise information for types without.

3 Place Capability Graphs

In this section, we introduce Place Capability Graphs (PCGs), and demonstrate how they address the problems discussed in Sec. 2.

A PCG is a directed, acyclic hypergraph that defines the organisation of capabilities to access memory, current borrows and the relationships between borrow extents relevant for understanding subsequent code. Fig. 7 provides an overview of its different components, which we will introduce throughout this section. *Place nodes* associate Rust places with *capabilities* (Fig. 7a), defining the actions that the Rust compiler currently permits on these places⁷. A place node with exclusive (E) capability represents a place that can be read from, written to, mutably borrowed, moved or dropped. Those with read (R) capability can be read or immutably borrowed, but not written to or dropped. Places with write (W) capability can be written to (for example, when initialising them), but not read from or dropped.

The second main type of PCG nodes⁸ are *lifetime projection* nodes. Lifetime projections $p \downarrow 'a$ are a novel construct used to represent a set of borrows currently stored in a place p (where 'r is one of the named lifetimes in the type of p), which, according to the borrow-checker: (a) all have the same borrow extent (all will end at the same program point), and, (b) have a borrow extent that has not yet ended. For example, if a variable x has type &'a mut String, then $x \downarrow 'a$ denotes the (singleton) set of borrows stored within x. As we will see later in this section, lifetime projection nodes allow us to mediate between precise reasoning about individual places, and the abstractions over sets of borrows as employed by Rust's borrow-checker.

The place node *leaves* of a PCG represent places which are currently accessible in the program; edges connecting to non-leaf nodes as parents reflect a reason why their (full) capabilities are not currently available (for example, due to a place being currently borrowed). At a high level, edges from lifetime projection nodes reflect potential flows of borrows, as well as justifications (respecting the borrow checking of the program) that a particular borrow can currently be dereferenced.

A PCG is constructed for each program point as a forward analysis over the MIR (CFG) representation of a Rust function, driven both by the statements of the function body and information from the (already-performed) Rust compiler's analyses (especially the borrow-checker). An initial PCG for a function is constructed by, for each function argument p: (a) adding a place node p: E, and (b) for each lifetime 'a in the type of p, adding a lifetime projection node $p \downarrow$ 'a.

For every statement, we define a corresponding PCG analysis rule consisting of (1) preconditions on the pre-existing PCG, and (2) how to calculate the PCG for after the statement. Before applying each rule, we query the borrow-checking results to see if any borrow-extents end before the statement, updating the current PCG accordingly if so.

⁷In addition to the capabilities listed in Fig. 7a, our model includes a capability ShallowExclusive (e), which is used to track the initialization state of Box types (representing a Box that owns currently uninitialised memory).

⁸As we will show later, both also come with additional variations called *labelled* versions of these node types.




Fig. 7. The PCG capabilities, components of the graph and their associated permitted behaviours. Capabilities describe the actions that the Rust compiler permits on a value via a particular place. PCG nodes denote memory locations: either places, or *lifetime projections* which describe a region of memory that the borrow checker permits access to. Edges in the PCG describe capability transfers, aliasing, and the flow of borrows.

```
struct StringList { hd: String, tl: Option<Box<StringList>>> }

fn take_head(list: StringList) -> String {
    // Initial: {list: E, RETURN: W}

    // Prepare: {list.hd: E, list.tl: E, RETURN: W}

return list.hd; // {list.hd: W, list.tl: E, RETURN: E}
}
```

- (a) A function that performs a partial move out of the argument list
- (b) Final PCG State

Fig. 8. An example of a partial move operation. The PCG reflects the splitting and partial ownership of list.

3.1 Fine-Grained Place Accounting with Unpack Edges

As motivated in Sec. 2.1, Rust's type-checking requires decomposing capabilities for composite types into field-specific capabilities (and the reverse); consumer tools typically need to manage their representations for these (potentially recursive) types with similar operations. For these reasons, our PCGs include explicit *unpack* and *pack* operations, which add (and remove, respectively) *unpack edges* representing decomposed capabilities.

Fig. 8a shows an example in which unpacking is needed. A source-level return statement such as return list.hd corresponds to a MIR move assignment RETURN = move list.hd. Our PCG analysis rule for move assignments p = move q requires as precondition a PCG with place nodes $p: \mathbf{W}$ and $q: \mathbf{E}$. The resulting PCG is obtained by:

- (1) Renaming these nodes to $p : \mathbf{E}$ and $q : \mathbf{W}$, respectively,
- (2) Renaming any lifetime projection nodes $p \downarrow a$ (for the target place p) as *labelled lifetime* projection nodes ($p \downarrow a$ at 1) (where 1 is the MIR identifier for the program point of this statement).
- (3) Renaming any lifetime projection nodes $q \downarrow 'a$ (for the moved-from place) with corresponding $p \downarrow 'a$ nodes.

The notions of (labelled) lifetime projection nodes will be discussed in the next subsection. Our rule as defined cannot be directly applied to the initial PCG in our example: the rule requires a (leaf)




Fig. 9. A simple example of borrowing.

place node for list.hd: E, whereas our prior PCG has list: E. To satisfy the rule precondition our model first inserts an *unpack* operation on list, which:

- (1) Updates the node list: E to list: \emptyset , and adds nodes for list.hd: E and list.tl: E.
- (2) Inserts an *unpack* hyperedge between these nodes: $list \rightarrow \{list.hd, list.tl\}$

After performing (1), the PCG is in a state that satisfies the precondition of the move assignment. Note that a *pack* operation requires that all children of the unpack edge have appropriate capabilities; this is no-longer possible after the move assignment (reflecting the restriction that Rust would not allow e.g. list to be moved or directly borrowed in this state). After every statement, if (unlike in this case) an unpack edge *can* be removed by packing, we do so, keeping the graphs smaller. Every unpack and pack operation is recorded at the appropriate program points so that downstream consumers can drive their own analyses with analogous steps.

3.2 Tracking Borrows with Borrow Edges

As explained in Sec. 2.2, Rust's borrowed references are used to temporarily transfer capabilities (and later return them), enabling in-place mutation. The simple example Fig. 9 shows the creation of a such borrow.

Our PCG rule for modelling mutable borrow creations such as $y = \&mut \times on Line 3$ requires exclusive capability for x (read capability suffices for Rust's shared borrows), and creates a new place node for y and new lifetime projection node for $y \downarrow 'a$, where &'a mut i32 is the elaborated type for y. The lifetime projection node in our PCGs models a set (in this case a singleton) of borrows potentially stored in y whose extents have not yet been ended (according to the borrow checker). A borrow edge $x \to y \downarrow 'a$ records the outstanding borrow of x into this set: concretely, it is currently aliased by the place $*y^9$. in particular, the existence of this edge in the graph explains why x does not (currently) have its default capabilities. The rule for statements r = &mut t is:

- (1) Requires the PCG to have capability **W** to r and capability **E** to t
- (2) Assigns capability E to r, removes all capability to t, and adds the borrow edge $t \to r \downarrow 'a$ Although in this example, the lifetime projection may seem overly complex as a representation for the (single) created borrow, as we will show in subsequent sections, lifetime projections enable uniform rules for tracking of borrows in scenarios where precise alias information is not available, e.g. borrowing across function calls and loops.

The rule for the assignment *y = 5 on Line 5 requires *y to be present in the PCG with capability **W**; obtaining this capability requires reorganising the PCG state $\{y : E\}$. The unpack operation for reference-typed values differs slightly from the case for owned places to reflect that dereferencing a borrow requires not only the borrow itself but *a justification from the borrow checking of the program* that this borrow has an extent which has not yet ended. Specifically, the unpack operation:

⁹In general, although unnecessary for this example, in cases where we know/knew the precise alias of these borrows, we record this as extra meta-data on the borrow edges.

- (1) Removes the capability for y, and adds exclusive capability to *y
- (2) *Labels* the lifetime projection $y \downarrow$ 'a with the current program point l
- (3) Inserts the unpack edge $\{y, y \downarrow 'a at l\} \rightarrow *y$

The role of *labelled* lifetime projection nodes is a technical one; while a place node is not a leaf, it is possible that the sets of borrows stored within it may change; for this reason, the lifetime projection node may have an out-of-date meaning as a set. The labelled versions of these nodes denote sets as they *were* at that point in the program. This is mostly a convenience for simplifying the definition of our rules in terms of local changes to the edges in our graphs; in particular, the notion of labelled lifetime projection nodes is important for the handling of nested references, explained in Sec. 3.7.

Immediately after the statement, the borrow-checking information from the compiler prescribes that the borrow extent associated with y ends: this causes our PCG to be updated, removing all edges associated with lifetime projection nodes that concern definitely-ended borrow extents; in this example, this makes x a leaf once more, and as a result, its capability is updated to reflect that it regains exclusive access (when the borrow edge originating from it expires). Since y's lifetime projection node can only refer to borrow extents the compiler considers to have ended, its capability is instead set to W, reflecting that all we can now do with this place is reassign it a new value.

3.3 Computing Joins and Tracking Path-Sensitive Borrows

When the control flow of a program branches, the PCG for both branches is computed separately, and then the resulting states are *joined* to compute the set of common leaves for use after the branch; these can then be further built-upon (or expired, as borrow extents end), depending on the subsequent code and borrow-checker information. More-subtly, we also manage to share maximal information from the graphs before the join point.

Computing the join for place nodes is straightforward: only the nodes which are leaves in both branches make up the place node leaves of the joined graph; this reflects the fact that Rust's ownership rules (along with e.g. initialisation analyses) are not path-sensitive. Borrows which survive the join will also be represented by a lifetime projection node for one of these joined leaves, but their connections back into the results of analysing the two branches must be *preserved*, to retain precise modelling of side-effects (and borrow expiries) performed later. We describe next how our PCGs track this path sensitive information precisely and efficiently (i.e. without path explosion), using Fig. 10a as a demonstrative example.

The PCG tracks path sensitive information by associating each branch in the CFG with a *branch-choice identifier*: a unique label representing the pair of a branch location and a chosen direction at this branching point. As our analysis is performed, it records which branch-choices we are currently analysing under; edges added to our graph are additionally labelled with these identifiers. For example, the borrows created in the first branches of this example are labelled with identifiers c_0 and c_1 . When a join point is reached, the edges from both joined graphs are included (retaining any labels), but *only* those created since the branch will have alternative structure to retain. In particular, edges which existed before the branch point and *survive* in either graphs will be preserved without duplication: the graph summarised for bb3 is not duplicated in the final result.

3.4 Borrows Inside Composite Data Types

Composite data types such as struct and tuple types are allowed to contain references, e.g., as in Fig. 11. In the MIR, creating a new instance of a composite datatype is a MIR statement of the form p = Aggregate(operands), where each operand is either a place or a constant. The PCG rule for




Fig. 10. Example demonstrating joins in the PCG: the state at bb3 is computed by joining the states at bb1 and bb2 (where c_0 and c_1 are the respective branch-choice identifiers), and bb6 is the join of the states at bb4 and bb6 (where c_2 and c_3 are the respective branch-choice identifiers).




Fig. 11. The PCG generated for a struct with borrow-typed fields.

such assignments is mostly analogous to the rule for normal place assignments: the assigned place is required to have capability \mathbf{W} and each (non-copy) place in the operands requires capability \mathbf{E} . Applying the rule results in a PCG state with \mathbf{E} capability to the assigned place and \mathbf{W} capability to the places that have been moved out of.


To reflect the constraints of the borrow-checker, the rule also adds additional *outlives* edges between the lifetime projections of the operands and lifetime projections of the assigned place. Concretely, for each lifetime projection $p' \downarrow r$ in *operands* and each lifetime projection $p \downarrow s$ in the target place, if the borrow checker requires r to outlive s, the rule adds an *outlives* edge $p' \downarrow r \rightarrow p \downarrow s$.

Fig. 11 presents PCGs created for a simple function that constructs a struct with borrow-typed fields. At the point when U32Pair is constructed, outlives edges are added between the lifetime projections of rx and pair.0 and those of ry and pair.1. When U32Pair is packed (i.e. at the end

```
fn choose<'a, T>(
    c: bool, rx: &'a mut T, ry: &'a mut T
    ) -> &'a mut T { ... }

fn f<'a>(ra: &'a mut u32, rb: &'a mut u32) {
    let res = choose(true, ra, rb);
    *res = 10;
}
```

(a) The function f() assigns the result of the choose() function to the variable res. Rust's borrow-checker constrains 'a to outlive the lifetime of res (denoted as 'r in Fig. 12a).



(b) The PCG generated at Line 7. The hyperedge introduced for the call to choose() reflects the borrow-checker constraints: res \downarrow 'r may borrow from ra \downarrow 'a and rb \downarrow 'b.

Fig. 12. The PCG generated for a function call.

of the function), these outlive edges are moved into the lifetime projection $pair \downarrow 'p$. We note that technically, the resulting graph has lost information (i.e. that x and y aliases *pair.0 and *pair.1 respectively). However, we believe that we can preserve this information by attaching metadata to moved edges, and plan to do so as future work.

3.5 Tracking Reborrowing Across Function Boundaries with Abstraction Edges

Reasoning modularly about function calls means that it is not possible to *precisely* account for aliasing across function boundaries. In such cases, the PCG uses *abstraction edges* to capture, as precisely as possible, the aliasing relation between the inputs and the outputs of a function call.

In the MIR, a function call is a statement of the form p = f(operands). The PCG rule for function calls is similar to the rule for creating composite data types (described in Sec. 3.4), with the main difference being that it connects lifetime projections with *abstraction* edges instead of *outlives* edges¹⁰. Concretely, for each lifetime projection $p_i \downarrow r_i$ in the input places of a function call, and each lifetime projection $p_o \downarrow r_o$, if the borrow checker requires r_i to outlive r_o , then the PCG adds an abstraction edge $p_i \downarrow r_i \rightsquigarrow p_o \downarrow r_o$.

Although similar in structure, the meaning of outlives and abstraction edges in the PCG differ. Namely, the PCG uses outlives edges to relate memory locations where precise aliasing information can be recovered, e.g., when a borrow is stored in a struct. Abstraction edges are used when the relation between the memory locations cannot be known statically (in a modular analysis), i.e., for function calls and loops (which we discuss in Sec. 3.6).

Fig. 12 demonstrates the usage of abstraction edges in function calls. Based on the types of res, ra, and rb, res may borrow from either variable. The PCG reflects this information by adding abstraction edges between the labelled lifetime projections for ra and rb with those in the result res. To obtain precise aliasing information, it would be necessary to consider the definition of the choose() function, therefore making the analysis non-modular.

Since recursive datatypes can contain references, function call abstractions can connect lifetime projections that each contain potentially unbounded number of memory locations. For example, the PCG after the call to get_nth() in Fig. 13 includes a lifetime abstraction connecting self \downarrow 'a to res \downarrow 'a; the list self can contain an unbounded number of references under lifetime 'a.

 $^{^{10}}$ The only other difference relates to function calls with inputs containing *nested* borrows, which we describe in Sec. 3.7.

```
enum StringList<'a> { Cons(&'a mut String, Box<StringList<'a>>), Nil }
impl <'a> StringList<'a> {
fn get_nth(self, n: usize) → Option<&'a mut String> { ... }
fn set_nth(self, n: usize, value: String) {
if let res@Some(node) = self.get_nth(n) { ① *node = value; }
}

(a) Rust code that manipulates the StringList data structure.
(b) The PCG at ①.
```

Fig. 13. The PCG generated for a type with a potentially unbounded number of references.

```
fn f(lhs_in: &mut List, rhs_in: &mut List) {
     let mut lhs = &mut *lhs_in; let mut rhs = &mut *rhs_in;
2
     let mut c = None; let mut cont = true;
3
     while cont {
                                                                    lhs in ↓
       lhs = lhs.tail.as_mut().unwrap();
5
       cont = lhs.len() > 0;
6
                                                                      lhs↓
                                                                                            rhs |
                                                                                                 'a
       if lhs.head > 0 { c = Some(&mut lhs.tail); }
7
                        { c = Some(&mut rhs.tail); }
8
9
10
     *c.unwrap() = None; lhs_in.tail = None;
11
                                                                       (a) PCG Loop Invariant
```

Fig. 14. An example of reborrowing across loops. Variables 1hs and rhs initially reborrow from 1hs_in and rhs_in respectively. During the loop, 1hs reborrows from itself and c borrows from both 1hs and rhs. Because the borrow rhs = *mut rhs_in does not change across the loop, it is not included in the invariant.

3.6 Reborrowing Across Loops

In the presence of loops, it is not possible to precisely track borrowing: in particular, the extent of borrows created *inside* the loop may extend beyond the loop. Our analysis constructs a *loop invariant* to summarise the borrowing that occurs after an arbitrary number of loop iterations.

The PCG structure used to describe a loop invariant is somewhat analogous to the structure for function calls: abstraction edges between lifetime projection nodes are used to summarise the borrow-checking constraints. However, the structure of the loop invariant can be more complex (and unlike for functions, is not even implicitly declared in the code): the abstraction edges introduced for a function call form a bipartite graph between the lifetime projections representing inputs and outputs; loop invariants can form more-general DAGs. For example, the code of Fig. 14 involves a loop with multiple transitive reborrows, such that c (conditionally) borrows from rhs and 1hs, which in turn reborrows transitively from 1hs_in: since the compiler accurately captures this chain of borrows, a suitable loop invariant structure to add to our PCG model must do the same, capturing the transitive relationship between c, 1hs, and 1hs_in.

Our key insight is that the structure within our graphs consisting of *only* the lifetime projection nodes and the edges connecting to them reflects the shape of outlives constraints enforced by the borrow checker on its corresponding notions of tracked borrow extents. This property is maintained because whenever we introduce lifetime projection nodes that might (according to the borrow checker) correspond to borrows on which the borrow-checker imposes constraints, we

```
struct List { head: u32, tail: Option<Box<List>> }
fn penultimate_mut<'a>(list: &'a mut List) -> Option<&'a mut u32> {
    let mut current: &'a mut List = &mut *list;
    let mut prev: Option<&'a mut u32> = None;
    while let Some(ref mut tail) = current.tail {
        prev = Some(&mut current.head); current = &mut *tail;
    }
    prev
}
```

Fig. 15. A reborrowing function that returns a reference the penultimate value in the list. Prior to the loop, current borrows from list. At the end of the loop, prev and current have reborrowed from the *previous* version of current.

query the borrow-checker and add the corresponding edges, as described in the previous subsection.

Based on this insight, we analyse loops with the following steps. Firstly, we gather the set of places accessed in the loop body, with a syntactic analysis. For each of these places that the compiler considers live at the loop head, we initialise a state¹¹ for analysing the loop body by: (1) labelling each of these places' nodes and lifetime projections (marking them as the versions just before the loop), (2) making a fresh copy of each, from which the loop body analysis will be performed, and (3) connecting each newly-created lifetime projection node to those labelled in step (1) for which the borrow-checker decides an outlives-relation exists.

We then run our PCG analysis rules as normal through the loop body, obtaining a PCG at the end of the loop body. The remainder of our algorithm for loops is based on two PCGs: the one from just before the loop, and the one from the end of the loop body. We construct an *abstraction graph* for each of these two PCGs by removing all of the intermediate nodes *except* for lifetime projection nodes and (in each graph) replacing all edges between them with abstraction edges. By construction, lifetime projections are connected in the abstraction graphs only where there is a corresponding borrow-checker constraint. Conceptually, the two abstraction graphs describe the minimal constraints required to explain the borrowing at the respective program points: the first graph expresses constraints the borrow-checker imposes after 0 loop iterations, while the second summarises those the borrow-checker imposes after any number *greater* than 0 of loop iterations.

Finally, we join the information present in these two abstraction graphs in three steps, which we illustrate on the code in Fig. 16. First, both graphs are further reduced by removing any nodes that the borrow checker does not consider to be *live* after the loop: these capture constraints which cannot be necessary in the summary of the loop; as nodes are removed, we add edges to connect surviving nodes which were transitively connected through the removed ones (the transitive closure of the edges on the remaining nodes is preserved). Fig. 16b and Fig. 16c show the reduced versions of the abstraction graphs for the states before and after the loop body. Then, the edges in both graphs are combined into a single graph; in our example the result is the same as for that after the loop body. Finally, we remove edges from the resulting graph that correspond to structure that was shared in *both* original graphs, and therefore unrelated to the loop. This resulting structure connects the nodes relevant for places live after the loop to those they may have transitively borrowed from across any number of loop iterations; this structure in terms of abstract edges is used to update the original PCG for before the loop, summarising its overall effect.

 $^{^{11}}$ At submission time we detected an issue in our current implementation of this step (cf Sec. 4.2), but this rule is correct.




Fig. 16. PCG states at the start and end of the loop in Fig. 15, and their corresponding abstraction graphs. In this case, the PCG uses the abstraction graph for the PCG state at the end of the loop as the loop invariant.

Fig. 17. A Rust program that uses nested borrows. The call to the swap() function changes the set of references stored in rx and ry.

3.7 Nested Borrows

The ability of borrows to be *nested* gives rise to an additional source of complexity when using nested borrows as arguments to functions. When an argument containing a nested borrow is used in a function call, the *callee* can use the argument to change the set of borrows stored in the *caller*'s places¹². For example, in Fig. 17, the call to f() causes the reference r1, originally stored in x.f, to be moved to be moved to y.f, and the reference r3 originally in y.f to be moved to x.f.

Accordingly, for each nested lifetime in the arguments to a function call, the PCG introduces an abstraction edge that connects versions of the corresponding lifetime projections *just before* the

¹²This can *only* happen in the presence of nested borrows: a function call can modify the value stored at a caller's place, but in the absense of nested borrows, that place itself cannot store any references.




Fig. 18. PCG states before and after the swap operation in swap() function.

call to their versions *just after* the call. For example, the edge introduced to the call to f() (shown in Fig. 18a), indicates that the combined set of borrows under the nested lifetimes 'r2 and 's2 *after* the call contain references in the combined set *before* the call.

When x and y become available, the set of references in x and y differ from their original values. The PCG reflects this by connecting their corresponding lifetime projections (e.g. x \downarrow 'r0 and y \downarrow 's0) to the *descendants* of their previous versions (e.g. x \downarrow 'r0 at 6 and y \downarrow 's0 at 7). This reflects that the set of borrows currently stored across x and y originated from the original set at the prior program point. Because the interior nodes between the current and old versions of the lifetime projections are labelled nodes, and therefore inaccessible, they are removed from the PCG.

4 Evaluation and Implementation

In this section, we describe our Rust implementation and its evaluation. We designed our evaluation to answer the following three questions:

- (Q1) Can our implementation handle most real-world Rust code? (Sec. 4.2)
- (Q2) Can our PCGs serve as the basis for other analysis tools? (Sec. 4.3 and Sec. 4.4)
- (Q3) Does our implementation accurately reflect Rust's borrow-checker constraints? (Sec. 4.5)

4.1 Implementation

Our implementation is written in Rust and available as a crate that can be included as a library. The implementation supports both the current Rust NLL borrow checker as well as the Polonius borrow checker. In addition, the implementation can also produce graphical debug output that produces diagrams similar to the figures included in this paper.

Our library provides multiple interfaces for clients to consume the results of the analysis. Clients can directly analyse the PCGs themselves, querying the graphs to e.g. answer questions about aliasing relationships (as we do in our Flowistry implementation). Clients can also consume *annotations* that describe the operations that transform consecutive PCG states in the program. Our implementation in Prusti, for example, consumes these annotations to generate Viper assertions. We note that both of these interfaces expose path-sensitive information: clients can filter the graphs and annotations to only include those relevant for a specific program path.

4.2 Top 500 Crates

To evaluate the PCG implementation on a wide range of code, we ran our implementation on functions from the top 500 most downloaded crates on crates.io, excluding crates that did not

Status	Details	Count
Success		119,338
Unsupported	DerefUnsafePtr	1,629
	ClosureCall	215
	InlineAssembly	80
	ExpansionOfAliasType	6
	IndexingNonIndexableType	5
	AssignBorrowToNonReferenceType	1
	Timeout	1
Total		121,274

Table 1. Per-Function Results of PCG Analysis. Failures ExpansionOfAliasType, IndexingNonIndexableType, and AssignBorrowToNonReferenceType occurred due to limitations normalizing type aliases in the Rust compiler: normalising a type alias erases lifetime information that is required for the PCG analysis. Timeout indicates that the function analysis was terminated after two hours.

compile on our test system configuration 13 . Table 1 presents statistics about the PCG runs, showing both successful analyses and the distribution of error cases.

Our analysis was able to generate PCGs at every program point for the vast majority of functions (98.4%) in the crates we evaluated. For the remaining functions, most of them failed because they used features that our model does not currently support: unsafe pointers, inline assembly, and calls to closures¹⁴. For 12 functions, PCG construction failed due to a limitation in resolving type aliases in the Rust compiler: the compiler's interface for normalising a type also erases lifetime information, which is necessary for our analysis. Finally, analysis for one function from the serde_derive did not complete within two hours and was therefore recorded as a timeout.

Just before submission, we spotted that our current implementation does not correctly initialise the state for analysing loop bodies, according to our model's rules in Sec. 3.6. The fix is straightforward ¹⁵, and this issue does not affect our extensive evaluations in practice, since real-world code is unlikely to (and apparently does not) exhibit the combination of features required.

Our evaluation completed in 167 minutes on a six-core Intel Xeon E-2236 with 64 gigabytes of RAM, using the default borrow checker and Rust nightly 2024-12-15. Although our implementation supports the usage of the next-generation Polonius borrow checker, we used the standard borrow checker for our evaluation as some crates are not feasible to check with the Polonius borrow checker (with some taking longer than one hour to borrow check).

4.3 Flowistry

Flowistry [7] is an IDE tool that performs an information flow analysis to identify what statements in a Rust program could influence the value of a given expression. As part of their implementation, they developed a Rust alias analysis.

To evaluate our claim that PCGs can form the basis of other analysis tools, and provide evidence for the correctness of our analysis, we developed a modified version of Flowistry that uses our

¹³In total there were nine crates that did not compile: winreg, criterion-plot, tiny-keccak, redox_users, plotters, darling, derive_more, tokio-native-tls, and clang-sys. The reasons for compilation errors were either that the operating system was not supported, necessary external libraries were missing, or that the compilation required additional configuration arguments to be supplied via the cargo build tool.

¹⁴We note that our model supports the construction of closures, and the usage of closures as function call inputs.

¹⁵We plan to submit the fixed version as an artefact, confirming analogous results in practice.

PCG implementation to perform the alias analysis, replacing their existing analysis. The version of Flowistry using our implementation passed all of the tests in Flowistry's test suite.

4.4 Prusti

Prusti [1] is a verifier that translates Rust programs into Viper [21], a verification language based on separation logic. In order to check functional properties, Prusti first verifies that the borrow-checker correctly enforced memory safety by automatically generating its own proof of memory safety (the core proof). However, to do this automatically, Prusti must infer a variety of annotations required for a Viper proof. Currently, Prusti uses its own complex ad hoc analysis to infer these annotations.

We developed a prototype version of Prusti that instead uses our PCG implementation to infer proof annotations. This significantly simplified the Prusti codebase while also enabling support for some Rust features (such as references in structs or reborrowing in loops) that their analysis did not support. Our PCGs successfully help infer all the annotations required for Prusti's core proof:

- Predicate *fold* and *unfold* statements. These are a key feature that enables support for recursive data types. Due to the similarity of separation logic to Rust's ownership system, these have a one-to-one correspondence with our pack and unpack operations.
- Loop invariants that specify the loop's memory footprint. These are required for all loops and correspond to the PCG state at the head of the loop.
- Magic wand *package* and *apply* statements. These describe how permissions flow from an expired reference to the original owning data structure and are required for reborrowing methods and reborrowing in loops. They correspond to our abstraction edges.

Our prototype Prusti queries the PCG for the annotations to be inserted at every MIR location and interleaves these annotations with its own encoding of the operational semantics of the program. By cleanly separating these two tasks, our approach makes it easier to identify errors in the encoding of the operational semantics (which, in the original Prusti, were often hidden by the unpredictable inference analysis). Additionally, these errors are easier to debug since the memory safety violation can be explained at the level of the MIR, instead of the elaborated Viper program only.

We focused on implementing the features required to show that our PCG model can help verifiers with Rust's ownership system, and as a result, we did not implement some orthogonal features, such as support for slices, arrays, or closures; calls to trait methods; or polymorphic methods. Evaluating our prototype directly against a subset of the Prusti test suite (the should-verify category with overflow checks disabled), encoding *only* the memory safety proof and not the functional correctness specifications, yielded a result of 129 tests passed, 41 failed, and 111 ignored due to unsupported features. With our prototype, we then successfully verified a variety of hand-crafted examples (including all the examples presented in this paper), some of which demonstrate Rust features that the analysis from the original Prusti does not support, such as programs with reborrowing inside loops, structs with references, or reborrowing functions with multiple pledges.

4.5 Mutation Testing

To demonstrate that the PCG accurately reflects the restrictions enforced by the Rust compiler, we built a mutation testing tool which uses the PCG to mutate the MIR of well-typed Rust programs into mutants which violate particular ownership or borrowing rules.

We describe the mutations performed by our tool below:

• MutablyLendShared creates a mutable borrow to a place behind a shared borrow.

Mutation	tot	fail	pass	%fail	error codes
MutablyLendShared	1009867	1009497	370	99.96%	0381, 0382, 0499, 0502, 0596
ReadFromWriteOnly	395299	395299	0	100.00%	0381
WriteToShared	1009396	1008980	370	99.96%	0381, 0382, 0384, 0503, 0506, 0594
MoveFromBorrowed	419555	419264	291	99.93%	0161, 0381, 0382, 0505, 0507, 0508, 0509
BorrowExpiryOrder	196470	196374	96	99.96%	0381, 0382, 0499, 0502, 0505
AbstractExpiryOrder	38220	38203	17	99.96%	0382, 0502
Total	3068807	3067617	1144	99.96%	

Table 2. Results of PCG-Directed Mutation Testing on top 250 crates. *tot* lists the total number of mutants produced by the mutation. *#run* lists the number of mutants passed to the borrow checker. *pass* lists the number of mutants which passed borrow checking. *fail* lists the number of mutants which failed borrow checking. Note that this is the intended outcome. *%fail* lists the percentage of mutants which failed borrow checking. *error codes* lists the set of Rust compiler error codes triggered by mutants.

- WriteToShared writes to a place behind a shared borrow.
- ReadFromWriteOnly reads from a place with **W** capability.
- MoveFromBorrowed moves out of a place behind a mutable borrow.
- BorrowExpiryOrder identifies a place p_1 which blocks another place p_2 via a mutable borrow and attempts to use p_2 before p_1 .
- AbstractExpiryOrder identifies a place p_1 which blocks another place p_2 via a mutable borrow and through an abstraction edge and attempts to use p_2 before p_1 .

Table 2 reports the results of running our tool on the top 250 most downloaded crates on crates.io. Note that fail and pass do not add up to tot; WriteToShared caused 46 compiler panics which we do not count towards fail since their cause may not have been related to type-checking. In addition, our tool crashed on 7 crates, so we do not include their data. As indicated in the pass column, 99.96% of mutants produced by our tool trigger errors, demonstrating that in the cases covered by our mutations, type-checking restrictions systematically derived from a PCG are nearly always reflected by the compiler. Of the remaining mutants (those that passed type-checking) we have examined, all appear to also violate some rule.

Take the program given in Fig. 19, for example. When Line 4 is omitted, reborrow_pair is well-typed. When Line 4 is included, *fst blocks (*pair). snd through the mutable borrow created in line Line 3, and so this function fails type-checking. However, a roughly equivalent mutation at the MIR level produces a program which passes type-checking.

Table 2 also reports the error messages triggered by each mutation. Analysis by hand confirms that each mutation triggers at least a set of error messages which one would expect given the modification applied to the MIR. However, certain mutations triggered surprising error messages. If we find that these messages or the unexpected behavior of the type-checker mentioned earlier correspond to issues in the Rust compiler, we intend to submit bug reports.

5 Related Work and Potential Consumers

Where applicable, we discuss related work in two senses: on the one hand, comparing with alternative models for Rust's type-checking, and on the other, discussing how we believe existing projects could exploit the information provided by our model and its implementation.

```
struct Pair<T> { fst: T, snd: T }
fn reborrow_pair<T>(pair: &mut Pair<T>) {
    let (fst, snd) = (&mut pair.fst, &mut pair.snd);
    if false { let _ = &(*pair).snd; let _ = &*fst; } // mutation
    let _ = &mut *fst; let _ = &mut *snd;
}
```

Fig. 19. Source Rust approximation of a mutant that passes borrow checking

Prusti. As discussed in Sec. 4, Prusti [1] translates Rust verification problems into a separation logic setting. Its encoding is presented in terms of the idea of a *place capability summary*¹⁶, which is presented semi-formally as a representation analogous to the leaves in our PCGs. However, rules for manipulating Rust types, modelling borrows etc. are only formalised indirectly via the target separation logic. Prusti proposed using separation logic *magic wands* to represent a pending transfer of capabilities back to borrowed-from place(s). In *proving* these magic wands, Prusti's verification requires a step-by-step justification for *how* these capabilities are returned (as well as that any user-specifications are guaranteed). At time of writing, Prusti did not support re-borrowing in loops, re-borrows concerning nested lifetimes in types, or function calls using multiple lifetimes.

The prototype developed in our evaluation shows that our novel model is not only usable for tools such as Prusti, but helps to alleviate some limitations. In particular, our model can provide the detailed annotations needed to drive pre-existing Prusti proofs automatically, without the need for the tool's own complex inference algorithms. In addition, we were able to relatively support examples with reborrowing inside loops and more-general function signatures than Prusti could support previously; is it likely that our model will enable further such improvements in future [9].

Aeneas. The Aeneas project defines a formal model of (its own algorithms for) Rust's type- and borrow-checking, as well as a verification platform based on these [13, 14]. Verification is performed by translation from (safe) Rust into a functional language, embedded into a variety of proof assistants for manual proof; both moves and borrows of capabilities are handled by assignment from one value to another. When Rust (re-)borrows span function calls and loop bodies, additional functions called *backward functions* are generated, whose implementations must define how to undo the steps performed as the corresponding borrows were created.

Aeneas' model is fully formalised and (unlike ours) also *defines its own type- and borrow-checker* (in fact, a class of potential algorithms). However, their model of borrowing has several limitations when compared to ours: (1) it does not represent precise path-sensitive information for (re)borrows, even for loop/function-free code, (2) there is no support for reborrowing via nested lifetimes in types (for example, borrows stored in a struct type), which are not mentioned in the formal model or supported by the tool, and (3) the technique for computing loop invariants presented in [13] relies on heuristics which (they claim) need not terminate and uses heuristic join operations that can introduce less-precise summaries of loops than Rust's borrow checker. Conversely, our modelling of loops captures Rust's borrow-checking constraints precisely, does not require a fixpoint calculation (we reuse the compiler's results), and also applies to types with nested lifetimes.

We are confident that our model could however be used to generate the information required by the Aeneas verifier for its *translation*: managing recursive representations of types is similar, and the generation of backward functions requires similar steps to the proofs of magic wands in Prusti, for which we have demonstrated proof-of-concept support. As with our Prusti prototype,

 $^{^{16}}$ The name for our model here is inspired by this notion.

we believe it might also be possible to lift some of the existing limitations of Aeneas using the information provided by our model, especially with respect to general loops and nested lifetimes.

Aquascope. Aquascope [6] is a Rust analysis designed to help programmers visualise the type-checking of their Rust programs. The tool extracts ownership and borrowing information directly from a customised version of the Rust compiler, to enable extracting this information even for programs that do not type-check. While a notion of capabilities (called permissions in their work) per program point is visible in Aquascope, as well as whether or not a place is currently borrowed; information about why and how a place is borrowed is not available, nor is any information path-sensitive. Consistently with these choices, loops and function calls are not summarised, and to our knowledge nested lifetimes are not directly visualised. We believe in principle that all the information needed by Aquascope could, however, be quite easily extracted from PCGs, except that we currently only provide such information for programs the Rust compiler accepts.

RustBelt, RustHornBelt and Creusot. RustBelt [15] is an early formal model for Rust, and defines a logical interpretation of Rust's type-checking as an instantiation of the Iris framework [16]. This interpretation models Rust ownership using separation logic predicates, but borrows via a custom logic of ghost state called the *lifetime logic*; in particular, this setup allows proofs about *unsafe* Rust, where the standard meanings of borrows might be customised for specific library implementations.

RustHornBelt [20] is a variant of RustBelt designed to enable functional specifications on verified libraries. This is achieved via a novel usage of *prophecy values* to reflect borrows and their values as they *will* be eventually modified. Although prophecies are an alternative means of reasoning about borrows to showing how capabilities flow back, in the *soundness proof* for RustHornBelt one has to show the existence of an acyclic relation between the borrows, summarising their dependencies; this is similar to the borrowing information produced by our model.

These models are not directly comparable with ours: they do not connect directly to Rust programs or the compiler's representations; their languages are loop-free (automated loop analysis is particularly challenging in Rust). However, the models are fully formalised and can reason about unsafe code, while ours concerns only the aspects of Rust that the type system governs directly. Our rules for creating and dereferencing borrows take some inspiration from RustBelt: the dual usage of place nodes and lifetime projection nodes is reminiscent of RustBelt's rules, which require not only access to the borrowed memory but a justification that the corresponding lifetime is currently live.

Creusot [8] is a Rust verifier based on the ideas of the RustHornBelt model. It translates Rust programs into functional programs but in a different manner to Aeneas; it exposes the notion of prophecy values in specifications, so that users can write specifications concerning (re)borrows that span function calls and loops by relating their current and *future* values. While this technique does not require summaries of borrow information to the same extent, we believe that visualising and understanding these summaries (for example for loops) might still help tool users to understand which specifications could be meaningful to express. We are confident that Creusot's translation could also be driven by the information in our model.

Other Rust Semantics. We are aware of several older attempts to formalise aspects of Rust's type system (e.g. [17, 22, 27, 28]); to our knowledge, these do not cover the detailed borrowing concerns addressed by our model, and are typically for idealised definitions of Rust-like languages. Some are operational semantics, which by nature do not require the same complex rules to summarise Rust's implied properties for general path-sensitive information, loops or function calls.

Other Rust Analyses. Many Rust verification and analysis tools could potentially make use of our model. Verus [18] is a verifier whose translation to SMT requires similar information; while the tool

doesn't currently support reborrows that span function calls or loops, there is long-standing interest in supporting this in future [10], which would require analogous solutions to those we present in this paper. Flux [19] is a Rust verifier based on Liquid Types which also requires compiler-generated information for its translation that our model can provide. Rudra [2] is a mature program analysis for Rust, whose analyses require type-system-related information; to our knowledge these analyses are all flow-insensitive, and our model could easily provide (more than) the required basis.

6 Conclusions and Future Work

We presented Place Capability Graphs, a novel model of Rust's type and borrow checking. We demonstrated the construction of PCGs from Rust's internal programmatic representation. In our evaluation, we showed that PCGs support a large subset of real-world Rust code, accurately reflect the constraints of the borrow-checker, and can be used as the basis for program analysis tools.

There are several promising avenues of future work. We could extend our model to support more features of Rust, such as closure calls and potentially even unsafe code. Alternatively, we could also continue the formal development of our work by defining a semantics for the model. We are hopeful that our implementation of Place Capability Graphs can serve as the basis for a wide range of Rust analysis tools, something which we have already demonstrated via our integrations into Prusti and Flowistry. Moving forward, we intend to work with the community to identify other applications of our model and, if needed, extend the model to support additional use cases.

7 Data Availability Statement

We will submit all aspects of our evaluation (including access to the standalone implementation of our model) as an artefact, including sufficient instructions to reproduce our various evaluations. Our implementation also produces visualisations similar to the figures used in our paper, which can be used to manually inspect instances of our model as generated on chosen Rust code.

References

- [1] Vytautas Astrauskas, Peter Müller, Federico Poli, and Alexander J. Summers. 2019. Leveraging Rust types for modular specification and verification. *Proc. ACM Program. Lang.* 3, OOPSLA (2019), 147:1–147:30. https://doi.org/10.1145/3360573
- [2] Yechan Bae, Youngsuk Kim, Ammar Askar, Jungwon Lim, and Taesoo Kim. 2021. Rudra: Finding Memory Safety Bugs in Rust at the Ecosystem Scale. In SOSP '21: ACM SIGOPS 28th Symposium on Operating Systems Principles, Virtual Event / Koblenz, Germany, October 26-29, 2021, Robbert van Renesse and Nickolai Zeldovich (Eds.). ACM, 84– 99. https://doi.org/10.1145/3477132.3483570
- [3] John Boyland, James Noble, and William Retert. 2001. Capabilities for Sharing: A Generalisation of Uniqueness and Read-Only. In European Conference on Object-Oriented Programming (ECOOP) (Lecture Notes in Computer Science, Vol. 2072), Jørgen Lindskov Knudsen (Ed.). Springer, 2–27.
- [4] Elias Castegren and Tobias Wrigstad. 2016. Reference Capabilities for Concurrency Control. In 30th European Conference on Object-Oriented Programming (ECOOP 2016) (Leibniz International Proceedings in Informatics (LIPIcs), Vol. 56), Shriram Krishnamurthi and Benjamin S. Lerner (Eds.). Schloss Dagstuhl-Leibniz-Zentrum fuer Informatik, Dagstuhl, Germany, 5:1–5:26. https://doi.org/10.4230/LIPIcs.ECOOP.2016.5
- [5] Sylvan Clebsch, Sophia Drossopoulou, Sebastian Blessing, and Andy McNeil. 2015. Deny Capabilities for Safe, Fast Actors. In International Workshop on Programming Based on Actors, Agents, and Decentralized Control (AGERE! 2015). ACM, 1–12.
- [6] Will Crichton, Gavin Gray, and Shriram Krishnamurthi. 2023. A Grounded Conceptual Model for Ownership Types in Rust. Proc. ACM Program. Lang. 7, OOPSLA2, Article 265 (Oct. 2023), 29 pages. https://doi.org/10.1145/3622841
- [7] Will Crichton, Marco Patrignani, Maneesh Agrawala, and Pat Hanrahan. 2022. Modular information flow through ownership. In Proceedings of the 43rd ACM SIGPLAN International Conference on Programming Language Design and Implementation (San Diego, CA, USA) (PLDI 2022). Association for Computing Machinery, New York, NY, USA, 1–14. https://doi.org/10.1145/3519939.3523445
- [8] Xavier Denis, Jacques-Henri Jourdan, and Claude Marché. 2022. Creusot: A Foundry for the Deductive Verification of Rust Programs. In Formal Methods and Software Engineering - 23rd International Conference on Formal Engineering Methods, ICFEM 2022, Madrid, Spain, October 24-27, 2022, Proceedings (Lecture Notes in Computer Science, Vol. 13478), Adrián Riesco and Min Zhang (Eds.). Springer, 90-105. https://doi.org/10.1007/978-3-031-17244-1_6
- [9] Prusti Developers. 2024-2025. Personal Communication.
- [10] Verus Developers. 2022. Returning mutable references (discussion). https://github.com/verus-lang/verus/discussions/35 Accessed March, 2025.
- [11] Colin S. Gordon, Matthew J. Parkinson, Jared Parsons, Aleks Bromfield, and Joe Duffy. 2012. Uniqueness and Reference Immutability for Safe Parallelism. SIGPLAN Not. 47, 10 (Oct. 2012), 21–40.
- [12] Philipp Haller and Martin Odersky. 2010. Capabilities for Uniqueness and Borrowing. In European Conference on Object-Oriented Programming (ECOOP) (Lecture Notes in Computer Science, Vol. 6183), Theo D'Hondt (Ed.). Springer, 354–378.
- [13] Son Ho, Aymeric Fromherz, and Jonathan Protzenko. 2024. Sound Borrow-Checking for Rust via Symbolic Semantics. Proc. ACM Program. Lang. 8, ICFP, Article 251 (Aug. 2024), 29 pages. https://doi.org/10.1145/3674640
- [14] Son Ho and Jonathan Protzenko. 2022. Aeneas: Rust verification by functional translation. Proc. ACM Program. Lang. 6, ICFP (2022), 711–741. https://doi.org/10.1145/3547647
- [15] Ralf Jung, Jacques-Henri Jourdan, Robbert Krebbers, and Derek Dreyer. 2018. RustBelt: securing the foundations of the rust programming language. Proc. ACM Program. Lang. 2, POPL (2018), 66:1–66:34. https://doi.org/10.1145/3158154
- [16] RALF JUNG, ROBBERT KREBBERS, JACQUES-HENRI JOURDAN, ALEŠ BIZJAK, LARS BIRKEDAL, and DEREK DREYER. 2018. Iris from the ground up: A modular foundation for higher-order concurrent separation logic. *Journal of Functional Programming* 28 (2018), e20. https://doi.org/10.1017/S0956796818000151
- [17] Shuanglong Kan, David Sanán, Shang-Wei Lin, and Yang Liu. 2018. K-Rust: An Executable Formal Semantics for Rust. CoRR abs/1804.07608 (2018). arXiv:1804.07608 http://arxiv.org/abs/1804.07608
- [18] Andrea Lattuada, Travis Hance, Chanhee Cho, Matthias Brun, Isitha Subasinghe, Yi Zhou, Jon Howell, Bryan Parno, and Chris Hawblitzel. 2023. Verus: Verifying Rust Programs using Linear Ghost Types (extended version). *CoRR*

- abs/2303.05491 (2023). https://doi.org/10.48550/arXiv.2303.05491 arXiv:2303.05491
- [19] Nico Lehmann, Adam Geller, Gilles Barthe, Niki Vazou, and Ranjit Jhala. 2022. Flux: Liquid Types for Rust. CoRR abs/2207.04034 (2022). https://doi.org/10.48550/arXiv.2207.04034 arXiv:2207.04034
- [20] Yusuke Matsushita, Xavier Denis, Jacques-Henri Jourdan, and Derek Dreyer. 2022. RustHornBelt: a semantic foundation for functional verification of Rust programs with unsafe code. In PLDI '22: 43rd ACM SIGPLAN International Conference on Programming Language Design and Implementation, San Diego, CA, USA, June 13 17, 2022, Ranjit Jhala and Isil Dillig (Eds.). ACM, 841–856. https://doi.org/10.1145/3519939.3523704
- [21] Peter Müller, Malte Schwerhoff, and Alexander J. Summers. 2016. Viper: A Verification Infrastructure for Permission-Based Reasoning. In Verification, Model Checking, and Abstract Interpretation 17th International Conference, VMCAI 2016, St. Petersburg, FL, USA, January 17-19, 2016. Proceedings (Lecture Notes in Computer Science, Vol. 9583), Barbara Jobstmann and K. Rustan M. Leino (Eds.). Springer, 41–62. https://doi.org/10.1007/978-3-662-49122-5 2
- [22] Eric W. Reed. 2015. *Patina: A Formalization of the Rust Programming Language.* Technical Report UW-CSE-15-03-02. University of Washington.
- [23] Rust contributors. 2019. The Polonius Reference Implementation for the Rust Borrow-Checker. https://github.com/rust-lang/polonius Accessed April 4, 2019.
- [24] Rémy Rakic and Niko Matsakis on behalf of The Polonius Working Group. 2023. Polonius Update. https://blog.rust-lang.org/inside-rust/2023/10/06/polonius-update.html Accessed March 24, 2025.
- [25] Sven Stork, Karl Naden, Joshua Sunshine, Manuel Mohr, Alcides Fonseca, Paulo Marques, and Jonathan Aldrich. 2014.
 AEMinium: A Permission-Based Concurrent-by-Default Programming Language Approach. ACM Trans. Program.
 Lang. Syst. 36, 1 (March 2014), 2:1–2:42.
- [26] Alexa VanHattum, Daniel Schwartz-Narbonne, Nathan Chong, and Adrian Sampson. 2022. Verifying Dynamic Trait Objects in Rust. In 44th IEEE/ACM International Conference on Software Engineering: Software Engineering in Practice, ICSE (SEIP) 2022, Pittsburgh, PA, USA, May 22-24, 2022. IEEE, 321-330. https://doi.org/10.1109/ICSE-SEIP55303.2022.9794041
- [27] Feng Wang, Fu Song, Min Zhang, Xiaoran Zhu, and Jun Zhang. 2018. KRust: A Formal Executable Semantics of Rust. CoRR abs/1804.10806 (2018). arXiv:1804.10806 http://arxiv.org/abs/1804.10806
- [28] Aaron Weiss, Daniel Patterson, and Amal Ahmed. 2018. Rust Distilled: An Expressive Tower of Languages. arXiv preprint arXiv:1806.02693 (2018).