From Flatland to Space: Teaching Vision-Language Models to Perceive and Reason in 3D

Jiahui Zhang^{1*} Yurui Chen^{1*} Yanpeng Zhou^{2*} Yueming Xu¹ Ze Huang¹ Jilin Mei¹ Junhui Chen¹ Yu-Jie Yuan² Xinyue Cai² Guowei Huang² Xingyue Quan² Hang Xu² Li Zhang^{1†}

¹ School of Data Science, Fudan University ² Huawei Noah's Ark Lab https://fudan-zvg.github.io/spar



Figure 1. Overview of our *Spatial Perception And Reasoning (SPAR)* dataset and benchmark. Our dataset is sourced from 4,500 scenes and comprises 33 spatial tasks spanning single-view, multi-view, and video settings. Our benchmark includes over 7,000 carefully curated high-quality samples to comprehensively evaluate the spatial understanding capabilities of existing models.

Abstract

Recent advances in LVLMs have improved vision-language understanding, but they still struggle with spatial perception, limiting their ability to reason about complex 3D scenes. Unlike previous approaches that incorporate 3D representations into models to improve spatial understanding, we aim to unlock the potential of VLMs by leveraging spatially relevant image data. To this end, we introduce a novel 2D spatial data generation and annotation pipeline built upon scene data with 3D ground-truth. This pipeline enables the creation of a diverse set of spatial tasks, ranging from basic perception tasks to more complex reasoning tasks. Leveraging this pipeline, we construct SPAR-7M, a large-scale dataset generated from thousands of scenes across multiple public datasets. In addition, we introduce SPAR-Bench, a benchmark designed to offer a more comprehensive evaluation of spatial capabilities compared to existing spatial benchmarks, supporting both single-view and multi-view inputs. Training on both SPAR-7M and large-scale 2D datasets enables our models to achieve state-of-the-art performance on 2D spatial benchmarks. Further fine-tuning on 3D task-specific datasets yields competitive results, underscoring the effectiveness of our dataset in enhancing spatial reasoning.

1. Introduction

Recent advances in Large Vision-Language Models (LVLMs) have significantly enhanced vision-language un-

^{*}Equally contributed.

[†]Corresponding author (lizhangfd@fudan.edu.cn).

Dataset	Perception	Reasoning	Single view	Multi view†	Video	Task types	QA quantity
ScanQA [4]	X	1	×	×	1	-	27k
SQA3D [42]	×	1	×	×	1	16	33k
3D-LLM [25]	×	1	×	×	1	9	659k
LEO [29]	×	1	1	×	1	9	513k
SceneVerse [31]	X	1	×	×	1	3	2.5M
MMScan [40]	1	1	×	×	1	20	6.9M
SPAR-7M	1	1	1	1	1	33	7 M

Table 1. Comparison of spatial understanding datasets. † Multi-view questions involve 3–5 images per QA pair.

derstanding [3, 5, 21, 34, 35]. However, to empower VLMs to better interact with the physical world, spatial understanding is essential, serving as a cornerstone of embodied intelligence. Nevertheless, current VLMs exhibit limited spatial perception, often struggling with comprehensive understanding and reasoning about spatial relationships in complex scenes [10, 14, 19, 21, 25, 55].

A recent line of research explores enhancing spatial understanding by incorporating 3D representations of scenes [14, 23, 25, 28, 55]. However, these methods encounter several challenges. First, 3D data are scarce, with suboptimal quality and uneven distribution, making them unsuitable for large-scale pretraining. Second, designing a model (e.g., a point cloud encoder) to effectively capture 3D information is inherently challenging, particularly since complete 3D representations are often inaccessible in realworld scenarios. Moreover, these approaches modify the network architecture, hindering seamless integration with existing VLM frameworks [5, 35].

This raises the question: Is it truly necessary to incorporate 3D representations into VLMs? For humans, spatial understanding of the relationship between surrounding objects is innate, relying on the ability to observe and implicitly reconstruct the entire space from 2D observations. Motivated by this capability, we seek to empower VLMs to acquire spatial understanding directly from large-scale 2D data (e.g., image inputs), enabling them to perform spatial reasoning without explicit 3D supervision. To facilitate this, we construct a spatially relevant dataset tailored for training and evaluation. Additionally, to enable VLMs to tackle a broader range of 3D tasks, we design a multi-view-based 3D grounding approach.

We categorize spatial understanding into two levels: **spatial perception**, which encompasses fundamental spatial concepts such as depth, distance, relative positions, and camera viewpoints, representing low-level cognitive abilities; and **spatial reasoning**, which involves higher-order spatial understanding, requiring the ability to infer and construct 3D scenes implicitly. A critical aspect of this advanced ability is view matching, particularly in multi-view contexts.

Building on these two levels of spatial understanding, we introduce SPAR-7M, a dataset encompassing 33 tasks that cover a diverse range of complexities. These include basic perception tasks such as depth and distance estimation, more advanced reasoning tasks like cross-view object matching, and high-level spatial cognition tasks such as spatial imagination. To systematically organize these tasks, we classify them into three levels: low, medium, and high, reflecting a progression from Spatial Perception to Spatial Reasoning. To generate the necessary training data, we introduce a 2D data generation and annotation pipeline that derives rich supervision from 3D scene data. The resulting dataset, SPAR-7M, provides precise 3D groundtruth annotations, significantly improving both task diversity and reliability. Unlike existing approaches that rely solely on 2D annotations [10, 19], our dataset enables a more structured and accurate assessment of spatial understanding. Tab. 1 illustrates the diversity of input formats and task types within our dataset.

Despite the growing body of spatial benchmarks, many focus predominantly on high-level spatial reasoning, often overlooking fundamental spatial perception [24, 40, 41]. Furthermore, some benchmarks, particularly those using internet-collected images, struggle to effectively evaluate multi-view tasks, while others based on video inputs are not well-aligned with typical model inputs [51]. To address these limitations, we select 20 tasks from the *SPAR-7M* validation set. After carefully manual validation and filtering, we created *SPAR-Bench*, a comprehensive benchmark consisting of 7,207 questions that span tasks from basic perception to complex reasoning. *SPAR-Bench* supports both single-view and multi-view inputs, offering a more holistic and diverse evaluation of spatial understanding.

Our main contributions are as follows: (i) We introduce a 2D spatial QA generation pipeline leveraging 3D ground truth, enabling the creation of both single-view and multiview data. Additionally, we present *SPAR-7M*, a comprehensive dataset covering a wide range of tasks from spatial perception to reasoning. (ii) We present *SPAR-Bench*, a benchmark for evaluating the spatial capabilities of existing models. (iii) By training models on both *SPAR-7M* and large-scale 2D internet datasets, we achieve state-of-the-art performance across multiple 2D spatial benchmarks. Moreover, even with 2D-only inputs, further fine-tuning on 3D task-specific datasets yields competitive results. We will open-source *SPAR-7M* and *SPAR-Bench*, facilitating further research in spatial understanding.

2. Related work

Datasets for spatial understanding. Existing multimodal datasets primarily provide single-view or limited multi-view images, often designed for image-text retrieval or basic visual question answering, making them insufficient for advanced 3D reasoning [33, 38, 39, 53]. Some datasets attempt to address this by collecting large-scale images from the internet, but they lack precise 3D annotations, relying instead on estimation models, which limits their effectiveness in multi-view and spatial reasoning tasks [10, 19]. Others incorporate image sequences or 3D scene representations for object counting, spatial relationship reasoning, or grounding, but they mainly focus on high-level semantics while neglecting low-level geometric cues such as depth, distance, and camera parameters [4, 16, 42]. To overcome these limitations, we propose a 3D-ground-truth-based data generation pipeline capable of rendering single-view, multi-view, and video-based data. Our approach ensures precise spatial supervision, covering a broad spectrum of tasks from basic perception to advanced reasoning, structured into three difficulty levels. This provides a more comprehensive and scalable solution compared to existing datasets.

Benchmarks for evaluating spatial understanding. Existing spatial understanding benchmarks primarily focus on high-level reasoning while often neglecting fundamental spatial perception tasks [4, 24, 40–42, 51]. Most of them rely on either single-view images or video inputs, with limited consideration of multi-view settings, despite their ability to better represent local 3D structures. Single-view images restrict the complexity of questions that can be formulated and provide an incomplete assessment of VLMs' spatial reasoning capabilities. While some benchmarks use video inputs [51], many VLMs are not optimized for video processing, but this does not necessarily mean they lack spatial reasoning abilities. To address these limitations, we introduce SPAR-Bench, a more comprehensive benchmark that encompasses both fundamental and advanced spatial tasks. It supports both single-view and multi-view inputs, enabling a more systematic and reliable evaluation of spatial understanding.

3. Method

Our research aims to equip VLMs with robust and accurate spatial understanding, focusing on both fundamental 3D perception and higher-order spatial reasoning and imagination. To address the challenges posed by limited data, we propose a novel data generation pipeline that creates a diverse range of spatial understanding tasks. Our pipeline leverages 3D scenes from ScanNet [20], ScanNet++ [52], and Structured3D [54], ensuring a broad and diverse representation of indoor environments. Along with this, we introduce a new benchmark to provide a comprehensive evaluation of models' spatial capabilities. In the following sections, we first detail our data generation pipeline (Sec. 3.1) and the key characteristics of SPAR-7M (Sec. 3.2). We then introduce SPAR-Bench (Sec. 3.3), followed by an analysis of data quality and the manual filtering process used to ensure benchmark reliability (Sec. 3.4). Additionally, in Sec. 3.5, we present a multi-view-based 3D grounding approach designed to enhance VLMs' ability to tackle a broader range of 3D tasks.

3.1. 3D-driven data generation pipeline

This section introduces our proposed data generation pipeline. The input consists of the scene mesh, 3D bounding boxes of objects, the intrinsic and extrinsic of camera sequences, and the image sequences. Through a series of steps, including filtering, extracting 3D information, and task construction, we generate diverse spatial understanding data. The key steps of this process are detailed below, with the overall workflow illustrated in Fig. 2.

Filtering and subsampling. In the first step, we focus on reducing data redundancy by filtering out images with minimal camera movement. Specifically, each image is associated with a camera pose (position and orientation). If an image's camera position is within a distance threshold of a retained image and its orientation differs by less than an angular threshold, it is considered redundant and removed. The whole process is similar to keyframing and the implementation details can be found in the appendix 6.2.

Extracting 3D information. In the second step, we extract global 3D information from the scene and create a unified data structure to support multi-view cross-retrieval and annotation. This structure facilitates dataset alignment and the generation of downstream tasks. Each scene is represented by two types of entities: Image records and object records.

 Image record stores metadata for each image, such as its index, camera intrinsics and extrinsics, image dimensions, and the list of objects present. Each object is linked



Figure 2. **Data generation pipeline.** Our pipeline consists of three main parts: (1) Filtering redundant images by sampling approach. (2) Extracting scene 3D information and creating a unified data structure to support multi-view cross-retrieval and annotation. (3) Leveraging metadata to automatically generate a variety of tasks and forms of QA data.

to its 3D bounding box, 3D center point in world coordinates, and its 2D bounding box on the image plane.

• **Object record** contains global information for all objects in the scene, including their ID, category, and a list of images where they appear (referencing the corresponding image indices).

This structure creates a unified mapping between image and object data in world coordinates, simplifying the alignment and management of data from different sources. It also lays the foundation for multi-dataset annotations and task generation. Additional technical details can be found in the appendix 6.3.

Multi-tasks generation. In the third step, we use the complete 3D scene information to automatically generate a variety of tasks and corresponding QA pairs. Each task is configured with key details such as task type (e.g., distance prediction, spatial relations), input image count, question format, and the object types involved (object-to-object or object-to-observer relations).

For each task, we follow a specific pipeline to generate annotations, ensuring flexibility to extend or customize tasks as needed. After generating the annotations, placeholders in the template (e.g., [label_A], [label_B], [left_right]) are replaced with actual object labels and computed spatial information. The templates are initially created by humans, expanded with the help of GPT, and then refined through manual selection to ensure diversity and accuracy.

While the process for generating tasks is consistent, each of the 31 tasks follows its own unique procedure based on its specific requirements. Detailed information about task pipelines, QA templates, and GPT prompting can be found in the appendix 6.4.

3.2. Spatial dataset construction

Based on our data generation pipeline (Sec. 3.1), we construct *SPAR-7M*, a large-scale dataset designed for spatial understanding. *SPAR-7M* consists of approximately 4K indoor 3D scenes from diverse sources, covering 33 task types with over 7 million QA pairs. Each QA pair is paired with camera intrinsics, extrinsics, and depth information, enabling both multi-view reasoning and 3D spatial inference. The dataset includes tasks ranging from basic spatial perception (e.g., depth estimation, distance measurement) to high-level spatial reasoning (e.g., camera position prediction, multi-view spatial relations) (Fig. 4).

To comprehensively evaluate different aspects of spatial understanding, we incorporate three types of input formats: single-view, multi-view, and video. Single-view tasks test a model's ability to infer spatial properties from a single image, while multi-view tasks require integrating spatial information across different viewpoints. The video-based setting goes beyond individual frames to introduce higherlevel spatial perception and scene-level reasoning, challenging the model to understand the spatial structure of a more complex environment. While not all tasks include every input format, this diversity ensures a broad assessment of spatial reasoning across various contexts.

In addition to varying input formats, we categorize tasks based on their spatial relationships into object-object (OO) and object-camera (OC) types. OO tasks focus on the rel-



Figure 3. Dataset and benchmark visualization. We visualize some samples from our proposed SPAR-7M and SPAR-Bench. We show the diversity and richness of our dataset, which covers different task types, input types, and object types.

ative positioning of objects, such as determining whether one object is to the left, right, or behind another. OC tasks, on the other hand, emphasize the relationship between objects and the camera, requiring models to infer viewpointdependent properties. For multi-image inputs, one image is randomly selected as the primary viewpoint, serving as the reference for spatial reasoning.

3.3. Spatial benchmark construction

To systematically evaluate spatial understanding, we introduce *SPAR-Bench*, a benchmark designed to assess models across diverse spatial reasoning tasks and input modalities. Unlike existing benchmarks that primarily focus on highlevel reasoning or rely on video-based inputs, *SPAR-Bench* provides a more balanced evaluation by covering both spatial perception and reasoning in single-view and multi-view settings.

SPAR-Bench consists of 20 tasks covering depth estimation, distance prediction, spatial relation reasoning, and spatial imagination. These tasks are sampled from the SPAR-7M test set, with 400 QA pairs per task. After manual quality checking, the final benchmark includes 7207 QA pairs. Each task is formulated as either numerical prediction (fillin-the-blank) or classification (multiple-choice selection), evaluated using Mean Relative Absolute Error (MRA) and accuracy, respectively.

To capture different levels of spatial understanding, single-view tasks focus on spatial inference from a single image, while multi-view tasks require reasoning across multiple perspectives, such as object matching and camera pose inference. A full list of tasks and details on data construction are provided in the appendix 6.1. We visualize the dataset and benchmark in Fig. 3. More detailed QA of datasets can be found in appendix 6.5.



Figure 4. **Dataset statistics.** Our Dataset can be categorized into high, medium, and low three levels, totaling 33 subtasks.

3.4. Data quality check

To ensure the reliability of our proposed benchmark, we conduct a human verification process. Specifically, we sample 400 questions per task in the validation set, forming an 8,000-question benchmark. These questions undergo manual inspection, taking approximately 140 human hours. After filtering out problematic cases, 7,207 questions were retained, resulting in a dataset acceptance rate of 90.1%.

During verification, we focus on identifying vague ques-

tion stems, incorrect or misleading choices, ambiguous answers, and factual inconsistencies. Errors are marked, discussed, and either corrected or removed. This rigorous process ensures that our benchmark maintains high quality and reliability.



Figure 5. **Our 3D grounding pipeline via VLM.** For multi-view inputs, we decompose the task into frame selection and mono-3D grounding on the selected frame.

3.5. 3D grounding with VLMs

Expressing an object's spatial position within a scene is a crucial capability. Previous methods primarily relied on point cloud regression or classifying proposal bounding boxes. For video inputs, temproal grounding in VLM [26, 44] is widely explored, [50] use VLM as a frame selector to achieve 3D grounding with a series of tools. In contrast, we propose a novel 3D grounding approach that reformulates this task as a text generation problem, enabling seamless integration with VLMs. Specifically, we transform the 3D grounding task into a frame selection followed by mono-3D grounding. In the case of multi-view input, an object can be localized within a visible frame, allowing us to infer its UV coordinates, depth, and size, achieving accurate 3D localization through the camera pose of that frame. While this method already enables the localization of a 3D bounding box, we further introduce an optional refinement process. By optimally matching the predicted 3D bounding box with the proposal bounding box, we obtain the final refined result. The overall grounding pipeline is illustrated in Fig. 5.

4. Experiments

In this section, we assess the effectiveness of our dataset and investigate the potential upper limits of spatial reasoning in VLMs from three key perspectives:

- **Performance on existing spatial benchmarks:** We examine how pretraining on *SPAR-7M* improves model performance on image-based spatial benchmarks.
- Evaluation on our in-domain benchmark SPAR-Bench: We assess the pretrained model's capabilities using our proposed benchmark, SPAR-Bench, which provides a comprehensive evaluation of spatial understanding across various tasks.
- Fine-tuning on 3D-specific tasks: To investigate the generalization ability of our approach, we perform supervised fine-tuning (SFT) on 3D-specific benchmarks, including spatial QA and 3D grounding tasks.

Furthermore, in Sec. 4.4, we analyze the impact of different data compositions and training strategies on model performance, offering insights into optimal configurations for enhancing spatial reasoning capabilities.

Pretraining. To train a VLM with strong spatial capabilities while preserving generalization, we use a mixed pretraining dataset *SPAR-mix*. 40% of the data is uniformly sampled from our dataset, *SPAR-7M*, while the remaining 60% is uniformly sampled from general 2D data, sourced from the EMOVA configuration. This general data includes tasks such as image-text QA, chart understanding, and OCR. We pretrain the model on a total of 2 million samples, using the base model InternVL2.5-8B.

4.1. Evaluation on existing 2D spatial benchmarks

CV-Bench [48]. The Cambrian Vision-Centric Benchmark (CV-Bench) is a large-scale dataset with 2,638 manually verified examples, designed to assess 2D spatial relationships and object counting. It repurposes standard vision datasets, formulating natural language questions to evaluate spatial reasoning. Visual prompts, such as bounding boxes, are used to reduce ambiguity and ensure reliable assessments.

VSI-Bench [51]. The Visual-Spatial Intelligence Benchmark (VSI-Bench) evaluates spatial reasoning from egocentric video data, containing 5,000+ QA pairs from 288 realworld videos sourced from ScanNet [20], ScanNet++ [52], and ARKitScenes [7]. It covers diverse indoor environments and leverages object-level annotations for question generation. VSI-Bench includes eight tasks across three categories: configurational reasoning (object counting, relative position, route planning), measurement estimation (object and room size, absolute distance), and spatiotemporal reasoning (appearance order in videos). All questions undergo manual review to ensure accuracy.

To evaluate the effectiveness of our dataset, we compare models pretrained on our *SPAR-mix* (a combination of our data and the EMOVA dataset) against those trained solely

	VSI-Bench [51]	CV-Be	nch [48]	BLINK [24]	3DSRBench [41]	Seed-Image [33]	MME [22]	MMBench [38]	RealWorldQA [43]	TextVQA [46]
Methods		2D	3D			0				
GPT-4v [2]	-	64.3	73.8	51.1	-	71.6	1927	75.0	61.4	77.4
GPT-40 [2]	34.0	-	-	60.0	45.3	77.1	2310	83.4	75.4	-
Cambrain-8B [48]	-	72.3	72.0	-	-	74.7	1547	75.9	64.2	77.8
LLaVA-OV-7B [34]	25.3	-	-	48.2	44.1	-	1998	80.8	66.3	-
InternVL2-8B [18]	34.6	-	-	-	-	75.4	2215	81.7	-	77.4
Base VLM	32.4	74.2	78.5	46.6	58.3	76.5	2323	84.5	66.7	68.7
+EMOVA-2M	24.5	66.3	64.8	42.4	55.3	73.8	2186	80.2	63.1	63.8
+SPAR-mix	41.1	72.3	89.1	43.9	57.5	73.2	2163	79.9	64.7	62.9

Table 2. Comparison of model performance on various spatial understanding and 2D gerneral benchmarks. The base VLM is InternVL2.5-8B, and we use dynamic patch 3 during training and inference.

QA source	Hypersim [45]	SUNRGBD [47]	nuScenes [8]
Base VLM	73	87	62
+SPAR-mix	93	96	80

Table 3. Performance improvement on out-of-domain datasets in CV-Bench 3D.

on 2M EMOVA dataset [12]. As shown in Tab. 2, Pretraining with our mixed dataset results in significant performance gains and achieves SOTA performance on both the CV-Bench 3D and VSI-Bench benchmarks, which are specifically designed to evaluate spatial reasoning capabilities.Moreover, compared to models trained exclusively on 2M EMOVA dataset, our approach maintains competitive 2D generalization performance, demonstrating that integrating our dataset effectively enhances 3D spatial reasoning while preserving 2D capabilities.

Out-of-domain generalization ability. We also find that pretraining with our dataset enhances the model's spatial understanding across diverse, non-homogeneous datasets. Although our dataset is primarily derived from indoor scene datasets such as ScanNet [20], ScanNet++ [52], and Structured3D [54], the pretrained model shows consistent improvements across all tasks constructed with datasets different from ours in CV-Bench 3D, as shown in Tab. 3. Notably, on NuScenes, an outdoor dataset, our approach yields an 18-point performance gain, demonstrating its strong generalization ability beyond indoor environments.

4.2. Evaluation on SPAR-Bench

Our model performs well on out-of-domain spatial benchmarks. We further evaluate it on our *SPAR-Bench* and assess the spatial capabilities of other large language models.

Human vs. model performance. Tab. 4 shows that human performance far exceeds all models across all difficulty

levels. The average human score is 67.27, with 55.31 on low-level tasks, 72.32 on middle-level tasks, and 76.22 on high-level tasks. Among baseline models (excluding our fine-tuned version), Qwen2.5-VL-72B performs best, but still falls far below human level, with an average score of 39.40 (35.35 on low-level, 23.05 on middle-level, and 48.44 on high-level tasks). This highlights that even the strongest models struggle with complex spatial reasoning, particularly as task difficulty increases.

Limitations of existing models. The overall performance trend indicates that current models lack strong spatial perception and generalization ability for higher-order reasoning. The significant drop in scores from low-level to middle-level tasks suggests that models struggle to transition from basic spatial perception to more complex spatial relationships. For example, GPT-40 drops from 29.25 (low-level) to 24.93 (middle-level), and Qwen2.5-VL-72B drops from 35.35 to 23.05, highlighting difficulties in handling increasing spatial complexity. Additionally, performance in high-level tasks remains low, with most models scoring below 50, showing that multi-view and global spatial reasoning remain major challenges.

Impact of data augmentation. Fine-tuning InternVL2.5-8B on our dataset significantly improves performance across all levels. The fine-tuned model scores 65.53 on low-level, 63.01 on middle-level, and 61.29 on high-level tasks, showing notable gains in spatial reasoning. For example, Depth-OC increases from 25.78 (InternVL2.5-8B) to 81.53, and View Change Inference improves from 6.32 to 37.14. These improvements suggest that high-quality spatial data enhances model performance, particularly in multiview reasoning. However, the persistent gap between models and human performance indicates that data augmentation alone is insufficient, and further advances in multi-view fusion and spatial representation learning are needed.

Methods	Rank	.84k	Low	Depth-OC	Depth-OC-MV	Depth-OO	Depth-00-MV	Dist-OC	Dist-OC _{MV}	Dist-00	Dist-00.MV	Medium	PosMatch	CamMotion	ViewChgI	High	Distl-00	Distl-00.MV	ObjRel-OC-MV	ObjRel-OO	^{ObjRel-OO.MV}	Splmag-OC	Splmag-OC.MV	SpImag-00	Splmag-00-MV
Baseline																									
Chance Level (Random)	-	-	-	-	-	-	-	-	-	-	-	-	22.65	24.50	-	25.09	23.82	22.02	31.25	25.27	22.16	25.81	24.42	24.17	26.89
Chance Level (Frequency)	-	32.74	31.19	43.09	43.51	17.38	13.05	41.90	30.99	27.40	32.17	38.25	29.01	26.75	59.00	32.29	52.94	50.60	28.25	26.92	26.59	26.34	26.74	26.49	25.77
SPAR-Bench (tiny) API																									
Human Level	1	67.27	55.31	72.75	74.25	28.75	36.25	78.25	52.25	66.5	33.50	72.32	92	64	60.97	76.22	80	94	70	92	80	78	82	50	60
GPT-40 [2]	3	36.39	29.25	53.80	45.00	15.00	13.60	37.40	34.40	23.40	24.40	24.93	30	16	28.80	45.11	64	64	58	46	46	32	44	30	22
Claude-3.7-Sonnet [1]	5	21.77	25.43	41.00	45.40	11.20	12.20	42.60	19.60	26.00	5.40	7.33	16	6	0.00	23.33	40	48	22	36	14	12	20	6	12
Qwen2-VL-72B [49]	4	35.62	35.28	45.40	49.80	13.80	10.00	54.60	49.40	36.80	22.40	23.39	42	18	10.16	40.00	60	68	50	38	44	18	28	18	36
Qwen2.5-VL-72B [6]	2	39.40	35.35	53.20	46.80	17.80	29.00	49.60	57.40	14.40	14.60	23.05	40	16	13.16	48.44	74	74	60	56	50	20	34	24	44
SPAR-Bench (full)																									
InternVL2-2B [18]	10	28.06	21.74	18.06	24.81	23.20	20.97	19.47	19.95	26.83	20.61	22.83	39.69	23.00	5.81	35.42	51.18	55.95	46.00	31.59	23.82	36.02	34.30	17.55	22.41
InternVL2-4B [18]	4	32.01	28.94	23.94	27.22	20.00	18.12	42.57	40.16	31.29	28.18	29.16	49.87	21.00	16.62	35.70	56.76	55.36	40.25	36.81	25.21	28.76	32.27	21.19	24.65
InternVL2-8B [18]	3	33.02	26.83	25.75	30.88	20.67	20.78	39.03	36.19	19.15	22.19	36.49	63.36	28.00	18.11	37.37	64.71	54.46	42.75	37.36	26.32	34.14	31.10	20.86	24.65
InternVL2.5-2B [17]	8	30.14	25.79	39.67	39.72	12.12	15.03	30.94	29.59	20.22	19.02	22.93	37.91	24.25	6.64	36.41	51.47	56.85	50.25	33.79	24.10	27.15	35.17	26.49	22.41
InternVL2.5-4B [17]	7	30.55	25.66	29.06	32.97	21.77	16.83	20.84	26.85	28.13	28.79	29.75	47.07	33.25	8.92	35.16	54.12	58.93	35.50	29.67	34.63	24.73	31.39	19.21	28.29
InternVL2.5-8B [17]	1	36.28	29.46	25.78	29.31	23.79	18.76	46.82	42.68	22.62	25.89	31.88	61.32	28.00	6.32	43.80	59.71	56.85	51.75	44.23	41.55	36.56	41.57	22.52	39.50
LLaVA-OV-0.5B [34]	9	29.48	30.14	49.22	42.72	18.04	14.92	31.48	25.67	28.98	30.10	15.89	24.43	21.75	1.50	33.42	50.88	50.00	32.00	27.75	26.04	30.91	34.01	24.50	24.65
LLaVA-OV-7B [34]	5	31.20	21.79	30.33	26.94	18.58	13.87	10.43	13.64	31.24	29.29	26.13	38.68	30.25	9.47	40.14	56.47	55.06	37.25	48.63	38.23	30.38	33.72	26.49	35.01
Qwen2-VL-2b [49]	11	24.60	19.43	38.03	40.63	18.84	14.09	7.81	7.07	17.82	11.14	27.55	26.21	25.25	31.20	28.22	54.12	49.11	21.75	25.27	12.47	23.92	27.62	24.83	14.85
Qwen2-VL-7b [49]	6	30.74	27.52	35.97	35.22	20.83	12.88	28.68	29.95	28.21	28.45	20.44	35.37	20.25	5.69	37.03	59.71	52.38	30.25	38.46	41.00	22.04	28.49	22.52	38.38
Qwen2.5-VL-7b [6]	2	33.07	28.75	31.33	33.66	21.99	14.97	42.88	37.73	23.83	23.64	22.97	33.33	28.75	6.83	40.27	58.24	51.49	44.75	50.00	32.13	33.87	32.85	27.15	31.93
LLaVA-v1.5-7b [36]	12	23.65	10.85	5.17	12.53	17.37	11.34	7.25	5.26	18.73	9.12	26.50	24.43	26.75	28.31	34.09	51.18	52.38	34.25	24.18	26.87	34.68	29.94	22.52	30.81
LLaVA-v1.6-7b [37]	13	13.21	8.53	12.14	0.00	20.35	0.27	10.76	0.41	24.27	0.00	4.79	6.62	7.75	0.00	20.18	51.76	7.74	6.25	32.14	6.37	39.52	10.47	21.52	5.88
InternVL2.5-8B+SPAR-mix	-	63.25	65.53	81.53	79.22	38.25	35.51	78.93	79.18	68.13	63.50	63.01	78.88	73.00	37.14	61.29	86.47	79.76	64.00	69.23	59.00	47.31	50.00	42.38	53.50

Table 4. **Performance of different models on** *SPAR-Bench*. Shaded cells indicate the best scores in each category. The highest, second-highest, and third-highest scores in each category are highlighted with light red, light orange, and light yellow, respectively. *SPAR-Bench (tiny)* refers to a subset of the full benchmark, where 50 questions are sampled per task.

	SQA3D [42]	ScanQ	A [4]
Methods	EM@1	BLEU-4	CiDEr
3D-LLM [25]	-	12.0	69.4
Chat-3D v2 [27]	54.7	14.0	87.6
LEO [29]	50.0	13.2	101.4
LL3DA [14]	-	13.5	76.8
Scene-LLM [23]	54.2	12.0	80.0
SPAR-mix	58.1	15.3	90.7

 Table 5. Comparison of SQA3D and ScanQA performance across different LLM-based models.

Methods	Acc@0.25	Acc@0.5
ScanRefer [11]	37.3	24.3
MVT [30]	40.8	33.3
ViL3DRel [13]	47.9	37.7
3D-LLM [25]	30.3	-
Chat-3D v2 [27]	35.9	30.4
Grounded 3D-LLM [15]	47.9	44.1
SPAR-mix	48.8 (31.9)	43.1(12.4)

Table 6. Comparison of ScanRefer performance across different models. The content in "()" indicates results without refine.

4.3. Evaluation on 3D-specific tasks

In addition to the previously discussed spatial benchmarks, there are also tasks specifically defined in 3D scenes, which typically involve questions related to the entire scene. After pretraining the VLM using our dataset, we perform supervised fine-tuning (SFT) on 3D tasks to further investigate the spatial capabilities of the VLM.

Spatial QA. We use two benchmarks: ScanQA, which focuses on object attributes and spatial relationships within a scene, and SQA3D, a spatial benchmark where the task is to answer specific questions based on a given viewpoint description within the scene. This requires the model to demonstrate spatial imagination. We treat this as a multiview task during training. As shown in Tab. 5, despite not incorporating 3D information into the model, it still achieves the highest score when compared to the 3D LLMs.

3D grouding. We evaluate the 3D grounding capability of our model using the ScanRefer dataset. ScanRefer requires the model to locate objects in a scene based on textual descriptions. As shown in the Tab. 6, the values in parentheses represent the performance without proposal refinement. We observed that the VLM's depth predictions may sometimes be inaccurate when the distance is large due to the absence of 3D information. However, after refining, the results perform well. These results underline the potential of leveraging a VLM for grounding, showcasing its ability to perform well without the need for 3D information, while also tack-ling a more complex generative task.

		CV-Be	nch [48]	SPAR-Bench							
ViT	SPAR Ratio	2D	3D	Low	Medium	High					
Frozen	60%	68.68	89.67	66.87	64.28	55.43					
Unfrozen	60%	73.00	91.10	67.01	44.04	51.86					
Unfrozen	40%	74.13	89.09	66.97	42.21	48.19					

Table 7. **Performance comparison of different ViT configurations.** Models are trained with varying SPAR ratios and evaluated on CV-Bench (2D, 3D) and *SPAR-Bench*.

4.4. Ablation study

We evaluate the impact of ViT training strategies and SPAR data proportions on InternVL2.5-4B, trained with 2M samples from SPAR (3D) and EMOVA (2D). Tab. 7 presents results on CV-Bench (2D, 3D) and SPAR-Bench (Low, Middle, High levels).

Effect of freezing vs. unfreezing ViT. Comparing the first two rows with 60% SPAR, unfreezing ViT improves CV-Bench 2D (68.68 to 73.00) and 3D (89.67 to 91.10), but significantly degrades SPAR-Bench Middle (64.28 to 44.04) and High (55.43 to 51.86). This suggests that fine-tuning ViT benefits general vision tasks but weakens spatial reasoning, particularly in multi-view scenarios.

Effect of *SPAR-7M* **ratio.** Comparing the second and third rows with Unfrozen ViT, reducing the SPAR ratio from 60% to 40% slightly improves CV-Bench 2D (73.00 to 74.13) but reduces CV-Bench 3D (91.10 to 89.09). SPAR-Bench performance further drops, particularly in middle level (44.04 to 42.21) and high level (51.86 to 48.19) tasks, indicating that higher 3D data proportions enhance multiview spatial reasoning.

Findings. Freezing ViT preserves spatial understanding, while unfreezing benefits 2D tasks but harms multi-view reasoning. Higher SPAR ratios improve 3D reasoning, while increasing 2D data slightly benefits 2D vision at the cost of 3D perception.

5. Conclusion

We introduce *SPAR-7M*, a large-scale dataset constructed from thousands of scenes, specifically designed to enhance spatial reasoning. To provide a rigorous evaluation framework, we propose *SPAR-Bench*, a benchmark that offers a more comprehensive assessment of spatial understanding, supporting both single-view and multi-view inputs. Experimental results demonstrate that pretraining on *SPAR-7M* alongside general datasets enables models to achieve SOTA performance on VSI-Bench and CV-Bench 3D. Furthermore, fine-tuning on 3D task-specific datasets yields competitive results, highlighting the effectiveness of our dataset in bridging the gap between 2D and 3D spatial reasoning.

References

- Introducing the next generation of claude. https://www. anthropic.com/news/claude-3-family, 2024. 8
- [2] Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. arXiv preprint, 2023. 7, 8
- [3] Jean-Baptiste Alayrac, Jeff Donahue, Pauline Luc, Antoine Miech, Iain Barr, Yana Hasson, Karel Lenc, Arthur Mensch, Katherine Millican, Malcolm Reynolds, et al. Flamingo: a visual language model for few-shot learning. *NeurIPS*, 2022.
- [4] Daichi Azuma, Taiki Miyanishi, Shuhei Kurita, and Motoaki Kawanabe. Scanqa: 3d question answering for spatial scene understanding. In *CVPR*, 2022. 2, 3, 8
- [5] Jinze Bai, Shuai Bai, Yunfei Chu, Zeyu Cui, Kai Dang, Xiaodong Deng, Yang Fan, Wenbin Ge, Yu Han, Fei Huang, et al. Qwen technical report. *arXiv preprint*, 2023. 2
- [6] Shuai Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Sibo Song, Kai Dang, Peng Wang, Shijie Wang, Jun Tang, et al. Qwen2. 5-vl technical report. arXiv preprint, 2025. 8
- [7] Gilad Baruch, Zhuoyuan Chen, Afshin Dehghan, Tal Dimry, Yuri Feigin, Peter Fu, Thomas Gebauer, Brandon Joffe, Daniel Kurz, Arik Schwartz, et al. Arkitscenes: A diverse real-world dataset for 3d indoor scene understanding using mobile rgb-d data. arXiv preprint, 2021. 6
- [8] Holger Caesar, Varun Bankiti, Alex H Lang, Sourabh Vora, Venice Erin Liong, Qiang Xu, Anush Krishnan, Yu Pan, Giancarlo Baldan, and Oscar Beijbom. nuscenes: A multimodal dataset for autonomous driving. In CVPR, 2020. 7
- [9] Angel Chang, Angela Dai, Thomas Funkhouser, Maciej Halber, Matthias Niessner, Manolis Savva, Shuran Song, Andy Zeng, and Yinda Zhang. Matterport3d: Learning from rgb-d data in indoor environments. arXiv preprint, 2017. 16
- [10] Boyuan Chen, Zhuo Xu, Sean Kirmani, Brain Ichter, Dorsa Sadigh, Leonidas Guibas, and Fei Xia. Spatialvlm: Endowing vision-language models with spatial reasoning capabilities. In CVPR, 2024. 2, 3
- [11] Dave Zhenyu Chen, Angel X Chang, and Matthias Nießner. Scanrefer: 3d object localization in rgb-d scans using natural language. In ECCV, 2020. 8
- [12] Kai Chen, Yunhao Gou, Runhui Huang, Zhili Liu, Daxin Tan, Jing Xu, Chunwei Wang, Yi Zhu, Yihan Zeng, Kuo Yang, et al. Emova: Empowering language models to see, hear and speak with vivid emotions. arXiv preprint, 2024. 7
- [13] Shizhe Chen, Pierre-Louis Guhur, Makarand Tapaswi, Cordelia Schmid, and Ivan Laptev. Language conditioned spatial relation reasoning for 3d object grounding. *NeurIPS*, 2022. 8
- [14] Sijin Chen, Xin Chen, Chi Zhang, Mingsheng Li, Gang Yu, Hao Fei, Hongyuan Zhu, Jiayuan Fan, and Tao Chen. Ll3da: Visual interactive instruction tuning for omni-3d understanding reasoning and planning. In *CVPR*, 2024. 2, 8

- [15] Yilun Chen, Shuai Yang, Haifeng Huang, Tai Wang, Runsen Xu, Ruiyuan Lyu, Dahua Lin, and Jiangmiao Pang. Grounded 3d-llm with referent tokens. *arXiv preprint*, 2024.
- [16] Zhenyu Chen, Ali Gholami, Matthias Nießner, and Angel X Chang. Scan2cap: Context-aware dense captioning in rgb-d scans. In CVPR, 2021. 3
- [17] Zhe Chen, Weiyun Wang, Yue Cao, Yangzhou Liu, Zhangwei Gao, Erfei Cui, Jinguo Zhu, Shenglong Ye, Hao Tian, Zhaoyang Liu, et al. Expanding performance boundaries of open-source multimodal models with model, data, and testtime scaling. arXiv preprint, 2024. 8
- [18] Zhe Chen, Weiyun Wang, Hao Tian, Shenglong Ye, Zhangwei Gao, Erfei Cui, Wenwen Tong, Kongzhi Hu, Jiapeng Luo, Zheng Ma, et al. How far are we to gpt-4v? closing the gap to commercial multimodal models with open-source suites. arXiv preprint, 2024. 7, 8
- [19] An-Chieh Cheng, Hongxu Yin, Yang Fu, Qiushan Guo, Ruihan Yang, Jan Kautz, Xiaolong Wang, and Sifei Liu. Spatialrgpt: Grounded spatial reasoning in vision language models. *arXiv preprint*, 2024. 2, 3
- [20] Angela Dai, Angel X Chang, Manolis Savva, Maciej Halber, Thomas Funkhouser, and Matthias Nießner. Scannet: Richly-annotated 3d reconstructions of indoor scenes. In *CVPR*, 2017. 3, 6, 7, 12
- [21] Danny Driess, Fei Xia, Mehdi SM Sajjadi, Corey Lynch, Aakanksha Chowdhery, Ayzaan Wahid, Jonathan Tompson, Quan Vuong, Tianhe Yu, Wenlong Huang, et al. Palm-e: An embodied multimodal language model. 2023. 2
- [22] Chaoyou Fu, Peixian Chen, Yunhang Shen, Yulei Qin, Mengdan Zhang, Xu Lin, Jinrui Yang, Xiawu Zheng, Ke Li, Xing Sun, et al. Mme: A comprehensive evaluation benchmark for multimodal large language models. *arXiv preprint*, 2023. 7
- [23] Rao Fu, Jingyu Liu, Xilun Chen, Yixin Nie, and Wenhan Xiong. Scene-Ilm: Extending language model for 3d visual understanding and reasoning. *arXiv preprint*, 2024. 2, 8
- [24] Xingyu Fu, Yushi Hu, Bangzheng Li, Yu Feng, Haoyu Wang, Xudong Lin, Dan Roth, Noah A Smith, Wei-Chiu Ma, and Ranjay Krishna. Blink: Multimodal large language models can see but not perceive. In ECCV, 2024. 2, 3, 7
- [25] Yining Hong, Haoyu Zhen, Peihao Chen, Shuhong Zheng, Yilun Du, Zhenfang Chen, and Chuang Gan. 3d-llm: Injecting the 3d world into large language models. *NeurIPS*, 2023. 2, 8
- [26] Bin Huang, Xin Wang, Hong Chen, Zihan Song, and Wenwu Zhu. Vtimellm: Empower llm to grasp video moments. In *CVPR*, 2024. 6
- [27] Haifeng Huang, Yilun Chen, Zehan Wang, Rongjie Huang, Runsen Xu, Tai Wang, Luping Liu, Xize Cheng, Yang Zhao, Jiangmiao Pang, et al. Chat-scene: Bridging 3d scene and large language models with object identifiers. arXiv preprint, 2023. 8
- [28] Jiangyong Huang, Silong Yong, Xiaojian Ma, Xiongkun Linghu, Puhao Li, Yan Wang, Qing Li, Song-Chun Zhu, Baoxiong Jia, and Siyuan Huang. An embodied generalist agent in 3d world. arXiv preprint, 2023. 2

- [29] Jiangyong Huang, Silong Yong, Xiaojian Ma, Xiongkun Linghu, Puhao Li, Yan Wang, Qing Li, Song-Chun Zhu, Baoxiong Jia, and Siyuan Huang. An embodied generalist agent in 3d world. arXiv preprint, 2023. 2, 8
- [30] Shijia Huang, Yilun Chen, Jiaya Jia, and Liwei Wang. Multiview transformer for 3d visual grounding. In *CVPR*, 2022.
- [31] Baoxiong Jia, Yixin Chen, Huangyue Yu, Yan Wang, Xuesong Niu, Tengyu Liu, Qing Li, and Siyuan Huang. Sceneverse: Scaling 3d vision-language learning for grounded scene understanding. In ECCV, 2024. 2
- [32] Alexander Ku, Peter Anderson, Roma Patel, Eugene Ie, and Jason Baldridge. Room-across-room: Multilingual visionand-language navigation with dense spatiotemporal grounding. arXiv preprint, 2020. 16
- [33] Bohao Li, Yuying Ge, Yixiao Ge, Guangzhi Wang, Rui Wang, Ruimao Zhang, and Ying Shan. Seed-bench: Benchmarking multimodal large language models. In *CVPR*, 2024. 3, 7
- [34] Bo Li, Yuanhan Zhang, Dong Guo, Renrui Zhang, Feng Li, Hao Zhang, Kaichen Zhang, Peiyuan Zhang, Yanwei Li, Ziwei Liu, et al. Llava-onevision: Easy visual task transfer. *arXiv preprint*, 2024. 2, 7, 8
- [35] Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. Visual instruction tuning. *NeurIPS*, 2023. 2
- [36] Haotian Liu, Chunyuan Li, Yuheng Li, and Yong Jae Lee. Improved baselines with visual instruction tuning. In *CVPR*, 2024. 8
- [37] Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae Lee. Llava-next: Improved reasoning, ocr, and world knowledge, 2024. 8
- [38] Yuan Liu, Haodong Duan, Yuanhan Zhang, Bo Li, Songyang Zhang, Wangbo Zhao, Yike Yuan, Jiaqi Wang, Conghui He, Ziwei Liu, et al. Mmbench: Is your multi-modal model an all-around player? In ECCV, 2024. 3, 7
- [39] Yuliang Liu, Zhang Li, Mingxin Huang, Biao Yang, Wenwen Yu, Chunyuan Li, Xu-Cheng Yin, Cheng-Lin Liu, Lianwen Jin, and Xiang Bai. Ocrbench: on the hidden mystery of ocr in large multimodal models. *Science China Information Sciences*, 2024. 3
- [40] Ruiyuan Lyu, Jingli Lin, Tai Wang, Xiaohan Mao, Yilun Chen, Runsen Xu, Haifeng Huang, Chenming Zhu, Dahua Lin, and Jiangmiao Pang. Mmscan: A multi-modal 3d scene dataset with hierarchical grounded language annotations. *NeurIPS*, 2024. 2, 3
- [41] Wufei Ma, Haoyu Chen, Guofeng Zhang, Celso M de Melo, Alan Yuille, and Jieneng Chen. 3dsrbench: A comprehensive 3d spatial reasoning benchmark. arXiv preprint, 2024. 2, 7
- [42] Xiaojian Ma, Silong Yong, Zilong Zheng, Qing Li, Yitao Liang, Song-Chun Zhu, and Siyuan Huang. Sqa3d: Situated question answering in 3d scenes. arXiv preprint, 2022. 2, 3, 8
- [43] Taiki Miyanishi, Takuya Maekawa, and Motoaki Kawanabe. Sim2realqa: Using life simulation to solve question answering real-world events. *IEEE Access*, 2021. 7
- [44] Mengxue Qu, Xiaodong Chen, Wu Liu, Alicia Li, and Yao Zhao. Chatvtg: Video temporal grounding via chat with video dialogue large language models. In CVPR, 2024. 6

- [45] Mike Roberts, Jason Ramapuram, Anurag Ranjan, Atulit Kumar, Miguel Angel Bautista, Nathan Paczan, Russ Webb, and Joshua M Susskind. Hypersim: A photorealistic synthetic dataset for holistic indoor scene understanding. In *ICCV*, 2021. 7
- [46] Amanpreet Singh, Vivek Natarajan, Meet Shah, Yu Jiang, Xinlei Chen, Dhruv Batra, Devi Parikh, and Marcus Rohrbach. Towards vqa models that can read. In *CVPR*, 2019. 7
- [47] Shuran Song, Samuel P Lichtenberg, and Jianxiong Xiao. Sun rgb-d: A rgb-d scene understanding benchmark suite. In *CVPR*, 2015. 7
- [48] Peter Tong, Ellis Brown, Penghao Wu, Sanghyun Woo, Adithya Jairam Vedagiri IYER, Sai Charitha Akula, Shusheng Yang, Jihan Yang, Manoj Middepogu, Ziteng Wang, et al. Cambrian-1: A fully open, vision-centric exploration of multimodal llms. *NeurIPS*, 2024. 6, 7, 9
- [49] Peng Wang, Shuai Bai, Sinan Tan, Shijie Wang, Zhihao Fan, Jinze Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, et al. Qwen2-vl: Enhancing vision-language model's perception of the world at any resolution. arXiv preprint, 2024. 8
- [50] Runsen Xu, Zhiwei Huang, Tai Wang, Yilun Chen, Jiangmiao Pang, and Dahua Lin. Vlm-grounder: A vlm agent for zero-shot 3d visual grounding. arXiv preprint, 2024. 6
- [51] Jihan Yang, Shusheng Yang, Anjali W Gupta, Rilyn Han, Li Fei-Fei, and Saining Xie. Thinking in space: How multimodal large language models see, remember, and recall spaces. arXiv preprint, 2024. 2, 3, 6, 7
- [52] Chandan Yeshwanth, Yueh-Cheng Liu, Matthias Nießner, and Angela Dai. Scannet++: A high-fidelity dataset of 3d indoor scenes. In *ICCV*, 2023. 3, 6, 7, 12
- [53] Weihao Yu, Zhengyuan Yang, Linjie Li, Jianfeng Wang, Kevin Lin, Zicheng Liu, Xinchao Wang, and Lijuan Wang. Mm-vet: Evaluating large multimodal models for integrated capabilities. arXiv preprint, 2023. 3
- [54] Jia Zheng, Junfei Zhang, Jing Li, Rui Tang, Shenghua Gao, and Zihan Zhou. Structured3d: A large photo-realistic dataset for structured 3d modeling. In ECCV, 2020. 3, 7
- [55] Chenming Zhu, Tai Wang, Wenwei Zhang, Jiangmiao Pang, and Xihui Liu. Llava-3d: A simple yet effective pathway to empowering lmms with 3d-awareness. *arXiv preprint*, 2024. 2

6. Appendix

6.1. Benchmark task descriptions

The tasks are categorized into single-view and multi-view settings, covering depth estimation, distance prediction, spatial relations, and spatial imagination. The descriptions of each task are as follows:

Single-view tasks Single-view tasks test a model's ability to infer spatial properties from a single image. These tasks include:

- **Depth estimation (OC, OO, NA)**: Predicting absolute or relative depth values for objects
- **Distance prediction** (**OC**, **OO**, **NA**): Estimating the Euclidean distance between objects or from an object to the camera.
- Object center distance inference (OO, MCA): Given objects A, B and C, determine which of B and C is farther or closer to A.
- **Object spatial relation (OO, MCA)**: Determining relative positioning (e.g., left, right, in front of).
- **Spatial imagination (OC, OO, MCA)**: Predicting unseen spatial relationships based on limited visual information.

Multi-view tasks Multi-view tasks require reasoning across multiple images to infer spatial relationships. These tasks include:

- Viewpoint change inference (NA): Given two perspectives, output how the camera should be moved to see the second perspective.
- Multi-view depth estimation (OC, OO, NA): Predicting depth across multiple perspectives.
- Multi-view distance prediction (OC, OO, NA): Estimating object distances across different views.
- **Multi-view object matching (MCA)**: Identifying the same object across multiple views.
- **Camera pose inference** (MCA): Predict the position of the camera corresponding to the second perspective in the first image.
- Multi-view object spatial relation (OC, OO, MCA): Determining object relationships across multiple images.
- **Spatial imagination (OC, OO, MCA)**: Reasoning about spatial structure beyond visible views.

A tiny version of our *SPAR-Bench* evaluation results are shown in Tab. 8.

6.2. Image subsampling

We propose an efficient image filtering method based on camera poses to reduce redundant images with high similarity, so that can improve data processing efficiency. Given a scene S with a set of image sequence \mathcal{I} , our goal is to filter out similar images based on a translation threshold d_{trans} and a rotation angle threshold d_{rot} , obtaining a compact image sequence $\mathcal{I}' \subseteq \mathcal{I}$.

Specifically, for a given image sequence \mathcal{I} , we first load the corresponding camera intrinsic and extrinsic parameters. Each camera pose is represented by a 4×4 transformation matrix \mathbf{T}_i , consisting of a rotation matrix \mathbf{R}_i and a translation vector \mathbf{t}_i :

$$\mathbf{T}_{i} = \begin{bmatrix} \mathbf{R}_{i} & \mathbf{t}_{i} \\ \mathbf{0}^{T} & 1 \end{bmatrix}$$
(1)

where $\mathbf{t}_i \in \mathbb{R}^3$ and $\mathbf{R}_i \in SO(3)$. The world-to-camera transformation by inverting the given pose.

Translation filtering For each image i(i = 1, ..., n), we compute the Euclidean distance between its translation vector \mathbf{t}_i and the translation vector \mathbf{t}_j of a candidate image j(j = i + 1, ..., n):

$$d_{ij}^{trans} = \|\mathbf{t}_i - \mathbf{t}_j\| \tag{2}$$

If $d_{ij}^{trans} > d_{th}$, we believe that the difference between these two frames is significant enough and we will preserve the current frame j. If $d_{ij}^{trans} < d_{th}$, we will further perform rotation filtering.

Rotation filtering For images with smaller d_{ij}^{trans} , we compute the relative rotation matrix: $\mathbf{R}_{ij} = \mathbf{R}_i^{-1}\mathbf{R}_j$ The rotational difference is determined by the angle θ_{ij} , computed as:

$$\theta_{ij} = \cos^{-1} \left(\frac{\operatorname{Trace}(\mathbf{R}_{ij}) - 1}{2} \right) * \frac{180}{\pi}$$
(3)

If $\theta_{ij} < \theta_{th}$, image *j* is considered redundant and removed. After iterating through all images, the final filtered image set is as follows:

$$\mathcal{I}' = \{ i \in \mathcal{I} \mid \text{satisfies filtering criteria} \}$$
(4)

This method can filter out approximately 90% of redundant images, which ensures that only images with sufficiently distinct poses are retained, reducing redundancy while preserving viewpoint diversity.

In the experimental setup, we set the threshold parameter of the ScanNetPP dataset [52] with $d_{th} = 0.5$ and $\theta_{th} = 45$ and ScanNet [20] dataset with $d_{th} = 0.5$ and $\theta_{th} = 15$. For the Structured3D Dataset, we did not perform filtering and subsampling operations since the images in the dataset were sparse enough.

6.3. Image item construction

Given a scene S, we construct image items by extracting 3D object data and projecting it onto 2D images.

Methods		Low	Depth-OC	Depth-OC-MV	Depth-OO	Depth-OO-MV	Dist-OC	Dist-OC-MV	D_{ist-OO}	Dist-00-MV	Medium	PosMatch	CamMotion	View ChgI	High	Distl-OO	Distl-00-MV	ObjRel-OC-MV	ObjRel-OO	ObjRel-00-MV	SpImag-OC	SpImag-OC-MV	SpImag-00	SpImag-00-MV
Baseline																								
Chance Level (Random)	-	-	-	-	-	-	-	-	-			22	18	-		80	32	26	28	22	32	12	30	28
Chance Level (Frequency)	37.80	36.33	42.89	51.78	25.78	27.11	35.33	46.89	35.33	25.56	41.14	30	40	53.42	38.00	60	58	32	30	30	32	34	28	38
Human Level	67.27	55.31	72.75	74.25	28.75	36.25	78.25	52.25	66.5	33.50	72.32	92	64	60.97	76.22	80	94	70	92	80	78	82	50	60
GPT-40	36.39	29.25	53.80	45.00	15.00	13.60	37.40	34.40	23.40	24.40	24.93	30	16	28.80	45.11	64	64	58	46	46	32	44	30	22
Claude-3.7-Sonnet	21.77	25.43	41.00	45.40	11.20	12.20	42.60	19.60	26.00	5.40	7.33	16	6	0.00	23.33	40	48	22	36	14	12	20	6	12
Qwen2-VL-72B	35.62	35.28	45.40	49.80	13.80	10.00	54.60	49.40	36.80	22.40	23.39	42	18	10.16	40.00	60	68	50	38	44	18	28	18	36
Qwen2.5-VL-72B	39.40	35.35	53.20	46.80	17.80	29.00	49.60	57.40	14.40	14.60	23.05	40	16	13.16	48.44	74	74	60	56	50	20	34	24	44
InternVL2-2B	29.51	21.85	15.00	31.40	17.80	18.80	13.40	27.40	26.40	24.60	25.81	44	26	7.44	37.56	46	56	54	42	18	50	42	14	16
InternVL2-4B	32.10	29.55	22.02	28.40	18.80	14.20	47.60	52.60	26.00	26.60	33.88	52	30	19.64	33.78	46	54	44	30	30	26	26	26	22
InternVL2-8B	32.95	24.10	24.60	39.00	16.00	16.80	35.40	33.40	13.40	14.20	35.43	58	28	20.28	40.00	68	42	40	46	34	34	46	16	34
InternVL2.5-2B	31.81	27.85	44.80	42.20	11.20	7.00	40.20	35.40	24.20	17.80	22.48	40	22	5.44	38.44	68	48	50	48	26	18	38	20	30
InternVL2.5-4B	33.99	30.38	31.20	36.20	26.20	30.00	24.20	36.40	31.40	27.40	34.27	58	38	6.80	37.11	48	58	54	40	30	24	42	18	20
InternVL2.5-8B	37.27	28.38	27.40	31.80	19.60	19.00	40.40	48.80	15.00	25.00	31.47	66	22	6.40	47.11	58	54	50	52	52	44	58	22	34
Qwen2-VL-2b	26.88	23.45	44.20	50.00	25.20	17.40	7.40	12.60	20.60	10.20	28.01	22	24	38.04	29.56	52	50	20	24	10	40	30	24	16
Qwen2-VL-7b	32.84	27.98	37.80	36.20	23.60	7.00	28.00	31.80	31.60	27.80	16.36	26	18	5.08	42.67	58	54	26	40	54	34	36	40	42
Qwen2.5-VL-7b	33.48	31.25	27.80	37.20	27.40	19.80	50.00	47.60	17.60	22.60	19.84	26	24	9.52	40.00	52	50	44	56	28	28	36	32	34
LLaVA-OV-0.5B	30.84	33.20	55.40	51.60	22.80	10.00	35.20	28.20	36.60	25.80	15.08	24	20	1.24	34.00	52	56	40	36	16	30	40	22	14
LLaVA-OV-7B	34.73	27.95	42.80	44.60	25.20	24.00	12.80	12.60	38.40	23.20	27.69	48	22	13.08	43.11	64	62	26	58	42	24	40	32	40
llava-v1.5-7b	25.76	13.02	4.80	15.40	17.60	17.60	8.80	7.80	17.60	14.60	33.69	28	40	33.08	34.44	52	54	18	22	26	42	38	18	40
llava-v1.6-7b	13.50	9.00	10.60	0.00	20.40	0.00	16.20	0.00	24.80	0.00	6.00	8	10	0.00	20.00	46	14	12	30	6	42	6	20	4
ours	66.65	70.33	87.00	83.20	45.80	43.20	81.00	84.00	78.80	59.60	60.13	78	66	36.40	65.56	86	90	72	78	58	48	48	42	68

Table 8. Performance of different models on SPAR-Bench. All results are obtained on tiny SPAR-Bench. Shaded cells indicate best scores in each category.

Data loading and initialization For each scene, we load the corresponding 3D mesh, camera intrinsic and extrinsic parameters, and instance annotations. The scene mesh is represented as: $M = (\mathcal{V}, \mathcal{F})$ where \mathcal{V} is the set of vertices and \mathcal{F} is the set of triangular faces.

To determine the visibility of 3D faces in the image, we perform rasterization to obtain a mapping from image pixels to face indices: $pix_to_face_{(x,y)} = f_k$. where $f_k \in \mathcal{F}$ and pix_to_face stores the corresponding face index for each pixel (x, y). If a pixel does not correspond to any face, it will be marked as -1.

Object projection and bounding box computation For each 3D object, we compute the set of visible vertices and project them into the 2D image plane using:

$$p_{2D} = K(R \cdot p_{3D} + t) \tag{5}$$

where p_{3D} is a vertex in the 3D space, and p_{2D} is its projected 2D coordinate. The bounding box of the projected object is computed as: $B_{obj} = [x_{min}, y_{min}, x_{max}, y_{max}]$. To ensure a valid projection, we also enforce some constraints as follows:

- The fraction of visible object vertices f_v in the image must exceed a threshold τ_v , where $f_v = \frac{|V_{visible}|}{|V_{total}|}$.
- The projected object area must be above a minimum threshold A_{min} .

• The depth values in the z-buffer must be within a reasonable range. where $z_{min} = \min(Z_{obj}), \quad z_{max} = \max(Z_{obj})$

Each 3D object is associated with an oriented bounding box, defined by its centroid c, axis-aligned lengths l_x, l_y, l_z . Finally, the extracted image item dictionary, including object data, is used for downstream task generation.

6.4. Task data generation

In this section, we describe the detailed information on multi-task generation. We generate questions based on the template. These questions can be of three types: select, fill, or sentence. In each case, the goal is to generate a question that involves the spatial relationship between two objects. We will provide a Q&A format in the form of a template and fill in key information and answers in it.

Obj spatial relation This task is to describe the spatial relationships between objects in the 3D scene based on their spatial positions. The process involves several key steps: (1) Transforming 3D object coordinates from the original camera view into a common view. This transformation ensures that all spatial calculations are relative to the main camera view. Let c denotes the 3D center of an object in the world coordinate system, and **T** denotes the camera pose. The transformation is carried out as: c'_{homo} =

 $\mathbf{T}^{-1} \cdot c_{homo}$. where c_{homo} means homogeneous coordinate of object 3D center point. (2) Spatial Relationship Description. We describe their spatial relationships in terms of several key factors: above-below, left-right, near-far, and front-behind (relative to two objects). These relationships are determined based on their spatial coordinates and distance from the camera center. The distance is calculated by $d = ||c' - T_{trans}||_2$. We set the relationship threshold at 0.1m. If the difference in coordinates or distances is less than 0.1m, we consider the corresponding spatial relationship to be indistinguishable (empty).

Depth prediction Given an image I containing a set of detected objects $\mathcal{O} = \{o_1, o_2, ..., o_n\}$, we transform each object's 3D center point c into the camera coordinate system as $c' \in \mathbb{R}^3$. Then the transformed depth values dare extracted from the z-component of their transformed coordinates c', which means d = c'(z).

For the absolute depth prediction task, we use this value as the standard answer. For the relative depth estimation task, we calculate the depth difference between objects by: $\Delta d = |d_i - d_j|$. We will skip that case if two objects have overlapping bounding boxes or similar values.

Distance infer Given an image *I* containing a set of objects $\mathcal{O} = \{o_1, o_2, ..., o_n\}$, we define the 3D center of each object o_i in the world coordinate system as $\mathbf{c}_i \in \mathbb{R}^3$ and transformed them into the camera coordinate system as \mathbf{c}'_i . For the object-object type task, we random sample two objects o_A with \mathbf{c}'_A and o_B with \mathbf{c}'_B in the same scene. The Euclidean distance between them is given by: $d_{AB} = \|\mathbf{c}'_A - \mathbf{c}'_B\|_2$, where $\|\cdot\|_2$ represents the L_2 -norm. For the object-camera type task, we calculate the distance with $|\mathbf{c}'_i|_2$. To ensure numerical stability and consistency in question-answer generation, the computed distance is rounded to the nearest 0.1 meter. If the two objects have overlapping 3D bounding boxes or the distance is smaller than the threshold, we will skip that case.

Spatial volume infer For an object o_i in the image, we first obtain its 3D bounding box in the world coordinate system and then transform it into the camera coordinate system by the extrinsic transformation matrix. The center coordinate is denoted as c'_i and each corner point of 3D bounding box is denoted as b'_{ij} , j = (1, 2, ..., 8). The object's dimensions(length, width, and height) are derived as follows:

$$h = \max_{j} b_{i,j}^{(z)} - \min_{j} b_{i,j}^{(z)}$$

$$l = \max_{j,k} ||b_{i,j}^{(xy)} - b_{i,k}^{(xy)}||$$

$$w = \min_{j,k} ||b_{i,j}^{(xy)} - b_{i,k}^{(xy)}||$$
(6)

where $b_{i,j}^{(xy)} = (b_{i,j}^{(x)}, b_{i,j}^{(y)})$ represents the 2D projection of the bounding box in the XY plane. To ensure consistency, all dimensions are converted to centimeters. The final estimated volume is given by: $V = h \cdot l \cdot w$.

Spatial imagination Our spatial imagination task aims to evaluate the spatial reasoning capabilities of LLM models by analyzing object relationships before and after camera transformations in a 3D environment. Given an image and corresponding scene metadata, we randomly sample objects and generate structured question-answer (QA) pairs that describe spatial relationships.

For each image I, it is associated with a set of objects $\mathcal{O} = \{o_1, o_2, ..., o_N\}$. We randomly sample objects $o_A, o_B, o_C, o_D \subset \mathcal{O}$ for relational comparisons. To analyze object relationships from different viewpoints, we transform the camera pose $\mathbf{P} \in SE(3)$ so that it moves towards object A and faces object B. The new camera pose is constructed as follows:

$$\mathbf{t}_{A \to B} = \mathbf{c}_{A} \quad \mathbf{f} = \frac{\mathbf{c}_{B} - \mathbf{c}_{A}}{\|\mathbf{c}_{B} - \mathbf{c}_{A}\|}$$
$$\mathbf{v} = \frac{\mathbf{u}_{0} \times \mathbf{f}}{\|\mathbf{u}_{0} \times \mathbf{f}\|} \quad \mathbf{u} = \mathbf{f} \times \mathbf{v} \quad \mathbf{r} = -\mathbf{v}$$
(7)

where \mathbf{c}_A , \mathbf{c}_B are 3D center coordinates of object o_A and o_B respectively. $\mathbf{u}_0 = [0, 0, 1]^T$. **f** is forward direction vector. \mathbf{v} , \mathbf{u} , **r** are left-vector, up-vector and right-vector respectively. So the new camera pose is computed as:

$$\mathbf{P}_{A \to B} = \begin{bmatrix} \mathbf{r} & \mathbf{u} & \mathbf{f} & \mathbf{t}_{A \to B} \\ 0 & 0 & 0 & 1 \end{bmatrix}$$
(8)

We extract the up-vector **u** from $\mathbf{P}_{A\to B}$ to compute the vertical rotation angle: $\theta = \cos^{-1}(\mathbf{u}_z)$. If $\theta > 60^\circ$, we will discard this viewpoint to maintain a reasonable observation angle.

After that, we compute the spatial relationship between object C and object D before and after camera transformation. The relationships are determined based on their relative positions in the original and transformed coordinate system. We describe their spatial relationships in terms of several key factors: above-below, left-right, near-far, and front-behind (relative to two objects). Please refer to the paragraph **Obj spatial relation** for details. The final step is to generate structured question-answer pairs. The same procedure is also applied after the camera-object type task.

Position matching Position matching aims to identify and compare the positions of the same object across different views. Given an object detected in multiple images, the task is to find its corresponding 2D bounding box in another view based on its known location in one reference image. We define the set of detected objects as: $\mathcal{O} = \{o_1, o_2, \ldots, o_N\}$. Each object o_i appears in a set of images: $\mathcal{I}_i = \{I_{i_1}, I_{i_2}, \ldots, I_{i_m}\}$. If m < 2, the object is discarded. For each valid object, we randomly select two distinct images $I_{i_A}, I_{i_B} \in \mathcal{I}_i$ as a reference frame and target frame. The 3D bounding box of object o_i in world coordinate is denoted as b_i^{3D} . We project the 3D bounding box into the image plane by Eq. 5. The 2D bounding boxes in different images are denoted as $b_{i_A}^{2D}, b_{i_B}^{2D}$.

The system formulates the position-matching question as: Qusetion = Given object o_i and 2D bounding box $b_{i_A}^{2D}$ in image I_A , find its location in image I_B ; Answer = $b_{i_B}^{2D}$.

View change infer The view change inference task aims to determine the spatial displacement between different images. To ensure images exhibit a co-visibility relationship, we select different perspectives images containing the same object instance.

For two distinct images I_A, I_B containing the same object o, we first compute the center of the 2D bounding box to quantify the object's displacement in image space. If 2D bounding box of object o in image I_A is denoted as $b_A^{2D} = [x_A^{\min}, y_A^{\min}, x_A^{\max}, y_A^{\max}]$, the 2D center coordinate can be calculated as $c_A^{2D} = ((x_A^{\min} + x_A^{\max})/2, (y_A^{\min} + y_A^{\max})/2)$. We determined the object's location in image I_A, I_B according to c_A^{2D} and c_B^{2D} .

To further analyze the view movement in the world coordinate system, We compute the relative pose transformation: $\mathbf{T}_{AB} = \mathbf{T}_{A}^{-1}\mathbf{T}_{B}$. Finally, we determine the translation distance and rotation angle of the viewpoint based on the relative pose transformation matrix and designed rules.

Camera pose The camera pose task aims to estimate the relative camera motion and generate questions about the 2D coordinate and depth information.

We select distinct frames I_A , I_B containing the same object o to ensure there is an overlap between them. Firstly, we project the camera position of image I_B in the world coordinate into the coordinate system of image I_A . According to Eq. 5, the projected point coordinate is given by $p_{B|A} = K(R_A \cdot p_B + t_A)$, where R_A and t_A are the rotation matrix and the translation vector of I_A , K is camera intrinsic parameters. Then we calculate 2D image coordinates (u, v) and normalize to 0-1000:

$$u = \frac{p_{B|A}[0]}{p_{B|A}[2]} \cdot \frac{1000}{\text{width}} \quad v = \frac{p_{B|A}[1]}{p_{B|A}[2]} \cdot \frac{1000}{\text{height}} \tag{9}$$

If the projected point lies within the bounds of the image I_A , we compute the depth as: $d_{B|A} = (R_A \cdot p_B + t_A)[2]$

Obj frame location We introduce the object frame location task to identify the frames in which a given object appears. We select a reference frame and determine in which

other frames the object is present. This process enables the automatic generation of question-answer pairs related to object appearance across frames.

For an object o, we extract the set of frames: $I_o = \{I_1, I_2, ..., I_n\}$ in which it appears. To generate questions and answers for the object frame localization task, we randomly select one frame I_s as the reference frame. We also add some irrelevant frames as wrong options, and the answer consists of the list of other frame indices $I_o \setminus \{I_s\}$ where the object appears.

Obj frame location This task infers the chronological order in which multiple objects appear within a sequence of frames. By selecting a subset of objects and analyzing their first occurrence across frames, we generate structured question-answer pairs that facilitate the temporal reasoning ability of LLMs.

Given object set $\mathcal{O} = \{o_1, o_2, ..., o_N\}$ and associated image set $\mathcal{L} = \{\mathcal{I}_1, \mathcal{I}_2, ..., \mathcal{I}_N\}$, where \mathcal{I}_i means the set of frames that object o_i appears, we extract the first appearance frame of each object as $F_i = \min(f \mid f \in \mathcal{I}_i)$. F_i represents the first appearance frame of object o_i . Then we sort the first appearance frames of all objects to determine the order of appearance:

$$\mathcal{S} = \text{sort}(\{(o_1, F_1), (o_2, F_2), (o_3, F_3) \dots (o_N, F_N)\}) \quad (10)$$

where S is the ordered sequence of objects based on their first appearance. For sentence QA type, the ordered sequence and corresponding frame indices are embedded into a sentence. For fill-in-the-blank QA type, the question is to instruct the user to input the ordered sequence as a commaseparated list.

Obj count The object counting task estimates the number of object instances for each label category in the scene and generates structured question-answer pairs to facilitate the numerical reasoning ability of LLMs.

For each label $l \in \mathcal{L}$, the total number of object instances is computed as: $N(l) = |\mathcal{L}(l)|$, where N(l) represents the number of object instances associated with label l. We will exclude labels with fewer than two object instances.

Room size This task is designed for estimating the size of a room and generating corresponding question-answer pairs to facilitate the spatial reasoning ability of LLMs.

Given the room scene with 3D mesh $M = (\mathcal{V}, \mathcal{F})$, where \mathcal{V} is the set of vertices and \mathcal{F} is the set of faces, we first downsample the points by quantizing them into a grid with a specified voxel size $\delta = 0.1$. The quantized points are computed as: $\mathcal{Q} = \lfloor \mathcal{V}/\delta \rfloor$. We then retain only the unique voxels and obtain voxel centers: $\mathcal{P}_d = (\text{unique}(\mathcal{Q})+0.5)\cdot\delta$. If the downsampled set contains fewer than 100 points, we

revert to the original point cloud. To estimate the room area, we construct a concave hull using the α -shape algorithm:

$$\mathcal{H} = \text{AlphaShape}(\mathcal{P}_d[:, 0:2], \alpha) \tag{11}$$

where $\alpha = 0.1$ controls the concavity of the shape. The final room area is calculated as:

$$A = \sum_{h \in \mathcal{H}} \operatorname{area}(h) \tag{12}$$

To ensure valid QA generation, If the room area is below the threshold $A_{th} = 5$, no QA pairs will be generated.

Navigation We construct visual navigation data based on Matterport3D [9] and Room Across Room (RxR) [32] Dataset. For the navigation instructions and image sequences in RxR, we take the image sequence as input and construct question-answer pairs. We expect the LLM model to complete the absent key action information in the instructions, such as left turn, straight ahead, on the right side, and other keywords.

6.5. More visualization

We visualize the detailed QA of different tasks from our proposed *SPAR-7M* in Tab. 9 - 14.

Task	Question	Answer
Depth-OC-MV (fill)	The table (red point) is located at a depth of 1.5 meters. Estimate the depth of the food container (blue point). Calculate or judge based on the 3D center points of these objects. Ensure your answer contains only one number.	1.7
Depth-OC-MV (select)	Given the refrigerator (red point) is located at a depth of 0.9 meters in the Z-axis of the camera coordinate system, how far in depth is the dish soap bottle (blue point) at its center? Calculate or judge based on the 3D center points of these objects. Please select the correct option from the choices provided. A. 2.2; B. 2.3; C. 2.1; D. 1.4 . Your answer can only include one of options A, B, C or D.	D
Depth-OC-MV (sentence)	The wardrobe (red point) at a depth of 1.0 meters serves as a ref- erence. How deep is the power socket (blue point)? Calculate or judge based on the 3D center points of these objects.	With a central depth of 1.2 me- ters, power socket is referenced here.

Table 9. Detailed QA of the Depth Prediction Object-Camera Multi-view Task

Task	Question	Answer
DistI-OO (fill)	Between cooking pan (green point) and plastic bag (blue point), which object is positioned closer to coat (red point)? Calculate or judge based on the 3D center points of these objects. Submit your response as the name of one object exclusively.	Cooking pan
DistI-OO (choice)	Which object lies at a closer distance from backpack (red point): duffel bag (green point) or light switch (blue point)? Calculate or judge based on the 3D center points of these objects. Pick the appropriate answer from the options given. A. duffel bag; B. light switch. Your answer can only include one of options A, B.	A
DistI-OO (sentence)	Compare the positions of bed (green point) and chair (blue point). Which is farer to the heater (red point)? Calculate or judge based on the 3D center points of these objects.	The proximity of heater to bed is 2.0 meters, and to chair, it is 0.6 meters. Hence, the bed is farer to heater.

Table 11. Detailed	OA of the	Object Spatial	Relation 0	Object-Camera	Multi-view	Task
Tuble III Detailed	211 of the	Object Spana	iteration (object Cumera	initiality interv	T COLL

Task	Question	Answer
ObjRel-OC-MV (choice)	What is the direction of object chair (bbox) relative to the observer's primary angle? Calculate or judge based on the 3D center points of these objects. We use the first image to reflect the main perspective, which aligns with the observer's viewpoint. The options describe the spatial relationship between object and observer in terms of left-right (left, right, or empty if indistinguishable), above-below (above, below, or empty if indistinguishable). Select the correct response from the given choices. A. left, above, front; B. left, above, behind; C. right, below, front; D. right, above, front. Your answer can only include one of options A, B, C or D.	C
ObjRel-OC-MV (sentence)	Describe the spatial orientation of object bag (bbox) relative to the observer. Calculate or judge based on the 3D center points of these objects. The first image is positioned to serve as the main viewpoint for the observer.	Relative to the observer's place- ment, the bag (red bbox) appears to the right below. It seems to the front.

Table 12. Detailed QA	of the Object Spatial	Imagination Object-Camera	a Multi-view Task
-----------------------	-----------------------	---------------------------	-------------------

Task	Question	Answer
SpImag-OC-MV (choice)	How does the positional relationship of refrigerator (red bbox) to the observer evolve once the observer shifts to the 3D center of map poster (green bbox) and faces trash can (blue bbox)? Cal- culate or judge based on the 3D center points of these objects. Base your response on the observer's perspective, with the first image defined as the primary view before movement begins. For multiple-choice questions, consider only the state after the ob- server has moved. The options describe the spatial relationship between object and observer in terms of left-right (left, right, or empty if indistinguishable), above-below (above, below, or empty if indistinguishable). Select the appropriate option from the given choices. A. left , , behind; B. right, below, ; C. right, above, ; D. right, below, behind . Your answer can only include one of options A, B, C or D.	D
SpImag-OC-MV (sentence)	How does the observer's shift to the 3D center of wardrobe (green bbox) and orientation toward rug (blue bbox) affect the position- ing of bread packet (red bbox)? Calculate or judge based on the 3D center points of these objects. Frame your answer with the observer's perspective, assigning the first image as the main view before any motion.	Initially, the po- sition of bread packet appears to the left below to the observer. It is also to the front. After moving to wardrobe and orienting toward rug, bread packet changes to to the right below. It is now to the behind.

Task	Question	Answer
ViewChgI (fill)	If starting from the first image, how would the observer's camera need to move to recreate the second image? Provide the camera movement and rotation in the following format: move (right or left):(meters), move (down or up):(meters), move (forward or back):(meters), rotate (down or up):(degrees), rotate (right or left):(degrees) - The first three values are in meters The last two values are in degrees Use commas to separate each parameter Do not include any additional text. Example: move left: 2.6, move down: 0.1, move forward: 0.2, rotate up: 10, rotate left: 0.	move right: 1.2, move up: 0.4, move forward: 1.4, rotate up: 5, rotate left: 90
ViewChgI (sentence)	What changes in position or angle would the camera need to make to transition from the first image to the second?	In the initial frame, suitcase is located in the bottom-right and moves left and up to the bottom-left in the next image. Observ- ing these changes, it appears the camera movement is as fol- lows: To realign the second image: Move 0.6 meters forward. Shift sideways by 0.2 meters right. Rotate down by 10 degrees. Turn right by 10 de- grees.

Table 13. Detailed QA of the View Change Infer Task

Table 14. Detailed QA	of the Camera Pose Task
-----------------------	-------------------------

Task	Question	Answer
CamPos (fill)	Estimate the image-plane location and depth in meters of the second image's observer as it appears in the first image's coordinate space. Please ensure your answer is limited to a 2D coordinate and a depth, for instance: (200, 500), 1.2.	(113, 182), 3.8
CamPos (choice)	Where would the second image's observer be seen in the first im- age's space? Provide 2D image-plane coordinates and depth in me- ters. Choose the correct response from the given choices. A. Image Coor: (514, 95), Depth:4.8 meters; B. Image Coor: (258, 537), Depth: 6.9 meters; C. Image Coor: (108, 214), Depth: 6.3 meters; D. Image Coor: (921, 261), Depth: 4.6 meters. Your answer can only include one of options A, B, C or D.	Α
ViewChgI (sentence)	How does the camera's movement between the two images affect its position in the first image? Provide (X, Y) image-plane coordinates and depth in meters.	Relative to the first image, the second image's observer oc- cupies the position (650, 457), at a depth of 4.4 meters.