A PLASTICITY-AWARE METHOD FOR CONTINUAL SELF-SUPERVISED LEARNING IN REMOTE SENSING

Lars Möllenbrok, Behnood Rasti, Begüm Demir

Technische Universität Berlin, Germany BIFOLD – Berlin Institute for the Foundations of Learning and Data, Germany

Abstract—Continual self-supervised learning (CSSL) methods have gained increasing attention in remote sensing (RS) due to their capability to learn new tasks sequentially from continuous streams of unlabeled data. Existing CSSL methods, while learning new tasks, focus on preventing catastrophic forgetting. To this end, most of them use regularization strategies to retain knowledge of previous tasks. This reduces the model's ability to adapt to the data of new tasks (i.e., learning plasticity), which can degrade performance. To address this problem, in this paper, we propose a novel CSSL method that aims to learn tasks sequentially, while achieving high learning plasticity. To this end, the proposed method uses a knowledge distillation strategy with an integrated decoupling mechanism. The decoupling is achieved by first dividing the feature dimensions into task-common and task-specific parts. Then, the task-common features are forced to be correlated to ensure memory stability while the task-specific features are forced to be de-correlated facilitating the learning of new features. Experimental results show the effectiveness of the proposed method compared to CaSSLe, which is a widely used CSSL framework, with improvements of up to 1.12% in average accuracy and 2.33% in intransigence in a taskincremental scenario, and 1.24% in average accuracy and 2.01% in intransigence in a class-incremental scenario.

Index Terms—continual learning, self-supervised learning, deep learning, remote sensing.

I. INTRODUCTION

For learning from remote sensing (RS) image archives, deep neural networks (DNNs) are commonly utilized in a static training scenario, where all training data is presumed to be available from the outset of the training process. However, the static scenario does not reflect the dynamic characteristics of RS data acquisition. The expansion of Earth observation missions and the continuous operations of satellites lead to the regular collection of new RS images and the periodic release of new training sets. Frequent retraining from scratch with the combined previous (i.e., old) and new data results in substantial computational challenges, including extended training durations and high resource demands. However, updating the DNN by training only on the new data, causes catastrophic forgetting [1], which results in poor performance on old data. The catastrophic forgetting is caused by the data being non-independently and identically distributed across tasks, due to changes in land-use/land-cover, spectral response, and acquisition conditions.

To overcome these issues, continual learning (CL) can be used. CL aims to learn from a sequence of tasks, where each task is associated with different data. Most of the existing CL methods in RS, are developed in the context of supervised classification problems and thus require labeled training data for each CL task [2, 3]. Collecting a large number of training labels is both time-consuming and labor-intensive, making it impractical in operational scenarios. Consequently, the aforementioned methods are not suitable for operational CL applications in RS.

To address this issue, self-supervised learning (SSL) methods, which focus on learning general image features without relying on labeled training data, can be used. To the best of our knowledge, there is only a single continual SSL (CSSL) method developed for RS applications [4]. It combines the BarlowTwins [5] framework with a regularization strategy that is based on Elastic Weight Consolidation [6]. This method estimates the importance of model weights after learning a task and uses a regularization loss to discourage the changing of important weights to alleviate forgetting. However, the old weights might not always optimally capture the knowledge of the old tasks. Additionally, the old weight configuration might not be well suited to integrate knowledge learned from new data. Therefore, restricting the model weights to stay close to these potentially sub-optimal weights can reduce learning plasticity and lead to overall poor performance.

The development of CSSL methods has advanced further within the computer vision community. For instance, in [7] it is shown that SSL methods are less affected by forgetting. In [8], a simple CSSL framework, denoted CaSSLe, for contrastive learning-based SSL methods is introduced. In CaSSLe, when learning a new task, a frozen copy of the previous model is used for knowledge distillation. This is done by first mapping the current features to their previous state and then using the SSL loss of the considered SSL method to distill the knowledge. Since the distillation mechanism is naively restricting all feature mappings to their previous states, this can decrease the model's ability to adapt to the new task.

To address these problems, in this paper, we propose a novel CSSL method that achieves high learning plasticity while simultaneously retaining knowledge of old data.



Fig. 1. An illustration of the proposed continual self-supervised learning method.

II. PROPOSED METHOD

Let a sequence $\mathcal{T}_{1:T} = (\mathcal{T}_1, ..., \mathcal{T}_T)$ consist of T tasks, where each task \mathcal{T}_t is associated with a set $\mathcal{X}_t = \{X_1^t, ..., X_{n_t}^t\}$ of n_t RS images. The first task \mathcal{T}_1 is associated with an RS image archive \mathcal{X}_1 , whereas the subsequent tasks $\mathcal{T}_{2:T}$ can be associated with newly acquired RS data.

The proposed method aims to learn a general feature encoder on the sequence $\mathcal{T}_{1:T}$ in a self-supervised way. To this end, our method combines an SSL framework for learning general features from a task of the sequence with a novel knowledge distillation strategy. Unlike [8], our knowledge distillation strategy uses a decoupling mechanism [9] to encourage retaining task-common features while simultaneously encouraging the learning of task-specific features to increase learning plasticity. Fig. 1 shows a general overview of the method that is explained in detail in the following.

For learning a general feature encoder f on a task \mathcal{T}_t , the proposed method makes use of the BarlowTwins [5] framework. In this framework, f is combined with a projection head p to form the model $F = p \circ f$. Given an image X_i^t , two augmented views $V_{1,i}^t = a_1(X_i^t)$ and $V_{2,i}^t = a_2(X_i^t)$ are created, where $a_1 \sim \mathcal{A}_1$ and $a_2 \sim \mathcal{A}_2$ for two distributions \mathcal{A}_1 and \mathcal{A}_2 of image augmentations. The model F is trained on the view pairs and learns to correlate their feature representations while simultaneously reducing the redundancy of individual feature components to prevent collapse. To achieve this, the loss for training F on a batch \mathcal{B} of images is given by:

$$\mathcal{L}(\mathcal{B}) = \sum_{i} (1 - Q_{ii}^{\mathcal{B}})^2 + \lambda \sum_{i} \sum_{j \neq i} Q_{ij}^{\mathcal{B}^2}, \qquad (1)$$

where $Q^{\mathcal{B}}$ denotes the cross-correlation matrix of a batch of paired output features obtained from the image views and λ is a hyper-parameter to determine the contribution to the loss from the off-diagonal entries of the matrix. In detail, $Q^{\mathcal{B}}$ is defined by:

$$Q_{ij}^{\mathcal{B}} = \frac{\sum_{b \in \mathcal{B}} z_{1,i}^{b,t} z_{2,j}^{b,t}}{\sqrt{\sum_{b \in \mathcal{B}} (z_{1,i}^{b,t})^2} \sqrt{\sum_{b \in \mathcal{B}} (z_{2,j}^{b,t})^2}} \in [-1,1], \quad (2)$$

for the paired output features $\{(z_1^{b,t}, z_2^{b,t})\}_b$, where $z_k^{b,t} = F(V_{k,b}^t)$ for $X_b^t \in \mathcal{B}, k \in \{1, 2\}$, and b is used for indexing \mathcal{B} . For more details about the SSL framework and the used distributions of image augmentations, the reader is referred to [5]. For learning the first task \mathcal{T}_1 , minimizing (1) is the only objective.

For learning of a subsequent task \mathcal{T}_t , we assume to have access to the previous model F_{t-1} that was trained on tasks $\mathcal{T}_{1:t-1}$. The proposed method uses F_{t-1} and an additional learnable projector g together with a decoupling mechanism to distill knowledge from task-common features learned on previous tasks and reduce the redundancy of task-specific features learned in the current task. In detail, the encodings $f(V_{k,b}^t)$ of the current task are initially projected using g. Then, the cross-correlation matrix $\tilde{Q}^{\mathcal{B}}$ of size $K \times K$ ($\tilde{Q}_{ij}^{\mathcal{B}} \in [-1, 1]$) of the projected encodings and output features of F_{t-1} is computed, where K denotes the number of feature dimensions. It should be noted that different from $Q^{\mathcal{B}}$, $\tilde{Q}^{\mathcal{B}}$ is computed between tasks on the pairs

$$\{(g(f(V_{k,b}^t)), F_{t-1}(V_{k,b}^t))\}_b.$$
(3)

 $\tilde{Q}^{\mathcal{B}}$ is divided into a task-common part $\tilde{Q}_{c}^{\mathcal{B}}$ of size $K_{c} \times K_{c}$ and a task-specific part $\tilde{Q}_{s}^{\mathcal{B}}$ of size $K_{s} \times K_{s}$ with $K_{c} + K_{s} = K$. While the task-common features should be correlated to ensure memory stability, the task-specific features should be de-correlated to improve learning plasticity. Accordingly, the loss for the knowledge distillation from the previous task is given by the two parts:

$$\mathcal{L}_{c}(\mathcal{B}) = \sum_{i} (1 - \tilde{Q}_{c_{ii}}^{\mathcal{B}})^{2} + \lambda_{c} \sum_{i} \sum_{j \neq i} \tilde{Q}_{c_{ij}}^{\mathcal{B}^{2}}, \qquad (4)$$

$$\mathcal{L}_{s}(\mathcal{B}) = \sum_{i} \tilde{Q}_{s_{ii}}^{\mathcal{B}^{2}} + \lambda_{s} \sum_{i} \sum_{j \neq i} \tilde{Q}_{s_{ij}}^{\mathcal{B}^{2}},$$
(5)

where λ_c and λ_s are hyper-parameters that determine the contribution of the off-diagonal entries of the matrices $\tilde{Q}_c^{\mathcal{B}}$ and $\tilde{Q}_s^{\mathcal{B}}$, respectively.

The total loss for training the model F on subsequent tasks T_t ($t \ge 2$), is given by the following combination of losses:

$$\mathcal{L}_{CSSL} = \mathcal{L} + \frac{1}{2}(\mathcal{L}_c + \mathcal{L}_s).$$
(6)

It should be noted, that F_{t-1} is used as a frozen feature encoder that does not require gradient computations.

III. EXPERIMENTAL RESULTS

Experiments were conducted on RESISC45 [10] dataset, which includes 31500 RGB images of size 256×256 pixels. Each image is annotated with one of 45 different class labels and for each class there are 700 images. For each class, we randomly selected 560 images for training, 70 images for validation, and 70 images for testing. We defined 5 tasks based on the classes (i.e. each task contains samples from 9 classes). It should be noted that the class labels were only used for evaluation and are unknown to the model during training. For the encoder backbone f, we used ResNet50. For the projector g, we used a two-layer MLP with batch normalization and ReLU activation. The number K of feature dimensions was set to 2048. The hyper-parameters λ , λ_c and λ_s , which control the loss contribution of the off-diagonal entries, were all set to 0.1, according to [9]. We used the AdamW optimizer and trained for 300 epochs on each task. The batch size was set to 128 and the learning rate was set to 0.0001. We used cosine annealing with a warm-up of 10 epochs. For evaluation, we used a knearest-neighbor (kNN) classifier with k = 10. The results are reported in terms of average accuracy (AA), forgetting (F), and intransigence (I) and are obtained by averaging over three trials.

A. Evaluation Metrics

Here, we briefly define the evaluation metrics used in the experiments. Let $a_{l,j}$ denote the accuracy obtained on the test set of the *j*-th task after continual learning of the *l*-th task (for $l \ge j$). And let a_l^* denote the accuracy of a reference model trained on the joined data from the first *l* tasks. The AA, F, and I are defined by:

Average Accuracy:
$$AA_l = \sum_{j=1}^{l} a_{l,j},$$
 (7)

Forgetting:
$$F_l = \frac{1}{l-1} \sum_{j=1}^{l-1} \max_{i \in \{1, \dots, l-1\}} (a_{i,j} - a_{l,j}),$$
 (8)

Intransigence:
$$I_l = a_l^* - a_{l,l}$$
. (9)

The AA is associated with overall model performance. F is associated with the model's memory stability and I is associated with the model's learning plasticity [1].

We evaluated the model in task- and class-incremental scenarios. In the task-incremental scenario, the test sets of the individual tasks are used for evaluation, whereas in the classincremental scenario, a joined test set from all seen tasks is used for evaluation.

TABLE I

Average accuracy (\uparrow) obtained after the second task in the Class-Incremental Scenario for different numbers of dimensions for task-common and task-specific features.

Percentage of task-common dimensions	Numbers of Dimensions	AA ₂
50% 60% 70% 80% 90%	$K_c = 1024, K_s = 1024$ $K_c = 1228, K_s = 820$ $K_c = 1433, K_s = 615$ $K_c = 1638, K_s = 410$ $K_c = 1843, K_s = 205$	89.41 89.41 89.71 89.14 89.05

B. Experimental Analysis

First, we analyze the sensitivity to the numbers K_c and K_s of task-common and task-specific feature dimensions. Table I shows the AA₂ obtained on the validation set after the second task in the class incremental scenario. From the results, we can observe that by setting the number of task-common dimensions to 70% of the total feature dimensions (which corresponds to $K_c = 1433$ and $K_s = 615$) the method achieves the highest AA. It should be noted that we used the second task for validation since this is the first task, where the decoupling of feature dimensions is applied. The determined values are then fixed for the rest of the task sequence.

In the second set of experiments, we compare our method with the CaSSLe framework applied to BarlowTwins (that we from now on refer to as CaSSLe for simplicity). We also compare with a baseline of fine-tuning the BarlowTwins framework on the tasks sequentially. Tables II and III show the corresponding results for the task-incremental and the classincremental scenarios, respectively. From the tables, one can observe that the proposed method achieves the highest AA for all the tasks in both considered scenarios. As an example, in the task-incremental scenario, after learning the third task the proposed method achieves an AA of 93.4% which is 1.12%higher than CaSSLe and 1.52% higher than the baseline. As another example, in the class-incremental scenario, after learning the fifth task the proposed method achieves an AA of 83.49%, which is 1.24% higher than CaSSLe and 2.46%higher than the baseline. This shows that the proposed method can effectively learn feature encodings across tasks. From the tables, one can also observe that the proposed method shows lower I than CaSSLe, while only slightly increasing F. As an example, in the task-incremental scenario, after learning the third task the proposed method achieves an I score of 1.32% which is 2.33% lower than CaSSLe, while F is 0.48%, only 0.19% higher than CaSSLe. As another example, in the class-incremental scenario, after learning the fifth task the proposed method achieves an I score of 11.74%, which is 2.01% lower than CaSSLe and 1.77% lower than the baseline, while achieving an F score of 0.41%, which is even lower than the F score of CaSSLe at 0.71%. This shows that the proposed method can achieve a better trade-off in retaining knowledge from old tasks while being able to learn from new tasks. It should be noted that in the task-incremental

TABLE II

Average accuracy (\uparrow), forgetting (\downarrow) and intransigence (\downarrow) obtained for the proposed method, the CaSSLe framework and the baseline in the Task-Incremental Scenario.

Method	Task 1	Task 2	Task 3	Task 4	Task 5
	AA ₁ / F ₁ / I ₁	AA ₂ / F ₂ / I ₂	AA ₃ / F ₃ / I ₃	AA ₄ / F ₄ / I ₄	AA ₅ / F ₅ / I ₅
Baseline	92.01 / - / -	90.97 / 5.4 / 1.02	91.88 / 3.94 / 1.06	92.29 / 2.85 / 1.97	91.88 / 3.39 / 2.43
CaSSLe [8]	92.01 / - / -	92.05 / 0.65 / 3.6	92.28 / 0.29 / 3.65	92.07 / 0.37 / 5.61	92.42 / 0.7 / 4.07
Proposed Method	92.01 / - / -	92.3 / 1.56 / 2.17	93.4 / 0.48 / 1.32	92.63 / 1.43 / 3.39	92.98 / 1.08 / 3.23

TABLE III

Average accuracy (\uparrow), forgetting (\downarrow) and intransigence (\downarrow) obtained for the proposed method, the CaSSLe framework and the baseline in the Class-Incremental Scenario.

Method	Task 1 AA ₁ / F ₁ / I ₁	Task 2 AA ₂ / F ₂ / I ₂	Task 3 AA ₃ / F ₃ / I ₃	Task 4 AA ₄ / F ₄ / I ₄	Task 5 AA ₅ / F ₅ / I ₅
Baseline	92.01 / - / -	86.04 / 5.4 / 7.17	84.12 / 3.2 / 7.44	83.08 / 1.68 / 11.49	81.03 / 2.07 / 13.51
CaSSLe [8]	92.01 / - / -	88.25 / 0.65 / 7.51	85.95 / 0.28 / 7.46	83.86 / 0.87 / 11.92	82.25 / 0.71 / 13.75
Proposed Method	92.01 / - / -	88.6 / 1.59 / 5.87	86.59 / 0.81 / 6.12	84.28 / 1.37 / 10.45	83.49 / 0.41 / 11.74

scenario, the baseline achieves the best learning plasticity. This is due to the fact that in this scenario for evaluation the test sets of the tasks are used individually. Therefore, fine-tuning (baseline) on a given task is expected to yield the lowest I scores. Furthermore, the class-incremental scenario is harder and more realistic than the task-incremental scenario, therefore results are generally worse in this scenario. We would like to highlight, that in the class-incremental scenario, F scores are quite low in general while there is still a big gap for improving I scores. These results confirm that to improve AA the primary focus should be on effectively integrating new knowledge, with minimizing F regarded as a secondary priority.

IV. CONCLUSION

In this paper, we have presented a novel continual selfsupervised learning method for RS. The effectiveness of the proposed method arises from its knowledge distillation strategy, which incorporates a decoupling mechanism to partition feature dimensions into task-common and task-specific components. This design allows retaining knowledge of previous data while increasing learning plasticity. The experimental results show the success of the proposed method compared to the widely used CaSSLe framework. Furthermore, the results suggest that the primary focus in developing CSSL methods should be enhancing the model's ability to effectively integrate new knowledge, while preventing forgetting remains a secondary concern.

Although the experiments were conducted in the context of single-label classification of RGB images, the proposed method can be applied to any downstream learning task by adding a corresponding task head on top of the learned feature encoder, and to other modalities (e.g. multispectral images) by adjusting the image augmentations.

We note that the proposed method assumes the data for different continual learning tasks share the same modality. However, in real-world scenarios, each continual learning task may involve a different data modality. As future work, we plan to extend the proposed method to handle streams of multimodal data.

References

- L. Wang, X. Zhang, H. Su, and J. Zhu, "A comprehensive survey of continual learning: theory, method and application," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2024.
- [2] D. Ye, J. Peng, H. Li, and L. Bruzzone, "Better memorization, better recall: A lifelong learning framework for remote sensing image scene classification," *IEEE Transactions on Geoscience* and Remote Sensing, vol. 60, pp. 1–14, 2022.
- [3] N. Ammour, Y. Bazi, H. Alhichri, and N. Alajlan, "Continual learning approach for remote sensing scene classification," *IEEE Geoscience and Remote Sensing Letters*, vol. 19, pp. 1–5, 2022.
- [4] V. Marsocci and S. Scardapane, "Continual barlow twins: Continual self-supervised learning for remote sensing semantic segmentation," *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, vol. 16, pp. 5049– 5060, 2023.
- [5] J. Zbontar, L. Jing, I. Misra, Y. LeCun, and S. Deny, "Barlow twins: Self-supervised learning via redundancy reduction," *International conference on machine learning*, pp. 12310–12320, 2021.
- [6] J. Kirkpatrick, R. Pascanu, N. Rabinowitz, J. Veness, G. Desjardins, A. A. Rusu, K. Milan, J. Quan, T. Ramalho, A. Grabska-Barwinska *et al.*, "Overcoming catastrophic forgetting in neural networks," *Proceedings of the National Academy of Sciences*, vol. 114, no. 13, pp. 3521–3526, 2017.
- [7] D. Madaan, J. Yoon, Y. Li, Y. Liu, and S. J. Hwang, "Representational continuity for unsupervised continual learning," in *International Conference on Learning Representations*, 2022.
- [8] E. Fini, V. G. T. da Costa, X. Alameda-Pineda, E. Ricci, K. Alahari, and J. Mairal, "Self-supervised models are continual learners," *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 9621–9630, 2022.
- [9] Y. Wang, C. M. Albrecht, N. A. A. Braham, C. Liu, Z. Xiong, and X. X. Zhu, "Decoupling common and unique representations for multimodal self-supervised learning," *arXiv preprint* arXiv:2309.05300, 2024.
- [10] G. Cheng, J. Han, and X. Lu, "Remote sensing image scene classification: Benchmark and state of the art," *Proceedings of the IEEE*, vol. 105, no. 10, pp. 1865–1883, 2017.