

Universal Item Tokenization for Transferable Generative Recommendation

Bowen Zheng
Gaoling School of Artificial
Intelligence, Renmin University of
China
Beijing, China
bwzheng0324@ruc.edu.cn

Hongyu Lu
WeChat, Tencent
Guangzhou, China
luhy94@gmail.com

Yu Chen
WeChat, Tencent
Beijing, China
nealcui@tencent.com

Wayne Xin Zhao ✉
Gaoling School of Artificial
Intelligence, Renmin University of
China
Beijing, China
batmanfly@gmail.com

Ji-Rong Wen
Gaoling School of Artificial
Intelligence, Renmin University of
China
Beijing, China
jrwen@ruc.edu.cn

Abstract

Recently, generative recommendation has emerged as a promising paradigm, attracting significant research attention. The basic framework involves an item tokenizer, which represents each item as a sequence of codes serving as its identifier, and a generative recommender that predicts the next item by autoregressively generating the target item identifier. However, in existing methods, both the tokenizer and the recommender are typically domain-specific, limiting their ability for effective transfer or adaptation to new domains. To this end, we propose **UTGRec**, a Universal item Tokenization approach for transferable Generative Recommendation. Specifically, we design a universal item tokenizer for encoding rich item semantics by adapting a multimodal large language model (MLLM). By devising tree-structured codebooks, we discretize content representations into corresponding codes for item tokenization. To effectively learn the universal item tokenizer on multiple domains, we introduce two key techniques in our approach. For raw content reconstruction, we employ dual lightweight decoders to reconstruct item text and images from discrete representations to capture general knowledge embedded in the content. For collaborative knowledge integration, we assume that co-occurring items are similar and integrate collaborative signals through co-occurrence alignment and reconstruction. Finally, we present a joint learning framework to pre-train and adapt the transferable generative recommender across multiple domains. Extensive experiments on four public datasets demonstrate the superiority of UTGRec compared to both traditional and generative recommendation baselines.

CCS Concepts

• **Information systems** → **Recommender systems**.

Keywords

Universal Item Tokenization, Transferable Generative Recommendation

ACM Reference Format:

Bowen Zheng, Hongyu Lu, Yu Chen, Wayne Xin Zhao ✉, and Ji-Rong Wen. 2018. Universal Item Tokenization for Transferable Generative Recommendation. In *Proceedings of Make sure to enter the correct conference title from your rights confirmation email (Conference acronym 'XX)*. ACM, New York, NY, USA, 11 pages. <https://doi.org/XXXXXXXX.XXXXXXX>

1 Introduction

Sequential recommender systems aim to capture a user's personalized preference based on his/her historical interaction records. Typically, traditional approaches [7, 30] assign a unique ID to each item and represent user historical interactions as an item ID sequence in chronological order. Various methods [8, 15, 34, 58, 59] have been proposed to model item ID sequences and predict the next item the user is likely to interact with.

Recently, motivated by the promising potential of the generative paradigm in large language models (LLMs) [56] and generative retrieval methods [35, 39, 43, 52], a number of studies have explored this paradigm within recommender systems [14, 22, 24, 29, 57]. The basic idea of generative recommendation is to represent an item using a sequence of codes as its identifier instead of a single vanilla ID. Then, a generative model (e.g., T5 [28]) is employed to autoregressively generate the target item identifier, thereby achieving next-item prediction in a sequence-to-sequence manner. In this paradigm, the process of mapping an item to its identifier, referred to as *item tokenization*, plays a crucial role. Existing methods for item tokenization include co-occurrence matrix decomposition [24], hierarchical clustering [14, 32], and multi-level vector quantization [29, 42, 57]. The learned tokenizer associates each item with a series of codes that imply semantic knowledge, with shared prefix codes among different items reflecting their semantic similarity. To

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.
Conference acronym 'XX, June 03–05, 2018, Woodstock, NY

© 2018 Copyright held by the owner/author(s). Publication rights licensed to ACM.
ACM ISBN 978-1-4503-XXXX-X/18/06
<https://doi.org/XXXXXXXX.XXXXXXX>

further enhance the item tokenizer, some studies [21, 42] propose to incorporate collaborative signals to improve the quality of item identifiers and their effectiveness in recommendation tasks.

Despite the effectiveness, existing item tokenization methods are typically developed in a *domain-specific* manner. They often perform item clustering or train a RQ-VAE [54] using pre-encoded item embeddings derived from a single domain [29, 32], making the learned tokenizer the generative recommendation model less transferable across domains. Although it seems intuitive to directly extend these methods by training with multi-domain data, simple algorithms (*e.g.*, K-means) or model architectures (*e.g.*, RQ-VAE with MLP encoder) struggle to effectively capture the diverse and complex semantics across multiple domains [19, 40]. Moreover, pre-encoded item embeddings cannot be jointly trained with the tokenizer model, limiting the model’s ability to fully exploit its potential in learning item semantics. Considering the above limitations, we aim to develop a universal item tokenizer that can well transfer across multiple domains and also adapt to new domains. To achieve this, two key technical challenges should be addressed. First, the extensive variety of items across multiple domains entails diverse and complex semantics, necessitating the development of a tokenizer model with robust capabilities in content understanding and generalization. Second, it is important to effectively learn the item semantics while simultaneously integrating collaborative knowledge in recommendation scenarios.

In this paper, we propose **UTGRec**, a Universal item Tokenization approach for transferable Generative Recommendation. Different from existing domain-specific item tokenization methods [29, 42], our approach leverages the multimodal content of items as input and pre-trains a tokenizer model across multiple domains. Specifically, we focus on two key aspects, namely developing a universal item tokenizer and pre-training the model through item content reconstruction with collaborative integration. For universal item tokenization, we first learn multimodal token representations for encoding essential item semantics based on a multimodal large language model (MLLM). Then, we propose tree-structured codebooks for representation discretization, which enhances multi-domain semantic fusion through codebook sharing. For tokenizer pre-training, we propose an optimization objective that introduces two key techniques, namely raw content reconstruction and collaborative knowledge integration, for jointly capturing item and collaborative semantics. Raw content reconstruction introduces dual lightweight decoders to reconstruct the raw text and image from discrete representations, thereby learning the multi-modal knowledge embedded in the content. Regarding collaborative knowledge integration, we follow the assumption that co-occurring items are similar and incorporate collaborative knowledge into the item tokenizer via co-occurring item alignment and reconstruction. A key merit of our method lies in that it can jointly learn multimodal representation encoding and discretization modules. Finally, given the universal item tokenizer, we propose a learning framework to pre-train a transferable generative recommender.

In summary, our key contributions are as follows:

- We propose UTGRec, a transferable generative recommendation framework that can leverage both multimodal item content and collaborative knowledge for universal item tokenization.

- We design a novel representation discretization method via tree-structured codebooks while presenting an optimization approach that integrates content reconstruction with co-occurring item alignment and reconstruction.

- We conduct extensive experiments on four public datasets to evaluate the effectiveness of our approach, demonstrating that UTGRec outperforms all baselines and attains significant improvements in transferable recommendation.

2 Methodology

In this section, we present a universal item tokenization approach for transferable generative recommendation, named **UTGRec**.

2.1 Problem Formulation and Overview

Following prior studies [11, 40], we consider the sequential recommendation task across multiple domains. For each domain, an item set \mathcal{I} is given, and a user’s historical interactions are denoted as an item ID sequence $S = [i_1, i_2, \dots, i_n]$ arranged in chronological order, where $i \in \mathcal{I}$ denotes an interacted item. Sequential recommendation aims to capture user preferences and predict the next potential item i_{n+1} based on S . Different from the conventional setting, we adopt the generative paradigm in which each item is associated with a list of codes $[c_1, \dots, c_L]$ derived from its text T_i and image V_i , serving as its identifier. L is the length of the identifier. Through the above process called item tokenization, the item sequence S and the target item i_{n+1} can be tokenized into a pair of code sequences $X = [c_1^1, c_2^1, \dots, c_{L-1}^n, c_L^n]$ and $Y = [c_1^{n+1}, \dots, c_L^{n+1}]$, where each item is represented by L codes. Thus, the traditional sequential recommendation task is reformulated as a sequence-to-sequence problem, in which the next-item prediction is achieved by autoregressively generating the target item identifier (*i.e.*, Y). Formally, this problem can be written as:

$$P(Y|X) = \prod_{l=1}^L P(c_l^{n+1} | X, c_1^{n+1}, \dots, c_{l-1}^{n+1}). \quad (1)$$

To assign item identifiers, previous studies [24, 29, 42] have developed various item tokenizers. However, these tokenizers are typically domain-specific, generative recommenders trained with such tokenizers lack the ability to generalize to new domains. In this paper, we address this limitation by learning a universal item tokenizer. The overall framework is illustrated in Figure 1. First, we develop a universal item tokenizer based on the multimodal content of items and propose tree-structured codebooks for representation discretization (Section 2.2). Second, we perform item content reconstruction via discrete representations for multimodal semantic learning and integrate collaborative knowledge through alignment and reconstruction of co-occurring items (Section 2.3). Finally, we present a transferable generative recommender learning framework based on the universal item tokenizer (Section 2.4).

2.2 Universal Item Tokenization

To develop the universal item tokenizer, a key step is to sufficiently leverage the rich item semantics and establish a representation scheme that can well transfer across domains. Unlike previous text-based transferable item representations [9, 11], we consider




Figure 1: The overall framework of UTGRec.

leveraging multimodal item content for capturing more comprehensive semantic information. Moreover, to achieve multi-domain item tokenization, we design a novel representation discretization approach via tree-structured codebooks.

2.2.1 Item Content Encoding via MLLM. In our framework, each item i is associated with textual information T_i (e.g., the item title, features, and category) and a corresponding image V_i . To efficiently encode the multimodal content, we employ a MLLM to compress this information into several representations. Specifically, we employ Qwen2-VL [41] as the backbone model and formalize the item’s textual and visual information as the following input prompt:

Prompt for Item Content Encoding

```
<|vision_start|><IMAGE><|vision_end|>
This is an image of an item. The item’s information
also includes: “<TEXT>”. Compress the image and text
information into  $L$  tokens, representing content from
coarse to fine granularity.
<CODE_1><CODE_2> ... <CODE_L>
```

In this prompt, “<|vision_start|>” and “<|vision_end|>” are special tokens that delineate the beginning and end of the vision input. “<IMAGE>” is a placeholder for the image and would be replaced by visual token embeddings derived from the raw image V_i . Similarly, “<TEXT>” is a placeholder for the text T_i . Furthermore, “<CODE_1> ... <CODE_L>” represent L code tokens used to integrate content information, which are added to the MLLM vocabulary. Formally, we denote this prompt as $P(V_i, T_i)$ and feed it into the MLLM to obtain item representations:

$$\mathbf{H} = [\mathbf{h}_1, \mathbf{h}_2, \dots, \mathbf{h}_L] = \text{MLLM}(P(V_i, T_i)), \quad (2)$$

where $\mathbf{H} \in \mathbb{R}^{L \times d}$ denotes the output hidden states corresponding to tokens code tokens, serving as the representations of the compressed item content information.

2.2.2 Representation Discretization via Tree-Structured Codebooks. After obtaining L content representations of an item, we need to

map them into discrete codes for item tokenization. A straightforward method is to learn multi-level codebooks, as proposed in existing studies [29, 42], to discretize each content representation individually. However, this method presents two potential issues. First, although we instruct the MLLM to compress information of different granularities into multiple representations, these representations are essentially derived from the same item content, resulting in high similarity. Consequently, items with the same prefix code often share subsequent codes. Secondly, codebook representation collapse [31] is more likely to occur across multiple domains, that is, only a few codebook vectors are activated in each domain. This phenomenon significantly affects multi-domain fusion and undermines the sufficient utilization of codebooks. To address the above issues, we first apply the prefix residual operation to transform content representations into a basic representation and multi-level incremental representations, thereby alleviating high similarity. Subsequently, we present tree-structured codebooks, which enable joint optimization of codebook space and enhance codebook utilization by sharing multi-level codebooks and parameterizing each codebook into two components.

Prefix Residual Operation. Given the content representations \mathbf{H} , we leverage a MLP to project it to $\mathbf{H}' \in \mathbb{R}^{L \times d_c}$ for dimension adaptation, where d_c denotes the codebook dimension. Afterward, we apply the prefix residual operation as follows:

$$\tilde{\mathbf{h}}_l = \mathbf{h}'_l - \mathbf{h}'_{l-1}, \quad l \in 2, \dots, L, \quad (3)$$

where \mathbf{h}'_l denotes the l -th representation in \mathbf{H}' . Unlike the recursive subtraction used in residual quantization [1], our approach extracts the incremental representation $\tilde{\mathbf{h}}_l$ that captures the incremental information relative to the prefix representation, which is more diverse and distinguishable. Furthermore, $\tilde{\mathbf{h}}_1 = \mathbf{h}'_1$ serves as the item’s basic content representation, which remains unchanged.

Tree-Structured Codebooks. With the above prefix residual operation, we can obtain the basic representation and multi-level incremental representations of an item. To discretize these representations into a list of codes as the item identifier, we propose tree-structured codebooks, which consist of two components: the

root codebook and the leaf codebook. The root codebook is dedicated to the basic representation, capturing the primary content information of the item. The leaf codebook is shared across the multi-level incremental representations to model the incremental information from multiple domains, which can improve the codebook utilization and enhance multi-field fusion [17].

To alleviate representation collapse, we parameterize each codebook as $\mathbf{E}\mathbf{W}$, taking inspiration from recent work [62]. Here, $\mathbf{E} \in \mathbb{R}^{K \times d_c}$ denotes the codebook matrix and $\mathbf{W} \in \mathbb{R}^{d_c \times d_c}$ is a projection matrix, where K denotes the size of the codebook. Unlike traditional codebooks that only involve the codebook matrix \mathbf{E} , this method optimizes each row of the codebook matrix \mathbf{E} while jointly updating the projection matrix \mathbf{W} , thereby driving the optimization of the entire codebook space [62]. This advantage allows the gradient from each domain to drive the update of the entire codebook space, effectively preventing the fragmentation of codebook vectors and promoting multi-domain fusion. Then, we denote the root and leaf codebooks as $\mathbf{C}^r = \mathbf{E}^r \mathbf{W}^r$ and $\mathbf{C}^f = \mathbf{E}^f \mathbf{W}^f$ respectively and employ them to discretize representations as follows:

$$c_l = \begin{cases} \arg \min_j \|\tilde{\mathbf{h}}_l - \mathbf{e}_j^r \mathbf{W}^r\|_2^2, & \text{if } l = 1, \\ \arg \min_j \|\tilde{\mathbf{h}}_l - \mathbf{e}_j^f \mathbf{W}^f\|_2^2, & \text{if } l > 1, \end{cases} \quad (4)$$

where c_l denotes the l -th code of the item, \mathbf{e}_j^r and \mathbf{e}_j^f are the j -th codebook vectors in \mathbf{E}^r and \mathbf{E}^f respectively. The optimization objective of tree-structured codebooks is formulated as follows:

$$\mathcal{L}_{\text{Code}} = \frac{1}{2} (\mathcal{L}^r + \mathcal{L}^f), \quad (5)$$

where \mathcal{L}^r and \mathcal{L}^f are defined as follows:

$$\mathcal{L}^r = \|\text{sg}[\tilde{\mathbf{h}}_1] - \mathbf{e}_{c_1}^r \mathbf{W}^r\|_2^2 + \beta \|\tilde{\mathbf{h}}_1 - \text{sg}[\mathbf{e}_{c_1}^r \mathbf{W}^r]\|_2^2, \quad (6)$$

$$\mathcal{L}^f = \frac{1}{L-1} \sum_{l=2}^L \|\text{sg}[\tilde{\mathbf{h}}_l] - \mathbf{e}_{c_l}^f \mathbf{W}^f\|_2^2 + \beta \|\tilde{\mathbf{h}}_l - \text{sg}[\mathbf{e}_{c_l}^f \mathbf{W}^f]\|_2^2, \quad (7)$$

where $\text{sg}[\cdot]$ denotes the stop-gradient operation. β is used to balance the optimization between the item representations and codebooks, typically set to 0.25. \mathcal{L}^r and \mathcal{L}^f represent the losses associated with the root and leaf codebooks, respectively.

2.3 Item Content Reconstruction with Collaborative Integration

Unlike existing works [29, 42] that learn codebook semantics based on pre-coded embeddings, we employ the raw content information as reconstruction targets to ensure the completeness of the information. Simultaneously, we jointly optimize the item encoding and representation discretization process to achieve better multi-domain content understanding. Moreover, since simple content reconstruction cannot integrate collaborative knowledge in recommender systems, we further align and reconstruct co-occurring items to achieve collaborative integration within item tokenizer.

2.3.1 Raw Content Reconstruction. Based on tree-structured codebooks, we can obtain the codes of the item $[c_1, \dots, c_L]$ and corresponding discrete representations $[\mathbf{e}_{c_1}^r \mathbf{W}^r, \mathbf{e}_{c_2}^f \mathbf{W}^f, \dots, \mathbf{e}_{c_L}^f \mathbf{W}^f]$.

Then, we apply the inverse of the prefix residual operation, recursively restoring discrete increment representations into discrete content representations. Formally, the process can be written as: $\hat{\mathbf{h}}_l = \hat{\mathbf{h}}_{l-1} + \mathbf{e}_{c_l}^f \mathbf{W}^f$, where $\hat{\mathbf{h}}_1 = \mathbf{e}_{c_1}^r \mathbf{W}^r$, and the l -th discrete content representation $\hat{\mathbf{h}}_l$ is obtained by adding the l -th discrete increment representation $\mathbf{e}_{c_l}^f \mathbf{W}^f$ to the last discrete content representation $\hat{\mathbf{h}}_{l-1}$. After a linear projection for dimension adaptation, we denote all discrete content representations as $\hat{\mathbf{H}} \in \mathbb{R}^{L \times d}$. Subsequently, we introduce dual decoders to reconstruct the raw text and image, facilitating codebooks to learn the content semantics of the item.

Text Reconstruction. Before feeding discrete representations $\hat{\mathbf{H}}$ into the decoder, we first concatenate them with mask tokens: $\mathbf{H}^t = [\hat{\mathbf{H}}, \mathbf{M}^t]$, where $\mathbf{M}^t \in \mathbb{R}^{|T_i| \times d}$ is a mask token matrix used to label the item text to be reconstructed, obtained by repeating a mask embedding $|T_i|$ times. After that, we introduce a lightweight decoder (*i.e.*, one-layer Transformer model) with bidirectional attention to predict the raw item text. Formally, the optimization objective for text reconstruction is the following negative log-likelihood loss:

$$\mathcal{L}^t = - \sum_{x \in T_i} \log P(x | \text{Dec}^t(\mathbf{H}^t)), \quad (8)$$

where x denotes the token in item text T_i , Dec^t is the text decoder. The above task is analogous to masked language modeling (MLM) [3] with a mask probability of 100%, which forces the decoder to rely on discrete content representations for text reconstruction. Combined with the lightweight and weak decoder, this approach can effectively promote semantic learning of discrete content representations [48].

Image Reconstruction. Similar to text reconstruction, we also concatenate $\hat{\mathbf{H}}$ and the mask matrix $\mathbf{M}^v \in \mathbb{R}^{|V_i| \times d}$ to form vision decoder input \mathbf{H}^v . We then employ a lightweight visual decoder Dec^v to reconstruct the raw image V_i . However, representing the raw image as discrete tokens is challenging, as it is more naturally represented by continuous values. Therefore, we draw upon recent work [20], which introduces a small diffusion model and leverages diffusion loss as the reconstruction objective. This approach has been shown to be more advanced than naive MSE loss [20]. Thus, the image reconstruction loss is formulated as:

$$\mathcal{L}^v = \text{DiffLoss}(\text{Dec}^v(\mathbf{H}^v), V_i), \quad (9)$$

where $\text{DiffLoss}(\cdot, \cdot)$ denotes the diffusion loss, computed based on the decoder's output latent representations, with the raw item image V_i serving as the target.

Combining the above text and image reconstruction losses, we define the following raw content reconstruction loss:

$$\mathcal{L}_{\text{Raw}} = \mathcal{L}^t + \alpha \mathcal{L}^v, \quad (10)$$

where α is a hyper-parameter for the trade-off between text reconstruction and image reconstruction.

2.3.2 Collaborative Knowledge Integration. As discussed before, while raw content reconstruction captures universal knowledge from item content information, it overlooks critical collaborative signals that are essential for effective recommendation. To this end, we adopt the intuitive assumption in recommendation scenarios that co-occurring items are similar. For each item within the user

interaction sequence, we select its one-hop neighbors as positive examples for collaborative knowledge integration. By traversing all user interaction sequences, we construct a set of positive instances for item i , denoted as \mathcal{I}_i^+ . Then, each item is paired with a sampled positive item $i^+ \in \mathcal{I}_i^+$ as input. For collaborative knowledge integration within the item tokenizer, we propose two tasks: co-occurrence item alignment and reconstruction.

Co-occurring Item Alignment. For co-occurring item alignment, we aim to integrate collaborative knowledge into the MLLM encoder by aligning the content representations of positive items. Formally, as described in Section 2.2.1, we obtain the content representations \mathbf{H} and \mathbf{H}^+ for the item i and its positive item i^+ , respectively. Afterward, we apply contrastive learning to align \mathbf{H} and \mathbf{H}^+ through the InfoNCE [6] loss with in-batch negatives. The co-occurring item alignment loss can be calculated as follows:

$$\mathcal{L}_{\text{Ali}} = - \sum_{l=1}^L \log \frac{\exp(\cos(\mathbf{h}_l, \mathbf{h}_l^+)/\tau)}{\sum_{\hat{\mathbf{h}}_l \in \mathcal{B}_l} \exp(\cos(\mathbf{h}_l, \hat{\mathbf{h}}_l)/\tau)}, \quad (11)$$

where τ denotes a temperature hyper-parameter, and \mathcal{B}_l is a batch of content representations for positive items in l -th level. Since the batch data is constructed randomly, the negative instances within a batch are from a mixture of multiple domains, thereby facilitating the fusion of cross-domain knowledge.

Co-occurring Item Reconstruction. For co-occurrence reconstruction, our goal is to ensure that discrete content representations of positive pairs capture similar semantics. As discrete representations are looked up from codebooks and shared across different items, the representations of positive items may also appear in negative examples, which undermines the reliability of contrastive learning. Therefore, we propose reconstructing the content of the positive item based on discrete content representations $\hat{\mathbf{H}}$ corresponding to the current item. Formally, the co-occurring item reconstruction loss is calculated as:

$$\mathcal{L}_{\text{Re}} = \mathcal{L}^{t^+} + \alpha \mathcal{L}^{v^+}, \quad (12)$$

where \mathcal{L}^{t^+} denotes the loss for positive item text reconstruction (Eqn. (8)), and \mathcal{L}^{v^+} denotes the loss for positive item image reconstruction (Eqn. (9)). This negative-independent approach implicitly encourages the discrete representations of item i to learn consistent semantics of its positive sample, enabling codebooks to effectively encode the semantic similarity between them.

Finally, we integrate the raw content reconstruction loss (Eqn. (10)), the codebook learning loss (Eqn. (7)), and the two collaborative knowledge integration losses (Eqn. (11) and Eqn. (12)) to formulate the overall objective of the universal item tokenizer as follows:

$$\mathcal{L}_T = \mathcal{L}_{\text{Raw}} + \lambda \mathcal{L}_{\text{Code}} + \mu \mathcal{L}_{\text{Ali}} + \eta \mathcal{L}_{\text{Re}}, \quad (13)$$

where λ , μ and η are hyper-parameters for the trade-off between various objectives.

2.4 Recommender Learning Framework

After learning a universal item tokenizer, we first pre-train a generative recommender based on multi-domain data, and then fine-tune the pre-trained model for downstream domains.

2.4.1 Multi-Domain Pre-training. The multi-domain pre-training for generative recommender consists of two phases:

Multi-Domain Item Tokenization. We utilize the pre-trained universal item tokenizer T to uniformly map items across multiple domains to their corresponding identifiers, ensuring that all domains sharing the same code space. Thus, the item sequence S and the target item i_{n+1} are tokenized as $X = [c_1^1, c_2^1, \dots, c_{L-1}^n, c^n - L]$ and $Y = [c_1^{n+1}, \dots, c_L^{n+1}]$ respectively. These tokenized sequences from multiple domains are then mixed to form the pre-training data. Regarding conflict handling, unlike previous works [29, 42] that append a semantically irrelevant extra code, we reassign the last-level code to the second-nearest or a farther neighbor code. Finally, we mix code sequences from multiple domains as pre-training data for the generative recommender.

Generative Recommender Optimization. Generative recommendation reformulates the next-item prediction task as a sequence-to-sequence problem. Therefore, we optimize the model by minimizing the negative log-likelihood loss of the target sequence Y :

$$\mathcal{L}_R = - \log P(Y|X) = - \sum_{l=1}^L \log P(c_l^{n+1}|X, c_1^{n+1}, \dots, c_{l-1}^{n+1}). \quad (14)$$

2.4.2 Downstream Fine-tuning. In order to transfer and adapt to new domains, we consider two fine-tuning stages:

Item Tokenizer Fine-tuning. For effective knowledge transfer across multiple domains, a key challenge in generative recommendation is to maintain the correlation and transformation patterns between different codes learned during pre-training. To this end, we propose fixing the primary parameters (*i.e.*, E^r and E^f) of the tree-structured codebooks to retain the general knowledge and only fine-tune projection matrices W^r and W^f to incorporate domain-specific adaptations. Additionally, since the item tokenizer is fine-tuned within a specific domain, we fix the number of item codes L during fine-tuning. The fine-tuning task mirrors the pre-training process, and the loss function remains the same as defined in Eqn. (13).

Generative Recommender Fine-tuning. Given the fine-tuned item tokenizer, domain adaptation of the generative recommender is straightforward. We first employ the fine-tuned item tokenizer to tokenize the item interaction data from the new domain into code sequences. Then, the pre-trained generative recommender is fine-tuned using the negative log-likelihood loss defined in Eqn. (14).

3 Experiments

This section first sets up the experiment and then presents overall performance as well as in-depth analyses of UTGRec.

3.1 Experiment Setup

3.1.1 Dataset. To evaluate the performance of UTGRec, we select nine subsets from Amazon 2023 review dataset [10] and divide them into two groups as pre-training datasets and downstream datasets respectively. Five domains are used for pre-training: “Arts Crafts and Sewing”, “Baby Products”, “CDs and Vinyl”, “Cell Phones and Accessories”, and “Software”. Another four subsets as downstream datasets: “Musical Instruments”, “Industrial and Scientific”, “Video

Table 1: Statistics of the preprocessed datasets. Avg.len denotes the average length of item sequences.

Dataset	#Users	#Items	#Inter.	Avg.len	Sparsity
Pre-training	999,334	344,412	8,609,909	8.62	99.997%
Instrument	57,439	24,587	511,836	8.91	99.964%
Scientific	50,985	25,848	412,947	8.10	99.969%
Game	94,762	25,612	814,586	8.60	99.966%
Office	223,308	77,551	1,577,570	7.07	99.991%

Games”, and “Office Products”. Following prior studies [11, 29], we apply five-core filtering to all pre-training and downstream datasets, discarding low-activity users and items with fewer than five interactions. We group the historical item sequences by users and sort them by timestamps, with a maximum sequence length limit of 20 items. For item text, we concatenate the title, feature, and category fields within item metadata. For item images, we employ the “large” size images provided in the dataset. The detailed statistics of preprocessed datasets are presented in Table 1.

3.1.2 Baseline Models. To enable a comprehensive comparison, we categorize the baseline models into three distinct groups:

(1) Traditional sequential recommenders:

- **GRU4Rec** [8] leverages Gated Recurrent Units (GRUs) to model sequential patterns in user interactions.
- **BERT4Rec** [34] employs the bidirectional self-attention mechanism with a masked prediction objective for sequence modeling.
- **SASRec** [15] utilizes a unidirectional self-attention network to model user behaviors.
- **FMLP-Rec** [59] introduces an all-MLP model with learnable filters to reduce noise and effectively capture user preferences.

(2) Content-based sequential recommenders:

- **FDSA** [55] presents a dual-stream self-attention framework that independently models item-level and feature-level sequences for recommendation.
- **S³-Rec** [58] enhances sequential recommendation models by leveraging feature-item correlations as self-supervised signals.
- **UniSRec** [11] leverages the associated description text of items to learn universal representations across different domains.
- **VQ-Rec** [9] proposes representing item text as discrete codes and subsequently learning transferable code embeddings for universal sequence modeling.
- **MISSRec** [40] learns multimodal interest-aware sequence representation for transferable recommendation.

(3) Generative recommenders:

- **TIGER** [29] employs RQ-VAE to map items into semantic IDs, which serve as item identifiers, and adopts the generative retrieval paradigm for sequential recommendation.
- **LETTER** [42] enhances TIGER by incorporating collaborative and diversity regularization into RQ-VAE.
- **TIGER_M** [29] utilizes multimodal embeddings as item semantic embeddings for training the RQ-VAE. For the multimodal encoder, we tried CLIP [27] and Qwen2-VL-2B [41]. The results reported are the best of these two encoders.

3.1.3 Evaluation Settings. We evaluate model performance using two widely adopted metrics: top- K Recall and Normalized Discounted Cumulative Gain (NDCG), with K set to 5 and 10. Following previous studies [15, 29, 58], we employ the *leave-one-out* strategy for dataset splitting. For each user interaction sequence, the latest item is designated as the test data, the second most recent item as the validation data, and all remaining items as the training data. To ensure a rigorous comparison, we conduct the full-ranking evaluation over the entire item set. Additionally, the beam size is set to 50 for all generative recommendation models.

3.1.4 Implementation Details. We utilize Qwen2-VL-2B [41] as the backbone for our universal item tokenizer and perform low-rank fine-tuning using LoRA [12]. The dual decoders are implemented as two one-layer Transformer models. The root and leaf codebook sizes are set to 256 and 512, respectively, maintaining the total number of learnable codebook vectors consistent with baseline methods (e.g., TIGER). The item identifier length L is set to 3. For tokenizer optimization, we use the AdamW optimizer with initial learning rates of $3e-4$ for pre-training and $1e-4$ for fine-tuning. A cosine scheduler is employed to dynamically adjust the learning rates. The batch size per GPU is set to 16, with 16 GPUs used for pre-training over 3 epochs, followed by fine-tuning on downstream datasets for 20 epochs. The loss coefficient λ for codebook learning is set to 200. The hyper-parameters α , μ , and η are tuned in $\{0.3, 1, 3, 5, 10\}$, $\{0.001, 0.003, 0.01, 0.03\}$, and $\{0.01, 0.03, 0.1, 0.3\}$, respectively. Furthermore, all hyper-parameters are kept consistent across both pre-training and fine-tuning phases. For the generative recommender, we adopt the settings in TIGER [29], which employs T5 [28] as the backbone, and we tune the number of encoder and decoder layers within $\{1, 2, 3, 4, 5, 6\}$. We also leverage the AdamW optimizer and cosine scheduler to optimize the recommender. The initial learning rates for pre-training and fine-tuning are set to 0.005 and 0.003, respectively. The batch size per GPU is 256 and 4 GPUs are used for recommender training. The recommender is pre-trained across multiple domains for 50 epochs, while fine-tuning is conducted using an early stopping strategy based on validation performance to ensure convergence and prevent overfitting.

3.2 Overall Performance

We compare UTGRec with various baseline models on four public recommendation benchmarks. The overall results are shown in Table 2. From these results, we have the following observations:

Compared to traditional recommendation models (i.e., GRU4Rec, BERT4Rec, SASRec, FMLP-Rec), content-based models (i.e., FDSA, S³-Rec) achieve superior results and pre-training across multiple domains leads to further improvements (i.e., UniSRec, VQ-Rec, MISSRec). This phenomenon shows that incorporating item content information (e.g., item texts and images) and learning universal item representations can significantly improve recommendation performance. Generative recommenders (i.e., TIGER, LETTER, TIGER_M) benefit from the generative paradigm and the prior semantics within item identifiers, outperforming traditional recommendation models. Among these, LETTER surpasses TIGER due to its application of collaborative and diversity regularization in the item tokenizer. TIGER_M improves upon TIGER on Scientific and Game datasets but underperforms on Instrument and Office datasets, which indicates

Table 2: The overall performance comparisons between different baseline methods and UTGRec. The best and second-best results are highlighted in bold and underlined font, respectively. “*” denotes that the improvements are statistically significant with $p < 0.01$ in a paired t-test setting.

Dataset	Metric	GRU4Rec	BERT4Rec	SASRec	FMLP-Rec	FDSA	S ³ -Rec	UniSRec	VQ-Rec	MISSRec	TIGER	LETTER	TIGER _M	UTGRec
Instrument	Recall@5	0.0324	0.0307	0.0333	0.0339	0.0347	0.0317	0.0356	0.0361	<u>0.0384</u>	0.0370	0.0372	0.0365	0.0398*
	NDCG@5	0.0209	0.0195	0.0213	0.0218	0.0230	0.0199	0.0228	0.0231	<u>0.0250</u>	0.0244	0.0246	0.0239	0.0263*
	Recall@10	0.0501	0.0485	0.0523	0.0536	0.0545	0.0496	0.0560	0.0578	<u>0.0590</u>	0.0564	0.0580	0.0551	0.0616*
	NDCG@10	0.0266	0.0252	0.0274	0.0282	0.0293	0.0257	0.0299	0.0301	<u>0.0307</u>	0.0306	<u>0.0313</u>	0.0298	0.0334*
Scientific	Recall@5	0.0202	0.0186	0.0259	0.0269	0.0262	0.0263	0.0276	0.0285	<u>0.0291</u>	0.0264	0.0279	0.0280	0.0308*
	NDCG@5	0.0129	0.0119	0.0150	0.0155	0.0169	0.0171	0.0174	0.0188	<u>0.0190</u>	0.0175	0.0182	0.0182	0.0204*
	Recall@10	0.0338	0.0296	0.0412	0.0422	0.0421	0.0418	0.0437	0.0444	<u>0.0452</u>	0.0422	0.0435	0.0437	0.0481*
	NDCG@10	0.0173	0.0155	0.0199	0.0204	0.0213	0.0219	0.0226	0.0229	<u>0.0237</u>	0.0226	0.0232	0.0233	0.0255*
Game	Recall@5	0.0499	0.0460	0.0535	0.0528	0.0544	0.0485	0.0546	0.0560	0.0570	0.0559	0.0563	<u>0.0571</u>	0.0592*
	NDCG@5	0.0320	0.0298	0.0331	0.0338	0.0361	0.0315	0.0353	0.0333	0.0337	0.0366	0.0372	<u>0.0375</u>	0.0390*
	Recall@10	0.0799	0.0735	0.0847	0.0857	0.0852	0.0769	0.0864	0.0879	0.0862	0.0868	<u>0.0877</u>	0.0873	0.0909*
	NDCG@10	0.0416	0.0386	0.0438	0.0444	0.0448	0.0406	0.0453	0.0443	0.0426	0.0467	<u>0.0473</u>	0.0472	0.0491*
Office	Recall@5	0.0204	0.0182	0.0255	0.0259	0.0263	0.0247	0.0246	0.0272	0.0264	0.0288	<u>0.0290</u>	0.0280	0.0320*
	NDCG@5	0.0135	0.0119	0.0149	0.0156	0.0177	0.0139	0.0160	0.0178	0.0166	0.0199	<u>0.0201</u>	0.0195	0.0224*
	Recall@10	0.0307	0.0277	0.0375	0.0392	0.0380	0.0371	0.0372	0.0401	0.0374	0.0417	<u>0.0421</u>	0.0400	0.0462*
	NDCG@10	0.0168	0.0150	0.0187	0.0199	0.0215	0.0179	0.0201	0.0219	0.0200	0.0241	<u>0.0243</u>	0.0234	0.0269*

Table 3: Ablation study of our approach.

Methods	Instrument		Scientific	
	Recall@10	NDCG@10	Recall@10	NDCG@10
(0) UTGRec	0.0616	0.0334	0.0481	0.0255
(1) w/o TreeCode	0.0591	0.0319	0.0457	0.0239
(2) w/o \mathcal{L}_{Ali}	0.0599	0.0321	0.0464	0.0243
(3) w/o \mathcal{L}_{Re}	0.0607	0.0326	0.0468	0.0246
(4) w/o FT(T)	0.0551	0.0302	0.0415	0.0218
(5) Full FT	0.0559	0.0304	0.0423	0.0225
(6) w/o PT(R)	0.0583	0.0315	0.0451	0.0236
(7) w/o PT	0.0575	0.0310	0.0444	0.0232

that a naive integration of multimodal features may not always yield beneficial outcomes. Furthermore, limited by the domain-specific tokenizers and recommenders, generative baseline models do not consistently perform better than transferable sequential recommenders (e.g., MISSRec). This further highlights the importance of developing a transferable generative recommender.

Finally, our proposed UTGRec maintains the best performance in all cases, exhibiting substantial improvements over traditional, content-based, and generative baseline models. Different from previous generative recommenders, we propose a universal item tokenizer that leverages multimodal content for item semantic modeling. Based on this, we develop a transferable generative recommender, which effectively enhances model performance by integrating the strengths of the generative paradigm and cross-domain knowledge transfer.

3.3 Ablation Study

To investigate how the proposed techniques impact model performance, we conduct an ablation study on Instrument and Scientific datasets. Specifically, we consider the following six variants of UTGRec: (1) w/o TreeCode without the tree-structured codebooks

and instead applying the multi-level codebooks like RQ-VAE (Section ??). (2) w/o \mathcal{L}_{Ali} without the co-occurring item alignment loss (Eqn. (11)). (3) w/o \mathcal{L}_{Re} without the co-occurring item reconstruction loss (Eqn. (12)). (4) w/o FT(T) without tokenizer fine-tuning when transferring to downstream domains, instead directly using the pre-trained universal item tokenizer to tokenize items in the new domain. (5) Full FT does not fix the codebook matrices (i.e., E^r and E^f) of the tree-structured codebooks during fine-tuning. (6) w/o PT(R) without generative recommender pre-training. On downstream datasets, only the pre-trained item tokenizer is fine-tuned, while the generative recommender is trained from scratch. (7) w/o PT without both tokenizer and recommender pre-training, but learns both components within a domain-specific setting.

The experimental results for our UTGRec and its multiple variants are presented in Table 3. As observed, removing any of the aforementioned techniques leads to a decline in overall performance. The tree-structured codebooks outperform the straightforward multi-level codebooks (i.e., variant (1)). The absence of the co-occurring item alignment and reconstruction (i.e., variants (2) and (3)) results in a lack of collaborative knowledge within the universal item tokenizer, causing performance degradation. Directly applying the pre-trained item tokenizer to downstream datasets (i.e., variant (4)) fails to achieve the expected results, which is likely due to the entanglement of item codes in the new domain. Furthermore, fine-tuning all codebook parameters (i.e., variant (5)) may disrupt the associations between codes, resulting in the loss of general knowledge acquired during pre-training.

3.4 Further Analysis

3.4.1 Recommender Scalability Analysis. The generative recommender for a specific domain is often limited by data sparsity in recommendation scenarios, making it difficult to improve the performance through model scaling, as seen with LLMs [2, 16, 56]. In contrast, our proposed universal item tokenizer allows us to leverage more massive and diverse data from multiple domains, thereby




Figure 2: Performance comparison w.r.t. model scale.




Figure 3: hyper-parameter tuning on instrument dataset.

facilitating the effective scaling of generative recommenders. In this part, we explore the scalability of UTGRec by gradually increasing the number of encoder and decoder layers of the generative recommender to six layers. From the results in Figure 2, we can observe that the performance of baseline models (*i.e.*, TIGER, LETTER) shows a positive correlation with model scale only in a few layers. With a slight increase in model size, performance begins to degrade due to overfitting. Conversely, the performance of UTGRec generally improves as the model scales, which demonstrates that universal item tokenization and recommender pre-training are beneficial to the scalability of generative models.

3.4.2 Hyper-Parameter Analysis. We continue to investigate the impact of hyper-parameters in our approach. For the loss coefficient of image reconstruction, we tune α within the range $\{0.3, 1, 3, 5, 10\}$. As shown in Figure 3, the model attains the best results by achieving a trade-off between text and image semantic learning when α is set to 3. For the loss coefficient of co-occurring item alignment, we tune μ within the ranges $\{0.001, 0.003, 0.01, 0.03\}$. The results indicate that an inappropriate μ impairs the learning of item content representations, leading to suboptimal performance. The optimal value of μ is found to be 0.01. For the loss coefficient of co-occurring item reconstruction, we explore values of η from the set $\{0.01, 0.03, 0.1, 0.3\}$. UTGRec exhibits subpar performance when η is overly large and achieves optimal performance when η is 0.03.

3.4.3 Performance Comparison w.r.t. Long-tail Items. To validate the universality and generality on long-tail items, we split the test data into different groups according to the popularity of target items. Then, we compare the performance of various models on these data groups and present the improvements over TIGER in Figure 4. Transferable sequential recommenders (*i.e.*, UniSRec, MISSRec) outperform TIGER in the cold-start groups (*e.g.*, group $[0, 20)$), but their performance is weaker compared to generative models in




Figure 4: Performance comparison w.r.t. long-tail items.

popular groups (*e.g.*, group $[40, 60)$). In contrast, UTGRec consistently surpasses the baseline models across all groups, especially in less popular groups. This shows significant advantages of our transferable approach on long-tail items.

4 Related Work

In this section, we review related work from three aspects, sequential recommendation, generative recommendation and transfer learning for recommendation.

Sequential Recommendation. Sequential recommendation aims to predict the next potential item by capturing user’s personalized preferences in his/her sequential behaviors. Early studies [7, 30] follow the Markov chain assumption and learn the transformation matrix between the items. With the rapid development of deep learning, recent works typically leverage various deep neural networks to capture the sequential patterns of item ID sequence, including convolutional neural network (CNN) [37], recurrent neural network (RNN) [8, 36], graph neural network (GNN) [47, 51], multilayer perceptron (MLP) [59] and Transformer [15, 34]. Furthermore, several studies introduce item attributes [55, 58] or self-supervised signals [25, 50, 58] to enhance the sequence modeling. However, these methods are mainly developed based on item IDs, which results in item embeddings and model parameters being domain-specific.

Generative Recommendation. Generative recommendation [29] is a promising paradigm that reformulates the next-item prediction task as a sequence-to-sequence problem. In this paradigm, each item is tokenized into an identifier composed of multiple codes, and then a generative model is employed to autoregressively generate the target item identifier. Existing approaches for item tokenization can be roughly categorized into three groups: heuristic methods, cluster-based methods, and codebook-based methods. Heuristic methods primarily rely on manually defined rules, such as time order [5] and item category [14], to generate item identifiers. Cluster-based methods group items based on their embeddings [32, 45] or the co-occurrence matrix [14, 24] to assign item identifiers. Codebook-based methods [4, 18, 21, 26, 29, 42, 44] adopt learnable codebooks to quantize item semantic embeddings, thereby constructing fixed-length and semantically rich item identifiers. However, these methods mainly focus on learning domain-specific item tokenizers, which limits the ability of generative recommenders to transfer across domains.

Transfer Learning for Recommendation. Transferring knowledge from other domains [49, 60, 61] is a widely adopted strategy to address data sparsity and cold-start issues in recommender systems. Traditional transfer learning methods primarily rely on shared information between the source and target domains, such as overlapping users [13, 46, 53], items [33, 60], or attributes [38]. Recently, several studies [9, 11, 40] employ pre-trained language [3, 23] or multimodal models [27] to learn universal item representation and enable transferable sequential recommendation without overlapping users or items. However, these methods are still rooted in the traditional sequential recommendation paradigm, which is implemented by measuring the similarity between the sequence representation and candidate item representations. In contrast, we introduce universal item tokenization to achieve more effective transferable recommendations within the generative recommendation paradigm.

5 Conclusion

In this paper, we proposed UTGRec, a novel framework which achieves transferable generative recommendation through universal item tokenization. Unlike previous methods that learn domain-specific tokenizers, we introduced a universal item tokenizer that employs a MLLM with tree-structured codebooks for item tokenization. To effectively train the universal item tokenizer, we presented an item content reconstruction approach with collaborative integration. The reconstruction objective uses the raw item content as the target, enabling the learning of more essential characteristics. Simultaneously, we integrated collaborative knowledge through co-occurring item alignment and reconstruction. Given the universal item tokenizer, we developed a learning framework to pre-train a transferable generative recommender. Extensive experiments on four public datasets showed that UTGRec consistently outperforms both traditional and generative recommendation baselines. For future work, we will incorporate more domains and interaction data. Additionally, we will also investigate the scaling effect of the item tokenizer and the generative recommender.

References

- [1] Yongjian Chen, Tao Guan, and Cheng Wang. 2010. Approximate Nearest Neighbor Search by Residual Vector Quantization. *Sensors* 10, 12 (2010), 11259–11273.
- [2] Hyung Won Chung, Le Hou, Shayne Longpre, Barret Zoph, Yi Tay, William Fedus, Yunxuan Li, Xuezhi Wang, Mostafa Dehghani, Siddhartha Brahma, Albert Webson, Shixiang Shane Gu, Zhuyun Dai, Mirac Suzgun, Xinyun Chen, Aakanksha Chowdhery, Alex Castro-Ros, Marie Pellat, Kevin Robinson, Dasha Valter, Sharan Narang, Gaurav Mishra, Adams Yu, Vincent Y. Zhao, Yanping Huang, Andrew M. Dai, Hongkun Yu, Slav Petrov, Ed H. Chi, Jeff Dean, Jacob Devlin, Adam Roberts, Denny Zhou, Quoc V. Le, and Jason Wei. 2024. Scaling Instruction-Finetuned Language Models. *J. Mach. Learn. Res.* 25 (2024), 70:1–70:53. <https://jmlr.org/papers/v25/23-0870.html>
- [3] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2019, Minneapolis, MN, USA, June 2-7, 2019, Volume 1 (Long and Short Papers)*. Association for Computational Linguistics, 4171–4186. <https://doi.org/10.18653/V1/N19-1423>
- [4] Yijie Ding, Yupeng Hou, Jiacheng Li, and Julian McAuley. 2024. Inductive Generative Recommendation via Retrieval-based Speculation. *arXiv preprint arXiv:2410.02939* (2024).
- [5] Shijie Geng, Shuchang Liu, Zuohui Fu, Yingqiang Ge, and Yongfeng Zhang. 2022. Recommendation as Language Processing (RLP): A Unified Pretrain, Personalized Prompt & Predict Paradigm (P5). In *RecSys '22: Sixteenth ACM Conference on Recommender Systems, Seattle, WA, USA, September 18 - 23, 2022*. ACM, 299–315. <https://doi.org/10.1145/3523227.3546767>
- [6] Michael Gutmann and Aapo Hyvärinen. 2010. Noise-contrastive estimation: A new estimation principle for unnormalized statistical models. In *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics, AISTATS 2010, Chia Laguna Resort, Sardinia, Italy, May 13-15, 2010 (JMLR Proceedings, Vol. 9)*. JMLR.org, 297–304. <http://proceedings.mlr.press/v9/gutmann10a.html>
- [7] Ruining He and Julian J. McAuley. 2016. Fusing Similarity Models with Markov Chains for Sparse Sequential Recommendation. In *IEEE 16th International Conference on Data Mining, ICDM 2016, December 12-15, 2016, Barcelona, Spain*, Francesco Bonchi, Josep Domingo-Ferrer, Ricardo Baeza-Yates, Zhi-Hua Zhou, and Xindong Wu (Eds.). IEEE Computer Society, 191–200. <https://doi.org/10.1109/ICDM.2016.0030>
- [8] Balázs Hidasi, Alexandros Karatzoglou, Linas Baltrunas, and Domonkos Tikk. 2016. Session-based Recommendations with Recurrent Neural Networks. In *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2-4, 2016, Conference Track Proceedings*, Yoshua Bengio and Yann LeCun (Eds.). <http://arxiv.org/abs/1511.06939>
- [9] Yupeng Hou, Zhankui He, Julian J. McAuley, and Wayne Xin Zhao. 2023. Learning Vector-Quantized Item Representation for Transferable Sequential Recommenders. In *Proceedings of the ACM Web Conference 2023, WWW 2023, Austin, TX, USA, 30 April 2023 - 4 May 2023*, Ying Ding, Jie Tang, Juan F. Sequeda, Lora Aroyo, Carlos Castillo, and Geert-Jan Houben (Eds.). ACM, 1162–1171. <https://doi.org/10.1145/3543507.3583434>
- [10] Yupeng Hou, Jiacheng Li, Zhankui He, An Yan, Xiusi Chen, and Julian J. McAuley. 2024. Bridging Language and Items for Retrieval and Recommendation. *CoRR abs/2403.03952* (2024). <https://doi.org/10.48550/ARXIV.2403.03952> [arXiv:2403.03952](https://arxiv.org/abs/2403.03952)
- [11] Yupeng Hou, Shanlei Mu, Wayne Xin Zhao, Yaliang Li, Bolin Ding, and Ji-Rong Wen. 2022. Towards Universal Sequence Representation Learning for Recommender Systems. In *KDD '22: The 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining, Washington, DC, USA, August 14 - 18, 2022*. ACM, 585–593. <https://doi.org/10.1145/3534678.3539381>
- [12] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. LoRA: Low-Rank Adaptation of Large Language Models. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*.
- [13] Guangmeng Hu, Yu Zhang, and Qiang Yang. 2018. CoNet: Collaborative Cross Networks for Cross-Domain Recommendation. In *Proceedings of the 27th ACM International Conference on Information and Knowledge Management, CIKM 2018, Torino, Italy, October 22-26, 2018*. ACM, 667–676. <https://doi.org/10.1145/3269206.3271684>
- [14] Wenyue Hua, Shuyuan Xu, Yingqiang Ge, and Yongfeng Zhang. 2023. How to Index Item IDs for Recommendation Foundation Models. In *Annual International ACM SIGIR Conference on Research and Development in Information Retrieval in the Asia Pacific Region, SIGIR-AP 2023, Beijing, China, November 26-28, 2023*, Qingyao Ai, Yiqin Liu, Alistair Moffat, Xuanjing Huang, Tetsuya Sakai, and Justin Zobel (Eds.). ACM, 195–204. <https://doi.org/10.1145/3624918.3625339>
- [15] Wang-Cheng Kang and Julian J. McAuley. 2018. Self-Attentive Sequential Recommendation. In *IEEE International Conference on Data Mining, ICDM 2018, Singapore, November 17-20, 2018*. IEEE Computer Society, 197–206. <https://doi.org/10.1109/ICDM.2018.00035>
- [16] Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B. Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeffrey Wu, and Dario Amodei. 2020. Scaling Laws for Neural Language Models. *CoRR abs/2001.08361* (2020). [arXiv:2001.08361](https://arxiv.org/abs/2001.08361) <https://arxiv.org/abs/2001.08361>
- [17] Doyup Lee, Chiheon Kim, Saehoon Kim, Minsu Cho, and Wook-Shin Han. 2022. Autoregressive Image Generation using Residual Quantization. In *IEEE/CVF Conference on Computer Vision and Pattern Recognition, CVPR 2022, New Orleans, LA, USA, June 18-24, 2022*. IEEE, 11513–11522. <https://doi.org/10.1109/CVPR52688.2022.01123>
- [18] Guanghan Li, Xun Zhang, Yufei Zhang, Yifan Yin, Guojun Yin, and Wei Lin. 2024. Semantic Convergence: Harmonizing Recommender Systems via Two-Stage Alignment and Behavioral Semantic Tokenization. [arXiv:2412.13771 \[cs.LG\]](https://arxiv.org/abs/2412.13771) <https://arxiv.org/abs/2412.13771>
- [19] Jiacheng Li, Ming Wang, Jin Li, Jimmiao Fu, Xin Shen, Jingbo Shang, and Julian J. McAuley. 2023. Text Is All You Need: Learning Language Representations for Sequential Recommendation. In *Proceedings of the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining, KDD 2023, Long Beach, CA, USA, August 6-10, 2023*, Ambuj K. Singh, Yizhou Sun, Leman Akoglu, Dimitrios Gunopoulos, Xifeng Yan, Ravi Kumar, Fatma Ozcan, and Jieping Ye (Eds.). ACM, 1258–1267. <https://doi.org/10.1145/3580305.3599519>
- [20] Tianhong Li, Yonglong Tian, He Li, Mingyang Deng, and Kaiming He. 2024. Autoregressive Image Generation without Vector Quantization. *CoRR abs/2406.11838* (2024). <https://doi.org/10.48550/ARXIV.2406.11838> [arXiv:2406.11838](https://arxiv.org/abs/2406.11838)
- [21] Enze Liu, Bowen Zheng, Cheng Ling, Lantao Hu, Han Li, and Wayne Xin Zhao. 2024. End-to-End Learnable Item Tokenization for Generative Recommendation. *CoRR abs/2409.05546* (2024). <https://doi.org/10.48550/ARXIV.2409.05546> [arXiv:2409.05546](https://arxiv.org/abs/2409.05546)

- [22] Zihan Liu, Yupeng Hou, and Julian J. McAuley. 2024. Multi-Behavior Generative Recommendation. In *Proceedings of the 33rd ACM International Conference on Information and Knowledge Management, CIKM 2024, Boise, ID, USA, October 21–25, 2024*, Edoardo Serra and Francesca Spezzano (Eds.). ACM, 1575–1585. <https://doi.org/10.1145/3627673.3679730>
- [23] Jianmo Ni, Gustavo Hernández Ábrego, Noah Constant, Ji Ma, Keith B. Hall, Daniel Cer, and Yinfei Yang. 2022. Sentence-T5: Scalable Sentence Encoders from Pre-trained Text-to-Text Models. In *Findings of the Association for Computational Linguistics: ACL 2022, Dublin, Ireland, May 22–27, 2022*. Association for Computational Linguistics, 1864–1874. <https://doi.org/10.18653/V1/2022.FINDINGS-ACL.146>
- [24] Aleksandr V. Petrov and Craig Macdonald. 2023. Generative Sequential Recommendation with GPTRec. *CoRR abs/2306.11114 (2023)*. <https://doi.org/10.48550/ARXIV.2306.11114> arXiv:2306.11114
- [25] Ruihong Qiu, Zi Huang, Hongzhi Yin, and Zijian Wang. 2022. Contrastive Learning for Representation Degeneration Problem in Sequential Recommendation. In *WSDM '22: The Fifteenth ACM International Conference on Web Search and Data Mining, Virtual Event / Tempe, AZ, USA, February 21 – 25, 2022*, K. Selcuk Candan, Huan Liu, Leman Akoglu, Xin Luna Dong, and Jiliang Tang (Eds.). ACM, 813–823. <https://doi.org/10.1145/3488560.3498433>
- [26] Haohao Qu, Wenqi Fan, Zihuai Zhao, and Qing Li. 2024. TokenRec: Learning to Tokenize ID for LLM-based Generative Recommendation. *CoRR abs/2406.10450 (2024)*. <https://doi.org/10.48550/ARXIV.2406.10450> arXiv:2406.10450
- [27] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. 2021. Learning Transferable Visual Models From Natural Language Supervision. In *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18–24 July 2021, Virtual Event (Proceedings of Machine Learning Research, Vol. 139)*. PMLR, 8748–8763. <http://proceedings.mlr.press/v139/radford21a.html>
- [28] Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020. Exploring the Limits of Transfer Learning with a Unified Text-to-Text Transformer. *J. Mach. Learn. Res.* 21 (2020), 140:1–140:67. <http://jmlr.org/papers/v21/20-074.html>
- [29] Shashank Rajput, Nikhil Mehta, Anima Singh, Raghunandan Hulikal Keshavan, Trung Vu, Lukasz Heldt, Lichan Hong, Yi Tay, Vinh Q. Tran, Jonah Samost, Maciej Kula, Ed H. Chi, and Mahesh Sathiamoorthy. 2023. Recommender Systems with Generative Retrieval. In *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 – 16, 2023*. http://papers.nips.cc/paper_files/paper/2023/hash/20dcab0f14046a5c6b02b61da9f13229-Abstract-Conference.html
- [30] Steffen Rendle, Christoph Freudenthaler, and Lars Schmidt-Thieme. 2010. Factorizing personalized Markov chains for next-basket recommendation. In *Proceedings of the 19th International Conference on World Wide Web, WWW 2010, Raleigh, North Carolina, USA, April 26–30, 2010*, Michael Rappa, Paul Jones, Juliana Freire, and Soumen Chakrabarti (Eds.). ACM, 811–820. <https://doi.org/10.1145/1772690.1772773>
- [31] Aurko Roy, Ashish Vaswani, Arvind Neelakantan, and Niki Parmar. 2018. Theory and Experiments on Vector Quantized Autoencoders. *CoRR abs/1805.11063 (2018)*. arXiv:1805.11063 <http://arxiv.org/abs/1805.11063>
- [32] Zihua Si, Zhongxiang Sun, Jiale Chen, Guozhang Chen, Xiaoxue Zang, Kai Zheng, Yang Song, Xiao Zhang, and Jun Xu. 2023. Generative Retrieval with Semantic Tree-Structured Item Identifiers via Contrastive Learning. *CoRR abs/2309.13375 (2023)*. <https://doi.org/10.48550/ARXIV.2309.13375> arXiv:2309.13375
- [33] Ajit Paul Singh and Geoffrey J. Gordon. 2008. Relational learning via collective matrix factorization. In *Proceedings of the 14th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, Las Vegas, Nevada, USA, August 24–27, 2008*. ACM, 650–658. <https://doi.org/10.1145/1401890.1401969>
- [34] Fei Sun, Jun Liu, Jian Wu, Changhua Pei, Xiao Lin, Wenwu Ou, and Peng Jiang. 2019. BERT4Rec: Sequential Recommendation with Bidirectional Encoder Representations from Transformer. In *Proceedings of the 28th ACM International Conference on Information and Knowledge Management, CIKM 2019, Beijing, China, November 3–7, 2019*, Wenwu Zhu, Dacheng Tao, Xueqi Cheng, Peng Cui, Elke A. Rundensteiner, David Carmel, Qi He, and Jeffrey Xu Yu (Eds.). ACM, 1441–1450. <https://doi.org/10.1145/3357384.3357895>
- [35] Weiwei Sun, Lingyong Yan, Zheng Chen, Shuaiqiang Wang, Haichao Zhu, Pengjie Ren, Zhumin Chen, Dawei Yin, Maarten de Rijke, and Zhaochun Ren. 2023. Learning to Tokenize for Generative Retrieval. In *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 – 16, 2023*, Alice Oh, Tristan Naumann, Amir Globerson, Kate Saenko, Moritz Hardt, and Sergey Levine (Eds.). http://papers.nips.cc/paper_files/paper/2023/hash/91228b942a4528cdae031c1b68b127e8-Abstract-Conference.html
- [36] Yong Kiam Tan, Xinxing Xu, and Yong Liu. 2016. Improved Recurrent Neural Networks for Session-based Recommendations. In *Proceedings of the 1st Workshop on Deep Learning for Recommender Systems, DLRS@RecSys 2016, Boston, MA, USA, September 15, 2016*. ACM, 17–22. <https://doi.org/10.1145/2988450.2988452>
- [37] Jiayi Tang and Ke Wang. 2018. Personalized Top-N Sequential Recommendation via Convolutional Sequence Embedding. In *Proceedings of the Eleventh ACM International Conference on Web Search and Data Mining, WSDM 2018, Marina Del Rey, CA, USA, February 5–9, 2018*, Yi Chang, Chengxiang Zhai, Yan Liu, and Yoelle Maarek (Eds.). ACM, 565–573. <https://doi.org/10.1145/3159652.3159656>
- [38] Jie Tang, Sen Wu, Jimeng Sun, and Hang Su. 2012. Cross-domain collaboration recommendation. In *The 18th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, KDD '12, Beijing, China, August 12–16, 2012*. ACM, 1285–1293. <https://doi.org/10.1145/2339530.2339730>
- [39] Yi Tay, Vinh Tran, Mostafa Dehghani, Jianmo Ni, Dara Bahri, Harsh Mehta, Zhen Qin, Kai Hui, Zhe Zhao, Jai Prakash Gupta, Tal Schuster, William W. Cohen, and Donald Metzler. 2022. Transformer Memory as a Differentiable Search Index. In *Advances in Neural Information Processing Systems 35: Annual Conference on Neural Information Processing Systems 2022, NeurIPS 2022, New Orleans, LA, USA, November 28 – December 9, 2022*, Sanmi Koyejo, S. Mohamed, A. Agarwal, Danielle Belgrave, K. Cho, and A. Oh (Eds.). http://papers.nips.cc/paper_files/paper/2022/hash/892840a6123b5ec99ebaab8be1530fba-Abstract-Conference.html
- [40] Jinpeng Wang, Ziyun Zeng, Yunxiao Wang, Yuting Wang, Xingyu Lu, Tianxiang Li, Jun Yuan, Rui Zhang, Hai-Tao Zheng, and Shu-Tao Xia. 2023. MISSRec: Pre-training and Transferring Multi-modal Interest-aware Sequence Representation for Recommendation. In *Proceedings of the 31st ACM International Conference on Multimedia, MM 2023, Ottawa, ON, Canada, 29 October 2023– 3 November 2023*, Abdulmotaleb El-Saddik, Tao Mei, Rita Cucchiara, Marco Bertini, Diana Patricia Tobon Vallejo, Pradeep K. Atrey, and M. Shammim Hossain (Eds.). ACM, 6548–6557. <https://doi.org/10.1145/3581783.3611967>
- [41] Peng Wang, Shuai Bai, Sinan Tan, Shijie Wang, Zhihao Fan, Jinze Bai, Keqin Chen, Xuejing Liu, Jialin Wang, Wenbin Ge, Yang Fan, Kai Dang, Mengfei Du, Xuancheng Ren, Rui Men, Dayiheng Liu, Chang Zhou, Jingren Zhou, and Junyang Lin. 2024. Qwen2-VL: Enhancing Vision-Language Model's Perception of the World at Any Resolution. *CoRR abs/2409.12191 (2024)*. <https://doi.org/10.48550/ARXIV.2409.12191> arXiv:2409.12191
- [42] Wenjie Wang, Honghui Bao, Xinyu Li, Zihzi Zhang, Yongqi Li, Fuli Feng, Seekiong Ng, and Tat-Seng Chua. 2024. Learned Item Tokenization for Generative Recommendation. In *International Conference on Information and Knowledge Management*.
- [43] Yujing Wang, Yingyan Hou, Haonan Wang, Ziming Miao, Shibin Wu, Qi Chen, Yuqing Xia, Chengmin Chi, Guoshuai Zhao, Zheng Liu, Xing Xie, Hao Sun, Weiwei Deng, Qi Zhang, and Mao Yang. 2022. A Neural Corpus Indexer for Document Retrieval. In *Advances in Neural Information Processing Systems 35: Annual Conference on Neural Information Processing Systems 2022, NeurIPS 2022, New Orleans, LA, USA, November 28 – December 9, 2022*, Sanmi Koyejo, S. Mohamed, A. Agarwal, Danielle Belgrave, K. Cho, and A. Oh (Eds.). http://papers.nips.cc/paper_files/paper/2022/hash/a46156bd3579c3b268108ea6aca71d13-Abstract-Conference.html
- [44] Yidan Wang, Zhaochun Ren, Weiwei Sun, Jiyuan Sun, Zhixiang Liang, Xin Chen, Ruobing Xie, Su Yan, Xu Zhang, Pengjie Ren, Zhumin Chen, and Xin Xin. 2024. Enhanced Generative Recommendation via Content and Collaboration Integration. *CoRR abs/2403.18480 (2024)*. <https://doi.org/10.48550/ARXIV.2403.18480> arXiv:2403.18480
- [45] Ye Wang, Jiahao Xun, Mingjie Hong, Jieming Zhu, Tao Jin, Wang Lin, Haoyuan Li, Linjun Li, Yan Xia, Zhou Zhao, and Zhenhua Dong. 2024. EAGER: Two-Stream Generative Recommender with Behavior-Semantic Collaboration. *CoRR abs/2406.14017 (2024)*. <https://doi.org/10.48550/ARXIV.2406.14017> arXiv:2406.14017
- [46] Chuhan Wu, Fangzhao Wu, Tao Qi, Jianxun Lian, Yongfeng Huang, and Xing Xie. 2020. PTUM: Pre-training User Model from Unlabeled User Behaviors via Self-supervision. In *Findings of the Association for Computational Linguistics: EMNLP 2020, Online Event, 16–20 November 2020 (Findings of ACL, Vol. EMNLP 2020)*. Association for Computational Linguistics, 1939–1944. <https://doi.org/10.18653/V1/2020.FINDINGS-EMNLP.174>
- [47] Shu Wu, Yuyuan Tang, Yanqiao Zhu, Liang Wang, Xing Xie, and Tieniu Tan. 2019. Session-Based Recommendation with Graph Neural Networks. In *The Thirty-Third AAAI Conference on Artificial Intelligence, AAAI 2019, The Thirty-First Innovative Applications of Artificial Intelligence Conference, IAAI 2019, The Ninth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2019, Honolulu, Hawaii, USA, January 27 – February 1, 2019*. AAAI Press, 346–353. <https://doi.org/10.1609/AAAI.V33I01.3301346>
- [48] Shitao Xiao, Zheng Liu, Yingxia Shao, and Zhao Cao. 2022. RetroMAE: Pre-Training Retrieval-oriented Language Models Via Masked Auto-Encoder. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing, EMNLP 2022, Abu Dhabi, United Arab Emirates, December 7–11, 2022*. Association for Computational Linguistics, 538–548. <https://doi.org/10.18653/V1/2022.EMNLP-MAIN.35>
- [49] Ruobing Xie, Qi Liu, Liangdong Wang, Shukai Liu, Bo Zhang, and Leyu Lin. 2022. Contrastive Cross-domain Recommendation in Matching. In *KDD '22: The 28th ACM SIGKDD Conference on Knowledge Discovery and Data Mining, Washington, DC, USA, August 14 – 18, 2022*. ACM, 4226–4236. <https://doi.org/10.1145/3534678.3539125>

- [50] Xu Xie, Fei Sun, Zhaoyang Liu, Shiwen Wu, Jinyang Gao, Jiandong Zhang, Bolin Ding, and Bin Cui. 2022. Contrastive Learning for Sequential Recommendation. In *38th IEEE International Conference on Data Engineering, ICDE 2022, Kuala Lumpur, Malaysia, May 9-12, 2022*. IEEE, 1259–1273. <https://doi.org/10.1109/ICDE53745.2022.00099>
- [51] Chengfeng Xu, Pengpeng Zhao, Yanchi Liu, Victor S. Sheng, Jiajie Xu, Fuzhen Zhuang, Junhua Fang, and Xiaofang Zhou. 2019. Graph Contextualized Self-Attention Network for Session-based Recommendation. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI 2019, Macao, China, August 10-16, 2019*. ijcai.org, 3940–3946. <https://doi.org/10.24963/IJCAI.2019/547>
- [52] Tianchi Yang, Minghui Song, Zihan Zhang, Haizhen Huang, Weiwei Deng, Feng Sun, and Qi Zhang. 2023. Auto Search Indexer for End-to-End Document Retrieval. In *Findings of the Association for Computational Linguistics: EMNLP 2023, Singapore, December 6-10, 2023*, Houda Bouamor, Juan Pino, and Kalika Bali (Eds.). Association for Computational Linguistics, 6955–6970. <https://doi.org/10.18653/V1/2023.FINDINGS-EMNLP.464>
- [53] Fajie Yuan, Guoxiao Zhang, Alexandros Karatzoglou, Joemon M. Jose, Beibei Kong, and Yudong Li. 2021. One Person, One Model, One World: Learning Continual User Representation without Forgetting. In *SIGIR '21: The 44th International ACM SIGIR Conference on Research and Development in Information Retrieval, Virtual Event, Canada, July 11-15, 2021*. ACM, 696–705. <https://doi.org/10.1145/3404835.3462884>
- [54] Neil Zeghidour, Alejandro Luebs, Ahmed Omran, Jan Skoglund, and Marco Tagliasacchi. 2022. SoundStream: An End-to-End Neural Audio Codec. *IEEE ACM Trans. Audio Speech Lang. Process.* 30 (2022), 495–507. <https://doi.org/10.1109/TASLP.2021.3129994>
- [55] Tingting Zhang, Pengpeng Zhao, Yanchi Liu, Victor S. Sheng, Jiajie Xu, Deqing Wang, Guanfeng Liu, and Xiaofang Zhou. 2019. Feature-level Deeper Self-Attention Network for Sequential Recommendation. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI 2019, Macao, China, August 10-16, 2019*, Sarit Kraus (Ed.). ijcai.org, 4320–4326. <https://doi.org/10.24963/IJCAI.2019/600>
- [56] Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang, Xiaolei Wang, Yupeng Hou, Yingqian Min, Beichen Zhang, Junjie Zhang, Zican Dong, Yifan Du, Chen Yang, Yushuo Chen, Zhipeng Chen, Jinhao Jiang, Ruiyang Ren, Yifan Li, Xinyu Tang, Zikang Liu, Peiyu Liu, Jian-Yun Nie, and Ji-Rong Wen. 2023. A Survey of Large Language Models. *CoRR* abs/2303.18223 (2023). <https://doi.org/10.48550/ARXIV.2303.18223> arXiv:2303.18223
- [57] Bowen Zheng, Yupeng Hou, Hongyu Lu, Yu Chen, Wayne Xin Zhao, Ming Chen, and Ji-Rong Wen. 2024. Adapting Large Language Models by Integrating Collaborative Semantics for Recommendation. In *40th IEEE International Conference on Data Engineering, ICDE 2024, Utrecht, The Netherlands, May 13-16, 2024*. IEEE, 1435–1448. <https://doi.org/10.1109/ICDE60146.2024.00118>
- [58] Kun Zhou, Hui Wang, Wayne Xin Zhao, Yutao Zhu, Sirui Wang, Fuzheng Zhang, Zhongyuan Wang, and Ji-Rong Wen. 2020. S3-Rec: Self-Supervised Learning for Sequential Recommendation with Mutual Information Maximization. In *CIKM '20: The 29th ACM International Conference on Information and Knowledge Management, Virtual Event, Ireland, October 19-23, 2020*, Mathieu d'Aquin, Stefan Dietze, Claudia Hauff, Edward Curry, and Philippe Cudré-Mauroux (Eds.). ACM, 1893–1902. <https://doi.org/10.1145/3340531.3411954>
- [59] Kun Zhou, Hui Yu, Wayne Xin Zhao, and Ji-Rong Wen. 2022. Filter-enhanced MLP is All You Need for Sequential Recommendation. In *WWW '22: The ACM Web Conference 2022, Virtual Event, Lyon, France, April 25 - 29, 2022*, Frédérique Laforest, Raphaël Troncy, Elena Simperl, Deepak Agarwal, Aristides Gionis, Ivan Herman, and Lionel Médini (Eds.). ACM, 2388–2399. <https://doi.org/10.1145/3485447.3512111>
- [60] Feng Zhu, Chaochao Chen, Yan Wang, Guanfeng Liu, and Xiaolin Zheng. 2019. DTCDR: A Framework for Dual-Target Cross-Domain Recommendation. In *Proceedings of the 28th ACM International Conference on Information and Knowledge Management, CIKM 2019, Beijing, China, November 3-7, 2019*. ACM, 1533–1542. <https://doi.org/10.1145/3357384.3357992>
- [61] Feng Zhu, Yan Wang, Chaochao Chen, Jun Zhou, Longfei Li, and Guanfeng Liu. 2021. Cross-Domain Recommendation: Challenges, Progress, and Prospects. In *Proceedings of the Thirtieth International Joint Conference on Artificial Intelligence, IJCAI 2021, Virtual Event / Montreal, Canada, 19-27 August 2021*. ijcai.org, 4721–4728. <https://doi.org/10.24963/IJCAI.2021/639>
- [62] Yongxin Zhu, Bocheng Li, Yifei Xin, and Linli Xu. 2024. Addressing Representation Collapse in Vector Quantized Models with One Linear Layer. *CoRR* abs/2411.02038 (2024). <https://doi.org/10.48550/ARXIV.2411.02038> arXiv:2411.02038