STRIVE: A Think & Improve Approach with Iterative Refinement for Enhancing Question Quality Estimation

Aniket Deroy* IIT Kharagpur West Bengal, India roydanik18@kgpian.iitkgp.ac.in

Abstract

Automatically assessing question quality is crucial for educators as it saves time, ensures consistency, and provides immediate feedback for refining teaching materials. We propose a novel methodology called STRIVE (Structured Thinking and Refinement with multi-LLMs for Improving Verified Question Estimation) using a series of Large Language Models (LLMs) for automatic question evaluation. This approach aims to improve the accuracy and depth of question quality assessment, ultimately supporting diverse learners and enhancing educational practices. The method estimates question quality in an automated manner by generating multiple evaluations based on the strengths and weaknesses of the provided question and then choosing the best solution generated by the LLM. Then the process is improved by iterative review and response with another LLM until the evaluation metric values converge. This sophisticated method of evaluating question quality improves the estimation of question quality by automating the task of question quality evaluation. Correlation scores show that using this proposed method helps to improve correlation with human judgments compared to the baseline method. Error analysis shows that metrics like relevance and appropriateness improve significantly relative to human judgments by using STRIVE.

CCS Concepts

 Computing methodologies → Natural language generation; • Applied computing \rightarrow Education.

Keywords

Education, Large Language Models (LLMs), Question Generation, Automated Question Assessment, Feedback, GPT

ACM Reference Format:

Aniket Derov and Subhankar Maity, 2025, STRIVE: A Think & Improve Approach with Iterative Refinement for Enhancing Question Quality Estimation. In . ACM, New York, NY, USA, 5 pages. https://doi.org/10.1145/ nnnnnnn.nnnnnnn

Conference'17, July 2017, Washington, DC, USA

© 2025 Copyright held by the owner/author(s). Publication rights licensed to ACM. ACM ISBN 978-x-xxxx-x/YY/MM

https://doi.org/10.1145/nnnnnnnnnnnn

Subhankar Maity IIT Kharagpur West Bengal, India subhankar.ai@kgpian.iitkgp.ac.in

1 Introduction

Automatically assessing question quality [7, 8, 20] is significant for educators for several reasons. First, it saves time, allowing educators to focus on teaching rather than question formulation [24]. Second, automated systems provide a standardized measure of question quality [17, 27], reducing subjectivity and bias in evaluations. In addition, educators can receive immediate feedback on the effectiveness of their created questions [5, 20], allowing the continuous refinement of the teaching materials. Information retrieval via questions [3, 9, 30] empowers learners to engage with knowledge more interactively and effectively. Integrating question-driven information retrieval into education can foster curiosity, critical thinking, and tailored learning experiences, creating a dynamic and accessible educational ecosystem. Here, the task is to automatically assess metrics such as grammaticality (i.e., Gram), relevance (i.e., Rel), appropriateness (i.e., App), complexity (i.e., Com), and novelty (i.e., Nov) in questions generated from educational materials [16]. Moreover, analyzing question quality can help educators identify gaps in curriculum coverage or areas where students may struggle, leading to more targeted instruction. We know that human evaluations of questions are costly. So we ask the question, Whether a novel method comprising of LLMs can replace human evaluations in terms of assessing educational question quality?

In this work, our contributions are as follows: (i) We propose a novel method called STRIVE that leverages the capabilities of LLMs to generate multiple evaluations based on each question's inherent strengths and weaknesses within the context of the question generation task. STRIVE identifies the most effective question assessment by assessing these evaluations, thus enhancing the quality of educational assessments. Furthermore, the method incorporates an iterative review process, utilizing two Think and Improve modules (TM) comprising LLMs to refine the evaluations until the results align between the two Think and Improve modules. (ii) We compare our baseline method with our proposed approach, STRIVE, and show that our approach achieves scores closer to the human baseline. The correlation scores [2, 23] show that our proposed approach STRIVE aligns better with human experts. The error analysis [1, 4, 13, 25] shows relevance and appropriateness is considerably improved using our proposed approach STRIVE.

2 Dataset

We used 1000 <Context, Question> pairs from the EduProbe [16] dataset for the purpose of our study. The dataset comprises of subjects like History, Geography, Environmental Studies, and Economics from 6th standard to 12th standard according to NCERT curriculum. We pick up 1000 contexts from the SciQ dataset [28]

^{*}Corresponding Author

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

and create 1000 <Context, Question> pairs from Chemistry, Biology, Physics, Earth Sciences, etc. We hired an educator to create question from every context. We use these <Context, Question> pairs for our study. The context and open-ended questions are used for the purpose of evaluations via the LLMs. To show the wider applicability of our work, we test our proposed approach STRIVE on two different datasets namely EduProbe and SciQ covering a wide range of subjects like History, Geography, Environmental Studies, Economics, Chemistry, Biology, Physics, Earth Sciences, etc.

3 Methodology

3.1 Baseline Approach

The methodology for the baseline approach is shown in Figure 4. The corresponding prompt for baseline approach is shown in Figure 1. The algorithm for baseline approach is shown in Algorithm 1.

Algorithm 1 Automated Question Quality Evaluation Using Baseline Approach

Require: Human Evaluation Metric definitions **Require:** Question and its context

Ensure: Human evaluation metric scores for the question

1: Provide Human evaluation metric definitions, context, question as input to LLM

return Final Human evaluation metric scores

3.2 STRIVE Approach

We first discuss the *Think and Improve* modules (i.e., TM_1 and TM_2) present in the STRIVE approach¹. There are two steps in the *Think and Improve* module: (a) In the first step, we generate multiple strengths and flaws for the question. We generate 10 different <strength, weakness> pairs for every question at different temperature values. (b) In the second step, we ask the LLM to choose the best set of strength from the available set of all strengths generated by the LLM in the previous step. We follow a similar methodology for selecting the weaknesses, we also calculate the metric scores corresponding to the evaluation metrics.

Figure 6 represents the overview for *Think and Improve* module for generating multiple strength and weakness pairs and then choosing the best strength and weakness pair from the set. Figure 2 shows the *Promptgen* used in Figure 6 to generate strength and weakness pairs from context and question. Figure 3 represents *Prompt_{judge}*, also used in Figure 6. The prompt in Figure 3 helps select the best strength and weakness pair from all available pairs and provides the evaluation metric scores.

The algorithm 2 outlines an iterative process for evaluating human evaluation metrics using two *Think and Improve* modules consisting of LLMs, referred to as TM_1 and TM_2 (See Figure 5). It begins by requiring definitions for the human evaluation metrics and initializing two empty sets: S_0 for strengths and F_0 for flaws. The algorithm takes a specific question and its context as input.

Algorithm 2 Automated Question Quality Evaluation Using STRIVE Approach

Require: Human Evaluation Metric definitions

Require: Initial strengths set S_0 and flaws set F_0 , both initialized as empty sets

Require: Question and its context

Ensure: Converged scores for the question

- 2: $F_0 \leftarrow \{\}$
- 3: $S_0, F_0 \leftarrow$ Identify 10 sets of strengths and flaws
- 4: $S_0, F_0 \leftarrow$ Use LLM as a judge to choose the best strength and flaw
- 5: Compute initial scores for human evaluation metrics with the given question and context
- 6: while convergence criteria are not met do
- 7: Provide S_0, F_0 as feedback, along with metric definitions, question, and context, to TM_2
- 8: $S_1 \leftarrow$ Generate 10 variations of Strengths
 - $F_1 \leftarrow \text{Generate 10 variations of Flaws}$

Select best strength and flaw

- 10: $S_1 \leftarrow$ Select best strength from S_1
- 11: $F_1 \leftarrow \text{Select best flaw from } F_1$
 - Generate scores for metrics by TM_2

12:

9:

13: Provide S_1 , F_1 as feedback, along with metric definitions, question, and context, to TM_1

▷ Generate variations of strengths and flaws from TM_1

- 14: $S_2 \leftarrow$ Generate 10 variations of Strength
- 15: $F_2 \leftarrow$ Generate 10 variations of Flaws
- ▷ Select best strength and flaw from TM_1
- 16: $S_2 \leftarrow$ Select best strength from S_2
- 17: $F_2 \leftarrow$ Select best flaw from F_2
- 18: Ask TM_1 to generate scores for human evaluation metrics
- 19: $S_0 \leftarrow S_2$
- 20: $F_0 \leftarrow F_2$

▶ Check for convergence

- 21: **if** scores from TM_1 and TM_2 are identical for two consecutive iterations **then**
- 22: Terminate the loop

23: end if

- 24: end while
 - return final scores and strengths/flaws

Initially, it computes initial strengths S_0 and flaws F_0 consisting of 10 pairs of strengths and flaws via LLMs and then again uses the LLM as a judge to decide the most suitable strength and flaw from all the possible strengths and flaws. Then the human metric scores corresponding to the question and context is calculated. TM_1 takes into consideration this entire evaluation process. During each iteration, the identified best strength and flaw are provided as feedback from TM_1 to TM_2 , along with the metric definitions, question, and context. TM_2 then generates ten variations of the strengths and flaws. From these variations, the LLM selects the best strength and the best flaw. TM_2 also calculates the scores for the evaluation metrics. TM_2 sends the best strength and flaw to TM_1 . The process iteratively continues until the evaluation metric scores

¹The phrases '**STRIVE Approach**' and '**Feedback-based Approach**' are used interchangeably in this section and subsequent sections.

^{1:} $S_0 \leftarrow \{\}$

STRIVE: A Think & Improve Approach with Iterative Refinement for Enhancing Question Quality Estimation

Conference'17, July 2017, Washington, DC, USA

generated by TM_1 and TM_2 are exactly same for all the evaluation metrics for two consecutive iterations. Figure 5 shows the figure for the iterative approach for the STRIVE algorithm via two *Think and Improve* modules. The iterative process continues until the evaluation metric scores converge between the two modules for two subsequent runs.



Figure 1: Prompt for evaluating metrics as per baseline method.



Figure 2: Prompt for generating multiple strength and weakness pairs in *Think and Improve* module.



Figure 3: Prompt for choosing the best strength and weakness pairs in the *Think and Improve* module and generating metric scores.



Figure 4: Overview of the Baseline Approach.



Figure 5: Overview of the STRIVE Approach.



Figure 6: Overview of the Think & Improve Module (i.e., TM).

Table 1: Model performance metrics for the EduProbe dataset. Values in <u>blue</u> represent the highest value for each metric and approach.

Model	Gram	App	Rel	Nov	Com		
Human Baseline	4.86	4.87	4.53	3.75	3.23		
EduProbe (Baseline Approach)							
GPT-4	4.71	4.67	4.18	3.56	3.12		
Gemini-Pro	4.58	4.61	4.12	3.48	3.03		
Llama3	4.48	4.34	3.89	3.34	3.07		
EduProbe (Feedback-based Approach)							
GPT-4	4.82	4.81	4.37	3.65	3.20		
Gemini-Pro	4.62	4.67	4.21	3.63	3.08		
Llama3	4.57	4.52	4.12	3.40	3.10		

4 Results

Table 1 shows model performance metrics for the EduProbe dataset. Table 2 shows model performance metrics for the SciQ dataset. Human baseline scores are the highest across all metrics, indicating that human evaluators provide the most grammatically accurate (i.e., Gram), appropriate (i.e., App), relevant (i.e., Rel), novel (i.e., Nov), and complex (i.e., Com) responses. GPT-4 shows competitive performance, but generally falls short of the human baseline, particularly in novelty for the baseline approach. Gemini-Pro scores lower than GPT-4. Llama3 scores lowest in all metrics within this approach, indicating less effective performance compared to the other models for the baseline approach.

For the feedback-based approach, GPT-4 scores improve compared to the baseline approach, especially in relevance and appropriateness, demonstrating the effectiveness of feedback in improving model performance. Gemini-Pro also shows improved scores in the Table 2: Model performance metrics for the SciQ dataset. Values in blue represent the highest value for each metric and approach.

Model	Gram	App	Rel	Nov	Com		
Human Baseline	4.84	4.74	4.25	3.80	4.09		
SciQ (Baseline Approach)							
GPT-4	4.24	4.52	4.14	3.54	3.53		
Gemini-Pro	4.22	4.44	4.12	3.50	3.24		
Llama3	4.03	4.21	3.85	3.45	3.19		
SciQ (Feedback-based Approach)							
GPT-4	4.60	4.71	4.23	3.65	3.81		
Gemini-Pro	4.42	4.51	4.22	3.60	3.65		
Llama3	4.34	4.42	4.03	3.54	3.71		

Table 3: Pearson correlation coefficient between GPT-4 generated scores and human experts. Values in <u>blue</u> represent the highest value for each metric and dataset.

Model	Gram	App	Rel	Nov	Com
EduProbe					
GPT-4 (Baseline Approach)	0.38	0.41	0.26	0.28	0.29
GPT-4 (Feedback-based Approach)	0.44	0.62	0.42	0.63	0.56
SciQ					
GPT-4 (Baseline Approach)	0.33	0.41	0.28	0.29	0.28
GPT-4 (Feedback-based Approach)	0.61	0.56	0.47	0.51	0.45

STRIVE approach, particularly in relevance and appropriateness, although it still does not match GPT-4. Llama3 shows slight improvements, but still trails behind the other LLMs. Our proposed approach, STRIVE seems to enhance performance, especially for GPT-4. For the SciQ dataset, the human baseline performs relatively well across all metrics, with the highest score in grammaticality and the lowest in novelty. For SciQ, GPT-4 shows moderate performance with a high score in grammaticality but lower scores in novelty and complexity for the baseline approach. Gemini-Pro has similar trends, with a strong appropriateness score but lower novelty and complexity. Llama3 consistently scores the lowest among the baseline models, particularly in novelty and complexity. For the feedbackbased approach, the performance generally improves across all metrics compared to the baseline approach. GPT-4 achieves higher scores in all human evaluation metrics than in the baseline approach. Gemini-Pro also improves, especially in grammaticality and relevance. Llama3 performance improves compared to the baseline approach.

Table 3 shows the Pearson correlation coefficient scores between GPT-4 and human experts. We hired 16 human experts who are experienced educators from the UpWork platform and distributed all the questions among the 16 human experts so that they could provide a human evaluation score for every question. For the EduProbe dataset, GPT-4 (Baseline Approach) shows relatively low correlation values, with the highest being for appropriateness and the lowest being for relevance. GPT-4 (Feedback-based Approach) shows improved correlations in all metrics. For SciQ, we observed a similar trend with the STRIVE approach (i.e., feedback-based approach) outperforming the baseline approach for all the correlation values

across all the metrics. In summary, these correlation values highlight the effectiveness of our proposed feedback-based approach in improving performance in different metrics.

5 Error Analysis

We selected 100 questions from the SciQ dataset and 100 questions from the EduProbe dataset. We checked what percentage of values predicted by human experts which match exactly with the LLM-generated values for the different metrics. Table 4 shows the

Table 4: Percentage of score matches between LLM and human experts. Values in blue represent the highest value for each metric.

Model	Gram	App	Rel	Nov	Com
GPT-4 (Baseline Approach)	60.5	45.0	40.5	50.5	48.0
GPT-4 (Feedback-based Approach)	74.5	71.0	63.0	61.0	68.5
Gemini Pro (Baseline Approach)	55.0	40.5	35.0	42.5	44.0
Gemini Pro (Feedback-based Approach)	70.0	69.0	61.5	55.5	62.0
Llama3 (Baseline Approach)	50.5	35.5	32.0	38.5	36.5
Llama3 (Feedback-based Approach)	68.5	60.5	54.0	48.5	50.0

percentage of score matches between LLM and human experts. We observe that several exact matches in scores between the LLMprovided scores and human experts improve in the case of the feedback-based approach as compared to the baseline approach for three LLMs namely, GPT-4, Gemini pro, and Llama3. The highest match between human experts and LLM is observed in grammaticality and appropriateness. The lowest match is observed for novelty between LLM and human experts. We observe that the percentage matches between GPT-4 (Feedback-based Approach) and human experts improve significantly for appropriateness and relevance.

6 Related Work

Evaluating questions [26] is a time-consuming and critical task given the reasoning that evaluating the questions [6, 22, 29, 30] automatically is challenging. Various aspects of question quality [15] like grammaticality, relevance, novelty, complexity, and appropriateness need to be measured, which is difficult to do manually. Automated metrics often fail to capture nuanced aspects [10, 19] of what makes a question "good" (e.g., relevance, clarity, or cognitive challenge). Automated metrics like BLEU and ROUGE rely on n-gram overlaps and ignore semantic quality or rephrasing. They do not account for the appropriateness or answerability of the question [11, 12] within the given context. Metrics [18, 19] like BLEU [21] and ROUGE [14] focus on surface-level similarity and cannot deeply understand, whether the question aligns with the context provided. So, there is not much work on automated evaluation of question generation using human evaluation-like metrics. In this work, we aim to fill this gap.

7 Conclusion

In conclusion, the ability to automatically assess question quality plays a vital role in modern education by streamlining the evaluation process. The novel STRIVE approach, using LLMs represents a significant advancement in this area. By generating multiple evaluations of a given question and iteratively refining these assessments, STRIVE provides a more accurate, nuanced understanding of the question quality. This approach not only supports educators in identifying areas for improvement, but also fosters better alignment with human judgment in terms of relevance, appropriateness, and overall effectiveness. The strong correlation between STRIVEgenerated evaluations and human assessments underscores the potential of this method to enhance educational practices. Additionally, error analysis shows strong improvements in relevance and appropriateness in our proposed feedback-based approach (i.e., STRIVE) compared to the baseline approach.

References

- [1] Jun Araki, Dheeraj Rajagopal, Sreecharan Sankaranarayanan, Susan Holm, Yukari Yamakawa, and Teruko Mitamura. 2016. Generating questions and multiplechoice answers using semantic analysis of texts. In Proceedings of COLING 2016, the 26th International Conference on Computational Linguistics: Technical Papers. 1125–1136.
- [2] Jacob Benesty, Jingdong Chen, and Yiteng Huang. 2008. On the importance of the Pearson correlation coefficient in noise reduction. *IEEE Transactions on Audio*, *Speech, and Language Processing* 16, 4 (2008), 757–765.
- [3] Luiz Bonifacio, Hugo Abonizio, Marzieh Fadaee, and Rodrigo Nogueira. 2022. Inpars: Unsupervised dataset generation for information retrieval. In Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval. 2387–2392.
- [4] Ping Cai, Xingyuan Chen, Hongjun Wang, and Peng Jin. 2020. The errors analysis of natural language generation—A case study of Topic-to-Essay generation. In 2020 16th International Conference on Computational Intelligence and Security (CIS). IEEE, 86–89.
- [5] Yingshan Chang and Yonatan Bisk. 2022. WebQA: A Multimodal Multihop NeurIPS Challenge. In NeurIPS 2021 Competitions and Demonstrations Track. PMLR, 232–245.
- [6] Vincent Claveau. 2021. Neural text generation for query expansion in information retrieval. In IEEE/WIC/ACM International Conference on Web Intelligence and Intelligent Agent Technology. 202–209.
- [7] Bidyut Das, Mukta Majumder, Santanu Phadikar, and Arif Ahmed Sekh. 2021. Automatic question generation and answer assessment: a survey. *Research and Practice in Technology Enhanced Learning* 16, 1 (2021), 5.
- [8] Daniel Deutsch, Tania Bedrax-Weiss, and Dan Roth. 2021. Towards questionanswering as an automatic metric for evaluating the content quality of a summary. *Transactions of the Association for Computational Linguistics* 9 (2021), 774–789.
- [9] Manas Gaur, Kalpa Gunaratna, Vijay Šrinivasan, and Hongxia Jin. 2022. Iseeq: Information seeking question generation using dynamic meta-information retrieval and knowledge graphs. In *Proceedings of the AAAI Conference on Artificial Intelligence*, Vol. 36. 10672–10680.
- [10] Guher Gorgun and Okan Bulut. 2024. Exploring quality criteria and evaluation methods in automated question generation: A comprehensive survey. *Education* and Information Technologies (2024), 1–32.
- [11] Roman M Horbatiuk, Taras Sitkar, Roman Lutsyshyn, Stepan Sitkar, and Mykhailo Ozhha. 2023. Test Automatic Generation an Algorithm for an Automated Testing System.. In ITTAP. 648–660.
- [12] Tianbo Ji, Chenyang Lyu, Gareth Jones, Liting Zhou, and Yvette Graham. 2022. QAScore—an unsupervised unreferenced metric for the question generation evaluation. *Entropy* 24, 11 (2022), 1514.
- [13] Thomas W Lauer, Eileen Peacock, and Sheila M Jacobs. 2013. Question generation and the systems analysis process. In *Questions and information systems*. Psychology Press, 47–62.
- [14] Chin-Yew Lin. 2004. Rouge: A package for automatic evaluation of summaries. In Text summarization branches out. 74–81.
- [15] Jennifer Madans, Kristen Miller, Aaron Maitland, and Gordon B Willis. 2011. Question evaluation methods: contributing to the science of data quality. John Wiley & Sons.
- [16] Subhankar Maity, Aniket Deroy, and Sudeshna Sarkar. 2023. Harnessing the Power of Prompt-based Techniques for Generating School-Level Questions using Large Language Models. In Proceedings of the 15th Annual Meeting of the Forum for Information Retrieval Evaluation. 30–39.
- [17] Sewon Min, Jordan Boyd-Graber, Chris Alberti, Danqi Chen, Eunsol Choi, Michael Collins, Kelvin Guu, Hannaneh Hajishirzi, Kenton Lee, Jennimaria Palomaki, et al. 2021. Neurips 2020 efficientqa competition: Systems, analyses and lessons learned. In NeurIPS 2020 Competition and Demonstration Track. PMLR, 86-111.

- [18] Antonio Moreno-Cediel, Jesus-Angel del Hoyo-Gabaldon, Eva Garcia-Lopez, Antonio Garcia-Cabot, and David de Fitero-Dominguez. 2024. Evaluating the performance of multilingual models in answer extraction and question generation. *Scientific Reports* 14, 1 (2024), 15477.
- [19] Nikahat Mulla and Prachi Gharpure. 2023. Automatic question generation: a review of methodologies, datasets, evaluation metrics, and applications. *Progress* in Artificial Intelligence 12, 1 (2023), 1–32.
- [20] Lin Ni, Qiming Bao, Xiaoxuan Li, Qianqian Qi, Paul Denny, Jim Warren, Michael Witbrock, and Jiamou Liu. 2022. Deepqr: Neural-based quality ratings for learnersourced multiple-choice questions. In Proceedings of the AAAI Conference on Artificial Intelligence, Vol. 36. 12826–12834.
- [21] Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: a method for automatic evaluation of machine translation. In Proceedings of the 40th annual meeting of the Association for Computational Linguistics. 311-318.
- [22] Revanth Gangi Reddy, Md Arafat Sultan, Martin Franz, Avirup Sil, and Heng Ji. 2022. Entity-conditioned question generation for robust attention distribution in neural information retrieval. In Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval. 2462–2466.
- [23] Philip Sedgwick. 2012. Pearson's correlation coefficient. Bmj 345 (2012).
- [24] Cunxiang Wang, Sirui Cheng, Qipeng Guo, Yuanhao Yue, Bowen Ding, Zhikun Xu, Yidong Wang, Xiangkun Hu, Zheng Zhang, and Yue Zhang. 2023. Evaluating Open-QA Evaluation. In Advances in Neural Information Processing Systems, A. Oh, T. Naumann, A. Globerson, K. Saenko, M. Hardt, and S. Levine (Eds.), Vol. 36. Curran Associates, Inc., 77013–77042. https://proceedings.neurips.cc/paper_files/paper/2023/file/ f323d594aa5d2c68154433a131c07959-Paper-Datasets_and_Benchmarks.pdf
- [25] Hongcui Wang, Christopher J Waple, and Tatsuya Kawahara. 2009. Computer assisted language learning system based on dynamic question generation and error prediction for automatic speech recognition. *Speech Communication* 51, 10 (2009), 995–1005.
- [26] Yuqi Wang, Lyuhao Chen, Songcheng Cai, Zhijian Xu, and Yilun Zhao. 2024. Revisiting Automated Evaluation for Long-form Table Question Answering. In Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing. 14696–14706.
- [27] Zichao Wang, Angus Lamb, Evgeny Saveliev, Pashmina Cameron, Jordan Zaykov, Jose Miguel Hernandez-Lobato, Richard E Turner, Richard G Baraniuk, Craig Barton, Simon Peyton Jones, et al. 2021. Results and insights from diagnostic questions: The neurips 2020 education challenge. In *NeurIPS 2020 Competition* and Demonstration Track. PMLR, 191–205.
- [28] Johannes Welbl, Nelson F Liu, and Matt Gardner. 2017. Crowdsourcing Multiple Choice Science Questions. W-NUT 2017 (2017), 94.
- [29] Liu Yang, Junjie Hu, Minghui Qiu, Chen Qu, Jianfeng Gao, W Bruce Croft, Xiaodong Liu, Yelong Shen, and Jingjing Liu. 2019. A hybrid retrieval-generation neural conversation model. In Proceedings of the 28th ACM international conference on information and knowledge management. 1341–1350.
- [30] Hamed Zamani, Susan Dumais, Nick Craswell, Paul Bennett, and Gord Lueck. 2020. Generating clarifying questions for information retrieval. In *Proceedings of* the web conference 2020. 418–428.