# arXiv:2504.07341v1 [quant-ph] 9 Apr 2025

# Learning to erase quantum states: thermodynamic implications of quantum learning theory

Haimeng Zhao,<sup>1,\*</sup> Yuzhen Zhang,<sup>2,†</sup> and John Preskill<sup>1,3,‡</sup>

<sup>1</sup>Institute for Quantum Information and Matter, California Institute of Technology, Pasadena, CA 91125, USA

<sup>2</sup>Department of Physics, University of California, Santa Barbara, CA 93106, USA

<sup>3</sup>AWS Center for Quantum Computing, Pasadena, CA 91125, USA

The energy cost of erasing quantum states depends on our knowledge of the states. We show that learning algorithms can acquire such knowledge to erase many copies of an unknown state at the optimal energy cost. This is proved by showing that learning can be made fully reversible and has no fundamental energy cost itself. With simple counting arguments, we relate the energy cost of erasing quantum states to their complexity, entanglement, and magic. We further show that the constructed erasure protocol is computationally efficient when learning is efficient. Conversely, under standard cryptographic assumptions, we prove that the optimal energy cost cannot be achieved efficiently in general. These results also enable efficient work extraction based on learning. Together, our results establish a concrete connection between quantum learning theory and thermodynamics, highlighting the physical significance of learning processes and enabling efficient learning-based protocols for thermodynamic tasks.

Do abstract learning processes have tangible physical consequences? For example, does the (in)ability to learn impact the amount of physical resources required to perform certain tasks?

Learning is the process of acquiring information, which can be used to execute actions [1–4]. Landauer's principle [5–10] illustrates how the energy cost of erasing a physical system depends on our knowledge of the system. In particular, given a system S in a state  $\rho$  with degenerate Hamiltonian  $\mathcal{H} = 0$ , the amount of work required to transform it to a reference pure state  $|0\rangle$  in an environment at temperature T is  $W \ge H(S)k_BT\ln 2$ , where  $k_B$ is the Boltzmann constant and H(S) is the entropy of the state. Entropy measures our ignorance of the state, and additional knowledge of the system reduces the optimal work cost to  $H(S|M)k_BT\ln 2$ , where H(S|M) is the entropy of the system conditioned on the memory Mthat records the knowledge [11]. However, this statement does not take into account the potential cost of acquiring the knowledge recorded in the memory.

To formalize this process of "learning to erase", we consider the simple scenario in which a source repeatedly produces an unknown *n*-qubit state  $|\psi_x\rangle$  from a class of m possible states  $\mathcal{C} = \{|\psi_x\rangle\}_{x=1}^m$ . At first, due to our ignorance of the state, we have to pay work to erase it. As we collect more copies of the state  $|\psi_x\rangle$ , we progressively learn enough information to identify the state. Once we have learned the state, we can erase additional copies without further work by reversing the state preparation unitary,  $U_x^{\dagger} |\psi_x\rangle = |0\rangle$ .

In this paper, we rigorously study this process using tools recently developed in quantum learning theory [12– 20] and explore its thermodynamic implications. We explain a general method that lifts any learning algorithm to a reversible one, enabling it to acquire knowledge from multiple copies of the unknown state and erase many additional copies at the optimal energy cost, saturating Landauer's limit (Figure 1(a)). We further pinpoint the quantitative relation between the energy cost of erasing a class of quantum states and their complexity, as measured by circuit depth, entanglement, or magic (Figure 1(b)).

After establishing the information-theoretical optimality of learning-to-erase protocols, we study their computational efficiency — whether they can be implemented in a number of elementary operations that scales polynomially with the system size n and number of copies N. We show that whenever the learning algorithm and state preparation are efficient, the constructed erasure protocol is also efficient. We illustrate this with a wide range of physically relevant classes of states, including shallowcircuit states, doped stabilizer states, matrix product states, and low-degree phase states. Conversely, under standard cryptographic assumptions, we prove that there exist classes of low-complexity states that are hard to learn and also hard to erase. For these states, Landauer's principle allows N copies to be erased by expending an amount of work independent of N, but for any efficient erasure protocol the cost scales nearly linearly with N. This is a genuine quantum many-body phenomenon and a much stronger no-go result than the third law of thermodynamics [21–24]. It also implies that the existing general purpose compress-to-erase methods [11, 25–27] require resources superpolynomial in n.

Finally, we show that our learning-to-erase protocols can be used to extract work [7, 28, 29], where similar optimality and (in)efficiency results hold. In particular, the no-go result implies that in general one can extract only a small fraction of all the possible work in polynomial time. In contrast, given efficiently learnable states, we can efficiently extract the optimal amount of work by learning.

<sup>\*</sup> haimengzhao@icloud.com

 $<sup>^{\</sup>dagger}$ yuzhenzhang@ucsb.edu

<sup>&</sup>lt;sup>‡</sup> preskill@caltech.edu



Figure 1. (a) Reversible learning algorithm  $\mathcal{L}$  can acquire knowledge of the unknown *n*-qubit state and erase *N* copies of it at the optimal work cost, saturating Landauer's limit. Here, *S* stores the copies used by the learning algorithm, *R* stores the rest, *M* is the memory of the learning algorithm, and *M'* is an auxiliary memory. The ancilla registers are omitted for clarity. (b) The work cost of erasing physically relevant classes of states grows with the complexity of the states, as measured by circuit depth, magic, entanglement, and degree. When the complexity is bounded, Landauer's limit can be achieved efficiently by learning. In contrast, when the complexity grows poly-logarithmically, no polynomial-time quantum algorithm can erase the states without paying a nearly maximal amount of work.

# I. GENERAL FORMULATION

We first consider the general case where the class of possible states  $C = \{|\psi_x\rangle\}_{x=1}^m$  is arbitrary and known (along with their state preparation unitaries  $\{U_x\}_{x=1}^m$ ). We assume that these states are distinct, in the sense that they are pairwise apart by a constant trace distance:  $\forall x \neq x', d_{\rm tr}(|\psi_x\rangle, |\psi_{x'}\rangle) = \frac{1}{2} ||\psi_x\rangle \langle \psi_x| - |\psi_{x'}\rangle \langle \psi_{x'}||_1 \ge \epsilon = \Theta(1)$  [30]. The state we aim to erase can be described by  $\rho = \sum_{x=1}^m p_x(|\psi_x\rangle \langle \psi_x|)^{\otimes N}$ , where  $\{p_x\}$  are the prior probabilities. Our goal is to design a protocol that can erase  $\rho$  with high success probability. To do so we describe a learning algorithm that identifies x, lift it to a reversible algorithm, and then use it to erase the state.

We adopt a learning algorithm [12] based on hypothesis selection [31] and Clifford classical shadows [32]. Given scopies of the state  $|\psi_x\rangle$ , we apply a random n-qubit Clifford gate on each copy and measure in the computational basis. The measurement statistics allow us to classically calculate unbiased estimators for the expectation values of  $\binom{m}{2} = O(m^2)$  Helstrom measurements [33] between all pairs of possible states in C. We can then use quantum hypothesis selection to find out the candidate state in Cthat is closest to  $|\psi_x\rangle$  in trace distance. When we have  $s = O(\log(m)/\epsilon^2) = O(\log m)$  samples, we are guaranteed to find the correct x with high probability  $p_{\text{succ}}$ . A detailed proof can be found in [12, Proposition 1].

The above learning algorithm involves randomness generation and irreversible measurements that may incur extra work cost. To avoid this, we describe a general method that lifts a learning algorithm to a reversible one. Formally speaking, a learning algorithm  $\mathcal{L}_0$  takes the system  $|\psi_x\rangle_S^{\otimes s}$  and a classical memory register  $|0\rangle_M$  as input and writes the learning outcome into

 $|x\rangle_M$  with high probability. It is implemented using a set of quantum and classical gates, random number generators, and projective measurements. We first replace every quantum and classical gates by their reversible counterparts [7, 34]. Then we replace projective measurements by their coherent version: to measure a set of projectors  $\{P_a\}$ , we apply an unitary U on the system and an ancilla A that records the measurement outcome. U completes the isometry  $\sum_a P_a \otimes |a\rangle \langle 0|$  such that  $U |\psi\rangle_S |0\rangle_A = \sum_a P_a |\psi\rangle_S |a\rangle_A$  for any  $|\psi\rangle_S$ . When classical random numbers are needed, we coherently measure  $|+\rangle$  states in the computational basis. All operations that depend on random numbers or measurement outcomes can be realized using reversible gates controlled by the ancilla. In this way, we have constructed a reversible learning algorithm  $\mathcal{L}$  (a unitary) that satisfies

$$\mathcal{L} |\psi_x\rangle_S^{\otimes s} |0\rangle_M |0\rangle_A = \sum_{x'=1}^m c_{x'|x} |x'\rangle_M |\mathrm{junk}_{x'}\rangle_{S,A}, \quad (1)$$

where the coefficients  $c_{x'|x} \in \mathbb{C}$  are determined by the probability of predicting x' given the state  $|\psi_x\rangle$ . In particular,  $|c_{x|x}|^2 \ge p_{\text{succ}}$  is close to one for any x.

Now we construct an erasure protocol  $\mathcal{E}(\mathcal{L})$  using the reversible learning algorithm  $\mathcal{L}$ . The construction is summarized in Figure 1(a). Given  $N \geq s$  copies of  $|\psi_x\rangle$ , the protocol proceeds by first executing  $\mathcal{L}$  on s copies. We call the s copies S and the rest R. Then we introduce an additional classical memory M' and use CNOT gates to copy the content of M into M'. Next, we apply the inverse  $\mathcal{L}^{-1}$  to S, M, A to uncompute [35] and get rid of the junk. We erase each copy in S and R by applying the inverse state preparation unitary conditioned on the learning outcome recorded in M'. Finally, we erase M'bit by bit using standard classical Landauer erasure [7], costing energy  $W = (\log_2 m)k_BT \ln 2$ . This is the only step that costs energy.

To prove the correctness of the erasure protocol  $\mathcal{E}(\mathcal{L})$ , we calculate the overlap between  $|x\rangle_{M'} |\psi_x\rangle_S^{\otimes s} |0\rangle_{M,A}$ and the intermediate state of  $\mathcal{E}(\mathcal{L})$  after uncomputation (apart from R):

$$\langle x|_{M'} \langle \psi_x|_S^{\otimes} \langle 0|_{M,A} \mathcal{L}^{\dagger} \sum_{x'} c_{x'|x} |x'\rangle_{M'} |x'\rangle_M |\operatorname{junk}_{x'}\rangle_{S,A}$$

$$= c_{x|x} \left( \sum_{x''} c_{x''|x}^* \langle x''|_M \langle \operatorname{junk}_{x''}|_{S,A} \right) |x\rangle_M |\operatorname{junk}_x\rangle_{S,A}$$

$$= |c_{x|x}|^2 \ge p_{\operatorname{succ}},$$

$$(2)$$

which means that the trace distance between the two states is  $\sqrt{1-|c_{x|x}|^4} \leq \sqrt{1-p_{succ}^2}$ . Due to the data processing inequality satisfied by the trace distance [36], after executing the rest of the erasure protocol (a fixed quantum channel), we have  $d_{tr}(\mathcal{E}(\mathcal{L})(|\psi_x\rangle^{\otimes N}|0\rangle), |0\rangle) \leq \sqrt{1-p_{succ}^2}$ . When the input is the mixture  $\rho = \sum_x p_x(|\psi_x\rangle \langle \psi_x|)^{\otimes N}$ , we invoke the triangle inequality and have trace distance  $\frac{1}{2} ||\mathcal{E}(\mathcal{L})(\rho \otimes |0\rangle \langle 0|) - |0\rangle \langle 0| ||_1 \leq \sum_x p_x d_{tr}(\mathcal{E}(\mathcal{L})(|\psi_x\rangle^{\otimes N}|0\rangle), |0\rangle) \leq \sqrt{1-p_{succ}^2}$ , which is close to zero. This concludes the proof of the correctness.

We note that the only step that costs energy in this erasure protocol is the step of erasing learning outcomes, which costs  $W = (\log_2 m)k_BT \ln 2$  joules of work, independent of N. This confirms our intuition that once we have learned the state, we can erase many more copies without further work. We also remark that this general method of constructing reversible learning algorithms illustrates that learning as a physical process does not itself have a fundamental energy cost. In principle, the energy cost only occurs when the learning agent needs to erase and recycle its memory. In practice, there may be an extra energy cost if the learning algorithm is not implemented in a fully coherent and reversible way.

The sample complexity s of the learning algorithm plays an interesting role in the erasure protocol. The above construction only works when  $N \geq s$  and when we have sufficient quantum working memory (ancilla supply) so that we have enough information to learn and space to make everything reversible. Extra work may be needed when these assumptions are not met. Assuming that the learning algorithm and the state preparation unitary have time complexity  $T_{\text{learn}}$  and  $T_{\text{prep}}$ , the total time complexity of  $\mathcal{E}(\mathcal{L})$  is  $O(T_{\text{learn}} + \log m + NT_{\text{prep}})$ . Therefore, whenever the learning and state preparation steps are efficient, the erasure protocol is also efficient.

We show that the above work cost is optimal by calculating the lower bound given by Landauer's principle. Since we are only given one copy of  $\rho$  (which contains N copies of  $|\psi_x\rangle$ ), the Landauer's limit is given by the one-shot max-entropy  $W \geq H_{\max}(\rho)k_BT\ln 2$ , where  $H_{\max}(\rho) = \log_2(\operatorname{rank}(\rho))$  is the max-entropy of  $\rho$  [9, 11, 29, 37, 38]. To calculate the rank of  $\rho$ , we construct the Gram matrix  $G_{xx'} = \langle \psi_x | \psi_{x'} \rangle^N$ . Assuming  $N > 2\log(m-1)/\log(1/(1-\epsilon^2)) = \Theta(\log m)$ (which is naturally satisfied when  $N \ge s$  and we always assume this from now on), we have  $\sum_{x' \ne x} |G_{xx'}| \le \sum_{x' \ne x} (1-\epsilon^2)^{N/2} < \sum_{x' \ne x} (m-1)^{-1} = 1 = G_{xx}, \forall x$ . This means that G is diagonally dominant and thus non-singular, implying that  $\{|\psi_x\rangle^{\otimes N}\}_{x=1}^m$  are linearly independent. Thus rank $(\rho) = m$  and Landauer's limit reads  $(\log_2 m)k_BT \ln 2$ . This coincides with the work cost of  $\mathcal{E}(\mathcal{L})$ , proving that the learning-to-erase protocol is information-theoretically optimal.

It is straightforward to generalize these results to erase a continuous class of states C. We can use the erasure protocol for a discrete class in conjunction with a minimal  $\epsilon$ -covering net of C, similar to [12, Theorem 1]. The resulting erasure protocol will be able to approximately erase every copy to  $\epsilon$  error in trace distance. The work cost will be  $(\log_2 m(C, d_{\rm tr}, \epsilon))k_BT \ln 2$  where  $m(C, d_{\rm tr}, \epsilon)$ is the size of the covering net. Meanwhile, this protocol can perfectly erase states drawn from a maximal  $\Theta(\epsilon)$ packing net of C. By Landauer's principle, this requires work  $(\log_2 \tilde{m}(C, d_{\rm tr}, \Theta(\epsilon))k_BT \ln 2$  when N is large, where  $\tilde{m}(C, d_{\rm tr}, \Theta(\epsilon))$  is the size of the packing net. Since m and  $\tilde{m}$  are equivalent up to a constant factor change in  $\epsilon$  [39], the erasure protocol is asymptotically optimal.

# II. WORK AND COMPLEXITY

We now apply the general formulation to several physically relevant classes of states, and illustrate how the work cost of erasure grows with the complexity of the states in the target class. For these classes, we give time efficient erasure protocols built from efficient learning algorithms. The results are summarized in Figure 1(b).

Our first example is shallow-circuit states  $C = \{|\psi\rangle = U |0^n\rangle\}$ , where U can be an arbitrary quantum circuit with depth d on a O(1)-dimensional lattice built from a finite-size two-qubit gate set G [13, 14, 40]. This class naturally describes the output state of finite-time evolution of physical systems [41] and noisy intermediate-scale quantum computation [42], offering quantum advantage over classical computation [43–48]. The number of possible states in this class is  $m = |G|^{\Theta(nd)}$ . Thus the required work cost is

$$W = \Theta(nd)k_B T \ln 2, \tag{3}$$

growing linearly with circuit depth d, when N is sufficiently large. For constant d, this optimal work cost is achieved efficiently using  $\mathcal{E}(\mathcal{L})$  with a polynomial-time learning algorithm  $\mathcal{L}$  that learns the local inversions of the shallow circuit and sews them together (the discrete gate set version of [14]). In particular, we have  $T_{\text{learn}} = \text{poly}(n) \cdot 2^{d^{O(1)}}$  and  $T_{\text{prep}} = O(nd)$ , and the total time complexity of erasure is  $O(\text{poly}(n) \cdot 2^{d^{O(1)}} + ndN)$ . A second example is t-doped stabilizer states  $\mathcal{C} = \{|\psi\rangle = U |0^n\rangle\}$ , where U is composed of an arbitrary

number of Clifford gates and at most t T-gates (T = diag $(1, e^{i\pi/4})$ ) [15, 16]. Here, t characterizes the amount of magic (or non-stabilizerness) in the state [49], which is closely related to universality [50, 51], classical simulability [52–54], and error correction [55, 56] of quantum computation. The number of possible states in the class is  $m = (2^{\Theta(n^2)})^t \times n^t = \exp \Theta(n^2 t)$  [52] because there are  $2^{\Theta(n^2)}$  possible Clifford unitaries in between each pair of T-gates. When N is large, the work cost for erasure is

$$W = \Theta(n^2 t) k_B T \ln 2, \tag{4}$$

growing linearly with the magic t. For  $t = O(\log n)$ , this is achieved efficiently by an efficient learning algorithm for t-doped stabilizer states, which identifies the state exactly by bell sampling [57] and estimating the stabilizer group (see [15]). We have  $T_{\text{learn}} = \text{poly}(n, 2^t)$  and  $T_{\text{prep}} = O(n^2 t)$ ; thus the total time complexity of erasure is  $O(\text{poly}(n, 2^t) + n^2 tN)$ .

Our third example is matrix product states (MPS)  $\mathcal{C} =$  $\{|\psi\rangle = \sum_{x \in \{0,1\}^n} A_1^{x_1} \cdots A_n^{x_n} |x\rangle\}, \text{ where } A_i^x \in \mathbb{C}^{\chi_i \times \chi_{i+1}}$ with bond dimension  $\chi_1 = \chi_{n+1} = 1$  and  $\chi_i \leq 2^{\mathcal{S}}$  [17]. Here, S is the maximal entanglement entropy across every cut of the system. MPS representations with constant  $\mathcal{S}$  exist for states with bounded entanglement, including ground states of one-dimensional gapped local Hamiltonians [58] and symmetry-protected topological phases [59], as well as important states like AKLT [60], GHZ, W and cluster states that are useful for quantum metrology [61] and universal quantum computation [62]. To calculate the work cost of erasing this continuous class of states, we bound the size of its  $\epsilon$ -covering and packing nets. Every MPS with entanglement entropy  $\mathcal{S}$  can be generated by a sequential quantum circuit with n gates each acting on  $O(\mathcal{S})$  qubits [63]. Utilizing existing covering number bounds on circuits with bounded gate complexity and fixed circuit structure [12, Theorem 8], we have  $\log m(\mathcal{C}, d_{\mathrm{tr}}, \epsilon) \leq O(n4^{O(\mathcal{S})} \log(n4^{O(\mathcal{S})}/\epsilon)) = \exp \tilde{O}(\mathcal{S}),$ where  $\tilde{O}$  omits log n, log log $(1/\epsilon)$  factors. To lower bound the packing number  $\tilde{m}$ , we note that an MPS with entanglement entropy  $\mathcal{S}$  can represent any  $\Theta(\mathcal{S})$ -qubit state tensored with zeroes on the remaining qubits. The set of general  $\Theta(\mathcal{S})$ -qubit states have log-packing number  $\exp \Omega(\mathcal{S})$ . Thus we have  $\log \tilde{m}(\mathcal{C}, d_{\mathrm{tr}}, \epsilon) \geq \exp \Omega(\mathcal{S})$ . Therefore, the work cost for erasure

$$W = \exp(\tilde{\Theta}(\mathcal{S}))k_B T \ln 2 \tag{5}$$

grows exponentially with the entanglement entropy S. For constant S, this is achieved efficiently using an efficient learning algorithm for MPS that sequentially learns n O(S)-qubit unitaries to disentangle the MPS (see [17]). We have  $T_{\text{learn}} = \text{poly}(n, 2^S)$  and  $T_{\text{prep}} = O(n4^S)$ , and the total time complexity of erasure is  $O(\text{poly}(n, 2^S) + n4^S N)$ .

The last example is low-degree phase states  $C = \{|\psi\rangle = 2^{-n/2} \sum_{x \in \{0,1\}^n} (-1)^{f(x)} |x\rangle\}$ , where  $f : \{0,1\}^n \to \{0,1\}$  is an arbitrary Boolean function with degree at most

k = O(1) [18]. They correspond to hypergraph states that are generated by k-body multi-controlled Z gates on  $|+\rangle^{\otimes n}$ . They are useful resources in measurement-based quantum computation [62, 64] and appear in quantum advantage experiments [65, 66] and oracle query algorithms [35]. By counting polynomial Boolean functions, we see that the number of such states is  $m = \prod_{j=0}^{k} 2^{\binom{n}{j}} = \exp \Theta(n^k)$  and the required work cost is

$$W = \Theta(n^k)k_B T \ln 2, \tag{6}$$

growing exponentially with degree k. For constant k, the erasure is efficient using an efficient learning algorithm that measures single-qubit X and Z observables and learns the gradient of f with respect to each argument (see [18, Theorem 3]). Here,  $T_{\text{learn}} = O(n^{3k-2})$  and  $T_{\text{prep}} = O(kn^k)$  [67], and the total time complexity of erasure is  $O(n^{3k-2} + kn^kN)$ .

In Figure 1(b), we summarize the above results and visualize how the optimal work cost of erasure grows with the four different complexity measures: circuit depth d, magic t, entanglement entropy S, and degree k. In particular, the work cost scales linearly with depth ( $\sim nd$ ) and magic ( $\sim n^2t$ ), where the growth with magic has a larger slope. Meanwhile, the work cost scales exponentially with entanglement entropy ( $\sim e^S$ ) and degree ( $\sim n^k$ ), where the growth with degree is faster. The computational complexity of erasure grows exponentially with all four measures of complexity. When the complexity is bounded, the optimal work cost can be achieved efficiently by learning.

### **III. COMPUTATIONAL HARDNESS**

For the above special classes of states, we have constructed efficient erasure protocols with optimal work cost. However, we show that this is not possible in general. We consider a particular class of states, pseudorandom states  $\{|\psi_x\rangle\}$  [68, 69], which cannot be efficiently distinguished from Haar random states with non-negligible (1/poly(n)) probability. Concretely, under the standard cryptographic conjecture that there exist one-way functions secure against any sub-exponential time quantum adversary (e.g., based on the learning with errors problems [70]), pseudorandom states can be constructed with  $d = \mathsf{polylog}(n)$  circuit depth [19]. Let  $N = \mathsf{poly}(n)$ . Because the entropy of  $\rho = \sum_x p_x (|\psi_x\rangle \langle \psi_x|)^{\otimes N}$  depends on m but not N, Landauer's principle asserts that the N copies can be erased with low work cost, independent of N. On the other hand, for the Haar ensemble, the Landauer cost of erasure is

$$W_{\text{Haar}} = \log_2 \binom{N+2^n-1}{N} k_B T \ln 2, \qquad (7)$$

because the density operator realized by the Haar ensemble has full rank over the totally symmetric subspace for N copies of a  $2^n$ -dimensional Hilbert space, which has dimension  $\binom{N+2^n-1}{N}$ . In the following, we prove that any polynomial-time quantum algorithm that can erase a pseudorandom state  $\rho = \sum_x p_x (|\psi_x\rangle \langle \psi_x|)^{\otimes N}$ with success probability close to one must require work cost  $W_{\text{Haar}}$ . The intuition is simple: if we can erase pseudorandom states with less work, then we can distinguish them from Haar random states by measuring the work cost, violating the definition of pseudorandom states.

To prove the statement, we suppose for the sake of contradiction that there exists an efficient erasure protocol  $\mathcal{E}$  that erases  $\rho$  with work cost less than  $W_{\text{Haar}}$ . We construct a distinguisher  $\mathcal{D}$  that distinguishes pseudorandom states from Haar random states. The distinguisher proceeds by executing  $\mathcal{E}$  on the given states and conducting two tests: (1) determine if the erasure is successful by measuring the projector  $|0\rangle \langle 0|$ ; and (2) test if the work cost is less than  $W_{\text{Haar}}$  by measuring the energy change in the energy source [71].  $\mathcal{D}$  outputs 0 if both tests pass, and 1 otherwise.

When given pseudorandom states, we have  $\Pr[\mathcal{D}((|\psi_x\rangle \langle \psi_x|)^{\otimes N}) = 0] = \Pr[\mathcal{D}(\rho) = 0]$  close to one, where the probability is over x and the randomness in  $\mathcal{D}$ ; here we used linearity of quantum channels and the guarantee that  $\mathcal{E}$  can erase pseu-When given Haar random states dorandom states.  $\rho_{\text{Haar}} = \int d |\psi\rangle \langle \psi\rangle \langle \psi| \rangle^{\otimes N}$ , the probability of outputting 0 is equal to  $\Pr[\mathcal{D}(|\psi\rangle \langle \psi|) = 0] = \Pr[\mathcal{D}(\rho_{\text{Haar}}) = 0]$ , the probability of one-shot successful erasure of  $\rho_{\text{Haar}}$  with work cost less than  $W_{\text{Haar}}$ . Because the erasure protocol  $\mathcal{E}$  is assumed to be efficient, this probability must also be close to one by the definition of pseudorandom states. But this contradicts Landauer's principle, which asserts that it is not possible to perform one-shot erasure with work cost less than  $H_{\text{max}}(\rho_{\text{Haar}})k_BT\ln 2 =$  $\log_2(\operatorname{rank}(\rho_{\operatorname{Haar}}))k_BT\ln 2 = W_{\operatorname{Haar}}$ . This completes the proof of the no-go result.

For a quantitative understanding, we note that  $W_{\text{Haar}}/(k_BT \ln 2) \ge nN(1 - (\log_2 N)/n)$ , which goes to the maximal value nN as n grows large with N = poly(n). But Landauer's limit for this class of states is only  $\Theta(nd) = n\text{polylog}(n)$ , independent of N. This means that Landauer's limit cannot be achieved in polynomial time, and asymptotically maximal work must be paid.

We remark that this is a much stronger no-go result than the third law of thermodynamics, which asserts that perfect erasure as a form of cooling requires diverging resources (time, size of the heat bath, etc.) [21–24]. The third law does not rule out the possibility of achieving Landauer's limit in polynomial time by paying 1/poly(n)extra work and using an infinite size heat bath. In contrast, our result shows that even with an infinite size heat bath, any procedure that can erase a particular class of low-depth states in polynomial time must pay a nearly maximal amount of work. This is a many-body phenomenon due to the complexity of large systems.

It helps to compare with the classical version of the problem. Classically, the state is a mixture of  $m \leq 2^n$  possible computational basis states copied N times. The

entropy is  $\log_2 m \leq n$ , which does not increase with N, even when the bit-strings are generated by pseudorandom functions. We can always erase N copies with work cost at most  $nk_BT \ln 2$ . Therefore, it is a genuine quantum feature to have a work cost  $W_{\text{Haar}}$  that scales with N. This originates from the fact that there are many more states when we allow superposition. The optimal classical erasure protocol is straightforward: we condition on the first copy of the bit-string, apply transversal CNOT gates to erase the other copies, and finally erase the first copy. From a learning perspective, this protocol learns the bitstring by looking at the first copy, and the knowledge of this one copy is sufficient for erasing the rest. In contrast, in the fully quantum case, many copies are needed to learn a state.

# **IV. WORK EXTRACTION**

The thermodynamic implications of quantum learning theory extend beyond erasure. In the task of work extraction, it is information-theoretically possible to extract  $W = (nN - H(\rho))k_BT \ln 2$  work from the state  $\rho$ [7, 10, 28, 29]. When learning is efficient, our learningto-erase protocols give efficient work extraction protocols with the maximal work yield: we simply erase the state first, and then extract work from each refreshed qubit. In contrast, there exist ensembles such that no polynomialtime quantum algorithm can extract more work than  $nNk_BT\ln 2 - W_{\text{Haar}} \leq N\log_2(N)k_BT\ln 2$ . Otherwise, one could construct an efficient erasure protocol with less than  $W_{\text{Haar}}$  work cost for pseudorandom states by first extracting work and then erasing each qubit (which costs  $nNk_BT \ln 2$  work and O(nN) = poly(n) time). Therefore, for general states, one can extract in polynomial time only a fraction  $\log_2(N)/n = O(\log(n)/n)$  of the available work, which becomes negligibly small for nlarge.

### V. DISCUSSION

We have established a concrete connection between quantum learning theory and thermodynamics. Our results illustrate that seemingly abstract learning processes have tangible physical consequences that determine the energy cost or gain in thermodynamic tasks. This allows us to study properties of learning itself from a thermodynamic perspective. In particular, we find that learning has no fundamental energy cost, if implemented in a fully coherent fashion.

This connection also enables efficient thermodynamic protocols based on learning, improving upon existing compression-based protocols that are not efficient in n[11, 25–27]. In a way, learning is compression — compressing quantum states into their classical descriptions — and efficient learning yields efficient compression [72]. These efficient erasure protocols may find applications in the initialization of distributed quantum metrology systems and in recycling qubits for repeated use in quantum experiments. They also provide a viable way to experimentally demonstrate Landauer's limit [73–75] and materialize Maxwell's demon as a learning agent [76–79] in the quantum many-body regime. These efficient energyoptimal protocols may be a key component in building future large-scale, energy-efficient quantum computers [80].

Our results also exemplify the drastic change of physical resources required by certain tasks when we are in the many-body regime. Ideas that date back to the early days of information theory, like Landauer's principle, may require reexamination via the lens of complexity [81, 82].

Our work opens up many interesting future directions. First, our setting can be extended to more realistic scenarios, where we want to erase many copies of mixed states  $\rho = \sum_x p_x \rho_x^{\otimes N}$ . A natural choice could be thermal states of unknown Hamiltonians that describe physical systems in thermal equilibrium. Efficient learning and erasing may be possible in this case, where we expect the optimal work cost to scale with N:  $\sum_x p_x NH(\rho_x) + H(\{p_x\})$ , because after we have identified  $\rho_x$ , we still need to pay work to erase each copy because it is mixed. Second, our results may be extended to continuous variable systems such as fermionic or bosonic systems and inspire efficient thermodynamic protocols there [83, 84]. Third, learning may yield efficient protocols for other thermodynamic tasks beyond erasure and work extraction.

Our computational hardness results may find cryptological applications related to energy storage, manipulation, and transfer. Intriguingly, limitations on erasing information in or extracting work from black holes may apply if the evolution of these systems is modeled accurately by pseudorandom unitaries [85–87]. Finally, it may be instructive to study other physical properties of learning processes beyond energy cost, such as their consequences for information dynamics [88], phase transitions [89], and noise robustness [20].

### ACKNOWLEDGMENTS

We thank Soonwon Choi, Bartek Czech, Jens Eisert, Philippe Faist, Yingfei Gu, Hsin-Yuan Huang, Jarrod R. McClean, Jinzhao Wang, and Yuxiang Yang for helpful discussions. We gratefully acknowledge support from the U.S. Department of Energy, Office of Science, National Quantum Information Science Research Centers, Quantum Systems Accelerator, and the National Science Foundation (PHY-2317110). The Institute for Quantum Information and Matter is an NSF Physics Frontiers Center.

- E. T. Jaynes, Information theory and statistical mechanics, Physical Review 106, 620 (1957).
- [2] E. T. Jaynes, Information theory and statistical mechanics. II, Physical Review 108, 171 (1957).
- [3] E. T. Jaynes, *Probability Theory: The Logic of Science*, edited by G. L. Bretthorst (Cambridge University Press, Cambridge, 2003).
- [4] R. Landauer, Information is Physical, Physics Today 44, 23 (1991).
- [5] R. Landauer, Irreversibility and Heat Generation in the Computing Process, IBM Journal of Research and Development 5, 183 (1961).
- [6] C. H. Bennett, Logical Reversibility of Computation, IBM Journal of Research and Development 17, 525 (1973).
- [7] C. H. Bennett, The thermodynamics of computation—a review, International Journal of Theoretical Physics 21, 905 (1982).
- [8] D. Reeb and M. M. Wolf, An improved Landauer principle with finite-size corrections, New Journal of Physics 16, 103011 (2014).
- [9] O. C. O. Dahlsten, R. Renner, E. Rieper, and V. Vedral, Inadequacy of von Neumann entropy for characterizing extractable work, New Journal of Physics 13, 053015 (2011).
- [10] R. P. Feynman, *Feynman Lectures on Computation: Anniversary Edition*, 2nd ed., edited by T. Hey (CRC Press, Boca Raton, 2023).

- [11] L. del Rio, J. Aberg, R. Renner, O. Dahlsten, and V. Vedral, The thermodynamic meaning of negative entropy, Nature 474, 61 (2011), arXiv:1009.1630 [quant-ph].
- [12] H. Zhao, L. Lewis, I. Kannan, Y. Quek, H.-Y. Huang, and M. C. Caro, Learning quantum states and unitaries of bounded gate complexity, PRX Quantum 5, 40306 (2024).
- [13] H.-Y. Huang, Y. Liu, M. Broughton, I. Kim, A. Anshu, Z. Landau, and J. R. McClean, Learning shallow quantum circuits, in *Proceedings of the 56th Annual ACM Symposium on Theory of Computing* (2024) pp. 1343– 1351, arXiv:2401.10095 [quant-ph].
- [14] Z. Landau and Y. Liu, Learning quantum states prepared by shallow circuits in polynomial time (2024), arXiv:2410.23618 [quant-ph].
- [15] L. Leone, S. F. E. Oliviero, and A. Hamma, Learning t-doped stabilizer states, Quantum 8, 1361 (2024), arXiv:2305.15398 [quant-ph].
- [16] S. Grewal, V. Iyer, W. Kretschmer, and D. Liang, Efficient learning of quantum states prepared with few nonclifford gates (2024), arXiv:2305.13409 [quant-ph].
- [17] M. Cramer, M. B. Plenio, S. T. Flammia, R. Somma, D. Gross, S. D. Bartlett, O. Landon-Cardinal, D. Poulin, and Y.-K. Liu, Efficient quantum state tomography, Nature Communications 1, 149 (2010).
- [18] S. Arunachalam, S. Bravyi, A. Dutt, and T. J. Yoder, Optimal algorithms for learning quantum phase states (2023), arXiv:2208.07851 [quant-ph].

- [19] T. Schuster, J. Haferkamp, and H.-Y. Huang, Random unitaries in extremely low depth (2024), arXiv:2407.07754 [quant-ph].
- [20] A. Anshu and S. Arunachalam, A survey on the complexity of learning quantum states, Nature Reviews Physics 6, 59 (2024).
- [21] H. Wilming and R. Gallego, Third Law of Thermodynamics as a Single Inequality, Physical Review X 7, 041033 (2017).
- [22] L. Masanes and J. Oppenheim, A general derivation and quantification of the third law of thermodynamics, Nature Communications 8, 14538 (2017).
- [23] J. Scharlau and M. P. Mueller, Quantum Horn's lemma, finite heat baths, and the third law of thermodynamics, Quantum 2, 54 (2018).
- [24] P. Taranto, F. Bakhshinezhad, A. Bluhm, R. Silva, N. Friis, M. P. Lock, G. Vitagliano, F. C. Binder, T. Debarba, E. Schwarzhans, F. Clivaz, and M. Huber, Landauer Versus Nernst: What is the True Cost of Cooling a Quantum System?, PRX Quantum 4, 010332 (2023).
- [25] M. Plesch and V. Bužek, Efficient compression of quantum information, Physical Review A 81, 032317 (2010).
- [26] Y. Yang, G. Chiribella, and D. Ebler, Efficient Quantum Compression for Ensembles of Identically Prepared Mixed States, Physical Review Letters 116, 080501 (2016).
- [27] M. Hayashi, *Quantum Information Theory: Mathematical Foundation*, Graduate Texts in Physics (Springer, Berlin, Heidelberg, 2017).
- [28] R. Alicki, M. Horodecki, P. Horodecki, and R. Horodecki, Thermodynamics of quantum informational systems - Hamiltonian description (2004), arXiv:quantph/0402012.
- [29] P. Faist, F. Dupuis, J. Oppenheim, and R. Renner, The minimal work cost of information processing, Nature Communications 6, 7669 (2015).
- [30] In this work, we use the standard notations for asymptotics. For two positive functions f(n) and g(n), f(n) = O(g(n)) if  $\exists n_0, C > 0$  such that  $\forall n > n_0, f(n) \leq Cg(n)$ .  $f(n) = \Omega(g(n))$  if g(n) = O(f(n)).  $f(n) = \Theta(g(n))$  if f(n) = O(g(n)) and  $f(n) = \Omega(g(n))$ .
- [31] C. Bădescu and R. O'Donnell, Improved quantum data analysis, TheoretiCS Volume 3, 10924 (2024).
- [32] H.-Y. Huang, R. Kueng, and J. Preskill, Predicting many properties of a quantum system from very few measurements, Nature Physics 16, 1050 (2020).
- [33] C. W. Helstrom, Quantum detection and estimation theory, Journal of Statistical Physics 1, 231 (1969).
- [34] E. Fredkin and T. Toffoli, Conservative logic, International Journal of Theoretical Physics 21, 219 (1982).
- [35] M. A. Nielsen and I. L. Chuang, *Quantum Computation and Quantum Information* (Cambridge university press, 2010).
- [36] M. M. Wilde, *Quantum Information Theory* (Cambridge University Press, Cambridge, 2013).
- [37] R. Renner and S. Wolf, Smooth Renyi entropy and applications, in *International Symposium onInformation The*ory, 2004. ISIT 2004. Proceedings. (2004) pp. 233–.
- [38] R. Konig, R. Renner, and C. Schaffner, The Operational Meaning of Min- and Max-Entropy, IEEE Transactions on Information Theory 55, 4337 (2009).
- [39] R. Vershynin, *High-Dimensional Probability: An Introduction with Applications in Data Science*, Cambridge Series in Statistical and Probabilistic Mathematics

(Cambridge University Press, Cambridge, 2018).

- [40] H.-S. Kim, I. H. Kim, and D. Ranard, Learning State Preparation Circuits for Quantum Phases of Matter (2024), arXiv:2410.23544.
- [41] D. Poulin, A. Qarry, R. Somma, and F. Verstraete, Quantum simulation of time-dependent hamiltonians and the convenient illusion of hilbert space, Physical Review Letters 106, 170501 (2011).
- [42] J. Preskill, Quantum computing in the NISQ era and beyond, Quantum 2, 79 (2018), arXiv:1801.00862 [quantph].
- [43] B. M. Terhal and D. P. DiVincenzo, Adaptive Quantum Computation, Constant Depth Quantum Circuits and Arthur-Merlin Games (2004), arXiv:quant-ph/0205133.
- [44] X. Gao, S.-T. Wang, and L.-M. Duan, Quantum Supremacy for Simulating a Translation-Invariant Ising Spin Model, Physical Review Letters 118, 040502 (2017).
- [45] V. Giovannetti, S. Lloyd, and L. Maccone, Architectures for a quantum random access memory, Physical Review A 78, 52310 (2008).
- [46] J. Haferkamp, D. Hangleiter, A. Bouland, B. Fefferman, J. Eisert, and J. Bermejo-Vega, Closing Gaps of a Quantum Advantage with Short-Time Hamiltonian Dynamics, Physical Review Letters 125, 250501 (2020).
- [47] D. Hangleiter and J. Eisert, Computational advantage of quantum random sampling, Reviews of Modern Physics 95, 035001 (2023).
- [48] S. Bravyi, D. Gosset, and R. König, Quantum advantage with shallow circuits, Science 362, 308 (2018).
- [49] Z.-W. Liu and A. Winter, Many-Body Quantum Magic, PRX Quantum 3, 020333 (2022).
- [50] Y. Shi, Both Toffoli and Controlled-NOT need little help to do universal quantum computation (2002), arXiv:quant-ph/0205115.
- [51] S. Bravyi and A. Kitaev, Universal quantum computation with ideal Clifford gates and noisy ancillas, Physical Review A 71, 022316 (2005).
- [52] S. Aaronson and D. Gottesman, Improved Simulation of Stabilizer Circuits (2008), arXiv:quant-ph/0406196.
- [53] S. Bravyi and D. Gosset, Improved Classical Simulation of Quantum Circuits Dominated by Clifford Gates, Physical Review Letters 116, 250501 (2016).
- [54] S. Bravyi, D. Browne, P. Calpin, E. Campbell, D. Gosset, and M. Howard, Simulation of quantum circuits by lowrank stabilizer decompositions, Quantum 3, 181 (2019), arXiv:1808.00128 [quant-ph].
- [55] E. Knill, Fault-Tolerant Postselected Quantum Computation: Schemes (2004), arXiv:quant-ph/0402171.
- [56] E. Knill, R. Laflamme, and L. Viola, Theory of quantum error correction for general noise, Physical Review Letters 84, 2525 (2000).
- [57] A. Montanaro, Learning stabilizer states by Bell sampling (2017), arXiv:1707.04012 [quant-ph].
- [58] M. B. Hastings, An Area Law for One Dimensional Quantum Systems (2018), arXiv:0705.2024.
- [59] B. Zeng, X. Chen, D.-L. Zhou, and X.-G. Wen, *Quantum Information Meets Quantum Matter: From Quantum Entanglement to Topological Phases of Many-Body Systems*, Quantum Science and Technology (Springer, New York, NY, 2019).
- [60] I. Affleck, T. Kennedy, E. H. Lieb, and H. Tasaki, Rigorous results on valence-bond ground states in antiferromagnets, Physical Review Letters 59, 799 (1987).

- [61] C. L. Degen, F. Reinhard, and P. Cappellaro, Quantum sensing, Reviews of Modern Physics 89, 035002 (2017).
- [62] R. Jozsa, An introduction to measurement based quantum computation (2005), arXiv:quant-ph/0508124.
- [63] C. Schön, E. Solano, F. Verstraete, J. I. Cirac, and M. M. Wolf, Sequential generation of entangled multiqubit states, Physical Review Letters 95, 110503 (2005).
- [64] R. Raussendorf and H. J. Briegel, A One-Way Quantum Computer, Physical Review Letters 86, 5188 (2001).
- [65] M. J. Bremner, R. Jozsa, and D. J. Shepherd, Classical simulation of commuting quantum computations implies collapse of the polynomial hierarchy, Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences 467, 459 (2010).
- [66] M. J. Bremner, A. Montanaro, and D. J. Shepherd, Achieving quantum supremacy with sparse and noisy commuting quantum computations, Quantum 1, 8 (2017).
- [67] C. Gidney, Constructing Large Controlled Nots (2015).
- [68] Z. Ji, Y.-K. Liu, and F. Song, Pseudorandom Quantum States, in *Advances in Cryptology – CRYPTO 2018*, edited by H. Shacham and A. Boldyreva (Springer International Publishing, Cham, 2018) pp. 126–152.
- [69] F. Ma and H.-Y. Huang, How to construct random unitaries (2024), arXiv:2410.10116 [quant-ph].
- [70] O. Regev, On lattices, learning with errors, random linear codes, and cryptography, J. ACM 56, 34:1 (2009).
- [71] Here, we assume that the energy source is classical and can be measured deterministically. If the energy source is quantum, we can always measure the work cost to 1/poly(n) accuracy in polynomial time. Thus the work cost lower bound in the no-go result will change to  $W_{\text{Haar}} 1/\text{poly}(n)$ .
- [72] Y. Yang, Compression of quantum shallow-circuit states, Physical Review Letters 134, 010603 (2025), arXiv:2404.11177 [quant-ph].
- [73] A. Bérut, A. Arakelyan, A. Petrosyan, S. Ciliberto, R. Dillenschneider, and E. Lutz, Experimental verification of Landauer's principle linking information and thermodynamics, Nature 483, 187 (2012).
- [74] R. Gaudenzi, E. Burzurí, S. Maegawa, H. S. J. van der Zant, and F. Luis, Quantum Landauer erasure with a molecular nanomagnet, Nature Physics 14, 565 (2018).
- [75] M. Scandi, D. Barker, S. Lehmann, K. A. Dick, V. F. Maisi, and M. Perarnau-Llobet, Minimally Dissipative Information Erasure in a Quantum Dot via Thermodynamic Length, Physical Review Letters **129**, 270601 (2022).
- [76] J. V. Koski, V. F. Maisi, J. P. Pekola, and D. V. Averin, Experimental realization of a Szilard engine with a single electron, Proceedings of the National Academy of Sci-

ences 111, 13786 (2014).

- [77] M. D. Vidrighin, O. Dahlsten, M. Barbieri, M. S. Kim, V. Vedral, and I. A. Walmsley, Photonic Maxwell's Demon, Physical Review Letters **116**, 050401 (2016).
- [78] P. A. Camati, J. P. S. Peterson, T. B. Batalhão, K. Micadei, A. M. Souza, R. S. Sarthour, I. S. Oliveira, and R. M. Serra, Experimental Rectification of Entropy Production by Maxwell's Demon in a Quantum System, Physical Review Letters 117, 240502 (2016).
- [79] N. Cottet, S. Jezouin, L. Bretheau, P. Campagne-Ibarcq, Q. Ficheux, J. Anders, A. Auffèves, R. Azouit, P. Rouchon, and B. Huard, Observing a quantum Maxwell demon at work, Proceedings of the National Academy of Sciences 114, 7561 (2017).
- [80] A. Auffèves, Quantum Technologies Need a Quantum Energy Initiative, PRX Quantum 3, 020101 (2022).
- [81] A. Munson, N. B. T. Kothakonda, J. Haferkamp, N. Y. Halpern, J. Eisert, and P. Faist, Complexity-constrained quantum thermodynamics (2024), arXiv:2403.04828 [quant-ph].
- [82] L. Leone, J. Rizzo, J. Eisert, and S. Jerbi, Entanglement theory with limited computational resources (2025), arXiv:2502.12284 [quant-ph].
- [83] A. A. Mele and Y. Herasymenko, Efficient Learning of Quantum States Prepared With Few Fermionic Non-Gaussian Gates, PRX Quantum 6, 010319 (2025).
- [84] F. A. Mele, A. A. Mele, L. Bittel, J. Eisert, V. Giovannetti, L. Lami, L. Leone, and S. F. E. Oliviero, Learning quantum states of continuous variable systems (2024), arXiv:2405.01431 [quant-ph].
- [85] P. Hayden and J. Preskill, Black holes as mirrors: Quantum information in random subsystems, Journal of High Energy Physics 2007, 120 (2007).
- [86] A. Bouland, B. Fefferman, and U. Vazirani, Computational Pseudorandomness, the Wormhole Growth Paradox, and Constraints on the AdS/CFT Duality, in 11th Innovations in Theoretical Computer Science Conference (ITCS 2020), Leibniz International Proceedings in Informatics (LIPIcs), Vol. 151, edited by T. Vidick (Schloss Dagstuhl – Leibniz-Zentrum für Informatik, Dagstuhl, Germany, 2020) pp. 63:1–63:2.
- [87] C. Akers, A. Bouland, L. Chen, T. Kohler, T. Metger, and U. Vazirani, Holographic pseudoentanglement and the complexity of the AdS/CFT dictionary (2024), arXiv:2411.04978 [hep-th].
- [88] B. Swingle, G. Bentsen, M. Schleier-Smith, and P. Hayden, Measuring the scrambling of quantum information, Physical Review A 94, 040302 (2016).
- [89] L. Zdeborová and F. Krzakala, Statistical physics of inference: Thresholds and algorithms, Advances in Physics 65, 453 (2016).