

A Large-scale Class-level Benchmark Dataset for Code Generation with LLMs

Musfiqur Rahman
Concordia University
Montreal, Canada

musfiqur.rahman@mail.concordia.ca

SayedHassan Khatoonabadi
Concordia University
Montreal, Canada

sayedhassan.khatoonabadi@concordia.ca

Emad Shihab
Concordia University
Montreal, Canada

emad.shihab@concordia.ca

Abstract

Recent advancements in large language models (LLMs) have demonstrated promising capabilities in code generation tasks. However, most existing benchmarks focus on isolated functions and fail to capture the complexity of real-world, class-level software structures. To address this gap, we introduce a large-scale, Python class-level dataset curated from 13,174 real-world open-source projects. The dataset contains over 842,000 class skeletons, each including class and method signatures, along with associated docstrings when available. We preserve structural and contextual dependencies critical to realistic software development scenarios and enrich the dataset with static code metrics to support downstream analysis. To evaluate the usefulness of this dataset, we use extracted class skeletons as prompts for GPT-4 to generate full class implementations. Results show that the LLM-generated classes exhibit strong lexical and structural similarity to human-written counterparts, with average ROUGE@L, BLEU, and TSED scores of 0.80, 0.59, and 0.73, respectively. These findings confirm that well-structured prompts derived from real-world class skeletons significantly enhance LLM performance in class-level code generation. This dataset offers a valuable resource for benchmarking, training, and improving LLMs in realistic software engineering contexts.

CCS Concepts

• **Software and its engineering** → **Software libraries and repositories**; *Object oriented languages*; • **Computing methodologies** → **Natural language processing**.

Keywords

Large Language Models, Code Generation, Software Repository Mining, Benchmark Dataset

ACM Reference Format:

Musfiqur Rahman, SayedHassan Khatoonabadi, and Emad Shihab. 2025. A Large-scale Class-level Benchmark Dataset for Code Generation with LLMs. In *Proceedings of The 29th International Conference on Evaluation and Assessment in Software Engineering (EASE 2025)*. ACM, New York, NY, USA, 8 pages. <https://doi.org/10.1145/nmnnnnn.nmnnnnn>

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

EASE 2025, Istanbul, Türkiye

© 2025 Copyright held by the owner/author(s). Publication rights licensed to ACM.

ACM ISBN 978-x-xxxx-xxxx-x/YYYY/MM

<https://doi.org/10.1145/nmnnnnn.nmnnnnn>

1 Introduction

Recent advancements in large language models (LLMs) have led to the development of various code generation benchmarks [9, 10, 13, 23, 27, 29, 30, 32, 52]. However, these benchmarks often fail to capture the complexity inherent in real-world software development. In practice, functions typically rely on class attributes (i.e., variables and methods defined within a class that influence its behavior), external libraries (third-party or built-in modules such as NumPy), and project-specific dependencies (custom modules, configurations, or APIs unique to a software project). Without accounting for these factors, existing benchmarks provide only a partial assessment of LLMs' ability to generate realistic and structurally coherent code.

CoderEval [53] addresses this issue by including non-standalone functions that depend on contextual information from surrounding code, such as variables, functions, or classes within the same file or project. However, it remains limited to function-level evaluation and does not assess LLMs' ability to generate complete, cohesive class structures—an essential aspect of software engineering.

To bridge this gap, ClassEval [15] introduced a benchmark for class-level code generation. The results reveal that LLMs perform significantly worse on class-level tasks than on function-level ones. Nevertheless, ClassEval is limited by its small scale, consisting of only 100 handcrafted tasks, which restricts its generalizability to real-world development. Furthermore, the class docstrings in ClassEval are complete and well-structured, including example (*input*, *output*) pairs. In contrast, real-world open-source projects rarely contain such detailed documentation. Understanding the efficiency and limitations of LLMs in class-level code generation for real-world tasks has thus become increasingly important.

Several recent studies have explored the limitations of LLMs in handling more complex code generation tasks, such as those involving hierarchical dependencies (e.g., multiple inheritance), beyond simple function implementation [22, 28]. These studies report poor LLM performance due to limited reasoning capabilities [25] and the intricate dependency structures typical of real-world software systems [12]. However, to date, no systematic study has evaluated LLMs' capabilities in class-level code generation across real-world projects—likely due to the lack of a robust dataset designed for such analysis.

To address this gap, we propose a new dataset of Python classes curated from real-world open-source projects. We focus on Python, as it is currently the most widely used programming language, as evidenced by several existing benchmarks [9, 10, 13, 15, 29, 32, 52] and studies [18, 43, 48]. Unlike manually crafted datasets, our benchmark provides complex and diverse class structures, enabling a realistic and scalable assessment of LLMs' ability to generate

context-aware class-level code. This dataset contributes to the literature in the following ways:

- It is the first benchmark dataset derived from real-world projects specifically for LLM-assisted class-level code generation.
- Both the dataset and the scripts used for its curation are publicly available [11] to support reproducibility and facilitate future research.
- We outline a set of potential research questions that can be explored using this dataset.

The remainder of the paper is organized as follows. Section 2 describes the data curation process, including how class skeletons are extracted and processed from real-world projects. Section 3 details the evaluation methodology, where LLM-generated classes are compared against human-written counterparts. Section 4 discusses the implications of the dataset and outlines possible research questions. Sections 5 and 6 cover the dataset’s limitations and review related work in LLM-based code generation benchmarks, respectively. Finally, Section 7 concludes the paper and suggests directions for future research.

2 Dataset Curation

In this section, we describe the process followed to curate the dataset.

- *Step 1 - Project Selection:* To construct a comprehensive class-level dataset, we began by identifying all projects from the CodeSearchNet [26] dataset. CodeSearchNet consists of functions represented as (*comment*, *code*) pairs extracted from real-life open-source projects on GitHub. A *comment* refers to a top-level function docstring [1], and the *code* refers to the corresponding human-written function. Since our goal is to extract classes from real-world software, we selected CodeSearchNet as our source of projects. Moreover, CodeSearchNet is a widely adopted and reliable dataset, having been used in several prior works [7, 17, 20, 35, 38, 44, 49–51, 55] in the software engineering domain. This selection ensured diversity in software projects, covering different coding styles and application domains, thus making the dataset more representative for evaluating class-level code generation. This step returned 13,590 projects.
- *Step 2 - Repository Analysis:* After identifying the projects, we cloned each repository, preserving the complete structure and dependencies of the codebases. This step ensured that all relevant files were available for analysis and maintained the integrity of the original repositories while enabling large-scale processing. During this step, we found that 416 repositories were no longer available¹, so we proceeded with the remaining 13,174 repositories. To extract static software metrics [16], we used Understand™ by SciTools [4], a widely used tool for static code analysis. This analysis provided detailed insights into class complexity, inheritance depth, method cohesion, and other structural properties of the code. These metrics help characterize the dataset and provide valuable metadata for evaluating the complexity of class-level code generation [33, 34, 47]. As a result of this step, we identified 1,000,032 Python classes across the analyzed projects.

¹Repositories were cloned between March 8 and March 11, 2025.

- *Step 3 - Class Extraction:* We used Python’s `ast` [3] library to generate Abstract Syntax Trees (ASTs) by parsing all `.py` files within the cloned repositories. This approach enabled structured access to syntactic elements and allowed for systematic extraction of class structures without relying on brittle, string-based parsing. Working at the AST level ensured accurate identification of class definitions, method signatures, and associated components. From each `.py` file, we extracted class skeletons, including class and method signatures along with their corresponding docstrings. These skeletons provide a structured representation of the code, preserving essential class-level design patterns, method interactions, and documentation practices. In Table 1, we show an example class (first row) and the corresponding skeleton extracted from it (middle row).
 - *Step 4 - Post-processing:* After extracting class skeletons, we performed a post-processing step to refine the dataset. First, we removed all classes that were either (1) partially processed or (2) caused an exception during the skeleton extraction phase. Qualitative analysis revealed that these issues typically arose when code snippets did not adhere to Python 3 standards, such as using a `print` statement without parentheses (e.g., `print "..."`)—cases where AST generation failed. We filtered out these problematic classes, resulting in 842,656 correctly processed classes. No further filtration was applied; all of these classes are included in the final dataset.
- Next, we counted the number of program units within each class skeleton. Program units include classes and methods, which form the structural foundation of object-oriented code. We also determined how many of these units had associated docstrings. Since not all program units in real-world projects are documented, this analysis provides a key metric for assessing dataset quality. Based on these counts, researchers can easily filter out classes where all program units are documented (i.e., total program units = total docstrings) to focus on cleaner subsets. This helps ensure that LLMs receive consistent and meaningful documentation to guide code generation. This post-processing step improves dataset usability by allowing researchers to selectively work with better-structured, well-documented class skeletons. Table 2 presents descriptive statistics for various class properties, while Table 3 provides a structured overview of the dataset.

3 Evaluation

In this section, we evaluate the quality of the curated dataset in supporting class-level code generation with LLMs by using the extracted class skeletons as part of structured prompts.

3.1 Approach

- *Step 1 - Random Sampling:* We randomly select 100 classes from the dataset using a threshold based on the *Comment To Code Ratio*. Specifically, only classes with a ratio above the dataset’s average are considered. The rationale behind this criterion is that a higher *Comment To Code Ratio* typically indicates richer documentation, which provides LLMs with more contextual information to guide code generation.

Table 1: An Example Python Class from `codenerix/django-codenerix` [2]: from Human-written Class to Class Skeleton to LLM-generated Class.

Human-written Class	<pre>class SubdomainMiddleware(object): """ A middleware class that adds a ``subdomain`` attribute to the current request. """ def get_domain_for_request(self, request): """ Returns the domain that will be used to identify the subdomain part for this request. """ return get_domain() def process_request(self, request): """ Adds a ``subdomain`` attribute to the ``request`` parameter. """ domain, host = map(lower, (self.get_domain_for_request(request), request.get_host())) pattern = r'^(?:P<subdomain>.*?)\.)?%(?:.*)*?\$' % re.escape(domain) matches = re.match(pattern, host) if matches: request.subdomain = matches.group('subdomain') else: request.subdomain = None logger.warning('The_host_%s_does_not_belong_to_the_domain_%s,_' 'unable_to_identify_the_subdomain_for_this_request', request.get_host(), domain)</pre>
Class Skeleton	<pre>class SubdomainMiddleware(object): """ A middleware class that adds a ``subdomain`` attribute to the current request. """ def get_domain_for_request(self, request): """ Returns the domain that will be used to identify the subdomain part for this request. """ pass def process_request(self, request): """ Adds a ``subdomain`` attribute to the ``request`` parameter. """ pass</pre>
LLM-generated Class	<pre>class SubdomainMiddleware(object): """ A middleware class that adds a ``subdomain`` attribute to the current request. """ def get_domain_for_request(self, request): """ Returns the domain that will be used to identify the subdomain part for this request. """ return request.get_host().split(':')[0] # Get the domain without port def process_request(self, request): """ Adds a ``subdomain`` attribute to the ``request`` parameter. """ domain = self.get_domain_for_request(request) subdomain = domain.split('.')[0] if domain.count('.') > 1 else None request.subdomain = subdomain</pre>

Table 2: Summary Statistics of Extracted Classes

Property	Average	Standard Deviation	25% Percentile	Median	75% Percentile
No. of Methods	3.82	14.36	0.00	2.00	4.00
No. of Lines	79.18	377.37	8.00	25.00	69.00
No. of Code Lines	52.25	277.13	6.00	15.00	45.00
No. of Comment Lines	17.79	106.87	0.00	3.00	13.00
No. of Blank Lines	10.54	43.77	1.00	3.00	9.00
Comment To Code Ratio	0.45	1.33	0.00	0.13	0.56

Table 3: Data Dictionary for the Curated Class-level Dataset

Field	Description
id	An index for each data point starting at 0.
repository_name	Name of the GitHub repository.
file_path	Path to the file which holds the class in the repository.
class_name	Name of the class in the file.
comment_to_code_ratio	Comment to code ratio of the class.
human_written_class	Code snippet that implements the class, including all docstrings.
class_skeleton	Extracted class skeleton, including class and method signatures along with corresponding docstrings (if available).
total_program_units	The number of classes and methods in the extracted class skeleton.
total_doc_str	The number of program units in the class skeleton that have associated docstrings.
<i>Additional 27 static code metrics obtained from Understand™ by SciTools [4].</i>	

- *Step 2 - Code Generation:* The extracted class skeletons are used as part of the prompts provided to an LLM to generate the complete class implementation. In this study, we use GPT-4 [6], as it was the most cost-efficient among the top three best-performing models for programming tasks at the time of evaluation² [5]. The following prompt is used to generate the code:

You are an expert Python programmer who can correctly implement complete Python classes based on the provided class skeletons. Implement the following class. Do not explain the code. The given class skeleton is as follows:
[CLASS SKELETON]

We generate the entire class at once using a holistic generation approach, which has been reported to be the most effective class-level code generation strategy for GPT-4 [15]. In Table 1, we present an example of a class skeleton (middle row) and the corresponding complete implementation generated by the LLM (last row).

- *Step 3 - Similarity Measure:* The LLM-generated classes are compared to the human-written reference implementations using three metrics: *BLEU*, *ROUGE*, and *TSED*. Each of these metrics ranges from 0 to 1, with higher values indicating greater similarity between the generated and reference code. While *BLEU* and *ROUGE* assess textual similarity, *TSED* captures structural similarity based on abstract syntax tree (AST) transformations. These metrics provide a well-rounded evaluation of the quality of generated code. The metrics are described in further detail in the following section.

3.2 Evaluation Metrics

3.2.1 Textual Similarity. n-gram language models have been used to represent code in previous studies [8, 24]. Furthermore, they have been used to evaluate LLM-generated code in the literature [21]. Therefore, we leverage this type of representation to measure the textual similarities between LLM-generated classes and the corresponding human-written classes, which are measured using the following two metrics:

- *BLEU:* The BLEU (Bilingual Evaluation Understudy) score measures the similarity between a machine-generated text and a reference text by computing the precision of n-grams while applying a brevity penalty for shorter translations [36]. It is calculated as:

$$BLEU = BP \cdot \exp \left(\sum_{n=1}^N w_n \log p_n \right) \quad (1)$$

where p_n is the precision of n-grams up to length N , and w_n is the weight assigned to each n-gram (typically uniform). The brevity penalty BP adjusts for short translations and is defined as:

$$BP = \begin{cases} 1, & \text{if } c > r \\ e^{(1-r/c)}, & \text{if } c \leq r \end{cases} \quad (2)$$

where c is the candidate translation length and r is the reference length. In our findings, we report both individual precision values, p_n as well as the overall BLEU score.

- *ROUGE:* The ROUGE (Recall-Oriented Understudy for Gisting Evaluation) score measures the quality of generated text by comparing it to reference text using recall-based metrics [31]. The most common variant, ROUGE-N, computes the overlap of n-grams between the candidate and reference text:

$$ROUGE-N = \frac{\sum_{s \in \text{Ref}} \sum_{\text{gram}_n \in s} \text{Count}_{\text{match}}(\text{gram}_n)}{\sum_{s \in \text{Ref}} \sum_{\text{gram}_n \in s} \text{Count}(\text{gram}_n)} \quad (3)$$

where $\text{Count}_{\text{match}}(\text{gram}_n)$ is the number of overlapping n-grams, and $\text{Count}(\text{gram}_n)$ is the total number of n-grams in the reference.

Another common variant, ROUGE-L, considers the longest common subsequence (LCS) between the candidate and reference:

$$ROUGE-L = \frac{LCS(\text{Cand}, \text{Ref})}{\text{Length}(\text{Ref})} \quad (4)$$

where $LCS(\text{Cand}, \text{Ref})$ is the length of the longest common subsequence between the candidate and reference text. ROUGE is widely used for evaluating text summarization and other NLP tasks.

²Code generation was performed on March 15, 2025.

Although both BLEU and ROUGE scores determine the textual similarity between two bodies of text based on n-gram overlaps, they complement each other. BLEU is a precision-oriented metric while ROUGE is a recall-oriented metric. In our evaluation, we chose $n = 3$ for the upper bound of n-grams since it is evident from prior works [24, 42] that no additional information is gained with the n-gram representation of code for $n > 3$.

3.2.2 Structural Similarity. Recent works [37, 42] claim that a structural representation, such as graphs and trees, is a better representation of code than n-grams. Therefore, to determine the quality of the generated class from the code structure point of view, we compare the AST of the LLM-generated code against the AST of the corresponding human-written code. Following previous works [19, 21], we use a metric based on tree edit distance called the *Tree Similarity of Edit Distance (TSED)* [46].

TSED is a novel metric for assessing code similarity [45]. It operates in three stages: (1) converting code into ASTs, (2) computing the tree edit distance, and (3) normalizing the distance to a 0–1 scale. The tree edit distance measures the minimum number of edit operations (insertion, deletion, renaming) required to transform one AST (T_1) into another (T_2) defined as:

$$\Delta(T_1, T_2) = \min_{ops} \sum_{i=1}^n w(op_i) \quad (5)$$

where ops is a sequence of edit operations and $w(op_i)$ is the cost of each operation. Since the tree edit distance computation is an NP-hard problem, the *All Path Tree Edit Distance (APTED)* algorithm [40] is employed to optimize the process. APTED is a tree edit distance algorithm that generalizes path strategies beyond LRH (Left, Right, Heavy) by considering all possible path strategies. Unlike existing approaches [14, 39, 54], APTED computes the optimal all-path strategy by incrementally computing cost sums in a bottom-up manner, storing results in cost arrays, ensuring minimal cost.

To ensure interpretability, the raw distance is normalized using the largest AST node count:

$$TSED = \frac{\Delta(T_1, T_2)}{\max(\text{Nodes}(T_1), \text{Nodes}(T_2))} \quad (6)$$

The normalization accounts for the structural complexity of the code, providing a robust measure of code similarity.

It is to be noted that none of the three metrics described above directly determine the quality of the extracted class skeletons; rather, they determine the quality of the LLM-generated classes, which were generated based on the provided class skeletons. A high-quality LLM-generated code implies that the class skeleton provides enough context for accurate code generation. This experiment provides insights into LLM performance on class-level code generation, highlighting their ability to utilize structured documentation, such as class skeleton, effectively.

3.3 Findings

The results of our experiment are presented in Table 4. Our analysis shows that most LLM-generated classes exhibit a high degree of similarity to human-written ones across all three evaluation metrics. The best-performing classes closely resemble human-written

implementations in both wording and structure, while the lower-performing examples still maintain a reasonable level of similarity. Notably, the lowest 25th percentile score across all three metrics is 0.5, indicating that even the weakest outputs retain moderate alignment with the reference implementations.

- **ROUGE Scores:** ROUGE@1-gram achieves the highest average score (0.83), while ROUGE@3-gram yields the lowest (0.69), reflecting the expected decline in overlap as n-gram size increases. The median value of 0.82, particularly strong in ROUGE-L, suggests substantial lexical similarity. These results indicate that the LLM-generated code captures many of the same tokens and token sequences as the human-written versions. Shorter token overlaps are more common, whereas longer sequences are slightly less frequent.
- **BLEU Scores:** Precision@1-gram shows the highest average score (0.85), with a gradual decrease as n-gram size increases, consistent with the greater difficulty in matching longer token sequences exactly. The overall BLEU score averages 0.59, echoing the ROUGE findings—LLMs tend to generate content with strong token-level similarity, but exact longer-sequence matches are less common.
- **TSED Scores:** The average TSED score is 0.73, with a standard deviation of 0.11, indicating moderate structural similarity between the generated and reference classes. This suggests that LLMs generally produce class structures that are close to the original ones, with some degree of variation.

Overall, LLMs are effective at mimicking human-written classes, particularly in terms of short token sequences, but they face challenges with longer, more complex or hierarchical contexts. This observation aligns with prior findings that class-level code generation is significantly more difficult for LLMs due to longer context windows and hierarchical dependencies [15, 41]. Since the quality of LLM-generated code heavily depends on the provided prompt, these findings highlight the value of incorporating extracted class skeletons as context. This confirms that the curated dataset serves as a valuable resource for advancing class-level code generation with LLMs. Various potential use cases for this dataset are discussed in the next section.

4 Discussion

We discuss the implications and potential use cases of the curated dataset below.

4.1 Implications

The curated class-level dataset offers significant benefits for both researchers and practitioners in software engineering and LLM-based code generation.

- For researchers, this dataset provides a benchmark for evaluating LLMs on class-level code generation, addressing a critical gap in function-level benchmarks. By incorporating real-world class structures and documentation, it enables the study of context-aware code synthesis and object-oriented design principles.
- For practitioners, this dataset can aid in developing new LLM architectures, fine-tuning techniques, and retrieval-augmented generation (RAG) approaches tailored for class-level code generation. Developers can leverage it to train and fine-tune custom

Table 4: Various Similarity Metrics Comparing LLM-generated Classes against their Human-written Counterparts.

Metrics	ROUGE				BLEU				TSED
	ROUGE @ 1-gram	ROUGE @ 2-gram	ROUGE @ 3-gram	ROUGE-L	Precision @ 1-gram	Precision @ 2-gram	Precision @ 3-gram	BLEU Score	
Average	0.83	0.75	0.69	0.80	0.85	0.73	0.65	0.59	0.73
Standard Deviation	0.11	0.14	0.15	0.12	0.09	0.12	0.13	0.14	0.11
25th Percentile	0.77	0.66	0.60	0.73	0.81	0.68	0.59	0.50	0.64
Median	0.85	0.77	0.71	0.82	0.87	0.75	0.66	0.59	0.71
75th Percentile	0.91	0.85	0.81	0.90	0.92	0.81	0.74	0.69	0.80

AI assistants that generate maintainable, structured code, reducing boilerplate work and improving productivity.

Overall, this dataset enhances LLM evaluation as well as training in real-world software engineering, driving advancements in AI-driven software development and intelligent coding assistants.

4.2 Potential Research Questions

We list potential research questions that can be answered by leveraging the dataset we present in this paper. We do not claim this to be an exhaustive list.

- (1) *Why does the code-generation performance of LLMs drop for class-level generation?* Understanding this drop can help identify challenges in maintaining inter-method dependencies, encapsulation, and structural coherence, leading to improvements in LLM-based code synthesis.
- (2) *How does the size of the class affect the class-level code generation with LLMs?* Larger classes introduce more dependencies and complexity, which may challenge LLMs’ ability to retain long-range contextual information and generate structurally sound code.
- (3) *How does the length of context windows of LLMs affect the class-level code generation?* Context window size directly influences how much of the class skeleton LLMs can consider at once, impacting their ability to generate consistent and logically connected methods.
- (4) *To what extent can LLMs capture class hierarchy when generating class-level code?* Since class hierarchies define inheritance relationships and method overrides, evaluating LLMs on this aspect helps assess their object-oriented design understanding.
- (5) *Do LLMs perform better in generating standalone classes vs. non-standalone classes?* Comparing these two cases provides insights into how well LLMs handle context dependencies, which is crucial for generating real-world, interconnected software components.
- (6) *How can fine-tuning LLMs with only class-level code improve generation performance?* Fine-tuning on class-level data may enhance LLMs’ ability to generate structured, contextually aware code, potentially mitigating performance drops seen in standard models.
- (7) *To what extent can retrieval-augmented generation improve the quality of class-level code generation?* Investigating how metrics like complexity, coupling, and cohesion enhance context-aware retrieval and improve code generation quality can open avenues for future research.

5 Limitations

We discuss some limitations to be mindful of when using the dataset below.

One limitation of the dataset is incomplete documentation, as not all program units have docstrings, potentially affecting code generation quality for those classes. Additionally, the dataset may exhibit structural bias, as it is sourced from open-source projects that follow specific coding conventions and design patterns, which may not generalize well to diverse software engineering practices. Another concern is potential data contamination, as LLMs trained on publicly available repositories may have already seen parts of the dataset. However, we argue that these limitations open avenues for future research, such as improving code generation for undocumented code and mitigating structural bias by curating diverse datasets.

Another limitation is that we only compare LLM-generated classes against their human-written counterparts without verifying their functional correctness. First, we lack test cases for the human-written classes, preventing us from verifying whether the generated code functions correctly. Additionally, due to the diverse nature of real-world projects in our dataset, we do not have sufficient domain knowledge to manually create meaningful test cases, limiting our ability to measure correctness beyond structural similarity. Second, executing the generated classes would require installing multiple dependencies for each project, which is impractical given the scale and diversity of the dataset. Furthermore, in cases where classes involve inheritance, the corresponding parent classes must also be available for successful execution. Without a controlled execution environment, validating correctness through runtime testing remains infeasible.

Despite these limitations, comparing LLM-generated classes with human-written ones still offers valuable insights into structural coherence, class organization, and documentation alignment. Since the primary goal of this paper is to curate a class-level dataset rather than generate class-level code, we leave the evaluation of LLM-generated classes as future work. Researchers can build on this dataset by incorporating automatically generated test cases,

dynamic analysis techniques, or expert assessments to more rigorously assess the functional correctness of generated code.

6 Related Work

Evaluating large language models (LLMs) for code generation has led to the development of several benchmark datasets, primarily assessing functional correctness and code structure. However, most existing benchmarks focus on function-level code generation, leaving gaps in evaluating class-level and real-world software development scenarios.

HumanEval [13] is a widely used benchmark consisting of 164 hand-written Python programming problems with function signatures and test cases. It introduced Pass@k as an evaluation metric, measuring how often a model generates a correct solution within k attempts. While useful for function-level evaluation, it lacks inter-method dependencies and does not assess LLMs’ ability to generate structured code.

Mostly Basic Programming Problems (MBPP) [10] extends function-level evaluation with 974 Python programs, each paired with natural language descriptions and test cases. It supports both few-shot learning and fine-tuning, making it useful for studying LLMs’ adaptability. However, like HumanEval, it evaluates isolated function synthesis rather than full software components.

Multi-HumanEval [9] builds on HumanEval by introducing multilingual code generation benchmarks, covering over 10 programming languages. It assesses LLMs’ ability to generalize across languages and supports code translation and robustness testing. Despite its contributions, it still focuses on function-level tasks, leaving class-level generation unexplored.

ClassEval [15] is the first benchmark designed for class-level code generation, containing 100 manually crafted Python classes. It reveals that LLMs perform significantly worse on class-level tasks compared to function-level benchmarks. The study also shows that holistic generation (generating the full class at once) works better for advanced models like GPT-4, while incremental generation benefits weaker models.

Although these benchmarks improve LLM evaluation, they remain limited in real-world applicability due to reliance on manually curated datasets. To the best of our knowledge, ours is the first class-level benchmark dataset derived from real-world projects which should better reflect software engineering complexities. This dataset enables rigorous evaluation of LLMs on class-level code generation by providing real-world class structures, dependencies, and documentation.

7 Conclusion

In this paper, we introduced a large-scale, real-world dataset for class-level LLM-assisted code generation. Curated from over 13,000 open-source Python projects, the dataset includes more than 842,000 class skeletons enriched with structural information and documentation making it suitable for evaluating LLMs in practical software engineering scenarios. Evaluation using GPT-4 shows strong lexical and structural similarity between generated and human-written classes, highlighting the value of using class skeletons as prompt context. This dataset lays the foundation for future research in

class-level code generation and serves as a robust resource for training, benchmarking, and analysis. The dataset has been anonymously shared here [11].

References

- [1] 2006. Docstring - Wikipedia - en.wikipedia.org. <https://en.wikipedia.org/wiki/Docstring>. [Accessed 30-01-2024].
- [2] 2010. GitHub - tkaemming/django-subdomains: Subdomain helpers for the Django framework, including subdomain-based URL routing. - github.com. <https://github.com/tkaemming/django-subdomains>. [Accessed 20-03-2025].
- [3] 2013. ast - Abstract Syntax Trees - docs.python.org. <https://docs.python.org/3/library/ast.html>. [Accessed 28-02-2025].
- [4] 2024. Understand: The Software Developer’s Multi-Tool - scitools.com. <https://scitools.com/>. [Version 7.0, Build 1217, Accessed 28-02-2025].
- [5] 2025. LLM Leaderboard 2025 - vellum.ai. <https://www.vellum.ai/llm-leaderboard>. [Accessed 13-03-2025].
- [6] Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altmenschmidt, Sam Altman, Shyamal Anadkat, et al. 2023. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774* (2023).
- [7] Toufique Ahmed and Premkumar Devanbu. 2022. Multilingual training for software engineering. In *Proceedings of the 44th International Conference on Software Engineering*. 1443–1455.
- [8] Miltiadis Allamanis, Earl T Barr, Premkumar Devanbu, and Charles Sutton. 2018. A survey of machine learning for big code and naturalness. *ACM Computing Surveys (CSUR)* 51, 4 (2018), 1–37.
- [9] Ben Athiwaratkun, Sanjay Krishna Gouda, Zijian Wang, Xiaopeng Li, Yuchen Tian, Ming Tan, Wasi Uddin Ahmad, Shiqi Wang, Qing Sun, Mingyue Shang, et al. 2022. Multi-lingual evaluation of code generation models. *arXiv preprint arXiv:2210.14868* (2022).
- [10] Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, et al. 2021. Program synthesis with large language models. *arXiv preprint arXiv:2108.07732* (2021).
- [11] Anonymous Authors. 2025. Anonymous Github - anonymous.4open.science. <https://anonymous.4open.science/r/class-level-benchmark-dataset-B132/>. [Accessed 23-03-2025].
- [12] Ramakrishna Bairi, Atharv Sonwane, Aditya Kanade, Vageesh DC, Arun Iyer, Suresh Parthasarathy, Sriram Rajamani, B Ashok, and Shashank Shet. 2023. CodePlan: Repository-level Coding using LLMs and Planning.(2023). *arXiv preprint cs.SE/2309.12499* (2023).
- [13] Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde De Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. 2021. Evaluating large language models trained on code. *arXiv preprint arXiv:2107.03374* (2021).
- [14] Erik D Demaine, Shay Mozes, Benjamin Rossman, and Oren Weimann. 2009. An optimal decomposition algorithm for tree edit distance. *ACM Transactions on Algorithms (TALG)* 6, 1 (2009), 1–19.
- [15] Xueying Du, Mingwei Liu, Kaixin Wang, Hanlin Wang, Junwei Liu, Yixuan Chen, Jiayi Feng, Chaofeng Sha, Xin Peng, and Yiling Lou. 2023. Classeval: A manually-crafted benchmark for evaluating llms on class-level code generation. *arXiv preprint arXiv:2308.01861* (2023).
- [16] Norman E Fenton and Martin Neil. 2000. Software metrics: roadmap. In *Proceedings of the Conference on the Future of Software Engineering*. 357–370.
- [17] Zi Gong, Yinpeng Guo, Pingyi Zhou, Cuiyun Gao, Yasheng Wang, and Zenglin Xu. 2022. MultiCoder: Multi-Programming-Lingual Pre-Training for Low-Resource Code Completion. *arXiv preprint arXiv:2212.09666* (2022).
- [18] Danielle Gonzalez, Thomas Zimmermann, and Nachiappan Nagappan. 2020. The state of the ml-universe: 10 years of artificial intelligence & machine learning software development on github. In *Proceedings of the 17th International conference on mining software repositories*. 431–442.
- [19] Suriya Gunasekar, Yi Zhang, Jyoti Aneja, Caio César Teodoro Mendes, Allie Del Giorno, Sivakanth Gopi, Mojan Javaheripi, Piero Kauffmann, Gustavo de Rosa, Olli Saarikivi, et al. 2023. Textbooks are all you need. *arXiv preprint arXiv:2306.11644* (2023).
- [20] Daya Guo, Shuai Lu, Nan Duan, Yanlin Wang, Ming Zhou, and Jian Yin. 2022. Unixcoder: Unified cross-modal pre-training for code representation. *arXiv preprint arXiv:2203.03850* (2022).
- [21] Kai Hartung, Sambit Mallick, Sören Gröttrup, and Munir Georges. 2024. Evaluation Metrics in LLM Code Generation. In *International Conference on Text, Speech, and Dialogue*. Springer, 214–226.
- [22] Junda He, Christoph Treude, and David Lo. 2024. LLM-Based Multi-Agent Systems for Software Engineering: Literature Review, Vision and the Road Ahead. *ACM Transactions on Software Engineering and Methodology* (2024).

- [23] Dan Hendrycks, Steven Basart, Saurav Kadavath, Mantas Mazeika, Akul Arora, Ethan Guo, Collin Burns, Samir Puranik, Horace He, Dawn Song, et al. 2021. Measuring coding challenge competence with apps. *arXiv preprint arXiv:2105.09938* (2021).
- [24] Abram Hindle, Earl T Barr, Mark Gabel, Zhendong Su, and Premkumar Devanbu. 2016. On the naturalness of software. *Commun. ACM* 59, 5 (2016), 122–131.
- [25] Jie Huang and Kevin Chen-Chuan Chang. 2022. Towards reasoning in large language models: A survey. *arXiv preprint arXiv:2212.10403* (2022).
- [26] Hamel Husain, Ho-Hsiang Wu, Tiferet Gazit, Miltiadis Allamanis, and Marc Brockschmidt. 2019. Codesearchnet challenge: Evaluating the state of semantic code search. *arXiv preprint arXiv:1909.09436* (2019).
- [27] Srinivasan Iyer, Ioannis Konstas, Alvin Cheung, and Luke Zettlemoyer. 2018. Mapping language to code in programmatic context. *arXiv preprint arXiv:1808.09588* (2018).
- [28] Juyong Jiang, Fan Wang, Jiasi Shen, Sungju Kim, and Sunghun Kim. 2024. A survey on large language models for code generation. *arXiv preprint arXiv:2406.00515* (2024).
- [29] Yuhang Lai, Chengxi Li, Yiming Wang, Tianyi Zhang, Ruiqi Zhong, Luke Zettlemoyer, Wen-tau Yih, Daniel Fried, Sida Wang, and Tao Yu. 2023. DS-1000: A natural and reliable benchmark for data science code generation. In *International Conference on Machine Learning*. PMLR, 18319–18345.
- [30] Yujia Li, David Choi, Junyoung Chung, Nate Kushman, Julian Schrittwieser, Rémi Leblond, Tom Eccles, James Keeling, Felix Gimeno, Agustin Dal Lago, et al. 2022. Competition-level code generation with alphacode. *Science* 378, 6624 (2022), 1092–1097.
- [31] Chin-Yew Lin. 2004. Rouge: A package for automatic evaluation of summaries. In *Text summarization branches out*. 74–81.
- [32] Jiawei Liu, Chunqiu Steven Xia, Yuyao Wang, and Lingming Zhang. 2023. Is your code generated by chatgpt really correct? rigorous evaluation of large language models for code generation. *Advances in Neural Information Processing Systems* 36 (2023), 21558–21572.
- [33] Alan MacCormack, John Rusnak, and Carliss Y Baldwin. 2006. Exploring the structure of complex software designs: An empirical study of open source and proprietary code. *Management Science* 52, 7 (2006), 1015–1030.
- [34] Alan MacCormack and Daniel J Sturtevant. 2016. Technical debt and system architecture: The impact of coupling on defect-related activity. *Journal of Systems and Software* 120 (2016), 170–182.
- [35] Arvind Neelakantan, Tao Xu, Raul Puri, Alec Radford, Jesse Michael Han, Jerry Tworek, Qiming Yuan, Nikolas Tezak, Jong Wook Kim, Chris Hallacy, et al. 2022. Text and code embeddings by contrastive pre-training. *arXiv preprint arXiv:2201.10005* (2022).
- [36] Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2002. Bleu: a method for automatic evaluation of machine translation. In *Proceedings of the 40th annual meeting of the Association for Computational Linguistics*. 311–318.
- [37] Profir-Petru Pârtaçi and Mahito Sugiyama. 2024. Bringing Structure to Naturalness: On the Naturalness of ASTs. In *Proceedings of the 2024 IEEE/ACM 46th International Conference on Software Engineering: Companion Proceedings*. 378–379.
- [38] Jan Pašek, Jakub Sido, Miloslav Konopík, and Ondřej Pražák. 2022. MQDD: Pre-training of Multimodal Question Duplication Detection for Software Engineering Domain. *arXiv preprint arXiv:2203.14093* (2022).
- [39] Mateusz Pawlik and Nikolaus Augsten. 2015. Efficient computation of the tree edit distance. *ACM Transactions on Database Systems (TODS)* 40, 1 (2015), 1–40.
- [40] Mateusz Pawlik and Nikolaus Augsten. 2016. Tree edit distance: Robust and memory-efficient. *Information Systems* 56 (2016), 157–173.
- [41] Musfiqur Rahman, SayedHassan Khatoomabadi, Ahmad Abdellatif, and Emad Shihab. 2024. Automatic detection of llm-generated code: A case study of claude 3 haiku. *arXiv preprint arXiv:2409.01382* (2024).
- [42] Musfiqur Rahman, Dharani Palani, and Peter C Rigby. 2019. Natural software revisited. In *2019 IEEE/ACM 41st International Conference on Software Engineering (ICSE)*. IEEE, 37–48.
- [43] Sebastian Raschka, Joshua Patterson, and Corey Nolet. 2020. Machine learning in python: Main developments and technology trends in data science, machine learning, and artificial intelligence. *Information* 11, 4 (2020), 193.
- [44] Iman Saberi, Fatemeh Fard, and Fuxiang Chen. 2023. Utilization of Pre-trained Language Model for Adapter-based Knowledge Transfer in Software Engineering. *arXiv preprint arXiv:2307.08540* (2023).
- [45] Yewei Song, Saad Ezzini, Xunzhu Tang, Cedric Lothritz, Jacques Klein, Tegawendé Bissyandé, Andrey Boytsov, Ulrick Ble, and Anne Goujon. 2024. Enhancing Text-to-SQL translation for financial system design. In *Proceedings of the 46th International Conference on Software Engineering: Software Engineering in Practice*. 252–262.
- [46] Yewei Song, Cedric Lothritz, Daniel Tang, Tegawendé F Bissyandé, and Jacques Klein. 2024. Revisiting code similarity evaluation with abstract syntax tree edit distance. *arXiv preprint arXiv:2404.08817* (2024).
- [47] Daniel Joseph Sturtevant. 2013. *System design and the cost of architectural complexity*. Ph. D. Dissertation. Massachusetts Institute of Technology.
- [48] Sarvar Sultonov. 2023. IMPORTANCE OF PYTHON PROGRAMMING LANGUAGE IN MACHINE LEARNING. *International Bulletin of Engineering and Technology* 3, 9 (2023), 28–30.
- [49] Yue Wang, Hung Le, Akhilesh Deepak Gotmare, Nghi DQ Bui, Junnan Li, and Steven CH Hoi. 2023. Codet5+: Open code large language models for code understanding and generation. *arXiv preprint arXiv:2305.07922* (2023).
- [50] Yutao Yang, Jie Zhou, Xuanwen Ding, Tianyu Huai, Shunyu Liu, Qin Chen, Yuan Xie, and Liang He. 2025. Recent advances of foundation language models-based continual learning: A survey. *Comput. Surveys* 57, 5 (2025), 1–38.
- [51] Zezhou Yang, Sirong Chen, Cuiyun Gao, Zhenhao Li, Xing Hu, Kui Liu, and Xin Xia. 2025. An Empirical Study of Retrieval-Augmented Code Generation: Challenges and Opportunities. *ACM Transactions on Software Engineering and Methodology* (2025).
- [52] Pengcheng Yin, Bowen Deng, Edgar Chen, Bogdan Vasilescu, and Graham Neubig. 2018. Learning to mine aligned code and natural language pairs from stack overflow. In *Proceedings of the 15th international conference on mining software repositories*. 476–486.
- [53] Hao Yu, Bo Shen, Dezhi Ran, Jiaxin Zhang, Qi Zhang, Yuchi Ma, Guangtai Liang, Ying Li, Qianxiang Wang, and Tao Xie. 2024. Codereval: A benchmark of pragmatic code generation with generative pre-trained models. In *Proceedings of the 46th IEEE/ACM International Conference on Software Engineering*. 1–12.
- [54] Kaizhong Zhang and Dennis Shasha. 1989. Simple fast algorithms for the editing distance between trees and related problems. *SIAM journal on computing* 18, 6 (1989), 1245–1262.
- [55] Ziyin Zhang, Chaoyu Chen, Bingchang Liu, Cong Liao, Zi Gong, Hang Yu, Jianguo Li, and Rui Wang. 2023. Unifying the perspectives of nlp and software engineering: A survey on language models for code. *arXiv preprint arXiv:2311.07989* (2023).