# Quantum *m*-out-of-*n* Oblivious Transfer<sup>\*</sup>

Zhide Chen, Hong Zhu

Department of Computer Science, Fudan University, Shanghai 200433, P.R.China.

Key Laboratory of Intelligent Information Processing, Fudan University, Shanghai 200433, P.R.China.

{02021091, hzhu}@fudan.edu.cn

#### Abstract

In the m-out-of-n Oblivious Transfer (OT) model, one party Alice sends n bits to another party Bob, Bob can get only m bits from the n bits. However, Alice cannot know which m bits Bob received. Y.Mu and Naor presented classical m-out-of-n Oblivious Transfer based on discrete logarithm. As the work of Shor, the discrete logarithm can be solved in polynomial time by quantum computers, so such OTs are unsecure to the quantum m-out-of-n OT (QOT) scheme based on the transmission of polarized light and show that the scheme is robust to general attacks, i.e. the QOT scheme satisfies statistical correctness and statistical privacy.

Keywords. Quantum, Oblivious Transfer.

## 1 Introduction

A number of recent papers have provided compelling evidence that certain computational, cryptographic, and information theoretic tasks can be performed more efficiently by models based on quantum physics than those based on classical physics [9].

Oblivious Transfer (OT) is used as a key component in many applications of cryptography [11, 5, 10]. Informally speaking in an Oblivious Transfer, *Alice* sends a bit to *Bob* that he receives half the time (this fact is out of their control), *Alice* does not find out what happened, *Bob* knows if he get the bit or nothing. Similarly, in a 1-out-of-2 Oblivious Transfer, *Alice* has two bits  $b_0$ ,  $b_1$  that she sends to *Bob* in such a way that he can decide to get either of them at his choosing but not both. *Alice* never finds out which bit *Bob* received.

In 2001, Naor presented a 1-out-of-n Oblivious Transfer [8], Y.Mu showed that *m*-out-of-*n* Oblivious Transfer could also be realized based on the discrete logarithm. In the *m*-out-of-*n* Oblivious Transfer( $1 \le m < n$ ), Alice sends *n* bits to Bob, Bob can get only *m* of them. In the case of quantum, Claude Crépeau provided a 1-out-of-2 quantum Oblivious Transfer based on the transmission of polarized light in 1994. The protocol of Crépeau's can be used directly to implement a one-out-of-three Oblivious Transfer.

The organization of this paper is as following: in section 2, we give the definitions of the correctness and privacy of the *m*-out-of-*n* OT protocol. In section 3, we review the 1-out-of-2 OT of Claude Crépeau and its intuition. In section 4, we construct an *m*-out-of-*n* OT, and in section 5 we show that this scheme satisfies statistical correctness and statistical privacy.

# 2 Definitions

The natural constraints (see below) of correctness and privacy of a *m*-out-of- $n \text{ OT}(1 \le m < n)$  is showed below.

**Definition 2.1** *Perfect Correctness:* It should be that when Alice and Bob follow the protocol and start with Alice's input bits  $b_1, b_2, \dots, b_n$  and Bob's input  $c_1, c_2, \dots, c_m \in \{1, 2, \dots, n\}$ , they finish with Bob getting  $b_{c_1}, b_{c_2}, \dots, b_{c_m} \in \{b_1, b_2, \dots, b_n\}$ .

**Definition 2.2** *Perfect Privacy:* It should be that, Alice can not find out about  $c_1, c_2, \ldots, c_m$ , and Bob can not find out more than m of  $b_1, b_2, \ldots, b_n$ .

The protocol we describe in the next section is of probabilistic nature. We cannot show that this protocol perfectly satisfies the above constraints but satisfies in a statistical sense: after an amount of work in

<sup>\*</sup>This work is partially supported by a grant from the Ministry of Science and Technology (#2001CCA03000), National Natural Science Fund (#60273045) and Shanghai Science and Technology Development Fund (#03JC14014).

O(N) time the protocol will satisfy for some positive constant  $\epsilon < 1$ .

**Definition 2.3** Statistical Correctness: It should be that, except with probability at most  $\varepsilon^N$ , when Alice and Bob follow the protocol and start with Alice's input bits  $b_1, b_2, \ldots, b_n$  and Bob's input  $c_1, c_2, \ldots, c_m \in \{1, 2, \cdots, n\}$  they finish with Bob getting  $b_{c_1}, b_{c_2}, \cdots, b_{c_m} \in \{b_1, b_2, \cdots, b_n\}$ .

**Definition 2.4** Statistical Privacy: It should be that, except with probability at most  $\epsilon^N$ , Alice can not find out  $c_1, c_2, \ldots, c_m$ , and Bob can not find out more than m of  $b_1, b_2, \ldots, b_n$ .

# 3 Quantum 1-out-of-2 Oblivious Transfer

In this section, we introduce the quantum 1-outof-2 OT provided by Claude Crépeau [3]. Let () denote the random variable that takes the binary value 0 with probability 1/2 and 1 with probability 1/2. Also, denote by []<sub>i</sub> the selection function such that  $[a_0, a_1, \dots, a_k]_i = a_i$ . Let  $\bigoplus = (|\leftrightarrow\rangle, |\downarrow\rangle)$  and  $\bigotimes = (|\searrow\rangle, |\swarrow\rangle)$  denote respectively the bases of rectilinear and diagonal polarization in the quantum state space of a photon. The quantum 1-out-of-2 OT is as follows:

### 3.1 Quantum 1-out-of-2 OT

**Protocol 3.1** *1-out-of-2*  $OT(b_0, b_1)(c)$ 

1.  $DO_{i=1}^{2n}$ 

- Alice picks a random bit  $r_i \leftarrow \textcircled{}$
- Alice picks a random bit β<sub>i</sub> ← €and defines her emission basis (|φ<sub>i</sub>⟩, |φ<sub>i</sub><sup>⊥</sup>⟩) ← [♣, ℵ]<sub>β<sub>i</sub></sub>
- Alice sends to Bob a photon π<sub>i</sub> with polarization [|φ<sub>i</sub>⟩, |φ<sup>⊥</sup><sub>i</sub>⟩]<sub>r<sub>i</sub></sub>
- Bob picks a random bit  $\beta'_i \leftarrow \textcircled{}$  and measures  $\pi_i$  in basis  $(|\theta_i\rangle, |\theta_i^{\perp}\rangle) \leftarrow [\textcircled{}, \widecheck{}]_{\beta'}$
- Bob  $r'_i \leftarrow \begin{cases} 0, & \text{if } \pi_i \text{ is observed as } |\theta_i\rangle \\ 1, & \text{if } \pi_i \text{ is observed as } |\theta_i^{\perp}\rangle \end{cases}$ sets

2. 
$$DO_{i=1}^{n}$$

- Bob runs  $commit(r'_i)$ ,  $commit(\beta'_i)$ ,  $commit(r'_{n+i})$ ,  $commit(\beta'_{n+i})$  with Alice
- Alice picks  $c_i \leftarrow \textcircled{C}$  and announces it to Bob
- Bob runs  $unveil(r'_{nc_i+i}), unveil(\beta'_{nc_i+i})$

- Alice checks that  $\beta_{nc_i+i} = \beta'_{nc_i+i} \rightarrow r_{nc_i+i} = r'_{nc_i+i}$
- if  $c_i = 0$  then Alice sets  $\beta_i \leftarrow \beta_{n+i}$  and  $r_i \leftarrow r_{n+i}$  and Bob set  $\beta'_i \leftarrow \beta'_{n+i}$  and  $r'_i \leftarrow r'_{n+i}$
- 3. Alice announces her choices  $\beta_1\beta_2\cdots\beta_n$  to Bob
- 4. Bob randomly selects two subsets  $I_0, I_1 \subset \{1, 2, \dots, n\}$  subject to  $|I_0| = |I_1| = n/3, I_0 \cap I_1 = \emptyset$  and  $\forall i \in I_c, \beta_i = \beta'_i$ , and he announces  $\langle I_0, I_1 \rangle$  to Alice
- 5. Alice receives  $\langle J_0, J_1 \rangle = \langle I_0, I_1 \rangle$ , computes and sends  $\hat{b}_0 \leftarrow b_0 \oplus \bigoplus_{j \in J_0} r_j$  and  $\hat{b}_1 \leftarrow b_1 \oplus \bigoplus_{j \in J_1} r_j$
- 6. Bob receives  $\langle \hat{b}_0, \hat{b}_1 \rangle$  and computes  $b_c \leftarrow \hat{b}_c \oplus \bigoplus_{j \in J_c} r'_j$

#### 3.2 Intuition behind 1-out-of-2 OT

In this 1-out-of-2 QOT, Alice must prevent Bob from storing the photons and waiting until she discloses the bases before measuring them, which would allow him to obtain both of Alice's bits with certainty. To realize this, Alice gets Bob to commit to the bits that he received and the bases that he used to measure them. Before going ahead with  $r_i$ , say, Alice checks that Bob had committed properly to  $r_{n+i}$  when he read that bit in the basis that she used to encode it. If at any stage Alice observes a mistake  $(\beta_{n+i} = \beta'_{n+i})$ but  $r_{n+i} \neq r'_{n+i}$ , she stops further interaction with Bob who is definitely not performing his legal protocol (this should never happen if Bob follows his protocol).

In this protocol,  $r_1r_2\cdots r_n$  are chosen by *Alice* in step 1 and are sent to *Bob* via an ambiguous coding referred to as the BB84 coding [1]: when *Alice* and *Bob* choose the same emission and reception basis, the bit received is the same as what was sent and uncorrelated otherwise. *Bob* builds two subsets: one  $I_c$  that will allow him to get  $b_c$ , and one  $I_{\overline{c}}$  that will spoil  $b_{\overline{c}}$ . The calculations of steps 5-6 are much that all the bits in a subset must be known by *Bob* in order for him to be able to obtain the output bit connected to that subset.

# 4 Protocol for Quantum *m*-out-of-*n* Oblivious Transfer

#### 4.1 Weak Bit Commitment

In 1993, Gilles Brassard, etc provided a quantum bit commitment scheme provably unbreakable by both parties [2]. However, unconditionally quantum bit commitment was showed impossible [7]. In [4], Aharonov provided a weak bit commitment.

**Definition 4.1** [4] In the weak bit commitment protocol, the following requirements should hold.

- If both Alice and Bob are honest, then both Alice and Bob accept.
- (Binding) If Alice tries to change her mind about the value of b, then there is non zero probability that an honest Bob would reject.
- (Sealing) If Bob attempts to learn information about the deposited bit b, then there is non zero probability that an honest Alice would reject.

In the following scheme, *Bob* will use this weak quantum bit commitment to commit.

## 4.2 Intuition for *m*-out-of-*n* OT

In the *m*-out-of-*n* OT, Bob should build *n* subsets  $I_1, I_2, \ldots, I_n \subseteq \{1, 2, \cdots, n\}, m$  of that will allow him to get  $b_{c_1}, b_{c_2}, \ldots, b_{c_m}$   $(c_1, c_2, \ldots, c_m \in \{1, 2, \ldots, n\})$ , and the other *I*'s will spoil the remnant *b*'s. In  $I_1 \cup I_2 \cup \cdots \cup I_n$ , the rate of the *i*'s satisfying  $\beta'_i = \beta_i$  would be more than  $\frac{m}{n}$  and less than  $\frac{m+1}{n}$ . i.e.

$$\frac{m}{n} \le \frac{\#\{i|\beta_i = \beta'_i, i \in I_1 \cup \dots \cup I_n\}}{|I_1 \cup \dots \cup I_n|} < \frac{m+1}{n}$$

In our scheme, we let the rate to be  $\frac{\frac{m}{n} + \frac{m+1}{n}}{2} = \frac{2m+1}{2n}$ . As  $\beta$ 's and  $\beta$ 's are choice randomly, we have

$$\lim_{N \to \infty} \frac{\#\{\beta_i = \beta'_i\}}{N} = \frac{1}{2}.$$

For a large N, the rate of *i*'s in  $\{1, 2, \dots, N\}$  that satisfy  $\beta'_i = \beta_i$  would be approximately  $\frac{1}{2}$ , then *Bob* should remove some *i*'s from the  $\{1, 2, \dots, N\}$ . The number of *i*'s that should be removed can be calculated as following:

If  $\frac{2m+1}{2n} < \frac{1}{2}$ , there are more *i*'s that satisfy  $\beta'_i = \beta_i$  than required, so *Bob* should remove *x i*'s that satisfying  $\beta'_i = \beta_i$  from  $\{1, 2, \dots, N\}$ . *x* can be calculated as follows:

$$\frac{\frac{N}{2} - x}{N - x} = \frac{2m + 1}{2n}$$
$$x = \frac{n - (2m + 1)}{2n - (2m + 1)}N$$

If  $\frac{2m+1}{2n} \geq \frac{1}{2}$ , there are more *i*'s that satisfy  $\beta'_i \neq \beta_i$  than required, so *Bob* should remove *x i*'s that satisfying  $\beta'_i \neq \beta_i$  from  $\{1, 2, \dots, N\}$ . *x* can be calculated as follows:

$$\frac{\frac{N}{2}}{N-x} = \frac{2m+1}{2n}$$
$$x = \frac{(2m+1)-n}{2m+1}N$$

N must satisfy (2n-(2m+1))(2m+1)|((2m+1)-n)Nso that x would be an interger. we let the *i*'s that was removed from  $\{1, 2, \dots, N\}$  be  $u_1, u_2, \dots, u_x$ .

#### 4.3 Quantum *m*-out-of-*n* OT

In the *m*-out-of-*n* QOT, Alice has input  $b_1, b_2, \dots, b_n$ , Bob has input  $c_1, c_2, \dots, c_m$ . The output of the scheme is  $b_{c_1}, b_{c_2}, \dots, b_{c_m}$ .

**Protocol 4.1** *m*-out-of-*n*  $QOT(b_1, b_2, \ldots, b_n)(c_1, c_2, \ldots, c_m)$ 

- 1.  $DO_{i=1}^{2N}$ 
  - Alice picks a random bit  $r_i \leftarrow \textcircled{C}$
  - Alice picks a random bit β<sub>i</sub> ← € and defines her emission basis (|φ<sub>i</sub>⟩, |φ<sub>i</sub><sup>⊥</sup>⟩) ← [⊕, ⊠]<sub>β<sub>i</sub></sub>
  - Alice sends to Bob a photon π<sub>i</sub> with polarization [|φ<sub>i</sub>⟩, |φ<sup>⊥</sup><sub>i</sub>⟩]<sub>r<sub>i</sub></sub>
  - Bob picks a random bit β'<sub>i</sub> ← € and measures π<sub>i</sub> in basis (|θ<sub>i</sub>⟩, |θ<sup>⊥</sup><sub>i</sub>⟩) ← [Φ, X]<sub>β'</sub>
  - Bob  $r'_i \leftarrow \begin{cases} 0, & \text{if } \pi_i \text{ is observed as } |\theta_i\rangle \\ 1, & \text{if } \pi_i \text{ is observed as } |\theta_i^{\perp}\rangle \end{cases}$ sets
- 2.  $DO_{i=1}^N$ 
  - Bob runs  $commit(r'_i)$ ,  $commit(\beta'_i)$ ,  $commit(r'_{N+i})$ ,  $commit(\beta'_{N+i})$  with Alice
  - Alice picks  $d_i \leftarrow \textcircled{}$  and announces it to Bob
  - Bob runs  $unveil(r'_{Nd_i+i}), unveil(\beta'_{Nd_i+i})$
  - Alice checks that  $\beta_{Nd_i+i} = \beta'_{Nd_i+i} \rightarrow r_{Nd_i+i} = r'_{Nd_i+i}$
  - if  $d_i = 0$  then Alice sets  $\beta_i \leftarrow \beta_{N+i}$  and  $r_i \leftarrow r_{N+i}$  and Bob set  $\beta'_i \leftarrow \beta'_{N+i}$  and  $r'_i \leftarrow r'_{N+i}$
- 3. Alice announces her choices  $\beta_1\beta_2\cdots\beta_N$  to Bob
- 4.  $DO_{i=1}^{x}$

- If  $\frac{2m+1}{2n} < \frac{1}{2}$  Bob runs  $unveil(r'_{u_j})$ , unveil $(\beta'_{u_j})$  that satisfying  $\beta_{u_j} = \beta'_{u_j}$ , Alice checks that  $\beta_{u_j} = \beta'_{u_j} \rightarrow r_{u_j} = r'_{u_j}$
- If  $\frac{2m+1}{2n} \geq \frac{1}{2}$  Bob runs  $unveil(r'_{u_j})$ ,  $unveil(\beta'_{u_j})$  that satisfying  $\beta_{u_j} \neq \beta'_{u_j}$
- 5. Bob randomly selects n subsets  $I_1, I_2, \dots, I_n \subset \{1, 2, \dots, N\} \{u_1, u_2, \dots, u_x\}$  subject to  $|I_1| = |I_2| = \dots = |I_n| = (N-x)/n, \forall j \neq k, I_j \cap I_k = \emptyset$ and  $\forall j \in I_{c_1} \cup I_{c_2} \cup \dots \cup I_{c_m}, \beta_j = \beta'_j$ , and he announces  $\langle I_1, I_2, \dots, I_n \rangle$  to Alice
- 6. Alice receives  $\langle J_1, J_2, \cdots, J_n \rangle = \langle I_1, I_2, \cdots, I_n \rangle$ , computes and sends  $\hat{b}_1 \leftarrow b_1 \oplus \bigoplus_{j \in J_1} r_j$ ,  $\hat{b}_2 \leftarrow b_2 \oplus \bigoplus_{j \in J_2} r_j$ ,  $\cdots$ ,  $\hat{b}_n \leftarrow b_n \oplus \bigoplus_{j \in J_n} r_j$  to Bob
- 7. Bob receives  $\langle \hat{b}_1, \hat{b}_2, \cdots, \hat{b}_n \rangle$  and computes  $b_{c_i} \leftarrow \hat{b}_{c_i} \oplus \bigoplus_{j \in J_{c_i}} r'_{c_j}, i = 1, 2, \cdots, m$

## 5 Analysis

In the *m*-out-of-*n QOT*, Bob must read the photons sent by Alice as they come: he cannot wait and read them later, individually or together. We assume that the channel used for the quantum transmission is free of errors, so that it is guaranteed that  $r'_i = r_i$  whenever  $\beta'_i = \beta_i$ . we now show that under the assumption this protocol satisfies the statistical version of the above constraints.

### 5.1 Correctness

**Lemma 5.1 Hoefding inequality** [6] Let  $X_1, X_2, \dots, X_n$  be total independent random variables with identical probability distribution so that  $E(X_i) = \mu$  and the range of  $X_i$  is in [a,b]. Let the simple average  $Y = (X_1 + X_2 + \dots + X_n)/n$  and  $\delta > 0$ , then

$$Pr[|Y - \mu| \ge \delta] \le 2 \cdot e^{\frac{-2n \cdot \delta^2}{b-a}}$$

So, if  $Pr[X_i = 0] = Pr[X_i = 1] = \frac{1}{2}$ , then  $\mu = \frac{1}{2}$ and a = 0, b = 1, we have the following inequality

$$\Pr[|\sum_{i=1}^{n} \frac{X_i}{n} - \frac{1}{2}| \ge \delta] \le 2 \cdot e^{-2 \cdot n\delta^2}$$

We show that most of the time the output is correct if the parties abide to their prescribed protocol. In a given run of the protocol, *Bob* will succeed in computing  $b_{c_1}, b_{c_2}, \ldots, b_{c_m}$  properly provided satisfying the following conditions :

when  $\frac{2m+1}{2n} < \frac{1}{2}$ 

$$\#\{i|\beta_i = \beta'_i\} - x \ge (N-x)m/n$$

or when  $\frac{2m+1}{2n} \ge \frac{1}{2}$ 

$$\#\{i|\beta_i = \beta'_i\} \ge (N-x)m/n$$

Because in that case he can form  $I_{c_1}, I_{c_2}, \ldots, I_{c_m}$  as prescribed and then he can compute the output bit as  $\hat{b}_{c_i} \oplus \bigoplus_{j \in I_{c_i}} r'_j$  which is

$$\widehat{b}_{c_i} \oplus \bigoplus_{j \in I_{c_i}} r'_j = b_{c_i} \oplus \bigoplus_{j \in J_{c_i}} r_j \bigoplus_{j \in I_{c_i}} r'_j = b_{c_i} \oplus \bigoplus_{j \in I_{c_i}} r_j \oplus r'_j$$

because  $J_{c_i}$  is  $I_{c_i}$ . Since  $\beta_i = \beta'_i \to r_j \oplus r'_j = 0$  makes all the right terms vanish, we end up with

$$\widehat{b}_{c_i} \oplus \bigoplus_{j \in I_{c_i}} r'_j = b_{c_i}$$

Therefore the protocol gives the correct output unless satisfying the following conditions : when  $\frac{2m+1}{2n} < \frac{1}{2}$ 

$$\#\{i|\beta_i = \beta'_i\} - x < (N-x)m/n$$

or when  $\frac{2m+1}{2n} \ge \frac{1}{2}$ 

$$\#\{i|\beta_i = \beta'_i\} < (N-x)m/n$$

in which case *Bob* is unable to form the set  $I_{c_1}, I_{c_2}, \ldots, I_{c_m}$  as prescribed. Now, we can calculate the probability that *Bob* can not form  $I_{c_1}, I_{c_2}, \ldots, I_{c_m}$ If  $\frac{2m+1}{2n} < \frac{1}{2}$  (i.e.  $2m+1 < n, x = \frac{n-(2m+1)}{2n-(2m+1)}N$ ), then the probability that *Bob* can get less than *m* bits is given by

$$\begin{split} &P[\#\{i|\beta_i = \beta'_i\} - x < (N-x)m/n] \\ &= P[\#\{i|\beta_i = \beta'_i\} < (N-x)m/n + x] \\ &= P[\sum_{i=1}^N \beta_i \oplus \beta'_i > N - ((N - \frac{n - (2m+1)}{2n - (2m+1)}N)m/n \\ &+ \frac{n - (2m+1)}{2n - (2m+1)}N)] \\ &= P[\frac{1}{N}\sum_{i=1}^N \beta_i \oplus \beta'_i > 1 - \frac{n - (m+1)}{2n - (2m+1)}] \\ &= P[\frac{1}{N}\sum_{i=1}^N \beta_i \oplus \beta'_i > \frac{n - m}{2n - (2m+1)}] \\ &\leq P[|\frac{1}{N}\sum_{i=1}^N \beta_i \oplus \beta'_i - \frac{1}{2}| > \frac{n - m}{2n - (2m+1)} - \frac{1}{2}] \end{split}$$

It is easy to check that  $\frac{n-m}{2n-(2m+1)} - \frac{1}{2} > 0.$ Given that  $P[\beta_i \oplus \beta'_i = 1] = 1/2$ , let N > 0  $\frac{\ln 2}{(\frac{n-m}{2n-(2m+1)}-\frac{1}{2})^2},$  this probability can be easily bounded by

$$\begin{array}{ll} < & 2 \cdot e^{-2 \cdot N(\frac{n-m}{2n-(2m+1)} - \frac{1}{2})^2} \\ = & 2 \cdot e^{-N(\frac{n-m}{2n-(2m+1)} - \frac{1}{2})^2} \cdot e^{-N(\frac{n-m}{2n-(2m+1)} - \frac{1}{2})^2} \\ < & e^{-N(\frac{n-m}{2n-(2m+1)} - \frac{1}{2})^2} \\ = & \varepsilon^N \end{array}$$

 $(\varepsilon=e^{-(\frac{n-m}{2n-(2m+1)}-\frac{1}{2})^2}<1)$  using Hoefding's inequality.

If  $\frac{2m+1}{2n} \ge \frac{1}{2}$  (i.e.  $2m+1 \ge n$ ,  $x = \frac{(2m+1)-n}{2m+1}$ ), then the probability that *Bob* can get less than *m* bits is given by

$$P[\#\{i|\beta_{i} = \beta'_{i}\} < (N-x)m/n]$$

$$= P[\sum_{i=1}^{N} \beta_{i} \oplus \beta'_{i} > N - (N - \frac{(2m+1) - n}{2m+1}N)m/n]$$

$$= P[\frac{1}{N}\sum_{i=1}^{N} \beta_{i} \oplus \beta'_{i} > 1 - \frac{m}{2m+1}]$$

$$\leq P[|\frac{1}{N}\sum_{i=1}^{N} \beta_{i} \oplus \beta'_{i} - \frac{1}{2}| > \frac{1}{2} - \frac{m}{2m+1}]$$

It is easy to check that  $\frac{1}{2} - \frac{m}{2m+1} > 0$ . Given that  $P[\beta_i \oplus \beta'_i = 1] = 1/2$ , let  $N > \frac{\ln 2}{(\frac{1}{2} - \frac{m}{2m+1})^2}$ , this probability can be easily bounded by

$$\begin{array}{ll} < & 2 \cdot e^{-2 \cdot N \left(\frac{1}{2} - \frac{m}{2m+1}\right)^2} \\ = & 2 \cdot e^{-N \left(\frac{1}{2} - \frac{m}{2m+1}\right)^2} \cdot e^{-N \left(\frac{1}{2} - \frac{m}{2m+1}\right)^2} \\ < & e^{-N \left(\frac{1}{2} - \frac{m}{2m+1}\right)^2} \\ = & \varepsilon^N \end{array}$$

 $(\varepsilon = e^{-(\frac{1}{2} - \frac{m}{2m+1})^2} < 1)$  using Hoefding's inequality. So, *Bob* can get less than *m* bits that sent from *Alice* with probability less than  $\varepsilon^N$ .

### 5.2 Privacy

We analyse the privacy of each party individually as if he or she is facing a malicious opponent.

### 5.2.1 Privacy for Bob

**Theorem 5.1** Alice can not find out much about  $c_1, c_2, \ldots, c_m$ ,

*Proof.* The only things *Alice* gets though the protocol are the sets  $J_1, J_2, \ldots, J_n$ .  $\beta_i$ 's and  $\beta'_i$ 's are independent from each other.  $J_1, J_2, \ldots, J_n$  will have uniform distribution over all possible pairs of disjoint subsets of size  $\frac{N-x}{n}$  for i = 1, i = 2, ... as well as for i = n. Therefore Alice learns nothing about the  $c_1, c_2, ..., c_m$ .

### 5.2.2 Privacy for Alice

**Theorem 5.2** Except with probability at most  $\epsilon^n$ , Bob can not find out much information about more that m of  $b_1, b_2, \ldots, b_n$ .

*Proof.* The probability of that Bob gets more than m bits (i.e. get at least m + 1 bits). So

If  $\frac{2m+1}{2n} < \frac{1}{2}$  (i.e. 2m+1 < n,  $x = \frac{n-(2m+1)}{2n-(2m+1)}N$ ), the probability that *Bob* can get more than m+1 bits is given by

$$\begin{split} &P[\#\{i|\beta_i = \beta'_i\} - x \ge (N-x)(m+1)/n] \\ &= P[\#\{i|\beta_i = \beta'_i\} \ge (N-x)(m+1)/n + x] \\ &= P[\sum_{i=1}^N \beta_i \oplus \beta'_i \le N - ((N - \frac{n - (2m+1)}{2n - (2m+1)}N)(m+1)/n + \frac{n - (2m+1)}{2n - (2m+1)}N)] \\ &\quad + 1)/n + \frac{n - (2m+1)}{2n - (2m+1)}N)] \\ &= P[\frac{1}{N}\sum_{i=1}^N \beta_i \oplus \beta'_i \le 1 - \frac{n - m}{2n - (2m+1)}] \\ &\le P[|\frac{1}{N}\sum_{i=1}^N \beta_i \oplus \beta'_i - \frac{1}{2}| > \frac{1}{2} - \frac{n - m}{2n - (2m+1)}] \end{split}$$

It is easy to check that  $\frac{1}{2} - \frac{n-m}{2n-(2m+1)} > 0$ . Given that  $P[\beta_i \oplus \beta'_i = 1] = 1/2$ , let  $N > \frac{\ln 2}{(\frac{1}{2} - \frac{n-m}{2n-(2m+1)})^2}$ , this probability can be easily bounded by

$$\begin{array}{ll} < & 2 \cdot e^{-2 \cdot N \left(\frac{1}{2} - \frac{n-m}{2n-(2m+1)}\right)^2} \\ = & 2 \cdot e^{-N \left(\frac{1}{2} - \frac{n-m}{2n-(2m+1)}\right)^2} \cdot e^{-N \left(\frac{1}{2} - \frac{n-m}{2n-(2m+1)}\right)^2} \\ < & e^{-N \left(\frac{1}{2} - \frac{n-m}{2n-(2m+1)}\right)^2} \\ = & \varepsilon^N \end{array}$$

 $(\varepsilon=e^{-(\frac{1}{2}-\frac{n-m}{2n-(2m+1)})^2}<1)$  using Hoefding's inequality.

If  $\frac{2m+1}{2n} \geq \frac{1}{2}$  (i.e.  $2m+1 \geq n$ ,  $x = \frac{(2m+1)-n}{2m+1}$ ), then the probability that *Bob* can get more than m+1 bits is given by

$$P[\#\{i|\beta_i = \beta'_i\} \ge (N-x)(m+1)/n] \\ = P[\sum_{i=1}^N \beta_i \oplus \beta'_i \le N - (N - \frac{(2m+1) - n}{2m+1}N)(m+1)]$$

$$+1)/n] = P[\frac{1}{N}\sum_{i=1}^{N}\beta_{i}\oplus\beta_{i}'\leq 1-\frac{m+1}{2m+1}] \\ \leq P[|\frac{1}{N}\sum_{i=1}^{N}\beta_{i}\oplus\beta_{i}'-\frac{1}{2}|>\frac{m+1}{2m+1}-\frac{1}{2}]$$

It is easy to check that  $\frac{m+1}{2m+1} - \frac{1}{2} > 0$ . Given that  $P[\beta_i \oplus \beta'_i = 1] = 1/2$ , let  $N > \frac{\ln 2}{(\frac{m+1}{2m+1} - \frac{1}{2})^2}$ , the probability can be easily bounded by

$$< 2 \cdot e^{-2 \cdot N(\frac{m+1}{2m+1} - \frac{1}{2})^2}$$

$$= 2 \cdot e^{-N(\frac{m+1}{2m+1} - \frac{1}{2})^2} \cdot e^{-N(\frac{m+1}{2m+1} - \frac{1}{2})^2}$$

$$< e^{-N(\frac{m+1}{2m+1} - \frac{1}{2})^2}$$

$$= \varepsilon^N$$

$$= \varepsilon^N$$

 $(\varepsilon = e^{-(\frac{m+1}{2m+1} - \frac{1}{2})^2} < 1)$  using Hoefding's inequality.

Finally, we show that *Bob* cannot get more than m bits by attacking the weak quantum bit commitment. Let the probability that he can cheat *Alice* in the weak QBC be  $p \ (0 , the probability that he can get one more bit is <math>p^{\frac{N-r}{n}} < \epsilon^N \ (\epsilon = p^{\frac{1}{2n}})$ .

So, *Bob* can get more than m bits that sent from *Alice* with probability less than  $\varepsilon^N$ .

In the 1-out-of-2 OT scheme, n = 2 and m = 1,  $\frac{2m+1}{2n} = \frac{3}{4} > \frac{1}{2}$ , then the probability is less than

 $2 \cdot e^{-N \cdot 2(\frac{m+1}{2m+1} - \frac{1}{2})^2} = 2 \cdot e^{-N \cdot 2(\frac{2}{3} - \frac{1}{2})^2} = 2 \cdot e^{-\frac{N}{18}}$ 

## 6 Conclusions and Future Work

In this paper, we construct an quantum *m*-out-of*n* OT based on the transmission of polarized light, which is an extension of the quantum 1-out-f-2 OT, and prove that this scheme satisfies statistical correctness and statistical privacy, i.e. except with a small probability  $\epsilon^N$ , *Bob* can get the correct *m* bits, and cannot get one more bit than required.

We think the following points is interesting for further research:

- 1. Implement and apply the QOT in the real world.
- 2. Find a QOT satisfies perfect correctness and perfect privacy.

# References

[1] Bennett, C.H. and Brassard, G., "Quantum Cryptography: Public-key Distribution and Coin Tossing", In Proceedings of the International Conference on Computers, Systems and Signal Processing, Bangalore, India, December 1984, pp. 175-179.

- [2] Brassard, G., Crépeau, C. Jozsa, R. and Langlois, D., "A Quantum Bit Commitment Scheme Probably unbreakable by both parties", In Proceedings of the 34th Annual IEEE Symposium on Foundations of Computer Science, November 1993, pp.362-371
- [3] Claude Crépeau. "Quantum Oblivious Transfer". Journal of Modern Optics, 41(12):2455C2466, 1994.
- [4] Dorit Aharonov, Amnon Ta-Shma, Umesh V. Vazirani, Andrew Chi-Chih Yao. "Quantum bit escrow". Proceedings of the 32nd Annual ACM Symposium on Theory of Computing(STOC'00), 2000.
- [5] Even, S., Goldreich, O. and Lempel, A., "A Randomized Protocol for Signing Contracts", Communications of the ACM, vol. 28, pp. 637-647, 1985.
- [6] W. Hoefding, "Probability Inequalities for Sums of Bounded Random Variables", Journal of the American Statistical Association, Vol.58, 1936, pp.13-30
- [7] Mayers, D. "Unconditionally Secure Quantum Bit Commitment is Impossible". Physical Review Letters 78. pp 3414-3417 (28 April 1997).
- [8] Moni Naor, Benny Pinkas. "Efficient Oblivious Transfer Protocols". SODA, 2001
- [9] P. W. Shor, "Polynomial-Time Algorithms for Prime Factorization and Discrete Logarithms on a Quantum Computer", SIAM Journal on Computing, V.26:(5), 1997.
- [10] Rabin, M.O., "How to exchange secrets by Oblivious Transfer", technical report TR-81, Aiken Computation Laboratory, Harvard University, 1981.
- [11] Wiesner, S., "Conjugate coding", Sigact News, vol.15, no. 1, 1983, pp.78-88; Manuscript written circa 1970, unpublished until it appeared in SIGACT News.
- [12] Yi Mu, Junqi Zhang, Vijay Varadharajan, "m out of n oblivious transfer," ACISP 2002, Lecture Notes in Computer Science 2384, Springer Verlag, 2002. pp. 395-405