MZ-TH 97-35



## A Program Package calculating

## **One- and Two-Loop Feynman Diagrams**

L. Brücher, J. Franzkowski, D. Kreimer

October 1997

L. Brücher<sup>1</sup>, J. Franzkowski<sup>2</sup>, D. Kreimer<sup>3</sup>

Institut für Physik Johannes Gutenberg-Universität Mainz Staudingerweg 7 D-55099 Mainz Germany

<sup>&</sup>lt;sup>1</sup>e-mail: bruecher@dipmza.physik.uni-mainz.de <sup>2</sup>e-mail: franzkowski@dipmza.physik.uni-mainz.de <sup>3</sup>e-mail: kreimer@dipmza.physik.uni-mainz.de

# Contents

1	Introduction	5
<b>2</b>	Preliminaries	7
3	Quick reference	11
4	Detailed description	19
5	Conclusion and outlook	61
A	opendix	63
$\mathbf{A}$	Examples	65
в	Technical details	75
Bi	bliography	81
In	dex	83

## 1 Introduction

#### 1.1 Intention

The aim of  $\chi foops$  is to calculate one-particle irreducible Feynman diagrams with one or two closed loops for arbitrary processes in the Standard model of particles and related theories. Up to now this aim is realized for all one-loop diagrams with at most three external lines and for two-loop diagrams with two external lines.

The results can be returned both algebraically and numerically. All necessary tensor integrals are treated for arbitrary masses and momenta. Those two-loop two-point functions for which no analytic result is known are integrated numerically by  $\chi$  loops.

The calculations are performed in Maple V – a language for symbolic computations [1, 2]. Numerical integrations are done using VEGAS – a procedure for adaptive Monte Carlo integration [3, 4]. For convenient input  $\chi$  loops has an Xwindows interface based on Tcl/Tk [5].

The package consists of the following parts:

▷ Input via Xwindows interface:

In a window the user selects the topology which shall be calculated. A Feynman diagram pops up in which the particle names have to be inserted.

 $\triangleright$  Processing with Maple:

The selected diagram is evaluated. The necessary steps for reducing the numerator (SU(N) algebra, Dirac matrices) are performed. The result is expressed in terms of one- and two-loop integrals.

 $\triangleright$  Evaluation of one-loop integrals:

One-loop one-, two- and three-point integrals are calculated analytically or numerically to any tensor rank using Maple. This part was already released separately [6,7].

 $\triangleright$  Evaluation of two-loop integrals:

All two-loop two-point topologies including tensor integrals are supported by the Maple routines. For those topologies where no analytic result is known,  $\chi$  coops creates either an analytic two-fold integral representation or integrates numerically with the help of VEGAS using C++ [8]. A parallelized implementation of the VEGAS algorithm invented by R. Kreckel [9,10] is part of this distribution.

The other topologies can be calculated analytically or numerically like one-loop integrals.

In the second chapter we briefly denote how to install and start the program. Chapter three gives several examples for quick and easy usage. A more detailed description of the user-interface can be found in chapter four of this manual.

## 1.2 Copyright

The copyright of this program package is owned by the Johannes Gutenberg-Universität Mainz, Germany.

*xloops* is "*cite-ware*". That means that you can freely use and redistribute it, but you have to cite *xloops* if you publish any results that you achieved with the help of it.

Any further program development which intends to use the name  $\chi loops$  or the incorporation of  $\chi loops$  or a part of the  $\chi loops$  code into any other program needs the permission of the authors.

With the receipt of  $\chi loops$  the customer accepts that he uses the program entirely on his own risk. Neither the authors nor the distributors of  $\chi loops$  are liable for any loss or damage as a result of any use which is made of this program.

## 1.3 Comments and bug reports

 $\chi loops$  is still under development. So if you have questions, comments or if you have found any bug – please don't hesitate to contact

#### xloops@thep.physik.uni-mainz.de

or one of the authors.

# 2 Preliminaries

## 2.1 Requirements

 $\chi loops$  can be used on any computer where Maple V is working. If Maple is not yet installed on your computer system you have to do that first. For numerical integration of two-loop integrals a compiler for C++ is necessary. The Xwindows interface needs Tcl/Tk and is at present only available for Unix. On other platforms or if Tcl/Tk is not installed the Xwindows interface will not work. In this case you can use the Maple part directly (cf. sect. 2.4 and 2.5). The Maple part covers most features of the  $\chi loops$  package but the input may be found not as user-friendly as if the interface is used.

## 2.2 Installation

The distribution of the  $\chi loops$  package is accessible via WWW at

```
http://wwwthep.physik.uni-mainz.de/~xloops/
```

It consists of one packed (tared, gzipped) file

xloops-1.0.tgz

This file contains all files needed for *xloops*. To install the package unpack xloops-1.0.tgz:

```
tar -xzvf xloops-1.0.tgz
```

 $\chi loops$  then automatically creates a subdirectory of the current directory which is called xloops. The package is then deposited there. In addition there will occur several subdirectories of xloops. A complete list of all files in the distribution is given in appendix B.4. Moreover, there exists an additional (tared, gzipped) file

xloops-lib.tgz

in the same directory as xloops-1.0.tgz which contains a library of one-loop diagrams (cf. sect. 4.5). For convenience one should unpack this file in the same directory where xloops-1.0.tgz was unpacked before.  $\chi loops$  will read from this library whenever a oneor two-loop integral has to be evaluated. If this library is missing  $\chi loops$  will create the necessary files automatically, but this will usually take some time. If you have the bash shell type

cd xloops/ configure This will settle the configuration of the Xwindows interface. configure will request

▷ the release of Maple V (1, 2, 3 or 4) you are using. There were subtle changes from release 2 to 3 in handling local and global variables, therefore it is important to select the correct option. Since we tested only Maple V release 1 and 3, for release 2 and 4 configure internally does the following replacement:

release 2: use the same files as for release 1 release 4: use the same files as for release 3 (with some patches)

which is expected to be consistent.

- ▷ the WWW browser which should be used for the on-line html version of this manual. The name of the executable (cf. netscape, mosaic, ...) must be inserted.
- $\triangleright$  the character encoding of your terminal (Isolatin 1 or standard ascii).
- ▷ whether multiprocessing is enabled. This question is necessary to choose between normal VEGAS or the parallelized version of VEGAS running on multiprocessor computers only. If multiprocessing is enabled the number of processors is requested.
- ▷ the platform. Several frequently used systems (Linux, Digital Unix, SUN Solaris, IBM AIX) are distinguished from other Unix to install the right Makefile for the numerical integration.
- ▷ whether a library of one-loop integrals should be build. It can take a lot of time (up to an hour) on slower computers to build the whole library. Therefore it is recommended not to do that, but to load a pre-built library xloops-lib.tgz from our WWW server instead.

After that several checks are performed. First an embarassing bug occuring in Maple releases up to release 3 is tested: If a file is read in a procedure, no output of the procedure will appear. Therefore we have written a little workaround for this bug, which can be installed by the user.

configure continues with a test run of the Makefile which is needed for numerical integrations. This Makefile depends on the platform. The run will take some time.

Finally you are asked to agree that automatically a mail is sent to the developer team of the  $\chi loops$  package. This mail is understood as registration of your  $\chi loops$  installation.

A typical run of configure is given in appendix A.1. configure automatically creates the *xloops* executable file.

If you have root access you can make it executable for all users. You then can set a symbolic link to /usr/bin, i.e.

cd /usr/bin ln -s  $\langle directory \rangle / \texttt{xloops/xloops}$  .

where  $\langle directory \rangle$  is the directory where  $\chi loops$  was installed.

If you don't have bash you can find the necessary instructions in the file README which is part of the *xloops* distribution.

#### 2.3 Getting started

You can now type

#### ./xloops

from the directory where  $\chi loops$  was installed before. This starts your  $\chi loops$  session. The main window of  $\chi loops$  (cf. fig. 3.1) will appear. If  $\chi loops$  was made executable for all users (cf. previous section) it can be started with

#### xloops

from any directory.

There is on principle no restriction in the number of  $\chi foops$  sessions which can be used simultaneously – by the same user or by different users. On the other hand the numerical integration with VEGAS should be used only once by each user (cf. sect. 4.6).

### 2.4 Installing the Maple part only

If you are only interested in the Maple routines you have to start the installation as in sect. 2.2, but you then skip configure and just copy all files with extension .ma

- ⊳ loops.ma
- $\triangleright$  fmrules.ma
- $\triangleright$  fmuser.ma
- ⊳ evalproc.ma
- $\triangleright$  oneloop.ma
- $\triangleright$  cfcn.ma
- ⊳ pv.ma
- ⊳ r.ma
- $\triangleright$  simple.ma
- $\triangleright$  twoloop.ma
- $\triangleright$  numint.ma
- $\triangleright$  values.ma
- $\triangleright$  unvalue.ma
- $\triangleright$  mess.ma

in one directory instead and delete the rest of the distribution. The correct .ma files you can find in the subdirectory xloops/MapleVR1 – if you use release 1 or 2 – or in the subdirectory xloops/MapleVR3 – if you have release 3 or higher.

## 2.5 Usage within a Maple session

You can use  $\chi loops$  within an ordinary Maple session as well: After having started Maple just type the following lines:

```
LoopPath:=\langle path \rangle;
read'\langle path \rangleloops.ma';
```

 $\langle path \rangle$  describes the directory where the .ma files are located. If the *xloops* package is installed properly this should be the path of the *xloops* directory to which you have to add MapleVR1 – if you are using release 1 or 2 of Maple V – or MapleVR3 – if you are using release 3 or higher. If the .ma files were copied to the current directory before you can skip the assignment of LoopPath and only type

```
read'loops.ma';
```

Now you can use the functions described in chapter 4.

# 3 Quick reference

## 3.1 Main window

After having typed the command xloops the main window (cf. fig. 3.1) appears on the screen. It consists of three parts:

- 1. The menu bar which contains several menues for  $\chi loops$  commands (for details cf. sect. 4.1.1).
- 2. The topology bar which displays all possible topologies for a definite m-loop n-point function. The selection of m closed loops and n external lines is done with the help of the menues Loops and Ext. Lines.
- 3. The *text window* with scroll bar which contains the results of calculations.

menu bar topology bar	
XLoops 1.0	
File <sup>/</sup> Model Loops Ext. Lines Options	Help
$\Theta & \Theta &$	
Maple V loaded ! > read(`/home/xloops/xloops/MapleVR3/loops.ma`): Warning: new definition for &*	
>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	
by Lars Brücher, Johannes Franzkowski, Dirk Kreimer	
bytes used=1040496, alloc=851812, time=0.43 bytes used=2049840, alloc=1310480, time=0.94	

Maple text window

Figure 3.1: Main window

Before we will explain the functions and their meanings in detail in the next chapter, we demonstrate here as an example how to use  $\chi loops$  for the calculation of a two-loop self-energy diagram and a one-loop vertex correction.

## 3.2 Two-loop self-energy

We now perform the calculation of a diagram which contributes to the Higgs self-energy  $\Sigma$  at the two-loop level:



The underlying topology is the master topology, which is located in the fourth place in the *topology bar* (cf. fig. 3.1). In this case the number of external lines and the number of closed loops is already fixed correctly, so one now has just to click on the topology.

Then the master topology appears in a separate window, the *diagram window* (cf. fig. 3.2). In this window for each internal and external particle the corresponding particle name has to be inserted. Only particles can occur here, no antiparticles. The allowed terms for particle names are listed in sect. 4.2.4. They can be obtained alternatively with the menu Help. The flow of charges and fermion or ghost numbers is determined by the arrows of the lines. The direction of an arrow is reverted with a click on it.



Figure 3.2: The diagram for the two-loop Higgs self-energy

Since in our example we have to deal only with chargeless scalars, the direction of arrows is meaningless and we have to insert the name H or higgs for each particle only.

For the sake of clearness, the flow of external momenta in our conventions is displayed in blue. In this example there is only one momentum

$$q_1 = (q_{10}, 0, 0, 0) = (q_{10}, 0).$$

Vanishing components are put together to a common zero-vector. In our case there exists only one parallel space component  $q_{10}$ . The orthogonal space is represented through a common 0.

When all particles are inserted,  $\chi$  loops is ready for calculation. The diagram window gives you the possibility to select different modes of evaluation.

Click on the Evaluate button: The output – for simplicity – is returned in terms of Oneloop and Twoloop functions which correspond directly to one-loop and two-loop functions explained in sect. 4.3 and 4.4. In our example the result consists only of the scalar master two-loop two-point function which xloops calls Twoloop2Pt2:

```
> G1 := EvalGraph2 (7, [higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,higgs,h
```

Generally, the output is decomposed in one or several form factors C1, C2, ... to reflect the Dirac  $\gamma$  or Lorentz structure of the result. Therefore the result is a list of form factors. The last entry in this list is the defining equation for the form factors. In our example of a scalar self-energy there appears only one form factor C1 and the defining equation is just the scalar C1. A more complicated situation can be found in the next section (for details cf. sect 4.2.10).

Moreover  $\chi$  loops assigned the whole result to a variable G1. Within an  $\chi$  loops session each calculation will get such a name in an unique way. This gives the user the opportunity to perform further calculations with the results of diagrams, for instance to sum up all evaluated graphs which contribute to the same process.

▷ Click on the Eval. Full button: *xloops* evaluates directly the Oneloop and Twoloop integrals. Now each form factor C1, ... is a Laurent expansion in terms of the ultraviolet regulator  $\varepsilon$ , where the significant coefficients of this expansion –  $\mathcal{O}(\varepsilon^{-1})$ ,  $\mathcal{O}(\varepsilon^{0})$  in the one-loop case,  $\mathcal{O}(\varepsilon^{-2})$ ,  $\mathcal{O}(\varepsilon^{-1})$ ,  $\mathcal{O}(\varepsilon^{0})$  in the two-loop case – are denoted in form of a list (cf. sect 4.2.10).

For those two-loop topologies where no analytic result is known - like in the case of our example, the finite part contributes two entries to the output list. The first

of them is a list itself which denotes an integral representation, the second contains the part which is analytically calculable:

```
GF1 := [
C1 = [0, 0],
          84
 81
     Mhiggs e
[-----
     4 4
8192
    sin(tw) Mw Pi
                                                    2
                  2
          2 Mhiggs
                                   2
                                                Mhiggs
 I Ln(Sqrt(x - ----- + I rho) + %1 + Sqrt(y - 2 y + 1 - ---- + I rho))
                 2
                                                    2
              q10
                                                 q10
                     2
                    q10 (- 2 x - 1) (- 2 y + 1)
                              2
              2 Mhiggs
   - 4 I Ln(Sqrt(x + 2 x + 1 - ----- + I rho) + %1
                          2
                           q10
                         2
   2 Mhiggs / 2
+ Sqrt(y - 2 y + 1 - ------ + I rho)) / (q10 (- 2 x - 1) (- 2 y + 1))
                      2
                      q10
                     2
                                                 2
                             ∠
2 Mhiggs
              2 Mhiggs
      I Ln(Sqrt(x - ----- + I rho) + %1 + Sqrt(y - ---- + I rho))
                     2
                                                 2
                  q10
                                             q10
    4 ------ + 4
                      2
                     q10 (- 2 x - 1) (- 2 y + 1)
                          2
                                                     2
                                       2 Mhiggs
                      Mhiggs
           2
  I Ln(Sqrt(x + 2 x + 1 - ----- + I rho) + %1 + Sqrt(y - ----- + I rho))
                       2
                                                    2
                       q10
                                                  q10
                       2
                     q10 (- 2 x - 1) (- 2 y + 1)
x = - infinity .. infinity, y = - infinity .. infinity],
0],
```

C1]

2 2 %1 := Sqrt(x + 2 x y + y - ------ + I rho) 2 q10

In our example the result is finite, therefore the first two entries in the list are zero. The only nonvanishing contribution comes from the integral representation. A more detailed description of the integral representation is given in sect. 4.4.3.

The result is a function of the Higgs mass Mhiggs and the external momentum q10. The coupling of the vertices involve the W mass Mw, the Weinberg angle tw and the electromagnetic coupling constant e. rho denotes the infinitesimal imaginary part of the masses in the denominator (cf. sect. 4.2.10), x and y are the variables which have to be integrated out numerically.

▷ Click on the Eval. Numeric button: The integral representation described above is evaluated directly with the help of VEGAS. This option exists only for two-loop integrals, because all one-loop integrals are analytically calculable.

Please be aware that *xloops* can only perform the numerical integration if all variables – Mhiggs and q10 in our example – are assigned with numerical values. For that purpose the menu File provides the Insert Maple Command entry. If this option is selected, a window (cf. fig. 3.3) appears, where any command can be passed directly to Maple. In our example we insert

q10:=91.17; Mhiggs:=300;

to evaluate the integral on the Z resonance for an assumed value of 300 GeV for the Higgs mass. After clicking on  $\boxed{\text{Eval. Numeric}}$  xloops starts the numerical integration.

Evaluate Maple Command					
Please insert your Maple command:					
q10 := 91.17; Mhiggs := 300;					
Evaluate Clear Buffer Close					

Figure 3.3: Direct Maple input of masses and momenta

The result including the numerical uncertainty appears in the *main window* and reads:

```
GM1 := [
C1 = [0, 0,
[.66598680119771701375*10 4
4 4
sin(tw) Mw
```

```
-8 -5 -7 -7
[-.354349*10 + .880157*10 I, .13042*10 + .148817*10 I]], 0],
```

C1]

In the result – compared to the [Eval. Full] option – the integral representation is now replaced by the numerical result of the integral. This result consists of a list: a pre-factor and another list. This list contains two entries: first the result of the VEGAS calculation, then the uncertainty VEGAS detected for this result (for details cf. sect. 4.2.10).

In our example the real part of the diagram is less than the numerical uncertainty, whereas the imaginary part is significantly larger. This means that the real part in fact is zero. Since we calculated the entire diagram which is not precisely  $\Sigma$  but  $-i\Sigma$ , this is what one expects below threshold.

Alternatively to the direct input of Maple commands described above it is possible to assign all known masses of particles, couplings and elements of the CKM matrix with the option Insert Particle Properties of the Options menu.

The input information for VEGAS can also be determined with the menu Options: Click on Numeric and an additional window will appear where the input parameters for VEGAS can be fixed (for details cf. sect. 4.1.4).

Finally the result can be saved in text mode to a file. Use in the menu File the entry Save Maple Output.

 $\triangleright$  Click on the Close button: The diagram window disappears.

The four buttons described above are completely independent. You can for example select [Eval. Numeric] without having clicked on [Evaluate] or [Eval. Full] before.

### 3.3 One-loop vertex correction

What follows is the calculation of a one-loop contribution of the correction to the eeZ vertex:



First one has to select the correct values in the menues Loops and Ext. Lines of the *main window* to get access to the one-loop three-point topologies. A click on the correct topology opens the *diagram window* (cf. fig. 3.4) where the particle names have to be inserted. Again the correct particle names can be found in sect. 4.2.4 or in the menu Help. The direction of the fermion line must be adjusted by clicking on the arrows. The flow of external momenta



Figure 3.4: The diagram for the eeZ one-loop vertex correction

is displayed in blue again. The three momenta are

$$q_{1} = (q_{10}, 0, 0, 0) = (q_{10}, 0)$$
$$q_{2} = (q_{20}, q_{21}, 0, 0) = (q_{20}, q_{21})$$
$$q_{1} - q_{2} = (q_{10} - q_{20}, -q_{21}, 0, 0) = (q_{10} - q_{20}, -q_{21})$$

where the vanishing orthogonal space components are not displayed in the window.  $q_{10}, q_{20}, q_{21}$  are the kinematical variables *xloops* uses for three-point functions. To get a numerical result, we assign these variables with

```
q10:=Mz0; q20:=Mz0/2; q21:=evalf(sqrt(Mz0^2/4-Melec^2));
```

using the option Insert Maple Command of the menu File so that all external particles are on-shell. Moreover the masses and couplings are assigned by the option Insert Particle Properties of the Options menu. The renormalization scale MU and the unit GeV can be omitted by setting

```
MU:=1; GeV:=1;
```

Clicking on the  $\overline{(E. Full})$  button gives the following result:

```
GF2 := [
```

```
C1 = [.000010058632263504308717 I,
```

```
- .00086276496443282788638 - .0072236143340212361270 I],
```

```
C2 = [.00010510130634321490041 I,
```

- .0090149159887518402249 - .075478582279918574719 I],

```
C3 = [0, .00083116483915048522171 + .0071524795241752712917 I],
```

```
C4 = [0, .0086847304974275009526 + .074735304153769864092 I],
                                  -9
                                                               -8
C5 = [0, .40863107990668029069*10]
                                    + .35164209243516742716*10
                                                                I],
C6 = [0, .000018229897665296319548 + .00015687498271956514041 I],
C7 = [0, .00019048176819004810260 + .0016391657617525244669 I],
                                     -28
C8 = [0, -.25407817700937862122*10]
                                        - .21701516787925566779*10
                                                                       I],
C9 = [0, .000017536874322335126422 + .00015153965406412662322 I],
C10 = [0, .00018324045975332954356 + .0015834176245538375947 I],
C11 = [0, -.20431553995334014636*10]
                                        - .17582104621758371369*10
                                                                      τ1.
C12 = [0, .22971899930888218199*10]
                                       .19620932339352982103*10
                                                                  I],
C13 = [ - .24074590585723032270*10
                                      Т
    .34651167097341202104*10
                               + .28882798115295165844*10 I],
C14 = [0, .36206542130597753444*10]
                                    + .000030179250351750043557 I].
                                   -28
C15 = [0, .12703908850468931061*10]
                                      + .10850758393962783388*10
                                                                     I],
C16 = [0, .34651167090811890878*10]
                                     + .26676643227928772485*10
                                                                   I],
C17 = [0, .36206542123775363980*10]
                                    + .000027874068547868333215 I],
C1 (1 &* Dg(nu1)) + C2 &*(1, Dg5, Dg(nu1)) + C3 &*(1, Dg0, Dg1, Dg(nu1))
     + C4 &*(1, Dg5, Dg0, Dg1, Dg(nu1)) + C5 (1 &* ONE) q2(nu1)
     + C6 (1 &* Dg0) q2(nu1) + C7 &*(1, Dg5, Dg0) q2(nu1)
     + C8 &*(1, Dg0, Dg1) q2(nu1) + C9 (1 &* Dg1) q2(nu1)
     + C10 &*(1, Dg5, Dg1) q2(nu1) + C11 (1 &* ONE) q1(nu1)
     + C12 (1 &* Dg5) q1(nu1) + C13 (1 &* Dg0) q1(nu1)
     + C14 &*(1, Dg5, Dg0) q1(nu1) + C15 &*(1, Dg0, Dg1) q1(nu1)
     + C16 (1 &* Dg1) q1(nu1) + C17 &*(1, Dg5, Dg1) q1(nu1)
                                                                         ]
```

The output is decomposed in several form factors C1, C2, ... to reflect the Dirac  $\gamma$  and Lorentz structure of the result. The last entry in this list is the defining equation for the form factors (cf. sect. 4.2.10).

## 4 Detailed description

There are two intentions covered by *xloops*:

- ▷ Either the calculation of complete Feynman diagrams. Here you need the Evaluate Graph window (see sect. 4.1) where you can insert particles into a Feynman diagram. Alternatively you can use the EvalGraph procedures in Maple described in sect. 4.2.
- ▷ Or the solution of single integrals occurring in the calculation of one- and two-loop diagrams. Then you can make use of the OneLoop and TwoLoop procedures explained in sect. 4.3 and 4.4.

The creation of a library for the integrals follows in sect. 4.5. The numerical integration of two-loop integrals is explained in sect. 4.6.

## 4.1 The Xwindows interface

#### 4.1.1 The functions of the menu bar

The *menu bar* provides a variety of different functions for the user. These functions are combined to groups which appear as menues if the user clicks on it. The list below gives a short overview. Additional descriptions can be found in the following sections.

- $\triangleright$  The menu File (cf. fig. 4.1a) has the following entries:
  - ▷ Insert Maple Command allows the insertion of an arbitrary command which is passed directly to Maple (cf. fig. 3.3). Especially the numerical input of masses, momenta and renormalization conditions can be done easily this way.
  - ▷ Save Maple Output saves the output as it is denoted in the Maple *text window* to an extra file. The name of the file has to be determined in a separate window, which appears if the user clicks on this entry.
  - $\triangleright$  New Process allows the user to collect a set of graphs and save them with a common process name. Detailed explanation can be found in section 4.1.3.
  - ▷ With Load Process processes which were declared with New Process before can be reloaded into the current  $\chi$  loops session (cf. sect. 4.1.3).
  - $\triangleright$  Create Process will call the graph generator to produce all graphs to a given number of loops and external lines in a pre-defined model (in future versions of *xloops* only).
  - $\triangleright$  Restart Maple terminates the current Maple session and removes all assigned variables. Maple and  $\chi foops$  are started again.
  - $\triangleright$  Quit terminates *xloops*.



Figure 4.1: The menues of the menu bar

- ▷ The menu Model (cf. fig. 4.1d) offers several physical models for calculation (for details cf. sect. 4.2.3).
- $\triangleright$  The menu Loops (cf. fig. 4.1e) selects the number of closed loops for the calculation. The user can choose between 0, 1 and 2. A change of this value results in different topologies displayed in the *topology bar*.
- $\triangleright$  The menu Ext. Lines (cf. fig. 4.1f) allows the user to choose the number of external lines. At the moment the upper limit is three. The change of this number results in a different *topology bar* as well.
- $\triangleright$  The menu Options (cf. fig. 4.1c) contains the following entries:
  - ▷ If History is selected *xloops* saves all calculations under a common process name. Those diagrams which were already saved before are read from disk. Otherwise, if History is not selected they are recalculated (cf. sect. 4.1.3).
  - $\triangleright$  With the selection of Oneloop Library  $\chi$  loops takes all one-loop functions from a pre-built library. Otherwise the one-loop functions are calculated every time they are needed (cf. sect. 4.5 and appendix B.2).
  - ▷ If Insert Particle Properties is selected the values of masses and couplings reported by the Particle Data Group [11] are inserted (cf. sect. 4.2.4).
  - ▷ Set Neutrino Masses 0 assigns all neutrino masses to zero (default) or, if not selected, leaves the neutrino masses unassigned. In this case an undefined neutrino mixing matrix exists as well (cf. sect. 4.2.4).

- $\triangleright$  Massless Light Fermions assigns the masses of all fermions except the *b* and *t* quark to zero (cf. sect. 4.2.4).
- ▷ Numeric defines the number of points and the number of iterations for the numerical integration with VEGAS (cf. sect. 4.6).
- ▷ Window Options allows the user to adjust the appearance of the Xwindows interface, especially the placement of the red arrows of the *diagram window* (cf. sect. 4.1.4).
- ▷ Save Options saves all options in the file .xloops in the home directory of the user.
- $\triangleright$  The menu Help (cf. fig. 4.1b) has three entries:
  - $\triangleright$  About shows a brief information on *xloops*.
  - $\triangleright$  Help gives a short help where especially the notation of all particle names in  $\chi loops$  is written.
  - ▷ Tutorial calls a WWW browser which displays the on-line html version of this manual.

#### 4.1.2 Topology bar and diagram window

According to the pre-defined values for the numbers of closed loops and external lines the *topology bar* displays all possible topologies. If the user clicks on one of them this topology appears in a separate window, the *diagram window*. This window consists of three parts: a *menu bar*, an area for inserting particles (*diagram area*) and a *command bar* with different buttons for evaluation (cf. fig. 4.2).

The *menu bar* provides two options. The right one, Export, gives the user the possibility to export the graph to a Postscript file. Only the *diagram area* of the *diagram window* is exported, *menu bar* and *command bar* are not included.

The left option, Subtopologies, will only be available in future versions. It will provide the possibility to switch between several subtopologies, which are obtained when external lines are interchanged. The upper topology in fig. 4.2 may serve as an example. This topology can be rotated by  $120^{\circ}$  or  $240^{\circ}$  which corresponds to a cyclic permutation of the external lines. This changes the topology to the same type of topology but with different momentum flow. In contrast, the lower topology in fig. 4.2 does not change if it is rotated by  $120^{\circ}$  or  $240^{\circ}$ . So this topology does not exhibit different subtopologies.

In the *diagram area* the topology is displayed graphically. For every propagator an entry for the insertion of particles is located. The correct terms for particle names are written in section 4.2.4. They can also be obtained from the Help function of the *main window*. The flow of charge and fermion and ghost numbers are determined by the red arrows on the propagator lines. Clicking on an arrow changes its direction. The correct flow of charge and fermion and ghost numbers can be settled in this way. Only particles, no antiparticles can be inserted. Charge conjugation may be achieved by inversion of arrows. Please keep in mind that the arrows don't describe the direction of momenta. The convention of momentum flow is shown graphically in the *diagram window* in blue. It is defined for all diagrams in the same way, to facilitate a final summation of all calculated diagrams.

If the user has inserted all particles and checked the charge flow, the *command area* gives him several possibilities for the evaluation of the diagram. They correspond to the different modes of evaluation as explained in section 4.2.10.



Figure 4.2: Different diagram windows

#### 4.1.3 Loading and saving of processes

For the evaluation of complete processes it is possible to save the contributing graphs with a common process name. Therefore  $\chi loops$  provides the File menu entries Load Process and New Process.

If Load Process is selected the *file window* (cf. fig. 4.3) appears on the screen. In this

- Load	History				
Existing Saved Processes					
Higgs_plus qed	H+ -> W+ h0 The basic QED graphs				
Process Name: ged					
ОК	Cancel				

Figure 4.3: The Load Process file window

window the processes which were already saved are listed on the left hand side. In addition for every process a user specified description is given on the right hand side. This may help to reidentify a process later. To select a specific process one clicks on a process name on the left. After clicking on the OK button the *history table* (cf. fig 4.4) of the selected process appears whereas Cancel closes the *file window*. In the *history table* all diagrams which were included in the corresponding process occur with a button. A click on such a button opens a *diagram window* (cf. fig 4.2) with which the Feynman diagram can be evaluated. The *history table* contains two menues:

- $\triangleright$  In Graphs one has the opportunity if the number of diagrams exceeds the capacity of the window to switch to another sheet of diagrams. The same effect have the arrows at the bottom of the *history table*.
- $\triangleright$  Close lets the *history table* disappear.

If the entry History of the Options menu is selected all results are saved. With History all calculations which were already saved in this or another  $\chi loops$  session are read in automatically and not calculated again. For each process  $\chi loops$  automatically creates a subdirectory of the directory  $\chi loops\_user$  where the results are saved to different files.

If History is selected without having specified a process before  $\chi foops$  assumes that a new process shall be added to the list and opens a similar file window (cf. fig 4.5) – the same window appears if New Process is selected. Two entries are provided for inserting a new process name and description at the bottom of the window. After the user inserted the name and description for his process and clicked on the OK button a new – and therefore empty – history table appears on the screen. All diagrams which are calculated from now are included in the history table as additional entries. The topology of the graph and the list of interacting particles are displayed.



Figure 4.4: The history table containing diagrams of the process  $H \to H$ 

- New I	History				
Existing Saved Processes					
Higgs_plus qed	H+ -> W+ h0 The basic QED graphs				
Process Name:					
Process Description:					
ок	Cancel				

Figure 4.5: The New Process file window

#### 4.1.4 Window options

With the entry Window Options of the Options menu the appearance of some windows of  $\chi loops$  can be adjusted to fit the terminal characteristics (cf. fig. 4.6). First, the size of the

- Window Options					
Size of History Window					
Rows: 15 Cohonns: 3	Set				
Arrow Scaling					
Please insert the place of the red arrow or a general scaling factor					
arrow peak place : 5 cm ScaleFactor : 1					
Set arrow place Set Factor	Close				

Figure 4.6: Window options of  $\chi loops$ 

history table (cf. fig. 4.4) can be changed by decreasing or increasing the numbers of the Rows and Columns entry in fig. 4.6. Then, the position of the arrows of the propagators in the diagram window can be corrected. This might be necessary on some terminal types, where the arrows of the propagators are misplaced. This has to do with the fact that the relation between screen dots (as used by Tk) and centimeters is different on different X terminals. The embarrassing consequence can be that the arrows of the propagators are misplaced. The problem can be avoided by inserting a global Scale Factor. Alternatively, if this factor is not obvious,  $\chi foops$  will calculate it. Therefore the user must insert the

position of the arrow on the ruler in the Arrow Scaling field of fig.  $4.6.^{1}$ 

### 4.2 Evaluation of Feynman diagrams

#### 4.2.1 Input

To evaluate a particular Feynman diagram *xloops* needs to know four ingredients:

- 1. The number of closed loops.
- 2. The number of external lines.
- 3. The topology, that means the information how the lines of the diagram are connected.
- 4. The particles of the diagram.

The first two numbers have to be selected with the help of the *menu bar* entries Loops and Ext. Lines (cf. sect. 4.1.1). Then the topology can be selected on the *topology bar* so that the *diagram window* pops up where the particles can be inserted (cf. sect. 4.1.2).

Internally the input from the Xwindows interface is converted to a procedure which performs the calculations in Maple. It is also possible to start directly from this routine for Maple – either with the Insert Maple Command of the File menu or within an ordinary Maple session where the Maple part of  $\chi$  foops was read in before (cf. sect. 2.5).

For that purpose the internal Maple commands will be mentioned in the following. All commands which follow without reference to the Xwindows interface have to be passed to Maple.

The input is then of the following form

- $\triangleright$  for tree diagrams: EvalGraph0(n,  $\langle list \rangle$ );
- $\triangleright$  for one-loop diagrams: EvalGraph1(n,  $\langle list \rangle$ );
- $\triangleright$  for two-loop diagrams: EvalGraph2(n,  $\langle list \rangle$ );

The different topologies with the same number of loops are numbered. The number of the desired topology has to be inserted in the function call for n. The correct number for each topology will be given below in sect. 4.2.2.  $\langle list \rangle$  describes the list of particles involved in the Feynman diagram. The conventions for the ordering of the particles are also explained for every topology in 4.2.2.

#### 4.2.2 Internal Notation

What follows is a list of all topologies which at present can be solved by *xloops*. This list is only of interest for direct Maple input. To fix the flow of charges and of fermion or ghost numbers in an unique way, each internal propagator is assigned with two particle names. For example [up,upbar] and [upbar,up] describe the up-quark propagator but with different direction of the quark line arrow. External lines are described by only one particle name.

As a convention all particles at each vertex are incoming. The arrows of the diagrams displayed below only describe the flow of momenta. Of course these arrows need not to coincide with the arrows of fermions or other charged particles.

For each topology we give the correct EvalGraph command as well as the command for the corresponding OneLoop or TwoLoop integral.

<sup>&</sup>lt;sup>1</sup>If the scaling factor is already correct, the arrow should point on the 5.

## Tree level

#### Three-point diagrams



## Four-point diagrams



### **One-loop** level

#### **One-point** diagrams



## Two-point diagrams





### Three-point diagrams





## Two-loop level

#### Two-point diagrams









For each encircled number one particle has to be inserted. The correct symbols for all allowed particles are listed in the next section. The conventions for the OneLoop and TwoLoop functions are denoted in sect. 4.3 and 4.4.

#### 4.2.3 Models

 $\chi$  foops distinguishes several models. The menu Model of the menu bar serves for the selection of the desired model. Internally the global variable Model selects the model which shall be used. The following models are declared in  $\chi$  foops:

- ▷ Standard Model the (minimal) standard model (electroweak and QCD). This corresponds to Model:=SM; and is the default value
- ▷ 2 Higgs Doublets Model the standard model with two Higgs doublets which corresponds to five physical Higgs particles; Model:=THDM;
- $\triangleright$  QCD QCD with three generations of Quarks; Model:=QCD;
- ▷ Electroweak Theory the electroweak sector of the standard model; Model:=EW;
- $\triangleright$  QED QED with three generations of Leptons and Quarks; Model:=QED;
- $\triangleright$  Phi<sup>4</sup> Theory  $\phi^4$ -theory in four dimensions; Model:=phifour;
- $\triangleright$  Phi<sup>3</sup> Theory  $\phi^3$ -theory in four dimensions; Model:=phithree;
- ▷ Goldstone Boson Equiv. Model the equivalence model for Goldstone bosons standard model vector bosons are replaced by scalar Goldstone modes [12–14]; Model:=GBEM;
- ▷ a user-defined model where arbitrary Feynman rules can be declared. To work with this option the user has to set Model:=user; and to read an additional file

read'(path)fmuser.ma';

where  $\langle path \rangle$  is the same path used for the assignment of LoopPath at the beginning of the Maple session (cf. sect. 2.5). In the file fmuser.ma the user-defined rules have to be inserted. Initially all QCD Feynman rules are denoted there as an example. The conventions of declaration can be taken from this example.

#### 4.2.4 Particles and Masses

What follows is a list which contains all particles  $\chi loops$  knows. The names valid in the Xwindows interface are denoted (second column from the left) as well as the names for internal use within Maple (third column from the left). In addition for each particle the models in which it is declared (right column) and the name which  $\chi loops$  uses for the corresponding particle mass (second column from the right) are listed.

•	-→ f, phi	<pre>① = phi ② = phi</pre>	$m_\phi=$ Mphi	phithree, phifour
$\overbrace{1}^{m_{\nu_e}}$	→ ve, nuelec	(1) = nuelec (2) = nuelecbar	$m_{ u_e}=$ Mnuelec	SM, EW, QED, THDM, GBEM
$\underbrace{\begin{array}{c} m_e \\ \hline 1 \end{array} (2) \end{array}$	→ e, elec	(1) = elec (2) = elecbar	$m_e = \; {\rm Melec}$	SM, EW, QED, THDM, GBEM
$\underbrace{\begin{array}{c} m_{\nu_{\mu}} \\ \hline 1 \\ \hline \end{array}}_{m_{\nu_{\mu}}} 2$	→ vµ, numu	(1) = numu (2) = numubar	$m_{ u_{\mu}}=$ Mnumu	SM, EW, QED, THDM, GBEM
$\underbrace{\begin{array}{c} m_{\mu} \\ \hline 1 \\ \hline \end{array}} $	<b>→</b> μ, mu	$\begin{array}{ccc} (1) &= & \mathtt{mu} \\ (2) &= & \mathtt{mubar} \end{array}$	$m_{\mu}=$ Mmu	SM, EW, QED, THDM, GBEM
$\underbrace{\begin{array}{c} m_{\nu_{\tau}} \\ \hline 1 \\ \end{array}} $	→ vy, nutau	(1) = nutau (2) = nutaubar	$m_{ u_{ au}}=$ Mnutau	SM, EW, QED, THDM, GBEM
$\underbrace{\begin{array}{c} m_{\tau} \\ \hline 1 \end{array} (2) \end{array}$	→ y, tau	(1) = tau (2) = taubar	$m_ au=$ Mtau	SM, EW, QED, THDM, GBEM
	—• u, up	(1) = up (2) = upbar	$m_u = \; { m Mup}$	SM, EW, QED, QCD, THDM, GBEM

$\underbrace{\begin{array}{c} m_d \\ \hline 1 \end{array}}^{m_d} 2$	d, down	$\begin{array}{l} (1) = \texttt{down} \\ (2) = \texttt{downbar} \end{array}$	$m_d={ m Mdown}$	SM, EW, QED, QCD, THDM, GBEM
$\underbrace{\begin{array}{c} m_c \\ \hline 1 \end{array}}^{m_c} 2$	c, charm	(1) = charm (2) = charmbar	$m_c =  {\tt Mcharm}$	SM, EW, QED, QCD, THDM, GBEM
$m_s$	s, strange	(1) = strange (2) = strangebar	$m_s = M { m strange}$	SM, EW, QED, QCD, THDM, GBEM
$\underbrace{\begin{array}{c} m_t \\ \hline 1 \end{array}}^{m_t} 2$	t, top	$\begin{array}{ll} (1) &= \texttt{top} \\ (2) &= \texttt{topbar} \end{array}$	$m_t =  { m Mtop}$	SM, EW, QED, QCD, THDM, GBEM
$\underbrace{\begin{array}{c} m_b \\ \hline 1 \end{array}}^{m_b} 2$	b, bottom	(1) = bottom (2) = bottombar	$m_b =  { m Mbottom}$	SM, EW, QED, QCD, THDM, GBEM
$\overbrace{1}^{m_{\gamma}}$	~, gamma	(1) = gamma (2) = gamma	$m_\gamma =$ Mgamma $= 0$	SM, EW, QED, THDM, GBEM
	W, wp	$\begin{array}{rcl} (1) &= & \texttt{wp} \\ (2) &= & \texttt{wm} \end{array}$	$m_W=$ Mw	SM, EW, THDM, GBEM
	Z, z0	$\begin{array}{rcl} (1) &= & z 0 \\ (2) &= & z 0 \end{array}$	$m_Z={ m Mz0}$	SM, EW, THDM, GBEM

••••••••••••••••••••••••••••••••••••••		g, gluon	<ol> <li>(1) = gluon</li> <li>(2) = gluon</li> </ol>	$m_g = Mgluon = 0$	SM, QCD, THDM
•	<b>-</b>	H, higgs	<ol> <li>= higgs</li> <li>= higgs</li> </ol>	$m_H=$ Mhiggs	SM, EW, GBEM
• ① ②	<b>-</b>	g+, goldp	$\begin{array}{llllllllllllllllllllllllllllllllllll$	_	SM, EW, THDM
•	•	g0, gold0	<ol> <li>(1) = gold0</li> <li>(2) = gold0</li> </ol>	_	SM, EW, THDM
<i>m</i> <sub>H₀</sub>		H. Higgs()	(1) = Higgs0	$m_{H_2} = MHiggs0$	THDM
1 2		.,	(2) = HiggsO		
$\begin{array}{c} m_{h_0} \\ \hline 1 \\ \end{array} $	<b>-</b>	h, higgs0	<ol> <li>= higgs0</li> <li>= higgs0</li> </ol>	$m_{h_0}=$ MhiggsO	THDM

36


Please note that the masses of the neutrinos are set to zero by default. To keep them as variables, one can switch off the entry Set Neutrino Mass 0 of the Options menu or use

UnsetNeutrinoMass0();

within Maple which removes any assignment of Mnuelec, Mnumu and Mnutau. As a consequence now a leptonic CKM matrix exists which behaves analogous to the usual CKM matrix of quarks (cf. sect. 4.2.6). The reverse command

```
SetNeutrinoMass0();
```

or the reselection of Set Neutrino Mass 0 sets all neutrino masses back to zero. The leptonic CKM matrix equals now the unit matrix.

The masses of photon and gluon are also set to zero by default. To keep them as variables you have to type

```
Mgamma:='Mgamma'; Mgluon:='Mgluon';
```

The masses of leptons and light quarks – all standard model fermions except b and t quark – can collectively be set to zero with the entry Massless Light Fermions of the Options menu or with

SetLightMass0();

and be unassigned with

UnsetLightMass0();

or another click on Massless Light Fermions. Apart from this, masses, momenta and couplings – as they are explained in the following sections – can be assigned by the user.

Moreover, if you want to assign all particle masses<sup>2</sup> as well as the couplings, the Cabibbo-Kobayashi-Maskawa matrix (CKM matrix) and the Weinberg angle with their experimentally determined values, you can use the entry Insert Particle Properties of the Options menu or type

```
read'(path)values.ma';
```

where  $\langle path \rangle$  is the same path used for the assignment of LoopPath at the beginning of the Maple session (cf. sect. 2.5). The file values.ma contains the parameters according to the currently published data of the Particle Data Group [11]. To remove all information of values.ma in a Maple session you can type

```
read'\langle path \rangleunvalue.ma';
```

or switch off the Insert Particle Properties entry. Instead of the fermion names which were already introduced one can also use the more general terms

up1, up2, up3, down1, down2, down3.

The difference is, that for these terms no electric charge Q and no weak isospin T31 is

<sup>&</sup>lt;sup>2</sup>Unfortunately the Higgs mass is not yet included

defined. While *xloops* assumes

Q(elec) = -1; T31(elec)  $= -\frac{1}{2};$   $Q(up) = \frac{2}{3};$  T31(up)  $= \frac{1}{2};$  ...

it has no values for Q(up1), T31(up1), ... and the user has the opportunity to make use of this freedom.

#### 4.2.5 Feynman rules

Since the conventions for Feynman rules vary in the literature, it is important to explain one's own rules: We use Feynman gauge, for electroweak processes according to the rules given in [15], but with all three-vertices and all propagators multiplied by -i and all fourvertices and the integration measure multiplied by i. This convention coincides with the rules of [16] – as far as these are applicable in Feynman gauge. From [16] we took the rules for QCD and the notation of the CKM matrix, too. The rules for the Two Higgs doublet model are from [17].

Anyway, you receive the rule for one particular vertex easily if you just use the tree level topologies or call the EvalGraph0 procedure.

In our convention the electromagnetic coupling  $\mathbf{e}$  and the strong coupling  $\mathbf{gs}$  are positive (the electric charge of the electron is  $-\mathbf{e}$ ). *xloops* automatically inserts a factor  $(2\pi)^{2\varepsilon-4}$  for every closed loop and an additional -1 for each fermion and ghost loop. This means that the dimension – which *xloops* calls D – equals 4 - 2 eps. The correct symmetry factor of the diagram is also included. The scale which keeps the coupling constants dimensionless is called MU.

#### 4.2.6 Mixing angles and CKM matrix

Three mixing angles are known by *xloops*: The usual Weinberg angle tw and - only relevant in the case of the Two Higgs doublet model - the angles alpha and beta (cf. [17]). The elements of the CKM matrix are denoted by CKM(up,down) ..., its complex conjugates are CKMC(up,down) .... If neutrino masses are not set equal to zero there exists also a leptonic CKM matrix with elements like CKM(nuelec,elec). If the neutrino masses are set to zero - which is the default (cf. sect. 4.2.4) - this matrix equals the unit matrix.

#### 4.2.7 Momenta and Metric

The external momenta q1(nu1), q2(nu1), ... may occur in two different contexts,

- 1. as Lorentz vectors q1(nu1), ... with Lorentz indices nu1, ...,
- 2. contracted with another Lorentz vector.

In the first case the momentum will appear in the output as it is. In the second case the contraction will be written in terms of parallel space components:

$$q10 = \sqrt{q_1^2}; \quad q20 = \frac{q_1 \cdot q_2}{\sqrt{q_1^2}}; \quad q21 = \sqrt{\frac{(q_1 \cdot q_2)^2}{q_1^2} - q_2^2};$$

$$q30 = \frac{q_1 \cdot q_3}{\sqrt{q_1^2}}; \quad q31 = -\frac{\hat{q}_2 \cdot q_3}{\sqrt{-\hat{q}_2^2}}; \quad q32 = \sqrt{\frac{(q_1 \cdot q_3)^2}{q_1^2} + \frac{(\hat{q}_2 \cdot q_3)^2}{\hat{q}_2^2} - q_3^2},$$

$$(4.1)$$

where the auxiliary property

$$\hat{q}_2 = q_2 - \frac{q_1 \cdot q_2}{q_1^2} q_1 \tag{4.2}$$

was used. In appendix A we demonstrate how this works in practice.

The metric tensor of *xloops* is G(nu1,nu2). It obeys the usual conventions

$$G(0,0) = 1;$$
  $G(1,1) = -1$  ...

The contraction of G(nu1,nu2) depends on whether the indices nu1 and nu2 are orthogonal space indices – then G(nu1,nu1) = D - DimP – or belong to the entire Minkowski space – this means that G(nu1,nu1) = D.

The totally antisymmetric tensor is Eps(nu1,nu2,nu3,nu4) with Eps(0,1,2,3) = 1.

#### 4.2.8 Dirac matrices

Dirac  $\gamma$ -matrices *xloops* calls Dg(mu1), .... Like the external momenta they can appear either as Lorentz vector as they are, or contracted by another Lorentz vector. In the latter case they are denoted by

$$Dg0 = \frac{\not q_1}{\sqrt{q_1^2}}; \quad Dg1 = -\frac{\not q_2}{\sqrt{-\hat{q}_2^2}}; \quad Dg2 = -\frac{\not q_3}{\sqrt{-\hat{q}_3^2}}$$
(4.3)

with

$$\hat{q}_3 = q_3 - \frac{q_1 \cdot q_3}{q_1^2} q_1 - \frac{\hat{q}_2 \cdot q_3}{\hat{q}_2^2} \hat{q}_2 \tag{4.4}$$

and the abbreviation (4.2). The Dirac structure is written as a string of the noncommutative product &\*. Since the program is also designed for diagrams with more than one fermion line it labels each string of Dirac matrices with a number. For example in the case of fermionic self-energies

will occur in the output – the latter two of course only in the case of W, Z or Goldstone boson exchange. ONE represents the identity of the Clifford algebra, Dg5 is  $\gamma_5$ . The first entry in the non-commutative string gives the number of the fermion line. The 1 means that the string belongs to the first fermion line which in this case is the only fermion line. In appendix A this treatment can be seen in practice.

#### 4.2.9 $SU(N_c)$ algebra

In QCD calculations *xloops* keeps the colour number Nc unassigned by default, but with

Nc:=3;

the number is fixed to its standard model value. The  $SU(N_c)$  algebra needs as ingredients

▷ the identity matrix of the SU(N<sub>c</sub>) algebra delta3(ta1,ta2) which should not be mixed with Kronecker delta8(ta1,ta2) which contracts the Gell-Mann matrices with the labels ta1 and ta2. Of course delta3(ta1,ta2) and delta8(ta1,ta2) are both diagonal with entries 1 in the diagonal. This means that

$$\sum_{\tt ta1} \tt delta3(ta1,ta1) = N_c = 3\,; \qquad \sum_{\tt ta1} \tt delta8(ta1,ta1) = N_c^2 - 1 = 8\,.$$

▷ the Gell-Mann matrices Ts(ta1,ta2,ta3) themselves, where ta1 – which is the number of the matrix – can take values from 1 to  $N_c^2$  – 1. ta2 and ta3 are the indices of a particular Gell-Mann matrix and therefore have values from 1 to  $N_c$ . The Ts(ta1,ta2,ta3) are normalized by the following trace condition:

$$\sum_{ta3,ta4} Ts(ta1,ta3,ta4) Ts(ta2,ta4,ta3) = 2 delta8(ta1,ta2)$$

 $\triangleright$  the usual structure functions fs(ta1,ta2,ta3) and ds(ta1,ta2,ta3) where all three indices vary from 1 to  $N_c^2 - 1$ . They are defined by the Lie algebra relation

$$\sum_{ta5} Ts(ta1,ta3,ta5) Ts(ta2,ta5,ta4) \\ = \frac{2}{Nc} delta8(ta1,ta2) delta3(ta3,ta4) \\ + \sum_{ta5} ds(ta1,ta2,ta5) Ts(ta5,ta3,ta4) \\ + i \sum_{ta5} fs(ta1,ta2,ta5) Ts(ta5,ta3,ta4),$$

where the fs(ta1,ta2,ta5) are completely antisymmetric and the ds(ta1,ta2, ta5) are completely symmetric.

#### 4.2.10 Output

The output of the diagrams is decomposed in one or several form factors C1, C2, ... to reflect the Dirac  $\gamma$  or Lorentz structure of the result. Therefore a list of form factors is returned. The last entry in this list is the defining equation for the form factors. The result is presented in the Maple *text window* of the *main window* and has the following structure:

$$G1 := \underbrace{[C1 = \dots, \dots, Cn = \dots, C1 \quad q1(nu1) \quad q2(nu2) + \dots + Cn \quad G(nu1, nu2) \dots]}_{\text{the form factors } Ci} \underbrace{C1 \quad q1(nu1) \quad q2(nu2) + \dots + Cn \quad G(nu1, nu2) \dots]}_{\text{defining equation for form factors}}$$

Let us consider for instance the self-energy of a vector boson.  $\chi loops$  finds as Lorentz structure C1 G(nu1,nu2) + C2 q1(nu1) q1(nu2) and the output roughly looks like

[C1 = term1, C2 = term2, C1 G(nu1, nu2) + C2 q1(nu1) q1(nu2)],

where term1 and term2 denote the form factors. In the case of a fermionic self-energy the result carries no Lorentz index. Instead, it is decomposed with respect to &\*(1,ONE), &\*(1,Dg5), &\*(1,Dg0) and &\*(1,Dg5,Dg0) and in the general case the result is of the form

Here all  $\gamma$ -matrices are contracted. In vertex functions with a fermion line and a vector boson there is also a Dg(nu1) appearing. In appendix A several examples are given in more detail. In the case of a scalar self-energy there appears only one form factor and the result reads

$$[C1 = term1, C1].$$

The form factors can be written in several modes of evaluation which correspond to the different buttons of the *diagram windows*:

- ▷ With Evaluate or if no qualifier is added to the EvalGraph procedures the output for simplicity is returned in terms of unevaluated Oneloop and Twoloop functions which correspond directly to the OneLoop and TwoLoop functions explained in sect. 4.3 and 4.4.
- ▷ To get complete answers, Eval. Full or in the case of EvalGraph1 and EvalGraph2 the qualifier full forces *xloops* to evaluate directly the Oneloop and Twoloop integrals. To be precise, you have to type

EvalGraph $m(n, \langle list \rangle, full);$ 

where *m* and *n* are numbers. Now each form factor C1, ... is a Laurent expansion in terms of the ultraviolet regulator  $\varepsilon = (4 - D)/2$ , where the significant coefficients of this expansion  $-\mathcal{O}(\varepsilon^{-1})$ ,  $\mathcal{O}(\varepsilon^{0})$  in the one-loop case,  $\mathcal{O}(\varepsilon^{-2})$ ,  $\mathcal{O}(\varepsilon^{-1})$ ,  $\mathcal{O}(\varepsilon^{0})$  in the two-loop case – are denoted in form of a list. The bosonic self-energy we introduced before now has the structure

$$\begin{bmatrix} C1 = [\varepsilon^{-1} - term, \varepsilon^0 - term], \\ C2 = [\varepsilon^{-1} - term, \varepsilon^0 - term], C1 \ G(nu1, nu2) + C2 \ q1(nu1) \ q1(nu2)]$$

for one-loop contributions and

$$\begin{bmatrix} C1 = [\varepsilon^{-2} - term, \varepsilon^{-1} - term, \varepsilon^{0} - term], \\ C2 = [\varepsilon^{-2} - term, \varepsilon^{-1} - term, \varepsilon^{0} - term], C1 \quad G(nul, nu2) + C2 \quad ql(nul) \quad ql(nu2)]$$

for two-loop diagrams.  $\varepsilon^{-2}$ -term and  $\varepsilon^{-1}$ -term are meant to represent the divergent part (the coefficients of  $\frac{1}{\varepsilon^2}$  and  $\frac{1}{\varepsilon}$ ) whereas  $\varepsilon^0$ -term is describing the finite part of the corresponding form factor. For those two-loop topologies where no analytic result is known, the finite part contributes two entries to the output list. The first of them is a list itself which denotes an integral representation, the second contains the part which is analytically calculable:

$$\begin{bmatrix} C1 = [\varepsilon^{-2} \text{-}term, \varepsilon^{-1} \text{-}term, numeric, \varepsilon^{0} \text{-}term], \\ C2 = [\varepsilon^{-2} \text{-}term, \varepsilon^{-1} \text{-}term, numeric, \varepsilon^{0} \text{-}term], \\ C1 \quad G(nu1, nu2) + C2 \quad g1(nu1) \quad g1(nu2)]. \end{bmatrix}$$

A more detailed description of the integral representation – which was called here numeric – is given in sect. 4.4.3.

▷ The integral representation is evaluated directly with the help of VEGAS if Eval. Numeric is used or if the qualifier full replaced by two lists which contain the input information for VEGAS:

`EvalGraphm(n, 
$$\langle \textit{list} 
angle$$
, [ $m_1, m_2$ ], [ $n_1, n_2$ ]);`

Within an ordinary Maple session one has in addition to assign the variable NumPath as described in sect. 4.6. The variables  $m_1, m_2, n_1, n_2$  represent the grids where the integrand is evaluated: first  $m_1$  iterations with  $m_2$  points – itmx=  $m_1$  and ncall=  $m_2$ are passed to VEGAS – and then  $n_1$  iterations with  $n_2$  points – this corresponds to itmx=  $n_1$  and ncall=  $n_2$ . In the Xwindow interface these values can be changed with the entry Numeric of the Options menu (cf. sect. 4.6). Real and imaginary part are integrated one after the other. The output has then the following structure:

$$\begin{bmatrix} C1 = [\varepsilon^{-2} \text{-}term, \varepsilon^{-1} \text{-}term, [factor, [result, error]], \varepsilon^{0} \text{-}term], \\ C2 = [\varepsilon^{-2} \text{-}term, \varepsilon^{-1} \text{-}term, [factor, [result, error]], \varepsilon^{0} \text{-}term], \\ C1 \ G(nu1, nu2) + C2 \ q1(nu1) \ q1(nu2)] \end{bmatrix}$$

where *factor* denotes an analytically evaluated pre-factor of the integrand. The result of the integral itself is called *result* here, *error* describes the uncertainty of the numerical integration which is returned by VEGAS. To be specific: the entire  $\mathcal{O}(\varepsilon^0)$  contribution is obtained by

$$factor \times result + \varepsilon^0$$
-term,

the complete uncertainty is

 $factor \times error$ ,

where the uncertainty of  $\varepsilon^0$ -term is neglected.

If not all parameters of the integrand carry numerical values the numerical integration cannot be performed. Therefore the same output as for the qualifier full is returned.

 $\triangleright$  With Eval. More or in the case of EvalGraph1, with the qualifier more instead of full, *xloops* evaluates even the  $\mathcal{O}(\varepsilon)$  of one-loop integrals. This becomes relevant if the one-loop integral is part of a two-loop calculation, because then it may be multiplied with a divergent one-loop Z-factor. This changes the output of a bosonic self-energy:

$$\begin{bmatrix} \mathsf{C1} = [\varepsilon^{-1} - term, \varepsilon^0 - term, \varepsilon^1 - term], \\ \mathsf{C2} = [\varepsilon^{-1} - term, \varepsilon^0 - term, \varepsilon^1 - term], \\ \mathsf{C1} \ \mathsf{G(nu1,nu2)} + \mathsf{C2} \ \mathsf{q1(nu1)} \ \mathsf{q1(nu2)}].$$

As far as the masses and momenta which enter the EvalGraph functions are symbols the output is given algebraically, whereas if they are all assigned with numbers the result will be numerical.

Generally, in the numerical case, the program sets the value of the imaginary part of the propagators, five digits higher than the numerical accuracy of the whole calculation, for example to  $10^{-15}$  if one calculates with 20 digits. When reading the program Maple sets the number of digits to 20 – except when the user specified a higher accuracy before, for instance:

Digits:=40;

In the algebraic case just **rho** is returned. The output is facilitated by the usage of several abbreviations (4.23, 4.24, 4.25, 4.26) for certain one-loop contributions which are introduced in detail in the context of the **OneLoop** procedure in sect. 4.3.3. The abbreviations are substituted if the **evalRex** command is used (cf. sect. 4.3.3).

#### 4.2.11 Special relations

If external momenta are zero or parallel,  $\chi foops$  omits those Lorentz vectors which are no longer independent and therefore redundant. The number of form factors – and the dimension of the parallel space – may decrease. If this is the case the form factors will no longer be expressed in terms of proper OneloopnPt and TwoloopnPtm functions, but with the help of its variants  $Oneloopk_nPt$  and  $Twoloopk_nPtm$  which are reduced in dimension of parallel space. The  $Oneloopk_nPt$  functions correspond to the  $OneLoopk_nPt$  functions from sect. 4.3.

If for instance in the case of the two-point function the external momentum q1 shall vanish, one has to make the following assignment before starting the calculation:

#### q10:=0;

Now the bosonic self-energy reduces to

[C1 = term1, C1 G(nu1,nu2)]

which means that one form factor vanished. The only remaining form factor is expressed by a **Oneloop1\_2Pt** function – this is a two-point function with a parallel space of dimension zero. The notation "1\_2Pt" reflects the fact that this function carries properties of the two-point function as well as of the one-point function.

If in the case of a three-point function both external momenta q1 and q2 have a common rest frame one has to make the assignment

q21:=0;

Now the momentum q2 will disappear from the equation which defines the form factors since it is no longer independent of q1 ("zero recoil limit"). In addition the proper Oneloop3Pt will switch to Oneloop2\_3Pt functions – a mixing of two- and three-point functions.

It is important here to make the assignment first and then to evaluate the diagram, because otherwise number and shape of form factors may be wrong. Moreover, if special relations exist which fix the variables of the EvalGraph functions or connect them with each other – like for instance the on-shell condition which connects masses and momenta – it is important first to declare these relations and then evaluate the functions.

Otherwise, if the functions are evaluated first analytically and then numbers or relations between variables are substituted in the result, Maple has to do more work than necessary. Moreover, it might happen in some special cases that an error occurs – something like "division by 0". Usually this sort of divergence is artificial and not an error  $\chi loops$  is responsible for – at the moment of calculation the parameters which cause the error message were general analytical expressions. The problem can be overcome in either expanding in the critical parameters before the insertion of values, or – and this is recommended here – in calling the diagram window or the EvalGraph routines with the final values for the arguments from the very beginning, because the program was taught to detect a lot of this critical points and to avoid such artificial infinities in the result.

#### 4.2.12 Fast evaluation

If the entry Oneloop Library of the Options menu is selected or – within an ordinary Maple session – the variable LibPath is assigned with some path, the procedures assume that a library of OneLoop functions is stored in the assigned directory – as described in sect. 4.5. The necessary integrals are then read from this directory – which of course is much faster (see sect. B.3). Otherwise, if LibPath is not assigned, the procedures are forced to recalculate the necessary OneLoop functions at any occurrence.

### 4.3 The OneLoop procedures

#### 4.3.1 Input

There exist nine basic functions for the calculation of one-loop integrals. The first three functions

- $\triangleright$  OneLoop1Pt(p, m, t)
- $\triangleright$  OneLoop2Pt $(p_0, p_{\perp}, q_{10}, m_1, m_2, t_1, t_2)$
- $\triangleright$  OneLoop3Pt $(p_0, p_1, p_\perp, q_{10}, q_{20}, q_{21}, m_1, m_2, m_3, t_1, t_2, t_3)$

correspond to the notation in parallel and orthogonal space variables. The next three functions

- $\triangleright$  OneLoop1\_2Pt $(p, m_1, m_2, t_1, t_2)$
- $\triangleright$  OneLoop1\_3Pt $(p, m_1, m_2, m_3, t_1, t_2, t_3)$
- $\triangleright$  OneLoop2\_3Pt $(p_0, p_{\perp}, q_{10}, q_{20}, m_1, m_2, m_3, t_1, t_2, t_3)$

are used in the case of reduced parallel space. All abovementioned functions require the tensor degree, the external momenta  $q_n$  and the masses  $m_n$  as input. The powers  $t_n$  of the propagator terms in the denominator are optional. The remaining three functions

- $\triangleright$  OneLoopTens1Pt(i, m, t)
- $\triangleright$  OneLoopTens2Pt $(i, q_1^2, m_1, m_2, t_1, t_2)$
- $\triangleright$  OneLoopTens3Pt $(i, q_1^2, q_2^2, (q_2 q_1)^2, m_1, m_2, m_3, t_1, t_2, t_3)$

require the squared external momenta as input variables and return the complete rank-i tensor. The powers  $t_n$  of the propagator terms in the denominator again are optional.

#### 4.3.2 Notation

In detail the basic functions directly correspond to the following integrals:

 $\triangleright$  One-point function:



$$\texttt{OneLoop1Pt}(p,m,t) = A^{(p)(t)}(m) = \int d^D l \ \frac{(l^2)^{\frac{p}{2}}}{[l^2 - m^2 + i\varrho]^t}$$
(4.5)

OneLoop1Pt(p,m) = OneLoop1Pt(p,m,1)

OneLoopTens1Pt
$$(i, m, t) = A^{(t)}_{\mu_1 \cdots \mu_i}(m) = \int d^D l \; \frac{l_{\mu_1} \cdots l_{\mu_i}}{[l^2 - m^2 + i\varrho]^t}$$
(4.7)

$$\texttt{OneLoopTens1Pt}(i,m) = \texttt{OneLoopTens1Pt}(i,m,1). \tag{4.8}$$

(4.6)

 $\triangleright$  Two-point function:



 $\texttt{OneLoop2Pt}(p_0, p_{\perp}, q_{10}, m_1, m_2, t_1, t_2) = B^{(p_0 p_{\perp})(t_1 t_2)}(q_{10}, m_1, m_2)$ 

$$= \int d^D l \; \frac{(l_0)^{p_0} \; (l_\perp)^{p_\perp}}{[(l+q_1)^2 - m_1^2 + i\varrho]^{t_1} \; [l^2 - m_2^2 + i\varrho]^{t_2}} \tag{4.9}$$

$$\texttt{OneLoop2Pt}(p_0, p_\perp, q_{10}, m_1, m_2) = \texttt{OneLoop2Pt}(p_0, p_\perp, q_{10}, m_1, m_2, 1, 1)$$
(4.10)

 $OneLoop1_2Pt(p, m_1, m_2, t_1, t_2)$ 

$$= \int d^D l \; \frac{(l^2)^{\frac{p}{2}}}{[l^2 - m_1^2 + i\varrho]^{t_1} [l^2 - m_2^2 + i\varrho]^{t_2}} \tag{4.11}$$

$$\texttt{OneLoop1_2Pt}(p, m_1, m_2) = \texttt{OneLoop1_2Pt}(p, m_1, m_2, 1, 1)$$
(4.12)

OneLoopTens2Pt $(i, q_1^2, m_1, m_2, t_1, t_2) = B_{\mu_1 \cdots \mu_i}^{(t_1, t_2)}(q_1^2, m_1, m_2)$ =  $\int d^D l \; \frac{l_{\mu_1} \cdots l_{\mu_i}}{[(l+q_1)^2 - m_1^2 + i\varrho]^{t_1} [l^2 - m_2^2 + i\varrho]^{t_2}}$  (4.13)

OneLoopTens2Pt
$$(i, q_1^2, m_1, m_2)$$
 = OneLoopTens2Pt $(i, q_1^2, m_1, m_2, 1, 1)$ . (4.14)

Abbreviations:

$$q_{10} = \sqrt{q_1^2}; \quad l_0 = \frac{l \cdot q_1}{\sqrt{q_1^2}}; \quad l_\perp = \sqrt{l_0^2 - l^2}.$$
 (4.15)

 $\triangleright$  Three-point function:



 $\texttt{OneLoop3Pt}(p_0, p_1, p_\perp, q_{10}, q_{20}, q_{21}, m_1, m_2, m_3, t_1, t_2, t_3)$ 

$$= C^{(p_0 p_1 p_\perp)(t_1, t_2, t_3)}(q_{10}, q_{20}, q_{21}, m_1, m_2, m_3)$$

$$= \int d^D l \; \frac{(l_0)^{p_0} \, (l_1)^{p_1} \, (l_\perp)^{p_\perp}}{[(l+q_1)^2 - m_1^2 + i\varrho]^{t_1} \, [(l+q_2)^2 - m_2^2 + i\varrho]^{t_2} \, [l^2 - m_3^2 + i\varrho]^{t_3}}$$
(4.16)

 $\texttt{OneLoop3Pt}(p_0, p_1, p_{\perp}, q_{10}, q_{20}, q_{21}, m_1, m_2, m_3)$ 

$$= \text{OneLoop3Pt}(p_0, p_1, p_\perp, q_{10}, q_{20}, q_{21}, m_1, m_2, m_3, 1, 1, 1)$$

$$(4.17)$$

 $\texttt{OneLoop2_3Pt}(p_0, p_\perp, q_{10}, q_{20}, m_1, m_2, m_3, t_1, t_2, t_3)$ 

$$= \int d^D l \; \frac{(l_0)^{p_0} \; (l_\perp)^{p_\perp}}{[(l+q_1)^2 - m_1^2 + i\varrho]^{t_1} \; [(l+q_2)^2 - m_2^2 + i\varrho]^{t_2} \; [l^2 - m_3^2 + i\varrho]^{t_3}}$$

 $\texttt{OneLoop2\_3Pt}(p_0, p_{\perp}, q_{10}, q_{20}, m_1, m_2, m_3)$ 

$$= \text{OneLoop2_3Pt}(p_0, p_\perp, q_{10}, q_{20}, m_1, m_2, m_3, 1, 1, 1)$$
(4.18)

OneLoop1\_3Pt $(p, m_1, m_2, m_3, t_1, t_2, t_3)$ 

$$= \int d^D l \; \frac{(l^2)^{\frac{p}{2}}}{[l^2 - m_1^2 + i\varrho]^{t_1} \; [l^2 - m_2^2 + i\varrho]^{t_2} \; [l^2 - m_3^2 + i\varrho]^{t_3}}$$

 $\texttt{OneLoop1_3Pt}(p, m_1, m_2, m_3) = \texttt{OneLoop1_3Pt}(p, m_1, m_2, m_3, 1, 1, 1) \tag{4.19}$ 

OneLoopTens3Pt
$$(i, q_1^2, q_2^2, (q_2 - q_1)^2, m_1, m_2, m_3, t_1, t_2, t_3)$$
  

$$= C^{(t_1, t_2, t_3)}_{\mu_1 \cdots \mu_i} (q_1^2, q_2^2, (q_2 - q_1)^2, m_1, m_2, m_3)$$

$$= \int d^D l \, \frac{l_{\mu_1} \cdots l_{\mu_i}}{[(l + q_1)^2 - m_1^2 + i\varrho]^{t_1} [(l + q_2)^2 - m_2^2 + i\varrho]^{t_2} [l^2 - m_3^2 + i\varrho]^{t_3}}$$
(4.20)

OneLoopTens3Pt $(i, q_1^2, q_2^2, (q_2 - q_1)^2, m_1, m_2, m_3)$ 

= OneLoopTens3Pt
$$(i, q_1^2, q_2^2, (q_2 - q_1)^2, m_1, m_2, m_3, 1, 1, 1)$$
. (4.21)

Abbreviations – using the auxiliary property (4.2):

$$q_{10} = \sqrt{q_1^2}; \quad q_{20} = \frac{q_1 \cdot q_2}{\sqrt{q_1^2}}; \quad q_{21} = \sqrt{\frac{(q_1 \cdot q_2)^2}{q_1^2}} - q_2^2; \\ l_0 = \frac{l \cdot q_1}{\sqrt{q_1^2}}; \quad l_1 = -\frac{l \cdot \hat{q}_2}{\sqrt{-\hat{q}_2^2}}; \quad l_\perp = \sqrt{l_0^2 - l_1^2 - l^2}.$$

$$(4.22)$$

Our notation for the OneLoop *n*Pt functions distinguishes between parallel and orthogonal space which is reflected by the definitions of (4.15) and (4.22) for the momentum components. Please keep in mind the fact that in our notation the indices  $p_0, p_1, \ldots$  represent the powers of the different components of the loop momentum l which should not be mixed with Lorentz indices  $\mu_1, \mu_2, \ldots$  of the corresponding tensor OneLoopTens*n*Pt.

If the powers  $t_n$  of the propagator terms in the denominator are omitted like in (4.6, 4.8, 4.10, 4.14, 4.17, 4.21) the program assumes the value 1 for each  $t_n$ .

#### 4.3.3 Output of OneLoopnPt

The results of the OneLoopnPt functions are Laurent expansions in terms of the ultraviolet regulator  $\varepsilon$ . Therefore the output of the OneLoopnPt procedures consists of a list where

the significant coefficients  $-\mathcal{O}(\varepsilon^{-1})$ ,  $\mathcal{O}(\varepsilon^{0})$  - of this expansion are denoted. In two-loop calculations the term of  $\mathcal{O}(\varepsilon^{1})$  of the one-loop functions is also of interest. For that purpose this coefficient is also calculated if the qualifier **more** is used in the function call:

Eingabe	Ausgabe
OneLoop1Pt(p,m,t)	$[\varepsilon^{-1}\text{-}term, \varepsilon^{0}\text{-}term]$
$\verb+OneLoop1Pt(p,m,t,more)+\\$	$[\varepsilon^{-1}\text{-}term, \varepsilon^{0}\text{-}term, \varepsilon^{1}\text{-}term]$
$\texttt{OneLoop1_2Pt}(p, m_1, m_2, t_1, t_2)$	$[\varepsilon^{-1}\text{-}term, \varepsilon^0\text{-}term]$
$\texttt{OneLoop1_2Pt}(p, m_1, m_2, t_1, \overline{t_2}, \texttt{more})$	$[\varepsilon^{-1}\text{-}term, \varepsilon^{0}\text{-}term, \varepsilon^{1}\text{-}term]$
${ t OneLoop2Pt}(p_0,p_\perp,q_{10},m_1,\overline{m_2},t_1,t_2)$	$[\varepsilon^{-1}$ -term, $\varepsilon^{0}$ -term]
${\tt OneLoop2Pt}(p_0,p_\perp,q_{10},m_1,m_2,t_1,t_2,{\tt more})$	$[\varepsilon^{-1}\text{-}term, \varepsilon^{0}\text{-}term, \varepsilon^{1}\text{-}term]$
$\texttt{OneLoop1_3Pt}(p,m_1,m_2,m_3,t_1,t_2,t_3)$	$[\varepsilon^{-1}$ -term, $\varepsilon^{0}$ -term]
$\texttt{OneLoop1\_3Pt}(p, m_1, m_2, m_3, t_1, t_2, t_3, \texttt{more})$	$[\varepsilon^{-1}\text{-}term, \varepsilon^{0}\text{-}term, \varepsilon^{1}\text{-}term]$
${\tt OneLoop2\_3Pt}(p_0,p_{\perp},q_{10},q_{20},m_1,m_2,m_3,t_1,t_2,t_3)$	$[\varepsilon^{-1}\text{-}term, \varepsilon^{0}\text{-}term]$
$\verb+OneLoop2_3Pt(p_0, p_{\perp}, q_{10}, q_{20}, m_1, m_2, m_3, t_1, t_2, t_3, \verb+more+)$	$[\varepsilon^{-1}\text{-}term, \varepsilon^{0}\text{-}term, \varepsilon^{1}\text{-}term]$
$\texttt{OneLoop3Pt}(p_0, p_1, p_{\perp}, q_{10}, q_{20}, q_{21}, m_1, m_2, \overline{m_3, t_1, t_2, t_3})$	$[\varepsilon^{-1}\text{-}term, \varepsilon^{0}\text{-}term]$
$\texttt{OneLoop3Pt}(p_0,p_1,p_\perp,q_{10},q_{20},q_{21},$	
$m_1, m_2, m_3, t_1, t_2, t_3, \texttt{more})$	$[\varepsilon^{-1}$ -term, $\varepsilon^{0}$ -term, $\varepsilon^{1}$ -term]

In the output  $\varepsilon^{-1}$ -term is meant to represent the divergent part (the coefficient of  $\frac{1}{\varepsilon}$ ) whereas  $\varepsilon^{0}$ -term is describing the finite part and  $\varepsilon^{1}$ -term the  $\mathcal{O}(\varepsilon)$  contribution.

As long as the arguments of the OneLoop functions are symbols the output is given algebraically, whereas of course numbers inserted for the arguments imply a numerical result. Like in the case of the EvalGraph routines, in numerical evaluations the program sets the value of  $\rho$ , the imaginary part of the propagators, five digits higher than the numerical accuracy of the whole calculation, for example to  $10^{-15}$  if one calculates with 20 digits. In the algebraic case just **rho** is returned. To get a compact result also in algebraic calculations, the output is written by using several abbreviations:

$$\begin{aligned} \text{R2ex1}(x,y) &= \sqrt{1 - \frac{x}{y}} \left[ \ln \left( 1 - \sqrt{1 - \frac{x}{y}} \right) - \ln \left( 1 + \sqrt{1 - \frac{x}{y}} \right) + i\pi \right] \end{aligned} \tag{4.23} \\ &- \ln(-x) - i\pi \\ \text{R2ex2}(x,y) &= \left( 1 + \sqrt{1 - \frac{x}{y}} \right) \operatorname{Li}_2 \left( 1 - \frac{1 - \sqrt{1 - \frac{x}{y}}}{1 + \sqrt{1 - \frac{x}{y}}} \right) \\ &+ \left( 1 + \sqrt{1 - \frac{x}{y}} \right) \left[ \ln \left( 1 - \sqrt{1 - \frac{x}{y}} \right) \right]^2 \\ &+ \left( 1 - \sqrt{1 - \frac{x}{y}} \right) \operatorname{Li}_2 \left( 1 - \frac{1 + \sqrt{1 - \frac{x}{y}}}{1 - \sqrt{1 - \frac{x}{y}}} \right) \\ &+ \left( 1 - \sqrt{1 - \frac{x}{y}} \right) \left[ \ln \left( 1 + \sqrt{1 - \frac{x}{y}} \right) \right]^2 \\ &+ \left( 1 - \sqrt{1 - \frac{x}{y}} \right) \left[ \ln \left( 1 + \sqrt{1 - \frac{x}{y}} \right) \right]^2 \end{aligned} \tag{4.24} \\ &+ \frac{1}{2} (\ln y)^2 + 2 (\ln x)^2 - 2 \ln x \ln y \end{aligned}$$

$$+ (\ln y - 2 \ln x) \left[ \left( 1 + \sqrt{1 - \frac{x}{y}} \right) \ln \left( 1 - \sqrt{1 - \frac{x}{y}} \right) \right]$$
$$+ \left( 1 - \sqrt{1 - \frac{x}{y}} \right) \ln \left( 1 + \sqrt{1 - \frac{x}{y}} \right) \right]$$
$$- i\pi \frac{\sqrt{x - y}}{\sqrt{-y}} \left[ 2 \ln 2 + \ln(x - y) \right]$$

$$R3ex2(x, y, z) = 2 \ln\left(1 - \frac{x}{z}\right) \eta(x, z) + 2 \ln\left(1 - \frac{y}{z}\right) \eta(y, z) + 2 \operatorname{Li}_2\left(1 - \frac{x}{z}\right) + 2 \operatorname{Li}_2\left(1 - \frac{y}{z}\right) + 2 (\ln z)^2$$
(4.25)

$$\begin{split} \mathtt{R3ex3}(x,y,z) &= 4\,\mathtt{S}_{12}\left(1-\frac{x}{z}\right) - 4\,\mathtt{Li}_3\left(1-\frac{x}{z}\right) + 4\,\mathtt{S}_{12}\left(1-\frac{y}{z}\right) - 4\,\mathtt{Li}_3\left(1-\frac{y}{z}\right) \\ &- 4\,\eta\left(x,\frac{1}{z}\right) \left\{\mathtt{Li}_2\left(\frac{x}{z}\right) + \ln\left(1-\frac{x}{z}\right)\ln\left(-\frac{x}{z}\right) + \frac{1}{2}\left[\ln\left(1-\frac{x}{z}\right)\right]^2\right\} \\ &- 4\,\eta\left(y,\frac{1}{z}\right) \left\{\mathtt{Li}_2\left(\frac{y}{z}\right) + \ln\left(1-\frac{y}{z}\right)\ln\left(-\frac{y}{z}\right) + \frac{1}{2}\left[\ln\left(1-\frac{y}{z}\right)\right]^2\right\} \\ &- 4\,\ln z\left[\mathtt{Li}_2\left(1-\frac{x}{z}\right) + \mathtt{Li}_2\left(1-\frac{y}{z}\right)\right] \\ &- 4\,\ln z\left[\eta\left(x,\frac{1}{z}\right)\ln\left(1-\frac{x}{z}\right) + \eta\left(y,\frac{1}{z}\right)\ln\left(1-\frac{y}{z}\right)\right] \\ &+ 2\,\mathtt{Li}_3\left(\frac{z-y}{z-x}\right) - 2\,\mathtt{Li}_3\left(\frac{(z-y)x}{(z-x)y}\right) + 2\,\mathtt{Li}_3\left(\frac{x}{y}\right) \end{split} \tag{4.26} \\ &+ \left[\ln\left(\frac{z-y}{z-x}\right)\right]^2\,\eta\left(\frac{y-x}{z},\frac{z}{z-x}\right) + 2\,\eta\left(y-x,\frac{1}{z}\right) \\ &\times \left\{\frac{1}{2}\left[\ln\left(\frac{z-y}{z-x}\right)\right]^2 - \ln\left(-\frac{z-y}{z-x}\right)\eta\left(\frac{z-y}{z},\frac{z}{z-x}\right)\right\} \\ &+ 2\,(\ln x - \ln y)\left[\mathtt{Li}_2\left(\frac{(z-y)x}{(z-x)y}\right) - \mathtt{Li}_2\left(\frac{x}{y}\right)\right] \\ &- \ln\left(1-\frac{x}{z}\right)\,(\ln x - \ln y)^2 - 2\,\zeta(3) - \frac{4}{3}\,(\ln z)^3 \\ &+ 2\left[\ln x - \ln y - \frac{1}{2}\ln\left(\frac{(z-y)x}{(z-x)y}\right)\right]\ln\left(\frac{(z-y)x}{(z-x)y}\right)\eta\left(\frac{y-x}{y},\frac{z}{z-x}\right). \end{split}$$

These functions are related to the corresponding  $\mathcal{R}$  functions<sup>3</sup> [18,19]. They represent the coefficients of the Taylor expansion in  $\varepsilon$  making use of (cf. [20])

$$\zeta(n) = \sum_{k=1}^{\infty} \frac{1}{k^n}$$
$$\operatorname{Li}_2(z) = -\int_0^z \frac{\ln(1-s)}{s} \, ds$$
$$\operatorname{Li}_3(z) = \int_0^z \frac{\operatorname{Li}_2(s)}{s} \, ds$$

<sup>3</sup>The function R3ex3(x, y, z) assumes that x and y have an imaginary part of different sign which is always the case.

$$S_{12}(z) = \frac{1}{2} \int_{0}^{z} \frac{\ln^2(1-s)}{s} ds$$
$$\eta(a,b) = 2\pi i \left[ \theta(-\operatorname{Im} a) \theta(-\operatorname{Im} b) \theta(\operatorname{Im} (ab)) - \theta(\operatorname{Im} a) \theta(\operatorname{Im} b) \theta(-\operatorname{Im} (ab)) \right]$$

The function

```
evalRex(\langle expression \rangle);
```

substitutes the Rnexm functions in  $\langle expression \rangle$  by the corresponding Polylogarithms.

#### 4.3.4 Output of OneLoopTensnPt

The functions **OneLoopTens***n***Pt** return a full tensor as output.

The output format looks similar to that of the EvalGraph routines. The following types of arguments – here only demonstrated for the two-point case – are allowed for all OneLoopTens nPt functions:

#### $\triangleright$ OneLoopTens2Pt(i):

The rank *i* tensor decomposition of the two-point function is given. The procedure returns a list consisting in the different coefficients, which are expressed in terms of the OneLoopnPt tensor integrals, and the defining equation for the coefficients, for instance in the case i = 2:

$$\begin{bmatrix} \text{C21} = -\frac{\text{OneLoop2Pt}(0,2)}{3-2\varepsilon}, \text{C20} = -\frac{\text{OneLoop2Pt}(0,2)}{q^2(-3+2\varepsilon)} \\ +\frac{\text{OneLoop2Pt}(2,0)}{q^2}, \text{C20 q1(nu1) q1(nu2)} + \text{C21 G(nu1,nu2)} \end{bmatrix}$$

 $\triangleright$  OneLoopTens2Pt(i, full):

The function inserts the results of the OneLoopnPt tensor integrals explicitly. Here again the case i = 2:

$$\begin{bmatrix} C21 = [\varepsilon^{-1} \text{-} term, \varepsilon^0 \text{-} term], C20 = [\varepsilon^{-1} \text{-} term, \varepsilon^0 \text{-} term], \\ C20 \text{ q1(nu1) q1(nu2)} + C21 \text{ G(nu1,nu2)} \end{bmatrix},$$

 $\triangleright$  OneLoopTens2Pt $(i, q_1^2, m_1, m_2, t_1, t_2)$ :

The function returns the same as OneLoopTens2Pt(i, full), but expressed in the user-defined terms for  $q_1^2, m_1$  and  $m_2$ . Of course numerical values are also allowed.  $t_1$  and  $t_2$  are optional.

 $\triangleright$  OneLoopTens2Pt $(i, q_1^2, m_1, m_2, t_1, t_2, more)$ : The function returns also the  $\mathcal{O}(\varepsilon)$  contribution. Again,  $t_1$  and  $t_2$  are optional:

$$\begin{bmatrix} C21 = [\varepsilon^{-1} \text{-} term, \varepsilon^0 \text{-} term, \varepsilon^1 \text{-} term], C20 = [\varepsilon^{-1} \text{-} term, \varepsilon^0 \text{-} term, \varepsilon^1 \text{-} term], \\ C20 \quad q1(nu1) \quad q1(nu2) + C21 \quad G(nu1, nu2) \end{bmatrix}.$$

The C20, C21, ... correspond to the coefficients of the Passarino-Veltman procedure.

#### 4.3.5 Infrared divergences

The program is regulating the infrared divergence of the three-point function as well – which may occur for instance if the momenta are on-shell and one mass is set to 0. There is no distinction made between UV and IR divergences – that means that there is no infrared dimension parameter  $\varepsilon_{\text{IR}}$ . Both kinds of divergences are described by  $\varepsilon = (4 - D)/2$ .

#### 4.3.6 Special relations

If special relations exist which fix the variables of the OneLoop functions or connect them with each other – like for instance the on-shell condition – it is important first to declare these relations and then to call the functions – as already stressed in the case of the EvalGraph routines.

If the functions are evaluated first analytically and then numbers or relations between variables are substituted in the result, it might happen in some special cases that an error occurs – something like "division by 0". Usually this sort of divergences is artifical due to the way the analytical result was written before the insertion (cf. sect. 4.2.11).

# 4.4 The TwoLoop procedures

#### 4.4.1 Input

Unlike for the one-loop functions on the two-loop level for each n-point case exist different types of integrals – which correspond to different topologies with the same number of external legs. To distinguish between the different n-point functions with the same n the **TwoLoop** procedures acquire an additional identification number:

```
\succ \texttt{TwoLoop2Pt1}(p_0, p_\perp, r_0, r_\perp, s, q_{10}, m_1, m_2, m_3, m_4, m_5, t_1, t_2, t_3, t_4, t_5):
```

```
\triangleright TwoLoop2Pt8(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, m_2, t_1, t_2)
```

- $\succ \texttt{TwoLoopTens2Pt1}(i_1, i_2, \boldsymbol{q_1^2}, m_1, m_2, m_3, m_4, m_5, t_1, t_2, t_3, t_4, t_5)$ :
- $\triangleright$  TwoLoopTens2Pt8 $(i_1, i_2, q_1^2, m_1, m_2, t_1, t_2)$ .

Like in the one-loop case each function needs the tensor degree, the external momenta  $q_n$  and the masses  $m_n$  as input. The powers  $t_n$  are again optional.

The functions TwoLoopTensnPtm require the squared external momenta as input variables and return the complete tensor, whereas the functions OneLoopnPtm correspond to the notation in parallel and orthogonal space variables.

#### 4.4.2 Notation

The functions correspond to the following integrals:

 $\triangleright$  Two-point functions:

Topology 1:



 $\texttt{TwoLoop2Pt1}(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, m_2, m_3, m_4, m_5, t_1, t_2, t_3, t_4, t_5)$ 

$$= \int d^{D}l \int d^{D}k \, \frac{(l_{0})^{p_{0}} \, (l_{\perp})^{p_{\perp}} \, (k_{0})^{r_{0}} \, (k_{\perp})^{r_{\perp}} \, (z)^{s}}{[(l+q_{1})^{2} - m_{1}^{2} + i\varrho]^{t_{1}} \, [l^{2} - m_{2}^{2} + i\varrho]^{t_{2}} \, [l^{2} - m_{3}^{2} + i\varrho]^{t_{3}}} \qquad (4.27)$$

$$\times \frac{1}{[(l+k)^{2} - m_{4}^{2} + i\varrho]^{t_{4}} \, [k^{2} - m_{5}^{2} + i\varrho]^{t_{5}}}$$

 $\texttt{TwoLoopTens2Pt1}(i_1,i_2,\bm{q_1^2},m_1,m_2,m_3,m_4,m_5,t_1,t_2,t_3,t_4,t_5)$ 

$$= \int d^{D}l \int d^{D}k \, \frac{l_{\mu_{1}} \cdots l_{\mu_{i_{1}}} k_{\nu_{1}} \cdots k_{\nu_{i_{2}}}}{[(l+q_{1})^{2} - m_{1}^{2} + i\varrho]^{t_{1}} [l^{2} - m_{2}^{2} + i\varrho]^{t_{2}} [l^{2} - m_{3}^{2} + i\varrho]^{t_{3}}} \qquad (4.28)$$
$$\times \frac{1}{[(l+k)^{2} - m_{4}^{2} + i\varrho]^{t_{4}} [k^{2} - m_{5}^{2} + i\varrho]^{t_{5}}}.$$

Topology 2:



 $\mathsf{TwoLoop2Pt2}(p_0, p_\perp, r_0, r_\perp, s, q_{10}, m_1, m_2, m_3, m_4, m_5, t_1, t_2, t_3, t_4, t_5)$ (4.29)

$$= \int d^D l \int d^D k \; \frac{(l_0)^{p_0} \; (l_\perp)^{p_\perp} \; (k_0)^{r_0} \; (k_\perp)^{r_\perp} \; (z)^s}{[(l+q_1)^2 - m_1^2 + i\varrho]^{t_1} \; [l^2 - m_2^2 + i\varrho]^{t_2} \; [(l+k)^2 - m_3^2 + i\varrho]^{t_3}} \\ \times \frac{1}{[(k-q_1)^2 - m_4^2 + i\varrho]^{t_4} \; [k^2 - m_5^2 + i\varrho]^{t_5}}$$

TwoLoopTens2Pt2
$$(i_1, i_2, q_1^2, m_1, m_2, m_3, m_4, m_5, t_1, t_2, t_3, t_4, t_5)$$
 (4.30)

$$= \int d^D l \int d^D k \, \frac{l_{\mu_1} \cdots l_{\mu_{i_1}} \, k_{\nu_1} \cdots k_{\nu_{i_2}}}{[(l+q_1)^2 - m_1^2 + i\varrho]^{t_1} \, [l^2 - m_2^2 + i\varrho]^{t_2} \, [(l+k)^2 - m_3^2 + i\varrho]^{t_3}} \\ \times \frac{1}{[(k-q_1)^2 - m_4^2 + i\varrho]^{t_4} \, [k^2 - m_5^2 + i\varrho]^{t_5}} \, .$$

Topology 3:



 $\texttt{TwoLoop2Pt3}(p_0, p_\perp, r_0, r_\perp, s, q_{10}, m_1, m_2, m_3, m_4, t_1, t_2, t_3, t_4)$ 

$$= \int d^{D}l \int d^{D}k \; \frac{(l_{0})^{p_{0}} \; (l_{\perp})^{p_{\perp}} \; (k_{0})^{r_{0}} \; (k_{\perp})^{r_{\perp}} \; (z)^{s}}{[(l+q_{1})^{2} - m_{1}^{2} + i\varrho]^{t_{1}} \; [l^{2} - m_{2}^{2} + i\varrho]^{t_{2}}} \times \frac{1}{[(l+k)^{2} - m_{3}^{2} + i\varrho]^{t_{3}} \; [k^{2} - m_{4}^{2} + i\varrho]^{t_{4}}}$$

$$(4.31)$$

TwoLoopTens2Pt3 $(i_1, i_2, q_1^2, m_1, m_2, m_3, m_4, t_1, t_2, t_3, t_4)$ 

$$= \int d^{D}l \int d^{D}k \, \frac{l_{\mu_{1}} \cdots l_{\mu_{i_{1}}} k_{\nu_{1}} \cdots k_{\nu_{i_{2}}}}{[(l+q_{1})^{2} - m_{1}^{2} + i\varrho]^{t_{1}} [l^{2} - m_{2}^{2} + i\varrho]^{t_{2}}} \times \frac{1}{[(l+k)^{2} - m_{3}^{2} + i\varrho]^{t_{3}} [k^{2} - m_{4}^{2} + i\varrho]^{t_{4}}}.$$
(4.32)

Topology 4:



(4.34)

$$\mathsf{TwoLoop2Pt4}(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, m_2, m_3, t_1, t_2, t_3)$$

$$= \int d^D l \int d^D k \; \frac{(l_0)^{p_0} \; (l_{\perp})^{p_{\perp}} \; (k_0)^{r_0} \; (k_{\perp})^{r_{\perp}} \; (z)^s}{[(l+q_1)^2 - m_1^2 + i\varrho]^{t_1} \; [(l+k)^2 - m_2^2 + i\varrho]^{t_2} \; [k^2 - m_3^2 + i\varrho]^{t_3}}$$
(4.33)

 $\texttt{TwoLoopTens2Pt4}(i_1,i_2,\boldsymbol{q_1^2},m_1,m_2,m_3,t_1,t_2,t_3)$ 

$$= \int d^D l \int d^D k \; \frac{l_{\mu_1} \cdots l_{\mu_{i_1}} k_{\nu_1} \cdots k_{\nu_{i_2}}}{[(l+q_1)^2 - m_1^2 + i\varrho]^{t_1} [(l+k)^2 - m_2^2 + i\varrho]^{t_2} [k^2 - m_3^2 + i\varrho]^{t_3}} \,.$$

Topology 5:



 $\texttt{TwoLoop2Pt5}(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, m_2, m_3, m_4, t_1, t_2, t_3, t_4)$ 

$$= \int d^{D}l \int d^{D}k \; \frac{(l_{0})^{p_{0}} \; (l_{\perp})^{p_{\perp}} \; (k_{0})^{r_{0}} \; (k_{\perp})^{r_{\perp}} \; (z)^{s}}{[(l+q_{1})^{2} - m_{1}^{2} + i\varrho]^{t_{1}} \; [l^{2} - m_{2}^{2} + i\varrho]^{t_{2}}} \times \frac{1}{[l^{2} - m_{3}^{2} + i\varrho]^{t_{3}} \; [k^{2} - m_{4}^{2} + i\varrho]^{t_{4}}}$$

$$(4.35)$$

 $\texttt{TwoLoopTens2Pt5}(i_1,i_2, \bm{q_1}^2, m_1, m_2, m_3, m_4, t_1, t_2, t_3, t_4)$ 

$$= \int d^{D}l \int d^{D}k \; \frac{l_{\mu_{1}} \cdots l_{\mu_{i_{1}}} k_{\nu_{1}} \cdots k_{\nu_{i_{2}}}}{[(l+q_{1})^{2} - m_{1}^{2} + i\varrho]^{t_{1}} [l^{2} - m_{2}^{2} + i\varrho]^{t_{2}}} \times \frac{1}{[l^{2} - m_{3}^{2} + i\varrho]^{t_{3}} [k^{2} - m_{4}^{2} + i\varrho]^{t_{4}}}.$$
(4.36)

Topology 6:



 $\texttt{TwoLoop2Pt6}(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, m_2, m_3, m_4, t_1, t_2, t_3, t_4)$ 

$$= \int d^{D}l \int d^{D}k \; \frac{(l_{0})^{p_{0}} (l_{\perp})^{p_{\perp}} (k_{0})^{r_{0}} (k_{\perp})^{r_{\perp}} (z)^{s}}{[(l+q_{1})^{2} - m_{1}^{2} + i\varrho]^{t_{1}} [l^{2} - m_{2}^{2} + i\varrho]^{t_{2}}} \times \frac{1}{[(k-q_{1})^{2} - m_{3}^{2} + i\varrho]^{t_{3}} [k^{2} - m_{4}^{2} + i\varrho]^{t_{4}}}$$

$$(4.37)$$

 $\texttt{TwoLoopTens2Pt6}(i_1,i_2,\bm{q_1}^2,m_1,m_2,m_3,m_4,t_1,t_2,t_3,t_4)$ 

$$= \int d^{D}l \int d^{D}k \; \frac{l_{\mu_{1}} \cdots l_{\mu_{i_{1}}} k_{\nu_{1}} \cdots k_{\nu_{i_{2}}}}{[(l+q_{1})^{2} - m_{1}^{2} + i\varrho]^{t_{1}} [l^{2} - m_{2}^{2} + i\varrho]^{t_{2}}} \times \frac{1}{[(k-q_{1})^{2} - m_{3}^{2} + i\varrho]^{t_{3}} [k^{2} - m_{4}^{2} + i\varrho]^{t_{4}}}.$$
(4.38)

Topology 7:



 $\mathsf{TwoLoop2Pt7}(p_0, p_\perp, r_0, r_\perp, s, q_{10}, m_1, m_2, m_3, t_1, t_2, t_3)$  (4.39)

$$= \int d^D l \int d^D k \; \frac{(l_0)^{p_0} \; (l_\perp)^{p_\perp} \; (k_0)^{r_0} \; (k_\perp)^{r_\perp} \; (z)^s}{[(l+q_1)^2 - m_1^2 + i\varrho]^{t_1} \; [l^2 - m_2^2 + i\varrho]^{t_2} \; [k^2 - m_3^2 + i\varrho]^{t_3}}$$

TwoLoopTens2Pt7
$$(i_1, i_2, q_1^2, m_1, m_2, m_3, t_1, t_2, t_3)$$
 (4.40)

$$= \int d^D l \int d^D k \; \frac{l_{\mu_1} \cdots l_{\mu_{i_1}} k_{\nu_1} \cdots k_{\nu_{i_2}}}{[(l+q_1)^2 - m_1^2 + i\varrho]^{t_1} [l^2 - m_2^2 + i\varrho]^{t_2} [k^2 - m_3^2 + i\varrho]^{t_3}} \,.$$

(4.42)

Topology 8:



$$TwoLoop2Pt8(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, m_2, t_1, t_2)$$

$$= \int d^D l \int d^D k \; \frac{(l_0)^{p_0} \, (l_{\perp})^{p_{\perp}} \, (k_0)^{r_0} \, (k_{\perp})^{r_{\perp}} \, (z)^s}{[(l+q_1)^2 - m_1^2 + i\varrho]^{t_1} \, [k^2 - m_2^2 + i\varrho]^{t_2}}$$

$$(4.41)$$

 $\texttt{TwoLoopTens2Pt8}(i_1,i_2,\boldsymbol{q_1^2},m_1,m_2,t_1,t_2)$ 

$$= \int d^D l \int d^D k \; \frac{l_{\mu_1} \cdots l_{\mu_{i_1}} k_{\nu_1} \cdots k_{\nu_{i_2}}}{[(\boldsymbol{l} + \boldsymbol{q_1})^2 - m_1^2 + i\varrho]^{t_1} [\boldsymbol{k}^2 - m_2^2 + i\varrho]^{t_2}}.$$

Like in the one-loop case for each function holds

$$TwoLoop2Ptn(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, \dots, m_k) 
= TwoLoop2Ptn(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, \dots, m_k, 1, \dots, 1)$$
(4.43)

TwoLoopTens2Pt
$$n(i_1, i_2, q_1^2, m_1, ..., m_k)$$
  
= TwoLoopTens2Pt $n(i_1, i_2, q_1^2, m_1, ..., m_k, 1, ..., 1)$ . (4.44)

This means that if the powers  $t_n$  of the propagator terms in the denominator are omitted the program assumes the value 1 for each  $t_n$ .

The abbreviations (4.15) we made in the one-loop case for parallel and orthogonal space notation are still valid.

There are several relations between different two-point functions. Some of them we would like to mention here:

$$TwoLoop2Pt1(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, m_2, m_3, m_4, m_5) = \frac{1}{m_3^2 - m_2^2} [TwoLoop2Pt3(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, m_3, m_4, m_5) - TwoLoop2Pt3(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, m_2, m_4, m_5)]$$

$$(4.45)$$

TwoLoop2Pt5 $(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, m_2, m_3, m_4)$ 

$$= \frac{1}{m_3^2 - m_2^2} \left[ \text{TwoLoop2Pt7}(p_0, p_\perp, r_0, r_\perp, s, q_{10}, m_1, m_3, m_4) - \text{TwoLoop2Pt7}(p_0, p_\perp, r_0, r_\perp, s, q_{10}, m_1, m_2, m_4) \right].$$
(4.46)

Both relations are only valid for  $m_2 \neq m_3$ , otherwise one has

$$\begin{aligned} \mathsf{TwoLoop2Pt1}(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, m_2, m_2, m_4, m_5, t_1, t_2, t_3, t_4, t_5) \\ &= \mathsf{TwoLoop2Pt3}(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, m_2, m_4, m_5, t_1, t_2 + t_3, t_4, t_5) \\ \mathsf{TwoLoop2Pt5}(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, m_2, m_2, m_4, t_1, t_2, t_3, t_4) \\ &= \mathsf{TwoLoop2Pt7}(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, m_2, m_4, t_1, t_2 + t_3, t_4). \end{aligned}$$
(4.47)

The two-point functions numbered with 1-4 are nonfactorizable whereas the functions 5-8 are products of one-loop integrals, for instance

$$\mathsf{TwoLoop2Pt6}(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, m_2, m_3, m_4, t_1, t_2, t_3, t_4)$$
(4.49)
$$= \begin{cases} \frac{(\frac{1}{2}, \frac{s}{2})}{(\frac{D-1}{2}, \frac{s}{2})} & \texttt{OneLoop2Pt}(p_0, p_{\perp}, q_{10}, m_1, m_2, t_1, t_2) \\ & \times & \texttt{OneLoop2Pt}(r_0, r_{\perp}, -q_{10}, m_3, m_4, t_3, t_4) & \text{if } s \text{ even} \\ & 0 & \text{if } s \text{ odd} \end{cases}$$

$$\mathsf{TwoLoop2Pt7}(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, m_2, m_3, t_1, t_2, t_3)$$
(4.50)  
$$= \begin{cases} \frac{(\frac{1}{2}, \frac{s}{2})}{(\frac{D-1}{2}, \frac{s}{2})} (-1)^{\frac{r_{\perp}}{2}} \frac{(D-1) \cdots (D-3+r_{\perp})}{D \cdots (D-2+r_0+r_{\perp})} \frac{r_0!}{(\frac{r_0}{2})! 2^{\frac{r_0}{2}}} \\ \times \mathsf{OneLoop2Pt}(p_0, p_{\perp}, q_{10}, m_1, m_2, t_1, t_2) \\ \times \mathsf{OneLoop1Pt}(r_0 + r_{\perp}, m_3, t_3) & \text{if } s, r_0, r_{\perp} \text{ even} \\ 0 & \text{else.} \end{cases}$$

#### 4.4.3 Output of TwoLoopnPtm

The output – like in the one-loop case – is a list which contains the relevant coefficients of the Laurent expansion in  $\varepsilon$ . Ultraviolet divergences at the two-loop level occur as terms of  $\mathcal{O}(\varepsilon^{-2})$  and  $\mathcal{O}(\varepsilon^{-1})$ . Therefore the notation of the output starts with two divergent coefficients.

For the two-point functions 1-4 the finite part cannot be given completely analytically for all mass cases. Therefore these functions have two entries in the output list which describe the finite part. The first one is a list itself denoting an integral representation, the second one gives the analytically calculable terms.

The integral representation is evaluated directly with the help of VEGAS if two arguments are added. Both arguments must be lists which contain each two numbers. These numbers carry the input information for VEGAS. Within an ordinary Maple session one has in addition to assign the variable NumPath as described in sect. 4.6.

input	output
TwoLoop2Pt $m(p_0, p_\perp, r_0, r_\perp, s, q_{10},$	$[\varepsilon^{-2}\text{-}term, \varepsilon^{-1}\text{-}term,$
$m_1,\ldots,m_k,t_1,\ldots,t_k)$	$numeric, \varepsilon^0$ - $term$ ]
TwoLoop2Pt $m(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10}, m_1, \dots, m_k, $	$[\varepsilon^{-2}\text{-}term, \varepsilon^{-1}\text{-}term,$
$t_1, \ldots, t_k, [l_1, l_2], [n_1, n_2])$	$[factor, [result, error]], \varepsilon^0$ -term]

numeric describes the integral representation. This list consists of the following entries

```
[factor, integrand, x=-infinity..infinity, y=-infinity..infinity]
```

where *integrand* is the integrand of the integral representation which has to be integrated over x and y in the interval  $(-\infty, \infty)$ . *factor* is an analytical factor which multiplies the integral representation.

The variables  $l_1, l_2, n_1, n_2$  represent the grids where the integrand is evaluated: first  $l_1$  iterations with  $l_2$  points –  $itmx = l_1$  and  $ncall = l_2$  are passed to VEGAS – and then  $n_1$  iterations with  $n_2$  points – this corresponds to  $itmx = n_1$  and  $ncall = n_2$ . Real and imaginary part are integrated one after the other.

The other entries of the output list have the same behaviour as in the one-loop case: As long as the arguments of the TwoLoop functions are symbols the output is given algebraically, whereas numbers inserted for the arguments imply a numerical result. In the numerical case, the program sets the value of  $\rho$ , the imaginary part of the propagators, five digits higher than the numerical accuracy of the whole calculation, for example to  $10^{-15}$  if one calculates with 20 digits. In the algebraic case just "rho" is returned.

In the case where all internal particles are massless the result is of course known analytically. In this case *numeric* is just [0].

The two-point functions 5-8 are products of one-loop integrals and therefore evaluated completely analytically. The output list has no entry for numerical evaluation and looks simply like:

input	output
$\texttt{TwoLoop2Pt}\textit{m}(p_0, p_{\perp}, r_0, r_{\perp}, s, q_{10},$	
$m_1,\ldots,m_k,t_1,\ldots,t_k)$	$[\varepsilon^{-2}\text{-}term, \varepsilon^{-1}\text{-}term, \varepsilon^{0}\text{-}term]$
$\texttt{TwoLoop2Pt}(p_0, p_\perp, r_0, r_\perp, s, q_{10}, m_1, \dots, m_k,$	
$t_1, \ldots, t_k, [l_1, l_2], [n_1, n_2])$	$[\varepsilon^{-2}\text{-}term,\varepsilon^{-1}\text{-}term,\varepsilon^{0}\text{-}term]$

The optional input of two lists for the VEGAS input data doesn't affect the output since no numerical integration is performed here. The  $\mathcal{O}(\varepsilon^1)$  is not relevant in two-loop calculations. Therefore the qualifier more does not exist for two-loop functions.

The divergent part of two-loop integrals is closely related to one-loop integrals. Therefore the same abbreviations (4.23, 4.24) as for one-loop integrals are appearing. They are substituted if the evalRex command is used (cf. sect. 4.3.3).

#### 4.4.4 Output of TwoLoopTensnPtm

The functions TwoLoopTensnPtm return a full tensor as output. The same types of arguments are allowed as for the corresponding OneLoopTensnPt functions described in sect. 4.3.4 – except the qualifier more.

# 4.5 The OneLoopLib procedures

For different calculations of the same **OneLoop** function it is of course rather inconvenient to start the whole program again. Therefore our package includes the functions

 $\triangleright$  OneLoopLib2Pt(i, j)

 $\triangleright$  OneLoopLib3Pt(i, j)

which generate a library of all OneLoop2Pt and OneLoop3Pt functions respectively up to the tensor rank *i*. All powers of the denominators from 1 to *j* are considered. The second parameter *j* is optional. If it is omitted the procedures assume the value 1 for *j*, so that no powers of denominators higher than one are calculated. These functions are then read by the proper procedures described before, so that they in any case speed up.

If you use the OneLoopLib functions within an ordinary Maple session and want to write this library in any other than the actual directory you have to assign the variable LibPath:

LibPath:= $\langle path \rangle$ ;

Now the library will be written to  $\langle path \rangle$ . The procedures will only look for the library if the entry Oneloop Library of the Options menu is selected or if LibPath is assigned. If the procedures search for an integral which is not contained in the library it will be calculated and stored in the library on the fly. Each integral corresponds to one file. In appendix B.2 we list the convention for the file names.

# 4.6 Numerical integration with VEGAS

For numerical integration a parallelized implementation of the VEGAS algorithm for C++ invented by R. Kreckel is provided with  $\chi foops$ . To use the routines within an ordinary Maple session one has to declare the variable NumPath:

 $\texttt{NumPath:=}\langle path \rangle;$ 

 $\langle path \rangle$  describes the directory where the integration routines are located. If  $\chi loops$  is installed properly this is the subdirectory cxx of the  $\chi loops$  directory.

The routines are customized for those TwoLoop procedures which cannot be calculated analytically. The most elegant way to perform those numerical integrations is described in sect. 4.2.10 and 4.4.3. In addition there is also the possibility to perform an integration separately. For that purpose there exists the command

```
NumIntC(\langle integrand \rangle, [m_1, m_2], [n_1, n_2]);
```

 $\langle integrand \rangle$  denotes the expression which has to be integrated numerically.  $\chi loops$  expects the integration variables to be named x and y – as they are called by the EvalGraph2 and TwoLoop procedures. The variables  $m_1, m_2, n_1, n_2$  represent the grids where the integrand is evaluated: first  $m_1$  iterations with  $m_2$  points – itmx=  $m_1$  and ncall=  $m_2$  are passed to VEGAS – and then  $n_1$  iterations with  $n_2$  points – this corresponds to itmx=  $n_1$  and ncall=  $n_2$ . Real and imaginary part are integrated one after the other. If only the real part is of interest one has to specify

 $\texttt{NumIntC}(\langle integrand \rangle, [m_1, m_2], [n_1, n_2], \texttt{Re});$ 

if only the imaginary part shall be evaluated one writes

NumIntC((integrand),  $[m_1, m_2]$ ,  $[n_1, n_2]$ , Im);

If NumIntC is called only with the first argument *xloops* takes the values  $m_1 = 20$ ,  $m_2 = 1000$ ,  $n_1 = 5$  and  $n_2 = 10000$ .

The output has the following format:

 $[\langle result \rangle, \langle error \rangle].$ 

 $\langle result \rangle$  describes the – possibly complex – numerical result,  $\langle error \rangle$  is the uncertainty (1 $\sigma$ ) of the numerical integration which is returned by VEGAS.

NumIntC performs the necessary internal steps (",compile, link") and starts the C++ program as subprocess. Maple waits until the subprocess terminates and finally re-reads the result.

The numerical integration with VEGAS should be used only once by each user. Otherwise there will occur conflicts because several numerical integrations would use the same C++ files.

- Nu	merical Options	•	
Vegas Options			
1st Integration	tmx (max. number of it.) 20		
1st integration	ncall (number of calls) 1000		
and Internation	itmx (max. number of it.) 5		
2nu micgration	ncall (number of calls)	)	
Ok			
		-	

Figure 4.7: Options for VEGAS

The entry Numeric of the Options menu enables the user to change the parameters for VEGAS. These parameters are set in a window displayed in fig. 4.7.

# 5 Conclusion and outlook

Our aim was to introduce a program package that gives any computer user the possibility to calculate particle processes without much effort in manpower and hardware. At this stage of development the program is still understood to be under construction. In fact we are planning to incorporate several additional features:

- $\triangleright$  One-loop four-, five- and six-point functions.
- $\triangleright$  Two-loop three- and four-point functions.
- ▷ Calculation of complete processes, generation of all diagrams which contribute to a process in a given order.
- $\triangleright$  Incorporation of other models, for instance supersymmetric theories.
- $\triangleright$  An interface for adding other models.
- $\triangleright$  A plotting device for automatical plotting of results.
- $\triangleright$  Automatical renormalization, determination of Z factors and renormalized functions.

# Acknowledgements

We would like to thank R. Stemler for his help in developing several procedures and A. Frink for his contribution and advice in devoloping the numerics and for valuable tests.

# Appendix

# A Examples

# A.1 Installation

A typical run of the **configure** script looks like the following:

./configure This is the XLOOPS installation script ! Which Release of Maple V are you using [1/2/3/4] ? 3 Enter the name of the WWW Browser executable, which XLOOPS should use ! netscape Do you have Isolatin-1 character encoding [y/n] ? y If you feel unsure, answer the following question with 'n'. XLOOPS can work in single processor mode on multi processor machines as well. Do you have multiprocessing (and POSIX thread library installed) [y/n] ? y How many processors has your computer ? 2 On which platform are you installing xloops ? Linux [1] Digital OSF [d] SUN Solaris [s] IBM AIX [a] Other Unix [o] 1 Instead of creating the library you can also get a prebuilt library from the XLOOPS homepage and unpack it. Shall I create the library of one-loop functions (takes approx. 1 hour) [y/n] ? n Now testing for Maple output bug while reading the library ! Maple V Release 3 (Universitaet Mainz) |\^/| .\_|\| |/|\_. Copyright (c) 1981-1994 by Waterloo Maple Software and the \ MAPLE / University of Waterloo. All rights reserved. Maple and Maple V <\_\_\_\_> are registered trademarks of Waterloo Maple Software. Type ? for help. > read('loops.ma'); Warning: new definition for &\* by Lars Brücher, Johannes Franzkowski, Dirk Kreimer ©1993-1997 Johannes Gutenberg Universität Mainz, Germany bytes used=1001220, alloc=851812, time=0.03 bytes used=2011736, alloc=1310480, time=0.03 > LibPath := '../lib/' ; LibPath := ../lib/

```
> EvalGraph1(3, [higgs, higgs, higgs, higgs, higgs, higgs], full);
bytes used=3011944, alloc=1834672, time=0.03
> quit;
bytes used=3662072, alloc=1834672, time=0.03
_____
Did you see any result of the Maple command 'EvalGraph' used above [y/n] ? n
System configuration completed, doing now some checks !
                This may take a while !
             Creating the index file for tcl !
Now testing the Makefile for numerical integrations generated for your System !
rm -f main funct.o numint.o div0.o vegas.o gauss.o utils.o
       -DGNU_COMPLEX -03 -fomit-frame-pointer -finline-functions -m486 -malign-
g++
functions=4 -malign-jumps=4 -malign-loops=4 -fexpensive-optimizations -funroll-1
oops -ffast-math -c funct.cxx
       -DGNU_COMPLEX -03 -fomit-frame-pointer -finline-functions -m486 -malign-
g++
functions=4 -malign-jumps=4 -malign-loops=4 -fexpensive-optimizations -funroll-1
oops -ffast-math -c numint.cxx
       -DGNU_COMPLEX -03 -fomit-frame-pointer -finline-functions -m486 -malign-
g++
functions=4 -malign-jumps=4 -malign-loops=4 -fexpensive-optimizations -funroll-1
oops -ffast-math -c div0.cxx
g++ -DGNU_COMPLEX -03 -fomit-frame-pointer -finline-functions -m486 -malign-fun
ctions=4 -malign-jumps=4 -malign-loops=4 -fexpensive-optimizations -funroll-loop
s -ffast-math -D_REENTRANT -DPVEGAS_POSIX -c vegas.c
        -DGNU_COMPLEX -O3 -fomit-frame-pointer -finline-functions -m486 -malign-
g++
functions=4 -malign-jumps=4 -malign-loops=4 -fexpensive-optimizations -funroll-1
oops -ffast-math -c gauss.cxx
       -DGNU_COMPLEX -03 -fomit-frame-pointer -finline-functions -m486 -malign-
g++
functions=4 -malign-jumps=4 -malign-loops=4 -fexpensive-optimizations -funroll-1
oops -ffast-math -c utils.cxx
g++ -o main funct.o numint.o div0.o vegas.o gauss.o utils.o -lm -lpthread mai
n.cxx
Division by 0 Errors will be ignored
Test: 1/0
Initializing SR-sequences with seed 876920052
Input parameters for vegas: ndim= 2 ncall=
                                                   968
                                                             2 thread(s)
                             ittot=
                                      1 itmx=
                                                          22<sup>1</sup> hypercubes
                                                  5
                             nprn= 0 ALPH= 1.50
                             mds= 1 nd= 200
                                                            npg=2
                                               0 xu[ 1]=
                              xl[ 1]=
                                                                   1
                              xl[ 2]=
                                               0 xu[ 2]=
                                                                   1
               1 : integral = -1.077957e-06 +/-
 iteration no.
                                                    9.2e-07
 all iterations: integral = -1.077957e-06+/- 9.2e-07 chi**2/IT n =
                                                                            0
 iteration no. 2 : integral = 1.703926e-07 +/-
                                                    7.1e-07
 all iterations: integral = -2.975584e-07+/- 5.6e-07 chi**2/IT n =
                                                                          1.2
 iteration no. 3 : integral = 1.407306e-09 +/-
                                                    4.3e-07
 all iterations: integral = -1.079265e-07+/- 3.4e-07 chi**2/IT n =
                                                                         0.67
 iteration no. 4 : integral = -6.310369e-08 +/-
                                                    4e-07
 all iterations: integral = -8.938296e-08+/- 2.6e-07 chi**2/IT n =
                                                                         0.45
 iteration no. 5 : integral = -2.702396e-07 +/-
                                                    3.2e-07
 all iterations: integral = -1.618004e-07+/-
                                                2e-07 chi**2/IT n =
                                                                         0.38
                                                  9800
 Input parameters for vegas: ndim= 2 ncall=
                                                             2 thread(s)
                             ittot=
                                       1 itmx=
                                                  3
                                                          70<sup>1</sup> hypercubes
                             nprn= 0 ALPH= 1.50
                             mds= 1 nd= 200
                                                            npg=2
```

xl[ 1]= 0 xu[ 1]= 1 x1[ 2]= 0 xu[ 2]= 1 1 : integral = -4.470697e-08 +/-6.2e-08 iteration no. all iterations: integral = -4.470697e-08+/- 6.2e-08 chi\*\*2/IT n = 0 iteration no. 2 : integral = 2.028027e-08 +/-5.3e-08 all iterations: integral = -6.763662e-09+/-4e-08 chi\*\*2/IT n = 0.63 iteration no. 3 : integral = -2.663549e-08 +/-5.1e-08 all iterations: integral = -1.435286e-08+/- 3.2e-08 chi\*\*2/IT n = 0.36 Total Number of ignored Divisions by 0: 0 Input parameters for vegas: ndim= 968 2 thread(s) 2 ncall= ittot= 1 itmx= 22<sup>1</sup> hypercubes 5 nprn= 0 ALPH= 1.50 mds= 1 nd= 200 npg=2 xl[ 1]= 0 xu[ 1]= 1 x1[ 2]= 0 xu[ 2]= 1 1 : integral = 7.704579e-06 +/iteration no. 1.3e-06 integral = 7.704579e-06+/- 1.3e-06 chi\*\*2/IT n = 0 all iterations: iteration no. 2 : integral = 8.286222e-06 +/-6.8e-07 all iterations: integral = 8.160574e-06+/- 6.1e-07 chi\*\*2/IT n = 0.16 iteration no. 3 : integral = 9.681104e-06 +/-6.2e-07 all iterations: integral = 8.902334e-06+/- 4.3e-07 chi\*\*2/IT n = 1.6 4 : integral = 8.987195e-06 +/-5e-07 iteration no. all iterations: integral = 8.938647e-06+/- 3.3e-07 chi\*\*2/IT n = 1.1 5 : integral = 8.732733e-06 +/-3.7e-07 iteration no. all iterations: integral = 8.84922e-06+/- 2.5e-07 chi\*\*2/IT n = 0.85 Input parameters for vegas: ndim= 2 ncall= 9800 2 thread(s) ittot= 1 itmx= З 70<sup>1</sup> hypercubes nprn= 0 ALPH= 1.50 mds= 1 nd= 200 npg=2 xl[ 1]= 0 xu[ 1]= 1 xl[ 2]= 0 xu[ 2]= 1 iteration no. 1 : integral = 8.890832e-06 +/-1e-07 all iterations: integral = 8.890832e-06+/-1e-07 chi\*\*2/IT n = 0 2 : integral = 8.87138e-06 +/iteration no. 5.3e-08 all iterations: integral = 8.875575e-06+/- 4.7e-08 chi\*\*2/IT n = 0.029 iteration no. 3 : integral = 8.798005e-06 +/-4.7e-08 all iterations: integral = 8.836898e-06+/- 3.4e-08 chi\*\*2/IT n = 0.68 Total Number of ignored Divisions by 0: 0

Make seems to work, so Makefile is correct !

If you had problems please edit the Makefile in the subdirectory ./cxx until it compiles correctly. Please report your system configuration and Makefile changes to xloops@thep.physik.uni-mainz.de !

Do you agree sending the XLOOPS team a mail [Y/n] ? Y

XLOOPS installed successfully, invoke with ./xloops !

# A.2 Examples with the Xwindows frontend

To demonstrate the input and output of  $\chi loops$  some typical examples are given. The Feynman diagrams in this chapter are Postscript pictures produced with  $\chi loops$ .

#### A.2.1 Output of one-loop integrals

#### Analytic examples

At first we want to show the different ways of evaluating the diagrams. As an example we have chosen a simple self-energy diagram. The advantage of this diagram is the relatively short result. The diagram on the right shows the process, a nondiagonal Z self-energy with a W bubble.



With Evaluate the following result is obtained:

As expected, the structure of form factors, indicated by the last element of the list above, is just proportional to  $g^{\mu\nu}$ . The pre-factor C1 is determined by an equation, which shows the corresponding Oneloop functions. In this example just Oneloop1Pt(0, Mw) appears. As pre-factor the coupling e, the Weinberg angle tw and the renormalization parameter MU occur.

With Eval. Full the OneLoop function can be evaluated further:

```
GF2 := [
                 2
              I e cos(tw) Mw
  C1 = [- 3/8 -----
                          2
                 sin(tw) Pi
                        2
                            2
                                 2
                                     2
                                            2
      1/16 I (- 6 Ln(4 Pi MU) Pi Mw + 4 Pi Mw
                                                        2
                                                            2
                                                               2
           - 6 (- Ln(Mw - I rho) - Ln(Pi) - gamma + 1) Pi Mw ) e cos(tw)
               (sin(tw) Pi )
                                                                        ],
```

Now the constant C1 is evaluated to a list, which elements represent the coefficients of the Laurent series in the dimensional regulator  $\varepsilon = (4 - D)/2$ . The first element of the list shows the divergence of the integral, the second element the convergent part.

Additionally the next order in dimensional regularization can be evaluated. Clicking on  $\boxed{\mathsf{Eval. More}}$  shows the result:

GM3 := [ 2 2 2 2 2 2 2 I e cos(tw) Mw I (- 6 Ln(4 Pi MU) Pi Mw + 4 Pi Mw - 6 %1) e cos(tw) C1 = [- 3/8 -----, 1/16 ----\_\_\_\_\_ 2 4 sin(tw) Pi sin(tw) Pi 2 2 2 2 2 2 1/16 I e cos(tw) (- 3 Ln(4 Pi MU ) Pi Mw 2 2 2 2 2 2 + Ln(4 Pi MU) (4 Pi Mw - 6 %1) - 6 (1/2 Ln(Mw - I rho) 2 - (- Ln(Pi) - gamma + 1) Ln(Mw - I rho) + 1/2 Ln(Pi) 2 2 2 - (- gamma + 1) Ln(Pi) + 1/12 Pi + 1/2 gamma - gamma + 1) Pi Mw + 4 %1 ) / (sin(tw) Pi ) ], C1 G(nu1, nu2)] 2 %1 := (- Ln(Mw - I rho) - Ln(Pi) - gamma + 1) Pi Mw

In the above result the list for C1 was just enhanced by an additinal element, the  $\mathcal{O}(\varepsilon^1)$ .

#### Numerical examples

In the following subsection we want to show some numerical examples, where different kinds of form factors occur. The values for couplings and particle masses where inserted with Insert Particle Properties from the Options menu. The momentum was set to q10:=Mz0; and the renormalization parameter was chosen to be MU:=1;. All results are given in natural units  $\hbar = c = 1$  and the energy scale GeV.



```
The results, when evaluated with Eval. Full, read:
(a)
GF4 := Γ
   C1 = [ - 2143.7993127296539430 I,
                                       -15
                                          + 16785.676157258815796 I], C1]
            - .33537943559210349312*10
(b)
GF5 := [
     C1 = [ - .11869586429575443972*10
                                          Ι,
                                                                 -5
                                   -5
          .37289405527131873878*10
                                    + .66133100616139736842*10
                                                                   I],
     C2 =
      [.052942866215076463492 I, - .16632491956127147989 - .32145019412334161258 I],
     C1 (1 &* ONE) + C2 (1 &* Dg0)]
(c)
GF6 := [
     C1 =
       [ - 6.4357348171046949024 I, 20.218457221868161079 + 34.784995718164094540 I],
     C2 = [.00077427320705022066450 ],
          - .0024324510191403821401 - .0041849285213475828278 I],
     C1 G(nu1, nu2) + C2 q1(nu1) q1(nu2)]
```

Figure (a) shows a scalar self-energy. So the result just consists of the scalar constant C1. Like in the previous example C1 is expanded as a series in  $\varepsilon$ . Figure (b) shows a fermionic self-energy, which has Dirac structure. So the form factors are the unity matrix ONE and Dg0. The pre-factors C1 and C2 are again represented as lists of coefficients of the Laurent series in  $\varepsilon$ . Finally figure (c) shows a vector boson self-energy. The result is proportional to the metric tensor G(nu1, nu2) and to the product of the external momenta q1(nu1) q1(nu2). Again two constants, C1 and C2, are needed.

#### A.2.2 Two-loop diagrams

Now some two-loop diagrams shall be evaluated numerically. The values are chosen as in the previous section, if no comment is made. First we want to show some two-loop diagrams which factorize, starting with a photon self-energy:



The typical structure of a photon self-energy,

C1 G(nu1, nu2) + C2 q1(nu1) q1(nu2),

can be seen. The difference to the one-loop self-energy (c) is just the fact, that this graph is more divergent. So the constants C1 and C2 have an additional list entry, the order  $\varepsilon^{-2}$ .

Next we demonstrate a three-point function. All momenta are on-shell, e.g. q10:=Mz0; q20:=Mz0/2; q21:=sqrt(Mz0^2-Melec^2); is passed to Maple with Insert Maple Command.



-8 -9 - .30410069590311173109\*10 - .86001332568491139242\*10 I], -34 -25 C2 = [0, .16428685998560205727\*10 - .72770813279248241968\*10 I, -7 -8 - .31775075936778308993\*10 - .89861644838148378070\*10 I], -27 -27 C3 = [0, .25907616430369099002\*10 + .17084563249491568053\*10 I, -10 -1 .50023692425121327568\*10 - .38336659269131090697\*10 I]. -27 -26 C4 = [0, .56375581291706017052\*10 + .83584350815468097846\*10 I, -9 -9 -9 -9 .52269088721608778944\*10 - .40057463723369682265\*10 I], -27 C5 = [0, .11444962108462501382\*10 - .21574341953884228136\*10 I, -26 - .13104643398124069502\*10 + .25219418322926334904\*10 I], -27 -27 C6 = [0, .19581694212974079513\*10 - .32129543956635657630\*10 I, -26 - .22477792468575032187\*10 + .37675015987648266663\*10 I], -31 C7 = [0, .13476989938404571673\*10 + .21449295663578860996\*10 I, -23 .10998568100\*10 - .26575450025692144978\*10 I], -31 C8 = [0, - .13476989941451368157\*10 - .21449295669672453982\*10 I, -22 -13 - .11492263298\*10 + .27768333121127352587\*10 I], -26 -26 C9 = [0, .31582291657035101225\*10 - .30101578572250827460\*10 I, .10838466684439346062\*10 + .56893589844240048516\*10 I], -26 -36 C10 = [0, - .98315817920409517794\*10 - .13705392377889147738\*10 I, .11324969215000662291\*10 + .59447352866059701005\*10 I], -27 -26 C11 = [0, .76454675644007305666\*10 - .48786422812941166168\*10 I,
-9 -9 .25011846212167898923\*10 - .19168329634264528256\*10 I], -26 -25 C12 = [0, - .20628807340956139895\*10 - .21423923511009696554\*10 I, -8 -8 .26134544360394034972\*10 - .20028731861370353818\*10 I], C1 (1 &\* Dg(nu1)) + C2 &\*(1, Dg5, Dg(nu1)) + C3 (1 &\* Dg0) q2(nu1) + C4 &\*(1, Dg5, Dg0) q2(nu1) + C5 (1 &\* Dg1) q2(nu1) + C6 &\*(1, Dg5, Dg1) q2(nu1) + C7 (1 &\* ONE) q1(nu1) + C8 (1 &\* Dg5) q1(nu1) + C9 (1 &\* Dg0) q1(nu1) + C10 &\*(1, Dg5, Dg0) q1(nu1) + C11 (1 &\* Dg1) q1(nu1) + C12 &\*(1, Dg5, Dg1) q1(nu1) ]

Of course the result has more form factors as the diagrams evaluated before. The reason for this is, that as external particles vector bosons as well as fermions occur.

# **B** Technical details

#### **B.1** File structure



To understand which files  $\chi loops$  uses for loading and saving of processes, it is necessary to have a short glance on the file structure, which  $\chi loops$  writes into every user's home directory. First of all  $\chi loops$  creates the subdirectory  $\chi loops\_user$ . In this directory  $\chi loops$ writes all user-specific data. If the user now starts to input a new process,  $\chi loops$  creates in  $\chi loops\_user$  a new subdirectory, which has the same name as the process. In this subdirectory  $\chi loops$  writes to basic files: the file Init with all options entered for this process (e.g. the model), and the file History.tab, where for every diagram a corresponding number and a particle list is saved. If one graph from this list is calculated,  $\chi loops$  creates a new file to save the result. The name of this file includes the number of the diagram in the particle list. If the user now tries to evaluate this graph again,  $\chi loops$  looks for the corresponding file and reads the result.

#### B.2 The one-loop library

To avoid multiple evaluation of one-loop integrals  $\chi$  foops can read these integrals from a pre-built library. This library is produced with by the OneLoopLib procedures and written to the directory, which is indicated by the variable LibPath. If the Xwindows interface is used, this variable points to a common directory, where all integrals are saved. Otherwise the user can set this variable to the directory, where he has his own library stored. If some integrals in the library are missing,  $\chi$  foops creates them automatically.<sup>1</sup>

In practice it is necessary to store not only the general mass case of each integral. Several special cases are also needed. The correspondence is

 $Bp_0p_1t_1t_2n_1.1LOOP \iff OneLoop2Pt(p_0, p_1, q, m_1, m_2, t_1, t_2)$ 

$$\begin{split} \mathbf{C} p_0 p_1 p_2 t_1 t_2 t_3 n_1 n_2 i_1 i_2 i_3 i_4 i_5 i_6.\, \mathbf{1LOOP} &\Longleftrightarrow \\ \mathbf{OneLoop3Pt} (p_0, p_1, p_2, q_1, q_{20}, q_{21}, m_1, m_2, m_3, t_1, t_2, t_3) \,. \end{split}$$

<sup>&</sup>lt;sup>1</sup>Currently only supported on Unix platforms.

The additional numbers  $n_1, n_2$  and the optional numbers  $i_1, i_2, i_3, i_4, i_5, i_6$  specify the different kinematical arrangements which have to be taken into account. In the following tables we list the conditions which belong to each case:

conditions			method of	effective
1	2	$n_1$	solution	<i>n</i> -point
q = 0	$m_1 = m_2$	triv.	D	1
			P	1
$m_1 = 0$	—	1	R	2
$m_2 = 0$		2	R	2
$q^2 + m_1^2 - m_2^2 = 0$	—	3	R	2
$q^2 - m_1^2 + m_2^2 = 0$		4	R	2
$q + m_1 + m_2 = 0$	—	5	R	2
$q - m_1 + m_2 = 0$		6	R	2
$q + m_1 - m_2 = 0$	—	7	R	2
$q - m_1 - m_2 = 0$		8	R	2

Two-point functions:

Three-point f	functions:
---------------	------------

		conditi	ons		method of	effective
1	2	3	4	$n_1 n_2$	solution	n-point
$q_{21} = 0$	$q_{20} = 0$	$q_1 = 0$	$m_1 = m_2 = m_3$	triv.	$2 \times D$	1
			$m_1 = m_2$	triv.	P D	1
			$m_1 = m_3$			1
			$m_2 = m_3$			1
				triv.	P	1
		$m_2 = m_3$	$q_1 + m_1 + m_3 = 0$	11	D R	2
			$q_1 + m_1 - m_3 = 0$	12		
			$q_1 - m_1 + m_3 = 0$	13		
			$q_1 - m_1 - m_3 = 0$	14		
				10	D	2
	$q_1 = q_{20}$	$m_1 = m_2$	$q_1 + m_1 + m_3 = 0$	21	D R	2
			$q_1 + m_1 - m_3 = 0$	22		
			$q_1 - m_1 + m_3 = 0$	23		
			$q_1 - m_1 - m_3 = 0$	24		
				20	D	2
	$q_{20} = 0$	—		40	P	2
	$q_1 = 0$	—		50	P L	2
	$q_1 = q_{20}$			60	P	2
	$(q_{20}^2 - m_2^2)$	$)q_1 - (q_1^2 - $	$m_1^2)q_{20} - m_3^2(q_{20} - q_1) = 0$	70	P	2
	—	—	—	80	P	2
$q_1 = 0$	$m_1 = m_3$	$\sqrt{q_{20}^2 - q_2^2}$	$\frac{1}{m_1} + m_1 + m_2 = 0$	31	L D R	2
		$\sqrt{q_{20}^2 - q_2^2}$	$\overline{k_1} + m_1 - m_2 = 0$	32		
		$\sqrt{q_{20}^2 - q_2^2}$	$\frac{1}{2} - m_1 + m_2 = 0$	33		
		$\sqrt{q_{20}^2 - q_2^2}$	$\frac{1}{m_1} - m_1 - m_2 = 0$	34		
				30	L D	2
				90	P L	2

conditions					method of	effective
1	2	3	4	$n_1 n_2$	solution	<i>n</i> -point
$q_{20} - q_1 = q_{21}$	$q_{20} = -q_{21}$					3
	$m_3 \neq 0$		—	C0	S	3
$q_{20} - q_1 = -q_{21}$	$q_{20} = q_{21}$					3
	$m_3 \neq 0$		—	D0	S	3
$q_{20} = q_{21}$	$m_2 \neq 0$			E0	S	3
$q_{20} = -q_{21}$	$m_2 \neq 0$			F0	S	3
$q_{20}^2 - q_{21}^2 = m_2^2$	$q_1^2 = m_1^2$	$m_3 = 0$		G0	S	3
$(q_{20} - q_1)^2 - q_{21}^2 = m_1^2$	$q_{20}^2 - q_{21}^2 = m_3^2$	$m_2 = 0$		H0	S	3
$\left[ (q_{20} - q_1)^2 - q_{21}^2 = m_2^2 \right]$	$q_1^2 = m_3^2$	$m_1 = 0$		IO	S	3

The table shows in the first columns the conditions to the masses  $m_i$  and the external momenta for a special case. Then the number occuring in the name of the file, in which the special case is saved is given. In the following two columns the method of solving this integrals and the effective *n*-point function to solve is given. The abbreviations for the method of solution have the following meaning:

- D Differentiation to the squares of masses.
- *P* Solving by partial fraction decomposition.
- R Special case of the  $\mathcal{R}$  function, either vanishing or equal arguments.
- L Solution by Lorentz transformation and reduction of parallel space.
- S Summands vanish in the sum of residua,
  - e.g. some residua are 0.

For the tensor integrals of the three point function the following additional cases occur:

conditions		method of	effective		
1	2	3		solution	n-point
$m_1 = 0$			$i_1 = 4$	R	3
	$m_2 = 0$		$i_1 = 6$	R	3
		$m_3 = 0$	$i_1 = 7$	R	3
	$m_3 = 0$		$i_1 = 5$	R	3
$m_2 = 0$			$i_1 = 2$	R	3
	$m_3 = 0$		$i_1 = 3$	R	3
$m_3 = 0$			$i_1 = 1$	R	3
$q_1^2 - m_1^2 + m_3^2 = 0$	$m_1 \neq 0$		$i_2 = 1$	R	3
$q_1^2 + m_1^2 - m_3^2 = 0$			$i_2 = 2$	R	3
$q_1^2 - m_2^2 + m_3^2 = 0$	$m_2 \neq 0$		$i_3 = 1$	R	3
$q_1^2 + m_2^2 - m_3^2 = 0$			$i_3 = 2$	R	3
$q_{20}^2 - m_2^2 + m_3^2 = 0$	$m_2 \neq 0$		$i_4 = 1$	R	3
$q_{20}^2 + m_2^2 - m_3^2 = 0$			$i_4 = 2$	R	3
$q_{20}^2 - q_{21}^2 - m_2^2 + m_3^2 = 0$			$i_4 = 3$	R	3
$q_{20}^2 - q_{21}^2 + m_2^2 - m_3^2 = 0$			$i_4 = 4$	R	3
$q_1^2 - m_1^2 + m_2^2 = 0$	$m_1 \neq 0$		$i_5 = 1$	R	3
$q_1^2 + m_1^2 - m_2^2 = 0$			$i_5 = 2$	R	3
$(q_{20} - q_1)^2 - m_1^2 + m_2^2 = 0$			$i_5 = 3$	R	3
$(q_{20} - q_1)^2 + m_1^2 - m_2^2 = 0$			$i_5 = 4$	R	3
$q_{20}^2 - \overline{q_{21}^2 - m_1^2 + m_2^2} = 0$	$m_2 \neq 0$		$i_6 = 1$	R	3
$q_{20}^2 - q_{21}^2 + m_1^2 - m_2^2 = 0$			$i_6 = 2$	R	3

To make the notation clearer, we give the following examples:

$Bp_0p_1t_1t_2$ .1LOOP	$\texttt{OneLoop2Pt}(p_0,p_1,q,m_1,m_2,t_1,t_2)$
$\mathtt{B}p_0p_1t_1t_2\mathtt{1.1LOOP}$	$\texttt{OneLoop2Pt}(p_0,p_1,q,0,m_2,t_1,t_2)$
${\tt B} p_0 p_1 t_1 t_2 {\tt 2.1LOOP}$	$\texttt{OneLoop2Pt}(p_0,p_1,q,m_1,0,t_1,t_2)$
${\tt B} p_0 p_1 t_1 t_2 {\tt 3.1LOOP}$	${\tt OneLoop2Pt}(p_0,p_1,\sqrt{m_2^2-m_1^2},m_1,m_2,t_1,t_2)$
$Bp_0p_1t_1t_2$ 4.1LOOP	${\tt OneLoop2Pt}(p_0,p_1,\sqrt{m_1^2-m_2^2},m_1,m_2,t_1,t_2)$
C $p_0p_1p_2t_1t_2t_3$ .1LOOP	${\tt OneLoop3Pt}(p_0,p_1,p_2,q_1,q_{20},q_{21},m_1,m_2,m_3,t_1,t_2,t_3)$
$\mathtt{C}p_0p_1p_2t_1t_2t_3\mathtt{1.1LOOP}$	${\tt OneLoop3Pt}(p_0,p_1,p_2,q_1,q_{20},0,m_1,m_2,m_3,t_1,t_2,t_3)$
$\mathtt{C}p_0p_1p_2t_1t_2t_3\mathtt{2.1LOOP}$	OneLoop3Pt $(p_0, p_1, p_2, q_1, q_{20}, q_{21}, q_1, \sqrt{q_{20}^2 - q_{21}^2}, 0, t_1, t_2, t_3)$
$\mathtt{C}p_0p_1p_2t_1t_2t_3\mathtt{3.1LOOP}$	$\texttt{OneLoop3Pt}(p_0, p_1, p_2, q_1, q_{20}, q_1 - q_{20}, m_1, m_2, m_3, t_1, t_2, t_3)$
$\mathtt{C}p_0p_1p_2t_1t_2t_3\mathtt{4.1LOOP}$	${\tt OneLoop3Pt}(p_0,p_1,p_2,q_1,q_{20},-q_{20},m_1,m_2,m_3,t_1,t_2,t_3)$
$\mathtt{C}p_0p_1p_2t_1t_2t_3\mathtt{5.1LOOP}$	$\texttt{OneLoop3Pt}(p_0, p_1, p_2, q_1, q_{20}, q_{20} - q_1, m_1, m_2, m_3, t_1, t_2, t_3)$
$\mathtt{C}p_0p_1p_2t_1t_2t_3\mathtt{6.1LOOP}$	${\tt OneLoop3Pt}(p_0,p_1,p_2,q_1,q_{20},q_{20},m_1,m_2,m_3,t_1,t_2,t_3)$
$\mathtt{C}p_0p_1p_2t_1t_2t_3\mathtt{7.1LOOP}$	${\tt OneLoop3Pt}(p_0,p_1,p_2,q_1,0,0,m_1,m_2,m_3,t_1,t_2,t_3)$
$\mathtt{C}p_0p_1p_2t_1t_2t_3\mathtt{8.1LOOP}$	${\tt OneLoop3Pt}(p_0,p_1,p_2,q_1,q_1,0,m_1,m_2,m_3,t_1,t_2,t_3)$
$\mathtt{C}p_0p_1p_2t_1t_2t_3\mathtt{9.1LOOP}$	${\tt OneLoop3Pt}(p_0,p_1,p_2,0,q_{20},q_{21},m_1,m_2,m_3,t_1,t_2,t_3)$

### **B.3** Run time and numerical stability

Typical run times for the different integrals are displayed in the following table. We used two different systems: (i) a DEC Alpha 8400 workstation (ii) a PC with i586 chip, 32 MB RAM and 133 MHz frequency running Linux. All systems are working with Maple V. Without using the library we found the following run times:

	DEC Alpha 8400		i586 133MHz	
tensor rank	numerical	algebraical	numerical	algebraical
	One-loop	o two-point fu	inctions	
0	$0.02 \mathrm{~s}$	$0.04 \mathrm{~s}$	$0.04 \mathrm{~s}$	$0.06 \mathrm{\ s}$
1	$0.04 \mathrm{~s}$	$0.21 \mathrm{~s}$	$0.06 \ s$	$0.26 \mathrm{~s}$
2	$0.07 \ { m s}$	$0.28 \ s$	$0.07 \ { m s}$	$0.48 \mathrm{\ s}$
3	$0.08 \mathrm{\ s}$	$0.41 \mathrm{\ s}$	$0.09 \ s$	$0.76 \mathrm{\ s}$
One-loop three-point functions				
0	$2.54 \mathrm{~s}$	$1.83 \mathrm{~s}$	$4.83 \mathrm{\ s}$	$3.31 \mathrm{~s}$
1	$2.57 \mathrm{~s}$	$2.23 \mathrm{~s}$	$5.09~\mathrm{s}$	$3.69 \mathrm{~s}$
2	$3.01 \mathrm{~s}$	$3.62 \mathrm{~s}$	$5.67 \mathrm{~s}$	$6.14 \mathrm{\ s}$
3	$3.78 \mathrm{\ s}$	$4.16 \mathrm{~s}$	$7.61 \mathrm{~s}$	34.58s

It should be emphasized that these are the times which are necessary to generate the functions once and forever using the OneLoopLibnPt routines. If they once are stored in the LibPath directory they may be read in quickly. With assigned LibPath we get:

	DEC Alpha 8400		i586 133MHz	
tensor rank	numerical	algebraical	numerical	algebraical
	One-loop	o two-point fu	unctions	
0	$0.34 \mathrm{~s}$	$0.03 \mathrm{\ s}$	$0.08 \mathrm{~s}$	$0.02 \mathrm{~s}$
1	$0.39 \ s$	$0.05 \ \mathrm{s}$	$0.09 \ s$	$0.03 \mathrm{\ s}$
2	$0.43 \mathrm{\ s}$	$0.06 \ s$	$0.19 \mathrm{~s}$	$0.03 \ \mathrm{s}$
3	$0.47~\mathrm{s}$	$0.06 \mathrm{\ s}$	$0.20 \mathrm{~s}$	$0.04 \mathrm{~s}$
	One-loop	three-point f	unctions	
0	$1.30 \mathrm{~s}$	$0.09 \ s$	$4.77 \mathrm{\ s}$	$0.47 \mathrm{\ s}$
1	$1.32 \mathrm{~s}$	$0.10 \mathrm{~s}$	$4.81 \mathrm{~s}$	$0.57 \mathrm{~s}$
2	$1.36 \mathrm{~s}$	$0.12 \mathrm{~s}$	$5.20 \mathrm{~s}$	$0.74 \mathrm{\ s}$
3	$1.88 \ s$	$0.45 \mathrm{\ s}$	$6.72 \mathrm{~s}$	$1.71 \mathrm{\ s}$

The accuracy and stability of numerical results may suffer from cancellations of large, approximately equal dilogarithms. Since Maple supports calculations of arbitrary precision, it is always possible to increase the number of digits to improve accuracy – instead of Fortran programs which are limited to Fortran's restricted accuracy.

Usually we calculated with 20 or 40 digits. For all practical purposes our numerical results were not influenced significantly – only in the last four or five digits – if the number of digits increased.

### B.4 The xloops distribution

The distribution (packed in xloops.tgz) consists of the following files:

```
README
                 graphen0.tcl
                                   graphenp.tcl
                                                     particles.txt
XLwidget.tcl
                 graphen1.tcl
                                   help.tcl
                                                     xlinit.tcl
configure*
                 graphen2.tcl
                                   history.tcl
                                                     xloops.prototyp
convert.tcl
                                   maple.tcl
                 graphen2a.tcl
graphen.tcl
                 graphen2b.tcl
                                   model.tcl
MapleVR1:
cfcn.ma
                    make_lib.map
                                         numint.ma_unix
                                                              simple.ma
evalproc.ma
                    mess.isolatin
                                         numint.ma_vms
                                                              test_maple_bug.map
fmrules.ma
                    mess.ma
                                         oneloop.ma
                                                              twoloop.ma
                                                              unvalue.ma
fmuser.ma
                    mess.no_iso
                                         pv.ma
                                                              values.ma
loops.ma
                    numint.ma
                                         r.ma
MapleVR3:
                    make_lib.map
cfcn.ma
                                         numint.ma_unix
                                                              simple.ma
evalproc.ma
                    mess.isolatin
                                         numint.ma_vms
                                                              test_maple_bug.map
fmrules.ma
                    mess.ma
                                                              twoloop.ma
                                         oneloop.ma
                                                              unvalue.ma
fmuser.ma
                    mess.no_iso
                                         pv.ma
                                                              values.ma
loops.ma
                    numint.ma
                                         r.ma
cxx:
                  gauss.h
div0.cxx
                                     makehead.solaris
                                                       numint2.vms*
div0.h
                  incl.cxx
                                     makethread.0
                                                        nvegas.c
dpc1.in
                  main.cxx
                                     makethread.1
                                                        pvegas.c
                                                       utils.cxx
dpc2.in
                  makefile.rest
                                     makethread.2
                                                        utils.h
dpc3.in
                  makefile.vms
                                     numint.cxx
dpc4.in
                  makehead.AIX
                                     numint.prototyp
                                                        vegas.c
                  makehead.Linux
                                     numint1.unix*
funct.cxx
funct.h
                  makehead.generic numint1.vms
                  makehead.osf
                                     numint2.unix*
gauss.cxx
```

lib: B00110.1loop

manual:
manual.html

xbms:

-	1	mp 112000 1110m	Portorinom	P112010.V0m
Hp112t0.xbm	Hp410t0.xbm	attention.xbm	p3l1t0.xbm	p4l2t14.xbm
Hp1l2t1.xbm	Hp4l1t0.xbm	file.xbm	p3l1t1.xbm	p4l2t15.xbm
Hp112t2.xbm	Hp4l1t1.xbm	help.xbm	p3l1t4.xbm	p4l2t16.xbm
Hp210t0.xbm	Hp4l1t2.xbm	insmath.xbm	p3l1t5.xbm	p4l2t17.xbm
Hp2l1t0.xbm	Hp412t0.xbm	leftarrow.xbm	p3l2t0.xbm	p4l2t18.xbm
Hp2l1t1.xbm	Hp412t1.xbm	p1l1t0.xbm	p3l2t1.xbm	p4l2t19.xbm
Hp212t0.xbm	Hp412t10.xbm	p1l1t1.xbm	p3l2t10.xbm	p412t2.xbm
Hp2l2t1.xbm	Hp412t11.xbm	p1l2t0.xbm	p3l2t11.xbm	p412t20.xbm
Hp2l2t10.xbm	Hp412t12.xbm	p1l2t1.xbm	p3l2t12.xbm	p4l2t21.xbm
Hp2l2t11.xbm	Hp412t13.xbm	p1l2t2.xbm	p3l2t13.xbm	p412t22.xbm
Hp212t2.xbm	Hp412t14.xbm	p1l2t3.xbm	p3l2t2.xbm	p412t23.xbm
Hp212t3.xbm	Hp412t15.xbm	p1proc.xbm	p3l2t3.xbm	p412t24.xbm
Hp212t4.xbm	Hp4l2t16.xbm	p210t0.xbm	p3l2t4.xbm	p412t25.xbm
Hp212t5.xbm	Hp412t17.xbm	p2l0t1.xbm	p3l2t5.xbm	p412t26.xbm
Hp212t6.xbm	Hp412t18.xbm	p2l1t0.xbm	p3l2t6.xbm	p412t27.xbm
Hp212t7.xbm	Hp412t19.xbm	p2l1t1.xbm	p3l2t7.xbm	p412t28.xbm
Hp310t0.xbm	Hp412t2.xbm	p2l1t2.xbm	p3l2t8.xbm	p412t3.xbm
Hp3l1t0.xbm	Hp412t20.xbm	p2l1t3.xbm	p3l2t9.xbm	p412t4.xbm
Hp3l1t1.xbm	Hp412t21.xbm	p2l2t0.xbm	p3proc.xbm	p412t5.xbm
Hp312t0.xbm	Hp412t22.xbm	p2l2t1.xbm	p410t0.xbm	p412t6.xbm
Hp3l2t1.xbm	Hp412t23.xbm	p2l2t10.xbm	p410t3.xbm	p412t7.xbm
Hp3l2t10.xbm	Hp412t24.xbm	p2l2t11.xbm	p4l1t0.xbm	p412t8.xbm
Hp3l2t11.xbm	Hp412t25.xbm	p2l2t2.xbm	p4l1t1.xbm	p412t9.xbm
Hp3l2t12.xbm	Hp412t26.xbm	p2l2t3.xbm	p4l1t2.xbm	p4proc.xbm
Hp3l2t13.xbm	Hp412t27.xbm	p2l2t4.xbm	p4l1t6.xbm	rightarrow.xbm
Hp312t2.xbm	Hp412t28.xbm	p2l2t5.xbm	p4l1t7.xbm	<pre>schraff.xbm</pre>
Hp312t3.xbm	Hp412t3.xbm	p212t6.xbm	p4l1t8.xbm	<pre>xloops.gif</pre>
Hp312t4.xbm	Hp412t4.xbm	p2l2t7.xbm	p412t0.xbm	<pre>xloops.xbm</pre>
Hp312t5.xbm	Hp412t5.xbm	p2l2t8.xbm	p4l2t1.xbm	
Hp3l2t6.xbm	Hp412t6.xbm	p2l2t9.xbm	p4l2t10.xbm	
Hp3l2t7.xbm	Hp412t7.xbm	p2proc.xbm	p4l2t11.xbm	
Hp3l2t8.xbm	Hp412t8.xbm	p3l0t0.xbm	p4l2t12.xbm	

## Bibliography

- B. W. Char, K. O. Geddes, G. H. Gonnet, B. L. Leong, M. B. Monagan, S. M. Watt. Maple V Language Reference Manual. Springer (1991)
- [2] B. W. Char, K. O. Geddes, G. H. Gonnet, B. L. Leong, M. B. Monagan, S. M. Watt. Maple V Library Reference Manual. Springer (1991)
- [3] G. P. Lepage. J. Comp. Phys. 27 (1978) 192
- [4] G. P. Lepage. Cornell Univ. Preprint CLNS-80/447 (1980)
- [5] J. K. Ousterhout. Tcl und Tk Entwicklung grafischer Benutzerschnittstellen f
  ür das XWindow-System. Addison-Wesley (1995)
- [6] L. Brücher, J. Franzkowski, D. Kreimer. Comp. Phys. Comm. 85 (1995) 153
- [7] L. Brücher, J. Franzkowski, D. Kreimer. Univ. Mainz Preprint MZ-TH/97-23 (1997)
- [8] B. Stroustrup. The C++ Programming Language. Addison-Wesley (1995)
- [9] R. Kreckel. Irreduzible Zwei-Loop-Beiträge zu den Prozessen  $\gamma\gamma \to \pi\pi$  und  $\eta \to \pi\gamma\gamma$ . Diploma thesis, Univ. Mainz (1997)
- [10] R. Kreckel. Univ. Mainz Preprint MZ-TH/97-30 (1997)
- [11] Particle Data Group. *Phys. Rev.* **D54** (1996) 1
- [12] B. W. Lee, C. Quigg, H. B. Thacker. *Phys. Rev.* D16 (1977) 1519
- [13] H. Veltman. Phys. Rev. **D41** (1990) 2294
- [14] K. Riesselmann, in: B. A. Kniehl (ed.). Perspectives for Electroweak Interactions in  $e^+e^-$  Collisions, page 175. World Scientific (1995)
- [15] K. Aoki, Z. Hioki, R. Kawabe, M. Konuma, T. Muta. Suppl. Prog. Theor. Phys. 73 (1982) 1
- [16] O. Nachtmann. *Phänomene und Konzepte der Elementarteilchenphysik*. Vieweg (1986)
- [17] J. F. Gunion, H. E. Haber, G. Kane, S. Dawson. The Higgs Hunter's Guide. Addison Wesley (1990)
- [18] B. C. Carlson. Special Functions of Applied Mathematics. Academic Press (1977)
- [19] L. Brücher, J. Franzkowski, D. Kreimer. Mod. Phys. Lett. A9 (1994) 2335
- [20] L. Lewin. *Polylogarithms and Associated Functions*. North Holland (1981)

# Index

٨	$D_{inco, \alpha}$ 19.19	т
A 21	$\begin{array}{c} \text{Dirac} \gamma \dots \dots 13, 18 \\ \text{distribution} \end{array}$	
About		Insert Manle
access	E	Command 15 17 19
arrow 12 16 21	e 15	Insert Particle
- direction 12, 16, 21	E Eull 17	Properties 16 17 20
- inversion	ee Z vortex 16	installation
– misplaced		integral representation 14, 15
– placement		integration
- position	$\underbrace{Eval. Numeric}_{Eval. Numeric} \dots $	– Monte Carlo
- position on the ruler26	Evaluate $\ldots \ldots 13, 16$	– numerical
Arrow Scaling	evaluation	intentions
ascii	- modes 13	Isolatin 18
	executable file	iterations21
В	Export	
bash	Ext. Lines 11, 16, 20	K
~	external lines $\dots \dots \dots 11, 20$	kinematical variables17
С	external momenta13, 15, 16	- assignment17
$\underbrace{C}_{++} \dots $	external particles $\dots \dots 17$	-
Cancel	- on-shell 17	L
character encoding		Linux
charge 12, 21	$\mathbf{F}$	Load Process 19, 23
- conjugation 21	fermion line	LoopPath 10
CKM matrix	- direction	Loops 11, 10, 20
- assignment	fermion number $\dots \dots 12, 21$	Lorentz structure 15, 18
$\begin{array}{c} (lose) \\ \hline \\ (lose) \\ \hline \\ \end{array}$	fermions21	М
closed loops $11, 20$	File 15–17, 19, 23	<i>main window</i> 9, 11, 15, 16, 21
Columns 25	file $window \dots 23$	Makefile8
command har 21	form factors $\dots 13, 18$	Maple
comments		– release
configure	G	- session10, 19
copyright	GeV 17	Maple part 9
couplings	ghost number $\dots 12, 21$	- installation
– assignment 16, 17	$Graphs \dots \dots 23$	masses
– electromagnetic		- assignment 16, 17
- values	Н	– infinitesimal
Create Process	Help 12, 16, 21	imaginary part $\dots 15$
	Higgs mass 15	- numerical input
D	Higgs self-energy 12	- of light fermions
diagram area21	History	– of neutrinos 20
diagram window	history table23	- values
$\dots 12, 13, 16, 21, 23, 25$	$-$ size $\dots 25$	Massless Light Fermions 21
Digital Unix8	html version $\dots \dots 8, 21$	master topology $\dots \dots 12$

menu bar 11, 19, 21	- description	Т
Mhiggs15	– name	Tcl/Tk5, 7
mixing matrix	- saving	text window11, 19
Model	process name20	threshold16
momenta	program start	Tk
– numerical input		topology. 11, 12, 16, 20, 21, 23
momentum flow $\dots \dots 21$	$\mathbf{Q}$	– two-loop
Monte Carlo integration 5	Quit19	$topology \ bar \dots 11, 12, 20, 21$
MU17	В	Tutorial
multiprocessing8		tw15
Mw15	README	two-loop functions
	regulator	- analytic result
N	ultraviolet 12	Twoloop13
neutrinos	- utraviolet	Twoloop2Pt213
New Process 19, 23	– numerical input 10	
Numeric 16, 21	ronormalization scale 17	U
numerical input 19	requirements 7	Unix
numerical integration	Restart Manle 19	V
$\dots 5, 8, 9, 15, 21, 60$	result 13 16	variables
numerical uncertainty 16	- assignment to a variable 13	romoval 10
0	– non-analytic 13	-1000000000000000000000000000000000000
ОК	– numerical	- input parameters 16
one-loop diagrams	- reading	– normal implementation 8
- library	- saving 16, 20, 23	– parallelized
Oneloop	- uncertainty	implementation 5.8
Oneloop Library	Rows	
Options16, 17, 20, 23	ruler	$\mathbf{W}$
orthogonal space $\dots 13, 17$		W mass
output	$\mathbf{S}$	Weinberg angle15
-	Save Maple Output16, 19	Window Options $\dots \dots 21$
Р	Save Options 21	WWW browser $\dots 8, 21$
parallel space13	Scale Factor $\dots 25$	
Particle Data Group20	Set Neutrino Masses 020	X
particle names $\dots \dots 12, 16$	simultaneous sessions9	X terminals25
physical models 20	start	.xloops21
Postscript	SUN Solaris8	xloops_user23













