

# A Variational Principle for the Asymptotic Speed of Fronts of the Density Dependent Diffusion-Reaction Equation

R. D. Benguria and M. C. Depassier

Facultad de Física

P. Universidad Católica de Chile

Casilla 306, Santiago 22, Chile

## Abstract

We show that the minimal speed for the existence of monotonic fronts of the equation  $u_t = (u^m)_{xx} + f(u)$  with  $f(0) = f(1) = 0$ ,  $m > 1$  and  $f > 0$  in  $(0, 1)$ , derives from a variational principle. The variational principle allows to calculate, in principle, the exact speed for general  $f$ . The case  $m = 1$  when  $f'(0) = 0$  is included as an extension of the results.

Several problems arising in population growth [1, 2], combustion theory [3, 4], chemical kinetics [5], and others [6], lead to an equation of the form

$$\frac{\partial \rho}{\partial t} + \vec{\nabla} \cdot \vec{j} = F(\rho),$$

where the source term  $F(\rho)$  represents net growth and saturation processes. The flux  $\vec{j}$  is given by Fick's law

$$\vec{j} = -D(\rho)\vec{\nabla}\rho,$$

where the diffusion coefficient  $D(\rho)$  may depend on the density or in simple cases be taken as a constant. In one dimension this leads to the equation

$$\frac{\partial \rho}{\partial t} = \frac{\partial}{\partial x} \left( D(\rho) \frac{\partial \rho}{\partial x} \right) + F(\rho). \quad (1a)$$

In what follows we shall assume that

$$F(\rho) > 0 \quad \text{in} \quad (0, 1), \quad \text{and} \quad F(0) = F(1) = 0, \quad (1b)$$

restrictions which are satisfied by several models. When the diffusion coefficient is constant and the additional requirement  $F'(0) > 0$  is satisfied, the asymptotic speed of propagation of localized small perturbations to the unstable state  $u = 0$  is bounded below and in some cases coincides [7] with the value  $c_L = 2\sqrt{F'(0)}$  which is obtained from considerations on the linearized equation [8]. However, when either  $F'(0) = 0$  or  $D(\rho)$  is not a constant, no hint for the speed of propagation of disturbances can be obtained from linear theory alone. A common choice for the diffusion coefficient is a power law, case with which we shall be concerned here. Therefore the equation that we study is

$$\frac{\partial \rho}{\partial t} = (\rho^m)_{xx} + F(\rho) \quad (2a)$$

with

$$F(0) = F(1) = 0, \quad \text{and} \quad F > 0 \quad \text{in} \quad (0, 1). \quad (2b)$$

Aronson and Weinberger [7, 2] have shown that the asymptotic speed of propagation of disturbances from rest is the minimal speed  $c^*(m)$  for which there exist monotonic travelling

fronts  $\rho(x, t) = q(x - ct)$  joining  $q = 1$  to  $q = 0$ . The equation satisfied by the travelling fronts is

$$(q^m)_{zz} + cq_z + F(q) = 0 \quad (3a)$$

with

$$q(-\infty) = 1, \quad q > 0, \quad q' < 0 \quad \text{in} \quad (-\infty, \omega), \quad q(\omega) = 0 \quad (3b)$$

where  $z = x - ct$ . The wave of minimal speed is sharp, that is,  $\omega < \infty$  when  $m > 1$  [2].

An explicit solution is known [1, 2] for the case  $F(q) = q(1 - q)$  and  $m = 2$ , the waveform is given by

$$q(z) = \left[ 1 - \frac{1}{2}e^{z/2} \right]_+$$

and it travels with speed  $c^*(2) = 1$  (here  $[x]_+ \equiv \max(x, 0)$ ). Recently the derivative  $dc/dm$  at  $m = 2$  has been calculated by two different methods. Its value is  $-7/24$  [9, 10]. Other exact solutions for different choices for  $m$  and  $F$  have been given in [11].

The purpose of this work is to give a variational characterization of the minimal speed  $c^*(m)$  for Eq.(3) when  $m > 1$ , and as a byproduct for the case  $m = 1$  when  $F'(0) = 0$ , both, cases for which no information is obtained from linear theory. The case  $m = 1$  with  $F'(0) > 0$  has been studied elsewhere [13]. Lower bounds have been obtained on the minimal speed  $c^*(m)$  [12]; the present results allow its exact calculation for arbitrary  $f$ .

Since the selected speed corresponds to that of a decreasing monotonic front, we may consider the dependence of its derivative  $dq/dz$  on  $q$ . Calling  $p(q) = -q^{m-1}dq/dz$ , where the minus sign is included so that  $p$  is positive, we find that the monotonic fronts are solutions of

$$p \frac{dp}{dq} - \frac{c^*}{m} p + \frac{1}{m} q^{m-1} F(q) = 0 \quad (4a)$$

with

$$p(0) = p(1) = 0, \quad p > 0 \quad \text{in} \quad (0, 1). \quad (4b)$$

Although the wave of minimal speed is sharp and therefore  $q'(0) < 0$ , by its definition  $p(0) = 0$  is true. We now show that the minimal speed  $c^*(m)$  follows from a variational principle whose Euler equation is Eq.(4a).

Let  $g$  be a positive function such that  $h = -g' > 0$ . Multiplying Eq.(4a) by  $g/p$  and integrating we obtain after integration by parts,

$$\frac{c}{m} = \frac{\int_0^1 \left[ \frac{1}{m} q^{m-1} F(q) \frac{g(q)}{p(q)} + h(q)p(q) \right] dq}{\int_0^1 g(q) dq}. \quad (5)$$

By Schwarz's inequality, since,  $q$ ,  $F$ ,  $g$  and  $h$  are positive we know

$$\frac{1}{m} q^{m-1} F \frac{g}{p} + hp \geq 2 \sqrt{\frac{1}{m} q^{m-1} F g h} \quad (6)$$

and therefore, replacing in Eq.(5) we have

$$c \geq 2 \frac{\int_0^1 \sqrt{m q^{m-1} F g h} dq}{\int_0^1 g dq}. \quad (7)$$

This bound has been already given by us [12]. We now show that it is always possible to find a  $g(q)$  such that the equality in Eq.(6) and therefore also in Eq.(7) holds. We do so by explicit construction of such a function  $g$ . The equality in Eq.(6) holds if

$$\frac{1}{m} q^{m-1} F \frac{g}{p} = hp \quad (8)$$

Let  $v(q)$  be the positive solution of

$$\frac{v'}{v} = \frac{c}{mp} \quad (9a)$$

and choose

$$g = \frac{1}{v'}. \quad (9b)$$

We have then

$$\frac{v''}{v} = \frac{(v')^2}{v^2} - \frac{c}{mp^2} p' = \frac{c}{m^2 p^3} q^{m-1} F(q)$$

where we have used Eq.(9a) to eliminate  $v'$  and Eq.(4a) to eliminate  $p'$ . Therefore,

$$h = -g' = \frac{v''}{(v')^2} = \frac{1}{mp^2} q^{m-1} F g > 0 \quad (9c)$$

where we have made use of Eqs.(9a) and (9b). With this expression for  $h$ , we can see that Eq.(8) is satisfied. In addition we must check that  $g$  as we have defined it is such that its integral exists. In fact as it exists and moreover one can always normalize  $g$  so that  $g(0) = 1$  and  $g(1) = 0$ . From the definition of  $g$  we obtain

$$g(q) = \frac{mp(q)}{c} \exp \left[ - \int_{q_0}^q \frac{c}{mp} dq' \right]$$

where  $0 < q_0 < 1$ . Since  $p(1) = 0$  and  $p$  is positive between 0 and 1 it follows that  $g(1) = 0$ . At zero no divergence occurs, as we now show. Call  $\hat{c} = c/m$  and  $f(q) = q^{m-1}F(q)/m$ . Then Eq.(4a) reads

$$pp' - \hat{c}p + f = 0 \quad (10a)$$

with

$$f(0) = f(1) = 0 \quad \text{and} \quad f'(0) = 0. \quad (10b)$$

For this case Aronson and Weinberger [7] have shown that  $p(q)$  approaches the fixed point  $q = 0$  as  $p = \hat{c}q = cq/m$ . Then, near 0,  $v'/v \approx 1/q$  or  $v \approx q$  and from its definition  $g(0) = 1$ . Then the integral of  $g$  exists. We have shown then

$$c^*(m) = \max 2 \frac{\int_0^1 \sqrt{mq^{m-1}Fgh} dq}{\int_0^1 g dq}. \quad (11)$$

where the maximum is taken over all functions  $g$  such that

$$g(0) = 1, \quad g(1) = 0 \quad \text{and} \quad h = -g' > 0.$$

It is perhaps of some interest to verify explicitly that the Euler equation for the maximizing  $g$  is indeed Eq.(4a). Let us study the maximization of the functional

$$J_m(g) = 2 \int_0^1 \sqrt{mq^{m-1}Fgh} dq$$

where  $h = -g' > 0$  subject to

$$\int_0^1 g(q) dq = 1.$$

The Euler equation for this problem is

$$\lambda + \sqrt{\frac{mq^{m-1}Fh}{g}} + \frac{d}{dq} \left( \sqrt{\frac{mq^{m-1}Fg}{h}} \right) = 0$$

where  $\lambda$  is the Lagrange multiplier. Using the expression given in Eq.(9c) for  $h$  we see that this is exactly Eq.(4a) with the Lagrange multiplier  $\lambda = -c$ .

As an application we shall consider the case  $F(q) = q(1-q)$  and  $m = 2$  for which the exact solution is known. Take as the trial function  $g(q) = (1-q)^2$ . Then we obtain

$$c \geq 4 \frac{\int_0^1 q(1-q)^2 dq}{\int_0^1 (1-q)^2 dq} = 1$$

the exact value, which shows that this is the function  $g$  for which the maximum is attained. In addition, due to the existence of the variational principle we may use the Feynman-Hellman formula to calculate the dependence of  $c(m)$  on parameters of  $F$ . We illustrate this by applying it to the calculation of  $dc/dm$  at  $m = 2$ . Taking the derivative of Eq.(10) with respect to  $m$  we obtain

$$\frac{dc}{dm} = \frac{1}{\int_0^1 g dq} \int_0^1 \frac{ghF}{\sqrt{mFq^{m-1}gh}} [q^{m-1}(1 + m \log q)] dq.$$

Evaluating at  $m = 2$ , with  $g(q) = (1 - q)^2$  we obtain

$$\frac{dc}{dm}(2) = 3 \int_0^1 q(1 - q)^2(1 + 2 \log q) dq = -\frac{7}{24}$$

the value previously obtained by other methods.

A fast estimation of the speed for other values of  $m$  can be obtained with simple trial functions. In Fig. 1 we show lower bounds for  $F = q(1 - q)$  using as trial functions  $g_1 = (1 - q)^2$  and  $g_2 = (1 - q)$ . With the first trial function we have the exact value at  $m = 2$ . The dotted line is the line of slope  $-7/24$  that coincides with the tangent at  $m = 2$ . For larger  $m$  a better estimate is obtained using  $g_2$ . The dashed line is the curve  $\sqrt{2/m}$  which has been suggested by Newman [1] as the best fit to his numerical results. With better choice of trial functions the exact value can be approached arbitrarily close.

Finally we observe that the case  $m = 1$  when  $F'(0) = 0$  follows directly here. Repeating the procedure starting now from equation (10), one obtains,

$$c = \max 2 \frac{\int_0^1 \sqrt{Fgh} dq}{\int_0^1 g dq}$$

where the maximum is taken over all functions  $g$  such that

$$g(0) = 1, \quad g(1) = 0 \quad \text{and} \quad h = -g' > 0.$$

To show this we have used  $v'/v = c/p$  and  $g = 1/v'$  and the asymptotic behavior described above.

## 1 Acknowledgments

We thank Prof. Dirk Meinköhn for giving us several useful references. This work was partially supported by Fondecyt project 193-0559.

## References

- [1] W. I. Newman, *J. Theor. Biol.* **85**, 325, (1980)
- [2] D. G. Aronson, in *Dynamics and Modelling of Reacting Systems*, edited by W. Stewart et al. (Academic, New York, 1980).
- [3] L. E. Vulis, *Thermal Regimes of Combustion* Mc. Graw-Hill (1961).
- [4] P. Clavin, in *Annual Reviews of Fluid Mechanics*, **26**, 321 (1994) and references therein.
- [5] S. K. Scott and K. Showalter, *J. Phys. Chem.* **96**, 8702 (1992)
- [6] W. I. Newman and C. Sagan, *Icarus* **46**, 293, (1981)
- [7] D. G. Aronson and H. F. Weinberger, *Adv. Math.* **30**, 33 (1978).
- [8] A. Kolmogorov, I. Petrovsky, and N. Piskunov, *Bull. Univ. Moscow, Ser. Int. A* **1**, 1 (1937).
- [9] D. G. Aronson and J. L. Vásquez, *Phys. Rev. Lett.* **72**, 348 (1994).
- [10] L. Y. Chen, Ph.D. Thesis, University of Illinois at Urbana-Champaign, 1994.
- [11] J. J. E. Herrera, A. Minzoni, and R. Ondarza, *Physica D* **57**, 249 (1992)
- [12] R. D. Benguria and M. C. Depassier, *Phys. Rev. Lett.* **73**, 2272 (1994).
- [13] R. D. Benguria and M. C. Depassier, submitted to *Commun. Math. Phys.* (1994).