Superluminal Tunneling Devices

Günter Nimtz II. Physikalisches Institut, Universität Köln

November 2001

Abstract

Photonic tunneling permits superluminal signal transmission. The principle of causality is not violated but the time duration between cause and effect can be shortened compared with an interaction exchange with velocity of light. This outstanding property can be applied to speed-up photonic signal modulation and transmission as well as to improve micro-electronic devices. Superluminal photonic signal transmission have been presented at microwave and infrared frequencies already. Presumably superluminal photonic and electronic devices can become reality having in mind the experimental evidence of the universal tunneling time of photons and of electrons.

1 Introduction

In 1992 Enders and the author have demonstrated that photonic tunneling takes place with superluminal signal velocity [1]. The experiments were carried out with microwaves. At that time any application of superluminal tunneling was not expected in spite of the popular semiconductor tunneling diode. A decade later I am going to present some potential applications of superluminal tunneling in photonics and electronics.

The special features of evanescenuniversal tunneling tit modes and wave mechanical tunneling are presented in this chapter. In the following chapters the essential properties of a signal as well as the universal tunneling time are introduced. The last chapters are devoted to applications of the tunneling process as well as to a summary of the strange tunneling properties.

Tunneling is the wave mechanical presentation of evanescent modes [2, 3]. Evanescent modes are dominantly found in undersized waveguides, in the forbidden frequency bands of periodic dielectric heterostructures, and with double prisms in the case of frustrated total reflection [4, 5]. These prominent examples of photonic tunneling barriers are sketched in Fig. 1. The dielectric lattice is equivalent to the electronic lattice of semiconductors with forbidden energy gaps.

Evanescent modes and tunneling wave functions are characterized by a purely *imaginary* wave number. For instance the wave equation yields for the electric field E(z)

$$E(z) = E_0 e^{i(\omega t - kx)} \quad \Rightarrow \quad E(z) = E_0 e^{i\omega t - \kappa x}, \tag{1}$$



Figure 1: Sketch of three prominent photonic barriers. a) illustrates an undersized wave guide (the central part of the wave guide has a cross-section being smaller than half the wavelength in both directions perpendicular to propagation), b) a photonic lattice (periodic dielectric hetero structure), and c) the frustrated total internal reflection of a double prism, where total reflection takes place at the boundary from a denser to a rarer dielectric medium.

where ω is the angular frequency, t the time, x the distance, k the wave number, and κ the *imaginary* wave number of the evanescent mode.

In the three introduced examples the modes are characterized by an exponential attenuation of transmission due to reflection by photonic barriers and by a lack of a phase shift inside the barrier. The latter means a zero time barrier traversal according to the phase time approach

$$\tau = d\phi/d\omega,\tag{2}$$

where τ, ϕ, ω are the phase-time, the phase, and the angular frequency, respectively. The observed very short tunneling time is caused at the barrier front boundary. In this report the tunneling time is defined as the time a group or a signal spent traversing a barrier. The time is measured outside the barrier with detectors positioned at the front and the back of the barrier.

This time corresponds to the phase-time or group delay, see Refs. [6, 7, 8] for example. In Fig.2 a pulse (i.e. a wavepacket) is sketched which represents a digital signal. The front of the envelope is very smooth corresponding to a narrow frequency band width. The frequency band is choosen with respect to the barrier in question in such a way that the pulse contains essentially evanescent frequency components. Such an evanescent pulse travels in zero time through opaque barriers, which in turn results in an infinite velocity in the phase-time approach neglecting the phase shift at the barrier front [1, 9].

In the review on *The quantum mechanical tunnelling time problem - revisited* by Collins et al. [10], the following statement has been made: the phase-time-result originally obtained by Wigner and by Hartman is the best expression to use for a wide parameter range of barriers, energies and wavepackets. The experimental results of photonic tunneling have confirmed this statement [4].



Figure 2: Sketch of two wave packets (i.e. pulses), amplitude vs time. The larger packet travelled slower than the attenuated one. The horizontal bars indicate the half width of the packets which do not depend on the packet's magnitude. The figure illustrates the gradually beginning of the packets. The forward tail of the smooth envelope may be described by the relation $[1 - exp(-t/\tau)][sin(\omega t)]$ for instance, where τ is a time constant.

Einstein causality prohibits superluminal signal velocity in vacuum and in media with a real refractive index. This rule does not hold for media characterized by an imaginary refractive index, where the phase shift is zero as in the case of evanescent modes. In order to avoid signal reshaping due to the dispersion of the special media the signal has to be frequency band limited. The problem of limited frequency band and the time limited duration of signals has been discussed and explained by quantum mechanical arguments [11, 12]. Actually, signals of limited frequency band and limited time duration have been transmited in the multiplex telephony for more than a hundred years. The theory for these technical signals and more general for all physical signals, presents the sampling theorem, which has been introduced by Shannon around 50 years ago [13]. More details about signal properties are presented in Chapter Signals.

Evanescent modes are solutions of the classical Maxwell equations, however, they display some nonclassical properties as for instance:

- 1. The evanescent modes seem to be represented by nonlocal fields as was predicted and later shown by transmission and partial reflection experiments [4, 9, 14]. Tunneling and reflection times are equal and independent of barrier length.
- 2. Evanescent modes have a negative energy, thus they cannot be measured [15, 16].

- 3. Evanescent modes can be described by virtual photons [17].
- 4. Evanescent modes are not Lorentz invariant as $(v_{\varphi}/c)^2 \rightarrow \infty$ holds, where $v_{\varphi} = x/\tau$ is the phase time velocity and c the velocity of light in vacuum. x represents the barrier length.

Obviously, evanescent modes are not fully describable by the Maxwell equations and quantum mechanics have to be taken into consideration. This is similar to the photoelectric effect which Einstein explained by quantum mechanics, i.e. by photons. In general electric fields are only detectable by a quantized energy exchange.



Figure 3: An example of a resonant electromagnetic tunneling structure with evanescent mode solutions (forbidden frequency bands) at microwave frequencies. Two periodic quarter wavelength hetero–structures of perspex and air which are separated by a distance of 18.9 cm forming a resonant cavity with a total length of 30 cm.

The tunneling time raised at the front of opaque barriers is constant and independent of barrier length. Thus with increasing barrier length the signal velocity increases at the same rate as the length. This phenomenon is often called Hartman effect [18, 19].

The effective barrier length can be significantly lengthened by resonant barrier structures without decreasing the transmission. Resonant tunneling structures with forbidden frequency bands are advantageous to speed-up signals with a narrow frequency band width [4, 20]. Figure 3 displays a resonant barrier built of two photonic lattices barriers. The dispersion relations of the respective transmission coefficients and the signal velocity of the periodic dielectric quarter wavelength heterostructure are displayed in Fig.4. For narrow frequency band limited signals there is no significant dispersion effect if the carrier frequency is placed in the centre of a forbidden frequency gap.

Each of the three barriers introduced in Fig.1 has a different dispersion relation. A simple one describes the frustrated total internal reflection of a double prism. In this case the transmitted electric field E_t and the imaginary wave number κ are given by the relations [3]:

$$E_t = E_0 e^{(i\omega t - \kappa z)} \tag{3}$$

$$\kappa = \left[\frac{\omega^2}{c^2}((\frac{n_1}{n_2})^2 - 1)\sin^2\theta)\right]^{1/2},\tag{4}$$



Figure 4: The graph (a) shows the dispersion relation for the resonant heterostructure vs frequency (Fig.3(a)). The transmission dispersion of the periodic heterostructure displays forbidden gaps separated by resonant peaks. The forbidden frequency gaps correspond to the tunneling regime, for details see Ref. [4]. The evanescent regime is characterized by a strong attenuation due to reflection. In (b) the group (signal) velocity in units of c is displayed for the resonant periodic dielectric quarter wavelength heterostructure vs frequency.

where θ is the angle of the incident beam, E_0 the electric field at the barrier entrance, n_1 and n_2 are the refractive indices, and $(n_1/n_2 \sin \theta > 1)$. The transmission $t = E_t/E_0$ as a function of air gap of a double prism was measured with microwaves and is shown in Fig.5. The displayed data are in agreement with Eqs.3, 4.

The tunneling time in the case of frustrated total internal reflection (FTIR) has been revisited recently [21, 22]. There is a theoretical shortcoming in describing the time behaviour of FTIR which is based on the approach with ideal plane waves. This approach holds for an unlimited beam diameter, but is not mimicking properly the experimental procedure with limited beam diameters [22, 23].

In this report two simple experiments are introduced, which demonstrate superluminal signal velocity in photonic barriers. The signal is represented by a pulse as used in digital communication systems [11, 16]; one example was measured with microwaves and one in the infrared frequency range as shown in Figs. 6, 7.

The digital signal displayed in Fig. 6 tunneled with a frequency band width of less than 10^{-2} at a speed of 8 c. The carrier frequency was 9.15 GHz. The starting of detecting the envelope of the tunneled signal is about 0.8 ns ealier as that of the airborne puls. The signal frequency band contained essentially evanescent components only.

The experimental set-up to determine and to demonstrate superluminal group velocity is shown in Fig.8 and 9. The group arrival was measured in vacuum where group, energy, and signal velocities are equal to c [24, 25], (actually, a signal does not depend on its magnitude as illustrated in Fig.2). Amplitude modulated microwaves with a frequency of 9.15 GHz ($\lambda = 3.28$ cm) are generated with an HP 8341B synthesized sweeper (10 MHz



Figure 5: Transmission vs air gap measured at two frequencies [22]. The data follow the theoretical relation of Eqs.3,4.

- 20 GHz). A parabolic antenna transmitted parallel beams. The transmitted signal has been received by another parabolic antenna, rectified by a diode (HP 8472A (NEG)) and displayed on an oscilloscope (HP 54825A).

The propagation time of a signal was measured across the air distance between transmitter and receiver and across the same distance but partially filled with the barrier of 28 cm length. The barrier structure is formed by quarter wavelength slabs of perspex and is introduced and analyzed in Figs. 3, 4. Each slab is 0.5 cm thick and the distance between two slabs is 0.85 cm. Two structures are separated by an air distance of 18.9 cm forming a resonant tunneling structure [4]. Comparing the two travelling times we see that the tunneled signal arrived the detector about 900 ps earlier than that pulse which travelled the same distance through air. The result corresponds to a signal velocity of the tunneled pulse of $8 \cdot c$.

The performed measurements are asymptotic. There is no coupling between the generation process, the detection process, and the photonic barrier. In addition the experiment is not stationary and the signal is measured in the dispersion free vacuum. The experimental situation is the same as that performed in the Hong-Ou-Mandel interferometer, in which the measurement is also asymptotic and yields the group velocity, the energy and the signal velocity at the same time [12, 26]. An infrared example of superluminal signal velocity is displayed in Fig.7.

So far we have discussed transmission experiments only. An experimental set-up for measuring the partial reflection by photonic barriers at microwave frequencies is presented in Fig.9. The procedure of varrying the barrier length in such an experiment is sketched in Fig.10.



Figure 6: Measured propagation time of two signals. The faster one has tunneled in the forbidden gap of the photonic barrier of the length of 28 cm. The pulses magnitudes are normalized. The tunneled signal (the half–width of the pulse, representing one bit) traversed the barrier more than 800 ps faster than the airborne signal. The corresponding velocity of the tunneled signal was $8 \cdot c$.

2 Signals

For instance, a signal may be a photon, which excites an atom with a well defined energy and polarization or it may be a word, which informs the receiver. Both examples are described by wavepackets of limited frequency band width and of limited time duration. The envelope of the photon as well as that of the word are travelling at the speed of light in vacuum. In vacuum group, signal, and energy velocities are equal c. Physical and of course all technical signals like those displayed in Figs. 6,7,11 are frequency band limited. Technical signals are either amplitude modulated (AM) or frequency modulated (FM). Definitions of the frequency bandwidth, of the time duration, and of the bandwidthtime interval product are introduced and explained in Ref. [29] for example. Frequency components of a signal outside the band width in charge of a hypothetical signal front are usually smaller than -60 dB compared with the signal peak component.

The Fourier transform yields for frequency band limited signals an unlimited time extension and hence a noncausal behaviour. However, the noncausal time components have never been detected. In the case of an unlimited frequency band the wave packet is presented by an analytic function and the information contained in the forward tail of the packet determines the whole packet [30]. This is mathematically correct but not relevant for signals from the physical point of view.



Figure 7: Measured propagation time of three digital signals [35]. (a) Pulse trace 1 was recorded in vacuum. Pulse 2 traversed a photonic lattice in the center of the frequency band gap (see part (b) of the figure), and pulse 3 was recorded for the pulse travelling through the fiber outside the forbidden band gap. The photonic lattice was a periodic dielectric hetero-structure fiber.

As mentioned above engineers have transmitted frequency band and time duration limited signals with the multiplex technology already a hundred years ago. A historic picture of such a multiplex transmission system is shown in Fig.12. Obviously, the five signals transmitted over one guide are frequency band limited and time duration limited. In this example the frequency band width has been 2 kHz and the time length about 0.3 ms. Shannon's and many other's theoretical investigations yielded in the result that the product of frequency band and of time duration represents the amount of information. The Fourier transform of such a multiplex technique yields a noncausal behaviour. This indicates that noncausal time components obtained from Fourier transform are not detectable [11, 12].

3 Universal Tunneling Time

An analysis of different experimental tunneling time data obtained with opaque barriers (i.e. $\kappa z > 1$) pointed to a universal time [31]. The relation

$$\tau \approx 1/\nu = T \tag{5}$$

$$\tau \approx h/W,$$
 (6)

was found independent of frequency and of the type of barrier studied [31, 32], where τ , ν and T are the tunneling time, the carrier frequency or a wave packet's energy W divided by the Planck constant h, and T the oscillation time of the wave. The microwave



Figure 8: Experimental set-up for the periodic dielectric quarter wavelength heterostructure to measure the group velocity, i.e. the signal velocity.

experiments near 10 GHz displayed a tunneling time of about 100 ps, experiments in the optical frequency regime near 427 THz a tunneling time of 2.2 fs for instance. In Ref. [31] it was conjectured that the relation holds also for wave packets with a rest mass having in mind the mathematical analogy between the Helmholtz and the Schrödinger equations. Quantum mechanical studies point to this conjecture [9, 10, 33]. Recently electron tunneling time was measured in a field emission experiment [34]. The measured times are between 6 fs and 8 fs. Assuming an electron energy of 0.6 eV (the barrier height was 1.7 eV) the empirical Eq.(5) yields a tunneling time of 7 fs.



Figure 9: Experimental set–up for the periodic dielectric quarter wavelength heterostructure to measure partial reflection as a function of barrier length.



Figure 10: Experimental procedure to measure partial signal reflection depending on photonic lattice structure.

4 Photonic Applications

Tunneling transmission has an exponential decrease with barrier length, the transmission loss is due to reflection. Actually, the transmission loss is not converted into heat and may be recycled in a special circuit design.

4.1 Tunneling

a) Recently Longhi et al. [35] performed tunneling of narrow band infrared pulses over a distance of 20 000 wavelengths corresponding to about 80 000 quarter wavelengths layers. Results are presented in Fig.7. The overall distance of the photonic fiber lattice was 2 cm. (Scaling the barrier length to 10 GHz microwaves the barrier would be 400 m long.) The periodic variation of the refractive index along the fiber between the two different quarter wavelength layers is only of the order of 10^{-4} . The measured group velocity was 2 c and the transmission intensity of the barrier was 1.5 %.

b) An analogous tunneling barrier of 16.81 m length is under construction at the University of Koblenz. The long structure is designed for microwave signals at a frequency of 9.15 GHz, i.e. at a wavelength of 3.28 cm. 159 dielectric layers differing in the refractive index between 1.00 (air) and 1.05 of a plastic material. The transition time of the huge barrier will be 14 ns compared with a vacuum time of 56 ns. The expected signal velocity will be 4 c at a transmission of intensity of 0.16 % [36]. The tunneled signal will arrive at the detector 49 ns earlier than the airborn one.

4.2 Partial Reflection By Photonic Barriers

a) Photonic barrier reflection is used at 1.5 μm wavelength in fiber optics. Barriers are performed by a 2 cm long piece of glass fiber with a weakly periodically changed refractive index similar to the barrier used in the superluminal transmission experiment by Longhi et al. mentioned above [35]. The losses of reflection by a photonic barrier (imaginary impedance) are less than that of a metal. Photonic barriers represent more effective mirrors than metallic ones. For example photonic barriers are profitably used to stabilize infrared laser diodes in optoelectronics.



b) Figure 13 shows time dependent reflection data by two mirrors at different positions and by photonic barriers of different lengths. Only the magnitude of the reflected pulse is changed but not the reflection time by the barrier length. The observed reflection time of about 100 ps equals the tunneling time in transmission of the barrier. The nonlocal behavior of tunneling modes gives the information on barrier length within one oscillation time at the barrier front.

We have designed an ultrafast modulator on the basis of partial reflection. The effective barrier length is modulated by an electric field induced change of the refractive index at half of the total barrier length. This results in an amplitude change of reflection, see Fig. 13. Another type of modulation can be achieved due to a local change of refractive index by signals exciting an optical active dielectric medium. For example this principle has been applied in experiments on negative group velocity, see e.g. Ref. [38]. In the case of the above microwave experiment the modulations at the distance of 15 cm away from



Figure 12: Historical picture of a multiplex transmission system Ref. [28].

the barrier entrance appears at the barrier front within 100 ps, whereas the corresponding luminal propagation time is five times longer.

5 Electronic Applications

5.1 The Tunneling Diode

The first man made tunneling device was the tunneling diode. It was invented by Esaki around 1960. This nonlinear electronic device is more and more used since that time. However, the tunneling time which would give the ultimate dynamical specification of such a diode has never been measured yet. Our conjecture is: the universal photonic tunneling time Ref. [31] is valid also for the electronic tunneling process. Actually, recent electronic tunneling time experiments support the conjecture [34]. The experimental data is in agreement with relation Eq. 6.

5.2 Superluminal Electron Transport

It was shown in several quantum mechanical studies by Low and Mende for instance that a particle suitably localized in space and time, which is transmitted through a long, high barrier, travels as if it tunneled it in zero time. [33]. Of course, the time spent inside the barrier was considered only. Again as in the case of photonic tunneling the barrier traversal velocity was superluminal even in the case of relativistic approaches [10, 33, 37]. The electronic transport in a semiconductor is rather slow compared with the velocity of light. The utmost highest electron velocity is given by the ballistic electron transport like in the case of an electron microscope or some semiconductor nano-device structures. Bias



Figure 13: Measured partial reflected microwave pulses vs time. Parameter is the barrier composition as shown in Fig. 10. The signal reflections from metal mirrors either substituting the barrier's front or back position are displayed [14]. In this example the wavelength has been 3.28 cm and the effective barrier length was 41 cm.

voltages of electronic devices are of the order of 1V. This results in a ballistic electron velocity of the order of magnitude of 10^6 m/s, which is two orders of magnitude smaller than c.

5.2.1 Electronic Lattice Structures

We propose an electronic lattice structure with alternating quarter wavelength layers of slightly different bandgaps, which can be traversed at superluminal speeds. The conduction band electron wavelength is of the order of magnitude of 1 nm. Ultrafast coupling of electronic device elements in a circuit could be performed and accelerate the speed of computers. For instance a periodic structure of Si/SiGe quarter wavelength layers represents an electronic lattice. Such a doping of a Si-semiconductor structure with the SiGe alloy yields a weak variation of the band gap analogous to the periodic dielectric fiber structure mentioned above. The electronic structure could have extensions up to more than 1 μ m and could be used to perform ultra-fast interconnections between device elements.

5.2.2 pn-Tunnel Junctions

Interband tunneling the basis of the classical tunneling diode can also be used for fast electronic interconnections. By an appropriate doping profile the tunneling path can be adjusted between some 100 nm up to several 1000 nm.

There is a problem left with all the tunneling applications: the high reflection at the barrier entrance. However, tunneling is not a dissipative process with energy loss. The reflected electronic power should be recycled by a smart circuit design.

6 Summing up

The tunneling process shows amazing properties in the case of opaque barriers to which we are not used to from classical physics. The tunneling time is universal and arises at the barrier front. It equals approximately the reciprocal frequency of the carrier frequency or of the wave packet energy divided by the Planck constant h. Inside a barrier the wave packet does not spent any time. This property results in superluminal signal and energy velocities. The latter became obvious in the single photon experiment, where the detector measured the superluminal energy velocity of the photon [39]. Another strange experience is that evanescent fields are not fully describable by the Maxwell equations. They carry a *negative* energy for instance which makes it impossible to detect them [15, 16, 40] and they are nonlocal. Incidentally, the properties are in agreement with the wave mechanical tunneling. For instance, this is a situation similar to the Hydrogen atom and the photoelectric effect, where quantum mechanics is necessary to explain the atom's stability and the photon-electron interaction.

The energy of signals is always finite resulting in a limited frequency spectrum. This is a consequence of Planck's quantization of radiation with an energy minimum of $\hbar\omega$ [11]. An electric field cannot be measured directly. All detectors need at least one energy quantum $\hbar\omega$ in order to respond. This is a fundamental deficiency of classical physics, which assumes any small amount of field and charge is measurable.

A physical signal has not a well defined envelope front. The latter would need infinite high frequency components with a accordingly high energy [6, 12]. In addition signals are not presented by an analytical function, otherwise the complete information would be contained in the forward tail of the signal [30].

Another consequence of the frequency band limitation of signals is, if they have only evanescent mode components, they can violate Einstein causality, which claims that signal and energy velocity is $\leq c$.

In spite of so much arguing about violation of Einstein causality [5], all the properties introduced above are useful for novel fast devices, for both photonics and electronics.

According to Collins et al. [10] the disputes on zero tunneling time (the time spent inside a barrier) are redundant after reading the papers by Wigner and Hartman. The discussions about superluminal tunneling remind me to the problem of multiplex transmission displayed in Fig. 12. Here a signal's finite time duration and frequency band limitation violate causality according to Fourier transform. However, no one had a ringing-up before the other phone was switched on. This indicates the crucial role of finite frequency bands and finite time duration of signals without violating the principle of causality [12].

7 Acknowledgments

I gratefully acknowledge discussions with A. Haibel, A. Stahlhofen, and R.-M. Vetter.

References

- [1] A. Enders and G. Nimtz, J. Phys. I France 2, 1693 (1992)
- [2] A. Sommerfeld, Vorlesungen über Theoretische Physik, Band IV, Optik Dieterchsche Verlagsbuchhandlung (1950)
- [3] R. P. Feynman, Lectures on Physics II, 33–12, Addison–Wesley (1970)
- [4] G. Nimtz and W. Heitmann, Prog. Quantum Electronics 21, 81 (1997)
- [5] R. Chiao and A. Steinberg, Progress in Optics XXXVII, 345 (1997)
- [6] A. Papoulis, The Fourier Integral And Its Applications, McGraw-Hill, New York (1962), Secs. 7.5 and 7.6
- [7] The IEEE Standard Dictionary of Electrical and Electronics Terms, IEEE Std 100-1996
- [8] NTIA 2000, National telecommunication and information Administration (USA), American National Standard of Telecommunication Terms.
- [9] Th. Hartman, J. Appl. Phys. 33, 3427 (1962)
 A. Enders and G. Nimtz, Phys. Rev. E 48, 632 (1994)
- [10] S. Collins, D. Lowe and J. Barker, J. Phys. C 20, 6213 (1987)
- [11] G. Nimtz, Eur. Phys. J., B. 7, 523 (1999)
- [12] G. Nimtz and A. Haibel, Ann. Phys. (Leipzig) **11**, 163 (2002)
- [13] C. E. Shannon, Bell Sys. Tech. J. 27, 379, and 623 (1948)
- [14] R.-M. Vetter, A. Haibel and G. Nimtz, arXiv. physics/0103073 (23 Aug 2001)
- [15] O. Bryngdahl, Progress in Optics **11**, 167 (1973)
- [16] G. Nimtz, General Relativity and Gravitation, **31**, 737 (1999)
 G. Nimtz, Ann. Phys. (Leipzig) **7**, 618 (1998)
- [17] C. K. Carniglia and L. Mandel, Phys. Rev. D 3, 280 (1971)
- [18] V. Olkhovsky and E. Recami, Phys. Rep. **214**, 339 [1992)
- [19] A. Enders and G. Nimtz, Phys. Rev. E 48, 632 (1994)

- [20] S. Longhi, P. Laporta, M. Belmonte, and E. Recami, arXiv:physics/0201013 v1 9 Jan 2002
- [21] A. A. Stahlhofen, Phys. Rev. A 62, 12112 (2000)
- [22] A. Haibel, G. Nimtz, and A. A. Stahlhofen, Phys. Rev. E 63, 047601 (2001)
- [23] J. J. Hupert, Appl. Phys. 6, 131 (1975)
- [24] L. Brillouin, Wave propagation and group velocity, Academic Press New York (1960)
- [25] J. A. Stratton, Electromagnetic Theory, McGraw-Hill Book Company, Inc. New York and London (1941)
- [26] A. Steinberg, P. Kwiat, R. Chiao, Phys. Rev. Lett. 68, 2421 (1992)
- [27] E. Desurvivre, Scientific American **266** January, 96 (1992)
- [28] H. D. Lüke, IEEE Commun. Magazine, April 1999, p. 106-108
- [29] berkeley physics course, Vol.3, waves, chap.6, McGraw-Hill Book Company, Inc. New York and London (1968)
- [30] F. Low, Annalen der Physik (Leipzig), 7, 660 [1998)
- [31] A. Haibel and G. Nimtz, Ann. Phys. (Leipzig), 10, 707(2001)
- [32] S. Esposito, Phys. Rev. E **64**, 026609 (2001)
- [33] F. E. Low and P. F. Mende, Ann. Phys. NY **210**, 380 (1991)
- [34] S. K. Sekatskii and V. S. Letokhov, Phys. Rev. B 64, 233311 (2001)
- [35] S. Longhi, M. Marano, P. Laporta, and M. Belmonte, Phys. Rev. E 64, 055602 (2001)
- [36] R.-M. Vetter, design of tunneling barriers, Dissertation 2002, University of Cologne, Physics Department.
- [37] C. R. Leavens and G. C. Aers, Phys. Rev. B 40, 5387 (1989);
 C. R. Leavens and W. R. McKinnon, Phys. Lett. A 194, 12 (1994)
- [38] L. Wang, A. Kuzmich and A. Dogariu, Nature, 406, 277 (2000)
- [39] A. Steinberg, P. Kwiat, and R. Chiao, Phys. Rev. Lett. **71**, 708 (1993)
- [40] S. Gasiorowicz, Quantum Physics, Second Edition, John Wiley & Sons, New York (1996)