

Comment on „Microscopic modeling of multi-lane highway traffic flow“, Nathan O. Hodas and Arnand Jagota, Am. J. Phys. 71 (12) 2003, pp. 1247

M. Risch, University of Applied Sciences, Augsburg, Germany

In heavy traffic with congested roadway the maximum traffic flow (road capacity) also depends on length of cars (minimum clearances). This is deduced in a simple derivation suited for classroom demonstration as well as homework. The resulting equation demonstrates a new relation to an apparently unrelated area of physics, the maximum ship velocity (hull speed) and explains why traffic is sometimes faster on the slow (right) lane on a congested multi-lane road.

Capacity of a road is determined by car velocity and distance between cars, besides other influences. Maximum capacity occurs at a specific speed, it usually is attained by self-regulating on a congested road. This equilibrium velocity can be derived using simplifying assumptions by derivation of an equation.

In a congested roadway capacity q of the road is determined by velocity v and following distance s of cars; v and s depend on each other. Following distance s of cars is a fixed fraction of the way to stop the car, typically 50% to 100 %^{1,2}. For sake of simplicity this fraction is set here to 1 (100%) without affecting essentials of results. Then s becomes sum of breaking distance and distance driven during reaction time t_h ,

$$s = \frac{v^2}{2g} + v \cdot t_h$$

It is assumed that maximum break acceleration is gravity g (friction coefficient μ times gravity, μ having a maximum of 1, stronger breaking would lock wheels^{3,4}). Calculation of the fraction of road length consumed by the car L/N requires to add the cars length l summing to

$$\frac{L}{N} = \frac{v^2}{2g} + v \cdot t_h + l$$

This neglects influences of slope and curvature of roads which practically often limit capacity⁵. Capacity of a road q_{max} is maximum traffic flow q equaling number of cars

past a region of a lane in time t

$$q = \frac{v}{L/N} = \frac{2g \cdot v}{v^2 + 2g \cdot v \cdot t_h + 2g \cdot l}$$

This function q demonstrates following dependencies:

- a) At v and l constant q continuously decreases with t_h
- b) At v and t_h constant q continuously decreases with l
- c) At t_h and l constant q has a maximum at v_{\max} resulting in a q_{\max}

For example:

At $l=5\text{m}$ and $t_h = 1\text{s}$ v_{\max} is $10 \text{ m/s} = 36 \text{ km/h} = 22\text{mi/h}$ and maximum traffic flow q_{\max} is 1700 cars/h/lane in agreement with observations^{1 2 5}.

q_{\max} occurring at v_{\max} is usually attained by self-regulating on a congested road^{2 3 4}.

q_{\max} is determined by the derivative of function $q(v)$:

$$q' = \frac{dq}{dv} = 2g \cdot \frac{2g \cdot l - v^2}{(v^2 + 2g \cdot v \cdot t_h + 2g \cdot l)^2}$$

Maximum traffic flow q_{\max} is attained when

$$2g \cdot l - v^2 = 0$$

yielding to a square root function

$$v_{\max} = \sqrt{2g \cdot l} \quad (1)$$

Examples: car $l = 5\text{m}$ $v_{\max} = 10 \text{ m/s} = 36 \text{ km/h}$, Truck $l = 15 \text{ m}$ $v_{\max} = 17 \text{ m/s} = 60 \text{ km/h}$

In traffic on a congested road, the slow (right) lane usually has trucks with longer l resulting in faster equilibrium speeds first, which will eventually even out by drivers choosing to change lanes.

Result (1) most curiously demonstrates a new relation to an apparently unrelated area of physics, the maximum ship velocity v_{mahu} (hull speed) of a ship displacing water and floating in deep water (deeper than ship length l) which is due to water wave Dispersion and resonance

$$v_{\text{mahull}} = \sqrt{g \cdot l / 2\pi} \quad \text{provided} \quad l < H \text{ (Water- depth)}$$

This new relation to an apparently unrelated area of physics might show students physics can be of great simplicity.

¹ D. Helbig and B. Tilch, „Generalised force model of traffic dynamics“, Phys. Rev. E 58 (1998) pp. 133-138

² D. Helbig, „Traffic and related self-driven many-particle systems“, Rev. Mod. Phys. 73(4), (2001) pp. 1067-1141

³ W. G. Unruh, „Instability in automobile braking“, Am. J. Phys. 52 (10) 1984, pp. 903-909

⁴ M. Risch, „Der *Kamm*´sche Kreis - Wie stark kann man beim Kurvenfahren Bremsen?“, (*Kamms´ Circle: How much can you break in a curve*), Praxis der Naturwissenschaften - Physik in der Schule, 51 (2002), No. 5, pp 7-15, editor: Aulis Deubner, [Translation can be obtained from author]

⁵ Organisation of Economic Co-operation and Development, *Traffic Capacity of major Routes* , 1983

⁶ Nathan O. Hodas and Arnand Jagota, „Microscopic modeling of multi-lane highway traffic flow“, Am. J. Phys. 71 (12) 2003, pp. 1247-1256

⁷ H. D. Keith, „Simplified Theory of Ship Waves“, Am. J. Physics 25, 466, 1957

email mrrisch@rz.fh-augsburg.de