Atomic vapor-based high efficiency optical detectors with photon number resolution

Daniel F. V. James^{*}

Theoretical Division T-4, University of California, Los Alamos National Laboratory, MS B-283, P.O. Box 1663, Los Alamos, NM 87545

Paul G. Kwiat[†]

Dept. of Physics, University of Illinois at Urbana-Champaign, Urbana IL 61801-3080

(Dated: June 7, 2002)

We propose a novel approach to the important fundamental problem of detecting weak optical fields at the few photon level. The ability to detect with high efficiency (> 99%), and to distinguish the number of photons in a given time interval is a very challenging technical problem with enormous potential pay-offs in quantum communications and information processing. Our proposal diverges from standard solid-state photo-detector technology by employing an atomic vapor as the active medium, prepared in a specific quantum state using laser radiation. The absorption of a photon will be aided by a dressing laser, and the presence or absence of an excited atom will be detected using the "cycling transition" approach perfected for ion traps. By first incorporating an appropriate upconversion scheme, our method can be applied to a wide variety of optical wavelengths.

PACS numbers: 42.50.-p, 32.80.-t, 85.60.Gz

Since its introduction more than 100 years ago [1], the notion of light quanta has remained an elusive and misunderstood concept [2]. The ability to detect individual quanta of radiation is of central importance to fundamental physics. A direct example of the ramifications of photon detector efficiencies are the tests of violations of Bell's inequalities [3], which reveal the non-local nature of quantum mechanics. By rapidly and randomly measuring the correlations of space-like separated particles, one can rule out all theories invoking a local realistic view of nature. In order for such a test to be indisputable, however, the detection efficiencies must be very high [4], and to date this has not been achieved in any optical experiment, though an experiment with rapid, random switching has been performed [5]. Recently, however, this "detector loophole" was closed in an elegant experiment using entangled ions [6] (though unfortunately the ions were so close together that the "locality loophole" ruled out any unambiguous test of non-locality). The cold trapped ions were detected with near 100% efficiency by the technique of light scattering via a "cycling" atomic transition; in brief, each ion is made to emit a large number of photons, which are then easily detected.

The importance of high efficiency photon detectors is not confined to fundamental physics. In addition to the obvious relevance for metrology, recently there have been a number of proposals for realizing scalable quantum computing using only linear optics [7]. A key ingredient for these proposals is very high efficiency photoncounting detectors (> 99% [8]). In addition, it is crucial that the detectors be able to distinguish the *number* of incident photons (e.g., tell the difference between 1 and 2 photons, or more generally, between n and n + 1). It has also been noted that such detectors would enable the preparation of novel quantum states of light, e.g., manyphoton entangled states [9], which could be of great utility in other quantum information schemes, such as quantum lithography [10]. Finally, there are other applications, such as telecom fiber-based quantum cryptography, where the low efficiencies and noise levels of current detectors significantly limit the achievable distances [11].

Most modern photon detectors rely to a greater or lesser extent on the photoelectric effect: incident photons are converted to individual photo-electrons, either ionized into vacuum or excited into the conduction band of some semi-conductor. Either way, one is relying on the capability of amplifying single electrons up to detectable levels of current in order to produce a tangible signal [12]. For example, the silicon avalanche photodiodes used in many photon counting experiment typically have efficiencies $\eta \approx 75\%$ [13]. A number of experiments have used a variation of this technology, in which the silicon is lightly doped. These "visible-light photon counters" have displayed $\eta \approx 88\%$, and predicted to be as high as 95% [13, 14]. Moreover, they have demonstrated the ability to distinguish the number of initial photo-electrons produced (which for $\eta \approx 100\%$ is the same as the number of incident photons). Unfortunately, these devices require cooling to 6K, and display very high dark count rates (up to $50,000 \text{ s}^{-1}$), undesirable for quantum communication.

We propose a new approach to the problem: instead of converting each photon to a single photo-electron, we propose a compound process by which a single photon can be converted into many photons. The basis of our proposal is to combine two successful experimental approaches of the last few years: the unprecedented ability to coherently slow and stop light [15], and the high efficiency scheme for projective quantum state measurements in ion traps mentioned above [6].

Our scheme consists of a cell containing the vapor of some atomic species, e.g., an alkali such as cesium (Fig. 1). This vapor will be used to coherently absorb the ra-



FIG. 1: a). Diagram illustrating schematically the proposed photo-detection technique. The polarizing beam splitter (PBS) dictates the polarizations of the applied optical fields, as assumed in deriving the Hamiltonian eq.(1).

diation from an incident beam in a controlled fashion. A number of auxiliary lasers prepare the initial quantum state of the atoms in the vapor, and control the interaction of the atoms with the radiation field. The radiation to be detected is directed into the cell along with an "escort" pulse, giving each photon some small probability to excite an atom to a metastable state – because there are many atoms, however, the chance that each photon is absorbed by one of them can be near unity. Next a strong read-out light is applied, which repeatedly excites any atom in the metastable state; the photons resulting from spontaneous decay may then be detected. And because there are many photons, the chance of not detecting any at all becomes vanishingly small for realistic detector efficiencies. In fact, if an imaging photon detection scheme is used, the number of excited atoms may even be counted, thereby allowing one to reliably distinguish input states of different photon number.

Four atomic levels will concern us; $|1\rangle$ and $|2\rangle$ are the two sub-levels of the ${}^{2}S_{1/2}$ ground state (for simplicity we will neglect hyperfine structure). The level $|3\rangle$ is the ${}^{2}P_{1/2}, m_{J} = -1/2$ sublevel, and $|4\rangle$ is the ${}^{2}P_{3/2}, m_{J} =$ 3/2 sublevel. The sublevels of the ${}^{2}P_{1/2} \cdot {}^{2}P_{3/2}$ doublet all decay rapidly to the ground state, and thus, provided the gas is at a thermal equilibrium temperature much less than $T \sim 10^{4}K$, initially there will be appreciable population only in the two ground state sublevels $|1\rangle$ and $|2\rangle$ (we will see that for other reasons one wants to first cool the atoms to ~ 1 mK).

The atoms are then prepared in state $|1\rangle$ by optical pumping (Fig.2a). Collisions between atoms will degrade this state preparation by exciting population back into state $|2\rangle$. The time taken for such collisions to occur is $\tau_{col} \approx \sqrt{M/3k_BT}/n\sigma$, with M the atomic mass, k_B Boltzmann's constant, T the temperature, nthe number-density of atoms, and σ the collisional crosssection (~ 10^{-14} cm² for alkalis). Collisions can be mitigated in a number of ways, such as use of buffer gas, decreasing the atomic density, cooling the atoms, using heavier atoms or by raising the energy difference between $|1\rangle$ and $|2\rangle$ (thereby making it less likely that a single collision will impart sufficient energy to induce the transition). The following two operations (i.e., the photon absorption and the readout via a cycling transition) must be accomplished in a time considerably smaller than τ_{col} .



FIG. 2: Diagram illustrating the atomic transitions envisioned for the three-stage photo-detection procedure. Stage (a) is optical pumping to level $|1\rangle$; stage (b) is the absorption of the photon with the assistance of a classical "escort" pulse; stage (c) is the detection of any atom in state $|2\rangle$.

Once the atoms are in state $|1\rangle$, the photon field is directed into the cell, accompanied by a strong "escort" laser pulse. The resulting two-photon Raman excitation to state $|2\rangle$ is described by the following interaction picture Hamiltonian:

$$\hat{H}_{I}(t) = \sum_{i=1}^{N} \frac{\hbar \Omega \left(\mathbf{r}_{i}, t\right)}{2} \left(|3\rangle \langle 2|\right)_{i} \exp\left[i \left(\omega_{32} - \omega_{e}\right) t\right]$$
$$+i\hbar \sum_{i=1}^{N} \sum_{\lambda} g_{\lambda,i} \hat{a}_{\lambda} \left(|3\rangle \langle 1|\right)_{i} \exp\left[i \left(\omega_{31} - \omega_{\lambda}\right) t\right] + h.a. \quad (1)$$

Here $\Omega(\mathbf{r}_i, t) = \langle 3|\hat{\mathbf{d}}|2\rangle \cdot \mathcal{E}_e(\mathbf{r}_i, t)/\hbar$ is the Rabi frequency of the $|2\rangle \leftrightarrow |3\rangle$ transition of the *i*-th atom due to the escort pulse (represented by the analytic signal $\mathcal{E}_e(\mathbf{r}_i, t) \exp(-i\omega_e t)$, with central frequency ω_e). The coefficient $g_{\lambda,i} = \sqrt{\omega_\lambda/2\varepsilon_0\hbar}\Phi_\lambda(\mathbf{r}_i)\langle 3|\hat{d}_z|1\rangle$, where $\Phi_\lambda(\mathbf{r}_i)$ is the spatial mode function for the λ -th mode of the incident field (with annihilation operator \hat{a}_λ and frequency

 ω_{λ}), ε_0 is the permittivity of the vacuum, and $\hat{\mathbf{d}}$ is the dipole moment operator. In writing (1), we assume that the escort and photon fields have negligible effect on the $|1\rangle \leftrightarrow |3\rangle$ transition; this is valid for a particular orientation of static magnetic field and specific polarizations for the escort field and the photon (see Fig. 1).

We assume that both the photon and the escort field are far detuned from resonance with the transitions $|1\rangle \leftrightarrow$ $|3\rangle$ and $|2\rangle \leftrightarrow |3\rangle$, respectively. In these circumstances, we may adiabatically eliminate the population of the upper level $|3\rangle$, and the dynamics of the system may be described to a good approximation by the following effective Hamiltonian [16]:

$$\hat{H}_{eff}(t) = i\hbar \sum_{i=1}^{N} \sum_{\lambda} f_{\lambda,i}(t) \quad \hat{a}^{\dagger}_{\lambda} \quad (|1\rangle\langle 2|)_{i} \exp\left[i\left(\omega_{\lambda} - \omega_{0}\right)t\right] + h.a.$$
(2)

where $f_{\lambda,i}(t) = \Omega(\mathbf{r}_i, t) g_{\lambda,i}^*/2\Delta$, $\omega_0 = \omega_{21} + \omega_e$ and $\Delta = \omega_{31} - \omega_0 \approx \omega_{31} - \omega_{\lambda}$. This is the Hamiltonian describing an effective two-level system interacting with a quantized field; the coupling constant $f_{\lambda,i}$ can be controlled by shaping the profile of the escort pulse.

An important property of this Hamiltonian is that it commutes with the "total excitation" operator $\sum_i (|2\rangle\langle 2|)_i + \sum_\lambda \hat{a}^{\dagger}_{\lambda} \hat{a}_{\lambda}$. As a consequence, the number of quanta of the radiation field plus the number of excited atoms must be a constant. Therefore, once the incident radiation field has been completely absorbed, the number of quanta it contained may be determined by measuring the number of atoms in the excited state. If we confine ourselves to single photon incident fields, the wavefunction will thus have the form

$$|\psi(t)\rangle = \sum_{\lambda} \alpha_{\lambda}(t)|1_{\lambda}\rangle|g\rangle + \sum_{i} \beta_{i}(t)|vac\rangle|2_{i}\rangle, \quad (3)$$

where $|g\rangle$ represents the state in which *all* of the atoms are in state $|1\rangle$; $|2_i\rangle \equiv (|2\rangle)_i |g\rangle$ the state in which all the atoms are in state $|1\rangle$, except the *i*-th atom which is in state $|2\rangle$; $|vac\rangle$ is the field vacuum state; and $|1_\lambda\rangle \equiv \hat{a}^{\dagger}_{\lambda}|vac\rangle$ is the state with one photon in mode λ . The probability amplitudes $\alpha_{\lambda}(t)$ and $\beta_i(t)$ obey the equations

$$\dot{\alpha}_{\lambda}(t) = -\sum_{i} f_{\lambda,i}(t)\beta_{i}(t) \exp\left[i\left(\omega_{\lambda}-\omega_{0}\right)t\right],$$

$$\dot{\beta}_{i}(t) = \sum_{\lambda} f_{\lambda,i}^{*}(t)\alpha_{\lambda}(t) \exp\left[-i\left(\omega_{\lambda}-\omega_{0}\right)t\right]. \quad (4)$$

By formally solving for $\alpha_{\lambda}(t)$, we obtain an integrodifferential equation for $\beta_i(t)$; under the Markov approximation and the assumption that we can neglect coherence between different atoms (so that superradiant effects are negligible), we obtain the following equation for $\beta_i(t)$:

$$\dot{\beta}_i(t) = \epsilon_i(t)\phi_i(t) - \frac{A_{31}}{2} |\epsilon_i(t)|^2 \beta_i(t), \qquad (5)$$

3

where A_{31} is the spontaneous decay rate of the $|3\rangle \rightarrow |1\rangle$ transition, $\epsilon_i(t) = [i\Omega(\mathbf{r}_i, t) \exp(-i\omega_0 t)/2\Delta]^*$ characterizes the influence of the escort pulse and $\phi_i(t) = \langle 3|\hat{d}_z|1\rangle \sum_{\lambda} \sqrt{\omega_{\lambda}/2\hbar\varepsilon_0}\alpha_{\lambda}(0)\Phi_{\lambda}(\mathbf{r}_i)\exp(-i\omega_{\lambda}t)$ characterizes the action of the photon we wish to detect. The first term on the right hand side of Eq.(5) represents the absorption of the photon, the second term re-emission. Equation (5) can be solved in closed form, yielding explicit expressions (dependent on the photonand escort-pulse shapes) for the absorption and scattering probabilities. In what follows, we have employed expressions derived from simple square-shaped pulses for both the photon and the escort pulses (although model dependent factors of order unity have been suppressed).

Once our single photon is absorbed by one of the atoms, we can detect this excited atom with very high probability by employing a third auxiliary laser. This "readout" laser is carefully tuned and polarized so that any population in each atom's excited state is pumped into some convenient upper state $|4\rangle$ (Fig.2c), chosen so that it will rapidly decay spontaneously back to the excited state only [6]. If the readout light persists for some microseconds, the atom in the excited state $|2\rangle$ will scatter many photons. By detecting and imaging the scattered radiation, one can therefore determine which atom is excited. The time taken for one such photon to be registered is $t_{ro} = \left(2\Omega_r^2 + A_{24}^2\right)/A_{24}\Omega_r^2\eta_{det}, \Omega_r$ being the readout laser Rabi frequency, A_{24} the decay rate of the $|4\rangle \rightarrow |2\rangle$ transition, and η_{det} the overall detection efficiency of the imaging system, including solid angle acceptance and photon detector efficiency.

The efficiency of the detector we have described is limited by three effects: the possibility that the photon may be scattered rather than absorbed by the atom, the possibility that the photon may pass through the medium without being absorbed by any atom, and the possibility that the atom which has absorbed the photon may be collisionally de-excited before the readout can take place. Using results derived from eq.(5) we find that the efficiency is given approximately by the formula

$$\eta \approx 1 - \left(\frac{T_p A_{31} \Omega_e^2}{16\Delta^2}\right)^2 - \exp\left[\frac{-q\ell_{cell}}{\ell_{abs}}\right] - \frac{t_{ro}}{2\tau_{col}}.$$
 (6)

Here T_p is the duration of the photon and escort pulses, Ω_e is the (constant) value of the escort pulse Rabi frequency, ℓ_{cell} is the length of the cell, q is the number of passes through the cell made by the photon and escort, and $\ell_{abs} = \Delta^2/(\lambda_{ph}^2 n \Omega_e^2 T_p A_{13})$ is the absorption length of the medium (λ_{ph} being the photon wavelength). If we assume a cesium density of 10^9cm^{-3} , cooled to the Doppler limit of ~ 10^{-3} K (thereby rendering collisional effects negligible [17]), a pulse duration T_p of 10 nsec, a detuning Δ of 0.5 GHz, a strong escort pulse with $\Omega_e = A_{13}$, a cell length $\ell_{cell} = 2$ mm, a beam area $A = 10^{-2} \text{ mm}^2$, q = 100 passes through the cell, and $\eta_{det} = 1/8$, then the theoretical detection efficiency will be $\eta \approx 99.8\%$.

Multiple photons can also be reliably measured by this technique. As long as the total number of incident photons is much less than the total number of atoms participating in the measurement, each photon will be absorbed by a different atom, and the number of fluorescing atoms observed during readout will be equal to the number of photons. Being able to spatially resolve the atoms will assist in counting them (the image of the moving atom emitting photons is somewhat reminiscent of the tracks in a bubble chamber), though even this is not completely necessary, as demonstrated in [6]; as long as the number of emitting atoms in each optically resolvable volume is sufficiently small that the photon statistics of 1, 2, etc. atoms radiating are distinguishable, the total number of atoms in state $|2\rangle$ can be determined. For example, with $\eta \approx 99.8\%$, we could in principle reliably distinguish states with ~ 50 photons.

A serious potential problem in realizing this scheme will be "dark counts". Provided collisional excitation of state $|2\rangle$ can be kept negligible, the principle mechanism by which this can occur is excitation out of $|1\rangle$ by the readout laser. In the example discussed above, the readout laser polarized to address the $|2\rangle \leftrightarrow |4\rangle$ transition can excite population in $|1\rangle$ to the ${}^{2}P_{3/2}, m_{J} = 1/2$ sublevel. Due to the Zeeman splitting, this transition will be detuned by $\delta = 2\mu_B B/3\hbar$ (μ_B being the Bohr magneton and B the magnetic field strength), and due to the different dipole moment strengths, the Rabi frequency will be reduced by a factor of $\sqrt{3}$. The probability of an atom emitting a dark count photon during readout is then $P_{dc} \approx t_{ro} A_{42} \Omega_r^2 / 6 \left(\delta^2 + \Omega_r^2 / 3 \right)$. For a magnetic field B = 1 T and $\Omega_r = 0.01 A_{42}$, $P_{dc} \sim 2 \times 10^{-5}$. The large number of atoms N present in the active medium may make dark counts a non-negligible effect (the above parameters yield N = 20,000, and a net dark count probability of 0.4). Ways to mitigate this problem, e.g., allowing the photon and its escort to pass through the atoms multiple times (thereby allowing a reduction in the number of atoms without a detrimental effect on the detection efficiency), or reducing the area of the optical beams, are a subject of on-going investigation.

It may be argued that a detector of this sort is of limited value because it operates only for a single frequency, and not, e.g., at the telecommunications wavelength of 1550 nm. If indeed we start out with a photon with a different wavelength (but still assumed to be of narrow bandwidth), we estimate that by first mixing the photon with a strong pulse of an appropriate frequency in a nonlinear optical crystal, we can have a near-unity probability of upconverting the photon to the frequency needed for our detection scheme. In this way the high efficiency detection method proposed above may be used over much of the optical spectrum. Note: While finishing our manuscript, it came to our attention that a similar proposal was suggested independently and essentially simultaneously by A. Imamoglu (http://xxx.lanl.gov/abs/quant-ph/0205196).

Acknowledgement: We acknowledge helpful discussions with B. Englert, P. Milonni, K. Molmer, E. Timmermans, and A. VanDevender. Note: This work was supported in part by funds from the Advanced Research and Development Activity and the Los Alamos QUEST initiative.

- * Electronic address: dfvj@t4.lanl.gov
- [†] Electronic address: kwiat@uiuc.edu
- [1] M. Planck, Ann. d. Physik (4) 4, 553 (1901).
- [2] For example, late in his life Albert Einstein remarked "All the fifty years of conscious brooding have brought me no closer to the answer to the question, 'What are light quanta?' Of course today every rascal thinks he knows the answer, but he is deluding himself." (Quoted in E. Wolf, "Einstein's Researches on the Nature of Light", *Optics News* 5, 24-39 (1979).)
- [3] J. F. Clauser, and A. Shimony, Rep. Prog. Phys. 41, 1883 (1978).
- [4] P. G. Kwiat, P. H. Eberhard, A. M. Steinberg and R. Y. Chiao, Phys. Rev. A 49, 3209 (1994).
- [5] G. Weihs, T. Jennewein, C. Simon, H. Weinfurter, and A. Zeilinger, Phys. Rev. Lett. 81, 5039 (1998).
- [6] M. A. Rowe, et al., Nature **409**, 791 (2001).
- [7] E. Knill, R. Laflamme, and G. Milburn, Nature 409, 46 (2001); D. Gottesman, A. Kitaev, and J. Preskill, Phys.Rev. A 64, 012310 (2001).
- S. Glancy, J. M. LoSecco, H. M. Vasconcelos and C. E. Tanner, quant-ph/0201047; S. D. Bartlett, E. Diamanti, B. C. Sanders, and Y. Yamamoto, quant-ph/0204073.
- [9] P. Kok and S. L. Braunstein, Phys. Rev. A 63, 033812 (2001); H. Lee, P. Kok, N. J. Cerf, and J. P. Dowling, Phys. Rev. A 65, 030101(R) (2002).
- [10] A. N. Boto et al., Phys. Rev. Lett. 85, 2733 (2000).
- [11] See, e.g., N. Gisin, G. Ribordy, W. Tittel, and H. Zbinden, Rev. Mod. Phys. 74, 145 (2002).
- [12] There has been recent progress in the use of superconducting single-photon detectors [G. N. Gol'tsman, et al., Appl. Phys. Lett. **79**, 705 (2001)]; however, $\eta \sim 20\%$.
- [13] P. G. Kwiat, A. M. Steinberg, R. Y. Chiao, P. H. Eberhard and M. D. Petroff, Phys. Rev. A 48, R867 (1993)
- [14] J. Kim, S. Takeuchi, Y. Yamamoto, and H. H. Hogue, Appl. Phys. Lett. **74**, 902 (1999); S. Takeuchi, J. Kim, Y. Yamamoto, and H. Hogue, *ibid.* **74**, 1063 (1999).
- [15] C. Liu, Z. Dutton, C. H. Behroozi, and L. V. Hau, Nature
 409, 490 (2001); D. F. Phillips, A. Fleischhauer, A. Mair,
 R. L. Walsworth, and M. D. Lukin, Phys. Rev. Lett. 86, 783 (2001).
- [16] We have neglected A.C. Stark shifts and the Lamb shift both may be compensated for by altering the appropriate polarization mode or laser detuning.
- [17] Low temperatures also ensure that atoms will not move appreciably during the measurement; the RMS velocity multiplied by the readout time t_{ro} will be 0.3 mm.