arXiv:quant-ph/0303107v2 15 Aug 2003 [arXiv:quant-ph/0303107v2 15 Aug 2003](http://arxiv.org/abs/quant-ph/0303107v2)

Quantum Bit Commitment Using Entangled States

Guang-Ping He

Advanced Research Center, Zhongshan University, Guangzhou 510275, China

Abstract

Based on the fact that the entanglement can not be created locally, we proposed a quantum bit commitment protocol, in which entangled states and quantum algorithms is used. The bit is not encoded with the form of the quantum states, and delaying the measurement is required. Therefore the protocol will not be denied by the Mayers-Lo-Chau no-go theorem, and unconditional security is achieved.

Typeset using REVTEX

Started from the original idea of Wiesner [1], quantum cryptography is playing an essential role in nowadays research on quantum information. Besides the well-known quantum key distribution protocol $[2-4]$, another crucial primitive in quantum cryptography is quantum bit commitment (QBC). As shown by Yao [5], a secure QBC scheme can be used to implement a secure quantum oblivious transfer scheme [6,7]. And Kilian [8] has shown that, in classical cryptography, oblivious transfer can be used to implement two-party secure computations [9]. Many other cryptographies, such as quantum coin tossing $[2,10-12]$ and quantum oblivious mutual identification [13], can also be constructed over QBC. All these cryptographies are very useful in the so-called "post-cold-war era", with a wide range of economic, financial and even military applications. In classical cryptography, these tasks can only be done through trusted intermediaries. Otherwise some unproven computational assumptions must be invoked, such as the hardness of factoring, which can easily be broken when quantum computer becomes practical [14]. Therefore people hope that quantum cryptography can get rid of those requirements, and the same goals can be achieved using the laws of physics alone. However, Mayers, Lo and Chau have claimed that unconditionally secure QBC scheme can never be achieved in principle [15,16], and all the protocols formerly purposed [5,17] are insecure. By delaying the measurement on quantum states, the participants can always succeed in cheating with Einstein-Podolsky-Rosen(EPR)-type of attacks, or the so-called Mayers attacks. This discovery is called the Mayers-Lo-Chau no-go theorem or MLC theorem. During the past half decade, attempts on fixing the problem with classical BC protocols (such as the classical computational BC scheme [18,19] or the two-prover BC scheme [20]) are also proven to be failed later [21,22]. Some protocols have to rely on relativity assumptions [23] or reduce to conditionally secure [24]. The failure of QBC seems to bring a fatal limitation to the power of quantum cryptography.

But in this paper, we will propose a new QBC protocol which can not be denied by the MLC theorem. EPR attacks will no longer succeed and unconditional security can be achieved.

A bit commitment scheme between two parties (Alice and Bob) generally includes two phases. In the commit phase, Alice has in mind a bit $(b = 0 \text{ or } 1)$ which she wants to commit to Bob. So she sends him a piece of evidence. Later, in the unveil phase, Alice announces the value of b, and Bob checks it with the evidence. A protocol is said to be binding if Alice cannot change the value of b after the commit phase, and is said to be concealing if Bob cannot tell what b is before the unveil phase. A secure protocol needs to be both binding and concealing.

The argument of the MLC theorem is based on the Yao's general model of QBC [5]. According to this model, previously proposed protocols that proven to be insecure are all starting with the following steps: Alice prepares a state $|0\rangle = \sum$ j $\sqrt{\lambda_j} |\alpha_j\rangle \otimes |\beta_j\rangle$ if $b = 0$ or $|1\rangle = \sum$ j $\sqrt{\lambda_j} \left| \alpha_j \right|$ $\langle \phi_j \rangle \otimes \langle \beta_j \rangle$ if $b = 1$, and sends the second register to Bob. Then Alice is supposed to carry out measurement on the first register to make it collapse to $|\alpha_k\rangle$ or $|\alpha'_{l}$ $\langle k \rangle$ according to the value of b. And Bob measures the second register to verify Alice's commitment. But in these protocols, the entanglement inside the quantum states is not fully utilized. Any classical information that the participants need to announce during the commit phase required by the protocol can all be calculated without the help of the entanglement. That is, the calculation involved is not thoroughly a quantum algorithm.

The value of b in fact depends only on the form of the first register, and not the form of the entire entangled state. As we know, entangled quantum states have the power to carry out parallel computations, which is much more powerful than classical algorithm. Therefore it is not surprise to see that by making full use of the entangled states, Alice can execute the protocol successfully even she delays her measurement, just as if she is executing the commitment with $b = 0$ and $b = 1$ simultaneously. Then in the unveil phase, she can apply local transformation on the first register to map the state between $|0\rangle$ and $|1\rangle$. This is the reason why Alice can cheat in these protocols [15,16,25].

So we can see that, to propose a secure QBC protocol that can stand this so-called Mayers attack, we must make full use of the computation power of the entangled states. The effect of the entanglement must be taken into consideration throughout the commitment, thus quantum algorithms must be involved. So the outline of our new protocol goes as: In the commit phase, Alice and Bob first share some certain entangled states which can solve a certain problem with quantum algorithm; Then Alice shows Bob that she has indeed solved the problem. Solving the problem should be able to force Alice to measure a minimum set of states even with the most efficient quantum algorithm, while the other states can be left unmeasured. Then we correlate the commit bit b with the states according to whether the states is measured or not. In the unveil phase, Alice should show Bob that there is a certain number of states which are indeed unmeasured. A state which is already measured and collapsed can not be used to fake a state which is still entangled with another state. Therefore the security of the commitment can be guaranteed.

For concreteness, in the following we shall use four quantum states of photon with different polarizations in the description. But in fact the protocol can be constructed on any other type of nonorthogonal states as well. Here we denote the four states of light polarization of angles 0° , 45° , 90° and 135° as $|0,0\rangle$, $|1,0\rangle$, $|0,1\rangle$ and $|1,1\rangle$ respectively. We will also consider the ideal setting only, where the quantum communication channel is supposed to be error-free. Before we get to the protocol, let us first consider the following problem:

Problem P:

Alice and Bob execute the following procedure:

(1) Alice sends Bob a series of photons $\{\beta_i | i \in S\}$ where $S \equiv \{1, ..., s\}$ is a set of natural numbers;

(2) $\overline{DO}_{i=1}^s$ Bob randomly picks a bit p'_i \mathcal{G}_i and measures β_i in the rectilinear basis (0° and 90°) polarized) if $p'_i = 0$, or the diagonal basis (45[°] and 135[°] polarized) if $p'_i = 1$. The outcome is denoted as $|p'_i\rangle$ $\langle q'_i\rangle_\beta;$

(3) Bob announces to Alice a series of "fake" results $\{|p''_i\rangle\}$ $\langle i', q_i'' \rangle_{\beta} | i \in S \},$ which needs not to be agreed with $\{|p'_i\>$ $\langle i, q'_i \rangle_{\beta} | i \in S \}$. He can choose to apply three types of lies:

lie a:
$$
p''_i = p'_i \wedge q''_i = \neg q'_i;
$$

lie b: $p''_i = \neg p'_i \wedge q''_i = q'_i;$
lie c: $p''_i = \neg p'_i \wedge q''_i = \neg q'_i.$

Let $L_a = \{i \in S | \underline{p''_i}$ $\langle g''_i, q''_i \rangle_{\beta} = |p'_i\rangle$ $q_i', \lceil q_i'$ $\{i\}_\beta\},\ L_b = \{i \in S \mid |p''_i\rangle\}$ $\langle g''_i, q''_i \rangle_{\beta} = |\gamma_{p'_i}|$ $\langle q'_i \rangle_{\beta}$, and $L_c =$ ${i \in S}$ | ${p''_i}$ $\left\langle \vec{q},q''_i\right\rangle _{\beta}=\lvert \lceil p'_i\rangle$ \overline{q}'_i $\langle i \rangle_{\beta}$, with $f_a = |L_a|/s$, $f_b = |L_b|/s$ and $f_c = |L_c|/s$ denoting the frequencies of Bob applying each type of lies. Suppose that $0 < f_a$, f_b , $f_c < 1/4$ and $f_b > f_c$.

Now the question is: how can Alice detects a set of lies D such that $D \subset L_a \cup L_b \cup L_c$ and $|D| \sim (f_a/2 + f_b/4 + f_c/4)s$?

This problem can easily be solved by the following "semi-classical" method. Alice can determine the states of all the s photons beforehand, i.e. in step (1) she prepares every photon β_i in a pure state $|p_i, q_i \rangle_\beta$ non-entangled with any other systems. Then she sets $D = \{ i \in S | | p''_i \}$ $\langle q''_i, q''_i \rangle_{\beta} = |p_i, \overline{\alpha q_i \rangle_{\beta}}$ after Bob announces $\{|p''_i\rangle\}$ $\langle i', q_i'' \rangle_{\beta} | i \in S \}$ in step (3). Now let us evaluate the size of this set \overline{D} . Since p'_i i_i is randomly chosen by Bob, for half of the states Bob will by chance choose the correct basis $p'_i = p_i$. Among this half, whenever Bob applies a lie a, it will be detected by Alice since she knows that Bob can never find q_i as q_i in his measurement once he uses the correct basis. But no *lie b* and *lie c* will be detected, since when Bob announces $p''_i = p'_i = p_i$, Alice does not know what the result should be when $|p_i,q_i\rangle_\beta$ is measured in the wrong basis p''_i i' . Meanwhile for the other half of states that Bob has measured with the wrong basis $p'_i = p_i$, the probabilities of finding $q'_i = q_i$ and $q'_i = q_i$ are both 1/2. Therefore when Bob applies lie b or lie c, $p_i'' = p_i'$ becomes the correct basis. The probability for such a state to satisfy $|p''_i\rangle$ $\langle g' \rangle_{\beta} = |p_i, \exists q_i \rangle_{\beta}$ is then 1/2. But no lie a will be detected in this case since $p_i'' = p_i'$ i_i is the wrong basis now. So we can see that, the number of lies that Alice totally detects is $|D| \sim (f_a/2 + f_b/4 + f_c/4)s$. That is, such a set D is just what is required by the problem.

But with full quantum algorithms we can solve the problem more efficiently. Alice can prepare every photon β_i as a mixture entangled with another system α_i . For example, in step (1) she can prepare the state of the whole incremental system as $|\psi_i\rangle = |\alpha_i \otimes \beta_i\rangle =$ $\cos\theta_i|x\rangle_\alpha \otimes |0, q_i\rangle_\beta + \sin\theta_i |y\rangle_\alpha \otimes |1, q_i\rangle_\beta$, where $|x\rangle_\alpha$ and $|y\rangle_\alpha$ are orthogonal to each other, $q_i \in \{0,1\}$ and $\theta_i \in (0,\pi/2)$. She sends β_i to Bob, and after step (3) she divides S into two subsets: $M = \{i \in S | q''_i = q_i\}$ and $U = \{i \in S | q''_i = q_i\}$. Due to the specific form of $|\psi_i\rangle$, Bob is more likely to find β_i as q_i than q_i no matter which basis he uses. Therefore when Alice finds Bob announcing $q''_i = q_i$, she knows that he is more likely to be lying. So for the states whose indices are included in U , she can just leave them unmeasured. And for $\forall i \in M$, She measures α_i in the basis $(|x\rangle_\alpha, |y\rangle_\alpha)$. She sets $p_i = 0$ if she finds $|x\rangle_\alpha$ or $p_i = 1$ if she finds $|y\rangle_{\alpha}$. Then she sets $D = \{i \in M | p_i = p''_i\}$ $'$ }. Detailed analyses can prove that both $D \subset L_a \cup L_b \cup L_c$ and $|D| \sim (f_a/2 + f_b/4 + f_c/4)s$ are automatically satisfied. Calculations also show that $|M| \sim [1/4 + (f_a + f_c)/2] s$ when Bob chooses p'_i i randomly. Thus we see that Alice can detect D by measuring only $[1/4 + (f_a + f_c)/2]$ s states. In the "semi-classical" method described above, Alice's action in step (1) is equivalent to preparing the states in an entangled form as well at first, but then measures all the s entangled states $|\psi_i\rangle$ to make β_i collapse into non-entangled pure states before Bob measure them. So we can see now with the full use of the computational power of the entangled states, Alice manages to measure less states than the "semi-classical" method while the same goal is achieved.

This quantum algorithm is already the most efficient one. One can verify that preparing $|\psi_i\rangle$ in other forms will have to measure more states when detecting D. For example, if Alice prepares $|\psi_i\rangle = |\alpha_i \otimes \beta_i\rangle = \cos \theta_i |x\rangle_\alpha \otimes |0,0\rangle_\beta + \sin \theta_i |y\rangle_\alpha \otimes |0,1\rangle_\beta$ and always measures α_i in the basis which can force β_i to collapse to p''_i i' , she will need to measure $s/2$ states to detect D. Or if she prepares $|\psi_i\rangle = |\alpha_i \otimes \beta_i\rangle = \cos \theta_i |x\rangle_\alpha \otimes |0,0\rangle_\beta + \sin \theta_i |y\rangle_\alpha \otimes |1,1\rangle_\beta$ and always measures those that satisfy $|p''_i\rangle$ $\left\langle \!\!{\,}^{\prime\prime}_{i},q''_{i}\right\rangle_{\beta} \,=\,\left\vert 0,1\right\rangle_{\beta}\vee\left\vert \!\!{\,}^{\prime\prime}_{i}\right\rangle_{\beta}$ $\langle i', q_i'' \rangle_{\beta} = |1, 0 \rangle_{\beta}$, she will need to measure $[1/4 + (f_a + f_b)/2]$ s states. All these numbers are larger than $[1/4 + (f_a + f_c)/2]$ s given f_a , f_b , f_c < 1/4 and $f_b > f_c$.

So if we build a protocol in which Alice is required to solve *Problem P* while only $[1/4 + (f_a + f_c)/2]$ s states are allowed to be measured, she has to follow the above quantum algorithm honestly. Now let us give a parameter c_i^0 ⁰ to each state $|\psi_i\rangle$ ($i \in S - D$), and set $c_i^0 = 0$ if $i \in U$ which means α_i is unmeasured by Alice, or $c_i^0 = 1$ if $i \in M - D$ which means α_i is already measured by Alice. Thus after solving *Problem P*, a string $c^0 = (c_1^0 c_2^0 ... c_n^0)$ $(n \equiv |S - D|)$ is created. Then we can adopt the codeword method in BCJL QBC protocol [17], encoding a codeword with c^0 to make it oriented to the commit bit b. So the entire description of our QBC protocol is:

The commit protocol: $(commit(b))$

(C1) Alice and Bob first agree on a security parameter s, then $\bigoplus_{i=1}^{s}$ Alice picks $\theta_i \in$ $(0, \pi/2)$ (θ_i needs not to be different for different i. For example, one can fix $\theta_i = \pi/4$ throughout the whole protocol) and randomly picks $q_i \in \{0, 1\}$, and prepares an entangled state $|\psi_i\rangle = |\alpha_i \otimes \beta_i\rangle = \cos \theta_i |x\rangle_\alpha \otimes |0, q_i\rangle_\beta + \sin \theta_i |y\rangle_\alpha \otimes |1, q_i\rangle_\beta$. Then she sends β_i to Bob and stores α_i ;

(C2) Bob chooses a number s' $(0 \le s' \le s)$ and randomly divides $S \equiv \{1, ..., s\}$ into two subsets S' and S'' such that $|S'| = s'$, $S'' = S - S'$. Then for $\forall i \in S'$ Bob stores β_i unmeasured. And for $\forall i \in S''$ Bob randomly picks a basis p'_i i_i and measures β_i . The outcome is denoted as $|p'_i\rangle$ $\langle q'_i \rangle_{\beta};$

(C3) Bob chooses f_a , f_b , f_c (0 < f_a , f_b , f_c < 1/4 and $f_b > f_c$) and announces to Alice the "fake" results $\{|p''_i\rangle\}$ $\langle f', q''_i \rangle_{\beta} | i \in S \}$ such that $f_a = (|L_a| + s'/4)/s$, $f_b = (|L_b| + s'/4)/s$ and $f_c = (|L_c| + s'/4)/s$, where $L_a = \{i \in S''| |p''_i$ $\langle g''_i, q''_i \rangle_{\beta} = |p'_i\rangle$ $q_i', \exists q_i'$ $\{i\}_\beta\},\ L_b=\{i\in S''|\ |p''_i\|$ $\langle g''_i, q''_i \rangle_{\beta} =$ $\Box p'_i$ $\langle i, q'_i \rangle_{\beta}$, and $L_c = \{i \in S'' | |p''_i$ $\langle g_i'', q_i''\rangle_{\beta} = |\exists p_i'$ $\overline{q}'_i, \overline{q}'_i$ $\langle \rangle_{\beta}\};$

(C4) Alice divides S into two subsets: $M = \{i \in S | q''_i = q_i \}$ and $U = \{i \in S | q''_i = q_i \}.$ For $\forall i \in M$, She measures α_i in the basis $(|x\rangle_\alpha, |y\rangle_\alpha)$. She sets $p_i = 0$ if she finds $|x\rangle_\alpha$ or $p_i = 1$ if she finds $|y\rangle_\alpha$. Then she sets $D = \{i \in M | p_i = p''_i\}$ i' } announces it to Bob;

(C5) Bob sets $D_{s'} = D \cap S'$. Then he measures β_i ($\forall i \in D_{s'}$) in the basis $p'_i = p''_i$ i and denotes the outcome as $|p'_i\rangle$ $\langle i, q'_i \rangle_{\beta}$. He agrees to continue only if $\{i \in D_{s'} | |p'_i\}$ $\langle q'_i \rangle_{\beta} =$ $|p_i''$ $\langle f'_{i}, q''_{i} \rangle_{\beta}$ = ϕ , $D \subset L_a \cup L_b \cup L_c \cup S'$ and $|D| \sim (f_a/2 + f_b/4 + f_c/4)s;$

 $(C6)$ Alice sets $c_i^0 = 0$ if $i \in U$ or $c_i^0 = 1$ if $i \in M - D$. Thus she obtains a binary string $c^0 = (c_1^0 c_2^0 ... c_n^0)$ $(n \equiv |S - D|);$

 $(C7)$ Alice and Bob execute the BCJL protocol [17] by using $c⁰$ to encode the codeword $(c⁰$ itself is not announced to Bob). That is:

 $(C7.1)$ Bob chooses a Boolean matrix G as the generating matrix of a binary linear (n, k, d) -code C and announces it to Alice, where the ratios d/n and k/n are agreed on by both Alice and Bob;

(C7.2) Alice chooses a non-zero random *n*-bit string $r = (r_1r_2...r_n) \in \{0,1\}^n$ and announces it to Bob;

 $(C7.3)$ Now Alice has in mind the value of the bit b that she wants to commit. Then she chooses a random *n*-bit codeword $c = (c_1c_2...c_n)$ from C such that $c \odot r = b$ (Here $c \odot r \equiv \bigoplus_{n=1}^{n}$ $\bigoplus_{i=1} c_i \wedge r_i);$

(C7.4) Alice announces to Bob $c' = c \oplus c^0$.

The unveil protocol: $(unveil(b, c, c^0, |\psi_i\rangle))$

(U1) Alice announces b, c, c⁰, $\{q_i, \theta_i | i \in S\}$ and $\{p_i | i \in M\}$ to Bob;

(U2) Alice sends the quantum registers $\{\alpha_i | i \in U\}$ to Bob;

(U3) Bob finishes the measurement on $\{\alpha_i | i \in U\}$ and $\{\beta_i | i \in S'\}$ to check Alice's announcement;

(U4) Bob checks $|M| \sim [1/4 + (f_a + f_c)/2] s$ and $(M - D) \cap L_b = \phi;$

(U5) Bob checks $b = c \odot r$ and (c is a codeword).

Unlike those described in *Problem P*, in step (C2) we allow Bob to choose a subset S', and delay the measurement on β_i ($\forall i \in S'$). For the states in this set, since Bob has to announce $|p''_i\rangle$ $\langle g'_i, q''_i \rangle_{\beta}$ randomly before he obtains $|p'_i\rangle$ $\langle q'_i, q'_i \rangle_{\beta}$, it is equivalent to lie with the frequencies $f_a = f_b = f_c = 1/4$ among the set. Thus by choosing s' properly, Bob can still control the total lying frequencies f_a , f_b and f_c , as those described in step (C3). The purpose of S' is to enhance Bob's chance on catching Alice cheating in steps $(C5)$ and $(U3)$. However, the protocol is still valid even if Bob chooses $S' = \phi$.

The purpose of step (U3) is to make sure that Alice does not shift the bits in string c^0 from 1 to 0. In another word, it is to check whether Alice has already measured a state α_i to make β_i collapse, but still tries to say that the two states are left entangled. There are many type of measurement that Bob can perform to catch this kind of cheating. When both the two registers α_i and β_i in $|\psi_i\rangle$ are not measured before (i.e. $i \in U \cap S'$), Bob can simply sort them by θ_i and q_i and then measure the amount of entanglement [26] between them. Since local transformations will not affect the entanglement, Alice can not make a measured α_i entangle with β_i without the help from Bob. So if the result of Bob's measurement turns out to be zero or much different from the expected value calculated from the form of $|\psi_i\rangle$ Alice announced, Bob should reject this commitment.

For the other states where one of the registers of $|\psi_i\rangle$ is already measured in the commit phase, Bob can use the form of $|\psi_i\rangle$ Alice announced to calculate the expected state $|e_i\rangle$ to which the other register of $|\psi_i\rangle$ should collapse. Then he measures this register in the basis $(|e_i\rangle, |e_i\rangle^{\perp})$. As we know, different measured results of one of the registers will cause the other register to collapse to different states, and these states are not orthogonal to each other when $\theta_i \neq 0 \wedge \theta_i \neq \pi/2$. Therefore if Alice has not followed the protocol honestly, the unmeasured register will have a non-zero probability to be found as $|e_i\rangle^{\perp}$ by Bob. For instance, suppose Alice has formerly prepared a state as $|\psi_{i_0}\rangle = |\alpha_{i_0} \otimes \beta_{i_0}\rangle = 1/\sqrt{2}(|x\rangle_\alpha \otimes |0,0\rangle_\beta + |y\rangle_\alpha \otimes |1,0\rangle_\beta).$ And in step (C3) Bob announces $|p''_{i}$ $\langle \zeta_0', q''_{i_0} \rangle_{\beta} = |1, 1 \rangle_{\beta}$. Alice will then include the index i_0 of this state in set M and measures α_{i_0} in the basis $(|x\rangle_\alpha, |y\rangle_\alpha)$. Suppose that she obtain $|x\rangle_{\alpha}$ in her measurement. So she will not include i_0 in set D. Now since $i_0 \in M - D$, she should set $c_{i_0}^0 = 1$. However, the dishonest Alice wants Bob to believe $c_{i_0}^0 = 0$, so she must send Bob a fake state $\tilde{\alpha}_{i_0}$. But she does not know the result of Bob's measurement on β_{i_0} . Since she has found α_{i_0} as $|x\rangle_\alpha$ in her measurement, there are three possibilities: Bob has found β_{i_0} as $|0,0\rangle_{\beta}$, $|1,0\rangle_{\beta}$, or $|1,1\rangle_{\beta}$. Then α_{i_0} has collapsed to $\sqrt{2/3}|x\rangle_{\alpha} + \sqrt{1/3}|y\rangle_{\alpha}$, $\sqrt{1/3} |x\rangle_{\alpha} + \sqrt{2/3} |y\rangle_{\alpha}$, or $|x\rangle_{\alpha}$ respectively. If she prepares $|\tilde{\alpha}_{i_0}\rangle = |x\rangle_{\alpha}$ and sends to Bob, chances are that Bob has formerly obtained $|p'_i\rangle$ $\langle q'_{i_0} \rangle_{\beta} = |0,0\rangle_{\beta}$ in step (C2) so he is expecting $|\alpha_{i_0}\rangle = \sqrt{2/3} |x\rangle_\alpha + \sqrt{1/3} |y\rangle_\alpha$. Then when he measures $\tilde{\alpha}_{i_0}$ in the basis $(\sqrt{2/3} \ket{x}_{\alpha} + \sqrt{1/3} \ket{y}_{\alpha}, -\sqrt{1/3} \ket{x}_{\alpha} + \sqrt{2/3} \ket{y}_{\alpha})$, he stands 1/3 chances to finds $\tilde{\alpha}_{i_0}$ as $-\sqrt{1/3}$ $|x\rangle_{\alpha} + \sqrt{2/3}$ $|y\rangle_{\alpha}$ and catches Alice cheating. In this case, the probability for Alice to cheat successfully for this single bit is $f = 2/3$. As the minimum distance between

codewords is d, to keep the total number of 0 in c^0 unchanged, a dishonest Alice will have to shift at least $d/2$ bits of c^0 from 1 to 0 to fulfill her cheating. Therefore the total probability for Alice to successfully cheat this way without being caught is less than $\max(f)^{d/2}$. Since d/n is fixed to be a constant in the protocol and $n \propto s$, this probability drops exponentially to zero as the security parameter s increases.

The purpose of step (U4) is to make sure that Alice does not shift the bits in string c^0 from 0 to 1. In our protocol, although Alice can shift a bit c_i^0 $\frac{0}{i}$ from 0 into 1 simply by measuring α_i , the total number of 1 in c^0 is already restrained to be about $|M - D|$ ∼ $(1 - f_b + f_c)s/4$. Since |M| is already the minimum of the number of states that Alice has to measure to solve *Problem P*, if she shift more bits from 0 into 1, there will be too much 1 in c 0 . So this kind of cheating is easy for Bob to find out. Also, solving *Problem P* with $|\psi_i\rangle = |\alpha_i \otimes \beta_i\rangle = \cos \theta_i |x\rangle_\alpha \otimes |0, q_i\rangle_\beta + \sin \theta_i |y\rangle_\alpha \otimes |1, q_i\rangle_\beta$ has a characteristic property: all lie b among the set of states that Alice measured will be detected. This is because when $β_i$ is found as $|0, \nceil q_i$)_β (or $|1, \nceil q_i$)_β) in Bob's measurement, $α_i$ will collapse to $|y\rangle_\alpha$ (or $|x\rangle_\alpha$ respectively). If Bob applies lie b by announcing it as $|1, q_i\rangle_{\beta}$ (or $|0, q_i\rangle_{\beta}$), Alice is then expecting to find α_i as $|x\rangle_\alpha$ (or $|y\rangle_\alpha$) in her measurement. Since $|x\rangle_\alpha$ and $|y\rangle_\alpha$ are orthogonal to each other, so when Alice measures only the states that satisfy $q_i^{\prime\prime} = \overline{q_i}$, lie b will be 100% detected and none of them will be left in set $M - D$. Thus if Bob finds $(M - D) \cap L_b \neq \phi$ in step (U4), he knows that Alice must have measured some states which do not satisfy $q''_i = \bar{q}_i$, or even has not prepared $|\psi_i\rangle$ in the correct form.

Therefore if Alice alters much of the bits in c^0 , she will inevitably be caught. Nevertheless, due to the fluctuation of random distribution, we can not expect the size of D detected by Alice to be exactly equal to $(f_a/2 + f_b/4 + f_c/4)s$. So if Alice alters only few bits of c^0 , she may escape from being caught. But the codeword method in the BCJL protocol can avoid this situation. That is, since the minimum distance between any legal codewords is d, altering only a small number of bits of c^0 will not be enough to change a codeword into another legal codeword. Therefore this way of cheating will make no sense to Alice at all.

Now we will show that the protocol is also secure against Bob. During the commit phase, since q_i is kept secret by Alice, Bob can not know how to divide S into subsets M and U. Though he knows that in the *n*-bit string c^0 $(n = |S - D| \sim (1 - f_a/2 - f_b/4 - f_c/4)s)$, there are $d^0 \equiv |M - D| \sim (1 - f_b + f_c) s/4$ bits in c^0 take the value 1, and the other $(n - d^0)$ bits are 0, he does not know the position of these bits. Thus the possible number of c^0 is $\binom{n}{d}$. Then Theorem 3.4 in Ref. [17] applies. Briefly, as $d^0 > \gamma n$ ($\gamma \equiv H^{-1}(1/2) \sim 0.1100279$), we have $\binom{n}{d}$ $\binom{n}{r}$ > $\binom{n}{r}$ > $2^{n/2}/\sqrt{n}$. Divide by 2^{n-k} (the number of syndromes of the code C), and we get: the number of codewords at Hamming distance d^0 has a lower bound $2^{k-n/2}/\sqrt{n}$, which is exponentially large in n as long as we choose $k/n > 1/2$ in step (C7.1). Therefore Lemmas 3.5 and 3.6 of Ref. [17] are also valid for our protocol. That is, Bob has exponentially small amount of Shannon information on the value of b before the unveil phase.

So we can see that our protocol is both unconditionally binding and concealing, therefore it is unconditionally secure. Briefly, the protocol evades the MLC-theorem for the following reason. There are two tasks for Alice to accomplish during the commit phase: *Task 1*: solve *Problem P*; and *Task 2*: commit the bit b. The purpose of *Task 1* is to prepare the input states for *Task 2*. The form of *Task 2* is quite similar to the BCJL QBC protocol. However, there is a critical difference: the encoding method. Unlike any protocols that can concluded by the Yao's general QBC model, in our protocol, whether a state $|\psi_i\rangle = |\alpha_i \otimes \beta_i\rangle$ is encoded

as 0 or 1 is not depended on the form of α_i , but on whether $|\psi_i\rangle$ is an entangled state or not. If $|\psi_i\rangle$ can be written as $|\alpha_i\rangle \otimes |\beta_i\rangle$ (which means that it is a non-entangled product state) we take $c_i^0 = 1$, else we take $c_i^0 = 0$. Since it is a basic principle that the entanglement between two systems α_i and β_i can not be created locally, there does not exist any local unitary transformation for Alice to map a state $|\psi_i\rangle = |\alpha_i\rangle \otimes |\beta_i\rangle$ into an entangled state. Of course if Alice can maintain every input state of *Task 2* in an entangled form $|\psi_i\rangle = |\alpha_i \otimes \beta_i\rangle$, she can unveil c_i^0 with any value she like, since such a state is free to map into $|\psi_i\rangle = |\alpha_i\rangle \otimes |\beta_i\rangle$. But to accomplish *Task 1*, Alice inevitably has to measure at least a certain number of these states to break down the entanglement between β_i and any other systems and make $|\psi_i\rangle$ collapse to $|\alpha_i\rangle \otimes |\beta_i\rangle$ (Here α_i can represent any systems not on Bob's side, including the environment). And this number sets the maximum of the allowed number of 1 in the codeword string c^0 in our protocol. Therefore, no LOCAL unitary transformation will be available for Alice to map the state $|b\rangle = |\psi_1\rangle \otimes |\psi_2\rangle \otimes ... \otimes |\psi_n\rangle$ into $|\exists b\rangle$. By this means, the cheating strategy in the MLC theorem can not work any more, and unconditionally secure is achieved. Full mathematical proof and detailed discussion on the limitation of the MLC theorem will be supplied elsewhere.

Thus by using entangled states to run quantum algorithms, we propose an unconditionally secure quantum bit commitment protocol. Therefore all the other cryptographies that base on bit commitment, such as unconditionally secure quantum oblivious transfer, two-party secure computations, quantum coin tossing and quantum oblivious mutual identification are then straight forward. The potential of quantum cryptography meets a great development.

REFERENCES

- [1] S.Wiesner, SIGACT News, 15, 78 (1983).
- [2] C.H.Bennett, G.Brassard, in *Proceedings of IEEE International Conference on Computers, Systems, and Signal Processing*, Bangalore, India, pp.175 (IEEE, New York, 1984).
- [3] A.K.Ekert, Phys. Rev. Lett. 67, 661 (1991).
- [4] C.H.Bennett, Phys. Rev. Lett. 68, 3121 (1992).
- [5] A.C.C.Yao, in *Proceedings of 1995 ACM Symposium on Theory of Computing*, May 1995, pp. 67 (ACM, New York, 1995).
- [6] C.H.Bennett, G.Brassard, C.Crepeau, and M.-H.Skubiszewska, in *Advances in Cryptology: Proceedings of Crypto '91, Vol.576 of Lecture Notes in Computer Science*, pp.351 (Springer-Verlag, 1992).
- [7] C. Crepeau, Journal of Modern Optics, special issue on Quantum Communication and Cryptography. 41, 2445 (1994).
- [8] J.Kilian, in *Proceedings of 1988 ACM Annual Symposium on Theory of Computing*, May 1988, pp.20 (ACM, New York, 1988).
- [9] C.Crepeau, J.van de Graaf, A.Tapp, in *Advances in Cryptology: Proceedings of Crypto '95*, Vol. 963, pp.110 (Springer-Verlag, Berlin, 1995).
- [10] D.A.Meyer, Phys. Rev. Lett. **82**, 1052 (1999).
- [11] S.J.van Enk, Phys. Rev. Lett. 84, 789 (2000).
- [12] L.Goldenberg, L.Vaidman, S.Wiesner, Phys. Rev. Lett. 82, 3356 (1999).
- [13] C. Crepeau and L.Salvail, in *Advances in Cryptology: Proceedings of Eurocrypt '95*, pp.133 (Springer-Verlag, 1995).
- [14] P.W.Shor, in *Proceedings of the 35th Annual Symposium on the Foundations of Computer Science*, pp. 124 (IEEE Computer Society, Los Alamitos, CA, 1994).
- [15] D.Mayers, Phys. Rev. Lett. 78, 3414 (1997).
- [16] H.-K.Lo, H.F.Chau, Phys. Rev. Lett. 78, 3410 (1997).
- [17] G.Brassard, C.Crepeau, R.Jozsa, D.Langlois, in *Proceedings of the 34th Annual IEEE Symposium on Foundations of Computer Science, 1993*, pp.362 (IEEE, Los Alamitos, 1993).
- [18] M.Naor, in *Advances in Cryptology: Proceedings of Crypto '89, Vol.435 of Lecture Notes in Computer Science*, pp.128 (Springer-Verlag, 1990).
- [19] M.Naor, R.Ostrovsky, R.Venkatesan, and M.Yung, in *Advances in Cryptology: Proceedings of Crypto '92*, pp.196 (Springer-Verlag, 1992).
- [20] M.Ben-Or, S.Goldwasser, J.Kilian, and A.Wigderson, in *Proceedings of the Twentieth Annual ACM Symposium on Theory of Computing*, pp.113 (Chicago, Illinois, 1988).
- [21] G.Brassard, C.Crepeau, D.Mayers, L.Salvail, LANL Report No. quant-ph/9806031.
- [22] H.K.Lo and H.F.Chau, Physica D 120, 177 (1998).
- [23] A.Kent, Phys. Rev. Lett. 83, 1447 (1999).
- [24] B.M.Terhal, D.P.DiVincenzo, and D.W.Leung, Phys. Rev. Lett. 86, 5807 (2001).
- [25] D.Mayers, LANL Report No. quant-ph/9603015.
- [26] P.Horodecki and A.Ekert, Phys. Rev. Lett. 89, 127902 (2002).