

# Communication complexity of remote state preparation with entanglement

Rahul Jain  
U.C. Berkeley  
Berkeley, USA.  
rahulj@cs.berkeley.edu \*

## Abstract

We consider the problem of *remote state preparation* recently studied in several papers. We study the *communication complexity* of this problem, in the presence of entanglement.

## 1 Introduction

The remote state preparation problem has been studied in several papers in recent times, see for example, [Lo00], [BHL<sup>+</sup>05], [BDS<sup>+</sup>01], [A.K01], [ZZ02]. We define the problem below. Let  $X$  be a set. Let  $\mathcal{S}(\mathcal{K})$  be the set of quantum states in the Hilbert space  $\mathcal{K}$ . Let an encoding  $E : X \mapsto \mathcal{S}(\mathcal{K})$  be a function from  $X$  to  $\mathcal{S}(\mathcal{K})$ . The remote state preparation,  $RSP(X, E, \epsilon)$  problem is as follows:

**Definition 1.1 (Remote state preparation)** *Let Alice, who knows the function  $E$ , get an input  $x \in X$ . Alice and Bob are required to communicate and at the end of the communication Bob should have a quantum state  $\rho_x$  such that  $F(\rho_x, E(x)) \geq 1 - \epsilon$ , for some  $0 \leq \epsilon < 1$ . Alice and Bob may start with some prior entanglement between them.*

In several papers in the remote state preparation problem, Alice instead of  $x$  is given a *description* of the state  $\rho_x$ . We assume in this work that the description is given in the form of the element  $x$  of  $X$ . In most of the earlier papers the basic problem studied is the trade-off between the *rate* [BHL<sup>+</sup>05] of communication and the rate of entanglement used. Instead we study the communication complexity of this problem, i.e. the best possible communication with which a given problem  $RSP(X, E, \epsilon)$  can be solved. By  $Q^{pub}(RSP(X, E, \epsilon))$  we denote the communication complexity, with prior entanglement, of  $RSP(X, E, \epsilon)$ . Please note that we are concerned with the total communication and not the rate as in earlier papers. Also in this work we are not bothered about the amount of entanglement used.

We consider a notion of *maximum possible information*  $T(E)$  in an encoding  $E$  and show that, in the presence of entanglement, the communication required for  $RSP(X, E, 0)$ , is at least  $T(E)/2$  and  $RSP(X, E, \epsilon)$  can be solved with communication at most  $\frac{8}{\epsilon^2}(4T(E) + 7)$ .

---

\*This work was supported by an Army Research Office (ARO), North California, grant number DAAD 19-03-1-00082.

There is an interesting point of note here. In earlier works since the problem was that of determining the rate of communication and rate of entanglement etc., the non-trivial aspect was the exact multiplicative constant in the rate. Since we are concerned with the total communication, the problem of identifying the best communication for a given  $RSP(X, E, \epsilon)$  even up to constants is non-trivial. It is easy to see that in specific cases like when  $T(E) = \log d$ , where  $d$  is the dimension of  $\mathcal{K}$ , or when  $T(E) = 0$ , that  $RSP(X, E, \epsilon)$  can be solved with communication which is like  $T(E)$  upto constants. But for general values of  $T(E)$  this problem is non-trivial.

## 2 Preliminaries

In this section we give a few definitions and state some facts that we will use later.

Given a joint quantum system  $AB$ , the mutual information between them is defined as  $I(A : B) = S(A) + S(B) - S(AB)$ , where  $S(A)$  is the von-Neumann entropy of the system  $A$ . Given two quantum states,  $\rho, \sigma$  the relative entropy between them is defined as  $S(\rho||\sigma) \triangleq \text{Tr} \rho(\log \rho - \log \sigma)$ . Let  $X$  be a finite set (below we always assume that  $X$  is a finite set) and let  $E : x \in X \mapsto \rho_x$  be an encoding over  $X$ . For a probability distribution  $\mu = \{p_x\}$  over  $X$  let  $X_\mu(E)$  be the bipartite state  $\mathbb{E}_\mu[|x\rangle\langle x| \otimes \rho_x] \triangleq \sum_{x \in X} p_x |x\rangle\langle x| \otimes \rho_x$ . Below  $\mathbb{E}_\mu[\cdot]$  always stands for probability average (expectation) under distribution  $\mu$  of the corresponding quantity. Please note the difference in the font with the notation for an encoding, which is represented by an ' $E$ '. Let  $I_\mu^X(E)$  be the mutual information between the two systems in  $X_\mu(E)$ . When the underlying set  $X$  is clear we omit the superscript. Let  $\rho_\mu \triangleq \mathbb{E}_\mu[\rho_x]$ . We note that in this case from definitions  $I_\mu^X(E) = \mathbb{E}_\mu[S(\rho_x||\rho_\mu)]$ .

**Definition 2.1** (*Maximum possible information*) Maximum possible information in an encoding  $E : X \mapsto \mathcal{S}(\mathcal{K})$  is defined as  $T_X(E) \triangleq \max_\mu I_\mu^X(E)$ . When the underlying set  $X$  is clear we omit the subscript. It is easily seen that if  $d$  is the dimension of  $\mathcal{K}$  then  $T(E) \leq \log d$ .

We use the following information-theoretic result called the *substate theorem* due to Jain, Radhakrishnan, and Sen [JRS02].

**Fact 2.1 (Substate theorem, [JRS02])** Let  $\mathcal{H}, \mathcal{K}$  be two finite dimensional Hilbert spaces and  $\dim(\mathcal{K}) \geq \dim(\mathcal{H})$ . Let  $\mathbb{C}^2$  denote the two dimensional complex Hilbert space. Let  $\rho, \sigma$  be density matrices in  $\mathcal{H}$  such that  $S(\rho||\sigma) < \infty$ . Let  $|\bar{\rho}\rangle$  be a purification of  $\rho$  in  $\mathcal{H} \otimes \mathcal{K}$ . Then, for  $r > 1$ , there exist pure states  $|\phi\rangle, |\theta\rangle \in \mathcal{H} \otimes \mathcal{K}$  and  $|\bar{\sigma}\rangle \in \mathcal{H} \otimes \mathcal{K} \otimes \mathbb{C}^2$ , depending on  $r$ , such that  $|\bar{\sigma}\rangle$  is a purification of  $\sigma$  and  $F(|\bar{\rho}\rangle\langle\bar{\rho}|, |\phi\rangle\langle\phi|) \geq 1 - \frac{1}{\sqrt{r}}$ , where

$$|\bar{\sigma}\rangle \triangleq \sqrt{\frac{r-1}{r2^{rk}}} |\phi\rangle|1\rangle + \sqrt{1 - \frac{r-1}{r2^{rk}}} |\theta\rangle|0\rangle$$

and  $k \triangleq 8S(\rho||\sigma) + 14$ .

The following fact can be found in Cleve et al [CvDNT98].

**Fact 2.2** *Let Alice have a classical random variable  $Z$ . Suppose Alice and Bob share a prior entanglement independent of  $Z$ . Initially Bob's qubits have no information about  $Z$ . Now let Alice and Bob run a quantum communication protocol, at the end of which Bob's qubits possess  $m$  bits of information about  $Z$ . Then, Alice has to send at least  $m/2$  qubits to Bob.*

We will require the following minimax theorem from game theory (see [OR94]).

**Fact 2.3** *Let  $A_1, A_2$  be non-empty, either finite or convex and compact subsets of  $\mathbb{R}^n$ . Let  $u : A_1 \times A_2 \mapsto \mathbb{R}$  be a continuous function. Let  $\mu_1, \mu_2$  be distributions on  $A_1$  and  $A_2$  respectively. Then,*

$$\min_{\mu_1} \max_{a_2 \in A_2} E_{\mu_1}[u(a_1, a_2)] = \max_{\mu_2} \min_{a_1 \in A_1} E_{\mu_2}[u(a_1, a_2)]$$

We will also require the following Local transition theorem [HJW93, May97].

**Theorem 2.1** *Let  $\rho$  be a quantum state in  $\mathcal{K}$ . Let  $|\phi_1\rangle$  and  $|\phi_2\rangle$  be two purification of  $\rho$  in  $\mathcal{H} \otimes \mathcal{K}$ . Then there is a local unitary transformation  $U$  acting on  $\mathcal{H}$  such that  $(U \otimes I)|\phi_1\rangle = |\phi_2\rangle$ .*

### 3 Communication bounds

The following lemma states the communication lower bound.

**Lemma 3.1** *Let  $E : x \mapsto \rho_x$  be an encoding, then  $Q^{pub}(RSP(X, E, 0)) \geq T(E)/2$ .*

**Proof:** Let  $T(E) = c$ . Let  $\mu$  be the distribution on  $X$  such that  $I_\mu(E) = c$ . Consider the random variable  $Z$  taking values in  $X$  with distribution  $\mu$ . Let Alice be given inputs according to  $\mu$ . We know that after the remote state preparation protocol mutual information between  $Z$  and the qubits of Bob, where the state is created, is  $c$ . Hence by fact 2.2 at least  $c/2$  qubits must be communicated by Alice to Bob. ■

**Remark:** As suggested by an anonymous referee we point here that the above lemma is not robust for positive  $\epsilon$ . This is because after allowing for a small error  $T(E')$  may be smaller than  $T(E)$  by up to order  $\epsilon \log d + \epsilon \log \epsilon$ , where  $E'$  is the new encoding obtained by allowing the positive error  $\epsilon$ . This follows from Fannes inequality.

On the other hand we show the following upper bound on the communication required to solve the problem.

**Theorem 3.1** *Let  $E : x \mapsto \rho_x$  be an encoding and  $0 < \epsilon < 1$  be a constant, then  $Q^{pub}(RSP(X, E, \epsilon)) \leq \frac{8}{\epsilon^2}(4T(E) + 7)$ .*

**Proof:** We first show the following key lemma.

**Lemma 3.2** *Let  $E : x \mapsto \rho_x$  be an encoding. There exists a distribution  $\mu$  such that*

$$\forall x \in X, S(\rho_x || \rho_\mu) \leq T(E)$$

**Proof:** Let  $A_1$  be the set of all distribution on the set  $X$ . Let  $A_2$  be the set  $X$  itself. The function  $u : A_1 \times A_2 \mapsto \mathbb{R}$  be such that  $u(\mu, x) = S(\rho_x || \rho_\mu)$ . The conditions of Fact 2.3 are satisfied and therefore we have:

$$\min_{\mu} \max_x S(\rho_x || \rho_\mu) \leq \min_{\mu: \text{distribution over } X} \max_x E_{\mu^*}[S(\rho_x || \rho_\mu)] \quad (1)$$

$$= \max_{\lambda: \text{distribution over } X} \min_{\mu} E_{\lambda}[S(\rho_x || \rho_\mu)] \quad (2)$$

$$\leq \max_{\lambda} E_{\lambda}[S(\rho_x || \rho_{\lambda})] \quad (3)$$

$$= \max_{\lambda} I_{\lambda}(E) = T(E) \quad (4)$$

Inequality (1) follows since relative entropy is jointly convex in its arguments. Equality (2) is from Fact 2.3. ■

Let  $T(E) = c$ , then from lemma 3.2 we get a distribution  $\mu$  on  $X$  such that  $\forall x, S(\rho_x || \rho_\mu) \leq c$ . Let Alice and Bob start with  $2^{rk}$  ( $r = 4/\epsilon^2, k = 8c+14$ ) copies of some purification  $|\psi\rangle$  of  $\rho_\mu$  with the purification part being with Alice and  $\rho_\mu$  with Bob in each of the copies of  $|\psi\rangle$ . Let us invoke Fact 2.1 with  $\rho \triangleq \rho_x, \sigma \triangleq \rho_\mu$  and  $|\bar{\rho}\rangle$  being any purification of  $\rho_x$ . Let  $|\psi_x\rangle$  be the purification of  $\rho_\mu$  obtained from Fact 2.1 corresponding to  $|\bar{\rho}\rangle$ . Since the reduced quantum state on Bob's part in both  $|\psi_x\rangle$  and  $|\psi\rangle$  is the same, from local transition theorem, there exists a transformation acting only in Alice's side which takes  $|\psi\rangle$  to  $|\psi_x\rangle$ . Alice on input  $x$ , transforms each  $|\psi\rangle$  to  $|\psi_x\rangle$  and measures the first bit. If she obtains 1 in any copy of  $|\psi_x\rangle$  she communicates the number of that copy to Bob. It is easily seen that the communication from Alice is at most  $rk = \frac{8}{\epsilon^2}(4c+7)$ . Also since  $\Pr(\text{Alice observes } 1) = \frac{r-1}{r2^{rk}}$ , and Alice makes  $2^{rk}$  tries she succeeds with probability at least  $1 - 1/r$ . In case she succeeds, let the state with Bob in which Alice succeeds be  $\rho'_x$ . From Fact 2.1,  $F(\rho'_x, \rho_x) \geq 1 - 1/\sqrt{r}$ . So for the final state  $\tilde{\rho}_x$  produced with Bob, it follows from concavity of fidelity that  $F(\tilde{\rho}_x, \rho_x) \geq 1 - 2/\sqrt{r} = 1 - \epsilon$ . ■

### Remarks:

1. Given an encoding  $E : x \mapsto \rho_x$ , a small constant  $\epsilon$  and states  $\rho'_x$  such that  $F(\rho'_x, \rho_x) \geq 1 - \epsilon$ , let a *perturbed encoding*  $E'$  be,  $E' : x \mapsto \rho'_x$ . It is quite possible that  $T(E')$  is much lesser than  $T(E)$  as allowed by Fannes bound. In such a case communication can be reduced a lot by running the above protocol for  $E'$  instead of  $E$  since we are ready to tolerate constant fidelity loss anyway.
2. One can consider the classical version of the remote state generation problem in which the encoding considered is a mapping from  $X$  to the set of classical distributions on some set. On input  $x \in X$  to Alice, they are required to communicate, at the end of which Bob is required to sample from a distribution close to  $E(x)$ . The same communication bounds apply for this problem as well.

## 4 Conclusions

The protocol for the upper bound, mentioned in this paper uses a large amount of entanglement. It will be interesting to see if it can be reduced or even eliminated if possible. Also it will be interesting to get entanglement-communication trade-offs for this problem as opposed to the trade-offs in the rates of entanglement and communication.

## 5 Acknowledgment

We thank Rohit Khandekar, Pranab Sen, Julia Kempe and Jaikumar Radhakrishnan for useful discussions and for pointing out useful references. We also thank anonymous referees for useful suggestions and comments.

## References

- [A.K01] Pati A.K. Minimum classical bit for remote preparation and measurement of a qubit. In *Phy. Rev. A*, volume 63, 2001.
- [BDS<sup>+</sup>01] C.H. Bennett, D.P. DiVincenzo, P.W. Shor, J.A. Smolin, B.M. Terkal, and W.K. Wootters. Remote state preparation. In *Phy. Rev. Letters*, volume 87, 2001.
- [BHL<sup>+</sup>05] C.H. Bennett, P. Hayden, W. Leung, P.W. Shor, and A. Winter. Remote preparation of quantum states. In *IEEE transaction of information theory*, volume 51, pages 56–74, 2005.
- [CvDNT98] R. Cleve, Wim van Dam, M. Nielsen, and A. Tapp. Quantum entanglement and the communication complexity of the inner product function. In *Proceedings of the 1st NASA International Conference on Quantum Computing and Quantum Communications*, Lecture Notes in Computer Science, vol. 1509, pages 61–74. Springer-Verlag, 1998. Also quant-ph/9708019.
- [HJW93] L.P. Hughston, R. Jozsa, and W.K. Wootters. A complete classification of quantum ensembles having a given density matrix. In *Phy. Lett.A*, volume 183, pages 14–18, 1993.
- [JRS02] R. Jain, J. Radhakrishnan, and P. Sen. Privacy and interaction in quantum communication complexity and a theorem about the relative entropy of quantum states. In *Proceedings of the 43rd Annual IEEE Symposium on Foundations of Computer Science*, pages 429–438, 2002.
- [Lo00] H.-K. Lo. Classical communication cost in distributed quantum information processing - a generalization of quantum communication complexity. In *Phy. Rev. A*, volume 62, 2000.
- [May97] D. Mayers. Unconditionally secure quantum bit commitment is impossible. In *Phy. Rev. Letters*, volume 78, pages 3414–3417, 1997.

- [OR94] M. Osborne and A. Rubinstein. *A course in game theory*. MIT Press, 1994.
- [ZZ02] B. Zeng and P. Zhang. Remote-state preparation in higher dimension and the parallelizable manifold  $s^{n-1}$ . In *Phy. Rev. A*, volume 65, 2002.